

Test report No. : 26HE0264-HO-A-1
Page : 1 of 16
Issued date : July 3, 2006
Revised data : July 5, 2006
FCC ID : UDFRC441-9315

RADIO TEST REPORT

Test Report No.: 26HE0264-HO-A-1

Applicant : Kubota corporation

Type of Equipment : Immobilizer for Construction machine

Model No. : RC441-9315

Test standard : FCC Part 15 Subpart C Section 15.209:2006

FCC ID : UDFRC441-9315

Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Apex Co., Ltd.

- 2. The results in this report apply only to the sample tested.
- 3. This equipment is in compliance with above regulation.
- 4. The test results in this report are traceable to the national or international standards.

Date of test: April 9,2006

Tested by : Norihisa Hashimoto

EMC Services

Naoki Sakamoto

Group Leader of EMC Services



Approved by:

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.

*As for the range of Accreditation in NVLAP, you may refer to the WEB address, http://ulapex.jp/emc/nvlap.htm

UL Apex Co., Ltd. Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 26HE0264-HO-A-1
Page : 2 of 16
Issued date : July 3, 2006
Revised data : July 5, 2006
FCC ID : UDFRC441-9315

UL Apex Co., Ltd. Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 26HE0264-HO-A-1
Page : 3 of 16
Issued date : July 3, 2006
Revised data : July 5, 2006
FCC ID : UDFRC441-9315

SECTION 1: Client information

Company Name : Kubota Corporation

Address : 64, Ishizu-kitamachi, Sakai-ku, Sakai-city, Osaka, 590-0823 Japan

Telephone Number : +81-722-41-7361 Facsimile Number : +81-722-41-0555 Contact Person : Keisuke Miura

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Immobilizer for Construction machine

Model No. : RC441-9315

Serial No. : 1

Rating : DC12.0V Country of Manufacture : Japan Receipt Date of Sample : April 6, 2006

Condition of EUT : April 0, 2000

Production model

(Not for Sale: This sample is equivalent to mass-produced items.)

Modification of EUT : No modification by the test lab.

2.2 Product Description

Model No: RC441-9315 (referred to as the EUT in this report) is the Immobilizer for Construction machine

Equipment Type : Transceiver
Frequency of Operation : 134.2kHz
Type of modulation : ASK
Power Control : No
Operating voltege(inner) : 5V

Antenna Type : Loop coil Antenna (Integral)

Antenna Connector Type : Soldering

UL Apex Co., Ltd. Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

 Test report No.
 : 26HE0264-HO-A-1

 Page
 : 4 of 16

 Issued date
 : July 3, 2006

 Revised data
 : July 5, 2006

 FCC ID
 : UDFRC441-9315

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C : 2006

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators

Section 15.209 Radiated emission limits, general requirements: 2006

FCC 15.31 (e)

The power supply of the EUT is transformed to DC5.0V and it is constantly provided to Radio part. Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

UL Apex Co., Ltd. Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 26HE0264-HO-A-1 : 5 of 16 Page **Issued date** : July 3, 2006 : July 5, 2006 Revised data : UDFRC441-9315

FCC ID

3.2 Procedures and results

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin *0)	Results
1	Conducted Emission	<fcc> ANSI C63.4:2003 7. AC powerline conducted emission measurements <ic> RSS-Gen 7.2.2</ic></fcc>	<fcc> Section 15.207 <ic> RSS-Gen 7.2.2</ic></fcc>	-	N/A *1)	N/A	N/A
	Electric Field Strength of Fundamental Emission	<fcc> ANSI C63.4:2003 13. Measurement of intentional radiators <ic> RSS-Gen 4.6, 4.9</ic></fcc>	<fcc> Section 15.209 <ic> RSS-210 2.6, 2.7</ic></fcc>	Radiated	N/A	42.5dB 0.13453MHz 0deg, X-axis, AV	Complied
3	Electric Field Strength of Spurious Emission	<fcc> ANSI C63.4:2003 13. Measurement of intentional radiators <ic> RSS-Gen 4.7, 4.9</ic></fcc>	<fcc> Section 15.205, 15.209 <ic> RSS-210 2.6, 2.7</ic></fcc>	Radiated	N/A	10.3dB 52.290MHz Vert, QP	Complied
4	-26dB Bandwidth	<fcc> ANSI C63.4:2003 13. Measurement of intentional radiators <ic></ic></fcc>	<fcc> Reference data <ic> -</ic></fcc>	Radiated	N/A	N/A	N/A

3.3 Addition to standards

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	99% Occupied	<ic>RSS-Gen 4.4.1</ic>	<ic>RSS-Gen 4.4.1</ic>	Radiated	N/A	N/A	N/A
	Band Width						

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Note: UL Apex's EMI Work Procedures No.QPM05 and QPM15.
*0) The result is rounded off to the second decimal place. Therefore, there may be 0.1 difference for the result.

^{*1)} The test is not applicable since the EUT does not have AC Mains.

^{*}These tests were performed without any deviations from test procedure except for additions or exclusions.

: 26HE0264-HO-A-1 Test report No. Page : 6 of 16 **Issued date** : July 3, 2006

: July 5, 2006 Revised data FCC ID : UDFRC441-9315

3.4 Uncertainty

Spurious Emission (Radiated)

The measurement uncertainty (with a 95% confidence level) for this test using Loop antenna is $\pm 4.41 dB(3m) / \pm 4.39 dB(10m)$.

The measurement uncertainty (with a 95% confidence level) for this test using Biconical antenna is ± 4.59 dB(3m) / ± 4.58 dB(10m).

The measurement uncertainty (with a 95% confidence level) for this test using Logperiodic antenna is ± 4.62 dB(3m)/ ± 4.60 dB(10m).

The measurement uncertainty (with a 95% confidence level) for this test using Horn antenna is ± 5.27 dB.

The data listed in this test report has enough margin, more than the site margin.

Other test except Conducted Emission and Spurious Emission (Radiated)

The measurement uncertainty (with a 95% confidence level) for this test is $\pm 3.0 \text{dB}$.

3.5 Test Location

UL Apex Co., Ltd. Head Office EMC Lab. *NVLAP Lab. code: 200572-0

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Γelephone : +8	81 596 24 8116	Facsimile	: +81 596 24	1 8124	
	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other
No.1 semi-anechoic chamber	313583	IC4247A	19.2 x 11.2 x 7.7m	7.0 x 6.0m	Preparation room
No.2 semi-anechoic chamber	655103	IC4247A-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	148738	IC4247A-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	
No.3 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	134570	IC4247A-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	-
No.4 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 shielded room	-	-	6.0 x 6.0 x 3.9m	N/A	-
No.6 shielded room	-	-	4.0 x 4.5 x 2.7m	N/A	-
No.6 measurement room	-	-	4.75 x 5.4 x 3.0m	N/A	-
No.7 shielded room	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement	-	-	3.1 x 5.0 x 2.7m	N/A	-

3.5 Test set up, Test instruments and Data of EMI

Refer to APPENDIX 1 to 3.

UL Apex Co., Ltd. **Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116 **Facsimile** : +81 596 24 8124

MF060b(14.06.06)

^{*} Size of vertical conducting plane (for Conducted Emission test): 2.0 x 2.0m for No.1, No.2, No. 3, and No. 4 semi-anechoic chambers and No.7 shielded room.

Test report No. : 26HE0264-HO-A-1

Page : 7 of 16

Issued date : July 3, 2006

Revised data : July 5, 2006

FCC ID : UDFRC441-9315

SECTION 4: Operation of E.U.T. during testing


4.1 Operating Modes

The mode is used: Continuous Transmitting mode

Justification : The system was configured in typical fashion (as a customer would normally use it)

for testing.

4.2 Configuration and peripherals



^{*} Cabling and setup were taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Immobilizer for Construction machine	RC441-9315	1	Asahi Denso	EUT
В	Transponder key	-	459A	Asahi Denso	-
C	Checker	-	-	Asahi Denso	-
D	Car Battery	40B19L	A030402	YUASA	-

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	Signal Cable	0.5	Unshielded	Unshielded	-
2	DC Cable	0.8	Unshielded	Unshielded	-

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Test report No. : 26HE0264-HO-A-1
Page : 8 of 16
Issued date : July 3, 2006
Revised data : July 5, 2006
FCC ID : UDFRC441-9315

SECTION 5: Radiated emission (Fundamental and Spurious Emission and –26dB Bandwidth)

Test Procedure

The Radiated Electric Field Strength intensity has been measured on No 1 semi anechoic chamber with a ground plane and at a distance of 3m.

Frequency: From 9kHz to 30MHz at distance 3m

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for each antenna angle 0deg., 45deg. and 90deg.

Frequency: From 30MHz to 1GHz at distance 3m

The measuring antenna height varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

Measurements were performed with a QP, PK, and AV detector.

The radiated emission measurements were made with the following detector function of the test receiver.

	From 9kHz to 90kHz	From 90kHz	From 150kHz	From 490kHz	From 30MHz
	and	to 110kHz	to 490kHz	to 30MHz	to 1GHz
	From 110kHz to 150kHz				
Detector Type	PK/AV	QP	PK/AV	QP	QP
IF Bandwidth	200Hz	200Hz	9kHz	9kHz	120kHz

⁻ The carrier level (or noise levels) was (or were) measured at each position of all three axes X, Y and Z, and the position that has the maximum noise was determined.

With the position, the noise levels of all the frequencies were measured.

* Part 15 Section 15.31 (f)(2) (9kHz-30MHz)

[Limit at 3m]=[Limit at 300m]-40 x log (3[m]/300[m]) [Limit at 3m]=[Limit at 30m]-40 x log (3[m]/30[m])

Test data : APPENDIX 3

Test result : Pass

Date: April 9, 2006 Tested by: Norihisa Hashimoto

UL Apex Co., Ltd. Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN