RF Exposure Evaluation declaration

Product Name : Wireless Outdoor Bridge

Model No. : ZA-4000

FCC ID : UDKZA4000

Applicant : Nanjing Z-Com Wireless Co.,Ltd

Address : 168 Long Pan Zhong Road, Jiangsu Software Park,

Suite 118 Nanjing, China 210002

Date of Receipt : 2007/04/25

Issued Date : 2007/07/09

Report No. : 075S002-RF-US

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by CNLA, NVLAP, NIST or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.



1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

	Electric	Magnetic	Power	Average			
Frequency	Field	Field		Average			
Range (MHz)	Strength	Strength	Density	Time			
	(V/m)	(A/m)	(mW/cm2)	(Minutes)			
(A) Limits for Occupational/ Control Exposures							
300-1500			F/300	6			
1500-100,000			5	6			
(B) Limits for General Population/ Uncontrolled Exposures							
300-1500			F/1500	6			
1500-100,000			1	30			

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*pi*r2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	Wireless Outdoor Bridge	
Test Item	:	RF Exposure Evaluation	
Test Site	:	AC-3	
Test Mode	:	Mode 1: Transmitter by 802.11a	

Antenna Gain:

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2 dBi or 1.58 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)
01	5745.00	47.4242	0.0150
03	5785.00	40.5509	0.0128
04	5805.00	47.5335	0.0150

Note:

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm2.