

RF Exposure Evaluation declaration

Product Name : Wireless Outdoor Bridge

Model No. : ZA-5000-E

FCC ID. : UDKZA5000E

Applicant: Nanjing Z-COM Wireless Co., Ltd.

Address : 168 Long Pan Zhong Road, Jiangsu Software Park, Suite 118

Nanjing, China 210002

Date of Receipt: 2006/06/06

Issued Date : 2006/07/19

Report No. : 066L128-1

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

Page: 1 of 3 Version: 1.0



1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

_		=	(/		
	Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time	
	(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm^2)	(Minutes)	
		(A) Limits for Occupational/ Control Exposures				
	300-1500			F/300	6	
	1500-100,000			5	6	
	(B) Limits for General Population/ Uncontrolled Exposures					
	300-1500			F/1500	6	
	1500-100,000			1	30	

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

 $Pd = power density in mW/cm^2$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

Page: 2 of 3 Version: 1.0



1.3. Test Result of RF Exposure Evaluation

Product : Wireless Outdoor Bridge (ZA-5000-E)

Test Item : RF Exposure Evaluation

Test Site : AC-3
Test Mode : Transmitter

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2dBi or 1.58 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at $R = 20 \text{ cm}$ (mW/cm^2)
149	5745.00	34.2768	0.0108
157	5785.00	31.0456	0.0098
161	5805.00	35.3997	0.0112

Note:

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Page: 3 of 3 Version: 1.0