

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1 style="text-align: center;"><b>TEST REPORT</b></h1>	<p>Reference No.:A07030114 Report No.:FCCA07030114 Page:1 of 56 Date: Apr. 04, 2007</p>
---	---	---

Product Name: Multifunction Bluetooth Stereo Car Kit  
 Model Number: BT-1250  
 Applicant: Sunswell Technology CO., LTD.  
                   12F-5, No.398, Huan-Pei Road, Chung-Li 320, Taoyuan,  
                   Taiwan, R.O.C.  
 Date of Receipt: Mar. 01, 2007  
 Finished date of Test Apr. 03, 2007  
 Applicable Standards: 47 CFR Part 15, Subpart C  
                           ANSI C63.4:2003

We, **Spectrum Research & Testing Laboratory Inc.**, hereby certify that one sample of the above was tested in our laboratory with positive results according to the above-mentioned standards. The records in the report are an accurate account of the results. Details of the results are given in the subsequent pages of this report.

Tested By : John Yu, Date: 4/4/2007  
 ( John Yu )

Approved By : 212, Date: 4/4/2007  
 ( Johnson Ho, Director )



## TABLE OF CONTENTS

1. DOCUMENT POLICY AND TEST STATEMENT.....	4
1.1 DOCUMENT POLICY .....	4
1.2 TEST STATEMENT .....	4
1.3 EUT MODIFICATION.....	4
2. DESCRIPTION OF EUT AND TEST MODE .....	5
2.1 GENERAL DESCRIPTION OF EUT .....	5
2.2 DESCRIPTION OF SUPPORT UNIT.....	5
2.3 DESCRIPTION OF TEST MODE .....	6
3. DESCRIPTION OF APPLIED STANDARDS.....	6
4. TECHNICAL CHARACTERISTICS TEST .....	7
4.1 CONDUCTED EMISSION.....	7
4.1.1 LIMIT .....	7
4.1.2 TEST EQUIPMENT .....	7
4.1.3 TEST SETUP .....	8
4.1.4 TEST PROCEDURE .....	8
4.1.5 EUT OPERATING CONDITION.....	8
4.1.6 TEST RESULT .....	9
4.2 RADIATED EMISSION TEST .....	14
4.2.1 LIMIT .....	14
4.2.2 TEST EQUIPMENT .....	15
4.2.3 TEST SET-UP.....	16
4.2.4 TEST PROCEDURE.....	17
4.2.5 EUT OPERATING CONDITION.....	17
4.2.6 RADIATED EMISSION TEST RESULT .....	18
4.3 CHANNEL SEPARATION TEST .....	22
4.3.1 LIMIT .....	22
4.3.2 TEST EQUIPMENT .....	22
4.3.3 TEST SET-UP.....	22
4.3.4 TEST PROCEDURE.....	22
4.3.5 EUT OPERATING CONDITION.....	22
4.3.6 TEST RESULT .....	23
4.4 QUANTITY OF HOPPING CHANNEL TEST .....	27
4.4.1 LIMIT .....	27
4.4.2 TEST EQUIPMENT .....	27
4.4.3 TEST SET-UP.....	27
4.4.4 TEST PROCEDURE.....	27
4.4.5 EUT OPERATING CONDITION.....	27
4.4.6 TEST RESULT .....	28
4.5 AVERAGE TIME OF OCCUPANCY TEST(DWELL TIME).....	29
4.5.1 LIMIT .....	29
4.5.2 TEST EQUIPMENT .....	29
4.5.3 TEST SET-UP.....	29
4.5.4 TEST PROCEDURE.....	29
4.5.5 EUT OPERATING CONDITION.....	29
4.5.6 TEST RESULT .....	30



4.6 MAXIMUM SPECTRAL PEAK POWER TEST .....	34
4.6.1 LIMIT .....	34
4.6.2 TEST EQUIPMENT .....	34
4.6.3 TEST SET-UP .....	35
4.6.4 TEST PROCEDURE .....	35
4.6.5 EUT OPERATING CONDITION .....	35
4.6.6 TEST RESULT .....	35
4.7 BAND EDGE TEST .....	38
4.7.1 LIMIT .....	38
4.7.2 TEST EQUIPMENT .....	39
4.7.3 TEST SET-UP .....	40
4.7.4 TEST PROCEDURE .....	41
4.7.5 EUT OPERATING CONDITION .....	41
4.7.6 TEST RESULT .....	41
4.8 POWER DENSITY TEST .....	44
4.8.1 LIMIT .....	44
4.8.2 TEST EQUIPMENT .....	44
4.8.3 TEST SET-UP .....	44
4.8.4 TEST PROCEDURE .....	44
4.8.5 EUT OPERATING CONDITION .....	44
4.8.6 TEST RESULT .....	45
4.9 20DB BANDWIDTH .....	48
4.9.1 LIMIT .....	48
4.9.2 TEST EQUIPMENT .....	48
4.9.3 TEST SET-UP .....	48
4.9.4 TEST PROCEDURE .....	48
4.9.5 EUT OPERATING CONDITION .....	48
4.9.6 TEST RESULT .....	49
5. ANTENNA APPLICATION .....	53
5.1 ANTENNA REQUIREMENT .....	53
5.2 RESULT .....	53
6. PHOTOS OF TESTING .....	54
7. TERMS OF ABRIVATION .....	56

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<b>TEST REPORT</b>	Reference No.:A07030114 Report No.:FCCA07030114 Page:4 of 56 Date: Apr. 04, 2007
---	--------------------	---

## **1. DOCUMENT POLICY AND TEST STATEMENT**

### **1.1 DOCUMENT POLICY**

- The report shall not be reproduced except in full, without the written approval of SRT Lab, Inc.

### **1.2 TEST STATEMENT**

- The test results in the report apply only to the unit tested by SRT Lab.
- There was no deviation from the requirements of test standards during the test.
- AC power source, 120 VAC/60 Hz, was used during the test.

### **1.3 EUT MODIFICATION**

- No modification in SRT Lab.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:5 of 56 Date: Apr. 04, 2007
---	----------------------	---

## 2. DESCRIPTION OF EUT AND TEST MODE

### 2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Multifunction Bluetooth Stereo Car Kit
MODEL NO.	BT-1250
POWER SUPPLY	DC 5V, 0.7A
FREQUENCY BAND	2.4GHz ISM, 2400~2483.5MHz
NUMBER OF CHANNEL	79
CHANNEL SPACING	1 MHz
RATED RF OUTPUT POWER	4 dBm (2.5mW)
MODE OF OPERATION	duplex
MODULATION TYPE	GFSK
BIT RATE OF TRANSMISSION	1Mbps
ANTENNA TYPE	PCB PATTERN
ANTENNA GAIN	0dBi
OPERATING TEMPERATURE	-40~105°C
CHANNEL BANDWIDTH	1MHz

**NOTE :**

The EUT has two model numbers as below on market. They are identical in all aspects except for the color of case.

For more detailed information, please refer to the EUT's specification or user's manual provided by manufacturer.

### 2.2 DESCRIPTION OF SUPPORT UNIT

The transmitter part of EUT was tested with a PC system and configured by the requirement of ANSI C63.4. All interface ports were connected to the appropriate support units via specific cables. The support units and cables are listed below.

NO	DEVICE	BRAND	MODEL #	FCC ID/DOC	CABLE
1	NOTEBOOK	DELL	PP01L	DOC	2.0m unshielded power cord
2	PRINTER	HP	HP3325	DOC	1.5m unshielded power cord 1.5m shielded data cord
3	DC POWER SUPPLY	LEADER	LPS-161A	N/A	1.8m unshielded power cord

**NOTE :** For the actual test configuration, please refer to the photos of testing.



## 2.3 DESCRIPTION OF TEST MODE

79 channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel	Frequency(MHz)
0	2402
39	2441
78	2480

EUT Configure Mode	Description
Mode1	Battery mode(Normal mode)
Mode2	USB charging mode

### NOTE :

1. Below 1 GHz, the channel 0, 39 and 78 were pre-tested in chamber. The channel 78, worst case one, was chosen for conducted and radiated emission test.
2. Above 1 GHz, the channel 0, 39 and 78 were tested individually.

## 3. DESCRIPTION OF APPLIED STANDARDS

The EUT is a kind of wireless product and to be connected with a PC system for normal use. According to the specifications provided by the applicant, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C

ANSI C63.4: 2003

All tests have been performed and recorded as the above standards.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:7 of 56 Date: Apr. 04, 2007
---	----------------------	---

## 4. TECHNICAL CHARACTERISTICS TEST

### 4.1 CONDUCTED EMISSION

#### 4.1.1 LIMIT

FREQUENCY (MHz)	Class A (dB $\mu$ V)		Class B (dB $\mu$ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.5 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

#### NOTE:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

#### 4.1.2 TEST EQUIPMENT


The following test equipment was used for the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9 KHZ TO 30 MHZ	ROHDE & SCHWARZ	ESHS30/ 826003/008	OCT. 2007 ETC
LISN (for EUT)	50 $\mu$ H, 50 ohm	FCC	FCC-LISN-50-25-2/ 01017	OCT. 2007 ETC
LISN (for Peripheral)	50 $\mu$ H, 50 ohm	FCC	FCC-LISN-50-25-2/ 01018	NOV. 2007 ETC
50 ohm TERMINATOR	50 ohm	HP	11593A/ 2	OCT. 2007 ETC
COAXIAL CABLE	5m	SUNCITY	CABLE 05/ #5-5M	NOV. 2007 SRT
ISOLATION TRANSFORMER	N/A	APC	AFC-11015/ F102040016	N/A
FILTER	2 LINE, 30A	FIL.COIL	FC-943/ 771	N/A
GROUND PLANE	2.3M (H) x 2.4M (W)	SRT	N/A	N/A
GROUND PLANE	2.4M (H) x 2.4M (W)	SRT	N/A	N/A

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.



### 4.1.3 TEST SETUP



**NOTE:**

1. The EUT was put on a wooden table with 0.8m height above ground plane, and 0.4m away from reference ground plane (> 2mx2m).
2. For the actual test configuration, please refer to the photos of testing.
3. The serial no. of the LISN connected to EUT is 951318.
4. The serial no. of the LISN connected to support units is 924839.

### 4.1.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4: 2003 and CISPR22:2006. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm/50 $\mu$ H as specified. All readings were quasi-peak and average values with 10 kHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. Both lines of the power mains of EUT were measured and the cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

### 4.1.5 EUT OPERATING CONDITION

Set the EUT under transmission condition continuously at a specific channel frequency.

Under Windows XP ran “EMI TEST” program, PC sent “H” pattern or accessed the following peripherals:

- Printer
- FDD
- HDD

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:9 of 56 Date: Apr. 04, 2007
---	----------------------	---

#### 4.1.6 TEST RESULT

Temperature:	25°C	Humidity:	58%RH
Frequency Range:	0.15 – 30 MHz	Tested Mode:	CH0
Receiver Detector:	Q.P. and AV.	Tested By:	John Yu
		Tested Date:	Mar. 28, 2007

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.174	0.30	50.52	43.74	50.82	44.04	65.31	55.31	-14.79	-11.58
0.519	0.24	37.68	35.74	37.98	36.04	56.00	46.00	-18.32	-10.26
3.041	0.13	39.02	32.34	39.17	32.49	56.00	46.00	-16.98	-13.66
5.051	0.11	32.40	28.06	32.55	28.21	60.00	50.00	-27.60	-21.94
6.431	0.10	29.12	21.51	29.36	21.85	60.00	50.00	-30.88	-28.49
15.666	0.10	26.36	20.20	36.00	20.44	60.00	50.00	-33.64	-29.80

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.171	0.30	51.76	44.11	52.06	44.41	65.40	55.40	-13.64	-11.29
0.975	0.24	40.74	39.42	40.98	39.66	56.00	46.00	-15.26	-6.58
1.319	0.13	39.52	37.83	39.65	37.96	56.00	46.00	-16.48	-8.17
11.466	0.11	27.12	21.51	27.23	21.62	60.00	50.00	-32.88	-28.49
12.440	0.10	26.92	21.24	27.02	21.34	60.00	50.00	-33.08	-28.76
18.341	0.10	26.62	20.51	26.72	20.61	60.00	50.00	-33.38	-29.49

#### NOTE :

1. Measurement uncertainty is +/-2dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies were very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:10 of 56 Date: Apr. 04, 2007
---	----------------------	--

Temperature:	25°C	Humidity:	58%RH
Frequency Range:	0.15 – 30 MHz	Tested Mode:	CH39
Receiver Detector:	Q.P. and AV.	Tested By:	John Yu
		Tested Date:	Mar. 28, 2007

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.153	0.30	51.46	23.40	51.76	23.70	65.82	55.82	-14.06	-32.12
1.129	0.15	32.92	28.05	33.07	28.20	56.00	46.00	-22.93	-17.80
2.259	0.11	38.68	35.73	38.79	35.84	56.00	46.00	-17.21	-10.16
7.680	0.10	25.30	18.07	25.40	18.17	60.00	50.00	-34.60	-31.83
7.720	0.10	24.88	19.39	24.98	19.49	60.00	50.00	-35.02	-30.51
17.860	0.10	28.56	17.87	28.66	17.97	60.00	50.00	-31.34	-32.03

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.150	0.30	52.04	24.18	52.34	24.48	65.98	55.98	-13.64	-31.50
0.744	0.21	30.22	21.60	30.43	21.81	56.00	46.00	-25.57	-24.19
2.259	0.11	43.82	39.87	43.93	39.98	56.00	46.00	-12.07	-6.02
2.497	0.11	38.28	32.78	38.39	32.89	56.00	46.00	-17.61	-13.11
6.594	0.10	19.48	14.21	19.58	14.31	60.00	50.00	-40.42	-35.69
15.287	0.10	19.26	12.22	19.36	12.32	60.00	50.00	-40.64	-37.68

**NOTE :**

1. Measurement uncertainty is +/-2dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies was very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:11 of 56 Date: Apr. 04, 2007
---	----------------------	--

Temperature:	25°C	Humidity:	58%RH
Frequency Range:	0.15 – 30 MHz	Tested Mode:	CH78
Receiver Detector:	Q.P. and AV.	Tested By:	John Yu
		Tested Date:	Mar. 28, 2007

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.153	0.30	51.44	23.30	51.74	23.60	65.82	55.82	-14.08	-32.22
0.648	0.23	34.00	26.69	34.23	26.92	56.00	46.00	-21.78	-19.09
1.962	0.11	35.94	30.16	36.05	30.27	56.00	46.00	-19.95	-15.73
2.259	0.11	36.64	33.12	36.75	33.23	56.00	46.00	-19.25	-12.77
6.218	0.10	29.94	24.28	30.04	24.38	60.00	50.00	-29.96	-25.62
15.215	0.10	24.74	19.82	24.84	19.92	60.00	50.00	-35.16	-30.08

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.162	0.30	50.08	21.94	50.38	22.24	65.34	55.34	-14.96	-33.10
0.509	0.24	33.00	26.49	33.24	26.73	56.00	46.00	-22.76	-19.27
2.259	0.11	40.36	37.24	40.47	37.35	56.00	46.00	-15.53	-8.65
7.050	0.10	25.50	19.03	25.60	19.13	60.00	50.00	-34.40	-30.87
14.074	0.10	22.78	16.32	22.88	16.42	60.00	50.00	-37.12	-33.58
15.359	0.10	22.88	15.14	22.98	15.24	60.00	50.00	-37.02	-34.76

**NOTE :**

1. Measurement uncertainty is +/-2dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies was very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:12 of 56 Date: Apr. 04, 2007
---	----------------------	--

Temperature:	25°C	Humidity:	57%RH
Frequency Range:	0.15 – 30 MHz	Tested Mode:	Link(Mode1)
Receiver Detector:	Q.P. and AV.	Tested By:	John Yu
Tested Date:	Mar. 28, 2007	Test Program:	EMITEST+Media player

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.153	0.30	50.26	23.03	50.56	23.33	65.82	55.82	-15.26	-32.49
0.500	0.24	31.06	24.55	31.30	24.79	55.98	45.98	-24.68	-21.19
3.695	0.10	39.48	33.78	39.58	33.88	56.00	46.00	-16.42	-12.12
4.081	0.10	39.82	33.49	39.92	33.59	56.00	46.00	-16.08	-12.41
7.131	0.10	37.78	32.15	37.88	32.25	60.00	50.00	-22.12	-17.75
28.222	0.10	33.52	27.75	33.62	27.85	60.00	50.00	-26.38	-22.15

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.156	0.30	50.24	22.37	50.54	22.67	65.66	55.66	-15.12	-32.99
0.500	0.24	31.60	24.99	31.84	25.23	55.98	45.98	-24.14	-20.75
3.695	0.10	39.70	33.73	39.80	33.83	56.00	46.00	-16.20	-12.17
6.431	0.10	38.60	32.85	38.70	32.95	60.00	50.00	-21.30	-17.05
6.929	0.10	38.22	32.53	38.32	32.63	60.00	50.00	-21.68	-17.37
27.864	0.10	32.44	26.67	32.54	26.77	60.00	50.00	-27.46	-23.23

**NOTE :**

1. Measurement uncertainty is +/-2dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies was very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:13 of 56 Date: Apr. 04, 2007
---	----------------------	--

Temperature:	25°C	Humidity:	58%RH
Frequency Range:	0.15 – 30 MHz	Tested Mode:	Link(Mode2)
Receiver Detector:	Q.P. and AV.	Tested By:	John Yu
Tested Date:	Mar. 28, 2007	Test Program:	EMITEST+Media player

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.150	0.30	52.18	24.55	52.48	24.85	65.98	55.98	-13.50	-31.13
0.639	0.23	33.22	27.01	33.45	27.24	56.00	46.00	-22.56	-18.77
2.447	0.11	27.44	21.86	27.55	21.97	56.00	46.00	-28.45	-24.03
5.264	0.10	28.78	23.13	28.88	23.23	60.00	50.00	-31.12	-26.77
5.731	0.10	28.56	23.38	28.66	23.48	60.00	50.00	-31.34	-26.52
24.625	0.10	26.65	20.72	26.75	20.82	60.00	50.00	-33.25	-29.18

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.150	0.30	51.96	23.71	52.26	24.01	65.98	55.98	-13.72	-31.97
0.504	0.24	36.24	27.77	36.48	28.01	56.00	46.00	-19.52	-17.99
1.220	0.14	29.52	21.60	29.66	21.74	56.00	46.00	-26.34	-24.26
5.162	0.10	28.94	22.24	29.04	22.34	60.00	50.00	-30.96	-27.66
7.060	0.10	32.00	18.83	32.10	18.93	60.00	50.00	-27.90	-31.07
15.195	0.10	19.26	14.28	19.36	14.38	60.00	50.00	-40.64	-35.62

**NOTE :**

1. Measurement uncertainty is +/-2dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies was very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:14 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.2 RADIATED EMISSION TEST

### 4.2.1 LIMIT

FCC Part15, Subpart C Section 15.209 limit of radiated emission measurement for frequency below 1000 MHz. The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

FREQUENCY (MHz)	DISTANCE(m)	FIELD STRENGTH (dB $\mu$ V/m)
30 – 88	3	40.0
88 - 216	3	43.5
216 - 960	3	46.0
ABOVE 960	3	54.0

**NOTE:**

1. In the emission tables above, the tighter limit applies at the band edges.
2. Distance refers to the distance between measuring instrument, antenna, and the closest point of any part of the device or system.

FCC Part 15, Subpart 15.35(b) limit of radiated emission for frequency above 1000MHz

FREQUENCY (MHz)	Class A (dB $\mu$ V/m) (at 3m)		Class B (dB $\mu$ V/m) (at 3m)	
	PK.	AV.	PK.	AV.
Above 1000	80.0	60.0	74.0	54.0

FCC Part 15, Subpart C Section 15.249. The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

FUNDAMENTAL FREQUENCY (MHz)	FILED STRENGTH OF FUNDAMENTAL (dB $\mu$ V/m) (at 3m)		FIELD STRENGTH OF HARMONICS (dB $\mu$ V/m) (at 3m)	
	PK.	AV.	PK.	AV.
902-928	114	94	74.0	54.0
2400-2483.5	114	94	74.0	54.0
5725-5875	114	94	74.0	54.0
24000-24250	128	108	88	68

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:15 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.2.2 TEST EQUIPMENT


The following test equipment was used during the radiated emission test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9kHz TO 2.75 GHz	ROHDE & SCHWARZ	ESCS30/ 830245/012	OCT. 2007 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3143/ 9509-1152	JUN. 2007 SRT
PRE-AMPLIFIER	1 GHz TO 26.5 GHz	HP	8449B/ 3008A01019	AUG. 2007 ETC
HORN ANTENNA	1 GHz TO 18 GHz	EMCO	3115/ 9602-4681	DEC. 2007 ETC
OATS	3 – 10 M MEASUREMENT	SRT	SRT-1	DEC. 2007 SRT
COAXIAL CABLE	25M	SUNCITY	J400-25M-2NP/ #153-25M	JUN. 2007 SRT
FILTER	2 LINE, 30A	FIL.COIL	FC-943/ 869	N/A
FREQUENCY CONVERTER	N/A	APC	AFC-2KBB/ F100030031	AUG. 2007 SRT

**NOTE:**

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.
2. The Open Area Test Site (SRT-1) is registered by FCC with No. 90957 and VCCI with No. R-1081.
3. The Open Area Test Site (SRT-2) is registered by FCC with No. 98458 and VCCI with No. R-1168.

#### 4.2.3 TEST SET-UP



**NOTE :**

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<b>TEST REPORT</b>	Reference No.:A07030114 Report No.:FCCA07030114 Page:17 of 56 Date: Apr. 04, 2007
---	--------------------	--

#### **4.2.4 TEST PROCEDURE**

The EUT was tested according to the requirement of ANSI C63.4:2003 and CISPR 22:2006. The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz, all readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak or average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

First, Find the margin or higher points at least 6 points by software, then use manual to find the maximum data. The procedure is referred on the test procedure of SRT LAB.

#### **4.2.5 EUT OPERATING CONDITION**

Same as section 4.5 of this report.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:18 of 56 Date: Apr. 04, 2007
---	----------------------	--

#### 4.2.6 RADIATED EMISSION TEST RESULT

Temperature:	25°C	Humidity:	57%RH
Frequency Range:	1 – 12.5GHz	Measured Distance:	3m
Receiver Detector:	Q.P. or AV.	Tested Mode:	CH0(Mode 1)
Tested By:	John Yu	Tested Date:	Mar. 28, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2402	-32.16	28.54	71.8	50.3	68.2	46.7	N/A	N/A	N/A	N/A	48.3	1.25
4804	-30.47	33.64	43.2	*	46.4	*	74.0	54.0	-27.6	*	78.6	1.33
7206	-28.90	36.26	45.1	*	52.5	*	74.0	54.0	-21.5	*	94.8	1.51
2383.71	-32.22	27.97	45.8	*	41.5	*	74.0	54.0	-32.5	*	75.6	1.68
2487.67	-32.18	28.17	45.1	*	41.1	*	74.0	54.0	-32.9	*	136	1.21
2511.71	-32.08	28.26	43.2	*	39.4	*	74.0	54.0	-34.6	*	228	1.18

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2402	-32.16	28.00	67.7	60.7	63.5	56.5	N/A	N/A	N/A	N/A	87.2	1.83
4804	-30.47	33.64	42.7	*	45.9	*	74.0	54.0	-28.1	*	148	2.17
7206	-28.90	36.26	43.6	*	51.0	*	74.0	54.0	-23.0	*	187	2.98
2228.94	-32.51	27.66	46.2	*	41.3	*	74.0	54.0	-32.7	*	325	1.86
2416.73	-32.19	28.03	42.7	*	38.5	*	74.0	54.0	-35.5	*	193	1.91
2517.92	-32.04	28.30	45.8	*	42.1	*	74.0	54.0	-31.9	*	37.2	2.15

#### NOTE :

1. Measurement uncertainty is +/-2dB.
2. \*\*: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:19 of 56 Date: Apr. 04, 2007
---	----------------------	--

Temperature:	27°C	Humidity:	59%RH
Frequency Range:	1-12.5GHz	Measured Distance:	3m
Receiver Detector:	Q.P. or AV.	Tested Mode:	CH39(Mode1)
Tested By:	John Yu	Tested Date:	Mar. 28, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2441	-32.23	28.62	67.5	50.3	63.9	46.7	N/A	N/A	N/A	N/A	148	1.92
4882	-30.26	33.71	43.7	*	47.1	*	74.0	54.0	-26.9	*	67.4	2.27
7323	-29.04	36.36	44.2	*	51.5	*	74.0	54.0	-22.5	*	182	2.11
2371	-32.27	27.94	45.4	*	41.1	*	74.0	54.0	-32.9	*	47	2.86
2491.62	-32.17	28.18	43.7	*	39.7	*	74.0	54.0	-34.3	*	48.3	1.97
2571.62	-31.92	28.60	43.9	*	40.6	*	74.0	54.0	-33.4	*	92.4	1.62

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2441	-32.23	28.08	71	60.7	66.9	56.6	N/A	N/A	N/A	N/A	128	1.88
4882	-30.26	33.71	47.1	*	50.5	*	74.0	54.0	-23.5	*	63.7	1.65
7323	-29.04	36.36	43.8	*	51.1	*	74.0	54.0	-22.9	*	158	1.29
2175.61	-32.35	27.55	43.2	*	38.4	*	74.0	54.0	-35.6	*	229	1.26
2413.94	-32.18	28.03	46.8	*	42.6	*	74.0	54.0	-31.4	*	239	1.11
2494.61	-32.17	28.19	41.7	*	37.7	*	74.0	54.0	-36.3	*	327	1.23

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. \*\*: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:20 of 56 Date: Apr. 04, 2007
---	----------------------	--

Temperature:	27°C	Humidity:	59%RH
Frequency Range:	1-12.5GHz	Measured Distance:	3m
Receiver Detector:	PK. or AV.	Tested Mode:	CH78(Mode1)
Tested By:	John Yu	Tested Date:	Mar. 28, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)		AZ( $^{\circ}$ )	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2480.00	-32.19	28.73	66.4	50.3	62.9	46.8	N/A	N/A	N/A	N/A	34.0	1.2
4960.00	-30.26	33.77	40.7	*	44.2	*	74.0	54.0	-29.8	*	302.0	1.1
7440.00	-28.95	36.45	43.2	*	50.7	*	74.0	54.0	-23.3	*	48.0	1.1
2351.12	-32.35	27.90	43.1	*	38.7	*	74.0	54.0	-35.3	*	273.0	1.1
2412.31	-32.18	28.02	37.5	*	33.3	*	74.0	54.0	-40.7	*	132.0	1.2
2568.91	-31.91	28.58	38.7	*	35.4	*	74.0	54.0	-38.6	*	124.0	1.1

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)		AZ( $^{\circ}$ )	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2480.00	-32.19	28.16	63.3	60.7	59.3	56.7	N/A	N/A	N/A	N/A	91.0	1.2
4960.00	-30.26	33.77	42.3	*	45.8	*	74.0	54.0	-28.2	*	38.0	1.1
7440.00	-28.95	36.45	38.2	*	45.7	*	74.0	54.0	-28.3	*	267.0	1.3
1284.30	-33.75	24.82	39.8	*	30.9	*	74.0	54.0	-43.1	*	140.0	1.3
2367.19	-32.29	27.93	37.1	*	32.7	*	74.0	54.0	-41.3	*	127.0	1.1
2562.19	-31.87	28.55	37.9	*	34.6	*	74.0	54.0	-39.4	*	280.0	1.4

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. \*\*: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:21 of 56 Date: Apr. 04, 2007
---	----------------------	--

Temperature:	27°C	Humidity:	59%RH
Frequency Range:	30MHz-1GHz	Measured Distance:	3m
Receiver Detector:	PK. Or AV.	Tested Mode:	Link(Mode2)
Tested By:	John Yu	Tested Date:	Mar. 28, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
223.3564	2.63	10.62	21.0	*	34.3	*	40.0	*	-5.7	*	65	1.25
325.2546	3.15	14.55	18.2	*	35.9	*	47.0	*	-11.1	*	75	1.45
456.2145	3.90	17.80	12.3	*	34.0	*	47.0	*	-13.0	*	145	1.32
659.3245	4.81	20.36	3.2	*	28.4	*	47.0	*	-18.6	*	252	1.02
785.3260	5.29	22.90	0.1	*	28.3	*	47.0	*	-18.7	*	112	1.65
801.3256	5.34	22.81	2.1	*	30.2	*	47.0	*	-16.8	*	256	1.24

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dB $\mu$ V)		Emission (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
235.3654	2.69	10.95	21.0	*	34.6	*	47.0	*	-12.4	*	142	1.27
299.3654	3.02	13.70	17.0	*	33.7	*	47.0	*	-13.3	*	123	1.24
654.3250	4.78	20.16	8.5	*	33.4	*	47.0	*	-13.6	*	89	1.15
711.3692	5.07	21.84	1.2	*	28.1	*	47.0	*	-18.9	*	129	1.36
800.3695	5.33	22.80	0.2	*	28.3	*	47.0	*	-18.7	*	63	1.03
883.2654	5.74	24.26	0.9	*	30.9	*	47.0	*	-16.1	*	78	1.64

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. \*\*: Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:22 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.3 CHANNEL SEPARATION TEST

### 4.3.1 LIMIT

FCC Part15, Subpart C Section 15.247(a)(1). Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

FREQUENCY RANGE (MHz)	Limit(kHz)
902-928	>25kHz
2400-2483.5	>25kHz
5725-5850	>25kHz


### 4.3.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test :

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	APR. 2008 R&S

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.3.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

### 4.3.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.

### 4.3.5 EUT OPERATING CONDITION

Same as section 4.1.5 of thes report.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:23 of 56 Date: Apr. 04, 2007
---	----------------------	--

#### 4.3.6 TEST RESULT

Temperature:	27°C	Humidity:	59%RH
Spectrum Detector:	PK	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Mar. 29, 2007

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	SEPARATION READ VALUE (kHz)	SEPARATION LIMIT (kHz)
0	2402	1000.000	>25kHz
39	2441	1000.000	>25kHz
78	2480	1004.000	>25kHz




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.:A07030114  
Report No.:FCCA07030114  
Page:24 of 56  
Date: Apr. 04, 2007


CH0:



Date: 27.MAR.2007 19:06:02

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:25 of 56 Date: Apr. 04, 2007
---	----------------------	--


CH39:



Date: 27.MAR.2007 19:14:39

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:26 of 56 Date: Apr. 04, 2007
---	----------------------	--

CH78:



Date: 27.MAR.2007 19:23:30

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:27 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.4 QUANTITY OF HOPPING CHANNEL TEST

### 4.4.1 LIMIT

FCC Part15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	Limit (Quantity of Hopping Channel)			
	20dB bandwidth <250kHz	20dB bandwidth >250kHz	20dB bandwidth <1MHz	20dB bandwidth >1MHz
902-928	50	25	N/A	N/A
2400-2483.5	N/A	N/A	75	15
5725-5850	N/A	N/A	75	N/A


### 4.4.2 TEST EQUIPMENT

The following test equipment was used during the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	APR. 2008 R&S

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.4.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

### 4.4.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.

### 4.4.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.


 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:28 of 56 Date: Apr. 04, 2007
---	----------------------	--

#### 4.4.6 TEST RESULT

Temperature:	27°C	Humidity:	59%RH
Spectrum Detector:	PK	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Mar. 29, 2007

HOPPING CHANNEL FREQUENCY RANGE	QUANTITY OF HOPPING CHANNEL READ VALUE	QUANTITY OF HOPPING CHANNEL LIMIT
2402~2480	79	75

CH0-CH78



Date: 27.MAR.2007 18:55:51

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:29 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.5 AVERAGE TIME OF OCCUPANCY TEST(Dwell Time)

### 4.5.1 LIMIT

FCC Part15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	LIMIT (ms)		
	20dB bandwidth <250kHz(50Channel)	20dB bandwidth >250kHz(25Channel)	20dB bandwidth <1MHz(75Channel)
902-928	400(20s)	400(10s)	NA
2400-2483.5	NA	NA	400(30s)
5725-5850	NA	NA	400(30s)

**NOTE:** The “()” is all channel's average time of occupancy.


### 4.5.2 TEST EQUIPMENT

The following test equipment was used during the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	APR. 2008 R&S

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.5.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

### 4.5.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.

### 4.5.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:30 of 56 Date: Apr. 04, 2007
---	----------------------	--

#### 4.5.6 TEST RESULT

Temperature:	27°C	Humidity:	59%RH
Spectrum Detector:	PK	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Mar. 30, 2007


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	Pulse Time (μs)	Burts (in 1 sec.)	Time of occupancy (Dwell Time) (ms)	Average time of occupancy LIMIT (ms)
0	2402.00	418	10	132.0	400
39	2441.00	418	10	132.0	400
78	2480.00	418	10	132.0	400



# TEST REPORT

Reference No.:A07030114  
Report No.:FCCA07030114  
Page:31 of 56  
Date: Apr. 04, 2007

CH0:




Date: 22.Mar.2007 09:05:56



# TEST REPORT

Reference No.:A07030114  
Report No.:FCCA07030114  
Page:32 of 56  
Date: Apr. 04, 2007

Ch39:




Date: 23.Mar.2007 09:10:03

----



# TEST REPORT

CH78:



Date: 27.Mar.2007 09:11:48

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:34 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.6 MAXIMUM SPECTRAL PEAK POWER TEST

### 4.6.1 LIMIT

FCC Part15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	Quantity of Hopping Channel	LIMIT (W)			
		50	25	15	75
902-928	1(30dBm)	0.125(21dBm)	NA	NA	NA
2400-2483.5	NA	NA	0.125(21dBm)	1(30dBm)	NA
5725-5850	NA	NA	NA	NA	1(30dBm)

### 4.6.2 TEST EQUIPMENT


The following test equipment was used during the test :

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	APR. 2008 R&S
POWER METER	N/A	BOONTON	4232A/ 29001	MAY 2007 ETC
POWER SENSOR	DC-18GHz 0.3 $\mu$ W-100mW 50 $\Omega$	BOONTON	51011-EMC/ 31184	JUN. 2007 ETC

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.



### 4.6.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

### 4.6.4 TEST PROCEDURE

The EUT was operating in hopping mode or could control its channel.  
Printed out the test result from the spectrum by hard copy function.  
Recorded the read value of the power meter.

### 4.6.5 EUT OPERATING CONDITION


Same as section 4.1.5 of this report.

### 4.6.6 TEST RESULT

Temperature:	27°C	Humidity:	59%RH
Spectrum Detector:	PK	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Mar. 30, 2007


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)
0	2402.0000	-2.02	30
39	2441.0000	-1.33	30
78	2480.0000	-0.20	30

CH0:



Date: 26.MAR.2007 20:15:42


CH39:



Date: 26.MAR.2007 20:42:55

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:37 of 56 Date: Apr. 04, 2007
---	----------------------	--

CH78:



Date: 26.MAR.2007 20:35:32

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:38 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.7 BAND EDGE TEST

### 4.7.1 LIMIT

FCC Part15, Subpart C Section 15.247. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

OPERATING FREQUENCY RANGE (MHz)	SPURIOUS EMISSION FREQUENCY (MHz)	LIMIT	
		Peak power ration to emission(dBc)	Emission level(dBuV/m)
902-928	<902	>20	NA
	>928	>20	NA
	960-1240	NA	54
2400-2483.5	<2400	>20	NA
	>2483.5-2500	NA	54
5725-5850	<5350-5460	NA	54
	<5725	>20	NA
	>5850	>20	NA

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:39 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.7.2 TEST EQUIPMENT


The following test equipment was used during the test :

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	APR. 2008 R&S
EMI TEST RECEIVER	9 kHz TO 2750 MHz	ROHDE & SCHWARZ	ESCS30/ 830245/012	AUG. 2007 R&S
SPECTRUM	9KHz-26.5GHz	HP	8593E/ 3710A03220	MAY 2008 ETC
PRE-AMPLIFIER	1GHz-26.5GHz Gain:30dB	HP	8449B/ 3008A01019	NOV. 2008 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3142/ 9701-1124	FEB. 2007 SRT
HORN ANTENNA	1GHz to 18GHz	EMCO	3115/ 9602-4681	DEC. 2007 ETC
OATS	3 - 10 M measurement	SRT	SRT-1	APR. 2008 SRT

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.7.3 TEST SET-UP

FOR RF CONDUCTED TEST (dBc)



The EUT was connected to the spectrum through a  $50\Omega$  RF cable.

FOR RADIATED EMISSION TEST



**NOTE :**

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:41 of 56 Date: Apr. 04, 2007
---	----------------------	--

#### 4.7.4 TEST PROCEDURE

1. The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.
2. The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22.  
The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz. All readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak and average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

#### 4.7.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

#### 4.7.6 TEST RESULT

Temperature:	27°C	Humidity:	59%RH
Spectrum Detector:	PK & AV	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Apr. 02, 2007

##### 1. Conducted test


Frequency (MHz)	PEAK POWER OUTPUT (dBm)	Emission read Value(dBm)	Result of Band edge (dBc)	Band edge LIMIT (dBc)
<2400	-4.84	-45.83	40.99	>20dBc
>2483.5	-0.27	-47.83	47.56	>20dBc

##### 2. Radiated emission test

Frequency (MHz)	Antenna polarization (H/V)	PEAK POWER OUTPUT (dBm)	Emission read Value(dBm)	Band edge Limit (dBuV/m)
<2400	V	58.69	33.7	54
>2483.5	V	55.68	37.6	54


<2400MHz:

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:42 of 56 Date: Apr. 04, 2007
---	----------------------	--



Date: 27.MAR.2007 19:46:23

>2483.5MHz



Date: 27.MAR.2007 19:54:06

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:44 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.8 POWER DENSITY TEST

### 4.8.1 LIMIT

FCC Part15, Subpart C Class B

Frequency Range (MHz)	Limit (dBm/kHz)
902-928	
2400-2483.5	8dBm/3kHz
5725-5850	


### 4.8.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9 kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2008 R & S

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.8.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

### 4.8.4 TEST PROCEDURE

The EUT was operating in transmitter mode and could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.

### 4.8.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.


 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:45 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.8.6 TEST RESULT

Temperature:	27°C	Humidity:	59%RH
Spectrum Detector:	PK.	Tested By:	John Yu
Tested Result:	Pass	Tested Date:	Apr. 02, 2007


Channel Number	Channel Frequency (MHz)	RF POWER LEVEL IN 3KHz BW (dBm/3kHz)	MAXIMUM Limit (dBm/3kHz)
1	2402.0000	-2.83	8
2	2443.0000	-2.08	8
3	2480.0000	-0.93	8

CH0:



 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:46 of 56 Date: Apr. 04, 2007
---	----------------------	--

CH39:



Date: 26.MAR.2007 20:42:55




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.:A07030114  
Report No.:FCCA07030114  
Page:47 of 56  
Date: Apr. 04, 2007

CH78:



Date: 26.MAR.2007 20:35:32

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:48 of 56 Date: Apr. 04, 2007
---	----------------------	--

## 4.9 20dB Bandwidth

### 4.9.1 LIMIT

Frequency Range (MHz)	Limit(kHz)				
	Quantity of Hopping Channel	50	25	15	75
902-928	<250	>250	NA	NA	
2400-2483.5	NA	NA	>1000	<1000	


### 4.9.2 TEST EQUIPMENT

The following test equipment was used during the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	APR. 2008 R&S

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.9.3 TEST SET-UP



The EUT was connected to a spectrum through a  $50\Omega$  RF cable.

### 4.9.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.

### 4.9.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.:A07030114  
Report No.:FCCA07030114  
Page:49 of 56  
Date: Apr. 04, 2007


## 4.9.6 TEST RESULT

Temperature:	26°C	Humidity:	55%RH
Spectrum Detector:	PK	Tested by:	John Yu
Test Result:	PASS	Tested Date:	Apr. 03, 2007

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	20dB DOWN BW (kHz)
0	2402	848
39	2441	876
78	2480	868

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:50 of 56 Date: Apr. 04, 2007
---	----------------------	--


CH0:



Date: 26.MAR.2007 21:38:32

 <p><b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan</p>	<h1>TEST REPORT</h1>	Reference No.:A07030114 Report No.:FCCA07030114 Page:51 of 56 Date: Apr. 04, 2007
---	----------------------	--

Ch39:



Date: 26.MAR.2007 21:29:36




**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.:A07030114  
Report No.:FCCA07030114  
Page:52 of 56  
Date: Apr. 04, 2007

CH78:



Date: 27.MAR.2007 17:34:28



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.:A07030114  
Report No.:FCCA07030114  
Page:53 of 56  
Date: Apr. 04, 2007

## 5. Antenna application

### 5.1 Antenna requirement

The EUT's antenna is met the requirement of FCC part15C section15.203 and 15.204.

FCC part15C section15.247 requirement:

Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

### 5.2 Result

The EUT's antenna used a dipole antenna and integrated on PCB. The antenna's gain is 2dBi and meets the requirement.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.:A07030114  
Report No.:FCCA07030114  
Page:56 of 56  
Date: Apr. 04, 2007

## 7. TERMS OF ABRIVATION

AV.	Average detection
AZ( $^{\circ}$ )	Turn table azimuth
Correct.	Correction
EL(m)	Antenna height (meter)
EUT	Equipment Under Test
Horiz.	Horizontal direction
LISN	Line Impedance Stabilization Network
NSA	Normalized Site Attenuation
Q.P.	Quasi-peak detection
SRT Lab	Spectrum Research & Testing Laboratory, Inc.
Vert.	Vertical direction