

# ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

## INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 15 SUBPART C REQUIREMENT

OF

<b>Product Name:</b>	<b>Red Laser Remo-pen</b>
<b>Brand Name:</b>	<b>N/A</b>
<b>Model Name:</b>	<b>R24, R32</b>
<b>Model Differences:</b>	<b>Model R24 operates with red light whereas model R32 with green light</b>
<b>FCC ID:</b>	<b>UDRALP02450501B1</b>
<b>Report No.:</b>	<b>ER/2006/30032</b>
<b>Issue Date:</b>	<b>Jul. 27, 2006</b>
<b>FCC Rule Part:</b>	<b>§15.249</b>
<b>Prepared for</b>	<b>OPCOM INC. 8F-5,NO.6,Lane 609,Sec. 5,Chung Hsing Rd. Sanchung City, Taipei Hsien, Taiwan</b>
<b>Prepared by</b>	<b>SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei County, Taiwan.</b>



**Note:** This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the document.

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

## VERIFICATION OF COMPLIANCE

**Applicant:** OPCOM INC.  
8F-5,NO.6,Lane 609,Sec. 5,Chung Hsing Rd. Sanchung City, Taipei  
Hsien, Taiwan

**Product Description:** Red Laser Remo-pen

**Brand Name:** N/A

**FCC ID Number:** UDRALP02450501B1

**Model No.:** R24, R32

**Model Difference:** Model R24 operates with red light whereas model R32 with green light

**File Number:** ER/2006/30032

**Date of test:** Jul. 17, 2006 ~ Jul. 24, 2006

**Date of EUT Received:** Jul. 16, 2006

### We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.249.

The test results of this report relate only to the tested sample identified in this report.

**Test By:** Danny Yeh **Date** Jul. 27, 2006

**Test By:** Danny Yeh

**Prepared By:** Elisa Chen **Date** Jul. 27, 2006

**Prepared By:** Elisa Chen

**Approved By:** Vincent Su **Date** Jul. 27, 2006

**Approved By:** Vincent Su

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。



FCC ID: UDRALP02450501B1

REPORT NO: ER/2006/30032

DATE: Jul. 27, 2006

Page: 3

## Version

Version No.	Date
00	Jul. 27, 2006

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issued defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

## Table of Contents

<b>1.</b>	<b>GENERAL INFORMATION .....</b>	<b>5</b>
1.1	PRODUCT DESCRIPTION .....	5
1.2	RELATED SUBMITTAL(S) / GRANT (S) .....	5
1.3	TEST METHODOLOGY .....	6
1.4	TEST FACILITY .....	6
1.5	SPECIAL ACCESSORIES .....	6
1.6	EQUIPMENT MODIFICATIONS .....	6
<b>2.</b>	<b>SYSTEM TEST CONFIGURATION .....</b>	<b>7</b>
2.1	EUT CONFIGURATION .....	7
2.2	EUT EXERCISE .....	7
2.3	TEST PROCEDURE .....	7
2.4	LIMITATION .....	8
2.5	CONFIGURATION OF TESTED SYSTEM .....	10
<b>3.</b>	<b>SUMMARY OF TEST RESULTS .....</b>	<b>11</b>
<b>4.</b>	<b>CONDUCTED EMISSIONS TEST (NOT APPLICABLE IN THIS REPORT).....</b>	<b>12</b>
4.1	MEASUREMENT PROCEDURE: .....	12
4.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	12
4.3	MEASUREMENT EQUIPMENT USED: .....	12
4.4	MEASUREMENT RESULT: .....	12
<b>5.</b>	<b>RADIATED EMISSION TEST .....</b>	<b>13</b>
5.1	MEASUREMENT PROCEDURE .....	13
5.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	13
5.3	MEASUREMENT EQUIPMENT USED: .....	14
5.4	FIELD STRENGTH CALCULATION .....	14
5.5	MEASUREMENT RESULT .....	15
<b>6.</b>	<b>26 DB BAND WIDTH MEASUREMENT.....</b>	<b>24</b>
6.1	MEASUREMENT PROCEDURE .....	24
6.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	24
6.3	MEASUREMENT EQUIPMENT USED: .....	24
6.4	MEASUREMENT RESULTS: .....	24

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

## 1. GENERAL INFORMATION

### 1.1 Product Description

The OPCOM INC., Model: R24, R32 (referred to as the EUT in this report) The EUT is a Laser Remoter Pen.

A major technical descriptions of EUT is described as following:

- A). Operation Frequency: 2403-2474MHz, channel listed below.
- B). Modulation Type:TDMA
- C). Antenna Designation: Trace Antenna, Non-User Replaceable (Fixed)
- D). Power Supply: 1.5 Vdc from AAA battery.

	Presenter	ID
CH1	2.403Ghz	65536 sets
CH2	2.405Ghz	65536 sets
CH3	2.407Ghz	65536 sets
CH4	2.414Ghz	65536 sets
CH5	2.419Ghz	65536 sets
CH6	2.424Ghz	65536 sets
CH7	2.429Ghz	65536 sets
CH8	2.434Ghz	65536 sets
CH9	2.439Ghz	65536 sets
CH10	2.444Ghz	65536 sets
CH11	2.449Ghz	65536 sets
CH12	2.454Ghz	65536 sets
CH13	2.459Ghz	65536 sets
CH14	2.464Ghz	65536 sets
CH15	2.469Ghz	65536 sets
CH16	2.474Ghz	65536 sets

### 1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **UDRALP02450501B1** filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules. The composite system

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issued defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

**SGS Taiwan Ltd.** | No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 | t (886-2) 2299-3939 | f (886-2) 2298-2698 | [www.sgs.com.tw](http://www.sgs.com.tw)

(receiver) is compliance with Subpart B is authorized under a verification procedure.

### 1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the address of SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003 and CISPR 22/EN 55022 requirements. Site No. 1(3 &10 meters) Registration Number: 94644, Both OATS and Anechoic chamber (3 meters) was accredited by CNLA (0513).

### 1.5 Special Accessories

Not available for this EUT intended for grant.

### 1.6 Equipment Modifications

Not available for this EUT intended for grant.

## 2. System Test Configuration

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT Exercise

The Transmitter was operated in the engineering operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

### 2.3 Test Procedure

#### 2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 7 and 13 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and Average detector mode.

#### 2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 8 and 13 of ANSI C63.4-2003.

## 2.4 Limitation

### (1) Conducted Emission

According to section 15.207(a) Conducted Emission Limits is as following.

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 – 0.5	66 - 56	56 - 46
0.5 – 5	56	46
5 - 30	60	50

### (2) Radiated Emission 15.249(a)

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following.

Frequency (MHz)	Field strength of Fundamental	Field strength of Harmonics	Distance (m)
902 - 928	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
2400 – 2483.5	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
5725 – 5875	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
24.0 – 24.25 GHz	250 mV/m (107.95dBuV/m)	2500 uV/m (67.95dBuV/m)	3

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

### (3) Radiated Emission 15.249 (d)

Emission Radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209 as below, whichever is the lesser attenuation.

Frequency (MHz)	Field strength $\mu\text{V/m}$	Distance (m)	Field strength at 3m $\text{dB}\mu\text{V/m}$
1.705-30	30	30	69.54
30-88	100	3	40
88-216	150	3	43.5
216-960	200	3	46
Above 960	500	3	54

### (4) Radiated Emission 15.249(e)


For frequencies above 1000MHz, the above field strength limits are based on average limits. The peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20dB under any condition of modulation.

Remark: 1. Emission level in  $\text{dB}\mu\text{V/m} = 20 \log (\mu\text{V/m})$

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of  $\xi$  15.205
4. Emission spurious frequency which appearing within the Restricted Bands specified in provision of  $\xi$  15.205, then the general radiated emission limits in  $\xi$  15.209 apply.

## 2.5 Configuration of Tested System

**Fig. 2-1 Configuration of TX**



**Table 2-2 Equipment Used in Tested System**

Item	Equipment	Mfr/Brand	Model/ Type No.	FCC ID	Series No.	Data Cable	Power Cord
1	DC Power Supply	Topward	3303D	N/A	981327	NA/	N/A

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

### 3. Summary Of Test Results

FCC Rules	Description Of Test	Result
§15.207	Conducted Emission	N/A
§15.249(a)(e)	Radiated Emission	Compliant
§15.249(d)	26dB band width Measurement	Compliant

#### Description of test modes

The EUT has been tested under normal operating mode.

The X, Y and Z-axis of EUT were pre-test at channel low(2403MHz), mid (2439MHz) and high(2474MHz); the worst case X mode is reported.


This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

## 4. Conducted Emissions Test (Not applicable in this report)

### 4.1 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

### 4.2 Test SET-UP (Block Diagram of Configuration)



### 4.3 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMC Analyzer	HP	8594EM	3624A00203	09/02/2005	09/03/2006
EMI Test Receiver	R&S	ESCS30	828985/004	06/09/2006	06/10/2007
Transient Limiter	HP	11947A	3107A02062	09/02/2005	09/03/2006
LISN	Rolf-Heine	NNB-2/16Z	99012	12/31/2005	12/30/2006
LISN	Rolf-Heine	NNB-2/16Z	99013	12/24/2005	12/23/2006
Coaxial Cables	N/A	No. 3, 4	N/A	12/01/2005	12/01/2206

### 4.4 Measurement Result:

N/A

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

**SGS Taiwan Ltd.** | No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 | t (886-2) 2299-3939 | f (886-2) 2298-2698 | [www.sgs.com.tw](http://www.sgs.com.tw)


## 5. Radiated Emission Test

### 5.1 Measurement Procedure


1. The EUT was placed on a turntable that is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

### 5.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

### 5.3 Measurement Equipment Used:

966 Chamber					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2006	03/28/2007
Spectrum Analyzer	Agilent	E7405A	US41160416	08/27/2005	08/26/2006
Bilog Antenna	SCHWAZBECK	VULB9163	152	06/03/2006	06/02/2007
Horn antenna	Schwarzbeck	BBHA 9120D	309/320	08/16/2005	08/15/2006
Horn antenna	Schwarzbeck	BBHA 9170	184/185	07/04/2006	07/03/2007
Pre-Amplifier	HP	8447D	2944A09469	07/19/2006	07/18/2007
Pre-Amplifier	HP	8449B	3008A00578	02/26/2006	02/25/2007
Turn Table	HD	DT420	N/A	N.C.R	N.C.R
Antenna Tower	HD	MA240-N	240/657	N.C.R	N.C.R
Controller	HD	HD100	N/A	N.C.R	N.C.R
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	10/09/2005	10/08/2006
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	10/09/2005	10/08/2006
Site NSA	SGS	966 chamber	N/A	11/17/2005	11/16/2006

### 5.4 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

SGS Taiwan Ltd. | No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3939

f (886-2) 2298-2698

[www.sgs.com.tw](http://www.sgs.com.tw)

## 5.5 Measurement Result

### Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	TX CH Low	Test Date	Jul. 20, 2006
Fundamental Frequency	2403MHz	Test By	Danny
Temperature	25°C	Pol	Ver./Hor
Humidity	65%		

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
30.00	V	Peak	44.46	-15.29	29.17	40.00	-10.83
66.86	V	Peak	35.80	-15.61	20.19	40.00	-19.81
95.96	V	Peak	36.87	-17.52	19.35	43.50	-24.15
152.22	V	Peak	31.34	-13.58	17.76	43.50	-25.74
30.00	H	Peak	42.15	-15.29	26.86	40.00	-13.14
66.86	H	Peak	34.72	-15.61	19.11	40.00	-20.89
176.47	H	Peak	32.39	-15.02	17.37	43.50	-26.13

#### Remark :

- (1) Measuring frequencies from 30 MHz to the 1GHz .
- (2) Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- (3) Datas of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz, VBW=300KHz.

**Radiated Spurious Emission Measurement Result (below 1GHz)**

Operation Mode TX CH Mid Test Date Jul. 20, 2006  
Fundamental Frequency 2439MHz Test By Danny  
Temperature 25°C Pol Ver./Hor  
Humidity 65%

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
30.00	V	Peak	40.78	-15.29	25.49	40.00	-14.51
63.95	V	Peak	34.50	-15.01	19.49	40.00	-20.51
95.96	V	Peak	35.86	-17.52	18.34	43.50	-25.16
152.22	V	Peak	31.00	-13.58	17.42	43.50	-26.08
30.00	H	Peak	38.61	-15.29	23.32	40.00	-16.68
66.86	H	Peak	34.27	-15.61	18.66	40.00	-21.34
160.95	H	Peak	32.19	-14.33	17.86	43.50	-25.64

## Remark :

- (1) Measuring frequencies from 30 MHz to the 1GHz .
- (2) Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- (3) Datas of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz, VBW=300KHz.

**Radiated Spurious Emission Measurement Result (below 1GHz)**

Operation Mode TX CH High Test Date Jul. 20, 2006  
Fundamental Frequency 2474MHz Test By Danny  
Temperature 25°C Pol  
Humidity 65% Ver./Hor

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
57.16	V	Peak	44.18	-14.89	29.29	40.00	-10.71
95.96	V	Peak	39.28	-17.52	21.76	43.50	-21.74
139.61	V	Peak	32.26	-13.92	18.34	43.50	-25.16
30.00	H	Peak	39.39	-15.29	24.10	40.00	-15.90
66.86	H	Peak	34.01	-15.61	18.40	40.00	-21.60
93.05	H	Peak	34.25	-17.72	16.53	43.50	-26.97

## Remark :

- (1) Measuring frequencies from 30 MHz to the 1GHz。
- (2) Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- (3) Datas of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz, VBW=300KHz.

### Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode: TX CH Low  
Fundamental Frequency: 2403MHz  
Temperature : 25 °C  
Humidity : 65 %

Test Date : Jul. 20, 2006  
Test By: Danny  
Pol: Vertical

Freq. (MHz)	Ant.Pol H/V	Peak	AV	Factor (dB)	Actual Peak	Actual FS	Peak Limit	AV Limit	Margin (dB)
		Reading (dBuV)	Reading (dBuV)		FS (dBuV/m)	AV (dBuV/m)	at 3m (dBuV/m)	at 3m (dBuV/m)	
2403.0	V	82.44	--	-3.40	79.04	--	114.00	94.00	-14.96
4806.0	V	55.04	35.14	6.59	61.63	41.73	74.00	54.00	-12.27
7209.0	V	46.32	33.1	9.27	55.59	42.37	74.00	54.00	-11.63
9612.0	V	--	--			--	74.00	54.00	H
12015.0	V	--	--			--	74.00	54.00	H
14418.0	V	--	--			--	74.00	54.00	H
16821.0	V	--	--			--	74.00	54.00	H
19224.0	V	--	--			--	74.00	54.00	H
21627.0	V	--	--			--	74.00	54.00	H
24030.0	V	--	--			--	74.00	54.00	H
2400.0	V	38.43	--	-3.4	35.03	--	74.00	54.00	-18.97
									S

Remark :

- (1) Measuring frequencies from 30MHz to the 10th of fundamental frequency。
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issued defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode: TX CH Low

Test Date : Jul. 20, 2006

Fundamental Frequency: 2403MHz

Test By: Danny

Temperature : 25°C

Pol: Horizontal

Humidity : 65%

Freq. (MHz)	Ant. H/V	Peak	AV	Factor	Actual	Actual	Peak Limit	AV Limit	Margin	
		Reading (dBuV)	Reading (dBuV)		Peak FS (dBuV/m)	AV FS (dBuV/m)	at 3m (dBuV/m)	at 3m (dBuV/m)		
2403.0	H	93.55	--	-3.40	90.15	--	114.00	94.00	-3.85	F
2709.5	H	40.06	--	-2.54	37.52	--	74.00	54.00	-16.48	S
4806.0	H	59.81	35.88	2.99	62.80	38.87	74.00	54.00	-11.20	H
7209.0	H	43.28	32.56	9.27	52.55	41.83	74.00	54.00	-12.17	H
9612.0	H	--	--			--	74.00	54.00		H
12015.0	H	--	--			--	74.00	54.00		H
14418.0	H	--	--			--	74.00	54.00		H
16821.0	H	--	--			--	74.00	54.00		H
19224.0	H	--	--			--	74.00	54.00		H
21627.0	H	--	--			--	74.00	54.00		H
24030.0	H	--	--			--	74.00	54.00		H
2400.0	H	50.12	32.57	-3.40	46.72	29.17	74.00	54.00	-7.28	S

Remark :

- (1) Measuring frequencies from 30MHz to the 10th of fundamental frequency .
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issued defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

**SGS Taiwan Ltd.** | No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 | t (886-2) 2299-3939 | f (886-2) 2298-2698 | [www.sgs.com.tw](http://www.sgs.com.tw)

### Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode: TX CH Mid  
Fundamental Frequency: 2439MHz  
Temperature : 25 °C  
Humidity : 65 %

Test Date : Jul. 20, 2006  
Test By: Danny  
Pol: Vertical

Freq. (MHz)	Ant.Pol H/V	Peak	AV	Factor (dB)	Actual Peak	Actual FS	Peak Limit	AV Limit	Margin (dB)
		Reading (dBuV)	Reading (dBuV)		FS (dBuV/m)	AV (dBuV/m)	at 3m (dBuV/m)	at 3m (dBuV/m)	
2439.0	V	82.44	--	-3.40	79.04	--	114.00	94.00	-14.96
4878.0	V	--	--			--	74.00	54.00	H
7317.0	V	46.32	33.1	9.27	55.59	42.37	74.00	54.00	-11.63
9756.0	V	--	--			--	74.00	54.00	H
12195.0	V	--	--			--	74.00	54.00	H
14634.0	V	--	--			--	74.00	54.00	H
17073.0	V	--	--			--	74.00	54.00	H
19512.0	V	--	--			--	74.00	54.00	H
21951.0	V	--	--			--	74.00	54.00	H
24390.0	V	--	--			--	74.00	54.00	H
4874.0	V	55.04	35.14	6.59	61.63	41.73	74.00	54.00	-12.27
									S

Remark :

- (1) Measuring frequencies from 30MHz to the 10th of fundamental frequency。
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issued defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode: TX CH Mid Test Date : Jul. 20, 2006  
 Fundamental Frequency: 2439MHz Test By: Danny  
 Temperature : 25°C Pol: Horizontal  
 Humidity : 65%

Freq. (MHz)	Ant.	Pol.	Peak	AV	Factor	Actual	Actual	Peak Limit	AV Limit		
			Reading	Reading		Peak FS (dBuV/m)	AV FS (dBuV/m)	at 3m (dBuV/m)	at 3m (dBuV/m)	Margin (dB)	
H/V	(dBuV)	(dBuV)	(dB)								
2439.0	H		94.43	--	-3.26	91.17	--	114.00	94.00	-2.83	F
4878.0	H		56.54	34.90	3.18	59.72	38.08	74.00	54.00	-15.92	S
7317.0	H		44.44	32.55	8.43	52.87	40.98	74.00	54.00	-13.02	S
9756.0	H		--	--			--	74.00	54.00		H
12195.0	H		--	--			--	74.00	54.00		H
14634.0	H		--	--			--	74.00	54.00		H
17073.0	H		--	--			--	74.00	54.00		H
19512.0	H		--	--			--	74.00	54.00		H
21951.0	H		--	--			--	74.00	54.00		H
24390.0	H		--	--			--	74.00	54.00		H

## Remark :

- (1) Measuring frequencies from 30MHz to the 10th of fundamental frequency .
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issued defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode: TX CH High  
Fundamental Frequency: 2474MHz  
Temperature : 25 °C  
Humidity : 65 %

Test Date : Jul. 20, 2006  
Test By: Danny  
Pol: Vertical

Freq. (MHz)	Ant. H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Factor (dB)	Actual		Peak Limit at 3m (dBuV/m)	AV Limit at 3m (dBuV/m)	Margin (dB)
					Peak FS (dBuV/m)	AV FS (dBuV/m)			
2474.0	V	82.44	--	-3.10	79.34	--	114.00	94.00	-14.66
4948.0	V	--	--	--	--	--	74.00	54.00	--
7422.0	V	49.4	33.44	9.63	59.03	43.07	74.00	54.00	-14.97
9896.0	V	--	--			--	74.00	54.00	
12370.0	V	--	--			--	74.00	54.00	
14844.0	V	--	--			--	74.00	54.00	
17318.0	V	--	--			--	74.00	54.00	
19792.0	V	--	--			--	74.00	54.00	
22266.0	V	--	--			--	74.00	54.00	
24740.0	V	--	--			--	74.00	54.00	
2566.5	V	48.69	--	-2.83	45.86	--	74.00	54.00	-8.14
4939.0	V	55.45	34.61	3.34	58.79	37.95	74.00	54.00	-15.21
2483.5	V	32.24	--	-3.04	29.20	--	74.00	54.00	-24.80

Remark :

- (1) Measuring frequencies from 30MHz to the 10th of fundamental frequency .
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issued defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

**Radiated Spurious Emission Measurement Result (above 1GHz)**

Operation Mode: TX CH High Test Date : Jul. 20, 2006  
Fundamental Frequency: 2474MHz Test By: Danny  
Temperature : 25°C Pol: Horizontal  
Humidity : 65%

Freq. (MHz)	Ant.Pol.	Peak	AV	Factor	Actual	Actual	Peak Limit	AV Limit	Margin	
		Reading	Reading		Peak FS (dBuV/m)	AV FS (dBuV/m)	at 3m (dBuV/m)	at 3m (dBuV/m)		
H/V	(dBuV)	(dBuV)	(dB)						(dB)	
2474.0	H	93.16	--	-3.10	90.06	--	114.00	94.00	-3.94	F
4948.0	H	--	--			--	74.00	54.00		H
7422.0	H	47.27	32.81	9.63	56.90	42.44	74.00	54.00	-11.56	H
9896.0	H	--	--			--	74.00	54.00		H
12370.0	H	--	--			--	74.00	54.00		H
14844.0	H	--	--			--	74.00	54.00		H
17318.0	H	--	--			--	74.00	54.00		H
19792.0	H	--	--			--	74.00	54.00		H
22266.0	H	--	--			--	74.00	54.00		H
24740.0	H	--	--			--	74.00	54.00		H
4939.0	H	58.18	34.82	3.34	61.52	38.16	74.00	54.00	-12.48	S
2483.5	H	37.57	--	-3.04	34.53	--	74.00	54.00	-19.47	S

Remark :

- (1) Measuring frequencies from 30MHz to the 10th of fundamental frequency .
- (2) Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB
- (3) "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- (4) Datas of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- (6) Spectrum AV mode IF B bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

## 6. 26 dB Band Width Measurement

### 6.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set ETU normal operating mode.
3. Set SPA Center Frequency = fundamental frequency, RBW, VBW = 100KHz, Span =3MHz.
4. Set SPA Max hold. Mark peak, -26dB.

### 6.2 Test SET-UP (Block Diagram of Configuration)

Same as 4.2 Radiated Emission Measurement.

### 6.3 Measurement Equipment Used:

Same as 4.2 Radiated Emission Measurement.


### 6.4 Measurement Results:

Channel	26dB Bandwidth
Channel Low	2.904MHz
Channel Mid	3.278MHz
Channel High	3.080MHz


Refer to attached data chart.

## 26 dB Band Width test Plot

*Low*




*Mid*



This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issued defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。

SGS Taiwan Ltd. | No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 | t (886-2) 2299-3939 | f (886-2) 2298-2698 | [www.sgs.com.tw](http://www.sgs.com.tw)

**High**

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification, and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. 此報告是遵循本公司訂定之通用服務條款所製作發放。請注意此條款列印於背面，將本公司之義務，免責，管轄權皆明確規範之。此報告結果除非另有說明僅對檢驗之樣品負責。本報告未經本公司書面許可，不可部份複製。