## HYUNDAI CALIBRATION & CERTIFICATION TECH. CO., LTD.



PRODUCT COMPLIANCE DIVISION SAN 136-1, AMI-RI , BUBAL-EUP, ICHEON-SI, KYOUNGKI-DO, 467-701, KOREA

TEL: +82 31 639 8518 FAX: +82 31 639 8525 www.hct.co.kr

## CERTIFICATE OF COMPLIANCE

## FCC PART 15.247 Certification

Applicant Name: Uriver Inc

3<sup>rd</sup>.,Fl.,Bogwang Bldg.,Poi-dong, 238-7 Gangnam-gu, Seoul, Korea Date of Testing: Jun.22, 2007

Test Site/Location:

HCT, San 136-1 Ami-ri, Bubal-eup, Icheon-si,

Kyungki-do, Korea

Test Report No.: HCT-R07-0606

FCC ID: UDTSP300

**APPLICANT: Uriver Inc** 

**EUT Type:** 

Tri-Band GSM Phone with Bluetooth- Prototype

Frequency range:

2402 - 2480 MHz (Bluetooth)

Max. RF Output Power:

0.47 dBm (0.001114 W)

Trade Name/Model(s):

Uriver Inc. / SP300

FCC Classification:

FCC Part 15 Frequency Hopping Spread Spectrum Transceiver

Application Type:

Certification

FCC Rule Part(s):

Part 15 subpart C 15.247

Antenna Specifications:

Manufacturer: Integrated Microsystems Technology Inc.

PART NUMBER: IMABB05 / Chip Antenna

#### **Engineering Statement:**

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT Co., Ltd. certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti- Drug Abuse Act of 1998, 21 U.S. C. 853(a)

Report prepared by

: Young-Kwan Kim

Approved by

: Keun-Ho Park

Test engineer of RF Part

Manager of RF Part

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 1 of 42
HCT-R07-010	May 10, 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



# **Table of Contents**

1. GENERAL INFORMATION	3
1.1 EUT DESCRIPTION	. 3
2. TEST METHODOLOGY	4
2.1 EUT CONFIGURATION	4
2.2 EUT EXERCISE	4
2.3 GENERAL TEST PROCEDURES	4
2.4 DESCRIPTION OF TEST MODES	4
3. INSTRUMENT CALIBRATION	5
4. FACILITIES AND ACCREDITATIONS	6
4.1 FACILITIES	6
4.2 EQUIPMENT	6
5. SETUP OF EQUIPMENT UNDER TEST	6
5.1 SETUP CONFIGURATION OF EUT	6
6. TEST RESULT	7
6.1 SUMMARY	8
6.2 PEAK POWER	8
6.3 BAND EDGES MEASUREMENT	1 8
6.3.1 BAND EDGES RADIATED MEASUREMENT	1 8
6.4 FREQUENCY SEPARATION	1 8
6.5 NUMBER OF HOPPING FREQUENCY	2 1
6.6 TIME OF OCCUPANCY (DWELL TIME)	2 3
6.7 SPURIOUS EMISSIONS	2 6
6.7.1 Conducted Spurious Emissions	2 6
6.7 .2 Radiated Spurious Emissions	2 6
6.8 POWERLINE CONDUCTED EMISSIONS	3 7
7. LIST OF TEST EQUIPMENT4	1 2

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 2 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



# 1. GENERAL INFORMATION

Company Name: Uriver Inc.

Address: 3rd., Fl., Bogwang Bldg., Poi-dong, 238-7

Gangnam-gu, Seoul, Korea

Attention: TS JEONG - Managing Director

Tel. / Fax: 82-2-3497-8432 / 82-2-579-6624

E-Mail: tsjeong@uriver.co.kr

#### 1.1 EUT DESCRIPTION

• FCC ID: UDTSP300

• EUT Type: Tri -Band GSM Phone with Bluetooth

• Trade Name: Uriver Inc.

Model(s):
 SP300

• Frequency range: 2402 – 2480 MHz (Bluetooth)

• Transmit power: 0.47 dBm (0.001114 W)

• Modulation(s): GFSK

• Antenna Specification: Manufacturer: Integrated Microsystems Technology Inc.

PART NUMBER: IMABB05 / Chip Antenna

Gain (Avg): 0 dBi]

• Frequency range: 2402 – 2480 MHz (Bluetooth)

• Application Type: Certification

• FCC Classification: FCC Part 15 Frequency Hopping Spread Spectrum Transceiver

• FCC Rule Part(s): Part 15 subpart C 15.247

• Date(s) of Tests: June 22, 2007

• Report Serial No.: HCT-R07-0606

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 3 of 42



# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4. (Version :2003) Radiated testing was performed at an antenna to EUT distance 3 meters.

## 2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### 2.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

## 2.3 GENERAL TEST PROCEDURES

#### **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

#### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

#### 2.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 4 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



# 3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 5 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



## 4. FACILITIES AND ACCREDITATIONS

#### 4.1 FACILITIES

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1,Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 6, 2006(Registration Number: 90661)

#### 4.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

# 5. SETUP OF EQUIPMENT UNDER TEST

#### **5.1 SETUP CONFIGURATION OF EUT**

See test photographs for the actual connections between EUT and support equipment.

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 6 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



# **6. TEST RESULT**

# **6.1 SUMMARY**

Company Name: Uriver Inc.

FCC ID: UDTSP300

Method/System: Frequency Hopping Spread Spectrum (FHSS)

Number of Channels: 79

FCC Part	Test Description	Test Limit	Test	Test Result	Reference	
Section(s)	•		Condition			
TRANSMITTER	TRANSMITTER MODE (Tx)					
15.247(b)(1)	PEAK POWER	< 1 Watt if > 75 non-overlapping channels used		PASS	Section 6.2	
15.247(d)	BAND EDGES MEASUREMENT	Conducted < 20dBc		PASS	Section 6.3	
15.247(a)(1)	FREQEUNCY SEPARATION / 20 dB BANDWIDTH	> 2/3 of 20 dB BW for systems with Output Power < 125mW	CONDUCTED	PASS	Section 6.4	
15.247(a)(1)(iii)	NUMBER OF CHANNELS	> 15 Channels		PASS	Section 6.5	
15.247(a)(1)(iii)	TIME OF OCCUPANCY	< 0.4 sec in 31.6 sec period		PASS	Section 6.6	
15.247(d)	Conducted Spurious Emissions	Conducted < 20dBc		PASS	Section 6.7.1	
15.205 15.209	Radiated Spurious Emissions	Radiated < 20dBc Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits)	RADIATED	PASS	Section 6.7.2	
15.207	AC CONDUCTED EMISSIONS 150kHz – 30MHz	< FCC 15.207 limits or < RSS- Gen table 2 limits	LINE CONDUCTED	PASS	Section 6.8	

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 7 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	




## **6.2 PEAK POWER**

#### LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

- 1. For systems using digital modulation in the bands of 902  $\sim$  928 MHz, 2400  $\sim$  2483.5 MHz, and 5725  $\sim$  5850 MHz: 1 watt.
- 2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

## **Test Configuration**



#### **TEST PROCEDURE**

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode. The RBW is set to 1MHz. The VBW is set to 3MHz.

#### **TEST RESULTS**

No non-compliance noted

#### **Test Data**


Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	0.47	0.001114	1	PASS
Mid	2440	0.31	0.001074		PASS
High	2480	-0.31	0.000931		PASS

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 8 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	




## **Test Plots**

## Peak Power (Low CH)



Date: 22.JUN.2007 11:36:14

## Peak Power ( Mid CH )




Title: SP300

Date: 22.JUN.2007 11:37:02

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 9 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



## Peak Power ( High CH )



Title: SP300 Date: 22.JUN.2007 11:37:56

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 10 of 42




## **6.3 BAND EDGES MEASUREMENT**

#### LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

## **Test Configuration**



#### **TEST PROCEDURE**

The spectrum analyzer is set to:

- 1. Span = 8 MHz
- 2. RBW = 100 KHz
- 3. VBW = 300 KHz
- 4. Sweep = auto


#### **TEST RESULTS**

See attached.


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 11 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



# Test Data Band Edges (CH-Low)



## Band Edges (CH-Low)



HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 12 of 42




#### 6.3.1 BAND EDGES RADIATED MEASUREMENT

#### LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

#### **Test Configuration**



#### **TEST PROCEDURE**

- 1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
- (a) PEAK: RBW = VBW = 1 MHz / Sweep = AUTO
- (b) AVERAGE: RBW = 1 MHz / VBW = 10 Hz / Sweep = AUTO
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

#### **TEST RESULTS**

Refer to attach spectrum analyzer data chart.


HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 13 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	




## **Test Data**

Band Edges (Low- CH) Polarity: Vertical

**Detector mode: Peak** 






HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 14 of 42




## Band Edges (Low- CH)

## **Polarity: Horizontal**

## **Detector mode: Peak**







HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 15 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



## Band Edges (High- CH) Polarity: Vertical

## **Detector mode: Peak**







HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 16 of 42



## Band Edges (High- CH) Polarity: Horizontal

## **Detector mode: Peak**





HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 17 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	




## **6.4 FREQUENCY SEPARATION**

## LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

## **Test Configuration**



#### **TEST PROCEDURE**

The spectrum analyzer is set to:

- 1. Span = 3 MHz
- 2. RBW = 30 KHz
- 3. VBW = 100 KHz
- 4. Sweep = auto

The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.

## **TEST RESULTS**

No non-compliance noted

#### **Test Data**


Channel Separation	20dB Bandwidth		Limit	Result
(MHz)		(KHz)	(KHz)	
	Low CH	854		
1.005	Middle CH	854	>25	Pass
	High CH	854		

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 18 of 42




## **Test Plot**

## **Measurement of Channel Separation**




# Test Plot 20 dB bandwidth (Low CH)




HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 19 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



## (Mid CH)



## (High CH)



 
 HCT PT.15.247 TEST REPORT
 FCC CERTIFICATION REPORT
 WWW.hct.co.kr

 Test Report No. HCT-R07-010
 Test Dates: May. 10 2007
 EUT Type: Tri-band GSM Phone with Bluetooth
 FCC ID: UDTSP300
 Page 20 of 42




## **6.5 NUMBER OF HOPPING FREQUENCY**

## LIMIT

According to  $\S15.247(a)(1)(ii)$ , Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

## **Test Configuration**



## **TEST PROCEDURE**

The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer was set to :

- 1. Span = the frequency band of operation (Start = 2400 MHz, Stop = 2483.5 MHz)
- 2. RBW = 300 KHz
- 3. VBW = 1 MHz
- 4. Sweep = auto

The trace was allowed to stabilize.

#### **TEST RESULTS**

No non-compliance noted


## **Test Data**

Result (No. of CH)	Limit (No. of CH)	Result
79	>75	Pass

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 21 of 42



# **Test Plot Channel Number** 2.4 GHz - 2.4835 GHz



Title: SP300 Date: 22.JUN.2007 11:50:40

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 22 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	




## **6.6 TIME OF OCCUPANCY (DWELL TIME)**

## LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

## **Test Configuration**



#### **TEST PROCEDURE**

EUT was set to transmit the longest packet type (DH5)

- 1. Span = zero span
- 2. RBW = 1 MHz
- 3. VBW = 3 MHz
- 4. Sweep = as necessary to capture the entire dwell time per channel

The marker-delta function was used to determine the dwell time.

#### **TEST RESULTS**

See the table.

#### DH 5


CH Low: 2.93 \* (1600/6)/79 \* 31.6 = 312.5 (ms) CH Mid: 2.93 \* (1600/6)/79 \* 31.6 = 312.5 (ms) CH High: 2.93 \* (1600/6)/79 \* 31.6 = 312.5 (ms)

Channel	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.93	312.5	31.6		PASS
Mid	2.93	312.5	31.6	400	PASS
High	2.93	312.5	31.6		PASS


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 23 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



# Test Plots DH 5 ( Low CH )




## (MidCH)



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 24 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



# (CH High)



Title:

SP300 22.JUN.2007 11:56:02 Date:

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 25 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	




## 6.7 SPURIOUS EMISSIONS

## 6.7.1 Conducted Spurious Emissions

#### LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

## **Test Configuration**



#### **TEST PROCEDURE**

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 300 KHz.

Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.


#### **TEST RESULTS**

No non-compliance noted


HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 26 of 42



# Test Plots (Low CH)




## (Mid CH)



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT	FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 27 of 42	
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300		



# (High CH)



Title:

SP300 22.JUN.2007 11:59:15 Date:

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 28 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



## **6.7.2 Radiated Spurious Emissions**

## LIMIT

1. 20dBc in any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed


Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 29 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	




## **Test Configuration**

## Below 30 MHz




## 30 MHz - 1 GHz



HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 30 of 42



#### Above 1 GHz



#### **TEST PROCEDURE**

- 1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 31 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



#### **TEST RESULTS**

9 kHz - 30MHz

**Operation Mode:** Normal Link

- 1. Measuring frequencies from 9 kHz to the 30MHz.
- 2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
- 3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
- 4. Limit line = specific Limits (dBuV) + Distance extrapolation factor

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 32 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



## **TEST RESULTS**

## Below 1 GHz

**Operation Mode:** Normal Link

Frequency	Reading	Ant. Factor	Cable Loss	ANT POL	Total	Limit	Margin
MHz	dBuV	dB	dB	(H/V)	dBuV/m	dBuV/m	dB
98.20	23.1	9.8	2.3	V	35.1	43.5	-8.4
97.00	22.3	9.7	2.2	V	34.2	43.5	-9.3
246.90	19.4	17.3	3.6	V	40.3	46	-5.7
389.10	16.3	16.8	4.5	V	37.7	46	-8.3
416.70	11.5	17.4	4.7	V	33.6	46	-12.4
459.20	12.4	18.5	4.9	V	35.8	46	-10.2
245.30	10.5	17.3	3.6	Η	31.4	46	-14.6
356.20	12.8	16.5	4.3	Н	33.6	46	-12.4
389.10	12.8	16.8	4.5	Н	34.2	46	-11.8
415.40	10.7	17.4	4.7	Н	32.8	46	-13.2
469.30	8.1	18.7	4.9	Н	31.7	46	-14.3
549.70	8.3	20.2	5.3	Н	33.9	46	-12.1

- 1. Measuring frequencies from 30 MHz to the 1 GHz.
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Quasi peak detector mode.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 33 of 42



## Above 1 GHz

**Operation Mode: CH Low** 

Frequency	Level	AN. CL.	ANT. POL	Total	Limit	Margin	Detect
[MHz]	[dBuV]	[dB]	[H/V]	[dBuV/m]	[dBuV/m]	[dB]	
4804.00	1.6	36.7	V	38.3	54	-15.7	AV
4804.00	2.9	36.7	Н	39.6	54	-14.4	AV
7206.00	-1.8	40.5	V	38.7	54	-15.3	AV
7206.00	-1.3	40.5	Н	39.2	54	-14.8	AV
4804.00	12.2	36.7	Н	48.9	74	-25.1	PK
N/A							
		_			_		_
_							

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
- a. Peak Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
- b. AV Setting 1 GH z- 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 34 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



**Operation Mode: CH Mid** 

Frequency	Level	AN. CL.	ANT. POL	Total	Limit	Margin	Detect
[MHz]	[dBuV]	[dB]	[H/V]	[dBuV/m]	[dBuV/m]	[dB]	
4882.00	1.0	36.9	V	37.9	54	-16.1	AV
4882.00	1.6	36.9	Н	38.5	54	-15.5	AV
7323.00	-2.6	40.7	V	38.1	54	-15.9	AV
7323.00	-1.8	40.7	Н	38.9	54	-15.1	AV
4882.00	11.1	36.7	Н	47.8	74	-26.2	PK
N/A							
			_				

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
  - a. Peak Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GH z- 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 35 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



Operation Mode: CH High

Frequency	Level	AN. CL.	ANT. POL	Total	Limit	Margin	Detect
[MHz]	[dBuV]	[dB]	[H/V]	[dBuV/m]	[dBuV/m]	[dB]	
4960.00	1.4	37.1	V	38.5	54	-15.5	AV
4960.00	3.1	37.1	Н	40.2	54	-13.8	AV
7440.00	-2.4	41.0	V	38.6	54	-15.4	AV
7440.00	-0.3	41.0	Н	40.7	54	-13.3	AV
4960.00	12.2	36.7	Н	48.9	74	-25.1	PK
N/A							

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
  - a. Peak Setting 1 GHz 26 GHz, RBW = 1 MHz, VBW = 1 MH.
  - b. AV Setting 1 GH z- 26 GHz, RBW = 1 MHz, VBW = 10 Hz.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 36 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



## **6.8 POWERLINE CONDUCTED EMISSIONS**

#### LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Evenuency Denne (MUT)	Limits (dBμV)			
Frequency Range (MHz)	Quasi-peak	Average		
0.15 to 0.50	66 to 56	56 to 46		
0.50 to 5	56	46		
5 to 30	60	50		

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

#### **Test Configuration**

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

#### **TEST PROCEDURE**

- 1. The EUT is placed on a wooden table 80 cm above the reference groundplane.
- 2. The EUT is connected via LISN to a test power supply.
- 3. The measurement results are obtained as described below:
- 4. Detectors Quasi Peak and Average Detector.

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 37 of 42
HCT-R07-010	May. 10 2007	Tri-band GSM Phone with Bluetooth	UDTSP300	



## **Test Plot**


## **Conducted emissions (Line 1)**

HCT

#### EMC TEST LAB.

EUT: SP300 Manufacturer: Operating Condition: CAMERA MODE
Test Site: SHIELD ROOM
Operator: DH.RYU Operator: DH.RYU
Test Specification: CISPR 22 CLASS B Comment:

SCAN TABLE: "CISPR 22 Voltage"
Short Description: CISPR 22 Voltage
Start Stop Step Detector Meas Start Stop Step Frequency Frequency Width 150.1 kHz 500.0 kHz 2.5 kHz Transducer Detector Meas. Time Bandw. 10.0 ms 9 kHz Bandw. MaxPeak None Average 500.0 kHz 5.0 MHz 5.0 kHz 10.0 ms 9 kHz MaxPeak None Average 5.0 MHz 30.0 MHz 5.0 kHz 10.0 ms 9 kHz MaxPeak Average



#### MEASUREMENT RESULT: "PHONE fin QP"

6/13/2007 1	0:15AM					
Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dΒμV	dB	dΒμV	dB		
0.220100	48.50	10.0	63	14.4		
0.225100	48.40	10.0	63	14.2		
0.440100	42.00	10.0	57	15.1		
0.540000	43.60	10.1	56	12.4		
0.650000	42.00	10.1	56	14.0		
0.755000	41.30	10.1	56	14.7		
7.865000	25.20	11.0	60	34.8		
7.970000	30.00	11.0	60	30.0		
8.290000	30.50	11.0	60	29.5		

Page 1/2 6/13/2007 10:15AM HCT EMC LAB

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 38 of 42



## MEASUREMENT RESULT: "PHONE\_fin AV"

6/13/2007	10:15AM					
Frequenc M	cy Level Hz dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.2201	00 37.40	10.0	53	15.4		
0.3276	00 31.90	10.0	50	17.6		
0.4401	00 32.10	10.0	47	15.0		
0.54500	00 13.40	10.1	46	32.6		
0.65500	00 29.70	10.1	46	16.3		
0.8700	00 27.10	10.1	46	18.9		
5.63000	00 12.70	10.7	50	37.3		
7.98500	00 16.30	11.0	50	33.7		
9.79000	00 13.90	11.1	50	36.1		

Page 2/2 6/13/2007 10:15AM HCT EMC LAB

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 39 of 42




## Conducted emissions (Line 2)

HCT

#### EMC TEST LAB.

EUT: SP300 Manufacturer: Operating Condition: CAMERA MODE
Test Site: SHIELD ROOM
Operator: DH.RYU
Test Specification: CISPR 22 CLASS B
Comment: N

SCAN TABLE: "CISPR 22 Voltage"
Short Description: CISPR 22 Voltage
Start Stop Step Detector Meas
Frequency Frequency Width Time
150.1 kHz 500.0 kHz 2.5 kHz MaxPeak 10.0 Detector Meas. Time IF Transducer Bandw. 10.0 ms 9 kHz Average MaxPeak 500.0 kHz 5.0 MHz 5.0 kHz 10.0 ms 9 kHz None Average MaxPeak 5.0 MHz 30.0 MHz 5.0 kHz 10.0 ms 9 kHz None Average



#### MEASUREMENT RESULT: "PHONE\_fin QP"

6/13/2007	10:18AM					
Frequenc	cy Level	Transd	Limit	Margin	Line	PE
ME	Hz dBµV	dB	dΒμV	dB		
0.22260	00 47.40	10.0	63	15.3		
0.43260	00 36.70	10.0	57	20.5		
0.44760	00 42.90	10.1	57	14.0		
0.56000	00 43.20	10.1	56	12.8		
0.89500	00 38.90	10.1	56	17.1		
1.00500	00 38.00	10.1	56	18.0		
8.16000	00 27.90	11.0	60	32.1		
8.50500	00 22.20	11.0	60	37.8		
8.60500	00 25.40	11.0	60	34.6		

Page 1/2 6/13/2007 10:18AM HCT EMC LAB

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 40 of 42



## MEASUREMENT RESULT: "PHONE\_fin AV"

6/13/2007	10:18A	M				
Frequen M	all.	evel Tra dBµV	nsd Lim dB dB		gin Li: dB	ne PE
0.2251	00 3:	2.00 1	0.0	53 20	0.6	
0.3326	00 3:	1.00 1	0.0	49 18	3.4	
0.4476	00 2	8.70 1	0.1	47 18	3.2	
0.5500	00 30	0.40 1	0.1	46 15	5.6	
0.6650	00 28	8.00 1	0.1	46 18	3.0	
0.7750	00 1	9.20 1	0.1	46 20	6.8	
8.1750	00 1	3.70 1	1.0	50 36	5.3	
16.1050	00 1	3.70 1	2.0	50 36	5.3	
24.0000	00 1	6.40 1	2.6	50 33	3.6	

Page 2/2 6/13/2007 10:18AM HCT EMC LAB

HCT PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 41 of 42



# 8. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Date	Cal Interval	Calibration Due	Serial No.
Rohde & Schwarz	ESI40/ EMI Test Receiver	11/06/2006	Annual	11/06/2007	831564103
Rohde & Schwarz	ESCI/ EMI Test Receiver	08/24/ 2006	Annual	08/24/ 2007	100033
Rohde & Schwarz	ESH2-Z5/ LISN	04/20/2007	Annual	04/20/2008	861741/013
Rohde & Schwarz	ESH3-Z6/ LISN	04/11/2007	Annual	03/16/2008	837950/023
Schwarzbeck	VULB 9160/ TRILOG Antenna	04/20/2007	Annual	04/20/2008	9160-3150
HD	MA240/ Antenna Position Tower	N/A	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	03/16/2007	Annual	03/16/2008	375.8810.352
MITEQ	AMF-60-0010 1800-35-20P	01/24/2007	Annual	01/24/2008	1200937
MITEQ	AMF-6D-01180-35-20P	02/24/2007	Annual	02/24/2008	990893
Schwarzbeck	BBHA 9120D/ Horn Antenna	03/30/2007	Annual	03/30/2008	147
Schwarzbeck	BBHA9170/ SHF-EHF Horn Antenna	03/20/2007	Annual	03/20/2008	BBHA9170342
Rohde & Schwarz	HFH2-Z2/Loop Antenna	05/11/2007	Annual	01/10/2008	881056/070
ADVANTEST	R3273/Spectrum Analyzer	05/02/2007	Annual	05/02/2008	J004821
Agilent	E4416A /Power Meter	01/22/2007	Annual	01/22/2008	GB41291412
Agilent	E7405A	10/02/2006	Annual	10/02/2007	US40240209
Weinschel	2/Attenuator	01/24/2007	Annual	01/24/2008	BR0554
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	06/28/2006	Annual	06/28/2007	1

HCT PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		
Test Report No. HCT-R07-010	Test Dates: May. 10 2007	EUT Type: Tri-band GSM Phone with Bluetooth	FCC ID: UDTSP300	Page 42 of 42