

SPECIFIC ABSORPTION RATE (SAR)

TEST REPORT

of

GPS tracker

Model Name:

GL100

Trade Name:

eLoc

FCC ID:

UDV-0809182008007

Report No.:

SH08090012S01

prepared for

SHANGHAI SIMCOM LIMITED

Build A, No. 633 JinZhong Rd., ChangNing District Shanghai, PRC China.

prepared by

Shenzhen Electronic Product Quality Testing Center

Morlab Laboratory

3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District Shenzhen 518055 P. R. China

Tel: +86 755 86130398 Fax: +86 755 86130218











NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant, it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.



GENERAL SUMMARY

Product Name	GPS tracker Development Stage Identical prototype
Standard(s)	47CFR §2.1093: Radiofrequency Radiation Exposure Evaluation: Portable Devices FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01): Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.
Conclusion	Localized Specific Absorption Rate (SAR) of this portable wireless equipment has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this test report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report. General Judgment: Pass Date of issue: Oct. 07, 2008
Comment	TX Freq. Band: 824.20 MHz-848.80 MHz RX Freq. Band: 869.20 MHz-893.80 MHz 1930.20 MHz -1989.80 MHz Antenna Character: build inside The test result only responds to the measured sample.
Teste	by: Ou Omchoo Date: 2008. 10. 8 Lou Qinchao ORLA
Checked	Zhang Jun
Approved	d by: Su Feng



Contents

1. GENERAL CONDITIONS

2. ADMINISTRATIVE DATA

- 2.1. Identification of the Responsible Testing Laboratory
- 2.2. Identification of the Responsible Testing Location(s)
- 2.3. Organization Item
- 2.4. Identification of Applicant
- 2.5. Identification of Manufacture

3. EQUIPMENT UNDER TEST (EUT)

- 3.1. Identification of the Equipment under Test
- 3.2. Identification of all used Test Sample of the Equipment under Test

4. OPERATIONAL CONDITIONS DURING TEST

- 4.1. Schematic Test Configuration
- 4.2. SAR Measurement System

5. CHARACTERISTICS OF THE TEST

- 5.1. Applicable Limit Regulations
- 5.2. Applicable Measurement Standards

6. LABORATORY ENVIRONMENT

7. 3G MEASUREMEAMENT PROCEDURE

8. TEST RESULTS

- 8.1. Dielectric Performance
- 8.2. Summary of Measurement Results
- 8.3. Conclusion

9. MEASUREMENT UNCERTAINTY

10. MAIN TEST INSTRUMENTS

This Test Report consists of the following Annexes:

Annex A: Accreditation Certificate

Annex B: Test Layout

Annex C: Sample Photographs

Annex D: Graph Test Results

Annex E: System Performance Check Data



1. GENERAL CONDITIONS

- 1.1 This report only refers to the item that has undergone the test.
- 1.2 This report standalone does not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities.
- 1.3 This document is only valid if complete; no partial reproduction can be made without written approval of Shenzhen Morlab Communications Technology Co., Ltd.
- 1.4 This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of Shenzhen Morlab Communications Technology Co., Ltd. and the Accreditation Bodies, if it applies.
- 1.5 This production is a GPS tracker no speech function.



Report No: SH08010003S01

2. Administrative Date

2.1. Identification of the Responsible Testing Laboratory

Company Name: Shenzhen Morlab Communications Technology Co.,Ltd.

Department: Testing Department

Address: 3FI, Electronic Testing Building, ShaHe Road, NanShan District,

Shenzhen, P. R. China

Telephone: +86 755 86130268 **Fax:** +86 755 86130218

Responsible Test Lab

Mr. Shu Luan Managers:

2.2. Identification of the Responsible Testing Location(s)

Company Name: Shenzhen Electronic Product Quality Testing Center Morlab

Laboratory

Address: 3FI, Electronic Testing Building, ShaHe Road, NanShan District,

Shenzhen, P. R. China

2.3. Organization Item

Morlab Report No.: SH08090012S01
Morlab Project Leader: Mr. Lou Qinchao

Morlab Responsible for

Accreditation scope:

Mr. Shu Luan

Start of Testing: 2008-9-24 End of Testing: 2008-10-6

2.4.Identification of Applicant

Company Name: SHANGHAI SIMCOM LIMITED

Address: Build A, No. 633 JinZhong Rd., ChangNing District Shanghai, PRC

China

 Contact person:
 Mr. Tang Erchang

 Telephone:
 +86 (0) 13818816267

 Fax:
 +86-021-54278901

2.5.Identification of Manufacture

Company Name: SHANGHAI SIMCOM LIMITED.

Address: Build A, No. 633 JinZhong Rd., ChangNing District Shanghai, PRC


China

 Contact person:
 Mr. Tang Erchang

 Telephone:
 +86 (0) 13818816267

 Fax:
 +86-021-54278901

Notes: This data is based on the information offered by the applicant.





3. Equipment Under Test (EUT)

3.1.Identification of the Equipment under Test

Brand Name: eLoc

Type Name: GL100

Marking Name: eLoc

Test frequency GSM 850MHz and PCS 1900MHz

Development Stage Identical prototype
Accessories Charger, Battery
Battery Model GL100(JLFV)
Battery specification 3.7V 1300mAh

General description: Antenna type Integrated

Operation mode Call established

Modulation mode GMSK

Max. Power 0.43W for GSM850MHz band

(ERP/EIRP) 0.49W for PCS1900MHz band

3.2.Identification of all used Test Sample of the Equipment under Test

EUT Code	Serial Number	Hardware Version	rdware Version Software Version IME	
#1	N.A.	V1.02	ADI 16.0	

NOTE:

- 1. The EUT consists of normal options: Charger, Lithium Battery as listed above.
- 2. Please refer to Appendix C for the photographs of the EUT. For a more detailed features description of the EUT, please refer to its User's Manual.



4 OPERATIONAL CONDITIONS DURING TEST

4.1 Schematic Test Configuration

During SAR test, EUT is in Traffic Mode (Channel Allocated) at Normal Voltage Condition. A communication link is set up with a System Simulator (SS) by air link, and a call is established.

The TCH is allocated to 128, 189 and 251 respectively in the case of GSM 850 MHz, or to 512, 661 and 810 respectively in the case of PCS 1900 MHz. The EUT is commanded to operate at maximum transmitting power.

The EUT shall use its internal transmitter. The antenna(s), battery and accessories shall be those specified by the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. If a wireless link is used, the antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the handset.

The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the handset by at least 35 dB.

4.2 SAR Measurement System

The SAR measurement system being used is the COMOSAR Test Bench, which consists of a




Figure 1. SAR Lab Test Measurement Set-up

KUKA 6-axis robot arm and controller, Antennessa probe with *no amplifier* and SAM phantom. The system is controlled remotely from a PC, which contains the software to control most of the bench devices and stores measurement data. The software also displays the data obtained from test scans,






and determines the averaged SAR values (averaging region 1 gram or 10 gram) for compliance testing. In operation, the system first does an area (2D) scan at a fixed depth within the liquid from the inside wall of the phantom. When the maximum SAR point has been found, the system will then carry out a 3D scan centered at that point to determine volume averaged SAR level.

4.2.1 Robot system specification

The robot is used to articulate the probe to programmed positions inside the phantom head to obtain the SAR readings from the DUT.





4.2.2 Probe Specification

Antennessa isotropic waterproof and low loss SAR probe

Antennessa probes are constructed with a triangular section bar in alumina. On each face, a dipole and a resistive line are printed. A Schottky diode is placed in the center of each dipole.

This probe is designed to fulfill CENELEC, IEEE and FCC recommendations for the measurement of electromagnetic fields radiated by mobile phones and base stations.

All probes are protected by waterproof and low loss girdle. The dosimetric probe has special calibration factors for each frequency and mode.

Due to the specific structure and high sensitivity of Antennessa probes, the E field evaluation needs *no amplification* between the sensors and the PC.

Technical data

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the on defined in the IEEEE and CENELEC standard. These uncoupled dipoles perform the isotropic and wideband measurements necessary to assess mobile phones SAR.

Frequency range	100 MHz - 30 GHz
Length	330 mm
Dipoles Length	4.5 mm
Maximum external diameter	8 mm
Probe tip external diameter	5 mm
Distance between dipoles and the probe tip	<2.7mm
Dipole resistance (in the connector plane)	1M to 2M
Axial isotropy in human-equivalent liquids	± 0.25 dB
Hemispherical Isotropy in human- equivalent liquids	± 0.5 dB
Linearity	± 0.5 dB
Maximum operating SAR	100 Watts/kg
Lower SAR detection threshold	0.0015 Watts/kg
Connectors	6 male wires (Hirose SR30)







Figure 2. Specification and characterization parameters of antennessa probe





4.2.3 Phantoms, Device Holder and Simulant Liquid

4.2.3.1 Sam Phantom




The SAM phantom is used to measure the SAR relative to person's exposure to electro-magnetic field radiated by mobile phones.

Technical Data

Shell thickness	2 mm +/-0.2 mm				
Filling volume	27 liters				
Dimensions	1000 mm (Length) ; 500 mm (Width) ; 200 mm (Height)				
5 molded plastic points for high precision reference Delivered with					
4 nylon screws					

For thickness control purposes, the phantom has several integrated thickness control points (see crosses on the picture below)





Position of the thickness control points

The SAM phantom is delivered with a CAD CD-ROM including the 3D data of the internal shape of the shell. These data are used by the 6 axis robot control software to define movements relative to its internal surface.

The SAM phantom also has 5 additional CAD-linked reference points to properly position the 6-axis robot (probe tip) in the phantom shell.

The SAM phantom has reference points at the center of the flat area (for measurements with dipoles) and near its mouth and ear for mobile phone positioning purposes.

The phantom is equipped with a tap for draining the liquid.

The liquid quantity necessary t fill the phantom is approximately 20 liters.


All phantoms are tested after production. The test is made on 22 different points. It is based on an ultrasonic system measurement, which allows measuring the thickness with a precision of $10\mu m$. The mould has been controlled by a certification company.

4.2.3.2 Device and Dipole Holder



The SAR value is approximatively inversely proportional to the square of the distance between the source and the internal phantom surface. For a source at 5mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of $\pm 20\%$. An accurate device positioning is therefore essential for accurate and repeatable measurements.





This positioning system allows the translating of the mobile phone along the x, y and z axis, as well as the required rotation around the phantom ear, for the 2 positions defined by standards (0° "cheek" position and 15° "tilt" position).

The correct position can be easily determined thanks to an additional tool with a pointer. The top part of the system, above the curved rail, can be fixed definitively so that subsequent adjustments just concern the angle or the x, y or z axis.

This simplifies the positioning of the acoustic output of the telephone on the cross section of the phantom, before rolling the system underneath the phantom. It also improves the accuracy and repeatability of positioning with a tolerance ≤0.65mm.

4.2.3.3 Tissue Simulating Liquids

There is no simulating liquids that can cover all frequency bands. Therefore, our system is using different liquids for the measured band as explained bellows.

The parameters of the simulating solution strongly influence the SAR values. The different normalization organizations have defined adapted solutions for the each mobile system.

GSM liquid: is made of 1-2 Propylene Glycol, de-ionized water and NaCl, reconstituting the electric properties of human tissues at 900MHz.

PCS Liquid: is made of de-ionized water, DGBE, Triton X 100 and NaCl, reconstituting the electric properties of human tissues at 1800MHz.

UMTS Liquid: is made of de-ionized water, DGBE, Triton X 100 and NaCl, reconstituting the electric properties of human tissues at 2000MHz.




Several measurement systems are available for measuring the dielectric parameters.


Antennessa has developed its own software, based on a coaxial probe. This method allows measurement of liquid permittivity between 300 MHz and 6GHz.





4.2.4 SAR measurement procedure








Channel	Left			Right				
	Cheek Tilt		Cheek		Tilt			
	Retracted	Extended	Retracted	Extended	Retracted	Extended	Retracted	Extended
Mode 1:								
High			S2(-1.4dB)	S2(-0.4dB)			S2(-2.2dB)	S2(-1.4dB)
Middle	S1(-4dB)	S1(-4dB)	S1(-1.5dB)	S1(-0.5dB)	S1(-5dB)	S1(-5dB)	S1(-2.5dB)	S1(-1.5dB)
Low			S2(-1.3dB)	S2(-0.7dB)			S2(-2.7dB)	S2(-0.6dB)
Mode 2:								
High			S2(-2.7dB)	S2(-1.1dB)				
Middle	S1(-5dB)	S1(-5dB)	S1(-2.5dB)	S1(-1dB)	S1(-6dB)	S1(-6dB)	S1(-5dB)	S1(-5dB)
Low			S2(-2.2dB)	S2(-0.8dB)				

After an area scan has been done at a fixed distance of 8mm from the surface of the phantom on the source side, a 3D scan is set up around the location of the maximum spot SAR. First, a point within the scan area is visited by the probe and a SAR reading taken at the start of testing. At the end of testing, the probe is returned to the same point and a second reading is taken. Comparison between these start and end readings enables the power drift during measurement to be assessed.

Above is the scanning procedure flow chart and table from the IEEE p1528 standard. This is the procedure for which all compliant testing should be carried out to ensure that all variations of the device position and transmission behavior are tested.

4.2.5 Validation Test Using Flat Phantom

The following procedure, recommended for performing validation tests using flat phantom is based on the procedures described in the IEEE standard P1528. Setup according to the setup diagram below:





4.2.5.1 Setting up the Box Phantom for Validation Testing

One of the main purposes of the flat part of the phantom is for validation of the system. By placing the highly-symmetric and matched reference dipole below the phantom and using the same device holder, the system can now be used to check that the probe and software are giving accurate readings.

The antennas are developed with a $\lambda_0/4$ balun, so that all calibration dipoles are totally symmetrical.

Each validation dipole is used to check the whole SAR measurement chain in its frequency band. They are especially developed to make SAR measurements near a flat SAM phantom filled with human-equivalent liquid, according to the standards.

Each dipole has been designed to be plugged in the Antennessa phone positioning system. Validation measurements are made according to the standard, as the Antennessa phone positioning system is totally metal free.





4.2.5.2 Equipments and Results of Validation TestingEquipments:

name	Type and specification		
Signal generator	SMT 06		
Directional coupler	MFR 34078		
Amplifier	BLMA 0820-6		
Deference dinale	SN 36/05 DIP C20		
Reference dipole	SN 36/05 DIP G23		

Results:

	Frequency	Date	Target value(1g)	Test value(1g)
			W/kg	W/kg
	850MHz 2008.10.05 9.5		9.5	9.94 (Body)
ſ	1900MHz	2008.10.06	39.7	37.68 (Body)

4.2.6 Measurement Procedure

The following steps are used for each test position

Establish a call with the maximum output power with a base station simulator. The connection between



the mobile phone and the base station simulator is established via air interface.

Measurement of the local E-field distribution is done with a grid of 8 to 16mm*8 to 16mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolating scheme.

Around this point, a cube of 30*30*30mm or 32*32*32mm is assessed by measuring 5 or 8*5 or 8*4 or 5mm. With these data, the peak spatial-average SAR value can be calculated.

4.2.7 Description of Interpolation/Extrapolation Scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is base on a fourth-order least square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8mm. to obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1gram requires a very fine resolution in the three-dimensional scanned data array.

5 CHARACTERISTICS OF THE TEST

5.1 Applicable Limit Regulations

47CFR §2.1093: Radiofrequency Radiation Exposure Evaluation: Portable Devices

FCC OET Bulletin 65(Edition 97-01), Supplement C(Edition 01-01): Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption



Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

They specify the measurement method for demonstration of compliance with the SAR limits for such equipments.

6 LABORATORY ENVIRONMENT

Table: The Ambient Conditions during SAR Test

Temperature	Min. =15°C, Max. =30°C			
Relative humidity	Min. =30%, Max. =70%			
Ground system resistance	<0.5Ω			
Ambient noise is checked and found very low and in compliance with requirement of standards.				
Reflection of surrounding objects is minimized and in compliance with requirement of standards.				



7 3G MEASUREMEAMENT PROCEDURE

7.1 Procedures Used To Establish Test Signal

The device was placed into a simulated call using a base station simulator in a shielded chamber. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR. SAR measurements were taken with a fully charged battery. In order to verify that the device was tested and maintained at full power, this was configured with the base station simulator. The SAR measurement software calculates a reference point at the start and end of the test to check for power drifts. If conducted power deviations of more then 5% occurred, the tests were repeated. 7.2 SAR Measurement Conditions for CDMA2000 1x.

7.2 SAR Measurement Conditions for CDMA2000 1x

These procedures were followed according to FCC "SAR Measurement Procedures for 3G Devices", June 2006.

7.2.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by "SAR Measurement Procedures for 3G Devices", June 2006. Maximum output power is verified on the High, Middle and Low channels according to procedures defined in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in "All Up" condition. 1. If the mobile station supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only. 2. Under RC1, C.S0011 Table 4.4.5.2-1 (Table.A) parameters were applied. 3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH0 and demodulation of RC 3, 4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH0 data rate Channel and 9600 bps SCH0 data rate. 4. Under RC3, C.S0011 Table 4.4.5.2-2(Table.B) was applied. 5. FCHs were configured at full rate for maximum SAR with "All Up" power control bits.

Table 1: Parameters for Max. Power for RC1

Parameter	Units	Value
Îor	dBm/1.23 MHz	-104
Pilot E _c	dΒ	-7
Traffic E _c	dВ	-7.4



Table 2: Parameters for Max. Power for RC3

Parameter	Units	Value
Îor	dBm/3.69 MHz	-99
Pilot E _c	dВ	-10
Traffic E _c	dВ	-12.4

7.2.2 Head SAR Measurement

SAR for head exposure configurations is measured in RC3 with the DUT configured to transmit at full rate using Loop back Service Option SO55. SAR for RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

7.2.3 Body SAR Measurement

SAR for body exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + SCHn) is not required when the maximum average output of each RF channel is less than ¼ dB higher than that measured with FCH only. Otherwise, SAR is measured on the maximum output channel (FCH + SCHn) with FCH at full rate and SCH0 enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels are enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts. Body SAR in RC1 is not required when the maximum average output of each channel is less than ¼dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1; with Loop back Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR for that channel in RC3.





Band		SO2	SO2	SO55	SO55	TDSO
	Channel					SO32
		RC1/1	RC3/3	RC1/1	RC3/3	RC3/3
	128	28.12	27.56	28.25	28.35	28.22
GSM850	189	28.43	28.31	28.50	28.52	28.45
	251	28.33	28.22	28.35	28.49	28.42
	512	23.48	23.55	23.45	23.58	23.46
PCS1900	661	39.57	24.00	24.01	24.06	24.17
	810	24.15	24.10	24.12	24.27	24.28

26

61



8 TEST RESULTS

8.1 Dielectric Performance

The measured 1-gram averaged SAR values of the device against the head and the body are provided in Table 1. The relative humidity and ambient temperature of test facility were 60% ~65% and 21.0 °C ~23.5°C respectively. The SAM head phantom (SN 36/05 SAM 25) was full of the head tissue simulating liquid. The depth of the body tissue was 15.0cm. The distance between the back of the device and the bottom of the flat phantom is 1.5cm. A base station simulator was used to control the device during the SAR measurement. The phone was supplied with full-charged battery for each measurement.

For body-worn measurements, the device was tested against flat phantom representing the user body. Under measurement phone was put on in the belt holder.

Cal. Due **Function** Name Model No. Series No. Cal. Date SN 36/05 DIP Dipole antenna 2008.10.05 1 year **SAR Measurement** Dipole 835 FREQ 850MHz C20 Dipole antenna 2008.10.06 1 year SN 36/05 DIP **SAR Measurement FREQ** Dipole 1900 G23 1900MHz Measurement SN 12/05 EP 2007-12-**SAR Measurement** E-field Probe 1 year

probe

Table 1: SAR Measurement Calibration

Temperature: 21.0~23.5°C, Relative Humidity: 60~65%.									
1	Frequency	Conductivity σ (S/m)							
Target value	850 MHz	55.2	0.97						
Validation value	850 MHz	54.41	1.00						
Target value	1900MHz	53.3	1.52						
Validation value	1900MHz	54.85	1.50						



8.2 Summary of Measurement Results (GSM850MHz and PCS 1900MHz Band)

Table 3: SAR Values (GSM 850 MHz Band), Measured against the body

Temperature: 21.0~23.5°C, Relative Humidity: 60~65%.						
Limit of SAR (W/kg)	1 g Average					
Limit of SAR (W/kg)	1.6					
	Measurement Result (W/kg)					
Test Case	1 g Average					
	(W/kg)					
Side, Low Channel	0.342					
Side, Mid Channel	0.303					
Side, High Channel	0.326					
Side, Middle Channel (BACK)	0.268					

Table 4: SAR Values (PCS 1900 MHz Band), Measured against the body

Temperature: 21.0~23.5°C, Relative Humidity: 60~65%.							
Limit of SAP (M/kg)	1 g Average						
Limit of SAR (W/kg)	1.6						
	Measurement Result (W/kg)						
Test Case	1 g Average						
	(W/kg)						
Side, Low Channel	0.437						
Side, Mid Channel	0.468						
Side, High Channel	0.373						
Side, Middle Channel (BACK)	0.409						

8.3 Conclusion

Peak Spatial-Average Specific Absorption Rate (SAR) of this portable wireless device has been measured in all configurations requested by the relevant standards cited in Clause 5.2 of this report. SAR values are **below** exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.



9 Measurement Uncertainties

The following table includes the uncertainty table of the IEEE 1528. The values are determined by Antennessa.

UNCERTAINTY EVALUATION FOR DEVICE SAR TEST

			LUATION			· ILOI				
a	b	С	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k	
Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi	
Measurement System										
Probe calibration	E.2.1	6.0	N	1	1	1	6.0	6.0	8	
Axial Isotropy	E.2.2	2.5	R	√3	(1-Cp) ^{1/2}	(1-Cp) ^{1/2}	1.0	1.0	∞	
Hemispherical Isotropy	E.2.2	4.0	R	√3	V Cp	V _{Cp}	1.6	1.6	∞	
Boundary effect	E.2.3	1.0	R	V3	1	1	0.6	0.6	8	
Linearity	E.2.4	5.0	R	V3	1	1	2.9	2.9	8	
System detection limits	E.2.5	1.0	R	√3	1	1	0.6	0.6	8	
Readout Electronics	E.2.6	0.5	N	1	1	1	0.5	0.5	88	
Reponse Time	E.2.7	0.2	R	√3	1	1	0.1	0.1	8	
Integration Time	E.2.8	2.0	R	√3	1	1	1.2	1.2	8	
RF ambient Conditions	E.6.1	3.0	R	V3	1	1	1.7	1.7	88	
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	√3	1	1	1.2	1.2	∞	
Probe positioning with respect to Phantom Shell	E.6.3	1.0	R	√3	1	1	0.6	0.6	∞	
Extrapolation, interpolation and integration Algoritms for Max. SAR Evaluation	E.5.2	1.5	R	√3	1	1	0.9	0.9	8	
		Tes	t sample	Related						
Test sample positioning	E.4.2.1	1.5	N	1	1	1	1.5	1.5	N-1	
Device Holder Uncertainty	E.4.1.1	5.0	N	1	1	1	5.0	5.0		
Output power Variation - SAR drift measurement	6.6.2	2.5	R	√3	1	1	1.4	1.4	8	
Phantom and Tissue Parameters										
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	4.0	R	√3	1	1	2.3	2.3	8	
Liquid conductivity - deviation from target value	E.3.2	1.6	R	√3	0.64	0.43	0.6	0.4	8	



Liquid conductivity - measurement uncertainty	E.3.3	2.5	N	1	0.64	0.43	1.6	1.1	М
Liquid permitivity - deviation from target value	E.3.2	2.9	R	√3	0.6	0.49	1.0	0.8	8
Liquid permitivity - measurement uncertainty	E.3.3	2.5	N	1	0.6	0.49	1.5	1.2	М
Combined Standard Uncertainty			RSS				9.5	9.4	
Expanded Uncertainty (95% Confidence interval)			k				18.6	18.4	





UNCERTAINTY FOR SYSTEM PERFORMANCE CHECK

а	b	С	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k	
Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi	
Measurement System										
Probe calibration	E.2.1	6.0	N	1	1	1	6.0	6.0	∞	
Axial Isotropy	E.2.2	2.5	R	√3	(1-Cp) ^{1/2}	(1-Cp) ^{1/2}	1.0	1.0	∞	
Hemispherical Isotropy	E.2.2	4.0	R	V3	V _{Cp}	√ Cp	1.6	1.6	∞	
Boundary effect	E.2.3	1.0	R	V3	1	1	0.6	0.6	∞	
Linearity	E.2.4	5.0	R	V3	1	1	2.9	2.9	∞	
System detection limits	E.2.5	1.0	R	V3	1	1	0.6	0.6	·	
Readout Electronics	E.2.6	0.5	N	1	1	1	0.5	0.5		
Reponse Time	E.2.7	0.2	R	V3	1	1	0.1	0.1	∞	
Integration Time	E.2.8	2.0	R	V3	1	1	1.2	1.2	∞	
RF ambient Conditions	E.6.1	3.0	R	V3	1	1	1.7	1.7	∞	
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	√3	1	1	1.2	1.2	00	
Probe positioning with respect to Phantom Shell	E.6.3	1.0	R	√3	1	1	0.6	0.6	00	
Extrapolation, interpolation and integration Algoritms for Max. SAR Evaluation	E.5.2	1.5	R	√3	1	1	0.9	0.9	8	
			Dipe	ole						
Dipole axis to liquid Distance	8,E.4.2	1.0	N	√3	1	1	0.6	0.6	N-1	
Input power and SAR drift measurement	8,6.6.2	2.5	R	√3	1	1	1.4	1.4	8	
Phantom and Tissue Parameters										
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	4.0	R	√3	1	1	2.3	2.3	8	
Liquid conductivity - deviation from target value	E.3.2	1.6	R	√3	0.64	0.43	0.6	0.4	00	
Liquid conductivity - measurement uncertainty	E.3.3	2.5	N	1	0.64	0.43	1.6	1.1	М	



Liquid permitivity - deviation from target value	E.3.2	2.9	R	√3	0.6	0.49	1.0	0.8	8
Liquid permitivity - measurement uncertainty	E.3.3	2.5	N	1	0.6	0.49	1.5	1.2	М
Combined Standard Uncertainty			RSS				8.0	7.9	
Expanded Uncertainty (95% Confidence interval)			k				15.6	15.4	





10 MAIN TEST INSTRUMENTS

Function	Name	Model No.	Series No.	Cal. Due Date
General	Desktop Computer	Pentium IV 2.4GHz	X1023533	2009-07-30
General	SAR measurement software	OpenSAR V2.0.1e	1	2009-07-30
	Vector Network Analyzer	ZVB 8	100154	2009-09-26
	PC 3.5 Calibration Kit	ZV-Z32	100356	2009-09-26
	Test Cable	ZV-Z13	100152	2009-07-15
Liquid mixing and calibration	Constant temperature cultivating cabinet	DNP-9272	L-504468	2009-08-01
	Liquid thermometer	Testo 106-T1	/	2009-07-21
	Electric scale	YP20KN	/	2009-08-26
	Magnetic stirring machine	90-1B	/	2009-11-09
And calib	oration probe, beaker, test tube, inj	ector, calibration bottles,	2009-07-30	
	Dipole antenna FREQ 850MHz	Dipole 835	SN 36/05 DIP C20	2008-10-05
	Dipole antenna FREQ 1900MHz	Dipole 1900	SN 36/05 DIP G23	2008-10-06
	Power amplifier (Freq.: 0.8- 2.0GHz)	BLMA 0820-6	056060A	2009-11-27
	Directional coupler (Freq.: 0.5- 2.0GHz)	MFR 34078	CPL-5220-20-SMA- 79	2009-09-24
SAR	Signal generator	SMT 06	101836	2009-09-26
Measurement	Power meter	NRVD	101311	2009-09-25
	Multi meter	2000	1062728	2009-09-19
	Robot	KCP2 Std.ed05	00171	2009-10-01
	Measurement probe	E-field Probe	SN 12/05 EP 61	2008-12-26
	Flat Phantom	1	SN 36/05 SAM 25	2009-10-01
	Test table	1	SN 35/05 TABP13	2009-10-01
	Supporter (Holder)	1	SN 45/04 MSH09	2009-10-01





ANNEX A

of

Shenzhen Morlab Communications Technology Co., Ltd.

CONFORMANCE TEST REPORT FOR HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

REPORT NO: SH08090012S01

SHANGHAI SIMCOM LIMITED

GPS tracker

Accreditation Certificate











China National Accreditation Service for Conformity Assessment

LABORATORY ACCREDITATION CERTIFICATE

(No. CNAS L1659)

China National Accreditation Service for Conformity Assessment has accredited

Shenzhen Electronic Product Quality Testing Center (CQCS Testing Co. Ltd.)

Electronic Testing Building Wenguang Road, Shahe West, Xili Town, Nanshan

District, Shenzhen, Guangdong, China

to ISO/IEC 17025:1999 General Requirements for the Competence of Testing and Calibration Laboratories(CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing and calibration.

The scope of accreditation is detailed in the attached schedule bearing the same accreditation number as above. The schedule forms an integral part of this certificate.

Date of Issue: 2007-01-17
Date of Expiry: 2009-10-08

Date of Initial Accreditation: 1999-08-03

有多年

Signed on behalf of China National Accreditation Service for Conformity Assessment

China National Accreditation Service for Conformity Assessment(CNAS) is authorized by Certification and Accreditation Administration of the People's Republic of China (CNCA) to operate the national accreditation systems for conformity assessment. CNAS is the signatory to International Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (ILAC MRA), and the signatory to Asia Pacific Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (APLAC MRA).





ANNEX B

of

Shenzhen Morlab Communications Technology Co.,Ltd.

CONFORMANCE TEST REPORT FOR HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

REPORT NO: SH08090012S01

SHANGHAI SIMCOM LIMITED

GPS tracker

Type Name: GL100

Hardware Version: V1.02 Software Version: ADI 16.0

TEST LAYOUT











Figure B.1 COMOSAR Test Bench Test Layout




Figure B.2 Depth of Simulating Liquid in SAM Flat (Body) Phantom






Figure B.3EUT Body Position(FRONT)



Figure B.4EUT Body Position(BACK)





ANNEX C

of

Shenzhen Morlab Communications Technology Co.,Ltd.

CONFORMANCE TEST REPORT FOR HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

REPORT NO: SH08090012S01

SHANGHAI SIMCOM LIMITED GPS tracker

Type Name: GL100

Hardware Version: V1.02 Software Version: ADI 16.0

Sample Photographs












Photograph of the Equipment under Test









1.2 Inside


















ANNEX D

of

Shenzhen Morlab Communications Technology Co.,Ltd.

CONFORMANCE TEST REPORT FOR HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

REPORT NO: SH08090012S01

SHANGHAI SIMCOM LIMITED

GPS tracker

Type Name: GL100


Hardware Version: V1.02
Software Version: ADI 16.0

Graph Test Results














SAR Test GSM 850 Body (Low Channel)

System / software:	COMOSAR / OpenSAR	Modn. Duty Cycle:	1: 4
	v2.0.1e		
Date:	2008-10-5	Input Power Level:	28.5dBm
Project Name:	SH08090012S01	DUT Battery Model/No:	GL100(JLFV)
Ambient Temperature:	21.5°C	Probe Serial Number:	SN 12/05 EP 61
Device Under Test:	GL100	Simulating Liquid:	850 MHz BODY tissue
Relative Humidity:	60%	Relative Permittivity:	54.51
Phantom name:	Flat	Conductivity:	0.98
Phantom S/No:	SN 36/05 SAM 25	Liquid Temperature:	21.6°C
Phantom File:	sam_direct_droit2_surf	Max SAR X-axis	6.00 mm
	8mm.txt	Location:	
Device Position:	850_Body	Max SAR Y-axis	21.00 mm
		Location:	
Antenna	Integrated	SAR 1g:	0.342206 W/kg
Configuration:			
Test Frequency:	850 MHz	SAR 10g:	0.230896 W/kg
Comment:	1	SAR Drift during Scan:	3.09 %
Type of Modulation:	GMSK	Extrapolation:	poly4
ConvF	33.38,31.28,28.37	Liquid Parameter	1






Page 40 of 50






SAR Test GSM 850 Body (Middle Channel)

~		 ay (miaale onaliici)	,
System / software:	COMOSAR / OpenSAR	Modn. Duty Cycle:	1: 4
	v2.0.1e		
Date:	2008-10-5	Input Power Level:	28.7dBm
Project Name:	SH08090012S01	DUT Battery Model/No:	GL100(JLFV)
Ambient Temperature:	21.5°C	Probe Serial Number:	SN 12/05 EP 61
Device Under Test:	GL100	Simulating Liquid:	850 MHz BODY tissue
Relative Humidity:	60%	Relative Permittivity:	54.41
Phantom name:	Flat	Conductivity:	1.00
Phantom S/No:	SN 36/05 SAM 25	Liquid Temperature:	21.6°C
Phantom File:	sam_direct_droit2_surf	Max SAR X-axis	6.00 mm
	8mm.txt	Location:	
Device Position:	850_Body	Max SAR Y-axis	18.00 mm
		Location:	
Antenna	Integrated	SAR 1g:	0.302653W/kg
Configuration:			
Test Frequency:	850 MHz	SAR 10g:	0.202573 W/kg
Comment:	1	SAR Drift during Scan:	-1.62 %
Type of Modulation:	GMSK	Extrapolation:	poly4
ConvF	33.38,31.28,28.37	Liquid Parameter	1












SAR Test GSM 850 Body (High Channel)

	· · · · · · · · · · · · · · · · · · ·	 oay (ingin onanion)	
System / software:	COMOSAR / OpenSAR	Modn. Duty Cycle:	1: 4
	v2.0.1e		
Date:	2008-10-5	Input Power Level:	28.6dBm
Project Name:	SH08090012S01	DUT Battery Model/No:	GL100(JLFV)
Ambient Temperature:	21.5°C	Probe Serial Number:	SN 12/05 EP 61
Device Under Test:	GL100	Simulating Liquid:	800 MHz BODY tissue
Relative Humidity:	60%	Relative Permittivity:	54.3
Phantom name:	Flat	Conductivity:	1.01
Phantom S/No:	SN 36/05 SAM 25	Liquid Temperature:	21.6°C
Phantom File:	sam_direct_droit2_surf	Max SAR X-axis	5.00 mm
	8mm.txt	Location:	
Device Position:	850_Body	Max SAR Y-axis	18.00 mm
		Location:	
Antenna	Integrated	SAR 1g:	0.325622 W/kg
Configuration:			
Test Frequency:	850 MHz	SAR 10g:	0.217036 W/kg
Comment:	1	SAR Drift during Scan:	-1.72 %
Type of Modulation:	GMSK	Extrapolation:	poly4
ConvF	33.38,31.28,28.37	Liquid Parameter	1






Page 42 of 50







SAR Test GSM 850 Body (Middle Channel, BACK)

0 7 11 1	Test down ood bod	יעי	miaaio onaiiioi, br	· · · · · ·
System / software:	COMOSAR / OpenSAR		Modn. Duty Cycle:	1: 4
	v2.0.1e			
Date:	2008-10-5		Input Power Level:	28.8dBm
Project Name:	SH08090012S01		DUT Battery Model/No:	GL100(JLFV)
Ambient Temperature:	21.5°C		Probe Serial Number:	SN 12/05 EP 61
Device Under Test:	GL100		Simulating Liquid:	850 MHz BODY tissue
Relative Humidity:	60%		Relative Permittivity:	54.41
Phantom name:	Flat		Conductivity:	1.00
Phantom S/No:	SN 36/05 SAM 25		Liquid Temperature:	21.6°C
Phantom File:	sam_direct_droit2_surf		Max SAR X-axis	-7.00 mm
	8mm.txt		Location:	
Device Position:	850_Body		Max SAR Y-axis	18.00 mm
			Location:	
Antenna	Integrated		SAR 1g:	0.268339 W/kg
Configuration:				
Test Frequency:	850 MHz		SAR 10g:	0.101082 W/kg
Comment:	1		SAR Drift during Scan:	-2.42 %
Type of Modulation:	GSMK		Extrapolation:	poly4
ConvF	33.38,31.28,28.37		Liquid Parameter	1






Page 43 of 50






SAR Test PCS 1900 Body (Low Channel)

System / software:	COMOSAR / OpenSAR	Modn. Duty Cycle:	1: 4
	v2.0.1e		
Date:	2008-10-6	Input Power Level:	23.7dBm
Project Name:	SH08090012S01	DUT Battery Model/No:	GL100(JLFV)
Ambient Temperature:	21.5°C	Probe Serial Number:	SN 12/05 EP 61
Device Under Test:	GL100	Simulating Liquid:	1900 MHz BODY tissue
Relative Humidity:	60%	Relative Permittivity:	54.83
Phantom name:	Flat	Conductivity:	1.48
Phantom S/No:	SN 36/05 SAM 25	Liquid Temperature:	21.6°C
Phantom File:	sam_direct_droit2_surf	Max SAR X-axis	2.00 mm
	8mm.txt	Location:	
Device Position:	1900_Body	Max SAR Y-axis	00.00 mm
		Location:	
Antenna	Integrated	SAR 1g:	0.437302 W/kg
Configuration:			
Test Frequency:	1900 MHz	SAR 10g:	0.266580 W/kg
Comment:	1	SAR Drift during Scan:	3.09 %
Type of Modulation:	GMSK	Extrapolation:	poly4
ConvF	39.76,36.97,33.37	Liquid Parameter	1






Page 44 of 50







SAR Test PCS 1900 Body (Middle Channel)

System / software:	COMOSAR / OpenSAR	Modn. Duty Cycle:	1: 4
-	v2.0.1e		
Date:	2008-10-6	Input Power Level:	24.3dBm
Project Name:	SH08090012S01	DUT Battery Model/No:	GL100(JLFV)
Ambient Temperature:	21.5°C	Probe Serial Number:	SN 12/05 EP 61
Device Under Test:	GL100	Simulating Liquid:	1900 MHz BODY tissue
Relative Humidity:	60%	Relative Permittivity:	54.85
Phantom name:	Flat	Conductivity:	1.50
Phantom S/No:	SN 36/05 SAM 25	Liquid Temperature:	21.6°C
Phantom File:	sam_direct_droit2_surf	Max SAR X-axis	5.00 mm
	8mm.txt	Location:	
Device Position:	1900_Body	Max SAR Y-axis	1.00 mm
		Location:	
Antenna	Integrated	SAR 1g:	0.467877 W/kg
Configuration:			
Test Frequency:	1900 MHz	SAR 10g:	0.285542 W/kg
Comment:	1	SAR Drift during Scan:	-1.62 %
Type of Modulation:	GMSK	Extrapolation:	poly4
ConvF	39.76,36.97,33.37	Liquid Parameter	1






Page 45 of 50






SAR Test PCS 1900 Body (High Channel)

		_	oay (mgm onamon)	
System / software:	COMOSAR / OpenSAR		Modn. Duty Cycle:	1: 4
	v2.0.1e			
Date:	2008-10-6		Input Power Level:	24.5dBm
Project Name:	SH08090012S01		DUT Battery Model/No:	GL100(JLFV)
Ambient Temperature:	21.5°C		Probe Serial Number:	SN 12/05 EP 61
Device Under Test:	GL100		Simulating Liquid:	1900 MHz BODY tissue
Relative Humidity:	60%		Relative Permittivity:	54.82
Phantom name:	Flat		Conductivity:	1.53
Phantom S/No:	SN 36/05 SAM 25		Liquid Temperature:	21.6°C
Phantom File:	sam_direct_droit2_surf		Max SAR X-axis	1.00 mm
	8mm.txt		Location:	
Device Position:	1900_Body		Max SAR Y-axis	0.00 mm
			Location:	
Antenna	Integrated		SAR 1g:	0.372701 W/kg
Configuration:				
Test Frequency:	1900 MHz		SAR 10g:	0.223807 W/kg
Comment:	1		SAR Drift during Scan:	-1.72 %
Type of Modulation:	GMSK		Extrapolation:	poly4
ConvF	39.76,36.97,33.37		Liquid Parameter	1






Page 46 of 50






SAR Test PCS 1900 Body (Middle Channel, BACK)

		 Third Charmon, Br	•
System / software:	COMOSAR / OpenSAR	Modn. Duty Cycle:	1: 4
	v2.0.1e		
Date:	2008-10-6	Input Power Level:	24.3dBm
Project Name:	SH08090012S01	DUT Battery Model/No:	GL100(JLFV)
Ambient Temperature:	21.5°C	Probe Serial Number:	SN 12/05 EP 61
Device Under Test:	GL100	Simulating Liquid:	1900 MHz BODY tissue
Relative Humidity:	60%	Relative Permittivity:	54.85
Phantom name:	Flat	Conductivity:	1.50
Phantom S/No:	SN 36/05 SAM 25	Liquid Temperature:	21.6°C
Phantom File:	sam_direct_droit2_surf	Max SAR X-axis	0.00 mm
	8mm.txt	Location:	
Device Position:	1900_Body	Max SAR Y-axis	0.00 mm
		Location:	
Antenna	Integrated	SAR 1g:	0.409053 W/kg
Configuration:			
Test Frequency:	1900 MHz	SAR 10g:	0.250595W/kg
Comment:	1	SAR Drift during Scan:	-2.42 %
Type of Modulation:	SMSK	Extrapolation:	poly4
ConvF	39.76,36.97,33.37	Liquid Parameter	1





Page 47 of 50





ANNEX E

of

Shenzhen Morlab Communications Technology Co.,Ltd.

CONFORMANCE TEST REPORT FOR HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

REPORT NO: SH08090012S01

SHANGHAI SIMCOM LIMITED GPS tracker

Type Name: GL100

Hardware Version: V1.02 Software Version: ADI 16.0

System Performance Check Data













System Check GSM 850 Body

	Cyclom chicak com coc zou,					
System / software:	COMOSAR / OpenSAR	Modn. Duty Cycle:	1: 4			
	v2.0.1e					
Date:	2008-10-5	Input Power Level:	24dBm			
Project Name:	SH08090012S01	DUT Battery Model/No:	1			
Ambient Temperature:	21.5°C	Probe Serial Number:	SN 12/05 EP 61			
Device Under Test:	Dipole Antenna (100W)	Simulating Liquid:	850 MHz BODY tissue			
Relative Humidity:	60%	Relative Permittivity:	54.41			
Phantom name:	Validation plane	Conductivity:	1.00			
Phantom S/No:	SN 36/05 SAM 25	Liquid Temperature:	21.6°C			
Phantom File:	sam_direct_droit2_surf	Max SAR X-axis	-1.00 mm			
	8mm.txt	Location:				
Device Position:	850_Body	Max SAR Y-axis	-1.00 mm			
		Location:				
Antenna	1	SAR 1g:	9.945581 W/kg			
Configuration:	1					
Test Frequency:	850 MHz	SAR 10g:	6.760474W/kg			
Comment:	1	SAR Drift during Scan:	-0.47 %			
Type of Modulation:	GMSK	Extrapolation:	poly4			
ConvF	33.38,31.28,28.37	Liquid Parameter	1			






Page 49 of 50






System Check PCS 1900 Body

	- ,	CO 1000 Body	T
System / software:	COMOSAR / OpenSAR	Modn. Duty Cycle:	1: 4
	v2.0.1e		
Date:	2008-10-6	Input Power Level:	24dBm
Project Name:	SH08090012S01	DUT Battery Model/No:	1
Ambient Temperature:	21.5°C	Probe Serial Number:	SN 12/05 EP 61
Device Under Test:	Dipole Antenna (100W)	Simulating Liquid:	1900 MHz BODY tissue
Relative Humidity:	60%	Relative Permittivity:	54.85
Phantom name:	Validation plane	Conductivity:	1.50
Phantom S/No:	SN 36/05 SAM 25	Liquid Temperature:	21.6°C
Phantom File:	sam_direct_droit2_surf	Max SAR X-axis	0.00 mm
	8mm.txt	Location:	
Device Position:	1900_Body	Max SAR Y-axis	0.00 mm
		Location:	
Antenna	1	SAR 1g:	37.688026W/kg
Configuration:	/		
Test Frequency:	1900 MHz	SAR 10g:	16.943329 W/kg
Comment:	1	SAR Drift during Scan:	-0.47 %
Type of Modulation:	GMSK	Extrapolation:	poly4
ConvF	39.76,36.97,33.37	Liquid Parameter	1





Page 50 of 50