



A D T

# RF EXPOSURE REPORT

**REPORT NO.:** SA991116C06

**MODEL NO.:** MR12

**FCC ID:** UDX-60013010

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Meraki Inc.

**ADDRESS:** 660 Alabama St, 4th floor, San Francisco, CA  
94110

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou  
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	NA	Dec. 09, 2010



A D T

## 1. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

## 2. MPE CALCULATION FORMULA

$$Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

## 3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



A D T

#### 4. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

MODULATION MODE	FREQUENCY BAND (MHz)	MAX CONDUCTED POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
802.11b	2412-2462	24.1	6	20	0.204	1
802.11g	2412-2462	29.9	6	20	0.774	1
802.11n (20MHz)	2412-2462	29.9	3	20	0.388	1
802.11n (40MHz)	2422-2452	28.5	3	20	0.281	1

**NOTE:**

(802.11 b/g): Directional gain =3dBi+10log(2)=6dBi