


6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2412 MHz / Chain 3




Date: 21.MAY.2016 19:35:22

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2437 MHz / Chain 3




Date: 21.MAY.2016 16:41:46

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 4




Date: 21.MAY.2016 19:48:13

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2437 MHz / Chain 4




Date: 21.MAY.2016 16:42:00

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 1




Date: 21.MAY.2016 20:00:53

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 1




Date: 21.MAY.2016 13:40:14

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 2




Date: 21.MAY.2016 19:55:59

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2452 MHz / Chain 2




Date: 21.MAY.2016 13:36:55

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 3




Date: 21.MAY.2016 19:55:36

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 3




Date: 21.MAY.2016 13:43:43

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 4




Date: 21.MAY.2016 19:55:08

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2452 MHz / Chain 4



Date: 21.MAY.2016 13:36:22

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2412 MHz / Chain 1




Date: 21.MAY.2016 20:26:39

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 1



Date: 21.MAY.2016 17:24:49

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2462 MHz / Chain 2




Date: 21.MAY.2016 20:38:07

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 2



Date: 21.MAY.2016 17:25:04

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 3




Date: 21.MAY.2016 20:34:02

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 3



Date: 21.MAY.2016 17:25:19

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 4




Date: 21.MAY.2016 20:34:15

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 4




Date: 21.MAY.2016 17:25:37

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 1




Date: 21.MAY.2016 20:56:30

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 1




Date: 21.MAY.2016 13:13:47

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 2




Date: 21.MAY.2016 20:56:43

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 2




Date: 21.MAY.2016 13:13:31

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 3




Date: 21.MAY.2016 20:56:55

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 3




Date: 21.MAY.2016 13:13:11

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 4



Date: 21.MAY.2016 20:57:09


99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2437 MHz / Chain 4



Date: 21.MAY.2016 13:11:24


For Mode 3:

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 1




Date: 21.MAY.2016 18:30:13

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2462 MHz / Chain 1



Date: 21.MAY.2016 16:10:44

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 2




Date: 21.MAY.2016 18:29:59

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 2



Date: 21.MAY.2016 16:07:40

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2462 MHz / Chain 3




Date: 21.MAY.2016 18:55:23

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2462 MHz / Chain 3




Date: 21.MAY.2016 16:11:13

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2462 MHz / Chain 4




Date: 21.MAY.2016 18:54:39

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2462 MHz / Chain 4




Date: 21.MAY.2016 16:11:26

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 1




Date: 21.MAY.2016 19:22:49

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 1




Date: 21.MAY.2016 15:14:38

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz / Chain 2




Date: 21.MAY.2016 19:01:02

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 2




Date: 21.MAY.2016 15:14:23

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2452 MHz / Chain 3




Date: 21.MAY.2016 19:27:15

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2452 MHz / Chain 3




Date: 21.MAY.2016 15:16:26

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2452 MHz / Chain 4




Date: 21.MAY.2016 19:27:28

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2452 MHz / Chain 4




Date: 21.MAY.2016 15:16:40

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2412 MHz / Chain 1




Date: 21.MAY.2016 19:32:55

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2412 MHz / Chain 1




Date: 21.MAY.2016 16:32:35

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2437 MHz / Chain 2




Date: 21.MAY.2016 19:41:02

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2437 MHz / Chain 2




Date: 21.MAY.2016 16:46:35

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 3




Date: 21.MAY.2016 19:45:33

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 3




Date: 21.MAY.2016 16:37:59

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 4




Date: 21.MAY.2016 19:45:05

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 4




Date: 21.MAY.2016 16:38:13

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 1




Date: 21.MAY.2016 19:53:33

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 1




Date: 21.MAY.2016 14:43:50

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 2




Date: 21.MAY.2016 19:53:53

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 2




Date: 21.MAY.2016 14:46:47

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 3




Date: 21.MAY.2016 19:54:09

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 3




Date: 21.MAY.2016 14:46:35

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 4




Date: 21.MAY.2016 20:02:23

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 4



Date: 21.MAY.2016 14:46:20

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2462 MHz / Chain 1




Date: 21.MAY.2016 20:36:36

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 1




Date: 21.MAY.2016 17:44:16

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2462 MHz / Chain 2




Date: 21.MAY.2016 20:36:45

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 2



Date: 21.MAY.2016 17:44:00

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2412 MHz / Chain 3




Date: 21.MAY.2016 20:28:26

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2412 MHz / Chain 3



Date: 21.MAY.2016 17:40:11

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2412 MHz / Chain 4




Date: 21.MAY.2016 20:28:38

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 4




Date: 21.MAY.2016 17:43:30

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2422 MHz / Chain 1




Date: 21.MAY.2016 20:43:21

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2422 MHz / Chain 1




Date: 21.MAY.2016 13:18:51

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2422 MHz / Chain 2




Date: 21.MAY.2016 20:43:35

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2437 MHz / Chain 2




Date: 21.MAY.2016 12:49:14

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2422 MHz / Chain 3




Date: 21.MAY.2016 20:43:48

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2437 MHz / Chain 3




Date: 21.MAY.2016 12:48:24

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2422 MHz / Chain 4



Date: 21.MAY.2016 20:44:03


99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2437 MHz / Chain 4



Date: 21.MAY.2016 12:48:09

For Mode 4:

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2462 MHz / Chain 1




Date: 21.MAY.2016 18:56:44

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2462 MHz / Chain 1



Date: 21.MAY.2016 16:13:30

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 2




Date: 21.MAY.2016 18:33:53

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 2



Date: 21.MAY.2016 16:14:41

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 3




Date: 21.MAY.2016 18:32:53

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 3



Date: 21.MAY.2016 16:14:54

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 4




Date: 21.MAY.2016 18:32:03

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2412 MHz / Chain 4




Date: 21.MAY.2016 16:16:37

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz / Chain 1




Date: 21.MAY.2016 18:59:51

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 1



Date: 21.MAY.2016 15:25:27

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2452 MHz / Chain 2




Date: 21.MAY.2016 19:25:32

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 2




Date: 21.MAY.2016 15:26:17


6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 3



99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz / Chain 3




6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2422 MHz / Chain 4




Date: 21.MAY.2016 18:58:37

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2452 MHz / Chain 4



Date: 21.MAY.2016 15:22:53

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2412 MHz / Chain 1




Date: 21.MAY.2016 19:37:20

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2412 MHz / Chain 1



Date: 21.MAY.2016 16:53:37

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2412 MHz / Chain 2




Date: 21.MAY.2016 19:37:34

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 2



Date: 21.MAY.2016 16:50:05

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 3




Date: 21.MAY.2016 19:50:28

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 3



Date: 21.MAY.2016 16:51:46

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 4




Date: 21.MAY.2016 19:50:11

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT20 / 2462 MHz / Chain 4




Date: 21.MAY.2016 16:49:35

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 1




Date: 21.MAY.2016 19:53:02

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2422 MHz / Chain 1



Date: 21.MAY.2016 14:55:02

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 2




Date: 21.MAY.2016 20:06:25

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 2




Date: 21.MAY.2016 14:52:20

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 3




Date: 21.MAY.2016 20:06:42

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 3




Date: 21.MAY.2016 14:52:33

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 4




Date: 21.MAY.2016 20:06:53

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss2 VHT40 / 2437 MHz / Chain 4



Date: 21.MAY.2016 14:52:46

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 1




Date: 21.MAY.2016 20:30:33

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 1



Date: 21.MAY.2016 17:45:15

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2462 MHz / Chain 2




Date: 21.MAY.2016 20:40:22

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 2



Date: 21.MAY.2016 17:45:29

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 3




Date: 21.MAY.2016 20:31:03

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 3




Date: 21.MAY.2016 17:45:41

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2412 MHz / Chain 4




Date: 21.MAY.2016 20:29:50

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT20 / 2437 MHz / Chain 4




Date: 21.MAY.2016 17:45:57

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2422 MHz / Chain 1




Date: 21.MAY.2016 20:42:06

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2422 MHz / Chain 1




Date: 21.MAY.2016 12:03:47

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2422 MHz / Chain 2




Date: 21.MAY.2016 20:42:30

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 2



Date: 21.MAY.2016 12:09:38

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2437 MHz / Chain 3




Date: 21.MAY.2016 20:52:26

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 3




Date: 21.MAY.2016 12:09:16

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2437 MHz / Chain 4



Date: 21.MAY.2016 20:52:38

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss3 VHT40 / 2452 MHz / Chain 4




Date: 21.MAY.2016 12:09:00

<For Radio 3 Mode>


For Mode 5:

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz / Chain 5




Date: 24.MAY.2016 10:26:31

99% Occupied Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz / Chain 5




Date: 24.MAY.2016 10:42:03

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz / Chain 5




Date: 24.MAY.2016 10:28:18

99% Occupied Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 5




Date: 24.MAY.2016 10:39:25

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 5




Date: 24.MAY.2016 10:29:22

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 2437 MHz / Chain 5



Date: 24.MAY.2016 10:37:09

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2437 MHz / Chain 5



Date: 24.MAY.2016 10:30:49

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 2452 MHz / Chain 5



Date: 24.MAY.2016 10:33:18

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

<For Non-beamforming Mode>

The EUT was programmed to be in continuously transmitting mode.

<For Beamforming Mode>

The EUT was programmed to be in beamforming transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	Normal Link
Test Date	May 20, 2016		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	Normal Link
Test Mode	Mode 6		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	37.76	32.30	40.00	-7.70	40.85	0.26	20.76	29.57	200	125	QP	HORIZONTAL
2	96.93	32.82	43.50	-10.68	45.22	0.67	16.30	29.37	123	136	QP	HORIZONTAL
3	207.51	30.69	43.50	-12.81	42.14	1.16	16.28	28.89	302	199	QP	HORIZONTAL
4	241.46	30.79	46.00	-15.21	40.55	1.29	18.03	29.08	308	137	QP	HORIZONTAL
5	499.48	36.85	46.00	-9.15	40.37	2.04	23.90	29.46	129	163	QP	HORIZONTAL
6	886.51	37.08	46.00	-8.92	34.89	2.94	27.42	28.17	208	196	QP	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	37.76	36.48	40.00	-3.52	45.03	0.26	20.76	29.57	220	157 QP	VERTICAL
2	45.52	35.82	40.00	-4.18	48.56	0.33	16.48	29.55	226	189 QP	VERTICAL
3	52.31	35.46	40.00	-4.54	50.64	0.40	13.95	29.53	145	201 QP	VERTICAL
4	125.06	34.93	43.50	-8.57	45.09	0.82	18.25	29.23	122	196 QP	VERTICAL
5	151.25	35.30	43.50	-8.20	46.71	0.92	16.76	29.09	266	174 QP	VERTICAL
6	164.83	35.65	43.50	-7.85	47.54	0.99	16.15	29.03	241	146 QP	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

<For Radio 1 Non-beamforming Mode>


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.96	45.05	54.00	-8.95	40.73	6.02	32.82	34.52	316	235	Average	HORIZONTAL
2	4823.98	50.81	74.00	-23.19	46.49	6.02	32.82	34.52	316	235	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4823.94	46.96	54.00	-7.04	42.64	6.02	32.82	34.52	187	256 Average	VERTICAL
2	4824.02	51.65	74.00	-22.35	47.33	6.02	32.82	34.52	187	256 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.96	49.51	54.00	-4.49	45.09	6.02	32.91	34.51	336	301	Average	HORIZONTAL
2	4874.16	53.47	74.00	-20.53	49.05	6.02	32.91	34.51	336	301	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4873.90	53.72	74.00	-20.28	49.30	6.02	32.91	34.51	34	305	Peak
2	4873.98	50.07	54.00	-3.93	45.65	6.02	32.91	34.51	34	305	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4923.92	48.51	74.00	-25.49	44.00	6.01	32.99	34.49	319	153	Peak	HORIZONTAL
2	4924.00	40.59	54.00	-13.41	36.08	6.01	32.99	34.49	319	153	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4924.00	50.24	74.00	-23.76	45.73	6.01	32.99	34.49	38	320	Peak
2	4924.00	44.16	54.00	-9.84	39.65	6.01	32.99	34.49	38	320	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4822.08	35.69	54.00	-18.31	29.81	7.58	32.82	34.52	24	169	Average	HORIZONTAL
2	4823.80	48.62	74.00	-25.38	42.74	7.58	32.82	34.52	24	169	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	Limit	Level	Loss	Factor	Factor	deg	cm	
1	4818.24	48.99	74.00	-25.01	43.11	7.58	32.82	34.52	262	169	Peak
2	4821.96	36.77	54.00	-17.23	30.89	7.58	32.82	34.52	262	169	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4871.80	35.40	54.00	-18.60	29.40	7.60	32.91	34.51	134	196	Average	HORIZONTAL
2	4883.44	48.70	74.00	-25.30	42.67	7.60	32.93	34.50	134	196	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4871.24	48.31	74.00	-25.69	42.31	7.60	32.91	34.51	171	202	Peak
2	4872.08	35.65	54.00	-18.35	29.65	7.60	32.91	34.51	171	202	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4918.80	35.12	54.00	-18.88	29.03	7.61	32.97	34.49	129	164	Average	HORIZONTAL
2	4922.28	48.79	74.00	-25.21	42.70	7.61	32.97	34.49	129	164	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4918.72	48.33	74.00	-25.67	42.24	7.61	32.97	34.49	181	152	Peak
2	4920.68	35.05	54.00	-18.95	28.96	7.61	32.97	34.49	181	152	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4820.64	35.09	54.00	-18.91	29.21	7.58	32.82	34.52	153	171	Average	HORIZONTAL
2	4831.72	48.06	74.00	-25.94	42.16	7.58	32.84	34.52	153	171	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4824.96	34.86	54.00	-19.14	28.98	7.58	32.82	34.52	196	155	Average
2	4828.72	48.31	74.00	-25.69	42.41	7.58	32.84	34.52	196	155	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4870.20	36.04	54.00	-17.96	30.04	7.60	32.91	34.51	164	173	Average	HORIZONTAL
2	4875.56	48.73	74.00	-25.27	42.73	7.60	32.91	34.51	164	173	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4873.24	35.07	54.00	-18.93	29.07	7.60	32.91	34.51	199	240	Average
2	4875.52	48.89	74.00	-25.11	42.89	7.60	32.91	34.51	199	240	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4920.04	35.17	54.00	-18.83	29.08	7.61	32.97	34.49	243	209	Average	HORIZONTAL
2	4928.84	49.00	74.00	-25.00	42.88	7.62	32.99	34.49	243	209	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4917.16	35.15	54.00	-18.85	29.06	7.61	32.97	34.49	190	195	Average
2	4933.16	48.45	74.00	-25.55	42.33	7.62	32.99	34.49	190	195	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4842.76	48.02	74.00	-25.98	42.09	7.59	32.86	34.52	224	186	Peak	HORIZONTAL
2	4849.40	35.00	54.00	-19.00	29.06	7.59	32.86	34.51	224	186	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4844.08	35.11	54.00	-18.89	29.18	7.59	32.86	34.52	188	164	Average
2	4850.60	48.01	74.00	-25.99	42.07	7.59	32.86	34.51	188	164	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4875.04	34.90	54.00	-19.10	28.90	7.60	32.91	34.51	221	182	Average	HORIZONTAL
2	4878.08	47.82	74.00	-26.18	41.81	7.60	32.91	34.50	221	182	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4865.72	48.12	74.00	-25.88	42.16	7.59	32.88	34.51	265	166 Peak	VERTICAL
2	4875.08	34.91	54.00	-19.09	28.91	7.60	32.91	34.51	265	166 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4908.64	47.81	74.00	-26.19	41.75	7.61	32.95	34.50	310	237	Peak	HORIZONTAL
2	4908.72	34.98	54.00	-19.02	28.92	7.61	32.95	34.50	310	237	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4903.24	48.34	74.00	-25.66	42.28	7.61	32.95	34.50	268	216 Peak	VERTICAL
2	4906.92	34.93	54.00	-19.07	28.87	7.61	32.95	34.50	268	216 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	cm	deg	
1	4827.52	35.41	54.00	-18.59	29.02	7.08	34.21	34.90	155	226	Average
2	4827.72	48.15	74.00	-25.85	41.76	7.08	34.21	34.90	155	226	Peak


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4828.08	35.45	54.00	-18.55	29.06	7.08	34.21	34.90	170	113	Average
2	4830.92	48.71	74.00	-25.29	42.32	7.08	34.21	34.90	170	113	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	cm	deg	
1	4865.64	35.91	54.00	-18.09	29.38	7.14	34.29	34.90	163	79	Average
2	4876.60	48.70	74.00	-25.30	42.08	7.18	34.34	34.90	163	79	Peak


Vertical



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4866.32	35.69	54.00	-18.31	29.16	7.14	34.29	34.90	148	307	Average
2	4872.00	48.71	74.00	-25.29	42.09	7.18	34.34	34.90	148	307	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4923.08	36.03	54.00	-17.97	29.19	7.28	34.46	34.90	167	306	Average	HORIZONTAL
2	4932.16	49.13	74.00	-24.87	42.22	7.31	34.50	34.90	167	306	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4921.12	36.52	54.00	-17.48	29.68	7.28	34.46	34.90	157	113	Average
2	4933.40	49.27	74.00	-24.73	42.36	7.31	34.50	34.90	157	113	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4845.20	47.70	74.00	-26.30	41.24	7.11	34.25	34.90	143	165	Peak	HORIZONTAL
2	4852.28	35.48	54.00	-18.52	29.02	7.11	34.25	34.90	143	165	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4844.44	48.86	74.00	-25.14	42.40	7.11	34.25	34.90	167	336	Peak
2	4853.32	35.54	54.00	-18.46	29.01	7.14	34.29	34.90	167	336	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4865.32	35.88	54.00	-18.12	29.35	7.14	34.29	34.90	180	282	Average	HORIZONTAL
2	4881.80	49.00	74.00	-25.00	42.31	7.21	34.38	34.90	180	282	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	cm	deg	
1	4872.96	35.99	54.00	-18.01	29.37	7.18	34.34	34.90	117	64	Average
2	4877.96	49.29	74.00	-24.71	42.67	7.18	34.34	34.90	117	64	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4904.36	47.96	74.00	-26.04	41.20	7.24	34.42	34.90	201	74 Peak	HORIZONTAL
2	4912.28	35.85	54.00	-18.15	29.01	7.28	34.46	34.90	201	74 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	cm	deg	
1	4907.00	48.66	74.00	-25.34	41.90	7.24	34.42	34.90	157	86	Peak
2	4910.04	36.03	54.00	-17.97	29.19	7.28	34.46	34.90	157	86	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4823.91	55.37	74.00	-18.63	45.05	10.29	33.11	33.08	212	221 Peak	HORIZONTAL
2	4823.95	50.60	54.00	-3.40	40.28	10.29	33.11	33.08	212	221 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4823.93	57.27	74.00	-16.73	46.95	10.29	33.11	33.08	238	327 Peak	VERTICAL
2	4824.02	53.62	54.00	-0.38	43.30	10.29	33.11	33.08	238	327 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.98	51.99	54.00	-2.01	41.56	10.28	33.23	33.08	273	240 Average	HORIZONTAL
2	4873.99	55.90	74.00	-18.10	45.47	10.28	33.23	33.08	273	240 Peak	HORIZONTAL
3	7310.51	44.24	54.00	-9.76	29.20	12.42	36.09	33.47	171	243 Average	HORIZONTAL
4	7310.51	56.90	74.00	-17.10	41.86	12.42	36.09	33.47	171	243 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.98	57.06	74.00	-16.94	46.63	10.28	33.23	33.08	283	220 Peak	VERTICAL
2	4874.00	53.59	54.00	-0.41	43.16	10.28	33.23	33.08	283	220 Average	VERTICAL
3	7308.96	56.67	74.00	-17.33	41.63	12.42	36.09	33.47	236	89 Peak	VERTICAL
4	7315.58	44.26	54.00	-9.74	29.22	12.42	36.09	33.47	236	89 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.90	53.44	74.00	-20.56	42.88	10.28	33.35	33.07	200	225 Peak	HORIZONTAL
2	4923.97	47.29	54.00	-6.71	36.73	10.28	33.35	33.07	200	225 Average	HORIZONTAL
3	7385.54	55.99	74.00	-18.01	40.88	12.33	36.27	33.49	175	271 Peak	HORIZONTAL
4	7387.34	43.41	54.00	-10.59	28.30	12.33	36.27	33.49	175	271 Average	HORIZONTAL


Vertical



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.98	53.55	54.00	-0.45	42.99	10.28	33.35	33.07	300	219 Average	VERTICAL
2	4924.12	57.33	74.00	-16.67	46.77	10.28	33.35	33.07	300	219 Peak	VERTICAL
3	7383.98	55.98	74.00	-18.02	40.87	12.33	36.27	33.49	214	49 Peak	VERTICAL
4	7386.91	44.35	54.00	-9.65	29.24	12.33	36.27	33.49	214	49 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4820.72	50.44	74.00	-23.56	44.56	7.58	32.82	34.52	104	160	Peak
2	4821.40	37.76	54.00	-16.24	31.88	7.58	32.82	34.52	104	160	Average


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	4821.08	50.84	74.00	-23.16	44.96	7.58	32.82	34.52	121	164 Peak	VERTICAL
2	4822.24	38.15	54.00	-15.85	32.27	7.58	32.82	34.52	121	164 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4872.32	49.33	74.00	-24.67	43.33	7.60	32.91	34.51	100	185	Peak	HORIZONTAL
2	4873.76	37.06	54.00	-16.94	31.06	7.60	32.91	34.51	100	185	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4872.40	37.85	54.00	-16.15	31.85	7.60	32.91	34.51	122	194	Average	VERTICAL
2	4873.04	50.44	74.00	-23.56	44.44	7.60	32.91	34.51	122	194	Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4922.16	49.32	74.00	-24.68	43.23	7.61	32.97	34.49	106	166	Peak	HORIZONTAL
2	4922.24	37.40	54.00	-16.60	31.31	7.61	32.97	34.49	106	166	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	4921.64	50.05	74.00	-23.95	43.96	7.61	32.97	34.49	124	165 Peak	VERTICAL
2	4922.92	37.74	54.00	-16.26	31.65	7.61	32.97	34.49	124	165 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4821.72	51.37	74.00	-22.63	45.49	7.58	32.82	34.52	107	154	Peak	HORIZONTAL
2	4821.76	37.48	54.00	-16.52	31.60	7.58	32.82	34.52	107	154	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4821.56	37.22	54.00	-16.78	31.34	7.58	32.82	34.52	116	165 Average	VERTICAL
2	4823.00	49.04	74.00	-24.96	43.16	7.58	32.82	34.52	116	165 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4871.00	48.00	74.00	-26.00	42.00	7.60	32.91	34.51	109	175	Peak	HORIZONTAL
2	4872.56	36.45	54.00	-17.55	30.45	7.60	32.91	34.51	109	175	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4872.68	37.25	54.00	-16.75	31.25	7.60	32.91	34.51	126	178	Average
2	4873.68	50.52	74.00	-23.48	44.52	7.60	32.91	34.51	126	178	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	Limit	Level	Loss	Factor	Factor	deg	cm		
1	4922.36	49.48	74.00	-24.52	43.39	7.61	32.97	34.49	100	167	Peak	HORIZONTAL
2	4922.72	36.43	54.00	-17.57	30.34	7.61	32.97	34.49	100	167	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4922.64	48.97	74.00	-25.03	42.88	7.61	32.97	34.49	127	170	Peak
2	4922.72	36.83	54.00	-17.17	30.74	7.61	32.97	34.49	127	170	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4850.48	47.99	74.00	-26.01	42.05	7.59	32.86	34.51	126	160	Peak
2	4851.84	34.77	54.00	-19.23	28.83	7.59	32.86	34.51	126	160	Average


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4844.36	35.18	54.00	-18.82	29.25	7.59	32.86	34.52	137	164	Average
2	4853.00	47.55	74.00	-26.45	41.59	7.59	32.88	34.51	137	164	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4872.92	35.51	54.00	-18.49	29.51	7.60	32.91	34.51	107	174	Average	HORIZONTAL
2	4874.24	49.29	74.00	-24.71	43.29	7.60	32.91	34.51	107	174	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4873.68	36.17	54.00	-17.83	30.17	7.60	32.91	34.51	115	188	Average
2	4874.36	49.28	74.00	-24.72	43.28	7.60	32.91	34.51	115	188	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4903.56	48.57	74.00	-25.43	42.51	7.61	32.95	34.50	128	165 Peak	HORIZONTAL
2	4906.12	35.07	54.00	-18.93	29.01	7.61	32.95	34.50	128	165 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4903.68	35.95	54.00	-18.05	29.89	7.61	32.95	34.50	110	169	Average	VERTICAL
2	4907.84	48.06	74.00	-25.94	42.00	7.61	32.95	34.50	110	169	Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4823.57	32.65	54.00	-21.35	29.13	7.48	32.58	36.54	150	59 Average	HORIZONTAL
2	4824.03	45.21	74.00	-28.79	41.69	7.48	32.58	36.54	150	59 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4821.28	32.58	54.00	-21.42	29.06	7.48	32.58	36.54	150	237	Average
2	4836.50	45.58	74.00	-28.42	42.01	7.50	32.61	36.54	150	237	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4871.08	31.84	54.00	-22.16	28.13	7.56	32.68	36.53	150	37 Average	HORIZONTAL
2	4877.48	45.25	74.00	-28.75	41.54	7.56	32.68	36.53	150	37 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4872.70	46.05	74.00	-27.95	42.34	7.56	32.68	36.53	150	212 Peak	VERTICAL
2	4876.79	32.45	54.00	-21.55	28.74	7.56	32.68	36.53	150	212 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4922.91	44.49	74.00	-29.51	40.64	7.63	32.75	36.53	150	51 Peak	HORIZONTAL
2	4928.54	31.53	54.00	-22.47	27.63	7.65	32.78	36.53	150	51 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4922.64	30.44	54.00	-23.56	26.59	7.63	32.75	36.53	150	115	Average
2	4923.36	44.70	74.00	-29.30	40.85	7.63	32.75	36.53	150	115	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBUV/m	dBUV/m	Limit	Level	Loss	Factor	Factor	cm	deg	
1	4842.41	32.37	54.00	-21.63	28.76	7.52	32.63	36.54	150	28 Average	HORIZONTAL
2	4845.56	45.96	74.00	-28.04	42.34	7.52	32.63	36.53	150	28 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4839.24	32.39	54.00	-21.61	28.78	7.52	32.63	36.54	150	238 Average	VERTICAL
2	4848.38	45.58	74.00	-28.42	41.96	7.52	32.63	36.53	150	238 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4874.58	45.22	74.00	-28.78	41.51	7.56	32.68	36.53	150	86 Peak	HORIZONTAL
2	4876.56	32.08	54.00	-21.92	28.37	7.56	32.68	36.53	150	86 Average	HORIZONTAL


Vertical



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4870.83	45.32	74.00	-28.68	41.61	7.56	32.68	36.53	150	219 Peak	VERTICAL
2	4870.86	32.17	54.00	-21.83	28.46	7.56	32.68	36.53	150	219 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4900.76	31.58	54.00	-22.42	27.77	7.61	32.73	36.53	150	44 Average	HORIZONTAL
2	4905.11	44.35	74.00	-29.65	40.54	7.61	32.73	36.53	150	44 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4900.96	45.34	74.00	-28.66	41.53	7.61	32.73	36.53	150	294 Peak	VERTICAL
2	4903.28	31.83	54.00	-22.17	28.02	7.61	32.73	36.53	150	294 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3215.14	44.29	74.00	-29.71	45.23	5.94	29.80	36.68	227	15 Peak	HORIZONTAL
2	3216.33	38.44	54.00	-15.56	39.38	5.94	29.80	36.68	227	15 Average	HORIZONTAL
3	4823.88	48.29	74.00	-25.71	44.77	7.48	32.58	36.54	227	15 Peak	HORIZONTAL
4	4823.98	42.89	54.00	-11.11	39.37	7.48	32.58	36.54	227	15 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3215.25	50.43	74.00	-23.57	51.37	5.94	29.80	36.68	228	98 Peak	VERTICAL
2	3215.33	48.00	54.00	-6.00	48.94	5.94	29.80	36.68	228	98 Average	VERTICAL
3	4823.90	48.59	74.00	-25.41	45.07	7.48	32.58	36.54	228	98 Peak	VERTICAL
4	4824.00	42.83	54.00	-11.17	39.31	7.48	32.58	36.54	228	98 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3249.28	33.96	54.00	-20.04	34.75	6.00	29.88	36.67	100	117 Average	HORIZONTAL
2	3249.30	41.94	74.00	-32.06	42.73	6.00	29.88	36.67	100	117 Peak	HORIZONTAL
3	4873.75	47.68	74.00	-26.32	43.97	7.56	32.68	36.53	231	231 Peak	HORIZONTAL
4	4873.92	40.52	54.00	-13.48	36.81	7.56	32.68	36.53	231	231 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3249.28	44.68	74.00	-29.32	45.47	6.00	29.88	36.67	135	349 Peak	VERTICAL
2	3249.32	39.76	54.00	-14.24	40.55	6.00	29.88	36.67	135	349 Average	VERTICAL
3	4873.99	41.30	54.00	-12.70	37.59	7.56	32.68	36.53	297	103 Average	VERTICAL
4	4874.06	47.93	74.00	-26.07	44.22	7.56	32.68	36.53	297	103 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3282.34	41.61	74.00	-32.39	42.30	6.04	29.94	36.67	128	360 Peak	HORIZONTAL
2	3282.60	33.01	54.00	-20.99	33.70	6.04	29.94	36.67	128	360 Average	HORIZONTAL
3	4923.94	50.24	74.00	-23.76	46.34	7.65	32.78	36.53	270	232 Peak	HORIZONTAL
4	4923.99	45.43	54.00	-8.57	41.53	7.65	32.78	36.53	270	232 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3282.68	29.01	54.00	-24.99	29.70	6.04	29.94	36.67	100	60 Average	VERTICAL
2	3283.21	39.94	74.00	-34.06	40.63	6.04	29.94	36.67	100	60 Peak	VERTICAL
3	4923.96	45.92	54.00	-8.08	42.02	7.65	32.78	36.53	292	98 Average	VERTICAL
4	4924.01	50.44	74.00	-23.56	46.54	7.65	32.78	36.53	292	98 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3215.97	38.31	54.00	-15.69	39.25	5.94	29.80	36.68	103	334 Average	HORIZONTAL
2	3216.08	43.75	74.00	-30.25	44.69	5.94	29.80	36.68	103	334 Peak	HORIZONTAL
3	4823.79	30.01	54.00	-23.99	26.49	7.48	32.58	36.54	122	209 Average	HORIZONTAL
4	4824.68	43.82	74.00	-30.18	40.30	7.48	32.58	36.54	122	209 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3215.96	46.78	54.00	-7.22	47.72	5.94	29.80	36.68	148	339 Average	VERTICAL
2	3216.00	49.56	74.00	-24.44	50.50	5.94	29.80	36.68	148	339 Peak	VERTICAL
3	4823.56	30.93	54.00	-23.07	27.41	7.48	32.58	36.54	113	161 Average	VERTICAL
4	4823.92	43.63	74.00	-30.37	40.11	7.48	32.58	36.54	113	161 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3249.35	43.03	74.00	-30.97	43.82	6.00	29.88	36.67	100	116 Peak	HORIZONTAL
2	3249.36	35.90	54.00	-18.10	36.69	6.00	29.88	36.67	100	116 Average	HORIZONTAL
3	4873.16	44.20	74.00	-29.80	40.49	7.56	32.68	36.53	135	260 Peak	HORIZONTAL
4	4873.61	32.21	54.00	-21.79	28.50	7.56	32.68	36.53	135	260 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3249.25	46.11	74.00	-27.89	46.90	6.00	29.88	36.67	141	350 Peak	VERTICAL
2	3249.34	41.67	54.00	-12.33	42.46	6.00	29.88	36.67	141	350 Average	VERTICAL
3	4873.19	45.13	74.00	-28.87	41.42	7.56	32.68	36.53	115	58 Peak	VERTICAL
4	4873.63	32.37	54.00	-21.63	28.66	7.56	32.68	36.53	115	58 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3282.44	40.44	74.00	-33.56	41.13	6.04	29.94	36.67	100	111 Peak	HORIZONTAL
2	3282.63	29.79	54.00	-24.21	30.48	6.04	29.94	36.67	100	111 Average	HORIZONTAL
3	4923.02	31.89	54.00	-22.11	28.04	7.63	32.75	36.53	128	176 Average	HORIZONTAL
4	4924.50	45.12	74.00	-28.88	41.22	7.65	32.78	36.53	128	176 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3282.62	33.66	54.00	-20.34	34.35	6.04	29.94	36.67	129	360 Average	VERTICAL
2	3282.78	42.42	74.00	-31.58	43.11	6.04	29.94	36.67	129	360 Peak	VERTICAL
3	4923.79	33.01	54.00	-20.99	29.11	7.65	32.78	36.53	154	117 Average	VERTICAL
4	4923.79	45.54	74.00	-28.46	41.64	7.65	32.78	36.53	154	117 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3215.88	44.30	74.00	-29.70	45.24	5.94	29.80	36.68	100	333 Peak	HORIZONTAL
2	3216.00	38.86	54.00	-15.14	39.80	5.94	29.80	36.68	100	333 Average	HORIZONTAL
3	4823.14	30.55	54.00	-23.45	27.03	7.48	32.58	36.54	173	97 Average	HORIZONTAL
4	4823.37	43.59	74.00	-30.41	40.07	7.48	32.58	36.54	173	97 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3216.00	46.87	54.00	-7.13	47.81	5.94	29.80	36.68	129	339 Average	VERTICAL
2	3216.02	49.81	74.00	-24.19	50.75	5.94	29.80	36.68	129	339 Peak	VERTICAL
3	4823.44	30.63	54.00	-23.37	27.11	7.48	32.58	36.54	146	204 Average	VERTICAL
4	4824.11	43.83	74.00	-30.17	40.31	7.48	32.58	36.54	146	204 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3249.27	35.80	54.00	-18.20	36.59	6.00	29.88	36.67	100	116 Average	HORIZONTAL
2	3249.29	43.24	74.00	-30.76	44.03	6.00	29.88	36.67	100	116 Peak	HORIZONTAL
3	4873.00	31.74	54.00	-22.26	28.03	7.56	32.68	36.53	125	168 Average	HORIZONTAL
4	4873.50	45.19	74.00	-28.81	41.48	7.56	32.68	36.53	125	168 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3249.31	42.18	54.00	-11.82	42.97	6.00	29.88	36.67	141	349 Average	VERTICAL
2	3249.38	46.35	74.00	-27.65	47.14	6.00	29.88	36.67	141	349 Peak	VERTICAL
3	4873.53	32.37	54.00	-21.63	28.66	7.56	32.68	36.53	113	148 Average	VERTICAL
4	4873.54	45.47	74.00	-28.53	41.76	7.56	32.68	36.53	113	148 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3282.13	35.23	54.00	-18.77	35.92	6.04	29.94	36.67	114	112 Average	HORIZONTAL
2	3282.13	41.23	74.00	-32.77	41.92	6.04	29.94	36.67	114	112 Peak	HORIZONTAL
3	4823.39	42.79	74.00	-31.21	39.27	7.48	32.58	36.54	114	112 Peak	HORIZONTAL
4	4824.17	30.12	54.00	-23.88	26.60	7.48	32.58	36.54	114	112 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3282.11	33.53	54.00	-20.47	34.22	6.04	29.94	36.67	129	176 Average	VERTICAL
2	3282.22	47.53	74.00	-26.47	48.22	6.04	29.94	36.67	129	176 Peak	VERTICAL
3	4823.15	30.01	54.00	-23.99	26.49	7.48	32.58	36.54	129	176 Average	VERTICAL
4	4824.60	43.53	74.00	-30.47	40.01	7.48	32.58	36.54	129	176 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3229.35	36.19	54.00	-17.81	37.06	5.97	29.84	36.68	102	333 Average	HORIZONTAL
2	3229.42	43.17	74.00	-30.83	44.04	5.97	29.84	36.68	102	333 Peak	HORIZONTAL
3	4843.35	30.51	54.00	-23.49	26.90	7.52	32.63	36.54	115	29 Average	HORIZONTAL
4	4844.12	43.90	74.00	-30.10	40.29	7.52	32.63	36.54	115	29 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3229.30	44.14	54.00	-9.86	45.01	5.97	29.84	36.68	143	339 Average	VERTICAL
2	3229.32	47.65	74.00	-26.35	48.52	5.97	29.84	36.68	143	339 Peak	VERTICAL
3	4843.28	30.56	54.00	-23.44	26.95	7.52	32.63	36.54	104	332 Average	VERTICAL
4	4844.18	43.50	74.00	-30.50	39.89	7.52	32.63	36.54	104	332 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3249.18	42.07	74.00	-31.93	42.86	6.00	29.88	36.67	100	116 Peak	HORIZONTAL
2	3249.31	35.19	54.00	-18.81	35.98	6.00	29.88	36.67	100	116 Average	HORIZONTAL
3	4873.75	31.18	54.00	-22.82	27.47	7.56	32.68	36.53	136	278 Average	HORIZONTAL
4	4874.67	43.71	74.00	-30.29	40.00	7.56	32.68	36.53	136	278 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3249.23	45.17	74.00	-28.83	45.96	6.00	29.88	36.67	138	349 Peak	VERTICAL
2	3249.35	40.92	54.00	-13.08	41.71	6.00	29.88	36.67	138	349 Average	VERTICAL
3	4868.92	45.15	74.00	-28.85	41.44	7.56	32.68	36.53	139	68 Peak	VERTICAL
4	4873.76	31.47	54.00	-22.53	27.76	7.56	32.68	36.53	139	68 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3269.22	41.74	74.00	-32.26	42.47	6.02	29.92	36.67	115	117 Peak	HORIZONTAL
2	3269.30	33.15	54.00	-20.85	33.88	6.02	29.92	36.67	115	117 Average	HORIZONTAL
3	4903.58	31.27	54.00	-22.73	27.46	7.61	32.73	36.53	136	354 Average	HORIZONTAL
4	4904.31	43.71	74.00	-30.29	39.90	7.61	32.73	36.53	136	354 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	3269.28	37.77	54.00	-16.23	38.50	6.02	29.92	36.67	100	350 Average	VERTICAL
2	3269.36	43.77	74.00	-30.23	44.50	6.02	29.92	36.67	100	350 Peak	VERTICAL
3	4903.31	45.67	74.00	-28.33	41.86	7.61	32.73	36.53	127	105 Peak	VERTICAL
4	4903.83	32.05	54.00	-21.95	28.24	7.61	32.73	36.53	127	105 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4823.04	43.93	74.00	-30.07	40.41	7.48	32.58	36.54	158	223 Peak	HORIZONTAL
2	4824.64	30.39	54.00	-23.61	26.87	7.48	32.58	36.54	158	223 Average	HORIZONTAL
3	5000.00	42.49	54.00	-11.51	38.36	7.75	32.90	36.52	211	140 Average	HORIZONTAL
4	5000.02	49.97	74.00	-24.03	45.84	7.75	32.90	36.52	211	140 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4823.18	30.48	54.00	-23.52	26.96	7.48	32.58	36.54	154	294 Average	VERTICAL
2	4823.98	43.03	74.00	-30.97	39.51	7.48	32.58	36.54	154	294 Peak	VERTICAL
3	5000.00	45.27	54.00	-8.73	41.14	7.75	32.90	36.52	257	98 Average	VERTICAL
4	5000.00	50.84	74.00	-23.16	46.71	7.75	32.90	36.52	257	98 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preampl	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.03	43.88	74.00	-30.12	40.17	7.56	32.68	36.53	185	310 Peak	HORIZONTAL
2	4874.50	31.16	54.00	-22.84	27.45	7.56	32.68	36.53	185	310 Average	HORIZONTAL
3	4999.96	53.45	74.00	-20.55	49.32	7.75	32.90	36.52	300	182 Peak	HORIZONTAL
4	4999.97	48.76	54.00	-5.24	44.63	7.75	32.90	36.52	300	182 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.48	31.01	54.00	-22.99	27.30	7.56	32.68	36.53	171	66 Average	VERTICAL
2	4874.17	43.76	74.00	-30.24	40.05	7.56	32.68	36.53	171	66 Peak	VERTICAL
3	4999.98	47.81	54.00	-6.19	43.68	7.75	32.90	36.52	241	97 Average	VERTICAL
4	5000.06	52.19	74.00	-21.81	48.06	7.75	32.90	36.52	241	97 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss4 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.16	31.95	54.00	-22.05	28.10	7.63	32.75	36.53	197	196 Average	HORIZONTAL
2	4924.64	45.26	74.00	-28.74	41.36	7.65	32.78	36.53	197	196 Peak	HORIZONTAL
3	5000.01	43.58	54.00	-10.42	39.45	7.75	32.90	36.52	238	140 Average	HORIZONTAL
4	5000.17	50.82	74.00	-23.18	46.69	7.75	32.90	36.52	238	140 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.30	45.42	74.00	-28.58	41.57	7.63	32.75	36.53	132	78 Peak	VERTICAL
2	4923.80	32.57	54.00	-21.43	28.67	7.65	32.78	36.53	132	78 Average	VERTICAL
3	5000.00	52.18	74.00	-21.82	48.05	7.75	32.90	36.52	246	97 Peak	VERTICAL
4	5000.02	47.83	54.00	-6.17	43.70	7.75	32.90	36.52	246	97 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4843.35	43.44	74.00	-30.56	39.83	7.52	32.63	36.54	207	260	Peak
2	4843.73	31.41	54.00	-22.59	27.80	7.52	32.63	36.54	207	260	Average
3	4999.98	48.62	54.00	-5.38	44.49	7.75	32.90	36.52	298	165	Average
4	5000.03	53.90	74.00	-20.10	49.77	7.75	32.90	36.52	298	165	Peak


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4843.64	31.10	54.00	-22.90	27.49	7.52	32.63	36.54	181	188 Average	VERTICAL
2	4843.92	43.70	74.00	-30.30	40.09	7.52	32.63	36.54	181	188 Peak	VERTICAL
3	4999.99	48.12	54.00	-5.88	43.99	7.75	32.90	36.52	246	96 Average	VERTICAL
4	4999.99	52.32	74.00	-21.68	48.19	7.75	32.90	36.52	246	96 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4874.50	43.49	74.00	-30.51	39.78	7.56	32.68	36.53	206	101 Peak	HORIZONTAL
2	4874.78	31.27	54.00	-22.73	27.56	7.56	32.68	36.53	206	101 Average	HORIZONTAL
3	4999.99	49.14	54.00	-4.86	45.01	7.75	32.90	36.52	300	182 Average	HORIZONTAL
4	5000.02	53.58	74.00	-20.42	49.45	7.75	32.90	36.52	300	182 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.17	45.04	74.00	-28.96	41.33	7.56	32.68	36.53	128	329 Peak	VERTICAL
2	4874.09	31.01	54.00	-22.99	27.30	7.56	32.68	36.53	128	329 Average	VERTICAL
3	4999.97	45.79	54.00	-8.21	41.66	7.75	32.90	36.52	102	100 Average	VERTICAL
4	5000.03	50.96	74.00	-23.04	46.83	7.75	32.90	36.52	102	100 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss4 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4903.86	31.17	54.00	-22.83	27.36	7.61	32.73	36.53	162	263 Average	HORIZONTAL
2	4904.88	44.73	74.00	-29.27	40.92	7.61	32.73	36.53	162	263 Peak	HORIZONTAL
3	4999.99	43.80	54.00	-10.20	39.67	7.75	32.90	36.52	242	140 Average	HORIZONTAL
4	5000.10	51.12	74.00	-22.88	46.99	7.75	32.90	36.52	242	140 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4903.64	45.21	74.00	-28.79	41.40	7.61	32.73	36.53	121	319 Peak	VERTICAL
2	4904.61	31.29	54.00	-22.71	27.48	7.61	32.73	36.53	121	319 Average	VERTICAL
3	5000.00	48.95	54.00	-5.05	44.82	7.75	32.90	36.52	241	96 Average	VERTICAL
4	5000.02	53.09	74.00	-20.91	48.96	7.75	32.90	36.52	241	96 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4829.60	35.37	54.00	-18.63	29.47	7.58	32.84	34.52	284	143	Average
2	4831.36	48.23	74.00	-25.77	42.33	7.58	32.84	34.52	284	143	Peak


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4823.60	48.03	74.00	-25.97	42.15	7.58	32.82	34.52	61	140 Peak	VERTICAL
2	4824.00	35.92	54.00	-18.08	30.04	7.58	32.82	34.52	61	140 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4868.48	35.35	54.00	-18.65	29.35	7.60	32.91	34.51	188	121	Average
2	4869.44	48.16	74.00	-25.84	42.16	7.60	32.91	34.51	188	121	Peak


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4867.92	49.06	74.00	-24.94	43.06	7.60	32.91	34.51	286	133	Peak
2	4874.92	35.27	54.00	-18.73	29.27	7.60	32.91	34.51	286	133	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4919.00	35.16	54.00	-18.84	29.07	7.61	32.97	34.49	33	135 Average	HORIZONTAL
2	4921.12	48.01	74.00	-25.99	41.92	7.61	32.97	34.49	33	135 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4914.00	44.45	74.00	-29.55	38.36	7.61	32.97	34.49	224	124	Peak	VERTICAL
2	4914.00	34.71	54.00	-19.29	28.62	7.61	32.97	34.49	224	124	Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4821.68	35.30	54.00	-18.70	27.63	7.64	33.11	33.08	163	55 Average	HORIZONTAL
2	4823.87	48.35	74.00	-25.65	40.68	7.64	33.11	33.08	163	55 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4822.53	35.69	54.00	-18.31	28.02	7.64	33.11	33.08	154	334 Average	VERTICAL
2	4826.39	48.97	74.00	-25.03	41.26	7.65	33.14	33.08	154	334 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4871.66	35.15	54.00	-18.85	27.30	7.70	33.23	33.08	163	160 Average	HORIZONTAL
2	4872.37	47.79	74.00	-26.21	39.94	7.70	33.23	33.08	163	160 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4870.47	35.03	54.00	-18.97	27.18	7.70	33.23	33.08	173	104	Average
2	4873.18	48.59	74.00	-25.41	40.74	7.70	33.23	33.08	173	104	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11g CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4919.99	47.42	74.00	-26.58	39.42	7.75	33.32	33.07	166	262	Peak	HORIZONTAL
2	4925.04	34.51	54.00	-19.49	26.46	7.76	33.35	33.06	166	262	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4922.54	47.16	74.00	-26.84	39.16	7.75	33.32	33.07	152	215	Peak
2	4926.74	34.56	54.00	-19.44	26.51	7.76	33.35	33.06	152	215	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4820.64	35.06	54.00	-18.94	27.39	7.64	33.11	33.08	160	331	Average
2	4823.92	48.12	74.00	-25.88	40.45	7.64	33.11	33.08	160	331	Peak


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4824.83	35.23	54.00	-18.77	27.56	7.64	33.11	33.08	146	299 Average	VERTICAL
2	4825.22	48.16	74.00	-25.84	40.45	7.65	33.14	33.08	146	299 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4871.74	35.17	54.00	-18.83	27.32	7.70	33.23	33.08	173	272	Average
2	4878.09	48.96	74.00	-25.04	41.10	7.70	33.23	33.07	173	272	Peak


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4869.83	34.96	54.00	-19.04	27.11	7.70	33.23	33.08	169	311	Average
2	4874.51	48.34	74.00	-25.66	40.49	7.70	33.23	33.08	169	311	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4922.19	47.73	74.00	-26.27	39.73	7.75	33.32	33.07	160	183 Peak	HORIZONTAL
2	4923.33	34.48	54.00	-19.52	26.48	7.75	33.32	33.07	160	183 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4920.80	47.20	74.00	-26.80	39.20	7.75	33.32	33.07	184	219 Peak	VERTICAL
2	4925.35	34.63	54.00	-19.37	26.58	7.76	33.35	33.06	184	219 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4844.71	48.06	74.00	-25.94	40.30	7.67	33.17	33.08	150	108 Peak	HORIZONTAL
2	4847.56	34.95	54.00	-19.05	27.19	7.67	33.17	33.08	150	108 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4841.81	48.40	74.00	-25.60	40.64	7.67	33.17	33.08	170	148 Peak	VERTICAL
2	4842.37	34.90	54.00	-19.10	27.14	7.67	33.17	33.08	170	148 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4870.07	34.87	54.00	-19.13	27.02	7.70	33.23	33.08	158	109 Average	HORIZONTAL
2	4874.06	48.11	74.00	-25.89	40.26	7.70	33.23	33.08	158	109 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4869.37	35.05	54.00	-18.95	27.20	7.70	33.23	33.08	146	85 Average	VERTICAL
2	4869.80	48.15	74.00	-25.85	40.30	7.70	33.23	33.08	146	85 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4899.61	34.33	54.00	-19.67	26.38	7.73	33.29	33.07	190	131	Average
2	4902.93	48.29	74.00	-25.71	40.34	7.73	33.29	33.07	190	131	Peak


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4899.96	34.57	54.00	-19.43	26.62	7.73	33.29	33.07	157	56 Average	VERTICAL
2	4904.88	47.19	74.00	-26.81	39.24	7.73	33.29	33.07	157	56 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.60	47.20	74.00	-26.80	40.41	6.76	33.11	33.08	101	308	Peak	HORIZONTAL
2	4824.00	34.48	54.00	-19.52	27.69	6.76	33.11	33.08	101	308	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4823.68	34.04	54.00	-19.96	27.25	6.76	33.11	33.08	102	296 Average	VERTICAL
2	4823.73	47.16	74.00	-26.84	40.37	6.76	33.11	33.08	102	296 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.36	34.09	54.00	-19.91	27.13	6.81	33.23	33.08	102	308 Average	HORIZONTAL
2	4874.97	47.35	74.00	-26.65	40.39	6.81	33.23	33.08	102	308 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.73	33.87	54.00	-20.13	26.91	6.81	33.23	33.08	103	318 Average	VERTICAL
2	4874.80	47.20	74.00	-26.80	40.24	6.81	33.23	33.08	103	318 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.51	46.34	74.00	-27.66	39.21	6.85	33.35	33.07	102	330 Peak	HORIZONTAL
2	4925.00	33.22	54.00	-20.78	26.09	6.85	33.35	33.07	102	330 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.41	46.32	74.00	-27.68	39.19	6.85	33.35	33.07	101	302	Peak
2	4924.73	33.02	54.00	-20.98	25.89	6.85	33.35	33.07	101	302	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4843.68	34.29	54.00	-19.71	27.42	6.78	33.17	33.08	100	314	Average
2	4844.97	47.01	74.00	-26.99	40.14	6.78	33.17	33.08	100	314	Peak


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4844.75	47.23	74.00	-26.77	40.36	6.78	33.17	33.08	102	296 Peak	VERTICAL
2	4844.86	33.99	54.00	-20.01	27.12	6.78	33.17	33.08	102	296 Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.42	46.99	74.00	-27.01	40.03	6.81	33.23	33.08	104	289 Peak	HORIZONTAL
2	4873.47	33.99	54.00	-20.01	27.03	6.81	33.23	33.08	104	289 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.07	33.80	54.00	-20.20	26.84	6.81	33.23	33.08	102	277	Average
2	4873.36	47.24	74.00	-26.76	40.28	6.81	33.23	33.08	102	277	Peak


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss4 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 4		

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4903.24	32.98	54.00	-21.02	25.93	6.83	33.29	33.07	104	267	Average	HORIZONTAL
2	4904.82	45.75	74.00	-28.25	38.70	6.83	33.29	33.07	104	267	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4903.35	32.96	54.00	-21.04	25.91	6.83	33.29	33.07	103	253 Average	VERTICAL
2	4904.77	46.24	74.00	-27.76	39.19	6.83	33.29	33.07	103	253 Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<For Radio 1 Beamforming Mode>


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.90	35.23	54.00	-18.77	29.35	7.58	32.82	34.52	168	270	Average	HORIZONTAL
2	4826.18	49.23	74.00	-24.77	43.33	7.58	32.84	34.52	168	270	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4814.87	47.81	74.00	-26.19	41.93	7.58	32.82	34.52	274	264	Peak	VERTICAL
2	4824.26	35.88	54.00	-18.12	30.00	7.58	32.82	34.52	274	264	Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4869.96	47.58	74.00	-26.42	41.58	7.60	32.91	34.51	162	244	Peak
2	4874.00	35.85	54.00	-18.15	29.85	7.60	32.91	34.51	162	244	Average


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4868.33	34.26	54.00	-19.74	28.26	7.60	32.91	34.51	146	225	Average	VERTICAL
2	4879.83	47.99	74.00	-26.01	41.98	7.60	32.91	34.50	146	225	Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4921.24	34.22	54.00	-19.78	28.13	7.61	32.97	34.49	167	103 Average	HORIZONTAL
2	4929.51	47.91	74.00	-26.09	41.79	7.62	32.99	34.49	167	103 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4923.17	47.27	74.00	-26.73	41.18	7.61	32.97	34.49	194	222	Peak	VERTICAL
2	4924.06	34.83	54.00	-19.17	28.71	7.62	32.99	34.49	194	222	Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4855.35	47.30	74.00	-26.70	41.34	7.59	32.88	34.51	196	216 Peak	HORIZONTAL
2	4857.78	35.09	54.00	-18.91	29.13	7.59	32.88	34.51	196	216 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4860.09	35.03	54.00	-18.97	29.07	7.59	32.88	34.51	258	213	Average	VERTICAL
2	4863.55	47.02	74.00	-26.98	41.06	7.59	32.88	34.51	258	213	Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4857.40	47.58	74.00	-26.42	41.62	7.59	32.88	34.51	114	215	Peak	HORIZONTAL
2	4860.54	35.16	54.00	-18.84	29.20	7.59	32.88	34.51	114	215	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4854.06	36.64	54.00	-17.36	30.68	7.59	32.88	34.51	209	275 Average	VERTICAL
2	4864.19	47.73	74.00	-26.27	41.77	7.59	32.88	34.51	209	275 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4887.78	34.39	54.00	-19.61	28.36	7.60	32.93	34.50	288	174 Average	HORIZONTAL
2	4895.92	47.19	74.00	-26.81	41.13	7.61	32.95	34.50	288	174 Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4884.00	34.24	54.00	-19.76	28.21	7.60	32.93	34.50	268	200 Average	VERTICAL
2	4919.90	47.55	74.00	-26.45	41.46	7.61	32.97	34.49	268	200 Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss2 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4820.31	48.81	74.00	-25.19	42.93	7.58	32.82	34.52	118	114	Peak	HORIZONTAL
2	4823.60	37.11	54.00	-16.89	31.23	7.58	32.82	34.52	118	114	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4832.25	37.05	54.00	-16.95	31.15	7.58	32.84	34.52	124	341	Average	VERTICAL
2	4838.90	49.16	74.00	-24.84	43.26	7.58	32.84	34.52	124	341	Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss2 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4859.98	49.13	74.00	-24.87	43.17	7.59	32.88	34.51	147	102	Peak	HORIZONTAL
2	4874.00	37.43	54.00	-16.57	31.43	7.60	32.91	34.51	147	102	Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4852.13	48.91	74.00	-25.09	42.97	7.59	32.86	34.51	144	338	Peak	VERTICAL
2	4873.92	38.49	54.00	-15.51	32.49	7.60	32.91	34.51	144	338	Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss2 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4935.30	36.28	54.00	-17.72	30.16	7.62	32.99	34.49	146	305	Average	HORIZONTAL
2	4948.68	48.71	74.00	-25.29	42.56	7.62	33.01	34.48	146	305	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4899.16	36.21	54.00	-17.79	30.15	7.61	32.95	34.50	148	204	Average	VERTICAL
2	4905.17	48.89	74.00	-25.11	42.83	7.61	32.95	34.50	148	204	Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss2 VHT40 CH 3 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4820.04	37.00	54.00	-17.00	31.12	7.58	32.82	34.52	142	91	Average	HORIZONTAL
2	4825.33	49.21	74.00	-24.79	43.31	7.58	32.84	34.52	142	91	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4821.32	49.35	74.00	-24.65	43.47	7.58	32.82	34.52	151	294	Peak	VERTICAL
2	4837.35	36.99	54.00	-17.01	31.09	7.58	32.84	34.52	151	294	Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss2 VHT40 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4855.25	37.07	54.00	-16.93	31.11	7.59	32.88	34.51	148	334	Average	HORIZONTAL
2	4857.65	48.44	74.00	-25.56	42.48	7.59	32.88	34.51	148	334	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4852.77	37.01	54.00	-16.99	31.07	7.59	32.86	34.51	146	184	Average	VERTICAL
2	4857.97	49.00	74.00	-25.00	43.04	7.59	32.88	34.51	146	184	Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss2 VHT40 CH 9 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4882.69	36.49	54.00	-17.51	30.46	7.60	32.93	34.50	152	78	Average	HORIZONTAL
2	4922.67	48.40	74.00	-25.60	42.31	7.61	32.97	34.49	152	78	Peak	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4883.73	36.57	54.00	-17.43	30.54	7.60	32.93	34.50	150	228	Average	VERTICAL
2	4884.21	48.58	74.00	-25.42	42.55	7.60	32.93	34.50	150	228	Peak	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss3 VHT20 CH 1 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4883.89	48.56	74.00	-25.44	42.53	7.60	32.93	34.50	155	130 Peak	HORIZONTAL
2	4883.97	36.89	54.00	-17.11	30.86	7.60	32.93	34.50	155	130 Average	HORIZONTAL


Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4883.09	48.30	74.00	-25.70	42.27	7.60	32.93	34.50	312	144	Peak
2	4883.41	36.48	54.00	-17.52	30.45	7.60	32.93	34.50	312	144	Average


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss3 VHT20 CH 6 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4852.21	48.86	74.00	-25.14	42.92	7.59	32.86	34.51	214	153	Peak
2	4855.89	37.08	54.00	-16.92	31.12	7.59	32.88	34.51	214	153	Average


Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4852.05	49.18	74.00	-24.82	43.24	7.59	32.86	34.51	124	150	Peak	VERTICAL
2	4853.97	38.30	54.00	-15.70	32.34	7.59	32.88	34.51	124	150	Average	VERTICAL


Temperature	22°C	Humidity	56%
Test Engineer	Nyle Chang & Peter Wu & Gary Chu & DK Chang & Eddie Weng & Stim Song & Brain Sun	Configurations	IEEE 802. 11ac MCS0/Nss3 VHT20 CH 11 / Chain 1 + Chain 2 + Chain 3 + Chain 4
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4834.06	37.10	54.00	-16.90	31.20	7.58	32.84	34.52	318	155 Average	HORIZONTAL
2	4835.83	49.33	74.00	-24.67	43.43	7.58	32.84	34.52	318	155 Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4826.37	37.17	54.00	-16.83	31.27	7.58	32.84	34.52	89	144	Average	VERTICAL
2	4834.31	50.10	74.00	-23.90	44.20	7.58	32.84	34.52	89	144	Peak	VERTICAL