


Background: white ; Printing Black ; Backside adhesive Rubber coated
 Sticker supplied in Roll format ; Chromo Paper 90g/m2 ;
 Dimensions without tolerances reffer to ISO 2768-g ;
 The sticker should not peel off from The surface (metalic) on a temperature from -40 to +85°C
 Part has to correspond to BOSCH Standard N2580-1



Rear Of Unit



Block D

- 1 - Not Connected
- 2 - Not Connected
- 3 - Not Connected
- 4 - Not Connected
- 5 - Not Connected
- 6 - Not Connected
- 7 - Not Connected
- 8 - Not Connected
- 9 - Microphone GND (1)
- 10 - Microphone In (1)

Block A

- 1 - Gala input
- 2 - Telephone Mute input
- 3 - Subwoofer output
- 4 - Permanent Power +12V: Yellow
- 5 - SW Supply +12V Automatic Antenna Blue (*)
- 6 - Illumination / Dimmer Control input
- 7 - Ignition Switch: Red
- 8 - Power GND: Black

Block C

- 1 - Line Out - Left Rear
- 2 - Line Out - Right Rear
- 3 - Line Out - GND
- 4 - Line Out - Left Front
- 5 - Line Out - Right Front
- 6 - SW Supply +12V for External Amplifier Blue/White (*)
- 7 - Telephone Audio In +
- 8 - Telephone Audio In -
- 9 - Telephone Mute input
- 10 - SW Supply +12V for Remote Control (*)
- 11 - Remote Control In
- 12 - Remote Control GND
- 13 - Changer BUS - RXD
- 14 - Changer BUS - TXD
- 15 - CDC Permanent +12V Fused
- 16 - SW Supply +12V For CDC (*)
- 17 - Changer BUS - GND
- 18 - CDC/AUX1 Audio In - GND
- 19 - CDC/AUX1 Audio In - Left
- 20 - CDC/AUX1 Audio In - Right

Block B(Speakers)

- 1 - Right Rear + :Violet
- 2 - Right Rear - :Violet/Black
- 3 - Right Front + :Gray
- 4 - Right Front - :Gray/Black
- 5 - Left Front + :White
- 6 - Left Front - :White/Black
- 7 - Left Rear + :Green
- 8 - Left Rear - :Green/Black

AM: 530-1710KHz ; FM: 87.5-108MHz
 Voltage: 12VDC ; Negative Ground

Warnings:

Warranty void if this unit is damaged due to misuse or unauthorized service attempting.

Before making any electrical connections, disconnect the vehicle battery's negative terminal and carefully review this unit's Owner's Manual.

Connect each pair of speaker leads only to a single pair of speakers (or speaker system) that has an impedance of at least 4 ohms, as well as 40-watt power-handling capability. Never allow the uninsulated part of any speaker leads to touch a metal part of the vehicle.

Connect speaker leads to inputs on external amplifiers **ONLY** if indicated in amplifier's manual, otherwise this unit's internal amplifier will be damaged.

NOTICES:

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS:

- 1- THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND
- 2- THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION

This product was produced using lead free technology.
 Help keep the world clean. ! Dispose properly !

Remarks:

(*) - Total Max 150mA

(1) - No Connection on Models: Seattle MP57 and Kingston MP47

ROBERT BOSCH CORPORATION
 Sales Group Blaupunkt Division
 2800 South 25th Avenue, Broadview,
 Illinois 60155

**CLASS 1
 LASER PRODUCT**

See other **BLAUPUNKT** products at www.blaupunkt.com

DEALER

DATE SOLD/INSTALLED

120.0 mm

100.0 mm

Sticker Number 8613920500

Drawing By: Pedro Barreiro

Date :31/10/2006

Index : 00

Original CorelDrawV12