FCC TEST REPORT

FCC ID : UHVNP25W

Applicant : N&P CAR AUDIO SYSTEM CO., LTD.

Room 2502, Caiwuwei Development Building, No. 3083, Baoan South Road,

Luohu District, Shenzhen, China

Equipment Under Test (EUT):

Product description : Car Backup Rearview Camera

Model No. : NP25W

Standards : FCC 15 Paragraph 15.249

Date of Test: November 20, 2006

Test Engineer : Tiger Su

Reviewed By : Thelo 2hous

PERPARED BY:

Waltek Services (Shenzhen) Co., Ltd.

8C, West Tower, Aidi Building, No.5003 Binhe Rd, Futian District, Shenzhen518045, Guangdong, China.

Tel: 86-755-83551033 Fax: 86-755-83552400

2 Contents

1	CC	OVER PAGE	Page		
		ONTENTS			
2					
3		ST SUMMARY			
4	GE	NERAL INFORMATION	5		
	4.1	CLIENT INFORMATION	5		
	4.2	GENERAL DESCRIPTION OF E.U.T.			
	4.3	DETAILS OF E.U.T.			
	4.4	DESCRIPTION OF SUPPORT UNITS			
	4.5	STANDARDS APPLICABLE FOR TESTING			
	4.6	TEST FACILITY			
	4.7	TEST LOCATION			
5	_	UIPMENT USED DURING TEST			
6	CO	NDUCTED EMISSION TEST	8		
	6.1	TEST EQUIPMENT	8		
	6.2	TEST PROCEDURE			
	6.3	CONDUCTED TEST SETUP			
	6.4	EUT OPERATING CONDITION			
	6.5	CONDUCTED EMISSION LIMITS			
	6.6	CONDUCTED EMISSION TEST RESULT	10		
7	RADIATION EMISSION TEST				
	7.1	TEST EQUIPMENT	11		
	7.2	MEASUREMENT UNCERTAINTY	11		
	7.3	TEST PROCEDURE	11		
	7.4	RADIATED TEST SETUP			
	7.5	SPECTRUM ANALYZER SETUP			
	7.6	CORRECTED AMPLITUDE & MARGIN CALCULATION			
	7.7	SUMMARY OF TEST RESULTS			
	7.8	EUT OPERATING CONDITION			
	7.9	RADIATED EMISSIONS LIMIT			
	7.10	RADIATED EMISSIONS TEST RESULT			
8	BA	ND EDGE	16		
	8.1	TEST EQUIPMENT			
	8.2	TEST PROCEDURE.			
	8.3	BAND EDGE			
	8.4	BAND EDGE TEST RESULT	17		
9	PH	OTOGRAPHS OF TESTING	18		
	9.1	RADIATION EMISSION TEST VIEW FOR 30MHz-1000MHz	18		
	9.2	RADIATION EMISSION TEST VIEW FOR 1GHz-25GHz	18		
1() PH	OTOGRAPHS - CONSTRUCTIONAL DETAILS	19		
	10.1	EUT - Front View	19		
	10.2	EUT - BACK VIEW	19		
	10.3	PCB1 - Front View	20		
	10.4	PCB1 - BACK VIEW	20		

N&P CAR AUDIO SYSTEM CO., LTD.

FCC ID: UHVNP25W

11	FCC	C ID LABEL	22
1	0.6	PCB2 - BACK VIEW	21
1	0.5	PCB2 - Front View	21

3 Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Radiated Emission (30MHz to 25GHz)	FCC PART 15: 2003	ANSI C63.4: 2003	Class B	PASS
Conducted Emission (150KHz to 30MHz)	FCC PART 15: 2003	ANSI C63.4: 2003	Class B	N/A

4 General Information

4.1 Client Information

Applicant: N&P CAR AUDIO SYSTEM CO., LTD.

Address of Applicant: Room 2502, Caiwuwei Development Building, No. 3083, Baoan

South Road, Luohu District, Shenzhen, China

Manufacturer: N&P CAR AUDIO SYSTEM CO., LTD.

Address: Room 2502, Caiwuwei Development Building, No. 3083, Baoan

South Road, Luohu District, Shenzhen, China

4.2 General Description of E.U.T.

Product description: Car Backup Rearview Camera

Model No.: NP25W

4.3 Details of E.U.T.

Power Supply: DC 12V

4.4 Description of Support Units

The EUT has been tested as an independent unit.

4.5 Standards Applicable for Testing

The customer requested FCC tests for a Car Backup Rearview Camera. The standards used were FCC 15 Paragraph 15.249, Paragraph 15.207, Paragraph 15.209, Paragraph 15.31, Paragraph 15.33, Paragraph 15.35.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd ShenZhen Branch EMC Lab, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 556682, August 04, 2005.

4.7 Test Location

All Emissions tests were performed at:-

No.1 Workshop, M-10, Middle Section, Science & Technology Park, ShenZhen, China 518057.

5 Equipment Used during Test

Equipment	Brand Name	Model	Cal. Int Months	Last Cal. Date
3m Anechoic chamber				
EMC Analyzer	Agilent	E7402A	12	2006-08-30
EMI Test Receiver	R&S	ESS	12	2006-08-30
Pre Amplifier	Anritsu	MH648A	12	2006-08-30
Bilog Antenna	SCHAFFNER	CBL6111C	12	2006-08-30
Horn Antenna	ETS.LINDGREN	CH14-H052	12	2006-08-30
AM/FM Stereo Signa Generator	l Panasonic	VP-8122A	12	2006-08-30
Signal Generator	R&S	SMG	12	2006-08-30
RF Selector	точо	NS4901A	-	-
Turn Disc	HD	DS4150S	-	-
Antenna Mast	HD	MA2400	-	-
EMI Shielded Room				
Spectrum analyzer	ADVANTEST	R3261C	12	2006-08-30
EMI Test Receiver	R&S	ESS	12	2006-08-30
Pre Amplifier	Anritsu	MH648A	12	2006-08-30
LISN	R&S	MNZ050D11	12	2006-08-30
LISN	Kyoritsu	KNW-403D	12	2006-08-30
Absorbing Clamp	R&S	MDS-21	12	2006-08-30
Distortion Meter	MEGURO	MAK-6578A	12	2006-08-30
AM/FM Stereo Signa Generator	l Panasonic	VP-8122A	12	2006-08-30
Oscilloscope	LEADER	LS1020	12	2006-08-30
Function Generator	National	VP-7422A	12	2006-08-30
Signal Generator	R&S	SMG	12	2006-08-30
RF Selector	тоуо	NS4000	-	-

6 Conducted Emission Test

Product Name: Car Backup Rearview Camera
Test Requirement: FCC Part15 Paragraph 15.207

Test Method: Based on FCC Part15 Paragraph 15.207

Test Date:

Frequency Range: 150 kHz to 30MHz

Class B

Detector: Peak for pre-scan (9 kHz Resolution Bandwidth)

Quasi-Peak & Average if maximised peak within 6dB of

Average Limit

6.1 Test Equipment


Please refer to Section 5 this report.

6.2 Test Procedure

- 1. The EUT was tested according to ANSI C63.4: 2003. The frequency spectrum from 150kHz to 30MHz was investigated.
- 2. The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.3 Conducted Test Setup


The conducted emission tests were performed using the setup accordance with the ANSI C63.4:2003, The specification used in this report was the FCC Part15 Paragraph 15.207 limits.



6.4 EUT Operating Condition

Operating condition is according to ANSI C63.4: 2003.

- A. Setup the EUT and simulators as shown on follow.
- B. Enable RF signal and confirm EUT active.
- C. Modulate output capacity of EUT up to specification.



6.5 Conducted Emission Limits

 $66-56\ dB\mu V/m$ between $0.15MHz\ \&\ 0.5MHz$

 $56 \ dB\mu V/m$ between $0.5MHz \ \& \ 5MHz$

 $60 \ dB\mu V/m$ between $5MHz \ \& \ 30MHz$

Note: In the above limits, the tighter limit applies at the band edges.

6.6 Conducted Emission Test Result

Owing to the DC operation of EUT, this test is not performed.

7 Radiation Emission Test

Product Name: Car Backup Rearview Camera
Test Requirement: FCC Part15 Paragraph 15.249

Test Method: Based on FCC Part15 Paragraph 15.31 and Paragraph 15.33

Test Date: November 20, 2006 Frequency Range: 30MHz to 25GHz

Measurement Distance: 3m

Detector: Peak for pre-scan (120kHz resolution bandwidth)

Quasi-Peak if maximised peak within 6dB of limit

7.1 Test Equipment

Please refer to Section 5 this report.

7.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase centre variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on ANSI C63.4: 2003, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at SGS EMC Lab is +4.0 dB.

7.3 Test Procedure

- 1. Maximizing procedure was performed on the six (6) highest emissions to ensure EUT is compliant with all installation combinations.
- 2. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB μ V of specification limits), and are distinguished with a "Qp" in the data table.
- 3. The EUT was under normal mode during the final qualification test and the configuration was used to represent the worst case results.

7.4 Radiated Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003, The specification used in this report was the FCC Part15 Paragraph 15.249 and Paragraph 15.209 limits.



7.5 Spectrum Analyzer Setup

According to FCC Part15 Paragraph 15.249 Rules, the system was tested to 25000 MHz.

Start Frequency	30 MHz
Stop Frequency	25000 MHz
Sweep Speed Auto	
IF Bandwidth	100 kHz
Video Bandwidth	1 MHz
Quasi-Peak Adapter Bandwidth	120 kHz
Quasi-Peak Adapter Mode	Normal
Resolution Bandwidth	1MHz

7.6 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-7dB\mu V$ means the emission is $7dB\mu V$ below the maximum limit for Class B. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – Class B Limit

7.7 Summary of Test Results

According to the data in section 7.10, the EUT complied with the FCC Part15 Paragraph 15.249 standards.

7.8 EUT Operating Condition

Same as section 6.4 of this report.

7.9 Radiated Emissions Limit

A. FCC Part 15 subpart C Paragraph 15.249 Limit

Fundamental Frequency		Strength of lamental	Field Strength of Harmonics		
	mV/m	dBuV/m	uV/m	dBuV/m	
902-928MHz	50	94	500	54	
2400-2483.5 MHz	50	94	500	54	
5725-5875 MHz	50	94	500	54	
24.0-24.25GHz	250	108	2500	68	

Note: (1) RF Voltage(dBuV)=20 log RF Voltage(uV)

- (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (3)The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
- (4) Above 1GHz,do a Peak and average measurements for all emissions,Limit for peak is 74dBuvV/m,According to Part15.35(b) and average is 54BuvV/m.

B. Frequencies in restricted band are complied to limit on Paragraph 15.209

Frequency(MHZ)	Distance(m)	Field strength(dBuV/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note: (1) RF Voltage(dBuV)=20 log RF Voltage(uV)

- (2) In the Above Table, the tighter limit applies at the band edges.
- (3) Distance refers to the distance in meters between the measuring instrument antenna.

7.10 Radiated Emissions Test Result

Formula of conversion factors: the field strength at 3m was established by adding The meter reading of the spectrum analyzer (which is set to read in units of dBuV) To the antenna correction factor supplied by the antenna manufacturer. The antenna Correction factors are stared in terms of dB. The gain of the pressletor was accounted For in the spectrum analyser meter reading.

Example:

Freq(MHz) Meter Reading +ACF=FS

33 20dBuV+10.36dB=30.36dBuV/m @3m

Radiated Emission Test Data

Test Voltage: DC 12V
Test Mode: TX On
Temperature: 24 °C
Humidity: 52%RH
Test Result: PASS

Remarks: 30-1000MHz radiation test no significant emissions above the equipment noise floor were detected.

1GHZ-25GHZ Radiated Emission Data

Frequency (MHz)	Detector	Antenna Polarization	Emission Level (dBuV/m)	FCC 15 Subpart C Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Turntable Angle (°)
2432.00		Vertical	79.49	94.00	14.51	1.5	120
2432.00		Horizontal	70.37	94.00	23.63	1.5	90
4864.00	AV	Vertical	48.69	54.00	5.31	1.5	45
7296.00	AV	Vertical	48.12	54.00	5.88	1.5	90
9728.00	AV	Vertical	49.01	54.00	4.99	1.5	45
4864.00	AV	Horizontal	45.99	54.00	8.01	1.5	180
7296.00	AV	Horizontal	44.50	54.00	9.50	1.5	45
9728.00	AV	Horizontal	47.66	54.00	6.34	1.5	90
4684.00	PK	Vertical	65.10	74.00	8.90	1.5	90
7296.00	PK	Vertical	64.90	74.00	9.10	1.5	90
9728.00	PK	Vertical	64.20	74.00	9.80	1.5	180
4684.00	PK	Horizontal	65.97	74.00	8.03	1.5	120
7296.00	PK	Horizontal	63.37	74.00	10.63	1.5	45
9728.00	PK	Horizontal	63.20	74.00	10.80	1.5	45

Note: Above 1GHz,do a Peak and average measurements for all emissions,Limit for peak is 74dBuvV/m,According to Part15.35(b) and average is 54BuvV/m.

8 Band Edge

8.1 Test Equipment

Please refer to Section 5 this report.

8.2 Test Procedure

- 1. The EUT, peripherals were put on the turntable which table size is 1mX1.5m, table high 0.8m. All set up is according to ANSI C63.4: 2003.
- 2. The bandwidth of the fundamental frequency was measure by spectrum analyser with 10KHz RBW and 30KHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power 20dB.

8.3 Band Edge

Requirements: FCC 15.249(d), the emission power at the START and STOP frequencies shall be at least 50dB below the level of the fundamental or to the general radiated emission limits in FCC 15.209.

8.4 Band Edge Test Result

Product Name: Car Backup Rearview Camera

Test Item: Band Edge Test

Test Voltage: DC 12V
Test Mode: TX On
Temperature: 24 °C
Humidity: 52%RH




Note: (1) The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.249.


(2) This device does meet the FCC requirement.

9 Photographs of Testing

9.1 Radiation Emission Test View For 30MHz-1000MHz



9.2 Radiation Emission Test View For 1GHz-25GHz



10 Photographs - Constructional Details


10.1 EUT - Front View




10.2 EUT - Back View




10.3 PCB1 - Front View




10.4 PCB1 - Back View



10.5 PCB2 - Front View



10.6 PCB2 - Back View



11 FCC ID Label

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

The Label must not be a stick-on paper. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Proposed Label Location on EUT
EUT Bottom View/proposed FCC Mark Location

