



MET Laboratories, Inc.

Safety Certification - EMI - Telecom Environmental Simulation

914 WEST PATAPSCO AVENUE • BALTIMORE, MARYLAND 21230-3432 • PHONE (410) 354-3300 • FAX (410) 354-3313

33439 WESTERN AVENUE • UNION CITY, CALIFORNIA 94587 • PHONE (510) 489-6300 • FAX (510) 489-6372

3162 BELICK STREET • SANTA CLARA, CA 95054 • PHONE (408) 748-3585 • FAX (510) 489-6372

13501 MCCALLEN PASS • AUSTIN, TEXAS 78753 • PHONE (512) 287-2500 • FAX (512) 287-2513

December 10, 2015

ARRIS Group Inc.
3871 Lakefield Drive Suite 300
Suwanee, GA 30024

Dear Tony Figueiredo,

Enclosed is the EMC Wireless test report for compliance testing of the ARRIS Group Inc., TG1652G and TG1652A as tested to the requirements of Title 47 of the CFR, Ch. 1 (10-1-06 ed.), Part 15 Subpart C for Intentional Radiators.

Thank you for using the services of MET Laboratories, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,
MET LABORATORIES, INC.

Jennifer Warnell
Documentation Department

Reference: (\ARRIS Group Inc.\EMC86264-FCC247)

Certificates and reports shall not be reproduced except in full, without the written permission of MET Laboratories, Inc.

Electromagnetic Compatibility Criteria Test Report

for the

**ARRIS Group Inc.
TG1652G and TG1652A**

Tested under
the FCC Certification Rules
contained in
15.247 Subpart C for Intentional Radiators

MET Report: EMC86264-FCC247

December 10, 2015

Prepared For:

**ARRIS Group Inc.
3871 Lakefield Drive Suite 300
Suwanee, GA 30024**

Prepared By:
MET Laboratories, Inc.
914 W. Patapsco Ave.
Baltimore, MD 21230

Electromagnetic Compatibility Criteria Test Report

for the

**ARRIS Group Inc.
TG1652G and TG1652A**

Tested under
the FCC Certification Rules
contained in
15.247 Subpart C for Intentional Radiators



Surinder Singh, Project Engineer
Electromagnetic Compatibility Lab



Jennifer Warnell
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Part 15.247 under normal use and maintenance.



Asad Bajwa,
Director, Electromagnetic Compatibility Lab

Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	December 10, 2015	Initial Issue.

Table of Contents

I.	Executive Summary	1
A.	Purpose of Test	2
B.	Executive Summary	2
II.	Equipment Configuration	3
A.	Overview.....	4
B.	References.....	5
C.	Test Site	5
D.	Description of Test Sample	6
E.	Equipment Configuration.....	6
F.	Support Equipment	6
G.	Ports and Cabling Information.....	7
H.	Mode of Operation.....	7
I.	Modifications	7
a)	Modifications to EUT	7
b)	Modifications to Test Standard.....	7
J.	Disposition of EUT	7
III.	Electromagnetic Compatibility Criteria for Intentional Radiators.....	8
§ 15.203	Antenna Requirement	9
§ 15.207(a)	Conducted Emissions Limits.....	10
§ 15.247(a)(a)	6 dB and 99% Bandwidth	13
§ 15.247(b)	Peak Power Output	19
§ 15.247(d)	Radiated Spurious Emissions Requirements and Band Edge.....	29
§ 15.247(d)	RF Conducted Spurious Emissions Requirements and Band Edge.....	55
§ 15.247(e)	Peak Power Spectral Density	72
§ 15.247(i)	Maximum Permissible Exposure	82
IV.	Test Equipment	83
V.	Certification & User's Manual Information	85
A.	Certification Information	86
B.	Label and User's Manual Information	90

List of Tables

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing	2
Table 2. EUT Summary Table.....	4
Table 3. References	5
Table 4. Equipment Configuration	6
Table 5. Support Equipment.....	6
Table 6. Ports and Cabling Information	7
Table 7. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)	10
Table 8. Conducted Emissions, 15.207(a), Phase Line, Test Results.....	11
Table 9. Conducted Emissions, 15.207(a), Neutral Line, Test Results	12
Table 10. 6 dB Occupied Bandwidth, Test Results, 802.11b	14
Table 11. 6 dB Occupied Bandwidth, Test Results, 802.11g	14
Table 12. 6 dB Occupied Bandwidth, Test Results, 802.11n 20 MHz	14
Table 13. 6 dB Occupied Bandwidth, Test Results, 802.11n 40 MHz	14
Table 14. Output Power Requirements from §15.247(b)	19
Table 15. Peak Power Output, Test Results, 802.11b	20
Table 16. Peak Power Output, Test Results, 802.11g	20
Table 17. Peak Power Output, Test Results, 802.11n 20 MHz	20
Table 18. Peak Power Output, Test Results, 802.11n 40 MHz	20
Table 19. Restricted Bands of Operation.....	29
Table 20. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)	30
Table 21. Peak Power Spectral Density, Test Results, 802.11b	73
Table 22. Peak Power Spectral Density, Test Results, 802.11g	73
Table 23. Peak Power Spectral Density, Test Results, 802.11n 20 MHz	73
Table 24. Peak Power Spectral Density, Test Results, 802.11n 40 MHz	73
Table 25. Test Equipment List	84

List of Plots

Plot 1. Conducted Emissions, 15.207(a), Phase Line	11
Plot 2. Conducted Emissions, 15.207(a), Neutral Line	12
Plot 3. 6 dB Occupied Bandwidth, Low Channel, 802.11b.....	15
Plot 4. 6 dB Occupied Bandwidth, Mid Channel, 802.11b	15
Plot 5. 6 dB Occupied Bandwidth, High Channel, 802.11b	15
Plot 6. 6 dB Occupied Bandwidth, Low Channel, 802.11g.....	16
Plot 7. 6 dB Occupied Bandwidth, Mid Channel, 802.11g	16
Plot 8. 6 dB Occupied Bandwidth, High Channel, 802.11g	16
Plot 9. 6 dB Occupied Bandwidth, Low Channel, 802.11n 20 MHz.....	17
Plot 10. 6 dB Occupied Bandwidth, Mid Channel, 802.11n 20 MHz	17
Plot 11. 6 dB Occupied Bandwidth, High Channel, 802.11n 20 MHz	17
Plot 12. 6 dB Occupied Bandwidth, Low Channel, 802.11n 40 MHz.....	18
Plot 13. 6 dB Occupied Bandwidth, Mid Channel, 802.11n 40 MHz	18
Plot 14. 6 dB Occupied Bandwidth, High Channel, 802.11n 40 MHz	18
Plot 15. Conducted Output Power, Low Channel, 802.11b, Chain 0	21
Plot 16. Conducted Output Power, Mid Channel, 802.11b, Chain 0	21
Plot 17. Conducted Output Power, High Channel, 802.11b, Chain 0.....	21
Plot 18. Conducted Output Power, Low Channel, 802.11b, Chain 1	22
Plot 19. Conducted Output Power, Mid Channel, 802.11b, Chain 1	22
Plot 20. Conducted Output Power, High Channel, 802.11b, Chain 1	22
Plot 21. Conducted Output Power, Low Channel, 802.11g, Chain 0	23
Plot 22. Conducted Output Power, Mid Channel, 802.11g, Chain 0	23

Plot 23. Conducted Output Power, High Channel, 802.11g, Chain 0.....	23
Plot 24. Conducted Output Power, Low Channel, 802.11g, Chain 1	24
Plot 25. Conducted Output Power, Mid Channel, 802.11g, Chain 1	24
Plot 26. Conducted Output Power, High Channel, 802.11g, Chain 1	24
Plot 27. Conducted Output Power, Low Channel, 802.11n 20 MHz, Chain 0	25
Plot 28. Conducted Output Power, Mid Channel, 802.11n 20 MHz, Chain 0	25
Plot 29. Conducted Output Power, High Channel, 802.11n 20 MHz, Chain 0	25
Plot 30. Conducted Output Power, Low Channel, 802.11n 20 MHz, Chain 1	26
Plot 31. Conducted Output Power, Mid Channel, 802.11n 20 MHz, Chain 1	26
Plot 32. Conducted Output Power, High Channel, 802.11n 20 MHz, Chain 1	26
Plot 33. Conducted Output Power, Low Channel, 802.11n 40 MHz, Chain 0	27
Plot 34. Conducted Output Power, Mid Channel, 802.11n 40 MHz, Chain 0	27
Plot 35. Conducted Output Power, High Channel, 802.11n 40 MHz, Chain 0	27
Plot 36. Conducted Output Power, Low Channel, 802.11n 40 MHz, Chain 1	28
Plot 37. Conducted Output Power, Mid Channel, 802.11n 40 MHz, Chain 1	28
Plot 38. Conducted Output Power, High Channel, 802.11n 40 MHz, Chain 1	28
Plot 39. Radiated Spurious Emissions, Low Channel, 802.11b, Chain 0, Average.....	31
Plot 40. Radiated Spurious Emissions, Low Channel, 802.11b, Chain 0, Peak	31
Plot 41. Radiated Spurious Emissions, Mid Channel, 802.11b, Chain 0, Average	31
Plot 42. Radiated Spurious Emissions, Mid Channel, 802.11b, Chain 0, Peak	32
Plot 43. Radiated Spurious Emissions, High Channel, 802.11b, Chain 0, Average	32
Plot 44. Radiated Spurious Emissions, High Channel, 802.11b, Chain 0, Peak.....	32
Plot 45. Radiated Spurious Emissions, Low Channel, 802.11b, Chain 1, Average.....	33
Plot 46. Radiated Spurious Emissions, Low Channel, 802.11b, Chain 1, Peak	33
Plot 47. Radiated Spurious Emissions, Mid Channel, 802.11b, Chain 1, Average	33
Plot 48. Radiated Spurious Emissions, Mid Channel, 802.11b, Chain 1, Peak	34
Plot 49. Radiated Spurious Emissions, High Channel, 802.11b, Chain 1, Average	34
Plot 50. Radiated Spurious Emissions, High Channel, 802.11b, Chain 1, Peak.....	34
Plot 51. Radiated Spurious Emissions, Low Channel, 802.11g, Chain 0, Average.....	35
Plot 52. Radiated Spurious Emissions, Low Channel, 802.11g, Chain 0, Peak	35
Plot 53. Radiated Spurious Emissions, Mid Channel, 802.11g, Chain 0, Average	35
Plot 54. Radiated Spurious Emissions, Mid Channel, 802.11g, Chain 0, Peak	36
Plot 55. Radiated Spurious Emissions, High Channel, 802.11g, Chain 0, Average	36
Plot 56. Radiated Spurious Emissions, High Channel, 802.11g, Chain 0, Peak	36
Plot 57. Radiated Spurious Emissions, Low Channel, 802.11g, Chain 1, Average.....	37
Plot 58. Radiated Spurious Emissions, Low Channel, 802.11g, Chain 1, Peak	37
Plot 59. Radiated Spurious Emissions, Mid Channel, 802.11g, Chain 1, Average	37
Plot 60. Radiated Spurious Emissions, Mid Channel, 802.11g, Chain 1, Peak	38
Plot 61. Radiated Spurious Emissions, High Channel, 802.11g, Chain 1, Average	38
Plot 62. Radiated Spurious Emissions, High Channel, 802.11g, Chain 1, Peak.....	38
Plot 63. Radiated Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 0, Average	39
Plot 64. Radiated Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 0, Peak	39
Plot 65. Radiated Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 0, Average	39
Plot 66. Radiated Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 0, Peak	40
Plot 67. Radiated Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 0, Average	40
Plot 68. Radiated Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 0, Peak.....	40
Plot 69. Radiated Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 1, Average	41
Plot 70. Radiated Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 1, Peak	41
Plot 71. Radiated Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 1, Average	41
Plot 72. Radiated Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 1, Peak	42
Plot 73. Radiated Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 1, Average	42
Plot 74. Radiated Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 1, Peak.....	42
Plot 75. Radiated Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 0, Average	43

Plot 76. Radiated Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 0, Peak	43
Plot 77. Radiated Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 0, Average	43
Plot 78. Radiated Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 0, Peak	44
Plot 79. Radiated Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 0, Average	44
Plot 80. Radiated Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 0, Peak	44
Plot 81. Radiated Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 1, Average	45
Plot 82. Radiated Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 1, Peak	45
Plot 83. Radiated Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 1, Average	45
Plot 84. Radiated Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 1, Peak	46
Plot 85. Radiated Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 1, Average	46
Plot 86. Radiated Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 1, Peak	46
Plot 87. Radiated Restricted Band Edge, 802.11b, Low Channel, Average	47
Plot 88. Radiated Restricted Band Edge, 802.11b, Low Channel, Peak	47
Plot 89. Radiated Restricted Band Edge, 802.11b, High Channel, Average	48
Plot 90. Radiated Restricted Band Edge, 802.11b, High Channel, Peak	48
Plot 91. Radiated Restricted Band Edge, 802.11g, Low Channel, Average	49
Plot 92. Radiated Restricted Band Edge, 802.11g, Low Channel, Peak	49
Plot 93. Radiated Restricted Band Edge, 802.11g, High Channel, Average	49
Plot 94. Radiated Restricted Band Edge, 802.11g, High Channel, Peak	50
Plot 95. Radiated Restricted Band Edge, 802.11n 20 MHz, Low Channel, Average	51
Plot 96. Radiated Restricted Band Edge, 802.11n 20 MHz, Low Channel, Peak	51
Plot 97. Radiated Restricted Band Edge, 802.11n 20 MHz, High Channel, Average	51
Plot 98. Radiated Restricted Band Edge, 802.11n 20 MHz, High Channel, Peak	52
Plot 99. Radiated Restricted Band Edge, 802.11n 40 MHz, Low Channel, Average	53
Plot 100. Radiated Restricted Band Edge, 802.11n 40 MHz, Low Channel, Peak	53
Plot 101. Radiated Restricted Band Edge, 802.11n 40 MHz, High Channel, Average	53
Plot 102. Radiated Restricted Band Edge, 802.11n 40 MHz, High Channel, Peak	54
Plot 103. Conducted Spurious Emissions, Low Channel, 802.11b, Chain 0	56
Plot 104. Conducted Spurious Emissions, Mid Channel, 802.11b, Chain 0	56
Plot 105. Conducted Spurious Emissions, High Channel, 802.11b, Chain 0	56
Plot 106. Conducted Spurious Emissions, Low Channel, 802.11b, Chain 1	57
Plot 107. Conducted Spurious Emissions, Mid Channel, 802.11b, Chain 1	57
Plot 108. Conducted Spurious Emissions, High Channel, 802.11b, Chain 1	57
Plot 109. Conducted Spurious Emissions, Low Channel, 802.11g, Chain 0	58
Plot 110. Conducted Spurious Emissions, Mid Channel, 802.11g, Chain 0	58
Plot 111. Conducted Spurious Emissions, High Channel, 802.11g, Chain 0	58
Plot 112. Conducted Spurious Emissions, Low Channel, 802.11g, Chain 1	59
Plot 113. Conducted Spurious Emissions, Mid Channel, 802.11g, Chain 1	59
Plot 114. Conducted Spurious Emissions, High Channel, 802.11g, Chain 1	59
Plot 115. Conducted Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 0	60
Plot 116. Conducted Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 0	60
Plot 117. Conducted Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 0	60
Plot 118. Conducted Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 1	61
Plot 119. Conducted Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 1	61
Plot 120. Conducted Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 1	61
Plot 121. Conducted Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 0	62
Plot 122. Conducted Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 0	62
Plot 123. Conducted Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 0	62
Plot 124. Conducted Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 1	63
Plot 125. Conducted Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 1	63
Plot 126. Conducted Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 1	63
Plot 127. Conducted Band Edge, Low Channel, 802.11b, Chain 0	64
Plot 128. Conducted Band Edge, Mid Channel, 802.11b, Chain 0	64

Plot 129. Conducted Band Edge, High Channel, 802.11b, Chain 0	64
Plot 130. Conducted Band Edge, Low Channel, 802.11b, Chain 1	65
Plot 131. Conducted Band Edge, Mid Channel, 802.11b, Chain 1	65
Plot 132. Conducted Band Edge, High Channel, 802.11b, Chain 1	65
Plot 133. Conducted Band Edge, Low Channel, 802.11g, Chain 0	66
Plot 134. Conducted Band Edge, Mid Channel, 802.11g, Chain 0	66
Plot 135. Conducted Band Edge, High Channel, 802.11g, Chain 0	66
Plot 136. Conducted Band Edge, Low Channel, 802.11g, Chain 1	67
Plot 137. Conducted Band Edge, Mid Channel, 802.11g, Chain 1	67
Plot 138. Conducted Band Edge, High Channel, 802.11g, Chain 1	67
Plot 139. Conducted Band Edge, Low Channel, 802.11n 20 MHz, Chain 0	68
Plot 140. Conducted Band Edge, Mid Channel, 802.11n 20 MHz, Chain 0	68
Plot 141. Conducted Band Edge, High Channel, 802.11n 20 MHz, Chain 0	68
Plot 142. Conducted Band Edge, Low Channel, 802.11n 20 MHz, Chain 1	69
Plot 143. Conducted Band Edge, Mid Channel, 802.11n 20 MHz, Chain 1	69
Plot 144. Conducted Band Edge, High Channel, 802.11n 20 MHz, Chain 1	69
Plot 145. Conducted Band Edge, Low Channel, 802.11n 40 MHz, Chain 0	70
Plot 146. Conducted Band Edge, Mid Channel, 802.11n 40 MHz, Chain 0	70
Plot 147. Conducted Band Edge, High Channel, 802.11n 40 MHz, Chain 0	70
Plot 148. Conducted Band Edge, Low Channel, 802.11n 40 MHz, Chain 1	71
Plot 149. Conducted Band Edge, Mid Channel, 802.11n 40 MHz, Chain 1	71
Plot 150. Conducted Band Edge, High Channel, 802.11n 40 MHz, Chain 1	71
Plot 151. Peak Power Spectral Density, Low Channel, 802.11b, Chain 0	74
Plot 152. Peak Power Spectral Density, Mid Channel, 802.11b, Chain 0	74
Plot 153. Peak Power Spectral Density, High Channel, 802.11b, Chain 0	74
Plot 154. Peak Power Spectral Density, Low Channel, 802.11b, Chain 1	75
Plot 155. Peak Power Spectral Density, Mid Channel, 802.11b, Chain 1	75
Plot 156. Peak Power Spectral Density, High Channel, 802.11b, Chain 1	75
Plot 157. Peak Power Spectral Density, Low Channel, 802.11g, Chain 0	76
Plot 158. Peak Power Spectral Density, Mid Channel, 802.11g, Chain 0	76
Plot 159. Peak Power Spectral Density, High Channel, 802.11g, Chain 0	76
Plot 160. Peak Power Spectral Density, Low Channel, 802.11g, Chain 1	77
Plot 161. Peak Power Spectral Density, Mid Channel, 802.11g, Chain 1	77
Plot 162. Peak Power Spectral Density, High Channel, 802.11g, Chain 1	77
Plot 163. Peak Power Spectral Density, Low Channel, 802.11n 20 MHz, Chain 0	78
Plot 164. Peak Power Spectral Density, Mid Channel, 802.11n 20 MHz, Chain 0	78
Plot 165. Peak Power Spectral Density, High Channel, 802.11n 20 MHz, Chain 0	78
Plot 166. Peak Power Spectral Density, Low Channel, 802.11n 20 MHz, Chain 1	79
Plot 167. Peak Power Spectral Density, Mid Channel, 802.11n 20 MHz, Chain 1	79
Plot 168. Peak Power Spectral Density, High Channel, 802.11n 20 MHz, Chain 1	79
Plot 169. Peak Power Spectral Density, Low Channel, 802.11n 40 MHz, Chain 0	80
Plot 170. Peak Power Spectral Density, Mid Channel, 802.11n 40 MHz, Chain 0	80
Plot 171. Peak Power Spectral Density, High Channel, 802.11n 40 MHz, Chain 0	80
Plot 172. Peak Power Spectral Density, Low Channel, 802.11n 40 MHz, Chain 1	81
Plot 173. Peak Power Spectral Density, Mid Channel, 802.11n 40 MHz, Chain 1	81
Plot 174. Peak Power Spectral Density, High Channel, 802.11n 40 MHz, Chain 1	81

List of Figures

Figure 1. Block Diagram of Test Configuration.....	6
Figure 2. Block Diagram, Occupied Bandwidth Test Setup.....	13
Figure 3. Peak Power Output Test Setup.....	19
Figure 4. Block Diagram, Conducted Spurious Emissions Test Setup.....	55
Figure 5. Block Diagram, Peak Power Spectral Density Test Setup	72

List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
<i>d</i>	Measurement Distance
dB	Decibels
dB_μA	Decibels above one microamp
dB_μV	Decibels above one microvolt
dB_μA/m	Decibels above one microamp per meter
dB_μV/m	Decibels above one microvolt per meter
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
<i>f</i>	Frequency
FCC	Federal Communications Commission
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	kilohertz
kPa	kilopascal
kV	kilovolt
LISN	Line Impedance Stabilization Network
MHz	Megahertz
μH	microhenry
μ	microfarad
μs	microseconds
NEBS	Network Equipment-Building System
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
TWT	Traveling Wave Tube
V/m	Volts per meter
VCP	Vertical Coupling Plane

I. Executive Summary

A. Purpose of Test

An EMC evaluation was performed to determine compliance of the ARRIS Group Inc. TG1652G and TG1652A, with the requirements of Part 15, §15.247. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the TG1652G and TG1652A. ARRIS Group Inc. should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the TG1652G and TG1652A, has been **permanently** discontinued.

B. Executive Summary

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.247, in accordance with ARRIS Group Inc., purchase order number AR1067393. All tests were conducted using measurement procedure ANSI C63.4-2014.

FCC Reference 47 CFR Part 15.247:2005	Description	Compliance
Title 47 of the CFR, Part 15 §15.203	Antenna Requirement	Compliant
Title 47 of the CFR, Part 15 §15.207(a)	Conducted Emission Limits	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(2)	6dB Occupied Bandwidth	Compliant
Title 47 of the CFR, Part 15 §15.247(b)	Peak Power Output	Compliant
Title 47 of the CFR, Part 15 §15.247(d); §15.209; §15.205	Radiated Spurious Emissions Requirements	Compliant
Title 47 of the CFR, Part 15 §15.247(d)	RF Conducted Spurious Emissions Requirements	Compliant
Title 47 of the CFR, Part 15 §15.247(d)	RF Conducted Band Edge	Compliant
Title 47 of the CFR, Part 15; §15.247(e)	Peak Power Spectral Density	Compliant
Title 47 of the CFR, Part 15 §15.247(i)	Maximum Permissible Exposure (MPE)	Compliant

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing

II. Equipment Configuration

A. Overview

MET Laboratories, Inc. was contracted by ARRIS Group Inc. to perform testing on the TG1652G and TG1652A, under ARRIS Group Inc.'s purchase order number AR1067393.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the ARRIS Group Inc., TG1652G and TG1652A.

The results obtained relate only to the item(s) tested.

Model(s) Tested:	TG1652G and TG1652A
Model(s) Covered:	TG1652G and TG1652A
EUT Specifications:	Primary Power: 120 VAC, 60 Hz
	FCC ID: UIDTG1652
	Type of Modulations: 802.11b/g/n
	Equipment Code: DTS
	Peak RF Output Power: 24.9 dBm
	EUT Frequency Ranges: 2412 MHz – 2462 MHz
Analysis:	The results obtained relate only to the item(s) tested.
Environmental Test Conditions:	Temperature: 15-35° C
	Relative Humidity: 30-60%
	Barometric Pressure: 860-1060 mbar
Evaluated by:	Surinder Singh
Report Date(s):	December 10, 2015

Table 2. EUT Summary Table

B. References

CFR 47, Part 15, Subpart C	Federal Communication Commission, Code of Federal Regulations, Title 47, Part 15: General Rules and Regulations, Allocation, Assignment, and Use of Radio Frequencies
ANSI C63.4:2014	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
ISO/IEC 17025:2005	General Requirements for the Competence of Testing and Calibration Laboratories
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Table 3. References

C. Test Site

All testing was performed at MET Laboratories, Inc., 914 W. Patapsco Ave., Baltimore, MD 21230. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 3 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

D. Description of Test Sample

The ARRIS Group Inc. TG1652G and TG1652A, Equipment Under Test (EUT), is a DOCSIS® 3.0 Dual Band Concurrent 802.11ac Wireless Telephony Gateway with MoCA®2.0.




Figure 1. Block Diagram of Test Configuration

E. Equipment Configuration

The EUT was set up as outlined in Figure 1, Block Diagram of Test Setup. All cards, racks, etc., incorporated as part of the EUT is included in the following list.

Ref. ID	Name / Description	Model Number	Part Number	Serial Number	Revision
4	UUT	TG1652A or G	--	--	--

Table 4. Equipment Configuration

F. Support Equipment

Support equipment necessary for the operation and testing of the EUT is included in the following list.

Ref. ID	Name / Description	Manufacturer	Model Number
2s	Laptop	Assorted	N/A

Table 5. Support Equipment

G. Ports and Cabling Information

Ref. ID	Port Name on EUT	Cable Description	Qty.	Length (m)	Shielded (Y/N)	Termination Point
2C	Ethernet	5e Modular 8 pin	1	1	No	--
3C	AC Input	2 conductor, 18 AWG	1	2	No	(115v/60hz)

Table 6. Ports and Cabling Information

H. Mode of Operation

The provided instructions and software will configure the unit for operation at each required test mode.

I. Modifications

a) Modifications to EUT

No modifications were made to the EUT.

b) Modifications to Test Standard

No modifications were made to the test standard.

J. Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to ARRIS Group Inc. upon completion of testing.

III. Electromagnetic Compatibility Criteria for Intentional Radiators

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.203 Antenna Requirement

Test Requirement:

§ 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria:

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

Results:

The EUT as tested is compliant the criteria of §15.203. The furnished antenna is permanently attached to the unit.

Test Engineer(s): Surinder Singh

Test Date(s): 10/10/15

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.207(a) Conducted Emissions Limits

Test Requirement(s): **§ 15.207 (a):** For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	§ 15.207(a), Conducted Limit (dB μ V)	
	Quasi-Peak	Average
* 0.15- 0.45	66 - 56	56 - 46
0.45 - 0.5	56	46
0.5 - 30	60	50

Table 7. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)

Test Procedure:

The EUT was placed on a 0.8 m-high wooden table inside a screen room. The EUT was situated such that the back of the EUT was 0.4 m from one wall of the vertical ground plane, and the remaining sides of the EUT were no closer than 0.8 m from any other conductive surface. The EUT was powered from a 50 Ω /50 μ H Line Impedance Stabilization Network (LISN). The EMC receiver scanned the frequency range from 150 kHz to 30 MHz. Conducted Emissions measurements were made in accordance with *ANSI C63.4-2014 "Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40 GHz"*. The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50 Ω /50 μ H LISN as the input transducer to an EMC/field intensity meter. For the purpose of this testing, the transmitter was turned on. Scans were performed with the transmitter on.

Test Results: The EUT was compliant with this requirement.


Test Engineer(s): Surinder Singh

Test Date(s): 06/12/15

15.207(a) Conducted Emissions Test Results

Frequency (MHz)	Uncorrected Meter Reading (dB μ V) QP	Cable Loss (dB)	Corrected Measurement (dB μ V) QP	Limit (dB μ V) QP	Margin (dB) QP	Uncorrected Meter Reading (dB μ V) Avg.	Cable Loss (dB)	Corrected Measurement (dB μ V) AVG	Limit (dB μ V) AVG	Margin (dB) AVG
0.154	55.91	0	55.91	65.78	-9.87	51.26	0	51.26	55.78	-4.52
0.38	46.07	0	46.07	58.28	-12.21	35.23	0	35.23	48.28	-13.05
1.98	44.83	0	44.83	56	-11.17	34.82	0	34.82	46	-11.18
5.6	35.62	0.17	35.79	60	-24.21	29.42	0.17	29.59	50	-20.41
13.55	35.41	0.04	35.45	60	-24.55	30.29	0.04	30.33	50	-19.67
25.4	26.5	0.17	26.67	60	-33.33	20.86	0.17	21.03	50	-28.97

Table 8. Conducted Emissions, 15.207(a), Phase Line, Test Results




Plot 1. Conducted Emissions, 15.207(a), Phase Line

15.207(a) Conducted Emissions Test Results

Frequency (MHz)	Uncorrected Meter Reading (dB μ V) QP	Cable Loss (dB)	Corrected Measurement (dB μ V) QP	Limit (dB μ V) QP	Margin (dB) QP	Uncorrected Meter Reading (dB μ V) Avg.	Cable Loss (dB)	Corrected Measurement (dB μ V) AVG	Limit (dB μ V) AVG	Margin (dB) AVG
0.152	55.77	0	55.77	65.89	-10.12	46.87	0	46.87	55.89	-9.02
0.363	49.2	0	49.2	58.66	-9.46	45.9	0	45.9	48.66	-2.76
4.08	42.82	0.1	42.92	56	-13.08	36.33	0.1	36.43	46	-9.57
5.96	36	0.17	36.17	60	-23.83	30.35	0.17	30.52	50	-19.48
13.1	36.01	0.08	36.09	60	-23.91	30.46	0.08	30.54	50	-19.46
29.35	28.64	0.28	28.92	60	-31.08	22.93	0.28	23.21	50	-26.79

Table 9. Conducted Emissions, 15.207(a), Neutral Line, Test Results



Plot 2. Conducted Emissions, 15.207(a), Neutral Line

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(a)(2) 6 dB Bandwidth

Test Requirements: **§ 15.247(a)(2):** Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

Test Procedure: The transmitter was on and transmitting at the highest output power. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using a RBW approximately 1% of the total emission bandwidth, $VBW > RBW$. The 6 dB Bandwidth was measured and recorded. The measurements were performed on the low, mid and high channels.

Test Results The EUT was compliant with § 15.247 (a)(2).

The 6 dB Bandwidth was determined from the plots on the following pages.

Test Engineer(s): Djed Mouada

Test Date(s): 10/07/15




Figure 2. Block Diagram, Occupied Bandwidth Test Setup

Occupied Bandwidth Test Results

Occupied Bandwidth		
Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)
Low	2412	10.025
Mid	2437	9.656
High	2462	10.067

Table 10. 6 dB Occupied Bandwidth, Test Results, 802.11b

Occupied Bandwidth		
Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)
Low	2412	16.040
Mid	2437	16.084
High	2462	15.223

Table 11. 6 dB Occupied Bandwidth, Test Results, 802.11g

Occupied Bandwidth		
Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)
Low	2412	17.051
Mid	2437	17.240
High	2462	15.183

Table 12. 6 dB Occupied Bandwidth, Test Results, 802.11n 20 MHz


Occupied Bandwidth		
Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)
Low	2422	35.591
Mid	2437	35.209
High	2452	35.441

Table 13. 6 dB Occupied Bandwidth, Test Results, 802.11n 40 MHz


6 dB Occupied Bandwidth Test Results, 802.11b



Plot 3. 6 dB Occupied Bandwidth, Low Channel, 802.11b




Plot 4. 6 dB Occupied Bandwidth, Mid Channel, 802.11b




Plot 5. 6 dB Occupied Bandwidth, High Channel, 802.11b


6 dB Occupied Bandwidth Test Results, 802.11g



Plot 6. 6 dB Occupied Bandwidth, Low Channel, 802.11g




Plot 7. 6 dB Occupied Bandwidth, Mid Channel, 802.11g




Plot 8. 6 dB Occupied Bandwidth, High Channel, 802.11g


6 dB Occupied Bandwidth Test Results, 802.11n 20 MHz



Plot 9. 6 dB Occupied Bandwidth, Low Channel, 802.11n 20 MHz




Plot 10. 6 dB Occupied Bandwidth, Mid Channel, 802.11n 20 MHz




Plot 11. 6 dB Occupied Bandwidth, High Channel, 802.11n 20 MHz


6 dB Occupied Bandwidth Test Results, 802.11n 40 MHz



Plot 12. 6 dB Occupied Bandwidth, Low Channel, 802.11n 40 MHz



Plot 13. 6 dB Occupied Bandwidth, Mid Channel, 802.11n 40 MHz



Plot 14. 6 dB Occupied Bandwidth, High Channel, 802.11n 40 MHz

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(b) Peak Power Output

Test Requirements: **§15.247(b):** The maximum peak output power of the intentional radiator shall not exceed the following:

Digital Transmission Systems (MHz)	Output Limit (Watts)
902-928	1.000
2400-2483.5	1.000
5725- 5850	1.000

Table 14. Output Power Requirements from §15.247(b)

§15.247(c): if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in the Table 14, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400 – 2483.5 MHz band and using a point to point application may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

Fixed, point-to-point operation excludes the use of point-to-multipoint systems, Omni-directional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

Test Procedure: The transmitter was connected to a calibrated spectrum analyzer. The EUT was measured at the low, mid and high channels of each band at the maximum power level.

Test Results: The EUT was compliant with the Peak Power Output limits of §15.247(b).

Test Engineer(s): Surinder Singh

Test Date(s): 10/10/15




Figure 3. Peak Power Output Test Setup

Peak Power Output Test Results

Frequency (MHz)	Mode	Ant Port 0 Power (dBm)	Ant Port 1 Power (dBm)	Summed Power (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dB)
2412	802.11b	20.61	19.77	23.3	5.8	30	-6.7
2437	802.11b	21.39	20.67	24.1	5.8	30	-5.9
2462	802.11b	18.98	19.3	22.2	5.8	30	-7.8

Table 15. Peak Power Output, Test Results, 802.11b

Frequency (MHz)	Mode	Ant Port 0 Power (dBm)	Ant Port 1 Power (dBm)	Summed Power (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dB)
2412	802.11g	15.25	14.69	18	5.8	30	-12
2437	802.11g	21.61	22	24.9	5.8	30	-5.1
2462	802.11g	14.34	14.62	17.5	5.8	30	-12.5

Table 16. Peak Power Output, Test Results, 802.11g

Frequency (MHz)	Mode	Ant Port 0 Power (dBm)	Ant Port 1 Power (dBm)	Summed Power (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dB)
2412	HT20	14.67	14.45	17.6	2.8	30	-12.4
2437	HT20	21.15	21.51	24.4	2.8	30	-5.6
2462	HT20	14.19	14.4	17.4	2.8	30	-12.6

Table 17. Peak Power Output, Test Results, 802.11n 20 MHz


Note: n mode transmit uncorrelated data stream, therefore overall array gain is equal to zero.

Frequency (MHz)	Mode	Ant Port 0 Power (dBm)	Ant Port 1 Power (dBm)	Summed Power (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dB)
2422	HT40	13.23	11.3	15.4	2.8	30	-14.6
2437	HT40	18.1	17.8	21	2.8	30	-9
2452	HT40	15.03	14.85	18	2.8	30	-12


Table 18. Peak Power Output, Test Results, 802.11n 40 MHz

Note: n mode transmit uncorrelated data stream, therefore overall array gain is equal to zero.


Conducted Output Power Test Results, 802.11b, Chain 0



Plot 15. Conducted Output Power, Low Channel, 802.11b, Chain 0




Plot 16. Conducted Output Power, Mid Channel, 802.11b, Chain 0




Plot 17. Conducted Output Power, High Channel, 802.11b, Chain 0


Conducted Output Power Test Results, 802.11b, Chain 1



Plot 18. Conducted Output Power, Low Channel, 802.11b, Chain 1




Plot 19. Conducted Output Power, Mid Channel, 802.11b, Chain 1




Plot 20. Conducted Output Power, High Channel, 802.11b, Chain 1


Conducted Output Power Test Results, 802.11g, Chain 0



Plot 21. Conducted Output Power, Low Channel, 802.11g, Chain 0




Plot 22. Conducted Output Power, Mid Channel, 802.11g, Chain 0




Plot 23. Conducted Output Power, High Channel, 802.11g, Chain 0


Conducted Output Power Test Results, 802.11g, Chain 1



Plot 24. Conducted Output Power, Low Channel, 802.11g, Chain 1




Plot 25. Conducted Output Power, Mid Channel, 802.11g, Chain 1




Plot 26. Conducted Output Power, High Channel, 802.11g, Chain 1


Conducted Output Power Test Results, 802.11n 20 MHz, Chain 0



Plot 27. Conducted Output Power, Low Channel, 802.11n 20 MHz, Chain 0




Plot 28. Conducted Output Power, Mid Channel, 802.11n 20 MHz, Chain 0




Plot 29. Conducted Output Power, High Channel, 802.11n 20 MHz, Chain 0


Conducted Output Power Test Results, 802.11n 20 MHz, Chain 1



Plot 30. Conducted Output Power, Low Channel, 802.11n 20 MHz, Chain 1




Plot 31. Conducted Output Power, Mid Channel, 802.11n 20 MHz, Chain 1




Plot 32. Conducted Output Power, High Channel, 802.11n 20 MHz, Chain 1


Conducted Output Power Test Results, 802.11n 40 MHz, Chain 0



Plot 33. Conducted Output Power, Low Channel, 802.11n 40 MHz, Chain 0




Plot 34. Conducted Output Power, Mid Channel, 802.11n 40 MHz, Chain 0




Plot 35. Conducted Output Power, High Channel, 802.11n 40 MHz, Chain 0


Conducted Output Power Test Results, 802.11n 40 MHz, Chain 1



Plot 36. Conducted Output Power, Low Channel, 802.11n 40 MHz, Chain 1



Plot 37. Conducted Output Power, Mid Channel, 802.11n 40 MHz, Chain 1



Plot 38. Conducted Output Power, High Channel, 802.11n 40 MHz, Chain 1

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge

Test Requirements: §15.247(d); §15.205: Emissions outside the frequency band.

§15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

§15.205(a): Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090–0.110-----	16.42–16.423	399.9–410	4.5–5.15
¹ 0.495–0.505-----	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905-----	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128-----	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775-----	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775-----	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218-----	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825-----	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225-----	123–138	2200–2300	14.47–14.5
8.291–8.294-----	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366-----	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675-----	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475-----	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293-----	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025-----	240–285	3345.8–3358.36.	43–36.5
12.57675–12.57725-----	322–335.4	3600–4400	(²)

Table 19. Restricted Bands of Operation

¹ Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz.

² Above 38.6

Test Requirement(s): **§ 15.209 (a):** Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 20.

Frequency (MHz)	§ 15.209(a), Radiated Emission Limits (dB μ V) @ 3m
30 - 88	40.00
88 - 216	43.50
216 - 960	46.00
Above 960	54.00

Table 20. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)


Test Procedures: The transmitter was turned on. Measurements were performed of the low, mid and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance and compared to a 3 m limit line. Only noise floor was measured above 18 GHz.

Test Results: The EUT was compliant with the Radiated Spurious Emission limits of **§ 15.247(d)**.


Test Engineer(s): Surinder Singh

Test Date(s): 10/10/15


Radiated Spurious Emissions Test Results, 802.11b, Chain 0




Plot 39. Radiated Spurious Emissions, Low Channel, 802.11b, Chain 0, Average




Plot 40. Radiated Spurious Emissions, Low Channel, 802.11b, Chain 0, Peak




Plot 41. Radiated Spurious Emissions, Mid Channel, 802.11b, Chain 0, Average



Plot 42. Radiated Spurious Emissions, Mid Channel, 802.11b, Chain 0, Peak




Plot 43. Radiated Spurious Emissions, High Channel, 802.11b, Chain 0, Average



Plot 44. Radiated Spurious Emissions, High Channel, 802.11b, Chain 0, Peak


Radiated Spurious Emissions Test Results, 802.11b, Chain 1




Plot 45. Radiated Spurious Emissions, Low Channel, 802.11b, Chain 1, Average




Plot 46. Radiated Spurious Emissions, Low Channel, 802.11b, Chain 1, Peak



Plot 47. Radiated Spurious Emissions, Mid Channel, 802.11b, Chain 1, Average



Plot 48. Radiated Spurious Emissions, Mid Channel, 802.11b, Chain 1, Peak




Plot 49. Radiated Spurious Emissions, High Channel, 802.11b, Chain 1, Average




Plot 50. Radiated Spurious Emissions, High Channel, 802.11b, Chain 1, Peak


Radiated Spurious Emissions Test Results, 802.11g, Chain 0




Plot 51. Radiated Spurious Emissions, Low Channel, 802.11g, Chain 0, Average




Plot 52. Radiated Spurious Emissions, Low Channel, 802.11g, Chain 0, Peak




Plot 53. Radiated Spurious Emissions, Mid Channel, 802.11g, Chain 0, Average



Plot 54. Radiated Spurious Emissions, Mid Channel, 802.11g, Chain 0, Peak




Plot 55. Radiated Spurious Emissions, High Channel, 802.11g, Chain 0, Average



Plot 56. Radiated Spurious Emissions, High Channel, 802.11g, Chain 0, Peak


Radiated Spurious Emissions Test Results, 802.11g, Chain 1




Plot 57. Radiated Spurious Emissions, Low Channel, 802.11g, Chain 1, Average




Plot 58. Radiated Spurious Emissions, Low Channel, 802.11g, Chain 1, Peak




Plot 59. Radiated Spurious Emissions, Mid Channel, 802.11g, Chain 1, Average



Plot 60. Radiated Spurious Emissions, Mid Channel, 802.11g, Chain 1, Peak




Plot 61. Radiated Spurious Emissions, High Channel, 802.11g, Chain 1, Average




Plot 62. Radiated Spurious Emissions, High Channel, 802.11g, Chain 1, Peak


Radiated Spurious Emissions Test Results, 802.11n 20 MHz, Chain 0




Plot 63. Radiated Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 0, Average




Plot 64. Radiated Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 0, Peak




Plot 65. Radiated Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 0, Average



Plot 66. Radiated Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 0, Peak




Plot 67. Radiated Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 0, Average




Plot 68. Radiated Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 0, Peak


Radiated Spurious Emissions Test Results, 802.11n 20 MHz, Chain 1




Plot 69. Radiated Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 1, Average




Plot 70. Radiated Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 1, Peak




Plot 71. Radiated Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 1, Average



Plot 72. Radiated Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 1, Peak




Plot 73. Radiated Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 1, Average




Plot 74. Radiated Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 1, Peak


Radiated Spurious Emissions Test Results, 802.11n 40 MHz, Chain 0




Plot 75. Radiated Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 0, Average




Plot 76. Radiated Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 0, Peak




Plot 77. Radiated Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 0, Average



Plot 78. Radiated Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 0, Peak




Plot 79. Radiated Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 0, Average




Plot 80. Radiated Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 0, Peak


Radiated Spurious Emissions Test Results, 802.11n 40 MHz, Chain 1




Plot 81. Radiated Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 1, Average




Plot 82. Radiated Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 1, Peak




Plot 83. Radiated Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 1, Average



Plot 84. Radiated Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 1, Peak



Plot 85. Radiated Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 1, Average




Plot 86. Radiated Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 1, Peak


Radiated Band Edge Measurements

Test Procedures: The transmitter was turned on. Measurements were performed of the low, mid and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance and compared to a 3 m limit line.


Radiated Band Edge Measurements, 802.11b




Plot 87. Radiated Restricted Band Edge, 802.11b, Low Channel, Average



Plot 88. Radiated Restricted Band Edge, 802.11b, Low Channel, Peak




Plot 89. Radiated Restricted Band Edge, 802.11b, High Channel, Average




Plot 90. Radiated Restricted Band Edge, 802.11b, High Channel, Peak


Radiated Band Edge Measurements, 802.11g




Plot 91. Radiated Restricted Band Edge, 802.11g, Low Channel, Average



Plot 92. Radiated Restricted Band Edge, 802.11g, Low Channel, Peak




Plot 93. Radiated Restricted Band Edge, 802.11g, High Channel, Average




Plot 94. Radiated Restricted Band Edge, 802.11g, High Channel, Peak


Radiated Band Edge Measurements, 802.11n 20 MHz




Plot 95. Radiated Restricted Band Edge, 802.11n 20 MHz, Low Channel, Average



Plot 96. Radiated Restricted Band Edge, 802.11n 20 MHz, Low Channel, Peak




Plot 97. Radiated Restricted Band Edge, 802.11n 20 MHz, High Channel, Average




Plot 98. Radiated Restricted Band Edge, 802.11n 20 MHz, High Channel, Peak


Radiated Band Edge Measurements, 802.11n 40 MHz




Plot 99. Radiated Restricted Band Edge, 802.11n 40 MHz, Low Channel, Average



Plot 100. Radiated Restricted Band Edge, 802.11n 40 MHz, Low Channel, Peak



Plot 101. Radiated Restricted Band Edge, 802.11n 40 MHz, High Channel, Average



Plot 102. Radiated Restricted Band Edge, 802.11n 40 MHz, High Channel, Peak

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge

Test Requirement:

15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Test Procedure:

For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

Since the EUT had an integral antenna, conducted measurements could not be performed. Measurements needed to be taken radiated. An antenna was located 3 m away from the EUT and plots were taken. The EUT was rotated through all three orthogonal axes. The plots were corrected for both antenna correction factor and cable loss.

See following pages for detailed test results with RF Conducted Spurious Emissions.

Test Results:

The EUT was compliant with the Conducted Spurious Emission limits of **§15.247(d)**.

Test Engineer(s):

Surinder Singh

Test Date(s):

10/10/15






Figure 4. Block Diagram, Conducted Spurious Emissions Test Setup


Conducted Spurious Emissions Test Results, 802.11b, Chain 0



Plot 103. Conducted Spurious Emissions, Low Channel, 802.11b, Chain 0




Plot 104. Conducted Spurious Emissions, Mid Channel, 802.11b, Chain 0




Plot 105. Conducted Spurious Emissions, High Channel, 802.11b, Chain 0


Conducted Spurious Emissions Test Results, 802.11b, Chain 1



Plot 106. Conducted Spurious Emissions, Low Channel, 802.11b, Chain 1




Plot 107. Conducted Spurious Emissions, Mid Channel, 802.11b, Chain 1




Plot 108. Conducted Spurious Emissions, High Channel, 802.11b, Chain 1


Conducted Spurious Emissions Test Results, 802.11g, Chain 0



Plot 109. Conducted Spurious Emissions, Low Channel, 802.11g, Chain 0




Plot 110. Conducted Spurious Emissions, Mid Channel, 802.11g, Chain 0




Plot 111. Conducted Spurious Emissions, High Channel, 802.11g, Chain 0


Conducted Spurious Emissions Test Results, 802.11g, Chain 1



Plot 112. Conducted Spurious Emissions, Low Channel, 802.11g, Chain 1




Plot 113. Conducted Spurious Emissions, Mid Channel, 802.11g, Chain 1




Plot 114. Conducted Spurious Emissions, High Channel, 802.11g, Chain 1


Conducted Spurious Emissions Test Results, 802.11n 20 MHz, Chain 0



Plot 115. Conducted Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 0




Plot 116. Conducted Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 0




Plot 117. Conducted Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 0


Conducted Spurious Emissions Test Results, 802.11n 20 MHz, Chain 1



Plot 118. Conducted Spurious Emissions, Low Channel, 802.11n 20 MHz, Chain 1




Plot 119. Conducted Spurious Emissions, Mid Channel, 802.11n 20 MHz, Chain 1




Plot 120. Conducted Spurious Emissions, High Channel, 802.11n 20 MHz, Chain 1


Conducted Spurious Emissions Test Results, 802.11n 40 MHz, Chain 0



Plot 121. Conducted Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 0




Plot 122. Conducted Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 0




Plot 123. Conducted Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 0


Conducted Spurious Emissions Test Results, 802.11b, 802.11n 40 MHz, Chain 1



Plot 124. Conducted Spurious Emissions, Low Channel, 802.11n 40 MHz, Chain 1




Plot 125. Conducted Spurious Emissions, Mid Channel, 802.11n 40 MHz, Chain 1




Plot 126. Conducted Spurious Emissions, High Channel, 802.11n 40 MHz, Chain 1


Conducted Band Edge Test Results, 802.11b, Chain 0



Plot 127. Conducted Band Edge, Low Channel, 802.11b, Chain 0




Plot 128. Conducted Band Edge, Mid Channel, 802.11b, Chain 0




Plot 129. Conducted Band Edge, High Channel, 802.11b, Chain 0

Conducted Band Edge Test Results, 802.11b, Chain 0



Plot 130. Conducted Band Edge, Low Channel, 802.11b, Chain 1




Plot 131. Conducted Band Edge, Mid Channel, 802.11b, Chain 1




Plot 132. Conducted Band Edge, High Channel, 802.11b, Chain 1


Conducted Band Edge Test Results, 802.11g, Chain 0



Plot 133. Conducted Band Edge, Low Channel, 802.11g, Chain 0




Plot 134. Conducted Band Edge, Mid Channel, 802.11g, Chain 0




Plot 135. Conducted Band Edge, High Channel, 802.11g, Chain 0

Conducted Band Edge Test Results, 802.11g, Chain 1



Plot 136. Conducted Band Edge, Low Channel, 802.11g, Chain 1




Plot 137. Conducted Band Edge, Mid Channel, 802.11g, Chain 1




Plot 138. Conducted Band Edge, High Channel, 802.11g, Chain 1


Conducted Band Edge Test Results, 802.11n 20 MHz, Chain 0



Plot 139. Conducted Band Edge, Low Channel, 802.11n 20 MHz, Chain 0




Plot 140. Conducted Band Edge, Mid Channel, 802.11n 20 MHz, Chain 0



Plot 141. Conducted Band Edge, High Channel, 802.11n 20 MHz, Chain 0


Conducted Band Edge Test Results, 802.11n 20 MHz, Chain 1



Plot 142. Conducted Band Edge, Low Channel, 802.11n 20 MHz, Chain 1



Plot 143. Conducted Band Edge, Mid Channel, 802.11n 20 MHz, Chain 1




Plot 144. Conducted Band Edge, High Channel, 802.11n 20 MHz, Chain 1

Conducted Band Edge Test Results, 802.11n 40 MHz, Chain 0



Plot 145. Conducted Band Edge, Low Channel, 802.11n 40 MHz, Chain 0




Plot 146. Conducted Band Edge, Mid Channel, 802.11n 40 MHz, Chain 0



Plot 147. Conducted Band Edge, High Channel, 802.11n 40 MHz, Chain 0


Conducted Band Edge Test Results, 802.11b, 802.11n 40 MHz, Chain 1



Plot 148. Conducted Band Edge, Low Channel, 802.11n 40 MHz, Chain 1



Plot 149. Conducted Band Edge, Mid Channel, 802.11n 40 MHz, Chain 1



Plot 150. Conducted Band Edge, High Channel, 802.11n 40 MHz, Chain 1

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(e) Peak Power Spectral Density

Test Requirements: **§15.247(e):** For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure: The transmitter was connected directly to a Spectrum Analyzer through an attenuator. The power level was set to the maximum level throughout each of the 100 sweeps of power averaging. The RBW was set to 3 kHz and a VBW set to 9 kHz or greater. The spectrum analyzer was set to an auto sweep time and a peak detector was used. Measurements were carried out at the low, mid and high channels.

Test Results: The EUT was compliant with the peak power spectral density limits of **§ 15.247 (e)**.

The peak power spectral density was determined from plots on the following page(s).

Test Engineer: Surinder Singh

Test Date: 10/10/15




Figure 5. Block Diagram, Peak Power Spectral Density Test Setup

Peak Power Spectral Density Test Results

Frequency (MHz)	Mode	Ant Port 0 PSD (dBm)	Ant Port 1 PSD (dBm)	Summed PSD (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dB)
2412	802.11b	1.62	-1.78	3.3	5.8	8	-4.7
2437	802.11b	2.31	0.24	4.5	5.8	8	-3.5
2462	802.11b	0.104	-3.58	1.7	5.8	8	-6.3

Table 21. Peak Power Spectral Density, Test Results, 802.11b

Frequency (MHz)	Mode	Ant Port 0 PSD (dBm)	Ant Port 1 PSD (dBm)	Summed PSD (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dB)
2412	802.11g	-11.37	-12.04	-8.6	5.8	8	-16.6
2437	802.11g	-4.6	-4.56	-1.5	5.8	8	-9.5
2462	802.11g	-12.68	-12.16	-9.4	5.8	8	-17.4

Table 22. Peak Power Spectral Density, Test Results, 802.11g

Frequency (MHz)	Mode	Ant Port 0 PSD (dBm)	Ant Port 1 PSD (dBm)	Summed PSD (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dB)
2412	HT20	-11.92	-11.93	-8.9	2.8	8	-16.9
2437	HT20	-5.3	-5.2	-2.2	2.8	8	-10.2
2462	HT20	-12.8	-12.48	-9.6	2.8	8	-17.6

Table 23. Peak Power Spectral Density, Test Results, 802.11n 20 MHz


Note: n mode transmit uncorrelated data stream, therefore overall array gain is equal to zero.

Frequency (MHz)	Mode	Ant Port 0 PSD (dBm)	Ant Port 1 PSD (dBm)	Summed PSD (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dB)
2422	HT40	-16.88	-16.88	-13.8	2.8	8	-21.8
2437	HT40	-12.34	-12.76	-9.5	2.8	8	-17.5
2452	HT40	-15.54	-16.29	-12.8	2.8	8	-20.8


Table 24. Peak Power Spectral Density, Test Results, 802.11n 40 MHz

Note: n mode transmit uncorrelated data stream, therefore overall array gain is equal to zero.


Peak Power Spectral Density Test Results, 802.11b, Chain 0



Plot 151. Peak Power Spectral Density, Low Channel, 802.11b, Chain 0




Plot 152. Peak Power Spectral Density, Mid Channel, 802.11b, Chain 0




Plot 153. Peak Power Spectral Density, High Channel, 802.11b, Chain 0

Peak Power Spectral Density Test Results, 802.11b, Chain 1



Plot 154. Peak Power Spectral Density, Low Channel, 802.11b, Chain 1




Plot 155. Peak Power Spectral Density, Mid Channel, 802.11b, Chain 1




Plot 156. Peak Power Spectral Density, High Channel, 802.11b, Chain 1


Peak Power Spectral Density Test Results, 802.11g, Chain 0



Plot 157. Peak Power Spectral Density, Low Channel, 802.11g, Chain 0




Plot 158. Peak Power Spectral Density, Mid Channel, 802.11g, Chain 0




Plot 159. Peak Power Spectral Density, High Channel, 802.11g, Chain 0


Peak Power Spectral Density Test Results, 802.11g, Chain 1



Plot 160. Peak Power Spectral Density, Low Channel, 802.11g, Chain 1




Plot 161. Peak Power Spectral Density, Mid Channel, 802.11g, Chain 1




Plot 162. Peak Power Spectral Density, High Channel, 802.11g, Chain 1


Peak Power Spectral Density Test Results, 802.11n 20 MHz, Chain 0



Plot 163. Peak Power Spectral Density, Low Channel, 802.11n 20 MHz, Chain 0




Plot 164. Peak Power Spectral Density, Mid Channel, 802.11n 20 MHz, Chain 0




Plot 165. Peak Power Spectral Density, High Channel, 802.11n 20 MHz, Chain 0


Peak Power Spectral Density Test Results, 802.11n 20 MHz, Chain 1



Plot 166. Peak Power Spectral Density, Low Channel, 802.11n 20 MHz, Chain 1




Plot 167. Peak Power Spectral Density, Mid Channel, 802.11n 20 MHz, Chain 1




Plot 168. Peak Power Spectral Density, High Channel, 802.11n 20 MHz, Chain 1


Peak Power Spectral Density Test Results, 802.11n 40 MHz, Chain 0



Plot 169. Peak Power Spectral Density, Low Channel, 802.11n 40 MHz, Chain 0




Plot 170. Peak Power Spectral Density, Mid Channel, 802.11n 40 MHz, Chain 0



Plot 171. Peak Power Spectral Density, High Channel, 802.11n 40 MHz, Chain 0


Peak Power Spectral Density Test Results, 802.11b, 802.11n 40 MHz, Chain 1



Plot 172. Peak Power Spectral Density, Low Channel, 802.11n 40 MHz, Chain 1



Plot 173. Peak Power Spectral Density, Mid Channel, 802.11n 40 MHz, Chain 1



Plot 174. Peak Power Spectral Density, High Channel, 802.11n 40 MHz, Chain 1

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(i) Maximum Permissible Exposure

RF Exposure Requirements: **§1.1307(b)(1) and §1.1307(b)(2):** Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

RF Radiation Exposure Limit: **§1.1310:** As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit Calculation: EUT's operating frequencies @ 2400-2483.5 MHz; highest conducted power = 16.18dBm (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

Output Power = 24.9dBm

Antenna Gain = 5.8 dBi

Power density is equal to 0.234 mW/cm².

At a distance of 20 cm.

IV. Test Equipment

Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ISO/IEC 17025:2005.

MET Asset #	Equipment	Manufacturer	Model	Last Cal Date	Cal Due Date
1T4870	THERM./CLOCK/HUMIDITY MONITOR	CONTROL COMPANY	06-662-4, FB70258	3/14/2014	3/14/2016
1T4829	SPECTRUM ANALYZER	AGILENT	E4407B	9/30/2014	3/30/2016
1T4818	COMB GENERATOR	COM-POWER	CGO-520	SEE NOTE	
1T4149	HIGH-FREQUENCY ANECHOIC CHAMBER	RAY PROOF	81	NOT REQUIRED	
1T4505	TEMPERATURE CHAMBER	TEST EQUITY	115	2/11/2015	2/11/2016
1T2665	ANTENNA; HORN	EMCO	7/11/1908	5/3/2014	11/3/2015
1T4442	PRE-AMPLIFIER, MICROWAVE	MITEQ	AFS42-01001800-30-10P	SEE NOTE	
1T4418	LISN	SOLAR ELECTRONICS	9233-50-TS-50-N	10/24/2014	4/24/2016
1T4409	EMI RECEIVER	ROHDE & SCHWARZ	ESIB7	7/18/2014	7/18/2016
1T4300	SEMI-ANECHOIC CHAMBER # 1 (NSA)	EMC TEST SYSTEMS	NONE	7/24/2015	7/24/2016

Table 25. Test Equipment List

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.

V. Certification & User's Manual Information

Certification & User's Manual Information

A. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

§ 2.801 Radio-frequency device defined.

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

§ 2.803 Marketing of radio frequency devices prior to equipment authorization.

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
 - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
 - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.

- (e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:
- (i) *Compliance testing;*
 - (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production stages; or
 - (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.
- (e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.
- (f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.

Certification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:

§ 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.¹ *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer,* be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

§ 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

¹ In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.

Certification & User's Manual Information

§ 2.948 Description of measurement facilities.

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
- (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
- (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
- (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
- (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.

Certification & User's Manual Information

1. Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

§ 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

(1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

(2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

(3) All other devices shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

(4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

(5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

§ 15.21 Information to user.

The user's manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

§ 15.105 Information to the user.

- (a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

- (b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

End of Report