



EMC Technologies (NZ) Ltd  
PO Box 68-307, Newton  
Auckland 1145  
New Zealand  
Phone 09 360 0862  
Fax 09 360 0861  
E-Mail Address: aucklab@ihug.co.nz  
Web Site: www.emctech.com.au

## **TEST REPORT**

### **4RF SR+ SQ928M141 & FE928M141 Point to Multi-point Digital Radio**

*tested to the*

**Code of Federal Regulations (CFR) 47**

**Part 24 –Personal Communications Services  
Subpart D – Narrowband PCS**

*for*  
**EMC  
Technologies**

**4RF Limited**

This Test Report is issued with the authority of:

**Andrew Cutler - General Manager**



**All tests reported  
herein have been  
performed in accordance  
with the laboratory's  
scope of accreditation**

## Table of Contents

1. COMPLIANCE STATEMENT	3
2. RESULT SUMMARY	3
3. ATTESTATION	4
4. CLIENT INFORMATION	5
5. TEST SAMPLE DESCRIPTION	5
6. TEST RESULTS	7
7. TEST EQUIPMENT USED	20
8. ACCREDITATIONS	20
9. PHOTOGRAPHS	21

## 1. COMPLIANCE STATEMENT

The **4RF SR+ SQ928M141 & FE928M141 Point to Multi-point Digital Radio** complies with the limits defined in 47 CFR Part 24, Subpart D – Narrowband PCS and 47 CFR Part 2 when tested in-accordance with the test methods described in 47 CFR Part 2 and ANSI C63.4, 2002.

## 2. RESULT SUMMARY

The results of testing, carried out between 25<sup>th</sup> April and 1<sup>st</sup> May 2014, are summarised below.

Clause	Description	Result
90.203	Certification required	Noted
2.1046 24.132 (b)	RF power output Power and antenna height limits	Noted Noted
2.1049 2.202 24.131 24.133 (a) 24.133 (a)(1),(2)	Occupied bandwidth Bandwidths Authorised bandwidth Emission Limits Emission masks	Noted Noted Complies Complies Complies
2.1051	Spurious emissions at antenna terminals	Complies
2.1053	Field strength of spurious radiation	Complies
2.1055 24.135	Frequency stability Frequency stability	Noted Complies
1.1310	Radio frequency exposure limits	Complies

### 3. ATTESTATION

This report describes the tests and measurements performed for the purpose of determining compliance with the specification with the following conditions:

**The client selected the test sample.**

**The report relates only to the sample tested.**


**This report does not contain corrections or erasures.**

Measurement uncertainties with statistical confidence intervals of 95% are shown below test results. Both Class A and Class B uncertainties have been accounted for, as well as influence uncertainties where appropriate.


In addition this equipment has been tested in accordance with the requirements contained in the appropriate Commission regulations.

To the best of my knowledge, these tests were performed using measurement procedures that are consistent with industry or Commission standards and demonstrate that the equipment complies with the appropriate standards.

I further certify that the necessary measurements were made by EMC Technologies NZ Ltd, 47 MacKelvie Street, Grey Lynn, Auckland, New Zealand.



Andrew Cutler  
General Manager  
EMC Technologies NZ Ltd



EMC  
Technologies

## 4. CLIENT INFORMATION

**Company Name** 4RF Limited

**Address** 26 Glover Street  
Ngauranga  
Wellington

**Country** New Zealand

**Contact** Mr Paul Young

## 5. TEST SAMPLE DESCRIPTION

**Brand Name** Aprisa SR+

**Model Numbers** SQ928M141 & FE928M141

**Product** Point to Multi Point Digital Radio

**Manufacturer** 4RF Limited

**Manufactured in** New Zealand

**Designed in** New Zealand

**Serial Numbers** -

**FCC ID** UIPSQ928M141

The manufacturer has declared that the Aprisa SR+ SQ928M141 & FE928M141 are electrically identical such that the FCC ID: UIPSQ928M141 can be applied to both models.

The Aprisa SR+ FE928M141 comprises an Aprisa SR+ SQ928M141 in a 19" rack mount box with a duplexer mounted inside.

Full testing was carried out on the Aprisa SR+ SQ928M141 SR+ FE928M141 with limited testing, radiated emissions, carried out on the Aprisa SR+ FE928M141

The samples tested have the following specifications:

**Rated Transmitter Output Power**

5.0 Watts (37.0 dBm)

**Transmitter FCC frequency range**

930.0 - 931.0 MHz

940.0 - 941.0 MHz

**Test frequencies**

Channel	Frequency (MHz)	Power (Watts)	Spacing (kHz)
1	930.525	5.0	12.5, 25.0, 50.0
2	940.525	5.0	12.5, 25.0, 50.0

**Emission Designators / Modes of operation**

G1D and D1D emissions designators have been applied when the transmitter uses 12.5, 25.0 and 50 kHz channel spacing.

G1D emission designator is applied when QPSK modulation is utilised

D1D emission designator is applied when 16QAM and 64QAM modulation is utilised

**Power Supply**

The equipment is powered using an external DC supply.

**Standard Temperature and Humidity**

Temperature: +15°C to + 30°C maintained.

Relative Humidity: 20% to 75% observed.

**Standard Test Power Source**

Nominal Voltage: 13.8 V dc.

Standard Test Voltage: 13.8 V dc.

**Extreme Temperature**

High Temperature: + 50°C maintained.

Low Temperature: - 30°C maintained.

**Extreme Test Voltages**

High Voltage: 30.0 Vdc

Low Voltage: 10.0 Vdc

## 6. TEST RESULTS

### RF power output

Measurements were carried out at the RF output terminals of the transmitter using a 30 dB power attenuator and a  $50\ \Omega$  dummy load.

Measurements were carried out when the transmitter was not being modulated.

Testing was carried out at maximum rated power output of 5 watts (37 dBm).

**Nominal Frequency:** 930.525 MHz

Frequency (MHz)	Voltage (Vdc)	Rated (dBm)	Measured (dBm)
930.525	10.0	37.0	36.8
930.525	13.8	37.0	36.9
930.525	30.0	37.0	36.9

**Nominal Frequency:** 940.525 MHz

Frequency (MHz)	Voltage (Vdc)	Rated (dBm)	Measured (dBm)
940.525	10.0	37.0	36.8
940.525	13.8	37.0	36.9
940.525	30.0	37.0	36.9

### Limits:

The output power shall be within  $\pm 1$  dB of the manufacturers rated power.

**Result:** Complies.

**Measurement Uncertainty:**  $\pm 0.5$  dB

## **Emission types:**

The following emission types are used:

- G1D digital data when QPSK modulation is utilised
- D1D digital data when 16QAM or 64QAM modulation is utilised

## **Part 24.131 – Authorised Bandwidth:**

The authorized bandwidth of narrowband PCS channels will be 10 kHz for 12.5 kHz channels and 45 kHz for 50 kHz channels. For aggregated adjacent channels, a maximum authorized bandwidth of 5 kHz less than the total aggregated channel width is permitted.

Measurements have been made to verify the declared bandwidth.

The occupied bandwidth has been measured and compared against the occupied bandwidth declared by the client.

Measurements have been made of each modulation type using a spectrum analyser operating in peak hold mode and a 30 dB attenuator.

Initially power measurements are made using a resolution bandwidth of 120 kHz.

This level is used as a reference level on the spectrum analyser.

The resolution bandwidth is then changed to 100 Hz and the reference level minus 23 dB (99%) absolute bandwidth points determined.

**Nominal Frequency:** 940.525 MHz

<b>Emission</b>	<b>Channel (kHz)</b>	<b>Measured (kHz)</b>	<b>Authorised Bandwidth (kHz)</b>
<b>QPSK</b>	12.5	9.575	10.0
<b>16QAM</b>	12.5	8.580	10.0
<b>64QAM</b>	12.5	8.475	10.0
<b>QPSK</b>	25.0	18.900	20.0
<b>16QAM</b>	25.0	18.640	20.0
<b>64QAM</b>	25.0	17.850	20.0
<b>QPSK</b>	50.0	40.350	45.0
<b>16QAM</b>	50.0	39.700	45.0
<b>64QAM</b>	50.0	37.650	45.0

**Result:** Complies.

## 24.133 Emission Limits

Part 24.133 (a) states the power of any emission shall be attenuated below the transmitter power in accordance with the following:

(1) For transmitters authorized a bandwidth greater than 10 kHz:

(i) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of up to and including 40 kHz: at least  $116 \log_{10}((f_d+10)/6.1)$  decibels or 50 plus  $10 \log_{10}(P)$  decibels or 70 decibels, whichever is the lesser attenuation;

(ii) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 40 kHz: at least  $43+10 \log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation.

(2) For transmitters authorized a bandwidth of 10 kHz:

(i) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of up to and including 20 kHz: at least  $116 \times \log_{10}((f_d+5)/3.05)$  decibels or 50 plus  $10 \times \log_{10}(P)$  decibels or 70 decibels, whichever is the lesser attenuation;

(ii) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 20 kHz: at least  $43+10 \log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation.


The transmitter can operate in the band 930-931 and 940-941 using an authorised bandwidth of 10 kHz and channel spacing of 12.5 kHz and an authorised bandwidth of 45 kHz and a channel spacing of 50 kHz.

Measurements have been made of each modulation type using a spectrum analyser operating in peak hold mode and a 30 dB attenuator.


Initially power measurements are made using a resolution bandwidth of 120 kHz. This level is used as a reference level on the spectrum analyser.

**Nominal Frequency: 940.525 MHz**

**QPSK 12.5 kHz**




**16QAM 12.5 kHz**




## 64 QAM 12.5 kHz

Agilent 10:16:44 May 2, 2014




## QPSK 25.0 kHz

Agilent 15:15:08 Apr 29, 2014




## 16QAM 25.0 kHz

Agilent 15:40:21 Apr 29, 2014




## 64 QAM 25.0 kHz

Agilent 15:43:32 Apr 29, 2014




## QPSK 50.0 kHz

Agilent 11:28:59 May 2, 2014




## 16QAM 50.0 kHz

Agilent 11:42:53 May 2, 2014



**64 QAM 50.0 kHz**

Agilent 11:44:12 May 2, 2014

**Result:** Complies

EMC  
Technologies

## Transmitter spurious emissions at the antenna terminals

**Nominal Frequency:** 930.525 MHz

Spurious emission (MHz)	Emission level (dBm)	Limit (dBm)
1861.050	-58.9	-13.0
2791.575	<-65.0	-13.0
3722.100	<-70.0	-13.0
4652.625	<-70.0	-13.0
5583.150	<-70.0	-13.0
6513.675	<-70.0	-13.0
7444.200	<-70.0	-13.0
8374.725	<-70.0	-13.0
9305.250	<-70.0	-13.0

**Nominal Frequency:** 940.525 MHz

Spurious emission (MHz)	Emission level (dBm)	Limit (dBm)
1881.050	-59.0	-13.0
2821.575	<-65.0	-13.0
3762.100	<-70.0	-13.0
4702.625	<-70.0	-13.0
5643.150	<-70.0	-13.0
6583.675	<-70.0	-13.0
7524.200	<-70.0	-13.0
8464.725	<-70.0	-13.0
9405.250	<-70.0	-13.0

### Limit:

Applied emission limitations, on any frequency removed from the centre of the authorised bandwidth by a displacement frequency of more than 20 kHz shall be attenuated by at least  $43 + 10 \log(P)$ .

A rated power of 5.0 watts (37.0 dBm) gives a limit of -13 dBm.

The spectrum has been investigated up to the 10<sup>th</sup> harmonic of the transmitter.

Part 2.1051 states that emissions greater than 20 dB below the limit need not be specified.

Part 2.1057 states that the spectrum should be investigated up to the 10<sup>th</sup> harmonic if the transmitter operates below 10 GHz.

**Result:** Complies.

**Measurement Uncertainty:**  $\pm 3.3$  dB

## Field strength of the transmitter spurious emissions

**Nominal Frequency:** 930.525 MHz

Frequency (MHz)	Level (dB $\mu$ V/m)	Level (dBm)	Limit (dBm)	Polarity	Margin (dB)	Result
1861.0500	52.0	-45.4	-20.0	Vertical	25.4	Pass
1861.0500	49.4	-48.0	-20.0	Horizontal	28.0	Pass
2791.5750	41.0	-56.4	-20.0	Vertical	36.4	Pass
2791.5750	41.0	-56.4	-20.0	Horizontal	36.4	Pass
3722.1000	44.0	-53.4	-20.0	Vertical	33.4	Pass
3722.1000	44.0	-53.4	-20.0	Horizontal	33.4	Pass
4652.6250	46.0	-51.4	-20.0	Vertical	31.4	Pass
4652.6250	46.0	-51.4	-20.0	Horizontal	31.4	Pass
5583.1500	48.0	-49.4	-20.0	Vertical	29.4	Pass
5583.1500	48.0	-49.4	-20.0	Horizontal	29.4	Pass
6513.6750	51.0	-46.4	-20.0	Vertical	26.4	Pass
6513.6750	51.0	-46.4	-20.0	Horizontal	26.4	Pass
7444.2000	47.0	-50.4	-20.0	Vertical	30.4	Pass
7444.2000	47.0	-50.4	-20.0	Horizontal	30.4	Pass
8374.7250	48.0	-49.4	-20.0	Vertical	29.4	Pass
8374.7250	48.0	-49.4	-20.0	Horizontal	29.4	Pass
9305.2500	51.0	-46.4	-20.0	Vertical	26.4	Pass
9305.2500	51.0	-46.4	-20.0	Horizontal	26.4	Pass

**Nominal Frequency:** 940.525 MHz

Frequency (MHz)	Level (dB $\mu$ V/m)	Level (dBm)	Limit (dBm)	Polarity	Margin (dB)	Result
1881.0500	52.0	-45.4	-20.0	Vertical	25.4	Pass
1881.0500	48.7	-48.7	-20.0	Horizontal	28.7	Pass
2821.5750	41.0	-56.4	-20.0	Vertical	36.4	Pass
2821.5750	41.0	-56.4	-20.0	Horizontal	36.4	Pass
3762.1000	44.0	-53.4	-20.0	Vertical	33.4	Pass
3762.1000	44.0	-53.4	-20.0	Horizontal	33.4	Pass
4702.6250	46.0	-51.4	-20.0	Vertical	31.4	Pass
4702.6250	46.0	-51.4	-20.0	Horizontal	31.4	Pass
5643.1500	48.0	-49.4	-20.0	Vertical	29.4	Pass
5643.1500	48.0	-49.4	-20.0	Horizontal	29.4	Pass
6583.6750	51.0	-46.4	-20.0	Vertical	26.4	Pass
6583.6750	51.0	-46.4	-20.0	Horizontal	26.4	Pass
7524.2000	47.0	-50.4	-20.0	Vertical	30.4	Pass
7524.2000	47.0	-50.4	-20.0	Horizontal	30.4	Pass
8464.7250	48.0	-49.4	-20.0	Vertical	29.4	Pass
8464.7250	48.0	-49.4	-20.0	Horizontal	29.4	Pass
9405.2500	51.0	-46.4	-20.0	Vertical	26.4	Pass
9405.2500	51.0	-46.4	-20.0	Horizontal	26.4	Pass

In transmit mode the transmitter was tested while transmitting continuously while attached to a dummy load.

The power level of each emission was determined by replacing the transmitter with a dipole antenna that was connected to a signal generator.

The signal generator output level was increased until the same field strength level was observed at each emission frequency.

The level recorded is the signal generator output level in dBm less any gains / losses due to the coax cable and the dipole antenna.

Device was tested on an open area test site at a distance of 3 metres.

**Limit:**


All spurious emissions are to be attenuated by at least  $50 + 10 \log (P)$ .

The rated power of 5.0 watts (37.0 dBm) gives a limit of -20 dBm.

No measurements were made above the 10<sup>th</sup> harmonic.

**Result:** Complies.

**Measurement Uncertainty:**  $\pm 4.1$  dB



## Frequency Stability

Frequency stability measurements were between - 30°C and + 50°C in 10°C increments.

At each temperature the transmitter was given a period of 30 minutes to stabilise.

The transmitter was then turned on and the frequency error measured after a period of 1 minute.

**Nominal Frequency:** 940.525 MHz

### Frequency Error (Hz)

Temperature (°C)	Voltage (10.8 Vdc)	Voltage (13.8 Vdc)	Voltage (15.6 Vdc)
+50	+122.0	+122.0	+124.0
+40	+118.0	+118.0	+120.0
+30	+110.0	+111.0	+113.0
+20	+101.0	+101.0	+102.0
+10	+82.0	+84.0	+85.0
0	+75.0	+73.0	+73.0
-10	+56.0	+56.0	+57.0
-20	+51.0	+52.0	+52.0
-30	+10.0	+12.0	+12.0

### Limit:

Part 24.135 states that transmitters are required to have a frequency tolerance of 1.0 ppm.

This transmitter was tested on 940.525 MHz.

1.0 ppm = 1.0 x = 940.5 Hz.

A worst case error of +124 Hz or 0.132 ppm was observed

**Result:** Complies.

**Measurement Uncertainty:**  $\pm 30$  Hz.

Transmit Frequency 930.525 MHz

Minimum safe distances have been calculated below.

Power density,  $\text{mW/cm}^2 = E^2/3770$

- Occupational / Controlled Exposure limit will be  $3.10 \text{ mW/cm}^2$   
( $f/300 = 930.525 \text{ MHz}/300$ )

- General Population / Uncontrolled exposure limit will be  $0.62 \text{ mW/cm}^2$   
( $f/1500 = 930.525 \text{ MHz}/1500$ )

The minimum distance from the antenna at which the MPE is met is calculated from the equation relating field strength in V/m, transmit power in watts, transmit antenna gain, transmitter duty cycle and separation distance in metres:

$$E, \text{V/m} = (\sqrt{30 * P * G}) / d$$

**Controlled**

$$E = 3.10 \text{ mW/cm}^2 = E^2/3770$$

$$E = \sqrt{3.10 * 3770}$$

$$E = 108.1 \text{ V/m}$$

**Uncontrolled**

$$E = 0.62 \text{ mW/cm}^2 = E^2/3770$$

$$E = \sqrt{0.62 * 3770}$$

$$E = 48.3 \text{ V/m}$$

The rated maximum transmitter power (P) = 5 watts.

Transmitter is operated using an antenna with a gain (G) of up to 631 (+28 dBi).

The client has declared a duty cycle (DC) of 100% (1)

**Controlled**

$$d = \sqrt{30 * P * G * DC} / E$$

$$d = \sqrt{30 * 5 * 631 * 1} / 108.1$$

$$d = 2.84 \text{ metres or } 284 \text{ cm}$$

**Uncontrolled**

$$d = \sqrt{30 * 5 * 631 * 1} / 48.6$$

$$d = 6.33 \text{ metres or } 633 \text{ cm}$$

**Result:** Complies if the safe distances defined for each environment are applied.

## 7. TEST EQUIPMENT USED

Instrument	Manufacturer	Model	Serial #	Asset	Cal Due	Interval
Aerial Controller	EMCO	1090	9112-1062	3710	N/a	N/a
Aerial Mast	EMCO	1070-1	9203-1661	3708	N/a	N/a
Turntable	EMCO	1080-1-2.1	9109-1578	3709	N/a	N/a
VHF Balun	Schwarzbeck	VHA9103	-	3603	12/01/2015	1 year
Biconical	Schwarzbeck	BBA 9106	-	3612	12/01/2015	1 year
Log Periodic	Schwarzbeck	VUSLP 91111	9111-228	3785	12/01/2015	1 year
Horn Antenna	Electrometrics	RGA-60	6234	E1494	04/07/2014	1 year
Receiver	R & S	ESIB-40	100171	EMC4003	29/01/2015	1 year
Power Attenuator	Weinschel	49-20-43	GC104	E1308	N/a	N/a
Power Supply	Hewlett Packard	6032A	2743A-02859	E1069	N/a	N/a
Signal Generator	R & S	SMHU	838923/028	E1493	22/01/2015	1 year
Spectrum Analyzer	Hewlett Packard	E7405A	US39150142	RFS 3776	26/05/2014	1 year
Thermal chamber	Contherm	M180F	86025	E1129	01/06/2014	1 year
Thermometer	DSIR	RT200	035	E1049	01/06/2014	1 year

## 8. ACCREDITATIONS

Testing was carried out in accordance with EMC Technologies NZ Ltd registration with the Federal Communications Commission as a listed facility, Registration Number: 90838, which was last updated in July 2013.

All testing has been carried out in accordance with the terms of EMC Technologies (NZ) Ltd's International Accreditation New Zealand (IANZ) Accreditation to ISO/IEC 17025.

All measurement equipment has been calibrated in accordance with the terms of EMC Technologies (NZ) Ltd's International Accreditation New Zealand (IANZ) Accreditation to ISO/IEC 17025.

International Accreditation New Zealand has Mutual Recognition Arrangements for testing and calibration with various accreditation bodies in a number of economies. This includes NATA (Australia), UKAS (UK), SANAS (South Africa), NVLAP (USA), A2LA (USA), SWEDAC (Sweden). Further details can be supplied on request.



## 9. PHOTOGRAPHS

External photos of the device tested





Labels



## Radiated emissions test set up photos



