

Manufacturer's statement - attestation

The manufacturer; Food Automation – Service Techniques, Inc., as the responsible party for the equipment tested, hereby affirms:

- a) That he has reviewed and concurs that the test shown in this report are reflective of the operational characteristics of the device for which certification is sought;
- b) That the device in this test report will be representative of production units;
- c) That all changes (in hardware and software/firmware) to the subject device will be reviewed.
- d) That any changes impacting the attributes, functionality or operational characteristics documented in this report will be communicated to the body responsible for approving (certifying) the subject equipment.

Stanley Vreeland

Printed name of official



Signature of official

**905 HoneySpot Rd.
Stratford, CT 06615**

Address

08/03/11

Date

203-380-3510

Telephone number

svreeland@fastinc.com

Email address of official

FCC ID: U7JXWIRE-
REPEATER



Report No.:

31053510.001 XWIRE-
REPEATER.doc

Page 1 of 42

Electromagnetic Compatibility Test Report

Prepared in accordance with

FCC Part 15C and ANSI C63.10

On

Wireless Kitchen Management System

Repeater

Food Automation – Service Techniques, Inc. (FAST)
905 Honeyspot Rd
Stratford, CT 06615

Prepared by:

TUV Rheinland of North America, Inc.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

FCC ID: U7JXWIRE-
REPEATER



Report No.:

31053510.001 XWIRE-
REPEATER.doc

Page 2 of 42

Client:	Food Automation – Service Techniques, Inc. (FAST) 905 Honeyspot Rd Stratford, CT 06615		
Identification:	Wireless Kitchen Management System	Serial No.:	0N09224020
Test item:	Repeater	Date tested:	12/2/2010
Testing location:	TUV Rheinland of North America 336 Initiative Drive Rochester, NY 14624 U.S.A.		
Test specification:	Emissions: FCC Part 15 subpart C FCC Part 15.249(a) FCC Part 15.205(a) FCC Part 15.215(a) FCC Part 15.249(a), FCC Part 15.215(c) FCC Part 15.249(3), FCC Part 2.1093,		
Test Result:	The above product was found to be Compliant to the above test standard(s)		
tested by: Randall Masline	reviewed by: Cecil Gittens		
2 February 2011 _____ Date	_____ Name	_____ Signature	2 February 2011 _____ Date
Other Aspects:	None		
Abbreviations: OK, Pass, Compliant, Complies = passed Fail, Not Compliant, Does Not Comply = failed N/A = not applicable			
	 NVLAP Lab Code (200313-0)	Industry Canada	BSMI
US5253		34661C-1	SL2-IN-E-050R

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	SCOPE	4
1.2	PURPOSE	4
1.3	SUMMARY OF TEST RESULTS	5
2	LABORATORY INFORMATION	6
2.1	ACCREDITATIONS & ENDORSEMENTS.....	6
2.2	MEASUREMENT UNCERTAINTY EMISSIONS	7
2.3	CALIBRATION TRACEABILITY	8
2.4	MEASUREMENT EQUIPMENT USED	9
3	PRODUCT INFORMATION	10
3.1	PRODUCT DESCRIPTION.....	10
3.2	EQUIPMENT MODIFICATIONS	10
3.3	TEST PLAN.....	10
4	EMISSIONS.....	12
4.1	RADIATED EMISSIONS	12
4.2	CONDUCTED EMISSIONS.....	16
4.3	FIELD STRENGTH OF FUNDAMENTAL AND HARMONIC EMISSIONS	19
4.4	BAND EDGE REQUIREMENTS.....	31
4.5	FREQUENCY TOLERANCE	34
4.6	RF EXPOSURE MEASUREMENT (MOBILE DEVICE) 15.247(I)	36
APPENDIX A		38
5	TEST PLAN.....	38
5.1	GENERAL INFORMATION	38
5.2	MODEL(S) NAME	38
5.3	TYPE OF PRODUCT	38
5.4	EQUIPMENT UNDER TEST (EUT) DESCRIPTION	39
5.5	MODIFICATIONS	39
5.6	PRODUCT ENVIRONMENT	39
5.7	COUNTRIES	39
5.8	APPLICABLE DOCUMENTS	40
5.9	GENERAL PRODUCT INFORMATION	41
5.10	EUT ELECTRICAL POWERED INFORMATION	41
5.11	EUT MODES OF OPERATION	41
5.12	ELECTRICAL SUPPORT EQUIPMENT	42
5.13	NON - ELECTRICAL SUPPORT EQUIPMENT	42
5.14	EUT EQUIPMENT/CABLING INFORMATION	42

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

1 General Information

1.1 Scope

This report is intended to document the status of conformance with the requirements of the FCC Part 15C and ANSI C63.10 based on the results of testing performed on 12/2/2010 on the Wireless Kitchen Management System, Model No. Repeater, manufactured by Food Automation – Service Techniques, Inc. (FAST). This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

1.2 Purpose

Testing was performed to evaluate the performance of the EUT (Equipment Under Test) in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

1.3 Summary of Test Results

Applicant	Food Automation – Service Techniques, Inc. (FAST) 905 Honeyspot Rd Stratford, CT 06615	Tel	203-380-3510	Contact	Stan Vreeland
		Fax	203-377-8187	e-mail	svreeland@fastinc.com
Description		Wireless Kitchen Management System	Model Number	Repeater	
Serial Number		0N09224020	Test Voltage/Freq.	100-240VAC 50/60Hz	
Test Date Completed:		12/2/2010	Test Engineer	Randall Masline	
Standards		Description	Severity Level or Limit	Criteria	Test Result
FCC Part 15 subpart C Standard		Radio Frequency Devices - Subpart C: Intentional Radiators	See called out parts below	See Below	Complies
FCC Part 15.249(a) FCC Part 15.205(a) FCC Part 15.215(a)		Radiated Emissions Restricted Bands	Class B, 30 - 1000 MHz	Limit	Complies
FCC Part 15.207(a)		Conducted Emissions	Class B, 150kHz - 30MHz	Limit	Complies
FCC Part 15.249(a)		Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz and 24.0-24.25 GHz	50mv/m Fundamental	Limit	Complies
FCC Part 15.215(c)		Band Edge Requirements	Per Section 15.215(c) of the standard	Limit	Complies
FCC Part 15.249(3)		Frequency Tolerance	Carrier Maintained to 0.001% of frequency at -20°C to +50°C	Limit	Complies
FCC Part 2.1093		RF Exposure	MPE or SAR Requirements (Mobile)	Limit	Complies

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

2 Laboratory Information

2.1 *Accreditations & Endorsements*

2.1.1 US Federal Communications Commission (Expires 12/7/2013)

TUV Rheinland of North America located at 336 Initiative Dr, Rochester NY is accredited by the commission for performing testing services for the general public on a fee basis. This laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (Registration No US90575). The laboratory scope of accreditation includes: Title 47 CFR Part 15, and 18. The accreditation is updated every 3 years.

2.1.2 NIST / NVLAP (Expires 6/30/2011)

Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Standard 17025:2005 (Lab code: 200313-0). The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

2.1.3 VCCI

VCCI Accredited test lab. Registration numbers R-1065, C-1120, C-1121

2.1.4 Industry Canada (Expires 1/22/2012)

Registration No.: 3466C-1. The OATS has been accepted by Industry Canada to perform testing to 3 and to 10m, based on the test procedures described in ANSI C63.4-2003.

2.1.5 BSMI

Registration No.: SL2-IN-E-050R. The BSMI accreditation was obtained by NIST MRA with the BSMI.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

2.1.6 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{RAW} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where: RAW = Measured level before correction (dB μ V)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V/m}}{20}}$$

Sample radiated emissions calculation @ 30 MHz

Measurement +Antenna Factor–Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)

$$25 \text{ dBuV/m} + 17.5 \text{ dB} - 20 \text{ dB} + 1.0 \text{ dB} = 23.5 \text{ dBuV/m}$$

2.2 Measurement Uncertainty Emissions

Measurement	<i>U</i> _{lab}	<i>U</i> _{cispr}
Radiated Disturbance @ 10m		
30 MHz – 1000 MHz	4.57 dB	5.2 dB
Conducted Disturbance @ Mains Terminals		
150 kHz – 30 MHz	2.62 dB	3.6 dB
Disturbance Power		
30 MHz – 300 MHz	3.88 dB	4.5 dB

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions measurements is ± 1.6 dB.

The estimated combined standard uncertainty for conducted emissions measurements is ± 1.2 dB.

The expanded uncertainty at a level of 95% confidence is obtained by multiplying the combined standard uncertainty by a coverage factor of 2. Compliance criteria are not based on measurement uncertainty.

2.3 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard 17025:2005. Equipment calibration records are kept on file at the test facility.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

2.4 Measurement Equipment Used

Equipment	Manufacturer	Model #	Ref.	Serial #	Last Cal dd/mm/yy	Next Cal dd/mm/yy	Test
Horn	EMCO	3115	C031	9812-5635	16-Mar-10	16-Mar-12	RE
BiLog	Chase	CBL6111	C041	1170	1-Mar-10	1-Mar-11	RE
EMI Receiver	Rohde & Schwarz	ESVS 30	C310	826006/015	12-Dec-10	12-Dec-11	RE
Analyzer w RF Filter Section 85460A	HP	8546A	C311	3325A00127	28-Jul-10	28-Jul-11	RE, CE
Receiver (20Hz-40GHz)	Rohde & Schwarz	ESI 40	C320	839283/005	11-Dec-10	11-Dec-11	RE,CE
Temp./Humidity Chart Recorder	Honeywell		C419	639971	30-Dec-09	30-Dec-10	RE
Horn	EMCO	3160-09	C447	03-0338-018	17-Nov-10	17-Nov-12	RE
BiLog	Chase	CBL6111B	C448	2081	16-Nov-10	16-Nov-11	RE
Multimeter	Fluke	8062A	C452	4715199	12-Dec-10	12-Dec-11	All tests
Digital Pressure/Temp/RH	Davis	Perception II	C470	PB00218A16	23-Jun-10	23-Jun-11	All tests
Analyzer w RF Filter Section 85460A	HP	8546A	D004	3625A00356	28-Jul-10	28-Jul-11	CE

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

3 Product Information

3.1 Product Description

See Appendix A

3.2 Equipment Modifications

No modifications were needed to bring product into compliance.

3.3 Test Plan

The EUT product information, test configuration, mode of operation, test types, test procedures, test levels, pass/failure criteria, in this report were carried out per the product test plan located in appendix A of this report

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

FCC ID: U7JXWIRE-
REPEATER

 TÜVRheinland®
Precisely Right.

Report No.:

31053510.001 XWIRE-
REPEATER.doc

Page 11 of 42



Figure 1 – External Photo of EUT

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4 Emissions

4.1 Radiated Emissions

This test measures the electromagnetic levels of spurious signals generated by the EUT that radiated from the EUT and may affect the performance of other nearby electronic equipment.

4.1.1 Over View of Test

Results	Complies (as tested per this report)				Date	11/23/2010		
Standard	FCC Part 15.249(a) FCC Part 15.205(a) FCC Part 15.215(a)							
Product Model	Repeater			Serial#	0N09224020			
Configuration	See test plan for details							
Test Set-up	Tested on 10m O.A.T.S. at 3 meters, placed on turn-table, see test plans for details							
EUT Powered By	100-240VAC 50/60Hz	Temp	21°C	Humidity	46%	Pressure	1006mbar	
Frequency Range	30 - 1000 MHz @ 10m							
Perf. Criteria	Class B. (Below Limit)		Perf. Verification	Readings Under Limit				
Mod. to EUT	None		Test Performed By	Randall Masline				

4.1.2 Test Procedure

Radiated and FCC emissions tests were performed using the procedures of ANSI C63.10 including methods for signal maximizations and EUT configuration. The photos included with the report show the EUT in its maximized configuration.

The frequency range from 30 - 1000 MHz was investigated for radiated emissions.

Radiated emission testing was first performed at a distance of 3 meters in the semi-anechoic chamber in order to identify the specific frequencies for which these measurements will be made on the 10 m OATS.

4.1.3 Deviations

There were no deviations from the test methodology listed in the test plan for the radiated emission test.


4.1.4 Final Test

All final radiated emissions measurements were below (in compliance) the limits.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4.1.5 Final Graphs

NOTES:

Radiated Emissions Prescan
Vertical / Horizontal**Repeater low end**


Frequency MHz	Peak dBuV	QP dBuV	Class B-QP dB	Class A-QP dB	Trace Name
176.738	33.7				V - Max hold low end
192.825	34.8				V - Max hold low end
208.912	33.7				V - Max hold low end
224.512	32.9				V - Max hold low end
63.638	26.9				H - Max hold low end
74.362	26.0				H - Max hold low end
99.225	27.6				H - Max hold low end
160.650	29.0				H - Max hold low end

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

NOTES:

Radiated Emissions Prescan
Vertical / Horizontal

Repeater high end



Frequency MHz	Peak dBuV	QP dBuV	Class B-QP dB	Class A-QP dB	Trace Name
208.000	33.4				H - Max hold high end
226.000	31.8				H - Max hold high end
258.000	31.0				H - Max hold high end
274.000	31.8				H - Max hold high end
322.000	32.9				H - Max hold high end
226.000	33.2				V - Max hold high end

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4.1.6 Final Tabulated Data

Radiated Emissions Measurements								
Standard:	Class B/FCC Part 15.209(a)		Final	Date:	11/23/2010			
Device Tested:	FAST XWIRE-REPEATER		3m	File .xls:				
Measured Level								
Meas #	Freq (MHz)	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Δ	Result	Antenna Polarization	Angle (degrees)	Antenna Height (meters)
1	176.7680	31.10	40.00	-8.90	Complied	Horizontal	0	1.00
2	192.8250	31.70	40.00	-8.30	Complied	Horizontal	0	1.00
3	208.9120	31.20	40.00	-8.80	Complied	Horizontal	0	1.00
4	224.5120	30.50	40.00	-9.50	Complied	Horizontal	0	1.00
5	274.0000	28.70	47.00	-18.30	Complied	Horizontal	0	1.00
6	322.0000	29.90	47.00	-17.10	Complied	Horizontal	0	1.00

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4.2 Conducted Emissions

This test measures the electromagnet levels of spurious signals generated by the EUT on the AC power line that may affect the performance of other near by electronic equipment.

4.2.1 Over View of Test

Results	Complies (as tested per this report)			Date	11/23/2010			
Standard	FCC Part 15.249(a) FCC Part 15.205(a) FCC Part 15.215(a)							
Product Model	Repeater			Serial#	0N09224020			
Configuration	See test plan for details							
Test Set-up	Tested in shielded room EUT placed on table see test plans for details							
EUT Powered By	100-240VAC 50/60Hz	Temp	21° C	Humidity	46%	Pressure	1009mbar	
Frequency Range	150kHz - 30MHz							
Perf. Criteria	Class B (Below Limit)	Perf. Verification		Readings Under Limit for L1 & Neutral				
Mod. to EUT	None	Test Performed By		Randall Masline				

4.2.2 Test Procedure

Conducted and FCC emissions tests were performed using the procedures of ANSI C63.10 including methods for signal maximizations and EUT configuration. The photos included with the report show the EUT in its maximized configuration.

The frequency range from 150kHz - 30MHz was investigated for conducted emissions.

Conducted Emissions measurements were performed in the shielded room using procedures specified in the test plan and standard.

4.2.3 Deviations

There were no deviations from the test methodology listed in the test plan for the conducted emission test.

4.2.4 Final Test

All final conducted emissions measurements were below (in compliance) the limits.


The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4.2.5 Final Graphs

NOTES:

Conducted Emissions @ 120V/60Hz
Line / Neutral

Neutral - Repeater




Frequency MHz	Peak dBuV	QP dBuV	Delta QP-QP dB	Avg dBuV	Delta Avg-Avg dB	Transducer Correction dB	Cable Correction dB
0.469	37.3	36.2	-20.3	35.6	-10.9	-0.1	10.1
0.536	33.7	32.7	-23.3	32.4	-13.6	-0.3	10.1
2.412	38.5	36.9	-19.1	31.6	-14.4	-0.1	10.4
2.478	38.3	37.1	-18.9	31.9	-14.1	-0.1	10.4
2.545	38.5	36.8	-19.2	31.6	-14.4	-0.1	10.4
2.612	37.9	35.9	-20.1	30.5	-15.5	-0.1	10.4

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

NOTES:

Conducted Emissions @ 120V/60Hz
Line / Neutral

Line 1 - Repeater



Frequency MHz	Peak dBuV	QP dBuV	Delta QP-QP Limit dB	Avg dBuV	Delta Avg-Avg Limit dB	Transducer Correction dB	Cable Correction dB
0.202	42.3	40.6	-22.9	34.6	-19.0	-0.1	10.1
0.334	39.4	38.5	-20.9	36.3	-13.0	-0.1	10.1
0.469	39.3	38.3	-18.2	37.6	-8.9	-0.1	10.1
2.411	41.4	38.2	-17.8	28.9	-17.1	-0.1	10.4
2.544	41.9	39.9	-16.1	29.5	-16.5	-0.1	10.4
2.679	40.1	37.6	-18.4	26.9	-19.1	-0.1	10.4

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4.3 Field Strength of Fundamental and Harmonic Emissions

This test measures the electromagnetic levels of fundamental and spurious signals generated by the EUT that radiated from the EUT.

4.3.1 Test Over View

Results	Complies (as tested per this report)				Date	12/2/2010			
Standard	FCC Part 15.249(a)								
Product Model	Repeater			Serial#	0N09224020				
Configuration	See test plan for details								
Test Set-up	Tested at O.A.T.S.		EUT placed on table		See test plan for details				
EUT Powered By	100-240VAC 50/60Hz	Temp	22° C	Humidity	47%	Pressure	996mbar		
Perf. Criteria	50mv/m (Below Limit)		Perf. Verification	Readings under Limit					
Mod to EUT	None		Test Performed By	Randall Masline					

4.3.2 Test Procedure

Field Strength and FCC emissions tests were performed using the procedures of ANSI C63.10 including methods for signal maximizations and EUT configuration. The photos included with the report show the EUT in its maximized configuration.

Radiated emission testing measurements will be made on the 10 m OATS, at a 3m distance.

4.3.3 Deviations


There were no deviations from the test methodology listed in the test plan for the radiated emission test.

4.3.4 Final Test

All final radiated emissions measurements were below (in compliance) the limits.

The highest average measurement was made on channel 3 in the horizontal polarization at 93.3 dBuV at 2480.28056 MHz. The limit is 94dBuV

4.3.5 Final Data



Date: 2.DEC.2010 16:56:20

Figure 2 – Channel 1 Horizontal

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.





Figure 3 – Channel 1 Vertical


The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Date: 2.DEC.2010 17:00:40

Figure 4 – Channel 2 Horizontal


The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Date: 2.DEC.2010 17:01:39

Figure 5 – Channel 2 Vertical


The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Date: 2.DEC.2010 17:05:39

Figure 6 – Channel 3 Horizontal

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Date: 2.DEC.2010 17:04:13

Figure 7 – Channel 3 Vertical

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Ref Lvl
72 dB_{VV}

Marker 1 [T1]

64.80 dB_{VV}

2.40280561 GHz

RBW

1 MHz

RF Att

0 dB

VBW


1 MHz

SWT

12.5 ms

Unit


dB_{VV}



Date: 17.JAN.2011 11:36:24

Figure 8 – 1 to 6 GHz


The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Date: 17.JAN.2011 11:34:58

Figure 9 – 6 to 12 GHz


The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Date: 17.JAN.2011 11:33:57

Figure 10 – 12 to 18 GHz


The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Date: 17.JAN.2011 13:46:28

Figure 11 – 18 to 20 GHz

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Date: 17.JAN.2011 13:47:29

Figure 12 – 20 to 25 GHz

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4.4 Band Edge Requirements

The requirement is to ensure the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified, is contained within the frequency band designated in the rule section under which the equipment is operated. The designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperatures and supply voltage.

4.4.1 Test Over View

Results	Complies (as tested per this report)				Date	12/2/2010							
Standard	FCC Part 15.215(c)												
Product Model	Repeater		Serial#	0N09224020									
Configuration	See test plan for details												
Test Set-up	Tested in shielded room EUT placed on table See test plan for details												
EUT Powered By	100-240VAC 50/60Hz	Temp	22° C	Humidity	47%	Pressure	996mbar						
Perf. Criteria	Per Section 15.215(c) of the standard		Perf. Verification	Readings within the permitted band									
Mod to EUT	None		Test Performed By	Randall Masline									

4.4.2 Test Procedure

The measurement will be made using guidance from ANSI C63.10.

4.4.3 Deviations


There were no deviations from the test methodology.

4.4.4 Final Test

The band edge requirements of the EUT were within the limits specified in the standard.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.


4.4.5 Band Edge Requirement Data



Date: 2.DEC.2010 17:06:24

Figure 13 – Upper Band Edge

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Date: 2.DEC.2010 16:54:59

Figure 14 – Lower Band Edge

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4.5 Frequency Tolerance

4.5.1 Test Over View

Results	Complies (as tested per this report)			Date	12/2/2010						
Standard	FCC Part 15.249(3)										
Product Model	Repeater		Serial#	0N09224020							
Configuration	See test plan for details										
Test Set-up	Tested in 3m chamber EUT placed on table See test plan for details										
EUT Powered By	100-240VAC 50/60Hz	Temp	22° C	Humidity	47%	Pressure					
Mod to EUT	None		Test Performed By	Randall Masline							

4.5.2 Test Procedure

The frequency tolerance of the carrier signal shall be maintained within +/- 0.001% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment test shall be performed using a new battery.

4.5.3 Deviations

There were no deviations from the test methodology listed in the test plan for the Radiated Immunity test.

4.5.4 Final Test

The EUT met the performance criteria requirement as specified in the test plan of this report and in the standards.

4.5.5 Final Data

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Test	Frequency (GHz)	Allowable Deviation (MHz)	Result
-20 Degrees C at nominal	2.47967976	2.400	Complies
+50 Degrees C at nominal	2.48028080	2.400	Complies
Nominal Voltage 120VAC/60Hz	2.48028056	2.400	Complies
85% - 102 VAC	2.480028050	2.400	Complies
115% - 138 VAC	2.480028050	2.400	Complies

Table 1 – Frequency Tolerance

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4.6 RF Exposure Measurement (Mobile Device)

4.6.1 Test Methodology

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Semi-Anechoic Chamber, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula (see section 4.9.6) and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

4.6.2 RF Exposure Limit

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	$f / 1500$	6
1500-100,000	1.0	30

f = Frequency in MHz

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

4.6.3 EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit data at lowest, middle and highest channel individually.

4.6.4 Classification

The antenna of the product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. Therefore, this device is classified as a **Mobile Device**.

4.6.5 Test Results

4.6.6 Antenna Gain

The maximum Gain measured in Semi-Anechoic Chamber is 0.0 dBi or 1.0 (numeric).

4.6.7 Output Power into Antenna & RF Exposure value at distance 20cm:

Calculations for this report are based on highest power measurement and the highest gain of the antenna. Limit for MPE (from FCC part 1.1310 table 1) is f (MHz) / 1500 = 927.6 / 1500 = 0.62 mW/cm²

Highest Pout is 0.04mW, highest antenna gain (in linear scale) is 1.0, R is 20cm, and f = 2400 MHz

$Pd = (0.04 * 1.0) / (1600\pi) = \underline{0.007 \text{ mW/cm}^2}$, which is 0.613 mW/cm² below to the limit.

Note: This calculation is assuming 100% duty cycle, which would not be the case in normal operation.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

4.6.8 Sample Calculation

The Friis transmission formula: $Pd = (Pout * G) / (4 * \pi * R^2)$

Where:

Pd = power density in mW/cm²

$Pout$ = output power to antenna in mW

G = gain of antenna in linear scale

$\pi \approx 3.1416$

R = distance between observation point and center of the radiator in cm

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition, Page 640, Eq. (11-133).

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Appendix A

5 Test Plan

This test report is intended to follow this test plan outlined here in unless other wise stated in this here report. The following test plan will give details on product information, standards to be used, test set ups and refer to TUV test procedures. The test procedures will give the steps to be taken when performing the stated test. The product information below came via client, product manual, product itself and or the internet.

5.1 General Information

Client	Food Automation – Service Techniques, Inc. (FAST)
Address 1	905 Honeyspot Rd
Address 2	Stratford, CT 06615
Contact Person	Stan Vreeland
Telephone	203-380-3510
Fax	203-377-8187
e-mail	svreeland@fastinc.com

5.2 Model(s) Name

Repeater

5.3 Type of Product

Wireless Kitchen Management System

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

5.4 Equipment Under Test (EUT) Description

Food quality and supply chain monitor equipment.

5.5 Modifications

No modifications were necessary to meet compliance with regulations.

5.6 Product Environment

<input type="checkbox"/>	Residential	<input type="checkbox"/>	Hospital
<input checked="" type="checkbox"/>	Light Industrial	<input type="checkbox"/>	Small Clinic
<input checked="" type="checkbox"/>	Industrial	<input type="checkbox"/>	Doctor's office
<input type="checkbox"/>	Other		

*Check all that apply

5.7 Countries

<input checked="" type="checkbox"/>	USA
<input type="checkbox"/>	Canada

*Check all that apply

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

5.8 Applicable Documents

Standards	Description
FCC Part 15 subpart C Standard	Radio Frequency Devices - Subpart C: Intentional Radiators
FCC Part 15.249(a) FCC Part 15.205(a) FCC Part 15.215(a)	Radiated Emissions
FCC Part 15.207(a)	Conducted Emissions
FCC Part 15.249(a)	Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz and 24.0-24.25 GHz
FCC Part 15.215(c)	Band Edge Requirements
FCC Part 15.249(3)	Frequency Tolerance
FCC Part 2.1093	RF Exposure

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

5.9 General Product Information

Size	H	5.5cm	W	4cm	L	13cm
Weight		0.145 kg	Fork-Lift Needed		No	
Notes						

5.10 EUT Electrical Powered Information

5.10.1 Electrical Power Type

<input checked="" type="checkbox"/>	AC	<input type="checkbox"/>	DC	<input type="checkbox"/>	Batteries	<input type="checkbox"/>	Host -
-------------------------------------	----	--------------------------	----	--------------------------	-----------	--------------------------	--------

5.10.2 Electrical Power Information

Name	Type	Voltage		Frequency	Current	Notes
		min	max			
Mains	AC	100	240	50/60		
Notes						

5.11 EUT Modes of Operation

Transmitting at highest, lowest and middle channel at highest output power.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

5.12 Electrical Support Equipment

Type	Manufacture	Model	Connected To
None			

5.13 Non - Electrical Support Equipment

Item	Notes
Gas	None
Water	None

5.14 EUT Equipment/Cabling Information

EUT Port	Connected To	Location	Cable Type		
			Length	Shielded	Bead
Power	AC Mains	Bottom		No	No

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.