

RF Exposure / MPE Calculation

No. : 12608632H-C
Applicant : MITSUBISHI ELECTRIC CORPORATION
SANDA WORKS
Type of Equipment : Display Audio
Model No. : R1 LOW
FCC ID : UJHR1LOW
*WLAN 5 GHz Part

MITSUBISHI ELECTRIC CORPORATION SANDA WORKS declares that Model: R1 LOW complies with FCC radiation exposure requirement specified in the FCC Rule 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "R1 LOW" as calculated from (B) Limits for General Population / Uncontrolled Exposure of TABLE 1- LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) of §1.1310 Radiofrequency radiation exposure limits.

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = \frac{P \times G}{4 \times \pi \times r^2}$$

Where

P = 4.36 mW (Maximum average output power)

Time average was used for the above value in consideration of 6-minutes time-averaging
 Burst power average was used for the above value in consideration of worst condition.

G = 3.690 Numerical Antenna gain; equal to 5.67 dBi

r = 20 cm (Separation distance)

Power Density Result $S = 0.00320 \text{ mW/cm}^2$

Even taking into account the tolerance, this device can be satisfied with the limits.

**UL Japan, Inc.
Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999
Facsimile : +81 596 24 8124

Reference:**[Bluetooth Low Energy part (WiFi / BLE module: QCA6574AU)]**

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = \frac{P \times G}{4 \times \pi \times r^2}$$

Where

P = 0.64 mW (Maximum average output power)

- Time average was used for the above value in consideration of 6-minutes time-averaging
- Burst power average was used for the above value in consideration of worst condition.

G = 1.449 Numerical Antenna gain; equal to 1.61 dBi

r = 20 cm (Separation distance)

Power Density Result $S = 0.00018 \text{ mW/cm}^2$

Reference:**[Bluetooth Low Energy part (BLE chip: CC2640R2F)]**

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = \frac{P \times G}{4 \times \pi \times r^2}$$

Where

P = 1.02 mW (Maximum average output power)

- Time average was used for the above value in consideration of 6-minutes time-averaging
- Burst power average was used for the above value in consideration of worst condition.

G = 1.449 Numerical Antenna gain; equal to 1.61 dBi

r = 20 cm (Separation distance)

Power Density Result $S = 0.00029 \text{ mW/cm}^2$

Reference:**[Bluetooth part]**

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = \frac{P \times G}{4 \times \pi \times r^2}$$

Where

$P = 0.55$ mW (Maximum average output power)

Time average was used for the above value in consideration of 6-minutes time-averaging

Burst power average was used for the above value in consideration of worst condition.

$G = 1.449$ Numerical Antenna gain; equal to 1.61 dBi

$r = 20$ cm (Separation distance)

$$\text{Power Density Result } S = 0.00016 \text{ mW/cm}^2$$

Therefore, if WLAN 5GHz and Bluetooth Low Energy (WiFi / BLE module: QCA6574AU) transmit simultaneously,

$$\begin{aligned} S &= 0.00320 \text{ mW/cm}^2 + 0.00018 \text{ mW/cm}^2 \\ &= 0.000338 \text{ mW/cm}^2 \end{aligned}$$

Therefore, if WLAN 5GHz and Bluetooth transmit simultaneously,

$$\begin{aligned} S &= 0.00320 \text{ mW/cm}^2 + 0.00016 \text{ mW/cm}^2 \\ &= 0.00336 \text{ mW/cm}^2 \end{aligned}$$

Even taking into account the tolerance, this device can be satisfied with the limits.

* Bluetooth Low Energy (BLE chip: CC2640R2F) and WiFi / BLE module do not transmit simultaneously.

**UL Japan, Inc.
Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999
Facsimile : +81 596 24 8124