



47 CFR PART 15 SUBPART C - WI-FI

TEST REPORT

of

GSM/WCDMA mobile phone

Model Name: Perai-H
Brand Name: TechFaith
Report No.: SZ07060024E09
FCC ID: UJQ-09438T

prepared for

TechFaith Wireless Technology Group Limited.

No. 10A, Tower D2, IT Park, Electronic Town, Jiu Xian Qiao North Road,
Chao Yang District, Beijing, China (100015)

Shenzhen Electronic Product Quality Testing Center

Morlab Laboratory

3/F, Electronic Testing Building, Shahe Road, Xili,
Nanshan District, Shenzhen, 518055 P.R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.

TABLE OF CONTENTS

1.	TEST CERTIFICATION	4
2.	GENERAL INFORMATION	5
2.1	EUT Description	5
2.2	Test Standards and Results	6
2.3	Facilities and Accreditations	7
2.3.1	Facilities	7
2.3.2	Test Environment Conditions	7
3.	47 CFR PART 15C REQUIREMENTS	8
3.1	Peak Output Power	8
3.1.1	Requirement	8
3.1.2	Test Description	8
3.1.3	Test Result	9
3.2	20dB Bandwidth	13
3.2.1	Definition	13
3.2.2	Test Description	13
3.2.3	Test Result	13
3.3	Conducted Spurious Emissions	17
3.3.1	Requirement	17
3.3.2	Test Description	17
3.3.3	Test Result	17
3.4	Band Edge	24
3.4.1	Requirement	24
3.4.2	Test Description	24
3.4.3	Test Result	24
3.5	Conducted Emission	28
3.5.1	Requirement	28
3.5.2	Test Description	28
3.5.3	Test Result	29
3.6	Radiated Emission	32
3.6.1	Requirement	32



3.6.2	Test Description	32
3.6.3	Test Result.....	34

1. TEST CERTIFICATION

Equipment under Test: GSM/WCDMA mobile phone

Brand Name: TechFaith

Model Name: Perai-H

FCC ID: UJQ-09438T

Applicant: TechFaith Wireless Technology Group Limited.

No. 10A, Tower D2, IT Park, Electronic Town, Jiu Xian Qiao
North Road, Chao Yang District, Beijing, China (100015)

Manufacturer: TechFaith Wireless Technology Group Limited.

No. 10A, Tower D2, IT Park, Electronic Town, Jiu Xian Qiao
North Road, Chao Yang District, Beijing, China (100015)

Test Standards: 47 CFR Part 15 Subpart C

Test Date(s): July 25, 2007 – August 23, 2007

Test Result: PASS

* We Hereby Certify That:


The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by: Luo Biao Dated: 2007.08.23
Luo Biao

Reviewed by: Wei Yanquan Dated: 2007.08.23
Wei Yanquan

Approved by: Zeng Dexin Dated: 2007.08.23
Zeng dexin



2. GENERAL INFORMATION

2.1 EUT Description

EUT Type.....: GSM/WCDMA mobile phone
(Wi-Fi Module embedded)

Model Name: Perai-H

Serial No.....: (n.a, marked #1 by test site)

IMEI: 355792015105151

Modulation Type.....: DSSS

Frequency: The frequency range used is 2412MHz - 2462MHz (11 channels, at intervals of 5MHz);
The frequency block is 2400MHz to 2483.5MHz.

Power Supply.....: Battery

Brand name: XWORD

Mode no.: US454261A8T

Capacitance: 1500mAh

Rated voltage: 3.7V

Charge limited: 4.2V

Manufacturer: XWORD

Manufacturer Address: (n.a)

Ancillary Equipments.....: AC Adapter (Charger for Battery)

Model Name: MPW0508

Brand Name: TAMURA

Serial No.: (n.a. marked #1 by test site)

Rated Input: ~ 100-240V, 0.2A, 50/60Hz

Rated Output: = 5V, 800mA

Manufacturer: (n.a)

Wire Length: 105cm

Note 1: The EUT is a Mobile Phone, it contains Wi-Fi Module operating at 2.4GHz ISM band; the frequencies allocated for the Wi-Fi Module is $F(\text{MHz})=2412+5*(n-1)$ ($1 \leq n \leq 11$). The lowest, middle, highest channel numbers of the Wi-Fi Module used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).

Note 2: The EUT is supporting IEEE 802.11b/g protocols, IEEE 802.11b and IEEE 802.11g protocols are tested in this report.

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Wi-Fi, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-05 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.247(a)	Number of Hopping Frequency	(n.a)
2	15.247(b)	Peak Output Power	PASS
3	15.247(a)	20dB Bandwidth	PASS
4	15.247(a)	Carrier Frequency Separation	(n.a)
5	15.247(a)	Time of Occupancy (Dwell time)	(n.a)
6	15.247(c)	Conducted Spurious Emission	PASS
7	15.247(c)	Band Edge	PASS
8	15.207	Conducted Emission	PASS
9	15.209 15.247(c)	Radiated Emission	PASS

2.3 Facilities and Accreditations

2.3.1 Facilities

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Board for Laboratories (CNAL) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	20 - 25
Relative Humidity (%):	40 - 60
Atmospheric Pressure (kPa):	960

3. 47 CFR PART 15C REQUIREMENTS


3.1 Peak Output Power

3.1.1 Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.1.2 Test Description

A. Test Setup:



The Wi-Fi Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Wi-Fi Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Wi-Fi Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Service Simulator	Agilent	E5515C	GB43130131	2007.06	1year
Spectrum Analyzer	Agilent	E7405A	US44210471	2007.07	1year
Power Splitter	Weinschel	1506A	NW521	(n.a.)	(n.a.)
Attenuator 1	Resnet	20dB	(n.a.)	(n.a.)	(n.a.)
Attenuator 2	Resnet	3dB	(n.a.)	(n.a.)	(n.a.)

3.1.3 Test Result


3.1.3.1 IEEE 802.11b protocols

The Wi-Fi Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.


A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power			Limit		Verdict
		dBm	W	Refer to Plot	dBm	W	
1	2412	18.07	0.064	Plot A	21	0.125	PASS
6	2437	18.06	0.064	Plot B			PASS
11	2462	17.94	0.062	Plot C			PASS


B. Test Plot:



(Plot A: Channel = 2412)



(Plot B: Channel = 2437)



(Plot C: Channel = 2462)

3.1.3.2 IEEE 802.11g protocols


The Wi-Fi Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

A. Test Verdict:


Channel	Frequency (MHz)	Measured Output Peak Power	Limit	Verdict
---------	-----------------	----------------------------	-------	---------

		dBm	W	Refer to Plot	dBm	W	
1	2412	19.30	0.085	Plot A	21	0.125	PASS
6	2437	19.62	0.092	Plot B			PASS
11	2462	19.60	0.091	Plot C			PASS


B. Test Plot:



(Plot A: Channel = 2412)



(Plot B: Channel = 2437)



(Plot C: Channel = 2462)

3.2 20dB Bandwidth

3.2.1 Definition

The 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth ($10 \cdot \log 1\% = 20\text{dB}$) taking the total RF output power.

3.2.2 Test Description

See section 3.1.2 of this report.

3.2.3 Test Result

3.2.3.1 IEEE 802.11b protocols


The Wi-Fi Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to record the 20dB bandwidth of the Module.

A. Test Verdict:


The maximum 20dB bandwidth measured is 1.02MHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
1	2412	0.041	Plot A
6	2437	0.041	Plot B
11	2462	0.041	Plot C


B. Test Plot:



(Plot A: Channel = 2412)



(Plot B: Channel = 2437)



(Plot C: Channel = 2462)

3.2.3.2 IEEE 802.11g protocols


A. Test Verdict:

The maximum 20dB bandwidth measured is 1.02MHz according to the table below.


Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
---------	-----------------	----------------------	---------------

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
1	2412	0.041	Plot A
6	2437	0.041	Plot B
11	2462	0.041	Plot C


B. Test Plot:



(Plot A: Channel = 2412)



(Plot B: Channel = 2437)



(Plot C: Channel = 2462)

3.3 Conducted Spurious Emissions

3.3.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.3.2 Test Description

See section 3.1.2 of this report.

3.3.3 Test Result

The Wi-Fi Module operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.


3.3.3.1 IEEE 802.11b protocols

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2412	---	Plot A.1/A.2	17.94	-2.06	PASS
6	2437	---	Plot B.1/B.2	18.06	-1.94	PASS
11	2462	---	Plot C.1/C.2	18.07	-1.93	PASS

B. Test Plot:


Note: the power of the Module transmitting frequency should be ignored.




(Plot A.1: Channel = 1, 30MHz to 3GHz)




(Plot A.2: Channel = 1, 3GHz to 25GHz)




(Plot B.1: Channel = 6, 30MHz to 3GHz)



(Plot B.2: Channel = 6, 3GHz to 25GHz)



(Plot C.1: Channel = 11, 30MHz to 3GHz)



(Plot C.2: Channel = 11, 3GHz to 25Gz)

3.3.3.2 IEEE 802.11g protocols


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2412	---	Plot A.1/A.2	19.43	-0.57	PASS
6	2437	---	Plot B.1/B.2	19.75	-0.25	PASS
11	2462	---	Plot C.1/C.2	19.65	-0.35	PASS

B. Test Plot:


Note: the power of the Module transmitting frequency should be ignored.




(Plot A.1: Channel = 1, 30MHz to 3GHz)




(Plot A.2: Channel = 1, 3GHz to 25GHz)




(Plot B.1: Channel = 6, 30MHz to 3GHz)



(Plot B.2: Channel = 6, 3GHz to 25GHz)



(Plot C.1: Channel = 11, 30MHz to 3GHz)



(Plot C.2: Channel = 11, 3GHz to 25GHz)

3.4 Band Edge

3.4.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.4.2 Test Description

See section 3.1.2 of this report.

3.4.3 Test Result

The Wi-Fi Module operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.


3.4.3.1 IEEE 802.11b protocols

A. Test Verdict:


Note: {Marker Delta} = {Carrier Level} - {Max. Band Edge Power}.

Channel	Frequency (MHz)	Max. Band Edge		Carrier Level (dBm)	-20dBc Limit (dBm)	Marker Delta (dB)	Refer to Plot	Verdict
		Power (dBm)	@Frequency (MHz)					
1	2412	-28.55	2411.9	17.62	-2.38	26.17	Plot A	PASS
11	2462	-28.09	2462.1	17.93	-2.07	26.02	Plot B	PASS

B. Test Plot:



(Plot A: Channel = 1)



(Plot B: Channel = 11)


3.4.3.2 IEEE 802.11g protocols

A. Test Verdict:


Note: {Marker Delta} = {Carrier Level} - {Max. Band Edge Power}.

Channel	Frequency (MHz)	Max. Band Edge		Carrier Level (dBm)	-20dBc Limit (dBm)	Marker Delta (dB)	Refer to Plot	Verdict
		Power (dBm)	@Frequency (MHz)					
1	2412	-31.14	2409.15	17.61	-2.39	48.75	Plot A	PASS
11	2462	-34.28	2476.20	17.16	-2.84	51.44	Plot B	PASS

B. Test Plot:



(Plot A: Channel = 1)



(Plot B: Channel = 13)

3.5 Conducted Emission

3.5.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.5.2 Test Description

A. Test Setup:



The Wi-Fi Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The factors of the site are calibrated to correct the reading. During the measurement, the Wi-Fi Module is activated and controlled by the Wi-Fi Service Supplier

(SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2007.07	1year
LISN	Schwarzbeck	NSLK 8127	812744	2006.08	1year
Service Supplier	R&S	CMU200	100448	2007.10	1year
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)	(n.a.)

3.5.3 Test Result


The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

3.5.3.1 IEEE 802.11b protocols


A. Test Verdict Recorded for Suspicious Points:

No.	@Frequency (MHz)	Measured Emission Level (dBμV)				Limit (dBμV)		Verdict
		PK	QP	AV	Phase	QP	AV	
1	0.617	45.20	43.30	31.60	N	56.00	46.00	PASS
2	0.757	44.10	42.00	32.50	N	56.00	46.00	PASS
3	29.332	46.20	40.60	27.30	N	60.00	50.00	PASS
4	0.616	45.00	43.30	31.20	L	56.00	46.00	PASS
5	29.485	44.90	38.70	28.00	L	60.00	50.00	PASS

B. Test Plot:



(Plot A: N Phase)



(Plot B: L Phase)


3.5.3.2 IEEE 802.11g protocols

A. Test Verdict Recorded for Suspicious Points:


No.	@Frequency (MHz)	Measured Emission Level (dBμV)				Limit (dBμV)		Verdict
		PK	QP	AV	Phase	QP	AV	
1	0.587	46.31	---	---	N	56.00	46.00	PASS
2	0.614	46.21	---	---	N	56.00	46.00	PASS
3	0.763	45.98	---	---	N	56.00	46.00	PASS
4	2.859	46.70	---	---	N	56.00	46.00	PASS
5	29.332	46.20	40.60	27.30	N	60.00	50.00	PASS

No.	@Frequency (MHz)	Measured Emission Level (dB μ V)				Limit (dB μ V)		Verdict
		PK	QP	AV	Phase	QP	AV	
6	0.616	45.00	43.30	31.20	L	56.00	46.00	PASS
7	29.485	44.80	38.65	27.78	L	60.00	50.00	PASS

B. Test Plot:



(Plot A: N Phase)



(Plot B: L Phase)

3.6 Radiated Emission

3.6.1 Requirement

According to FCC section 15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).


According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

3.6.2 Test Description

A. Test Setup:



The Wi-Fi Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Wi-Fi Module is activated and controlled by the Wireless Router via a Common Antenna, and is set to operate under hopping-on test mode.

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	100448	2007.10	1year
Receiver	Agilent	E7405A	US44210471	2007.07	1year
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2006.08	2year
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2007.07	1year
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2007.07	1year

3.6.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors.

3.6.3.1 IEEE 802.11b protocols

A. Test Verdict for Harmonics:

The Fundamental Emissions

The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

Channel	Frequency (MHz)	Fundamental Emission (dBμV/m)		Antenna Polarization	Refer to Plot
		PK	AV		
1	2412	84.03	68.87	Horizontal	Plot A.3
		87.97	72.41	Vertical	Plot A.7
6	2437	83.49	67.60	Horizontal	Plot B.3
		88.11	72.86	Vertical	Plot B.7
11	2462	83.69	67.67	Horizontal	Plot C.3
		88.52	72.32	Vertical	Plot C.7

Band Edge Emissions Fall in the Restricted Bands

The field strength of band edge emission falling in adjacent restricted bands (2310MHz - 2390MHz, and 2483.5MHz - 2500MHz) per FCC section 15.205(a) is calculated via the "Marker-Delta" method:

$$\{\text{Max. Band Edge Emission}\} = \{\text{Fundamental Emission}\} - \{\text{Marker Delta}\}$$

In the formula above, refer to section 3.4.3 for the {Marker Delta}. The calculation results in the table below show the compliance with the radiated emission limits specified in FCC section 15.209(a).

CH	Freq. (MHz)	Fundamental Emission		Max. Band Edge			Limit (dBμV/m)	Verdict
		dBμV/m	Detector	@Freq. (MHz)	Marker Delta (dB)	Emission (dBμV/m)		
1	2412	87.97	PK	2400.00	41.02	46.95	74	PASS
		72.41	AV			31.39	54	PASS
11	2462	88.52	PK	2484.00	44.89	43.63	74	PASS
		72.32	AV			27.43	54	PASS

The Radiated Emissions Fall in the Restricted Bands


Channel	Frequency (MHz)	Antenna Polarization	Max. Emission in the Restricted Bands (dBμV/m)		Limit (dBμV/m)		Verdict
			PK	AV	PK	AV	

Channel	Frequency (MHz)	Antenna Polarization	Max. Emission in the Restricted Bands (dB μ V/m)		Limit (dB μ V/m)		Verdict
			PK	AV	PK	AV	
1	2412	Vertical	---	---	74	54	PASS
		Horizontal	---	---	74	54	PASS
6	2437	Vertical	---	---	74	54	PASS
		Horizontal	---	---	74	54	PASS
11	2462	Vertical	---	---	74	54	PASS
		Horizontal	---	---	74	54	PASS


Also refer to following plots for the emissions falling in the restricted bands.

B. Test Plot for the Whole Measurement Frequency Range:


Plots for Channel = 1




(Plot A.1: 9kHz to 30MHz)




(Plot A.2: Antenna Horizontal, 30MHz to 1GHz)




(Plot A.3: Antenna Horizontal, 1GHz to 7GHz)




(Plot A.4: Antenna Horizontal, 7GHz to 18GHz)




(Plot A.5: Antenna Horizontal, 18GHz to 25GHz)




(Plot A.6: Antenna Vertical, 30MHz to 1GHz)



(Plot A.7: Antenna Vertical, 1GHz to 7GHz)




(Plot A.8: Antenna Vertical, 7GHz to 18GHz)




(Plot A.9: Antenna Vertical, 18GHz to 25GHz)


Plot for Channel = 6




(Plot B.1: 9kHz to 30MHz)




(Plot B.2: Antenna Horizontal, 30MHz to 1GHz)




(Plot B.3: Antenna Horizontal, 1GHz to 7GHz)




(Plot B.4: Antenna Horizontal, 7GHz to 18GHz)




(Plot B.5: Antenna Horizontal, 18GHz to 25GHz)




(Plot B.6: Antenna Vertical, 30MHz to 1GHz)



(Plot B.7: Antenna Vertical, 1GHz to 7GHz)




(Plot B.8: Antenna Vertical, 7GHz to 18GHz)




(Plot B.9: Antenna Vertical, 18GHz to 25GHz)


Plot for Channel = 11




(Plot C.1: 9kHz to 30MHz)




(Plot C.2: Antenna Horizontal, 30MHz to 1GHz)




(Plot C.3: Antenna Horizontal, 1GHz to 7GHz)




(Plot C.4: Antenna Horizontal, 7GHz to 18GHz)




(Plot C.5: Antenna Horizontal, 18GHz to 25GHz)




(Plot C.6: Antenna Vertical, 30MHz to 1GHz)



(Plot C.7: Antenna Vertical, 1GHz to 7GHz)



(Plot C.8: Antenna Vertical, 7GHz to 18GHz)



(Plot C.9: Antenna Vertical, 18GHz to 25GHz)

3.6.3.2 IEEE 802.11g protocols

A. Test Verdict for Harmonics:

The Fundamental Emissions

The field strength of {Fundamental Emission} listed below is recorded, and used in the next table.

Channel	Frequency (MHz)	Fundamental Emission (dBμV/m)		Antenna Polarization	Refer to Plot
		PK	AV		
1	2412	82.45	67.84	Horizontal	Plot A.3
		83.12	70.15	Vertical	Plot A.7
6	2437	80.11	66.53	Horizontal	Plot B.3
		83.24	70.29	Vertical	Plot B.7
11	2462	83.69	67.44	Horizontal	Plot C.3
		84.64	70.87	Vertical	Plot C.7

Band Edge Emissions Fall in the Restricted Bands

The field strength of band edge emission falling in adjacent restricted bands (2310MHz - 2390MHz, and 2483.5MHz - 2500MHz) per FCC section 15.205(a) is calculated via the "Marker-Delta" method:

$$\{\text{Max. Band Edge Emission}\} = \{\text{Fundamental Emission}\} - \{\text{Marker Delta}\}$$

In the formula above, refer to section 3.4.3 for the {Marker Delta}. The calculation results in the table below show the compliance with the radiated emission limits specified in FCC section 15.209(a).

CH	Freq. (MHz)	Fundamental Emission		Max. Band Edge			Limit (dBμV/m)	Verdict
		dBμV/m	Detector	@Freq. (MHz)	Marker Delta (dB)	Emission (dBμV/m)		
1	2412	83.12	PK	2400.00	40.89	42.23	74	PASS
		70.15	AV			29.26	54	PASS
11	2462	84.64	PK	2484.00	43.68	40.96	74	PASS
		70.87	AV			27.19	54	PASS


The Radiated Emissions Fall in the Restricted Bands

Channel	Frequency (MHz)	Antenna Polarization	Max. Emission in the Restricted Bands (dBμV/m)		Limit (dBμV/m)		Verdict
			PK	AV	PK	AV	
1	2412	Vertical	---	---	74	54	PASS
		Horizontal	---	---	74	54	PASS
6	2437	Vertical	---	---	74	54	PASS
		Horizontal	---	---	74	54	PASS
11	2462	Vertical	---	---	74	54	PASS
		Horizontal	---	---	74	54	PASS


Also refer to following plots for the emissions falling in the restricted bands.

B. Test Plot for the Whole Measurement Frequency Range:


Plots for Channel = 1




(Plot A.1: 9kHz to 30MHz)




(Plot A.2: Antenna Horizontal, 30MHz to 1GHz)




(Plot A.3: Antenna Horizontal, 1GHz to 7GHz)




(Plot A.4: Antenna Horizontal, 7GHz to 18GHz)




(Plot A.5: Antenna Horizontal, 18GHz to 25GHz)




(Plot A.6: Antenna Vertical, 30MHz to 1GHz)



(Plot A.7: Antenna Vertical, 1GHz to 7GHz)




(Plot A.8: Antenna Vertical, 7GHz to 18GHz)




(Plot A.9: Antenna Vertical, 18GHz to 25GHz)


Plot for Channel = 6




(Plot B.1: 9kHz to 30MHz)




(Plot B.2: Antenna Horizontal, 30MHz to 1GHz)




(Plot B.3: Antenna Horizontal, 1GHz to 7GHz)




(Plot B.4: Antenna Horizontal, 7GHz to 18GHz)




(Plot B.5: Antenna Horizontal, 18GHz to 25GHz)




(Plot B.6: Antenna Vertical, 30MHz to 1GHz)



(Plot B.7: Antenna Vertical, 1GHz to 7GHz)




(Plot B.8: Antenna Vertical, 7GHz to 18GHz)




(Plot B.9: Antenna Vertical, 18GHz to 25GHz)


Plot for Channel = 11




(Plot C.1: 9kHz to 30MHz)




(Plot C.2: Antenna Horizontal, 30MHz to 1GHz)




(Plot C.3: Antenna Horizontal, 1GHz to 7GHz)




(Plot C.4: Antenna Horizontal, 7GHz to 18GHz)




(Plot C.5: Antenna Horizontal, 18GHz to 25GHz)




(Plot C.6: Antenna Vertical, 30MHz to 1GHz)



(Plot C.7: Antenna Vertical, 1GHz to 7GHz)



(Plot C.8: Antenna Vertical, 7GHz to 18GHz)



(Plot C.9: Antenna Vertical, 18GHz to 25GHz)

**** END OF REPORT ****