

Company: SiBEAM, Inc.  
FCC ID: UK2-SK9210TX-HS

Request for transmitter modular approval

### Transmitter Module Characteristics

Item	Requirements	EUT
<b>1</b>	Have its own RF shielding	Device is equipped with metal shielding to cover RF section. Refer to external photos.
<b>2</b>	Have buffered modulation/data inputs (if such inputs are provided),	All inputs to the module are buffered through logic or microprocessor inputs.
<b>3</b>	Have its own power supply regulation	Internal 1.0V, 1.2V, 2.5V power regulators. Refer to Block diagram.
<b>4</b>	Meet the antenna requirements of Section 15.203	Antenna requirements met. Refer to antenna specification provided and test report.
<b>5</b>	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Condition satisfied – Module tested in stand-alone configuration and is not inside another case during testing.
<b>6</b>	Be labeled with its own FCC ID number, <b>and</b> if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	Labelling requirements met – see photos.
<b>7</b>	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	Yes
<b>8</b>	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	See test report for maximum permissible exposure reported.