

1. How does the device Operate?

Answer: Power is provided by DC 12V power source. Frequencies are selected by a center button on the EUT.

2. Provide information on the device and its antenna.

Answer: The antenna is a built-in trace on the circuit board. (please see the attached :user manual and circuit)

3. How is it installed?

Answer: plug-in connector is inserted into the DC12V Power source. No other installation is required.

4 What test procedure was used?

Answer: ANSI C63.4-2003.

5. If tested in a car, how was it configured?

Answer: It was not tested in an automobile. It was tested in an outdoor 3 meter range as shown in the Test Set-Up photographs.

6. Was the tuning range properly verified? The test lab should indicate in the report that the tuning controls were manually adjusted to verify the maximum tuning range.

Answer: TX Frenquecy range 88.1-107.9MHz, Channel Spacing is 0.2 MHz. Please see the test report (Page 6 of 22) and manual.

7. Was the bandwidth properly tested with the maximum audio input? The test lab should describe the audio input signal (use a typical audio file from a typical device) - DO NOT use 1kHz tone from signal generator as specified under ETSI EN 301 357-1)

Answer: we played a song from iPod with the maximum audio input.

8. Does the device operate in a vehicle? Please state that this was verified.

Answer: It was not test in a vehicle.