

HomeTek Technology (Chang-An) Inc.

ADDRESS: South of Shatou Industry District, Chang-An  
Town, DongGuan City, GuangDong, China  
PHONE : 86-769-85303005 FAX : 86-769-85303006  
E - mail : dgxuhong@changan.net

## FCC TEST REPORT FOR

APPLICANT : Chuang Feng Electronics Co., Ltd.  
ADDRESS : HuaLi Industrial Zone, SongBoTang, ChangPing  
Town, DongGuan City, China.  
EUT : wireless optical mouse  
MODEL NO. : KM1005  
FCC ID : UK51005

Under Part 15, SUBPART B AND SUBPART C.

### CLASS B

### Certification

MEASUREMENT PROCEDURE USED


FCC RULES AND FCC / ANSI C63.4-2003

PREPARED BY :

HomeTek Technology (Chang-An) Inc.

South of Shatou Industry District, Chang-An Town,  
DongGuan City, GuangDong, China

Report # : FBRP6065



HomeTek Technology (Chang-An) Inc.

ADDRESS: South of Shatou Industry District, Chang-An  
Town, DongGuan City, GuangDong, China  
PHONE : 86-769-85303005 FAX : 86-769-85303006  
E - mail : dgxuhong@changan.net

## CERTIFICATION

EUT	: wireless optical mouse
MODEL NO.	: KM1005
FCC ID	: UK51005
Receipt Date	: 08/22/2006
REPORT #	: FBRP6065
APPLICANT	: Chuang Feng Electronics Co., Ltd.
ADDRESS	: HuaLi Industrial Zone, SongBoTang, ChangPing Town, DongGuan City, China.

### MEASUREMENT PROCEDURE USED :

FCC RULES AND REGULATION PART 15, SUBPART B AND SUBPART C  
AND FCC / ANSI C63.4-2003

We hereby show that:

The measurement shown in this test report were made in accordance with and no deviation with the procedures indicated, and the maximum energy emitted by the equipment was found to be within the FCC limits applicable.

This test result of this report applies to above tested sample only.

This test report shall not be reproduce in part without written approval of HomeTek Technology (Chang-An) Inc.

PREPARED BY : CATHY HE DATE : 09/07/2006  
Assistant

CHECK BY : GEORGE ZHOU DATE : 09/07/2006  
Director

APPROVED BY : GRANT HUANG / Manager DATE : 09/07/2006

FBRP6065





<b>TABLE OF CONTENTS .....</b>	<b>1</b>
<b>GENERAL INFORMATION .....</b>	<b>2</b>
<b>MODIFICATION LIST .....</b>	<b>4</b>
<b>CONDUCTED POWER LINE TEST.....</b>	<b>5</b>
1    TEST PROCEDURE .....	5
2    RESULT OF CONDUCTED EMISSION TEST .....	5
<b>RADIATED EMISSION TEST .....</b>	<b>6</b>
1    TEST INSTRUMENTS & FACILITIES.....	6
2    EUT OPERATING CONDITION .....	7
3    TEST SETUP .....	8
4    CONFIGURATION OF THE EUT .....	10
5    TEST PROCEDURE .....	13
6    LIMIT OF RADIATED EMISSION CLASS B .....	14
7    RESULT OF RADIATED EMISSION TEST .....	14
<b>PHOTO OF FCC ID LABEL .....</b>	<b>15</b>
<b>APPENDIX A</b>	
PHOTOS OF TEST CONFIGURATION	
<b>APPENDIX B</b>	
PHOTOS OF EUT	
<b>APPENDIX C</b>	
PLOT OF OCCUPIED BANDWIDTH	

**GENERAL INFORMATION**

1 APPLICANT : Chuang Feng Electronics Co., Ltd.

2 ADDRESS : HuaLi Industrial Zone, SongBoTang, ChangPing Town,  
DongGuan City, China.

3 MANUFACTURER : Chuang Feng Electronics Co., Ltd.

4 ADDRESS : HuaLi Industrial Zone, SongBoTang, ChangPing Town,  
DongGuan City, China.

5 DESCRIPTION OF EUT :  
EUT : wireless optical mouse  
FCC ID : UK51005  
Model Number : KM1005  
Serial # : N/A



## 6 FEATURES OF EUT :

- ☛ USB receiver is housed inside mouse for ultimate portability---lock ensures secure fit
- ☛ Perfect for travel use---eliminates cumbersome wires
- ☛ Works up to 4 ft from user's notebook or desktop computer
- ☛ Two sleep modes automatically puts mouse to rest after 5 seconds or 10 minutes of inactivity
- ☛ 800dpi
- ☛ Requires 2AAA 1.5V batteries

### System requirements:

- ☛ Windows 98,2000,Me or XP or Mac OS
- ☛ USB port
- ☛ PC 486 or higher

And the final test data were shown in this test report.



HomeTek Technology(Chang-An) Inc.

FCC ID : UK51005

## **MODIFICATION LIST**

THE FOLLOWING ACCESSORIES WERE ADDED TO THE EUT DURING TESTING :

NO MODIFICATION BY HOMETEK TECHNOLOGY(Chang-An) INC.



## CONDUCTED POWER LINE TEST

### 1 TEST PROCEDURE

According to **ANSI C63.4 – 2003**.

### 2 RESULT OF CONDUCTED EMISSION TEST

N/A(Conducted Power Line Test is not applicable to this EUT (Model : KM1005).



## RADIATED EMISSION TEST

### 1 TEST INSTRUMENTS & FACILITIES

The following test Instruments was used during the radiated emission test :

Item	Instruments /facilities	Specification	Manufacturer	Model # / S/N#	Date of Cal.
1	OPEN AREA TEST SITE	<input checked="" type="checkbox"/> OATS 1			SEP/2005
2	EMI TEST RECEIVER	20Hz ~ 26.5GHz	ROHDE & SCHWARZ	845636/007	SEP/2005
3	PRE-AMPLIFIER	9KHz ~ 1300MHz	HEWLETT PACKARD	8447D 1937A02095	SEP/2005
4	BICONICAL/LOG BROADBAND ANTENNA	25MHz ~ 2GHz	ANTENNA RESEACH	LPB2520/A 1095	OCT/2005
5	LOOP ANTENNA	10KHz~30MHz	ZHINAN	ZN30900A	NOV/2005
6	Attenuation	50Ω/6dB	JYE BAO	FAT-N (M-F) 001	SEP/2005
7	Cable	10m	SUHNER	RG214/U OS3-003	SEP/2005
8	Cable	14m	BELDEN	9913 OS3-001	SEP/2005
9	EMI 32 (software)	N/A	AUDIX	19991013-0923	N/A


Note : Items 1 ~ 7 were calibrated within period of 1 year.

## 2 EUT OPERATING CONDITION

- 2.1 Configure the EUT according to the **ANSI C63.4 - 2003**.
- 2.2 The frequency of the EUT is 27.045 MHz.
- 2.3 The radiated emission in the frequency range from 30 MHz - 1000 MHz was test in a horizontal and vertical polarization at HomeTek(Chang-An) Lab's open site I.
- 2.4 The crystal frequency of the EUT is 27.045 MHz.
- 2.5 Provided by 2AAA battery to Mouse. Connect receiver to USB port of Person computer.
- 2.6 Turn on all the power of EUT and peripheral.
- 2.7 The EUT was operated in its normal operating mode for the purpose of the measurements.
- 2.8 The receiving antenna polarized horizontally was varied from 1 to 4 meters and the wooden turntable was rotated through 360 degrees to obtain the highest reading on the ESMI test receiver or on the display of the spectrum analyzer. And also, each emission was to be maximized by changing the orientation of the EUT.
- 2.9 The photos of radiated test configuration, please refer to appendix A.**


### 3 TEST SETUP

#### 3.1 TEST SETUP OF OPEN SITE.



### 3.2 TEST SETUP OF EUT

ELECTRICAL AND ELECTRONIC EQUIPMENT IN THE RANGE OF 9kHz TO 40 GHz

 ANSI  
C63.4-2003


(Details for setup configuration, please refer to appendix A.)

LEGEND:

1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth forming a bundle 30 to 40 cm long, hanging approximately in the middle between ground plane and table.
2. I/O cables that are connected to a peripheral shall be bundled in center. The end of the cable may be terminated if required using correct terminating impedance. The total length shall not exceed 1m.
3. If LISNs are kept in the test setup for radiated emissions, it is preferred that they be installed under the ground plane with the receptacle flush with the ground plane.
4. Cables of hand-operated devices, such as keyboards, mouses, etc., have to be placed as close as possible to the controller.
5. Non-EUT components of EUT system being tested.
6. The rear of all components of the system under test shall be located flush with the rear of the table.
7. No vertical conducting wall used.
8. Power cords drape to the floor and are routed over to receptacle.

**Test Configuration**  
**Tabletop Equipment Radiated Emission**



## 4 CONFIGURATION OF THE EUT

The EUT was configured according to **ANSI C63.4 - 2003**. All I/O ports were connected to the appropriate peripherals. All peripherals and cables are listed below (including internal device) :

### 4.1 EUT

EUT Type : Proto Type Engineer Type Mass Production

Condition when received : Good Damage :

Device : wireless optical mouse

Applicant : Chuang Feng Electronics Co., Ltd.

Manufacturer : Chuang Feng Electronics Co., Ltd.

Model Number : KM1005

Serial Number : N/A

FCC ID : UK51005

### 4.2 Peripheral

Host Personal Computer

Manufacturer : DELL

Model Number : DMC

Power Cord : Un-Shielded ,3pin,1.5m

Power Supply Type : Switching

Serial Number : HMM5L 1X

FCC ID : FCC DoC

 Monitor

Manufacturer : DELL  
Model Number : E773c  
Power Cord : Un-Shielded ,3pin,1.5m  
Power Supply Type : Switching  
Serial Number : N/A  
FCC ID : FCC DoC

 KeyBoard

Manufacturer : DELL  
Model Number : SK-8110  
Serial Number : N/A  
FCC ID : FCC DoC  
Data Cable : Shielded,1.5 m,Connected to the PSII port  
Power Cord : N/A

 Printer

Manufacturer : EPSON  
Model Number : STYLUS C20SX  
Serial Number : DLRE134382  
FCC ID : FCC DoC  
Data Cable : Shielded, 1.5 m, Connected to the Printer port  
Power Cord & Adaptor : Un-Shielded, 1.8 m

 Modem

Manufacturer : ACEEX

Model Number : 1414

Serial Number : N/A

FCC ID : IFAXDM1414

Data Cable : Shielded, 1.5 m, Connected to the COM port

Power Cord &amp; Adaptor : Un-Shielded, 1.8 m

4.3 REMARK : N/A

## 5 TEST PROCEDURE

- 5.1 The EUT was test according to **ANSI C63.4 – 2003 & FCC Part 15.35/15.209/15.239**.
- 5.2 The radiated test was performed at HomeTek(Chang-An) Lab's Open Site I.
- 5.3 This site is on file with the FCC laboratory division, test firm registration number: 140723, expiration Date : 2004/09/29.
- 5.4 For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies. The signal of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 5.5 For emission frequencies measured below and above 1 GHz, set the spectrum analyzer or a 100KHz and 1MHz resolution bandwidth respectively for each frequency measured in item 5.4.
- 5.6 The receiving antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Move the antenna to a position where the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360 ° with a speed as slow as possible and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
- 5.7 Repeat item 5.6 until all frequencies need to be measured were completed.
- 5.8 Repeat item 5.7 with search antenna in vertical polarized orientations.
- 5.9 Check seven frequencies of highest emission with varying the placement of cables (if any) associated with EUT to obtain the worst case and record the result.
- 5.10 The frequency range from 30 MHz to 1 GHz were investigated, the measurement were made at 3 meters, with a BI-log antenna.

## 6 LIMIT OF RADIATED EMISSION CLASS B

Frequency (MHz)	Measurement Distance	dBuV/m	uV/m
Fundamental frequency	3 (M)	48	250
30 - 88	3 (M)	40	100
88 - 216	3 (M)	43.5	150
216 - 960	3 (M)	46	200
Above 960	3 (M)	54	500

- 6.1 The tighter limit shall apply at the edge between two frequency bands.
- 6.2 Measurement distance in meters between the measuring instrument antenna and the closed point of any part of the EUT or peripherals.


## 7 RESULT OF RADIATED EMISSION TEST

- 7.1 The frequency range from 30 MHz to 1 GHz was investigated.
- 7.2 All readings below or equal 1 GHz are quasi-peak or peak values with resolution bandwidth of 120 KHz. The reading of fundamental frequency is peak or average values. With resolution bandwidth of 120KHz.
- 7.3 The measurements were made at 3 meters of HomeTek(Chang-An) Lab's open site I.
- 7.4 Temperature : 27 °C, Humidity : 45 % RH.
- 7.5 Deviation form the test standards and rules : None
- 7.6 The radiation emission result were gained by the following method :  
Level = Reading Level + Probe Factor (Antenna Factor) + Cable Loss – Preamp Factor  
Over Limit = Level – Limit Line
- 7.7 The radiated mission test was passed at minimum margin :  
Vertical 27.112 MHz/ 43.31 dBuV/m, Antenna Height 1.1 Meter,  
Turn Table 92 degree, The Model : KM1005.
- 7.8 Result : **PASSED**

(Result of radiated emission test data were shown as following four pages.)

Data#: 1 File#: RP6065.EMI

Date: 8-26,2006 Time: 09:08:59



Hometek

Trace :

Limit : FCC Part 15 CLASS B 3m

Probe : LPB-250/A-031028\_3 HORIZONTAL

Margin: -6.0dB

EUT : KM1005

Power : Receiver:For USB Mouse:DC3V(2AAA Battery)

Memo :


Ref Trace:

Page: 1

Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Preamp		Remark
						dB	dB	
MHz	dB	dB	dB	dB	dB	dB	dB	
1 !	54.030	34.06	-5.94	40.00	46.20	13.85	1.90	27.89 Peak
2	81.020	32.56	-7.44	40.00	46.87	9.84	3.70	27.84 QP
3	108.110	34.62	-8.88	43.50	48.20	11.56	2.62	27.76 QP
4	134.850	32.19	-11.31	43.50	44.81	11.76	3.25	27.63 Peak
5	162.550	33.26	-10.24	43.50	46.89	10.09	3.78	27.49 Peak
6	188.842	31.92	-11.58	43.50	44.40	11.60	3.29	27.36 Peak
7	215.899	31.00	-12.50	43.50	41.91	12.90	3.46	27.27 Peak
8	243.100	32.60	-13.40	46.00	41.94	14.16	3.72	27.22 Peak

Data#: 2 File#: RP6065.EMI

Date: 8-26,2006 Time: 10:01:22



Hometek

Trace :

Limit : FCC Part 15 CLASS B 3m

Probe : LPB-250/A-031028\_3 VERTICAL

Margin: -6.0dB

EUT : KM1005

Power : Receiver:For USB Mouse:DC3V(2AAA Battery)

Memo :


Ref Trace:

Page: 1

Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Preamp			Remark
						dB	dB	dB	
1	54.130	33.95	-6.05	40.00	46.09	13.85	1.90	27.89	Peak
2	81.220	31.96	-8.04	40.00	46.27	9.84	3.70	27.84	QP
3	108.010	34.00	-9.50	43.50	47.58	11.56	2.62	27.76	QP
4	134.950	32.56	-10.94	43.50	45.18	11.76	3.25	27.63	Peak
5	162.450	32.94	-10.56	43.50	46.57	10.09	3.78	27.49	Peak
6	189.020	31.89	-11.61	43.50	44.37	11.60	3.29	27.36	Peak
7	216.199	31.13	-14.87	46.00	42.04	12.90	3.46	27.27	Peak
8	243.030	32.90	-13.10	46.00	42.24	14.16	3.72	27.22	Peak

Data#: 3 File#: RP6065.EMI

Date: 8-26,2006 Time: 11:06:29



Hometek

Trace :

Limit : FCC Part 15 CLASS B 3m

Probe : LPB-250/A-031028\_3 HORIZONTAL

Margin: -6.0dB

EUT : KM1005

Power : Receiver:For USB Mouse:DC3V(2AAA Battery)

Memo :


Ref Trace:

Page: 1

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark
	MHz	dB	dB	dB	dB	dB	dB	dB	
1	27.012	43.25	-4.75	48.00	56.87	13.80	0.51	27.93	Peak
2 !	54.130	34.16	-5.84	40.00	46.30	13.85	1.90	27.89	Peak
3	81.250	31.27	-8.73	40.00	45.57	9.84	3.70	27.84	QP
4	108.200	32.56	-10.94	43.50	46.18	11.52	2.62	27.76	QP
5	135.360	31.96	-11.54	43.50	44.58	11.76	3.25	27.62	Peak
6	161.980	33.16	-10.34	43.50	46.79	10.09	3.78	27.50	Peak
7	189.011	34.91	-8.59	43.50	47.04	11.90	3.32	27.36	Peak
8	216.110	33.02	-12.98	46.00	43.87	12.90	3.52	27.27	Peak

Data#: 4 File#: RP6065.EMI

Date: 8-26,2006 Time: 12:10:13



Hometek

Trace :

Limit : FCC Part 15 CLASS B 3m

Probe : LPB-250/A-031028\_3 VERTICAL

Margin: -6.0dB

EUT : KM1005

Power : Receiver:For USB Mouse:DC3V(2AAA Battery)

Memo :

Ref Trace:

Page: 1

Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Preamp			Remark
						dB	dB	dB	
MHz	dB	dB	dB	dB	dB				
1	27.112	43.31	-4.69	48.00	55.96	14.60	0.70	27.95	Peak
2	54.210	34.01	-5.99	40.00	46.15	13.85	1.90	27.89	Peak
3	81.150	31.72	-8.28	40.00	46.02	9.84	3.70	27.84	QP
4	108.100	32.46	-11.04	43.50	46.08	11.52	2.62	27.76	QP
5	135.260	31.16	-12.34	43.50	43.78	11.76	3.25	27.62	Peak
6	162.080	33.56	-9.94	43.50	47.19	10.09	3.78	27.50	Peak
7	189.110	32.81	-10.69	43.50	44.94	11.90	3.32	27.36	Peak
8	215.910	33.21	-10.29	43.50	44.13	12.90	3.46	27.27	Peak



## PHOTO OF FCC ID LABEL

### SAMPLE OF FCC ID LABEL :

FCC ID : #####

This device complies with part 15 of the FCC Rules.  
Operation is subject to the following two conditions: (1)  
This device may not cause harmful interference. And (2)  
this device must accept any interference that may cause  
undesired operation.

**Please refer to appendix B photo of ID location.**