


Installation guide

XS4 One S for European mortise locks

SALTO
inspired access







- Eng** Installation guide
E Guía de instalación
D Montageanleitung
F Guide d'installation
I Guida all'installazione
P Guia de instalação

E i 850 xx..series



E i 8xx.. series		E i 8xx..E5 series	
OUTSIDE	INSIDE	OUTSIDE	INSIDE
IP54	IP44	IP56	IP44

*112- FOR 7F MODEL



Not included
 No incluido
 Nicht enthalten
 Non incluse
 Non incluso
 Não incluido

Ø14

Ø25

Ø14

"A2" version has to be installed always with the SALTO LT2L tubular latch.
 La versión "A2" solo se puede instalar con el picaporte tubular SALTO LT2L.

SALTO LT2Lxx Tubular latch With Ei8xxA2.. Only!

To be used only with SALTO compatible escutcheons!
 A utiliser uniquement avec les ensembles plaques-béquilles SALTO compatibles!
 ¡Utilizar solamente con escudos SALTO compatibles!




Ø25
 Ø1"



Outside
 Exterior
 Außenseite
 Extérieur
 Esterno

Inside
 Interior
 Innenseite
 Intérieur
 Interno

t Door thickness			
3	32 - 47mm	35 mm	-
4	45 - 60 mm	50 mm	-
6	60 - 75 mm	30 mm	x2
7	75 - 90 mm	45 mm	x2
9	90 - 105 mm	30 mm	x4
1	105 - 120 mm	45 mm	x4
2	32 - 53 mm	35 mm	-
A		35 mm	-
B		45 mm	-
5		45 mm	-



SALTO recommends the use of a mortise lock, with a maximum 4° pre-turn.

SALTO recomienda utilizar cerraduras con un pregiro máximo de 4°.

SALTO empfiehlt den Einsatz von Einsteckschlössern mit max. 4° Vorspannung.

SALTO recommande d'utiliser des serrures à mortaiser avec un angle au repos de 4° maximum.

SALTO raccomanda l'utilizzo di una serratura con un angolo di pre-rotazione massimo di 4°.

SALTO recomenda utilizar fechaduras com uma pré rotação máxima de 4°.

MODELS: ELECTRONIC INFO. W80M - W40T - W40MH

1/4






226867-ED.-15/11/2023

Installation guide




XS4 One S for European mortise locks

SALTO
inspired access

(Eng) Select handing (E) Selección mano (D) Drückerichtung wählen (C) Choisir le sens de la bêche
(I) Scegliere il verso (P) Seleccione mão




(Eng) Installation (E) Instalación (D) Installation (F) Installation (I) Installazione (P) Instalação



Installation guide

XS4 One S for European mortise locks

SALTO
inspired access






Installation guide

XS4 One S for European mortise locks

SALTO
inspired access

E i 851 xx.. series


E i 8P1 xx.. series



Eng Other models E Otros modelos D Andere Modelle F D'autres modèles I Altri modelli P Outros modelos


E i 856 xx..

- Eng -Entry lock with privacy/ lockout funtion
- E -Modelo entrada con privacidad
- D -Beschlag mit Privacy-Funktion
- F -Béquille electronique avec fonction privacité
- I -Modello di entrata con privacy
- P -Modelo entrada com privacidade



E i 8P6 xx..

- Eng -Entry lock with privacy/lockout funtion and key override
- E -Modelo entrada con privacidad y llave de emergencia con registro
- D -Beschlag mit Privacy-Funktion und Notschlüssel
- F -Béquille electronique avec fontion privacité et clef de secours
- I -Modello entrata con privacy e chiave di emergenza con registrazione
- P -Modelo entrada com privacidade e chave de emergencia com registro



E T8xx.. series

