



ONE WORLD ◊ OUR APPROVAL

Wireless test report – 350995-2R1TRFWL

Applicant:

Eurotech SpA

Product name:

ReliaGATE 10-12

DynaGATE 10-12

Model:

REGATE-10-12-GS02

Model variant:

DYGATE-10-12-GS02

FCC ID:

UKMMRG1012

IC Registration number:

21442-MRG1012

Specifications:

◆ **FCC 47 CFR Part 15 Subpart C, §15.247**

Operation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz

◆ **RSS-247, Issue 2, Feb 2017, Section 5**

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs)
and Licence-Exempt Local Area Network (LE-LAN) Devices

5) Standard specifications for frequency hopping systems and digital transmission systems operating in the
bands 902–928 MHz, 2400–2483.5 MHz and 5725–5850 MHz

Date of issue: **October 12, 2018**

Test engineer(s):

Yong Huang, Wireless/EMC Specialist

Signature:

Reviewed by:

Kevin Rose, Wireless/EMC Specialist

Signature:

www.nemko.com

Nemko Canada Inc., a testing laboratory, is
accredited by the Standards Council of
Canada. The tests included in this report are
within the scope of this accreditation

FCC 15.247 and RSS-247.docx; Date: Feb 2018



Test location(s)

| | | |
|--------------|------------------------------------|------------------------------------|
| Company name | Nemko Canada Inc. | |
| Address | 303 River Road | 292 Labrosse Avenue |
| City | Ottawa | Pointe-Claire |
| Province | Ontario | Quebec |
| Postal code | K1V 1H2 | H9R 5L8 |
| Country | Canada | Canada |
| Telephone | +1 613 737 9680 | +1 514 694 2684 |
| Facsimile | +1 613 737 9691 | +1 514 694 3528 |
| Toll free | +1 800 563 6336 | |
| Website | www.nemko.com | www.nemko.com |
| Site number | FCC: CA2040; IC: 2040A-4 (3 m SAC) | FCC: CA2041; IC: 2040G-5 (3 m SAC) |

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

Table of contents

| | |
|--|-----------|
| Table of contents | 3 |
| Section 1. Report summary | 4 |
| 1.1 Applicant and manufacturer | 4 |
| 1.2 Test specifications | 4 |
| 1.3 Test methods | 4 |
| 1.4 Statement of compliance | 4 |
| 1.5 Exclusions | 4 |
| 1.6 Test report revision history | 4 |
| Section 2. Summary of test results | 5 |
| 2.1 FCC Part 15 Subpart C, general requirements test results | 5 |
| 2.2 FCC Part 15 Subpart C, intentional radiators test results for frequency hopping spread spectrum systems | 5 |
| 2.3 FCC Part 15 Subpart C, intentional radiators test results for digital transmission systems (DTS) | 5 |
| 2.4 ISED RSS-Gen, Issue 5, test results | 6 |
| 2.5 ISED RSS-247, Issue 2, test results for frequency hopping spread spectrum systems (FHSS) | 6 |
| 2.6 ISED RSS-247, Issue 2, test results for digital transmission systems (DTS) | 6 |
| Section 3. Equipment under test (EUT) details | 7 |
| 3.1 Sample information | 7 |
| 3.2 EUT information | 7 |
| 3.3 Technical information | 7 |
| 3.4 Product description and theory of operation | 8 |
| 3.5 EUT exercise details | 8 |
| 3.6 EUT setup diagram | 9 |
| 3.7 EUT sub assemblies | 9 |
| Section 4. Engineering considerations | 10 |
| 4.1 Modifications incorporated in the EUT | 10 |
| 4.2 Technical judgment | 10 |
| 4.3 Deviations from laboratory tests procedures | 10 |
| Section 5. Test conditions | 11 |
| 5.1 Atmospheric conditions | 11 |
| 5.2 Power supply range | 11 |
| Section 6. Measurement uncertainty | 12 |
| 6.1 Uncertainty of measurement | 12 |
| Section 7. Test equipment | 13 |
| 7.1 Test equipment list | 13 |
| Section 8. Testing data | 14 |
| 8.1 FCC 15.31(e) Variation of power source | 14 |
| 8.2 FCC 15.31(m) and RSS-Gen 6.9 Number of frequencies | 15 |
| 8.3 FCC 15.203 and RSS-Gen, section 6.8 Antenna requirement | 16 |
| 8.4 FCC 15.207(a) and RSS-Gen 8.8 AC power line conducted emissions limits | 17 |
| 8.5 FCC 15.247(a)(2) and RSS-247 5.2(a) Minimum 6 dB bandwidth for DTS systems | 21 |
| 8.6 FCC 15.247(b) and RSS-247 5.4 (d) Transmitter output power and e.i.r.p. requirements for DTS in 2.4 GHz | 25 |
| 8.7 FCC 15.247(d) and RSS-247 5.5 Spurious (out-of-band) unwanted emissions | 28 |
| 8.8 FCC 15.247(e) and RSS-247 5.2(b) Power spectral density for digitally modulated devices | 44 |
| Section 9. Block diagrams of test set-ups | 47 |
| 9.1 Radiated emissions set-up for frequencies below 1 GHz | 47 |
| 9.2 Radiated emissions set-up for frequencies above 1 GHz | 47 |
| 9.3 Conducted emissions set-up | 48 |
| 9.4 Antenna port set-up | 48 |

Section 1. Report summary

1.1 Applicant and manufacturer

| | |
|--------------|--|
| Company name | Eurotech SpA |
| Address | Via Fratelli Solari 3/a 33020 Amaro, UD, Italy |

1.2 Test specifications

| | |
|--|--|
| FCC 47 CFR Part 15, Subpart C, Clause 15.247 | Operation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–585 MHz |
| RSS-247, Issue 2, Feb 2017, Section 5 | Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices |

1.3 Test methods

| | |
|--|---|
| 558074 D01 DTS Meas Guidance v04 (April 5, 2017) | Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 |
| ANSI C63.10 v2013 | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices |
| RSS-Gen, Issue 5, April 2018 | General Requirements for Compliance of Radio Apparatus |

1.4 Statement of compliance

In the configuration tested, the EUT was found compliant.

Testing was performed against all relevant requirements of the test standard except as noted in section 1.5 below. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

See "Summary of test results" for full details.

1.5 Exclusions

None

1.6 Test report revision history

| Revision # | Date of issue | Details of changes made to test report |
|------------|--------------------|--|
| TRF | September 14, 2018 | Original report issued |
| R1 | October 12, 2018 | Report revised with additional antenna configuration |

Section 2. Summary of test results

2.1 FCC Part 15 Subpart C, general requirements test results

Table 2.1-1: FCC general requirements results

| Part | Test description | Verdict |
|------------|------------------------------|---------|
| §15.207(a) | Conducted limits | Pass |
| §15.31(e) | Variation of power source | Pass |
| §15.31(m) | Number of tested frequencies | Pass |
| §15.203 | Antenna requirement | Pass |

Notes: EUT is an AC powered device.

2.2 FCC Part 15 Subpart C, intentional radiators test results for frequency hopping spread spectrum systems

Table 2.2-1: FCC 15.247 results for FHSS

| Part | Test description | Verdict |
|--------------------|---|----------------|
| §15.247(a)(1)(i) | Requirements for operation in the 902–928 MHz band | Not applicable |
| §15.247(a)(1)(ii) | Requirements for operation in the 5725–5850 MHz band | Not applicable |
| §15.247(a)(1)(iii) | Requirements for operation in the 2400–2483.5 MHz band | Not applicable |
| §15.247(b)(1) | Maximum peak output power in the 2400–2483.5 MHz band and 5725–5850 MHz band | Not applicable |
| §15.247(b)(2) | Maximum peak output power in the 902–928 MHz band | Not applicable |
| §15.247(c)(1) | Fixed point-to-point operation with directional antenna gains greater than 6 dBi | Not applicable |
| §15.247(c)(2) | Transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams | Not applicable |
| §15.247(d) | Spurious emissions | Not applicable |
| §15.247(f) | Time of occupancy for hybrid systems | Not applicable |

2.3 FCC Part 15 Subpart C, intentional radiators test results for digital transmission systems (DTS)

Table 2.3-1: FCC 15.247 results for DTS

| Part | Test description | Verdict |
|---------------|---|----------------|
| §15.247(a)(2) | Minimum 6 dB bandwidth | Pass |
| §15.247(b)(3) | Maximum peak output power in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands | Pass |
| §15.247(c)(1) | Fixed point-to-point operation with directional antenna gains greater than 6 dBi | Not applicable |
| §15.247(c)(2) | Transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams | Not applicable |
| §15.247(d) | Spurious emissions | Pass |
| §15.247(e) | Power spectral density | Pass |
| §15.247(f) | Time of occupancy for hybrid systems | Not applicable |

2.4 ISED RSS-Gen, Issue 5, test results

Table 2.4-1: RSS-Gen results

| Part | Test description | Verdict |
|------|---|----------------|
| 7.3 | Receiver radiated emission limits | Not applicable |
| 7.4 | Receiver conducted emission limits | Not applicable |
| 6.9 | Operating bands and selection of test frequencies | Pass |
| 8.8 | AC power-line conducted emissions limits | Pass |

Notes: ¹ According to sections 5.2 and 5.3 of RSS-Gen, Issue 5 the EUT does not have a stand-alone receiver neither scanner receiver, therefore exempt from receiver requirements.

EUT is an AC powered device.

2.5 ISED RSS-247, Issue 2, test results for frequency hopping spread spectrum systems (FHSS)

Table 2.5-1: RSS-247 results for FHSS

| Part | Test description | Verdict |
|---------|--|----------------|
| 5.1 (a) | Bandwidth of a frequency hopping channel | Not applicable |
| 5.1 (b) | Minimum channel spacing | Not applicable |
| 5.1 (c) | Systems operating in the 902–928 MHz band | Not applicable |
| 5.1 (d) | Systems operating in the 2400–2483.5 MHz band | Not applicable |
| 5.1 (e) | Systems operating in the 5725–5850 MHz band | Not applicable |
| 5.3 | Hybrid Systems | Not applicable |
| 5.3 (a) | Digital modulation turned off | Not applicable |
| 5.3 (b) | Frequency hopping turned off | Not applicable |
| 5.4 | Transmitter output power and e.i.r.p. requirements | Not applicable |
| 5.4 (a) | Systems operating in the 902–928 MHz band | Not applicable |
| 5.4 (b) | Systems operating in the 2400–2483.5 MHz band | Not applicable |
| 5.4 (c) | Systems operating in the 5725–5850 MHz | Not applicable |
| 5.4 (e) | Point-to-point systems in 2400–2483.5 MHz and 5725–5850 MHz band | Not applicable |
| 5.4 (f) | Transmitters which operate in the 2400–2483.5 MHz band with multiple directional beams | Not applicable |
| 5.5 | Unwanted emissions | Not applicable |

Notes: None

2.6 ISED RSS-247, Issue 2, test results for digital transmission systems (DTS)

Table 2.6-1: RSS-247 results for DTS

| Part | Test description | Verdict |
|---------|--|----------------|
| 5.2 (a) | Minimum 6 dB bandwidth | Pass |
| 5.2 (b) | Maximum power spectral density | Pass |
| 5.3 | Hybrid Systems | |
| 5.3 (a) | Digital modulation turned off | Not applicable |
| 5.3 (b) | Frequency hopping turned off | Not applicable |
| 5.4 | Transmitter output power and e.i.r.p. requirements | |
| 5.4 (d) | Systems employing digital modulation techniques | Pass |
| 5.4 (e) | Point-to-point systems in 2400–2483.5 MHz and 5725–5850 MHz band | Pass |
| 5.4 (f) | Transmitters which operate in the 2400–2483.5 MHz band with multiple directional beams | Not applicable |
| 5.5 | Unwanted emissions | Pass |

Notes: None

Section 3. Equipment under test (EUT) details

3.1 Sample information

| | |
|------------------------|--------------|
| Receipt date | July 4, 2018 |
| Nemko sample ID number | Item #1 |

3.2 EUT information

| | |
|---------------|-----------------------------------|
| Product name | ReliaGATE 10-12 DynaGATE 10-12 |
| Model | REGATE-10-12-GS02 |
| Model variant | DYGATE-10-12-GS02 |
| Serial number | Y117LQA0010 |

3.3 Technical information

| | |
|---|---|
| Applicant IC company number | 21442 |
| IC UPN number | MRG1012 |
| All used IC test site(s) Reg. number | 2040G-5 |
| RSS number and Issue number | RSS-247 Issue 2, Feb 2017 |
| Frequency band | 2400 to 2483.5 MHz |
| Frequency Min (MHz) | 2412 |
| Frequency Max (MHz) | 2462 |
| RF power Min (W), Conducted | N/A |
| RF power Max (W), Conducted | 0.0347(15.4 dBm, 802.11b), 0.0251(14.0 dBm, 802.11g), .0.0120(13.0 dBm, 802.11n HT20), 0.0355(15.5 dBm, 802.11 HT40) |
| Field strength, Units @ distance | N/A |
| Measured BW (kHz) (6 dB) | 1110(802.11b), 1632(802.11g), 1667(802.11n HT20), 3511(802.11 HT40) |
| Calculated BW (kHz), as per TRC-43 | N/A |
| Type of modulation | 802.11b/g/n |
| Emission classification (F1D, G1D, D1D) | W7D |
| Transmitter spurious, Units @ distance | 53.93 dB μ V/m at 2390MHz, @ 3 m |
| Power requirements | 24 V _{DC} , via 120 V _{AC} adapter or battery |
| Antenna information | The EUT uses a unique antenna coupling. EUT has 2 antenna configurations. The max antenna peak gain is 5.47 dBi at 2.4 GHz band and 7.07 dBi at 5 GHz WIFI bands. Linx Technologies ANT-DB1-RAF-RPS (2.5 dBi for 2.4 GHz, 4.6 dBi antenna for 5 GHz) Taoglas MA.950.W.A.LBICG.005 (5.47 dBi for 2.4GHz, 7.07 for 5GHz) |

3.4 Product description and theory of operation

The ReliaGATE and DynaGATE 10-12 are IoT Edge Gateways that have been designed to deliver LTE connectivity (with 3G fallback) to industrial and lightly rugged applications. Based on the TI AM335x Cortex-A8 (Sitara) processor family, with 1 GB of RAM, 4 GB of eMMC and user-accessible MicroSD and dual Micro-SIM slots, the ReliaGATE and DynaGATE 10-12 are low power gateways suitable for demanding use cases. They support a 6 to 36 V power supply with transient protection and ignition sense, two protected RS-232/RS-485 serial ports, two CAN bus interfaces, three noise and surge protected USB ports, and four isolated digital interfaces

3.5 EUT exercise details

EUT was set to continuously transmit mode during tests, by test software provided by client.

The EUT runs a Linux operating system which allows for the testing to be performed using engineering test tools and scripts. Communication with the EUT is via a serial console or Ethernet connection which provides a Linux command line interface for execution of the test tools/scripts. These tools/scripts configure the radio modules to enable continuous transmission with the ability to adjust modulation, frequency and output power as required.

WiFi/BT – using a engineering test tool provided by the silicon vendor allowing for full radio control.

Cellular – using Linux scripts running AT command sequences provided by the cellular radio module vendor allowing for full radio control.

3.6 EUT setup diagram




Figure 3.6-1: Setup diagram

3.7 EUT sub assemblies

Table 3.7-1: EUT sub assemblies

| Description | Brand name | Model/Part number | Serial number |
|--------------|------------|-------------------|---------------|
| REGATE-10-12 | Eurotech | REGATE-10-12-GS02 | Y117LQA0010 |
| AC adapter | Sunny | SYS15412424 | None |

Section 4. Engineering considerations

4.1 Modifications incorporated in the EUT

There were no modifications performed to the EUT during this assessment.

4.2 Technical judgment

Differences between the variants are as below. REGATE-10-12 was chosen as representative worst-case.

| Model | ReliaGATE 10-12 | | | | | DynaGATE 10-12 | | | | | | | | | |
|--|---|-----------------|------------------|--|---------------------|---|-----------------|------------------|---------------------|------------------|--|--|--|--|--|
| Variant (Base Hardware) REGATE-10-12-xx | REGATE-10-12-GS02 (EMC Sample Unit) | REGATE-10-12-01 | REGATE-10-12-02 | REGATE-10-12-03 | REGATE-10-12-05 | DYGATE-10-12-GS02 (EMC Sample Unit) | DYGATE-10-12-01 | DYGATE-10-12-02 | DYGATE-10-12-03 | DYGATE-10-12-05 | | | | | |
| OS SW Versions Refer Note 1. | - | REGATE-10-12-21 | REGATE-10-12-22 | REGATE-10-12-23 | REGATE-10-12-25 | - | DYGATE-10-12-21 | DYGATE-10-12-22 | DYGATE-10-12-23 | DYGATE-10-12-25 | | | | | |
| REGATE-10-12-31 | REGATE-10-12-32 | REGATE-10-12-33 | REGATE-10-12-35 | | | DYGATE-10-12-31 | DYGATE-10-12-32 | DYGATE-10-12-33 | DYGATE-10-12-35 | | | | | | |
| GENERAL | | | | | | | | | | | | | | | |
| Processor | TI Sitara AM3352 1GHz | | | | | | | | | | | | | | |
| DRAM | 1GB DDR3 | | | | | | | | | | | | | | |
| STORAGE | 4GB eMMC, micro SD slot accessible under service panel opening, 256kbit EEPROM | | | | | | | | | | | | | | |
| PCB Design | Both models share the same PCB design with population differences as described below (8-layers PCB) | | | | | | | | | | | | | | |
| Ethernet | 2x 10-100Mbps on shielded RJ45 | | | | | | | | | | | | | | |
| Serial | Two identical 2-lines channels(RX/TX, RA+/RB-) available on 3.5mm terminal | | | | | | | | | | | | | | |
| Debug | RS232 3.3V TTL debug port available under service panel opening | | | | | | | | | | | | | | |
| CAN | Two identical Can bus ports available on 3.5mm terminal header with external power delivery 5V@100mA | | | | | | | | | | | | | | |
| Digital I/O | 2x Digital Input 36V, 1kV Opto-isolated, 2x Digital Output (40VDC), 500mA fuse protected, 1KHz Max Switching(optorelay) | | | | | | | | | | | | | | |
| USB | 3x Host 2.0 (Noise and Surge Protected) - Type A – Electrically identical to DynaGATE 10-12 Variants | | | 3x Host 2.0 (Noise and Surge Protected) - High Retention Type A - Electrically identical to ReliaGATE 10-12 Variants | | | | | | | | | | | |
| Expansion | Yes, for Side Expansion Modules (24way 2mm/2row female header) | | | | | | | | | | | | | | |
| WIRELESS | | | | | | | | | | | | | | | |
| LTE | TELIT LE910-NA1 LTE | None | None | TELIT LE910-NA1 LTE | TELIT LE910-NA1 LTE | None | None | None | TELIT LE910-NA1 LTE | | | | | | |
| WiFi | Jorjin WG7833-B0 | None | Jorjin WG7833-B0 | None | Jorjin WG7833-B0 | Jorjin WG7833-B0 | None | Jorjin WG7833-B0 | None | Jorjin WG7833-B0 | | | | | |
| GPS | Optional U-Blox NEO-M8x GPS Receiver | | | | | | | | | | | | | | |
| | Integrated U-Blox NEO-M8x GPS Receiver | | | | | | | | | | | | | | |
| OTHER | | | | | | | | | | | | | | | |
| RTC | Yes (Lithium BR1225 battery backup) | | | | | Yes (Supercap backup) | | | | | | | | | |
| Sensors | Temperature, Accelerometer | | | | | | | | | | | | | | |
| Buttons | 1x RESET, 1x user programmable available under the service panel | | | | | | | | | | | | | | |
| LEDs | 1x Power, 1x Cellular, 4x Programmable | | | | | | | | | | | | | | |
| TPM | Factory Option | | | | | | | | | | | | | | |
| SIM slot | 2x microSIM (User Accessible under the service panel) | | | | | | | | | | | | | | |
| Power | 6-36VDC, with Transient Protection, Vehicle Ignition Sense (2W typ.) | | | | | | | | | | | | | | |
| ENVIRONMENT | | | | | | | | | | | | | | | |
| Operating temp. range | - 20 to +70°C | | | | | - 40 to +85°C | | | | | | | | | |
| Storage temp. range | - 40 to +85°C | | | | | | | | | | | | | | |
| MECHANICAL | | | | | | | | | | | | | | | |
| Enclosure | ABS Plastic | | | | | Aluminium Sheetmetal | | | | | | | | | |
| Ingress | IP40 | | | | | | | | | | | | | | |
| Dimensions | 138.9x115.0x46.2mm (LxWxH) - with mounting bracket and SMA connectors | | | | | 138.9x118.2x51.6mm (LxWxH) - with mounting bracket and SMA connectors | | | | | | | | | |

Note 1: Radio module firmware and operating system based radio firmware loaded during OS boot are identical across all REGATE-10-12-xx and DYGATE-10-12-xx variants.

4.3 Deviations from laboratory tests procedures

No deviations were made from laboratory procedures.

Section 5. Test conditions

5.1 Atmospheric conditions

| | |
|-------------------|---------------|
| Temperature | 15–30 °C |
| Relative humidity | 20–75 % |
| Air pressure | 860–1060 mbar |

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

5.2 Power supply range

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages $\pm 5\%$, for which the equipment was designed.

Section 6. Measurement uncertainty

6.1 Uncertainty of measurement

UKAS Lab 34 and TIA-603-B have been used as guidance for measurement uncertainty reasonable estimations with regards to previous experience and validation of data. Nemko Canada, Inc. follows these test methods in order to satisfy ISO/IEC 17025 requirements for estimation of uncertainty of measurement for wireless products.

Measurement uncertainty budgets for the tests are detailed below. Measurement uncertainty calculations assume a coverage factor of $K = 2$ with 95% certainty.

Table 6.1-1: Measurement uncertainty

| Test name | Measurement uncertainty, dB |
|-----------------------------------|-----------------------------|
| All antenna port measurements | 0.55 |
| Conducted spurious emissions | 1.13 |
| Radiated spurious emissions | 3.78 |
| AC power line conducted emissions | 3.55 |

Section 7. Test equipment

7.1 Test equipment list

Table 7.1-1: Equipment list

| Equipment | Manufacturer | Model no. | Asset no. | Cal cycle | Next cal. |
|------------------------------|--------------------|-----------|-----------|-----------|-------------|
| 3 m EMI test chamber | TDK | SAC-3 | FA002532 | 2 year | June 5/19 |
| Flush mount turntable | Sunol | FM2022 | FA002550 | — | NCR |
| Controller | Sunol | SC104V | FA002551 | — | NCR |
| Antenna mast | Sunol | TLT2 | FA002552 | — | NCR |
| Receiver/spectrum analyzer | Rohde & Schwarz | ESU 40 | FA002071 | 1 year | Sept. 18/18 |
| Bilog antenna (20–2000 MHz) | Sunol | JB1 | FA002517 | 1 year | Dec. 6/18 |
| Power sensor | Rohde & Schwarz | NRP18S | FA002730 | 1 year | Sep 26/19 |
| Horn antenna (1–18 GHz) | EMCO | 3115 | FA001451 | 1 year | April 27/19 |
| Pre-amplifier (0.5–18 GHz) | COM-POWER | PAM-118A | FA002561 | 1 year | Sept. 21/18 |
| Horn antenna (18–40 GHz) | EMCO | 3116 | FA002487 | 2 year | Aug. 16/19 |
| Pre-amplifier (0.5–18 GHz) | COM-POWER | PAM-118A | FA002561 | 1 year | Sept. 21/18 |
| Pre-amplifier (18–40 GHz) | COM-POWER | PAM-840 | FA002508 | 1 year | May 8/19 |
| 50 Ω coax cable | C.C.A. | None | FA002603 | — | VOU |
| 50 Ω coax cable | C.C.A. | None | FA002605 | — | VOU |
| 50 Ω coax cable | C.C.A. | None | FA002831 | — | VOU |
| 50 Ω coax cable | C.C.A. | None | FA002607 | — | VOU |
| 50 Ω coax cable | Sucoflex | None | FA002563 | — | VOU |
| 2300-2583.5 MHz Notch Filter | Microwave Circuits | N0324413 | FA002693 | — | VOU |

Note: NCR - no calibration required, VOU - verify on use

Section 8. Testing data

8.1 FCC 15.31(e) Variation of power source

8.1.1 Definitions and limits

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

8.1.2 Test date

Start date August 1, 2018

8.1.3 Observations, settings and special notes

None

8.1.4 Test data

EUT Power requirements:

| | | | |
|---|--|--|---|
| If EUT is an AC or a DC powered, was the noticeable output power variation observed? | <input checked="" type="checkbox"/> AC | <input type="checkbox"/> DC | <input type="checkbox"/> Battery |
| If EUT is battery operated, was the testing performed using fresh batteries? | <input type="checkbox"/> YES | <input checked="" type="checkbox"/> NO | <input type="checkbox"/> N/A |
| If EUT is rechargeable battery operated, was the testing performed using fully charged batteries? | <input type="checkbox"/> YES | <input type="checkbox"/> NO | <input checked="" type="checkbox"/> N/A |

8.2 FCC 15.31(m) and RSS-Gen 6.9 Number of frequencies

8.2.1 Definitions and limits

FCC:

Measurements on intentional radiators or receivers shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table.

ISED:

Except where otherwise specified, measurements shall be performed for each frequency band of operation for which the radio apparatus is to be certified, with the device operating at the frequencies in each band of operation shown in table below. The frequencies selected for measurements shall be reported in the test report.

Table 8.2-1: Frequency Range of Operation

| Frequency range over which the device operates (in each band) | Number of test frequencies required | Location of measurement frequency inside the operating frequency range |
|---|-------------------------------------|--|
| 1 MHz or less | 1 | Center (middle of the band) |
| 1–10 MHz | 2 | 1 near high end, 1 near low end |
| Greater than 10 MHz | 3 | 1 near high end, 1 near center and 1 near low end |

Note: "near" means as close as possible to or at the centre / low end / high end of the frequency range over which the device operates.

8.2.2 Test date

Start date July 18, 2018

8.2.3 Observations, settings and special notes

None

8.2.4 Test data

Table 8.2-2: Test channels selection

| Modulation | Start of Frequency range, MHz | End of Frequency range, MHz | Frequency range bandwidth, MHz | Low channel, MHz | Mid channel, MHz | High channel, MHz |
|------------------|-------------------------------|-----------------------------|--------------------------------|------------------|------------------|-------------------|
| 802.11b/g/n HT20 | 2400 | 2483.5 | 83.5 | 2412 | 2437 | 2462 |
| 802.11n HT40 | 2400 | 2483.5 | 83.5 | 2422 | 2437 | 2452 |

8.3 FCC 15.203 and RSS-Gen, section 6.8 Antenna requirement

8.3.1 Definitions and limits

FCC:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

ISED:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report.

8.3.2 Test date

Start date July 18, 2018

8.3.3 Observations, settings and special notes

None

8.3.4 Test data

Must the EUT be professionally installed?

YES NO

Does the EUT have detachable antenna(s)?

YES NO

If detachable, is the antenna connector(s) non-standard?

YES NO N/A

8.4 FCC 15.207(a) and RSS-Gen 8.8 AC power line conducted emissions limits

8.4.1 Definitions and limits

FCC:

Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

IC:

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz, shall not exceed the limits in table below.

Unless the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in table below. The more stringent limit applies at the frequency range boundaries.

Table 8.4-1: Conducted emissions limit

| Frequency of emission, MHz | Quasi-peak | Conducted limit, dB μ V | Average** |
|-------------------------------|------------|-----------------------------|-----------|
| 0.15–0.5 | 66 to 56* | 56 to 46* | 56 to 46* |
| 0.5–5 | 56 | 46 | 46 |
| 5–30 | 60 | 50 | 50 |

Note: * - The level decreases linearly with the logarithm of the frequency.

** - A linear average detector is required.

8.4.2 Test date

Start date July 17, 2018

8.4.3 Observations, settings and special notes

The EUT was set up as tabletop configuration.

The spectral scan has been corrected with transducer factors (i.e. cable loss, LISN factors, and attenuators) for determination of compliance.

A preview measurement was generated with the receiver in continuous scan mode. Emissions detected within 6 dB or above limit were re-measured with the appropriate detector against the correlating limit and recorded as the final measurement.


Receiver settings for preview measurements:

| | |
|----------------------|------------------|
| Resolution bandwidth | 9 kHz |
| Video bandwidth | 30 kHz |
| Detector mode | Peak and Average |
| Trace mode | Max Hold |
| Measurement time | 100 ms |

Receiver settings for final measurements:

| | |
|----------------------|------------------------|
| Resolution bandwidth | 9 kHz |
| Video bandwidth | 30 kHz |
| Detector mode | Quasi-Peak and Average |
| Trace mode | Max Hold |
| Measurement time | 100 ms |

8.4.4 Test data



Plot 8.4-1: Conducted emissions on phase line

Table 8.4-2: Quasi-Peak conducted emissions results on phase line

| Frequency, MHz | Q-Peak result, dB μ V | Correction, dB | Margin, dB | Limit, dB μ V |
|----------------|---------------------------|----------------|------------|-------------------|
| 0.150 | 57.5 | 9.4 | 8.5 | 66.0 |
| 0.348 | 47.0 | 9.4 | 12.0 | 59.0 |

Table 8.4-3: Average conducted emissions results on phase line

| Frequency, MHz | Average result, dB μ V | Correction, dB | Margin, dB | Limit, dB μ V |
|----------------|----------------------------|----------------|------------|-------------------|
| 0.346 | 40.5 | 9.4 | 8.6 | 49.1 |


Notes:

¹ Result (dB μ V) = receiver/spectrum analyzer value (dB μ V) + correction factor (dB)

² Correction factor (dB) = LISN factor IL (dB) + cable loss (dB) + attenuator (dB)

³ Emissions that were continuously present for a minimum of 1 second and occurred more than once for every 15 seconds observation period were considered valid emissions. The maximum value of valid emissions have been recorded.

Sample calculation: 37.1 dB μ V (result) = 26.6 dB μ V (receiver reading) + 9.5 dB (Correction factor)



Plot 8.4-2: Conducted emissions on neutral line

Table 8.4-4: Quasi-Peak conducted emissions results on neutral line

| Frequency, MHz | Q-Peak result, dB μ V | Correction, dB | Margin, dB | Limit, dB μ V |
|----------------|---------------------------|----------------|------------|-------------------|
| 0.150 | 57.5 | 9.4 | 8.5 | 66.0 |

Notes: ¹ Result (dB μ V) = receiver/spectrum analyzer value (dB μ V) + correction factor (dB)

² Correction factor (dB) = LISN factor IL (dB) + cable loss (dB) + attenuator (dB)

³ Emissions that were continuously present for a minimum of 1 second and occurred more than once for every 15 seconds observation period were considered valid emissions. The maximum value of valid emissions have been recorded.

Sample calculation: 37.1 dB μ V (result) = 26.6 dB μ V (receiver reading) + 9.5 dB (Correction factor)

8.5 FCC 15.247(a)(2) and RSS-247 5.2(a) Minimum 6 dB bandwidth for DTS systems

8.5.1 Definitions and limits

FCC:

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

ISED:

The minimum 6 dB bandwidth shall be 500 kHz.

8.5.1 Test date

Start date July 19, 2018

8.5.2 Observations, settings and special notes

Spectrum analyser settings:

| | |
|----------------------|--|
| Resolution bandwidth | 100 kHz |
| Video bandwidth | ≥3 × RBW |
| Frequency span | 30 MHz for 20 MHz channel; 80 MHz for 40 MHz channel |
| Detector mode | Peak |
| Trace mode | Max Hold |

8.5.3 Test data

Table 8.5-1: 6 dB bandwidth results

| Modulation | Frequency, MHz | 6 dB bandwidth, MHz | Limit, MHz | Margin, MHz |
|--------------|----------------|---------------------|------------|-------------|
| 802.11b | 2412 | 11.11 | 0.5 | 10.61 |
| | 2437 | 9.90 | 0.5 | 9.40 |
| | 2462 | 10.30 | 0.5 | 9.80 |
| 802.11g | 2412 | 16.32 | 0.5 | 15.82 |
| | 2437 | 15.63 | 0.5 | 15.13 |
| | 2462 | 15.63 | 0.5 | 15.13 |
| 802.11n HT20 | 2412 | 16.67 | 0.5 | 16.17 |
| | 2437 | 15.33 | 0.5 | 14.83 |
| | 2462 | 15.15 | 0.5 | 14.65 |
| 802.11n HT40 | 2422 | 35.08 | 0.5 | 34.58 |
| | 2437 | 35.11 | 0.5 | 34.61 |
| | 2452 | 35.08 | 0.5 | 34.58 |

Table 8.5-2: 99% occupied bandwidth results

| Modulation | Frequency, MHz | 99% occupied bandwidth, MHz |
|--------------|----------------|-----------------------------|
| 802.11b | 2412 | 14.50 |
| | 2437 | 14.50 |
| | 2462 | 14.50 |
| 802.11g | 2412 | 16.44 |
| | 2437 | 16.64 |
| | 2462 | 16.64 |
| 802.11n HT20 | 2412 | 17.95 |
| | 2437 | 17.80 |
| | 2462 | 17.80 |
| 802.11n HT40 | 2422 | 36.70 |
| | 2437 | 36.82 |
| | 2452 | 36.93 |

Note: there is no 99% occupied bandwidth limit in the standard's requirements, the measurement results provided for information purposes only.




Figure 8.5-1: 6 dB bandwidth on 802.11b, sample plot




Figure 8.5-2: 6 dB bandwidth on 802.11g, sample plot




Figure 8.5-3: 6 dB bandwidth on 802.11n HT20, sample plot




Figure 8.5-4: 6 dB bandwidth on 802.11n HT40, sample plot




Figure 8.5-5: 99% bandwidth on 802.11b, sample plot




Figure 8.5-6: 99% bandwidth on 802.11g, sample plot




Figure 8.5-7: 99% bandwidth on 802.11n HT20, sample plot




Figure 8.5-8: 99% bandwidth on 802.11n HT40, sample plot

8.6 FCC 15.247(b) and RSS-247 5.4 (d) Transmitter output power and e.i.r.p. requirements for DTS in 2.4 GHz

8.6.1 Definitions and limits

FCC:

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

- (3) For systems using digital modulation in the 2400–2483.5 MHz band: 1 W (30 dBm). As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
- (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

- (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.
- (ii) Fixed, point-to-point operation, as used in paragraphs (c)(1)(i) and (c)(1)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.
- (2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:
 - (i) Different information must be transmitted to each receiver.
 - (ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:
 - (A) The directional gain shall be calculated as the sum of $10 \log$ (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
 - (B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.
 - (iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.
 - (iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

ISED:

d. For DTSs employing digital modulation techniques operating in the 2400–2483.5 MHz band, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

e. Fixed point-to-point systems in the 2400–2483.5 MHz band are permitted to have an e.i.r.p. higher than 4 W provided that the higher e.i.r.p. is achieved by employing higher gain directional antennas and not higher transmitter output powers. Point-to-multipoint systems, omnidirectional applications and multiple co-located transmitters transmitting the same information are prohibited from exceeding an e.i.r.p. of 4 W.

f. Transmitters operating in the band 2400–2483.5 MHz, may employ antenna systems that emit multiple directional beams simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers, provided that the emissions comply with the following:

- i Different information must be transmitted to each receiver.
- ii If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit specified in sections 5.4(b) and 5.4(d). However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of $10 \log$ (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
- iii If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the applicable power limit specified in sections 5.4(b) and 5.4(d). If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the applicable limit specified in sections 5.4(b) and 5.4(d). In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the applicable limit specified in sections 5.4(b) and 5.4(d) by more than 8 dB.
- iv Transmitters that transmit a single directional beam shall operate under the provisions of sections 5.4(b), 5.4(d) and 5.4(e).

8.6.1 Test date

Start date

July 19, 2018

8.6.2 Observations, settings and special notes

The test was performed using PKPM1 method of KDB 558074 . Tests were performed with highest and lowest data rates, only the worst cases were presented.

8.6.3 Test data

Table 8.6-1: Output power measurements results, Taoglas Antenna configuration

| Modulation | Frequency, MHz | Conducted output power, dBm | | Margin, dB | Antenna gain, dBi | EIRP, dBm | EIRP limit, dBm | EIRP margin, dB |
|--------------|----------------|-----------------------------|-------|------------|-------------------|-----------|-----------------|-----------------|
| | | Measured | Limit | | | | | |
| 802.11b | 2412 | 15.0 | 30 | 15.0 | 5.5 | 20.5 | 36 | 15.5 |
| | 2437 | 15.4 | 30 | 14.6 | 5.5 | 20.9 | 36 | 15.1 |
| | 2462 | 15.4 | 30 | 14.6 | 5.5 | 20.9 | 36 | 15.1 |
| 802.11g | 2412 | 13.5 | 30 | 16.5 | 5.5 | 19 | 36 | 17.0 |
| | 2437 | 14.0 | 30 | 16.0 | 5.5 | 19.5 | 36 | 16.5 |
| | 2462 | 13.4 | 30 | 16.6 | 5.5 | 18.9 | 36 | 17.1 |
| 802.11n HT20 | 2412 | 12.7 | 30 | 17.3 | 5.5 | 18.2 | 36 | 17.8 |
| | 2437 | 13.0 | 30 | 17.0 | 5.5 | 18.5 | 36 | 17.5 |
| | 2462 | 12.8 | 30 | 17.2 | 5.5 | 18.3 | 36 | 17.7 |
| 802.11n HT40 | 2422 | 15.4 | 30 | 14.6 | 5.5 | 20.9 | 36 | 15.1 |
| | 2437 | 15.5 | 30 | 14.5 | 5.5 | 21.0 | 36 | 15.0 |
| | 2452 | 15.2 | 30 | 14.8 | 5.5 | 20.7 | 36 | 15.3 |

Table 8.6-2: Output power measurements results, Linx Technology Antenna configuration

| Modulation | Frequency, MHz | Conducted output power, dBm | | Margin, dB | Antenna gain, dBi | EIRP, dBm | EIRP limit, dBm | EIRP margin, dB |
|--------------|----------------|-----------------------------|-------|------------|-------------------|-----------|-----------------|-----------------|
| | | Measured | Limit | | | | | |
| 802.11b | 2412 | 15.0 | 30 | 15.0 | 2.5 | 17.5 | 36 | 18.5 |
| | 2437 | 15.4 | 30 | 14.6 | 2.5 | 17.9 | 36 | 18.1 |
| | 2462 | 15.4 | 30 | 14.6 | 2.5 | 17.9 | 36 | 18.1 |
| 802.11g | 2412 | 13.5 | 30 | 16.5 | 2.5 | 16.0 | 36 | 20.0 |
| | 2437 | 14.0 | 30 | 16.0 | 2.5 | 16.5 | 36 | 19.5 |
| | 2462 | 13.4 | 30 | 16.6 | 2.5 | 15.9 | 36 | 20.1 |
| 802.11n HT20 | 2412 | 12.7 | 30 | 17.3 | 2.5 | 15.2 | 36 | 20.8 |
| | 2437 | 13.0 | 30 | 17.0 | 2.5 | 15.5 | 36 | 20.5 |
| | 2462 | 12.8 | 30 | 17.2 | 2.5 | 15.3 | 36 | 20.7 |
| 802.11n HT40 | 2422 | 15.4 | 30 | 14.6 | 2.5 | 17.9 | 36 | 18.1 |
| | 2437 | 15.5 | 30 | 14.5 | 2.5 | 18.0 | 36 | 18.0 |
| | 2452 | 15.2 | 30 | 14.8 | 2.5 | 17.7 | 36 | 18.3 |

8.7 FCC 15.247(d) and RSS-247 5.5 Spurious (out-of-band) unwanted emissions

8.7.1 Definitions and limits

FCC:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

ISED:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Table 8.7-1: FCC §15.209 and RSS-Gen – Radiated emission limits

| Frequency, MHz | Field strength of emissions | | Measurement distance, m |
|----------------|-----------------------------|-----------------------------------|-------------------------|
| | µV/m | dBµV/m | |
| 0.009–0.490 | 2400/F | 67.6 – 20 × log ₁₀ (F) | 300 |
| 0.490–1.705 | 24000/F | 87.6 – 20 × log ₁₀ (F) | 30 |
| 1.705–30.0 | 30 | 29.5 | 30 |
| 30–88 | 100 | 40.0 | 3 |
| 88–216 | 150 | 43.5 | 3 |
| 216–960 | 200 | 46.0 | 3 |
| above 960 | 500 | 54.0 | 3 |

Notes: In the emission table above, the tighter limit applies at the band edges.

For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test

Table 8.7-2: ISED restricted frequency bands

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090–0.110 | 12.57675–12.57725 | 399.9–410 | 7.25–7.75 |
| 0.495–0.505 | 13.36–13.41 | 608–614 | 8.025–8.5 |
| 2.1735–2.1905 | 16.42–16.423 | 960–1427 | 9.0–9.2 |
| 3.020–3.026 | 16.69475–16.69525 | 1435–1626.5 | 9.3–9.5 |
| 4.125–4.128 | 16.80425–16.80475 | 1645.5–1646.5 | 10.6–12.7 |
| 4.17725–4.17775 | 25.5–25.67 | 1660–1710 | 13.25–13.4 |
| 4.20725–4.20775 | 37.5–38.25 | 1718.8–1722.2 | 14.47–14.5 |
| 5.677–5.683 | 73–74.6 | 2200–2300 | 15.35–16.2 |
| 6.215–6.218 | 74.8–75.2 | 2310–2390 | 17.7–21.4 |
| 6.26775–6.26825 | 108–138 | 2483.5–2500 | 22.01–23.12 |
| 6.31175–6.31225 | 149.9–150.05 | 2655–2900 | 23.6–24.0 |
| 8.291–8.294 | 156.52475–156.52525 | 3260–3267 | 31.2–31.8 |
| 8.362–8.366 | 156.7–156.9 | 3332–3339 | 36.43–36.5 |
| 8.37625–8.38675 | 162.0125–167.17 | 3345.8–3358 | |
| 8.41425–8.41475 | 167.72–173.2 | 3500–4400 | |
| 12.29–12.293 | 240–285 | 4500–5150 | Above 38.6 |
| 12.51975–12.52025 | 322–335.4 | 5350–5460 | |

Note: Certain frequency bands listed in Table 8.7-2 and above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

Table 8.7-3: FCC restricted frequency bands

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090–0.110 | 16.42–16.423 | 399.9–410 | 4.5–5.15 |
| 0.495–0.505 | 16.69475–16.69525 | 608–614 | 5.35–5.46 |
| 2.1735–2.1905 | 16.80425–16.80475 | 960–1240 | 7.25–7.75 |
| 4.125–4.128 | 25.5–25.67 | 1300–1427 | 8.025–8.5 |
| 4.17725–4.17775 | 37.5–38.25 | 1435–1626.5 | 9.0–9.2 |
| 4.20725–4.20775 | 73–74.6 | 1645.5–1646.5 | 9.3–9.5 |
| 6.215–6.218 | 74.8–75.2 | 1660–1710 | 10.6–12.7 |
| 6.26775–6.26825 | 108–121.94 | 1718.8–1722.2 | 13.25–13.4 |
| 6.31175–6.31225 | 123–138 | 2200–2300 | 14.47–14.5 |
| 8.291–8.294 | 149.9–150.05 | 2310–2390 | 15.35–16.2 |
| 8.362–8.366 | 156.52475–156.52525 | 2483.5–2500 | 17.7–21.4 |
| 8.37625–8.38675 | 156.7–156.9 | 2690–2900 | 22.01–23.12 |
| 8.41425–8.41475 | 162.0125–167.17 | 3260–3267 | 23.6–24.0 |
| 12.29–12.293 | 167.72–173.2 | 3332–3339 | 31.2–31.8 |
| 12.51975–12.52025 | 240–285 | 3345.8–3358 | 36.43–36.5 |
| 12.57675–12.57725 | 322–335.4 | 3600–4400 | Above 38.6 |
| 13.36–13.41 | | | |

8.7.1 Test date

Start date July 19, 2018

8.7.2 Observations, settings and special notes

The spectrum was searched from 30 MHz to the 10th harmonic.

EUT was set to transmit continuously. Tests were performed with EUT set to highest and lowest data rate, different antenna configurations and modulation schemes were investigated, only the worst case are presented.

Radiated measurements were performed at a distance of 3 m. Cabinet radiated emissions were performed with antenna port terminated with 50 Ω load. Since fundamental power was tested using the maximum peak conducted output power procedure to demonstrate compliance, the spurious emissions limit is -20 dBc/100 kHz.

Spectrum analyzer settings for conducted spurious emissions measurements:

| | |
|-----------------------|----------|
| Resolution bandwidth: | 100 kHz |
| Video bandwidth: | 300 kHz |
| Detector mode: | Peak |
| Trace mode: | Max Hold |

Spectrum analyzer settings for radiated measurements within restricted bands below 1 GHz:

| | |
|-----------------------|----------|
| Resolution bandwidth: | 100 kHz |
| Video bandwidth: | 300 kHz |
| Detector mode: | Peak |
| Trace mode: | Max Hold |

Spectrum analyzer settings for peak radiated measurements within restricted bands above 1 GHz:

| | |
|-----------------------|----------|
| Resolution bandwidth: | 1 MHz |
| Video bandwidth: | 3 MHz |
| Detector mode: | Peak |
| Trace mode: | Max Hold |


Spectrum analyzer settings for average conducted measurements within restricted bands above 1 GHz:

| | |
|-----------------------|-----------------------|
| Resolution bandwidth: | 1 MHz |
| Video bandwidth: | 3 MHz |
| Detector mode: | power averaging (RMS) |
| Trace mode: | averaging (RMS) |

Spectrum analyzer settings for average radiated measurements within restricted bands above 1 GHz:


| | |
|-----------------------|----------|
| Resolution bandwidth: | 1 MHz |
| Video bandwidth: | 10 Hz |
| Detector mode: | Peak |
| Trace mode: | Max Hold |

8.7.4 Test data




Date: 19.JUL.2018 13:57:23

Figure 8.7-1: Conducted spurious emission at band edge outside restricted band, low channel, 802.11b




Date: 12.AUG.2018 13:54:06

Figure 8.7-2: Conducted spurious emissions at band edge outside restricted band, High channel, 802.11b



Date: 12.AUG.2018 13:57:09


Figure 8.7-3: Conducted spurious emission at band edge outside restricted band, low channel, 802.11g



Date: 12.AUG.2018 13:53:18


Figure 8.7-4: Conducted spurious emissions at band edge outside restricted band, High channel, 802.11g

8.7.4 Test data, continued




Date: 12.AUG.2018 13:55:55

Figure 8.7-5: Conducted spurious emission at band edge outside restricted band, low channel, 802.11n HT20




Date: 12.AUG.2018 13:51:52

Figure 8.7-6: Conducted spurious emissions at band edge outside restricted band, High channel, 802.11n HT20



Date: 12.AUG.2018 14:01:40

Figure 8.7-7: Conducted spurious emission at band edge outside restricted band, low channel, 802.11n HT40



Date: 12.AUG.2018 13:44:01

Figure 8.7-8: Conducted spurious emissions at band edge outside restricted band, High channel, 802.11n HT40

8.7.1 Test data, continued




Figure 8.7-9: Conducted spurious emissions outside restricted band, Low channel, 802.11b




Figure 8.7-10: Conducted spurious emissions outside restricted band, Mid channel, 802.11b






Figure 8.7-11: Conducted spurious emissions outside restricted band, High channel, 802.11b

8.7.1 Test data, continued




Date: 12.AUG.2018 14:12:09

Figure 8.7-12: Conducted spurious emissions outside restricted band, Low channel, 802.11g



Date: 12.AUG.2018 14:12:58


Figure 8.7-13: Conducted spurious emissions outside restricted band, Mid channel, 802.11g



Date: 12.AUG.2018 14:13:41


Figure 8.7-14: Conducted spurious emissions outside restricted band, High channel, 802.11g

8.7.1 Test data, continued




Date: 12.AUG.2018 14:09:35

Figure 8.7-15: Conducted spurious emissions outside restricted band, Low channel, 802.11n Ht20



Date: 12.AUG.2018 14:10:20


Figure 8.7-16: Conducted spurious emissions outside restricted band, Mid channel, 802.11n Ht20



Date: 12.AUG.2018 14:10:55


Figure 8.7-17: Conducted spurious emissions outside restricted band, High channel, 802.11n Ht20

8.7.1 Test data, continued




Date: 12.AUG.2018 14:05:52

Figure 8.7-18: Conducted spurious emissions outside restricted band, Low channel, 802.11n Ht40



Date: 12.AUG.2018 14:05:12


Figure 8.7-19: Conducted spurious emissions outside restricted band, Mid channel, 802.11n Ht40



Date: 12.AUG.2018 14:07:15


Figure 8.7-20: Conducted spurious emissions outside restricted band, High channel, 802.11n Ht40

8.7.4 Test data, continued




Date: 12.AUG.2018 14:29:33

Figure 8.7-21: Conducted spurious emissions within restricted band, Low channel, 802.11b



Date: 12.AUG.2018 14:30:23

Figure 8.7-22: Conducted spurious emissions within restricted band, Mid channel, 802.11b




Date: 12.AUG.2018 14:31:04

Figure 8.7-23: Conducted spurious emissions within restricted band, High channel, 802.11b

Note: EUT's antenna max gain and ground reflection factors below 1 GHz have been included in the factors of the plots above.

8.7.1 Test data, continued



Date: 12.AUG.2018 14:28:19

Figure 8.7-24: Conducted spurious emissions within restricted band, Low channel, 802.11g




Figure 8.7-25: Conducted spurious emissions within restricted band, Mid channel, 802.11g






Figure 8.7-26: Conducted spurious emissions within restricted band, High channel, 802.11g

Note: EUT's antenna max gain and ground reflection factors below 1 GHz have been included in the factors of the plots above.


8.7.1 Test data, continued



Date: 12.AUG.2018 14:32:08




Date: 12.AUG.2018 14:32:54




Date: 12.AUG.2018 14:34:04

Note: EUT's antenna max gain and ground reflection factors below 1 GHz have been included in the factors of the plots above.


8.7.1 Test data, continued



Date: 12.AUG.2018 14:35:16




Date: 12.AUG.2018 14:36:22



Date: 12.AUG.2018 14:36:55


Note: EUT's antenna max gain and ground reflection factors below 1 GHz have been included in the factors of the plots above.

8.7.4 Test data, continued




Date: 12.AUG.2018 13:21:00

Figure 8.7-33: Conducted spurious emission at band edge of restricted band, low channel, 802.11b




Date: 12.AUG.2018 13:23:08

Figure 8.7-34: Conducted spurious emissions at band edge of restricted band, High channel, 802.11b



Date: 12.AUG.2018 13:20:22


Figure 8.7-35: Conducted spurious emission at band edge of restricted band, low channel, 802.11g



Date: 12.AUG.2018 13:24:08


Figure 8.7-36: Conducted spurious emissions at band edge of restricted band, High channel, 802.11g

8.7.4 Test data, continued




Date: 12.AUG.2018 13:19:31

Figure 8.7-37: Conducted spurious emission at band edge of restricted band, low channel, 802.11n HT20




Date: 12.AUG.2018 13:25:30

Figure 8.7-38: Conducted spurious emissions at band edge of restricted band, High channel, 802.11n HT20



Date: 12.AUG.2018 13:16:56

Figure 8.7-39: Conducted spurious emission at band edge of restricted band, low channel, 802.11n HT40



Date: 12.AUG.2018 13:26:21

Figure 8.7-40: Conducted spurious emissions at band edge of restricted band, High channel, 802.11n HT40

Note: Transmitter spurious emission calculation as below:

$$E = \text{EIRP} - 20\log D + 104.8 = -41.30 - 20\log 3 + 104.8 = 53.96 \text{ dB}\mu\text{V/m at 3m}$$

margin of compliance = 54 - 42.85 = 11.15 dB

where: E = electric field strength in dB μ V/m, EIRP = equivalent isotropic radiated power in dBm = -41.30 dBm

D = specified measurement distance in meters = 3 m

Average field strength limit = 54 dB μ V/m at 3m

8.7.4 Test data, continued




Figure 8.7-41: Cabinet Radiated spurious emissions 1 to 18 GHz, Low channel





Figure 8.7-42: Cabinet Radiated spurious emissions 1 to 18 GHz, mid channel



Note: Spectrum was investigated from 30 MHz to 25 GHz. No spurious emission related to RF portion were detected within 6 dB below the limit

8.8 FCC 15.247(e) and RSS-247 5.2(b) Power spectral density for digitally modulated devices

8.8.1 Definitions and limits

FCC:

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

ISED:

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

8.8.1 Test date

Start date July 19, 2018

8.8.2 Observations, settings and special notes

The test was performed using method PKPSD (peak PSD).


Spectrum analyser settings:

| | |
|-----------------------|---------------------------------|
| Resolution bandwidth: | 3 kHz \leq RBW \leq 100 kHz |
| Video bandwidth: | $\geq 3 \times$ RBW |
| Frequency span: | 1.5 times the OBW |
| Detector mode: | Peak |
| Trace mode: | Max hold |

8.8.3 Test data


Table 8.8-1: PSD measurements results

| Modulation | Frequency, MHz | PSD, dBm/3 kHz | PSD limit, dBm/3 kHz | Margin, dB |
|--------------|----------------|----------------|----------------------|------------|
| 802.11b | 2412 | -9.1 | 8 | 17.1 |
| | 2437 | -7.6 | 8 | 15.6 |
| | 2462 | -9.1 | 8 | 17.1 |
| 802.11g | 2412 | -15.9 | 8 | 23.9 |
| | 2437 | -16.3 | 8 | 24.3 |
| | 2462 | -15.9 | 8 | 23.9 |
| 802.11n HT20 | 2412 | -16.9 | 8 | 24.9 |
| | 2437 | -16.6 | 8 | 24.6 |
| | 2462 | -15.8 | 8 | 23.8 |
| 802.11n HT40 | 2422 | -22.0 | 8 | 30.0 |
| | 2437 | -21.8 | 8 | 29.8 |
| | 2457 | -22.1 | 8 | 30.1 |




Date: 19 JUL 2018 13:49:29

Figure 8.8-1: PSD sample plot on 802.11b




Date: 12 AUG 2018 09:05:17

Figure 8.8-2: PSD sample plot on 802.11b



Date: 12 AUG 2018 10:15:42

Figure 8.8-3: PSD sample plot on 802.11n HT20




Date: 12 AUG 2018 11:05:44


Figure 8.8-4: PSD sample plot on 802.11n HT40

Section 9. Block diagrams of test set-ups


9.1 Radiated emissions set-up for frequencies below 1 GHz



9.2 Radiated emissions set-up for frequencies above 1 GHz



9.3 Conducted emissions set-up



9.4 Antenna port set-up

