



RADIO TEST REPORT

Test Report No. : 27AE0132-HO-A

Applicant : The Yokohama Rubber Company, Limited.
Type of Equipment : Air pressure transmitter
Model No. : FW01TR
Test standard : FCC Part 15 Subpart C Section 15.231:2006
FCC ID : UNK-FW01
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Apex Co., Ltd.
2. The results in this report apply only to the sample tested.
3. This equipment is in compliance with above regulation.
4. The test results in this report are traceable to the national or international standards.

Date of test : August 24, 2006

Tested by : M. Kosaka
Makoto Kosaka
EMC Services

Approved by : N. Sakamoto
Naoki Sakamoto
Group Leader of EMC Services

CONTENTS	PAGE
SECTION 1: Client information.....	3
SECTION 2: Equipment under test (E.U.T.)	3
SECTION 3: Test specification, procedures & results	4
SECTION 4: Operation of E.U.T. during testing.....	7
SECTION 5: Radiated emission (Fundamental and Spurious Emission)	8
APPENDIX 1: Photographs of test setup.....	9
Radiated emission.....	9
Worst case position	10
APPENDIX 2: Data of EMI test	11
Radiated Emission (Electric Field Strength of Fundamental and Spurious Emission)	11
Duty Factor Calculation and Transmitting time and interval	12
-20dB Bandwidth.....	13
99% Occupied Bandwidth.....	14
APPENDIX 3:Test Instruments.....	15

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

SECTION 1: Client information

Company Name : The Yokohama Rubber Company, Limited
Address : 2-1 Oiwake, Hiratsuka City, Kanagawa Pref., 254-8601 Japan
Telephone Number : +81-463-35-9701
Facsimile Number : +81-463-35-9771
Contact Person : Michito Kaneko

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Air pressure transmitter
Model No. : FW01TR
Serial No. : FW01-06100126
Rating : DC 3.0V(CR2450)
Country of Manufacture : Japan
Receipt Date of Sample : August 24, 2006
Condition of EUT : Production model
Modification of EUT : No modification by the test lab.

2.2 Product Description

Model No: FW01TR (referred to as the EUT in this report) is the Air pressure transmitter.

Equipment Type : Transmitter
Frequency of Operation : 315MHz
Type of modulation : FSK
Power Control : No
ITU code : F1D
Method of Frequency Generation : Crystal

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C : 2006
Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.231 Periodic operation in the band 40.66 - 40.70MHz
and above 70MHz

FCC 15.31 (e)

This test was performed with the New Battery (DC 3.0V) and the constant voltage was supplied to the EUT during the tests. Therefore, the EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

3.2 Procedures and results

No.	Item	Test Procedure	Specification	Deviation	Worst margin	Results
1	Transmitting time and Interval	<FCC> ANSI C63.4:2003 13. Measurement of intentional radiators <IC> -	<FCC> Section 15.231(e) <IC> RSS-210 A1.1.5	N/A	-	Complied
2	Electric Field Strength of Fundamental Emission	<FCC> ANSI C63.4:2003 13. Measurement of intentional radiators <IC> RSS-Gen 4.6	<FCC> Section 15.231(e) <IC> RSS-210 A1.1.5	N/A	22.6dB 315.01MHz Horizontal, AV	Complied
3	Electric Field Strength of Spurious Emission	<FCC> ANSI C63.4:2003 13. Measurement of intentional radiators <IC> RSS-Gen 4.7	<FCC> Section 15.205 Section 15.209 Section 15.231(e) <IC> RSS-210 A1.1.5, 2.6, 2.7	N/A	21.8dB 1260.07MHz Vertical, AV	Complied
4	-20dB Bandwidth	<FCC> ANSI C63.4:2003 13. Measurement of intentional radiators <IC> -	<FCC> Section 15.231(c) <IC> Reference data	N/A	-	Complied
5	Conducted emission	<FCC> ANSI C63.4:2003 7. AC powerline conducted emission measurements <IC> RSS-Gen 7.2.2	<FCC> Section 15.207 <IC> RSS-Gen 7.2.2	-	N/A*1)	N/A

Note: UL Apex's EMI Work procedures No. QPM05 and QPM15

*1) The test is not applicable since the EUT does not have AC Mains.

3.3 Addition to standards

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	99% Occupied Band Width	<IC> RSS-Gen 4.4.1	<IC> RSS-210 A1.1.3	Conducted	N/A	N/A	N/A

3.4 Uncertainty

Radiated Emission Test

The measurement uncertainty (with a 95% confidence level) for this test using Biconical antenna is ± 4.59 dB.
 The measurement uncertainty (with a 95% confidence level) for this test using Logperiodic antenna is ± 4.62 dB.
 The measurement uncertainty (with a 95% confidence level) for this test using Horn Antenna is ± 5.27 dB.
 The data listed in this test report has enough margin, more than the site margin.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

3.5 Test Location

UL Apex Co., Ltd. Head Office EMC Lab. *NVLAP Lab. code: 200572-0

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116 Facsimile : +81 596 24 8124

	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	313583	IC4247A	19.2 x 11.2 x 7.7m	7.0 x 6.0m	Preparation room
No.2 semi-anechoic chamber	655103	IC4247A-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	148738	IC4247A-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	
No.3 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	134570	IC4247A-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	-
No.4 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	-	6.0 x 6.0 x 3.9m	N/A	-
No.6 shielded room	-	-	4.0 x 4.5 x 2.7m	2.0 x 2.0 m	-
No.6 measurement room	-	-	4.75 x 5.4 x 3.0m	4.75 x 5.4 m	-
No.7 shielded room	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	-	3.1 x 5.0 x 2.7m	N/A	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3 and No.4 semi-anechoic chambers and No.7 shielded room.

3.6 Test set up, Test instruments and Data of EMI

Refer to APPENDIX 1 to 3.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)


SECTION 4: Operation of E.U.T. during testing

4.1 Operating Modes

The mode is used : Continuous Transmitting mode

Justification : The system was configured in typical fashion (as a customer would normally use it) for testing.

4.2 Configuration and peripherals



* Setup was taken into consideration and test data was taken under worse case conditions.

Description of EUT

No	Item	Model number	Serial number	Manufacturer	Remarks
A	Air pressure transmitter	FW01TR	FW01-06100126	The Yokohama Rubber Co., Ltd.	EUT

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)

SECTION 5: Radiated emission (Fundamental and Spurious Emission)

5.1 Operating environment

Test place : No.2 semi anechoic chamber
Temperature : See data
Humidity : See data

5.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0m by 0.5m, raised 80cm above the conducting ground plane. The EUT was set on the center of the tabletop. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength. A drawing of the set up is shown in the photos of APPENDIX 1.

5.3 Test conditions

Frequency range : 30MHz-3200MHz
Test distance : 3m
EUT position : Top of Polyurethane table
EUT operation mode : See Clause 4.1

5.4 Test procedure

The Radiated Electric Field Strength intensity has been measured on No.2 semi anechoic chamber with a ground plane and at a distance of 3m.

The measuring antenna height was varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

The radiated emission measurements were made with the following detector function of the test receiver.

	Below or equal to 1GHz	Above 1GHz (FCC15.205)	Above 1GHz (FCC15.231)
Detector Type	Peak and AV (=Peak with Duty factor)	Peak and AV (=Peak with Duty factor)	Peak and AV (=Peak with Duty factor)
IF Bandwidth	120kHz	PK: S/A:RBW 1MHz, VBW:1MHz	PK: S/A:RBW 1MHz, VBW:1MHz

- The carrier level (or, noise levels) was (or were) measured at each position of all three axes X, Y and Z, and the position that has the maximum noise was determined.

With the position, the noise levels of all the frequencies was measured.

5.5 Results

Summary of the test results: Pass

Date: August 24, 2006

Tested by: Makoto Kosaka

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(14.06.06)