





TEST REPORT FROM RFI GLOBAL SERVICES LTD

Test of: DC10-US

FCC ID: UOJ-DG03T

IC Certification Number: 6769A-DG03T

To: FCC Part 15.247: 2010 Subpart C, RSS-210 Issue 8 December 2010 & RSS-Gen Issue 3 December 2010

Test Report Serial No: RFI-RPT-RP79710JD03A V2.0

Version 2.0 Supersedes All Previous Versions

This Test Report Is Issued Under The Authority Of Chris Guy, Head of Global Approvals::	1. M. Wester
Checked By:	lan Watch
Signature:	1.M. Wester
Date of Issue:	24 March 2011

This report is issued in Adobe Acrobat portable document format (PDF). It is only a valid copy of the report if it is being viewed in PDF format with the following security options not allowed: Changing the document, Selecting text and graphics, Adding or changing notes and form fields.

This report may not be reproduced other than in full, except with the prior written approval of RFI Global Services Ltd. The results in this report apply only to the sample(s) tested.

Pavilion A, Ashwood Park, Ashwood Way, Basingstoke, Hampshire RG23 8BG Telephone: +44 (0)1256 312000 Facsimile: +44 (0)1256 312001 Email: info@rfi-global.com Website: www.rfi-global.com This page has been left intentionally blank.

Page 2 of 28 RFI Global Services Ltd

Table of Contents

1. Customer Information	4
2. Summary of Testing	5 5 5 6 6
3. Equipment Under Test (EUT)	7 7 7 7 8 8
4. Operation and Monitoring of the EUT during Testing	9 9 9
5. Measurements, Examinations and Derived Results 5.1. General Comments 5.2. Test Results 5.2.1. Transmitter AC Conducted Spurious Emissions 5.2.2. Transmitter 6 dB Bandwidth 5.2.3. Transmitter 20 dB Bandwidth 5.2.4. Transmitter Power Spectral Density 5.2.5. Transmitter Maximum Peak Output Power 5.2.6. Transmitter Radiated Emissions 5.2.7. Transmitter Radiated Emissions 5.2.8. Transmitter Band Edge Radiated Emissions	
6. Measurement Uncertainty	27
Appendix 1. Test Equipment Used	28

RFI Global Services Ltd Page 3 of 28

VERSION 2.0 ISSUE DATE: 24 MARCH 2011

1. Customer Information

Company Name:	Comfort Audio
Address:	Slottsmollan
	Halmstad
	302 31
	Sweden

Page 4 of 28 RFI Global Services Ltd

2. Summary of Testing

2.1. General Information

Specification Reference:	47CFR15.247	
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications) 2010: Part 15 Subpart C (Intentional Radiators) - Section 15.247	
Specification Reference:	47CFR15.207 and 47CFR15.209	
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications) 2010: Part 15 Subpart C (Intentional Radiators) - Sections 15.207 and 15.209	
Specification Reference:	RSS-Gen Issue 3 December 2010	
Specification Title:	General Requirements and Information for the Certification of Radio Apparatus	
Specification Reference:	RSS-210 Issue 8 December 2010	
Specification Title:	Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment.	
Site Registration:	FCC: 209735; Industry Canada: 3245B-2	
Location of Testing:	RFI Global Services Ltd, Wade Road, Basingstoke, Hampshire, RG24 8AH.	
Test Dates:	06 March 2011 to 11 March 2011	

2.2. Summary of Test Results

IC Reference	Measurement	Result
RSS-Gen 7.2.4	Transmitter AC Conducted Emissions	②
RSS-Gen 4.6.2 RSS-210 A8.2(a)	Transmitter 6 dB Bandwidth	Ø
RSS-Gen 4.6.1/4.6.3	Transmitter 20 dB Bandwidth	②
RSS-210 A8.2(b)	Transmitter Power Spectral Density	②
RSS-Gen 4.8 RSS-210 A8.4(4)	Transmitter Maximum Peak Output Power	Ø
RSS-Gen 4.9 RSS-210 A8.5	Transmitter Radiated Emissions	②
RSS-Gen 4.9 RSS-210 A8.5	Transmitter Band Edge Radiated Emissions	②
	RSS-Gen 7.2.4 RSS-Gen 4.6.2 RSS-210 A8.2(a) RSS-Gen 4.6.1/4.6.3 RSS-210 A8.2(b) RSS-Gen 4.8 RSS-210 A8.4(4) RSS-Gen 4.9 RSS-Gen 4.9 RSS-Gen 4.9	RSS-Gen 7.2.4 Transmitter AC Conducted Emissions RSS-Gen 4.6.2 RSS-210 A8.2(a) Transmitter 6 dB Bandwidth RSS-Gen 4.6.1/4.6.3 Transmitter 20 dB Bandwidth RSS-210 A8.2(b) Transmitter Power Spectral Density RSS-Gen 4.8 RSS-210 A8.4(4) Transmitter Maximum Peak Output Power RSS-Gen 4.9 RSS-Gen 4.9 RSS-Gen 4.9 RSS-Gen 4.9 RSS-Gen 4.9 Transmitter Radiated Emissions RSS-Gen 4.9 Transmitter Radiated Emissions

Key to Results



= Did not comply

RFI Global Services Ltd Page 5 of 28

2.3. Methods and Procedures

Reference:	ANSI C63.4 (2009)
Title:	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
Reference:	ANSI C63.10 (2009)
Title:	American National Standard for Testing Unlicensed Wireless Devices

2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

Page 6 of 28 RFI Global Services Ltd

3. Equipment Under Test (EUT)

3.1. Identification of Equipment Under Test (EUT)

Brand Name:	Comfort Audio
Model Name or Number:	Conference Microphone DC10-US
Serial Number:	SN0008808
Hardware Version Number:	CC08G
Software Version Number:	1.21a
FCC ID:	UOJ-DG03T
IC Certification Number::	6769A-DG03T

Description:	Mains Charger
Brand Name:	Comfort Audio
Model Name or Number:	FW7600/05
Serial Number:	1108B

Description:	External clip on microphone	
Brand Name:	Comfort Audio	
Model Name or Number:	Clip on microphone	
Serial Number:	None stated	

3.2. Description of EUT

The equipment under test was an advanced conference microphone.

3.3. Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

RFI Global Services Ltd Page 7 of 28

3.4. Additional Information Related to Testing

Tested Technology:	Digital Transmission System		
Type of Unit:	Transmitter		
Modulation:	FSK		
Power Supply Requirement:	Nominal 3.7V		
Maximum Conducted Peak Output Power:	7.7 dBm		
Transmit Frequency Range:	902 MHz to 928 MHz		
Transmit Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Bottom	1	904.65
	Middle	19	915.45
	Тор	38	926.85

3.5. Support Equipment

No support equipment was used to exercise the EUT during testing:

Page 8 of 28 RFI Global Services Ltd

4. Operation and Monitoring of the EUT during Testing

4.1. Operating Modes

The EUT was tested in the following operating mode(s):

- Continuous transmit mode (default and only supported operating mode) on bottom, middle and top channels as required.
- The EUT was only capable of operating in a continuous transmission mode and therefore had no idle or receive only mode

4.2. Configuration and Peripherals

The EUT was tested in the following configuration(s):

- Charging via supplied mains charger.
- External microphone attached.
- All the ports were terminated for the radiated emissions tests apart from the service port which will not be used by the final user and, therefore, was not terminated (as there is no commercially available cable).

RFI Global Services Ltd Page 9 of 28

ISSUE DATE: 24 MARCH 2011

5. Measurements, Examinations and Derived Results

5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to Section 6. Measurement Uncertainty for details.

Page 10 of 28 RFI Global Services Ltd

5.2. Test Results

5.2.1. Transmitter AC Conducted Spurious Emissions

Test Summary:

Test Engineer:	Crawford Lindsay	Test Date:	11 March 2011
Test Sample Serial No:	SN0008808		

FCC Part:	15.207
Test Method Used:	As detailed in ANSI C63.10 Section 6.2 referencing ANSI C63.4

Environmental Conditions:

Temperature (°C):	27
Relative Humidity (%):	29

Results: Quasi Peak


Frequency (MHz)	Line	Level (dBμV)	Limit (dB _µ V)	Margin (dB)	Result
0.348	Live	44.1	59.0	14.9	Complied
0.569	Live	37.9	56.0	18.1	Complied
2.225	Neutral	41.4	56.0	14.6	Complied
2.679	Neutral	42.7	56.0	13.3	Complied
3.300	Neutral	43.1	56.0	12.9	Complied
3.984	Neutral	41.3	56.0	14.7	Complied

Results: Average

Frequency (MHz)	Line	Level (dBμV)	Limit (dB _µ V)	Margin (dB)	Result
0.344	Live	29.4	49.1	19.7	Complied
0.564	Neutral	28.9	46.0	17.1	Complied
0.789	Neutral	26.6	46.0	19.4	Complied
1.239	Neutral	27.0	46.0	19.0	Complied
2.229	Neutral	30.7	46.0	15.3	Complied
2.679	Neutral	31.9	46.0	14.1	Complied
3.296	Neutral	32.8	46.0	13.2	Complied
3.908	Neutral	32.8	46.0	13.2	Complied

RFI Global Services Ltd Page 11 of 28

Transmitter AC Conducted Spurious Emissions (continued)



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying tables.

Page 12 of 28 RFI Global Services Ltd

5.2.2. Transmitter 6 dB Bandwidth

Test Summary:

Test Engineer:	Crawford Lindsay	Test Date:	7 March 2011
Test Sample Serial No:	SN0008808		

FCC Part:	15.247(a)(2)
Test Method Used:	As detailed in ANSI C63.10 Section 6.9.1 referencing KDB 558074 "Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005".

Environmental Conditions:

Temperature (°C):	23
Relative Humidity (%):	24

Results:

Channel	6 dB Bandwidth (MHz)	Limit (MHz)	Margin (MHz)	Result
Bottom	0.529	≥0.5	0.029	Complied
Middle	0.529	≥0.5	0.029	Complied
Тор	0.529	≥0.5	0.029	Complied


Note(s):


- 1. These measurements were performed radiated as the EUT has an integral antenna and does not have an external antenna port.
- 2. The measurements were taken with a RBW of 100 kHz as specified in FCC KDB 558074 "Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005".


RFI Global Services Ltd Page 13 of 28

Transmitter 6 dB Bandwidth (continued)

Results:







Page 14 of 28 RFI Global Services Ltd

5.2.3. Transmitter 20 dB Bandwidth

Test Summary:

Test Engineer:	Crawford Lindsay	Test Date:	7 March 2011
Test Sample Serial No:	SN0008808		

FCC Part:	2.1049
Test Method Used:	As detailed in ANSI C63.10 Section 6.9.1 referencing KDB 558074 "Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005"

Environmental Conditions:

Temperature (°C):	23
Relative Humidity (%):	24

Results:


Channel	20 dB Bandwidth (kHz)
Bottom	745.491
Middle	751.503
Тор	745.491


Note(s):


- 1. These measurements were performed radiated as the EUT has an integral antenna and does not have an external antenna port.
- 2. The measurements were taken with a RBW of 100 kHz as allowable under KDB 558074 "Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005".

RFI Global Services Ltd Page 15 of 28

Transmitter 20 dB Bandwidth (continued)







Page 16 of 28 RFI Global Services Ltd

5.2.4. Transmitter Power Spectral Density

Test Summary:

Test Engineer:	Andrew Edwards	Test Date:	11 March 2011
Test Sample Serial No:	SN0008808		

FCC Part:	15.247(e)
Test Method Used:	As detailed in ANSI C63.10 Section 6.11.2

Environmental Conditions:

Temperature (°C):	24
Relative Humidity (%):	21

Results:

Channel	Output Power (dBm/3 kHz)	Limit (dBm/3 kHz)	Margin (dB)	Result
Bottom	1.8	8.0	6.2	Complied
Middle	0.5	8.0	7.5	Complied
Тор	-2.2	8.0	10.2	Complied

Note(s):

1. These tests were performed radiated as the EUT has an integral antenna and does not have an external antenna port.


RFI Global Services Ltd Page 17 of 28

Transmitter Power Spectral Density (continued)

Results:







Page 18 of 28 RFI Global Services Ltd

5.2.5. Transmitter Maximum Peak Output Power

Test Summary:

Test Engineer:	Crawford Lindsay	Test Date:	6 March 2011
Test Sample Serial No:	SN0008808		

FCC Part:	15.247(b)(3)
Test Method Used:	As detailed in ANSI C63.10 Section 6.10.2 and Sections 6.3 and 6.6 referencing ANSI C63.4 (see note below)

Environmental Conditions:

Temperature (°C):	26
Relative Humidity (%):	24

Results:


Channel	Conducted Peak Power (dBm)	Declared Antenna Gain (dBd)	ERP (dBm)	ERP to EIRP Conversion Factor	EIRP (dBm)	De Facto EIRP Limit (dBm)	Margin (dB)	Result
Bottom	7.7	-3.5	4.2	2.15	6.35	36.0	29.65	Complied
Middle	6.6	-3.5	3.1	2.15	5.25	36.0	30.75	Complied
Тор	4.3	-3.5	0.8	2.15	2.95	36.0	33.05	Complied


Note(s):


- 1. These tests were performed radiated; therefore the EUT antenna gain is encompassed in the final result and not measurable.
- 2. As the EUT has an integral antenna, in order to obtain the conducted peak power (into the antenna) the declared antenna gain was subtracted from the measured ERP.
- 3. Tests were performed using a combination of the conducted test method described in ANSI C63.10 Section 6.10.1 and the test methods for radiated emissions measurements described in Sections 6.3 and 6.6. The reason for this being that the measurements were performed radiated as the EUT has an integral antenna and does have not an external antenna port.

RFI Global Services Ltd Page 19 of 28

Transmitter Maximum Peak Output Power (continued)







Page 20 of 28 RFI Global Services Ltd

5.2.6. Transmitter Radiated Emissions

Test Summary:

Test Engineer:	Crawford Lindsay	Test Date:	6 March 2011
Test Sample Serial No:	SN0008808		

FCC Part:	15.247(d) & 15.209(a)
Test Method Used:	As detailed in ANSI C63.10 Sections 6.3 and 6.5 referencing ANSI C63.4
Frequency Range	30 MHz to 1000 MHz

Environmental Conditions:

Temperature (°C):	26
Relative Humidity (%):	24

Results: Quasi-Peak


Frequency (MHz)	Antenna Polarity	Level (dBμV/m)	Limit (dBµV/m)	Margin (dB)	Result
30.108	V	20.3	40.0	19.7	Complied
33.834	V	14.1	40.0	25.9	Complied
41.160	V	14.3	40.0	25.7	Complied
68.516	V	8.9	40.0	31.1	Complied
331.207	V	31.6	46.0	14.4	Complied
388.792	V	29.6	46.0	16.4	Complied
446.393	V	34.9	46.0	11.1	Complied
475.209	V	30.7	46.0	15.3	Complied

Note(s):

- 1. The final measured value, for the given emission, in the table above incorporates the calibrated antenna factor and cable loss
- 2. The emission at 926.865 MHz shown on the 30 MHz to 1 GHz plot is the EUT fundamental.
- 3. The preliminary scans showed similar emission levels below 1 GHz, for each channel of operation. Therefore final radiated emissions measurements were performed with the EUT set to the top channel only.
- 4. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.
- 5. Measurements below 1 GHz were performed in a semi-anechoic chamber (RFI Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.

RFI Global Services Ltd Page 21 of 28

Transmitter Radiated Emissions (continued)



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

Page 22 of 28 RFI Global Services Ltd

5.2.7. Transmitter Radiated Emissions

Test Summary:

Test Engineer:	lan Watch	Test Date:	10 March 2011
Test Sample Serial No:	SN0008808		

FCC Part:	15.247(d) & 15.209(a)
Test Method Used:	As detailed in ANSI C63.10 Sections 6.3 and 6.6 referencing ANSI C63.4
Frequency Range	1 GHz to 9.3 GHz

Environmental Conditions:

Temperature (°C):	24
Relative Humidity (%):	21

Results: Peak Bottom Channel

Frequency	Antenna	Level	Limit	Margin	Result
(MHz)	Polarity	(dBμV/m)	(dBμV/m)	(dB)	
1809.290	Horizontal	61.9	81.6*	19.7	Complied

Results: Peak Middle Channel

Frequency (MHz)	Antenna Polarity	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Result
1830.870	Horizontal	63.5	80.5*	17.0	Complied

Results: Peak Top Channel


Frequency	Antenna	Level	Limit	Margin	Result
(MHz)	Polarity	(dBμV/m)	(dBμV/m)	(dB)	
1853.677	Horizontal	62.3	78.2*	15.9	Complied

Note(s):


- 1. *-20 dBc limit.
- 2. The final measured value, for the given emission, in the table above incorporates the calibrated antenna factor and cable loss.
- 3. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.
- 4. Pre-scans above 1 GHz were performed in a fully anechoic chamber (RFI Asset Number K0002) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 metres above the test chamber floor, in line with the EUT. Final measurements above 1 GHz were performed in a semi-anechoic chamber (RFI Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
- 5. All pre-scans were performed with a peak detector against average limits apart from measurements made in the range of 1 to 4GHz where pre-scans were performed with peak and average detectors and the applicable limit applied. This was due to the noise floor being close to the average limit when using a peak detector.


RFI Global Services Ltd Page 23 of 28

Transmitter Radiated Emissions (continued)











Average Detector



Page 24 of 28 RFI Global Services Ltd

Transmitter Radiated Emissions (continued)



8 GHz to 9.3 GHz

Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

RFI Global Services Ltd Page 25 of 28

5.2.8. Transmitter Band Edge Radiated Emissions

Test Summary:

Test Engineer:	Andrew Edwards	Test Date:	11 March 2011
Test Sample Serial No:	SN0008808		

FCC Part:	15.247(d)
Test Method Used:	As detailed in ANSI C63.10 Section 6.9.2

Environmental Conditions:


Temperature (°C):	24
Relative Humidity (%):	21


Results:


Frequency (MHz)	Peak Level (dBµV/m)	-20 dBc Limit (dBµV/m)	Margin (dB)	Result
902	63.0	81.5	18.5	Complied
928	64.8	78.3	13.5	Complied

Note(s):

1. The final measured value, for the given emission, in the table above incorporates the calibrated antenna factor and cable loss.







Upper Band Edge / Top Channel

Page 26 of 28 RFI Global Services Ltd

6. Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±3.25 dB
Radiated Maximum Peak Output Power	902 MHz to 928 MHz	95%	±2.94 dB
Spectral Power Density	902 MHz to 928 MHz	95%	±2.94 dB
6 dB Bandwidth	902 MHz to 928 MHz	95%	±0.92 ppm
20 dB Bandwidth	902 MHz to 928 MHz	95%	±0.92 ppm
Radiated Spurious Emissions	30 MHz to 10 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

RFI Global Services Ltd Page 27 of 28

Appendix 1. Test Equipment Used

RFI No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval Months
A1069	LISN	Rohde & Schwarz	ESH3-Z5	837469/012	13 Apr 2011	12
A1534	Pre Amplifier	Hewlett Packard	8449B	3008A00405	06 Jun 2011	12
A1818	Antenna	EMCO	3115	00075692	05 Sep 2011	12
A1936	Antenna	Schwarzbeck Mess - Elektronik	UBAA 9114	9114-223	25 Mar 2011	12
A1974	High Pass Filter	AtlanTecRF	AFH-01000	090000283	29 Dec 2011	12
A1996	Attenuator	Huber + Suhner	6810.17.B	301749	09 Feb 2012	12
A253	Antenna	Flann Microwave	12240-20	128	05 Sep 2011	12
A254	Antenna	Flann Microwave	14240-20	139	05 Sep 2011	12
A255	Antenna	Flann Microwave	16240-20	519	05 Sep 2011	12
A288	Antenna	Chase	CBL6111A	1589	05 Sep 2011	12
A553	Antenna	Chase	CBL6111A	1593	16 Mar 2011	12
G0543	Amplifier	Sonoma Instrument	310N	230801	30 Jun 2011	12
K0001	5m Semi-Anechoic Chamber	Rainford EMC	N/A	N/A	25 Apr 2011	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	05 Sep 2011	12
L1001	Test Receiver	Rohde & Schwarz	ESU26	100239	16 Mar 2011	12
M1124	Test Receiver	Rohde & Schwarz	ESI26	100046K	22 Apr 2011	12
M1263	Test Receiver	Rohde & Schwarz	ESIB7	100265	28 Jun 2011	12
M127	Spectrum Analyser	Rohde & Schwarz	FSEB 30	842 659/016	15 Sep 2011	12

NB In accordance with UKAS requirements all the measurement equipment is on a calibration schedule.

Page 28 of 28 RFI Global Services Ltd