

# FCC PART 15 B, CLASS B TEST REPORT

For

# AMGOO TELECOM (Shenzhen) CO.,LTD

3/F, Block R2-A(North), Gaoxin S. Ave. 4th, Hi-Tech Industrial Park, Nanshan District, Shenzhen, China

FCC ID: UOSAM241F

| Report Type: Original Report |  | Product Typ | oe:      |      |
|------------------------------|--|-------------|----------|------|
| Test Engineer:               | Jay Li   |             | Jay      | Lī   |
| Report Number:               | RSZ141201005   | -00A        |          |      |
| Report Date:                 | 2014-12-11   |             |          |      |
|                              | Jimmy Xiao   |             | Jimmy    | xiao |
| Reviewed By:                 | RF Engineer  |             | / ۱۳۳۰ - | **** |
| Prepared By:                 | Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn |             |          |      |

**Note**: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

# **TABLE OF CONTENTS**

| GENERAL INFORMATION                                | 3   |
|--|-----|
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3   |
| Objective  |     |
| RELATED SUBMITTAL(S)/GRANT(S)                      | 3   |
| TEST FACILITY                                      | 3   |
| SYSTEM TEST CONFIGURATION                          | 4   |
| DESCRIPTION OF TEST CONFIGURATION                  | 4   |
| EUT Exercise Software                              | 4   |
| SPECIAL ACCESSORIES.                               | 4   |
| EQUIPMENT MODIFICATIONS                            |     |
| SUPPORT EQUIPMENT LIST AND DETAILS                 |     |
| External I/O Cable                                 | 4   |
| EUT  |     |
| BLOCK DIAGRAM OF TEST SETUP                        | 5   |
| SUMMARY OF TEST RESULTS                            | 6   |
|  |     |
| FCC §15.107 – AC LINE CONDUCTED EMISSIONS          | 7   |
| APPLICABLE STANDARD                                | 7   |
| MEASUREMENT UNCERTAINTY                            | 7   |
| EUT Setup  |     |
| EMI TEST RECEIVER SETUP                            | 8   |
| TEST PROCEDURE                                     |     |
| TEST EQUIPMENT LIST AND DETAILS.                   |     |
| CORRECTED FACTOR & MARGIN CALCULATION              |     |
| TEST RESULTS SUMMARY                               |     |
| TEST DATA  | 9   |
| FCC §15.109 - RADIATED SPURIOUS EMISSIONS          | 12  |
| APPLICABLE STANDARD                                | 12  |
| MEASUREMENT UNCERTAINTY                            | 12  |
| EUT Setup  | 12  |
| EMI TEST RECEIVER SETUP                            | 13  |
| TEST PROCEDURE                                     |     |
| TEST EQUIPMENT LIST AND DETAILS.                   |     |
| CORRECTED AMPLITUDE & MARGIN CALCULATION           |     |
| TEST RESULTS SUMMARY                               | 14  |
| Test Data  | 1.4 |

#### **GENERAL INFORMATION**

#### **Product Description for Equipment under Test (EUT)**

The AMGOO TELECOM (Shenzhen) CO.,LTD's product, model number: AM241F (FCC ID:UOSAM241F) or the "EUT" in this report was a feature phone, which was measured approximately: 105.7 mm (L) x 52.5 mm (W) x 16.6 mm (H), rated with input voltage: DC 3.7 V rechargeable Li-ion battery, The highest operating frequency is 312 MHz.

Report No.: RSZ141201005-00A

Adapter Information:

Model: CH27

Input: AC100-240V, 50/60Hz, 0.2A

Output: DC 5.0V, 600mA

\*All measurement and test data in this report was gathered from production sample serial number: 1412009 (Assigned by Shenzhen BACL). The EUT supplied by the applicant was received on 2014-12-01.

#### **Objective**

This test report is prepared on behalf of *AMGOO TELECOM* (*Shenzhen*) *CO.,LTD* in accordance with Part 2-Subpart J, Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

#### **Related Submittal(s)/Grant(s)**

Part 15.247 DSS and Part 22H/24E PCE submissions with ID: UOSAM241F

#### **Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15 B, Class B Page 3 of 15

#### **SYSTEM TEST CONFIGURATION**

#### **Description of Test Configuration**

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode: Downloading (data transfer with computer)

#### **EUT Exercise Software**

No exercise software was used.

#### **Special Accessories**

No special accessory.

#### **Equipment Modifications**

No modification was made to the EUT tested.

#### **Support Equipment List and Details**

| Manufacturer | Description   | Model       | Serial Number            |
|--------------|---------------|-------------|--------------------------|
| DELL         | PC            | VOSTRO 220S | 127BP2X                  |
| DELL         | LCD Monitor   | E178WFPC    | CN-OWY564-64180-7C4-2SQH |
| DELL         | Keyboard      | L100        | CNORH656658907BL05DC     |
| DELL         | Mouse         | MOC5UO      | G1900NKD                 |
| SAST         | Modem         | AEM-2100    | 0293                     |
| PHILIPS      | Earphone      | SBCHP250    | N/A                      |
| Kingston     | Micro SD card | 4 GB        | N/A                      |

Report No.: RSZ141201005-00A


#### **External I/O Cable**

| Cable Description                 | Length (m) | From/Port | То       |
|-----------------------------------|------------|-----------|----------|
| Shielding Detachable K/B Cable    | 1.5        | Host PC   | Keyboard |
| Shielding Detachable Mouse Cable  | 1.5        | Host PC   | Mouse    |
| Shielding Detachable USB Cable    | 1.0        | Host PC   | EUT      |
| Shielding Detachable Serial Cable | 1.5        | Host PC   | Modem    |
| Shielding Detachable VGA Cable    | 1.5        | Host PC   | Monitor  |

FCC Part 15 B, Class B Page 4 of 15

### **Block Diagram of Test Setup**

For conducted emission



FCC Part 15 B, Class B Page 5 of 15

## **SUMMARY OF TEST RESULTS**

| FCC Rules | Description of Test         | Results    |
|-----------|-----------------------------|------------|
| §15.107   | AC Line Conducted Emissions | Compliance |
| §15.109   | Radiated Spurious Emissions | Compliance |

Report No.: RSZ141201005-00A

FCC Part 15 B, Class B Page 6 of 15

#### FCC §15.107 - AC LINE CONDUCTED EMISSIONS

#### **Applicable Standard**

According to FCC §15.107

#### **Measurement Uncertainty**


Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between AMN/ISN and receiver, AMN/ISN voltage division factor, AMN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Report No.: RSZ141201005-00A

| Port     | Measurement uncertainty                |
|----------|--|
| AC Mains | 3.26 dB (k=2, 95% level of confidence) |
| CAT 3    | 3.70 dB (k=2, 95% level of confidence) |
| CAT 5    | 3.86 dB (k=2, 95% level of confidence) |
| CAT 6    | 4.64 dB (k=2, 95% level of confidence) |

#### **EUT Setup**



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2009. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

The host PC was connected to a 120 VAC/60 Hz power source.

FCC Part 15 B, Class B Page 7 of 15

#### **EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |  |
|------------------|--------|--|
| 150 kHz – 30 MHz | 9 kHz  |  |

Report No.: RSZ141201005-00A

#### **Test Procedure**

During the conducted emission test, the host PC was connected to the first LISN and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

#### **Test Equipment List and Details**

| Manufacturer    | Description       | Model   | Serial Number              | Calibration<br>Date | Calibration<br>Due Date |
|-----------------|-------------------|---------|----------------------------|---------------------|-------------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCS30  | 100176                     | 2014-06-03          | 2015-06-03              |
| Rohde & Schwarz | LISN              | ENV216  | 3560.6650.12-<br>101613-Yb | 2014-06-09          | 2015-06-09              |
| Rohde & Schwarz | LISN              | ESH2-Z5 | 892107/021                 | 2014-06-09          | 2015-06-09              |
| Rohde & Schwarz | Transient Limitor | ESH3Z2  | DE25985                    | 2014-05-14          | 2015-05-14              |
| Rohde & Schwarz | CE Test software  | EMC 32  | V8.53                      |                     |                         |

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

#### **Corrected Factor & Margin Calculation**

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15 B, Class B
Page 8 of 15

#### **Test Results Summary**

According to the recorded data in following table, the EUT complied with the FCC Part 15.107, with the worst margin reading of:

#### 6.7 dB at 8.958250 MHz in the Line conducted mode

Report No.: RSZ141201005-00A

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

in BACL.,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

#### **Test Data**

#### **Environmental Conditions**

| Temperature:       | 24 ℃      |
|--------------------|-----------|
| Relative Humidity: | 50 %      |
| ATM Pressure:      | 101.0 kPa |

The testing was performed by Jay Li on 2014-12-04


FCC Part 15 B, Class B Page 9 of 15

EUT Operation Mode: Downloading

### AC 120V/60 Hz, Line

EMI Auto Test L

Report No.: RSZ141201005-00A




| Frequency<br>(MHz) | Corrected<br>Amplitude<br>(dBµV) | Correction<br>Factor<br>(dB) | Limit<br>(dBµV) | Margin<br>(dB) | Detector<br>(PK/Ave./QP) |
|--------------------|----------------------------------|------------------------------|-----------------|----------------|--------------------------|
| 8.958250           | 43.5                             | 19.6                         | 60.0            | 16.5           | QP                       |
| 8.958250           | 43.3                             | 19.6                         | 50.0            | 6.7            | Ave.                     |
| 9.255130           | 42.9                             | 19.7                         | 60.0            | 17.1           | QP                       |
| 9.255130           | 40.7                             | 19.7                         | 50.0            | 9.3            | Ave.                     |
| 15.402790          | 39.2                             | 19.8                         | 60.0            | 20.8           | QP                       |
| 15.402790          | 31.5                             | 19.8                         | 50.0            | 18.5           | Ave.                     |
| 16.557970          | 39.8                             | 19.9                         | 60.0            | 20.2           | QP                       |
| 16.557970          | 31.3                             | 19.9                         | 50.0            | 18.7           | Ave.                     |
| 16.893530          | 40.9                             | 19.9                         | 60.0            | 19.1           | QP                       |
| 16.893530          | 30.1                             | 19.9                         | 50.0            | 19.9           | Ave.                     |
| 17.616970          | 42.4                             | 19.9                         | 60.0            | 17.6           | QP                       |
| 17.616970          | 34.0                             | 19.9                         | 50.0            | 16.0           | Ave.                     |

FCC Part 15 B, Class B Page 10 of 15

#### AC 120V/60 Hz, Neutral

#### EMI Auto Test N

Report No.: RSZ141201005-00A



| Frequency<br>(MHz) | Corrected<br>Amplitude<br>(dBµV) | Correction<br>Factor<br>(dB) | Limit<br>(dBµV) | Margin<br>(dB) | Detector<br>(PK/Ave./QP) |
|--------------------|----------------------------------|------------------------------|-----------------|----------------|--------------------------|
| 8.857130           | 40.4                             | 19.6                         | 60.0            | 19.6           | QP                       |
| 8.857130           | 40.2                             | 19.6                         | 50.0            | 9.8            | Ave.                     |
| 9.361630           | 40.6                             | 19.6                         | 60.0            | 19.4           | QP                       |
| 9.361630           | 39.7                             | 19.6                         | 50.0            | 10.3           | Ave.                     |
| 13.956030          | 29.8                             | 19.6                         | 60.0            | 30.2           | QP                       |
| 13.956030          | 24.3                             | 19.6                         | 50.0            | 25.7           | Ave.                     |
| 15.675010          | 37.5                             | 19.6                         | 60.0            | 22.5           | QP                       |
| 15.675010          | 30.0                             | 19.6                         | 50.0            | 20.0           | Ave.                     |
| 16.774270          | 43.7                             | 19.6                         | 60.0            | 16.3           | QP                       |
| 16.774270          | 30.6                             | 19.6                         | 50.0            | 19.4           | Ave.                     |
| 17.548890          | 37.5                             | 19.6                         | 60.0            | 22.5           | QP                       |
| 17.548890          | 28.7                             | 19.6                         | 50.0            | 21.3           | Ave.                     |

#### Note:

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation The corrected factor has been input into the transducer of the test software.
- 2) Corrected Amplitude = Reading + Correction Factor
  3) Margin = Limit Corrected Amplitude

FCC Part 15 B, Class B Page 11 of 15

#### FCC §15.109 - RADIATED SPURIOUS EMISSIONS

#### **Applicable Standard**

FCC §15.109

#### **Measurement Uncertainty**


All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Report No.: RSZ141201005-00A

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown in below table. And the uncertainty will not be taken into consideration for the test data recorded in the report

| Frequency      | Polarity            | Measurement uncertainty                |
|----------------|---------------------|--|
| 30 MHz~200 MHz | Horizontal          | 4.62 dB (k=2, 95% level of confidence) |
| 30 MHZ~200 MHZ | Vertical            | 4.54 dB (k=2, 95% level of confidence) |
| 200 MHz∼1 GHz  | Horizontal          | 4.84 dB (k=2, 95% level of confidence) |
| 200 MHZ~1 GHZ  | Vertical            | 5.91 dB (k=2, 95% level of confidence) |
| 1 GHz~6 GHz    | Horizontal/Vertical | 4.68 dB (k=2, 95% level of confidence) |
| Above 6 GHz    | Horizontal/Vertical | 4.92 dB (k=2, 95% level of confidence) |

#### **EUT Setup**



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part 15.109 Class B limits.

FCC Part 15 B, Class B Page 12 of 15

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Report No.: RSZ141201005-00A

The spacing between the peripherals was 10 cm.

The host PC was connected to a 120 VAC/60 Hz power source.

#### **EMI Test Receiver Setup**

The system was investigated from 30 MHz to 2 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

| Frequency Range   | RBW                    | Video B/W | IF B/W  | Detector |  |
|-------------------|------------------------|-----------|---------|----------|--|
| 30 MHz – 1000 MHz | MHz – 1000 MHz 100 kHz |           | 120 kHz | QP       |  |
| Above 1 GHz       | 1MHz                   | 3 MHz     | /       | PK       |  |
|                   | 1MHz                   | 10 Hz     | /       | Ave.     |  |

#### **Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

#### **Test Equipment List and Details**

| Manufacturer    | Description        | Model       | Serial Number | Calibration<br>Date | Calibration<br>Due Date |  |
|-----------------|--------------------|-------------|---------------|---------------------|-------------------------|--|
| HP              | Amplifier          | 8447E       | 1937A01046    | 2014-05-06          | 2015-05-06              |  |
| Rohde & Schwarz | EMI Test Receiver  | ESCI        | 101120        | 2014-11-03          | 2015-11-03              |  |
| Sunol Sciences  | Broadband Antenna  | ЈВ3         | A111513       | 2014-06-18          | 2017-06-17              |  |
| A.H. System     | Horn Antenna       | SAS-200/571 | 135           | 2012-02-11          | 2015-02-10              |  |
| Rohde & Schwarz | Signal Analyzer    | FSIQ26      | 837405/023    | 2014-08-22          | 2015-08-22              |  |
| Mini            | Pre-amplifier      | ZVA-183-S+  | 5969001149    | 2014-04-23          | 2015-04-23              |  |
| TDK             | Chamber            | Chamber A   | 2#            | 2012-10-15          | 2015-10-15              |  |
| TDK             | Chamber            | Chamber B   | 1#            | 2012-07-23          | 2015-07-22              |  |
| R&S             | Auto test Software | EMC32       | V9.10         | -                   | -                       |  |

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC Part 15 B, Class B Page 13 of 15

#### **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Report No.: RSZ141201005-00A

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

#### **Test Results Summary**

According to the data in the following table, the EUT complied with the FCC §15.109 Class B, with the worst margin reading of:

#### 9.52 dB at 407.92 MHz in the Horizontal polarization mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

#### **Test Data**

#### **Environmental Conditions**

| Temperature:       | 23 ℃      |  |  |
|--------------------|-----------|--|--|
| Relative Humidity: | 50 %      |  |  |
| ATM Pressure:      | 101.0 kPa |  |  |

The testing was performed by Jay Li on 2014-12-03

FCC Part 15 B, Class B Page 14 of 15

| Frequency (MHz) | Receiver       |                          |                     | Rx Antenna |                | Corrected     | Corrected          | FCC Part 15B      |                |
|-----------------|----------------|--------------------------|---------------------|------------|----------------|---------------|--------------------|-------------------|----------------|
|                 | Reading (dBµV) | Detector<br>(PK/QP/Ave.) | Turntable<br>Degree | Height (m) | Polar<br>(H/V) | Factor (dB/m) | Amplitude (dBµV/m) | Limit<br>(dBµV/m) | Margin<br>(dB) |
| 167.81          | 39.58          | QP                       | 54                  | 1.9        | Н              | -14.4         | 25.18              | 43.5              | 18.32          |
| 311.97          | 46.35          | QP                       | 32                  | 1.3        | Н              | -12.1         | 34.25              | 46                | 11.75          |
| 323.93          | 43.84          | QP                       | 174                 | 1.1        | Н              | -12.0         | 31.84              | 46                | 14.16          |
| 407.92          | 46.48          | QP                       | 137                 | 1.1        | Н              | -10.0         | 36.48              | 46                | 9.52           |
| 473.84          | 35.96          | QP                       | 343                 | 2.6        | V              | -8.8          | 27.16              | 46                | 18.84          |
| 473.93          | 39.72          | QP                       | 339                 | 2.7        | V              | -8.8          | 30.92              | 46                | 15.08          |
| 1049.33         | 48.46          | PK                       | 1                   | 2.2        | V              | 0.13          | 48.59              | 74                | 25.41          |
| 1049.33         | 29.44          | Ave.                     | 1                   | 2.2        | V              | 0.13          | 29.57              | 54                | 24.43          |
| 1524.48         | 46.58          | PK                       | 77                  | 1.8        | Н              | 2.24          | 48.82              | 74                | 25.18          |
| 1524.48         | 26.60          | Ave.                     | 77                  | 1.8        | Н              | 2.32          | 28.92              | 54                | 25.08          |

Report No.: RSZ141201005-00A

- Correction Factor=Antenna factor (RX) + cable loss amplifier factor
   Corrected Amplitude = Correction Factor + Reading
- 3) Margin = Limit Corrected Amplitude

\*\*\*\*\* END OF REPORT \*\*\*\*\*

FCC Part 15 B, Class B Page 15 of 15