



FCC PART 15B, CLASS B TEST REPORT

For

Amgoo Telecom Co., Ltd.

3/F, Block R2-A (North), Gaoxin S.Ave.4th, Hi-Tech Industrial Park, Nanshan District, Shenzhen, China

FCC ID: UOSAM535

Report Type: Product Type:

Original Report Smartphone

Report Number: RSZ170713001-00A

Report Date: 2017-07-31

Rocky Kang

Reviewed By: RF Engineer

Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone,

Rocky Kang

Shenzhen, Guangdong, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★". This report may contain data were produced under the subcontractor and shall be marked with an asterisk "△".

TABLE OF CONTENTS

PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	3
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
Measurement Uncertainty	
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT Exercise Software	5
SPECIAL ACCESSORIES	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	
External I/O Cable.	
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
THE THOUGH TO A VINDA WINDOW A VOTE	0
TEST EQUIPMENT LIST	8
TEST EQUIPMENT LISTFCC §15.107 – AC LINE CONDUCTED EMISSIONS	
	9
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	9
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	9 9
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE	9 9 9 9
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION	
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY	
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION	
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY	99 99 10 10 10
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA	
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS	99 99 10 10 13 13
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS APPLICABLE STANDARD	99 99 10 10 10 13 13 13
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE	99 99 99 10 10 10 13 13 13 14 14
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED AMPLITUDE & MARGIN CALCULATION	99 99 99 10 10 10 13 13 13 14 14 14
FCC §15.107 – AC LINE CONDUCTED EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE CORRECTED FACTOR & MARGIN CALCULATION TEST RESULTS SUMMARY TEST DATA FCC §15.109 - RADIATED SPURIOUS EMISSIONS APPLICABLE STANDARD EUT SETUP EMI TEST RECEIVER SETUP TEST PROCEDURE	99 99 99 10 10 10 13 13 13 14 14 14

Report No.: RSZ170713001-00A

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Amgoo Telecom Co., Ltd.'s product, model number: AM535 (FCC ID: UOSAM535) or the "EUT" in this report was a Smartphone, which was measured approximately: $14.3 \text{ cm } (L) \times 7.1 \text{ cm } (W) \times 0.8 \text{ cm } (H)$, rated with input voltage: DC 3.8 V battery or DC 5V from adapter. The highest operating frequency is 2690 MHz.

Report No.: RSZ170713001-00A

Adapter Information:

Model: CH5

Input: AC 100-240V, 50/60Hz, 0.2A

Output: DC 5V, 1000 mA

*All measurement and test data in this report was gathered from production sample serial number: 1701663 (Assigned by applicant). The EUT supplied by the applicant was received on 2017-07-13.

Objective

This test report is prepared on behalf of *Amgoo Telecom Co.*, *Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS, Part 15.247 DTS and Part 22H/24E/27 PCE submissions with FCC ID: UOSAM535.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	uncertainty
Conducted Emissions	±1.95dB
All emissions, radiated	±4.88dB

FCC Part 15B, Class B Page 3 of 15

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Report No.: RSZ170713001-00A

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP(Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 15B, Class B Page 4 of 15

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode: Downloading (data transfer with computer)

EUT Exercise Software

"BurnIn test v5.3" exercise software was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	PC	VOSTRO 220S	127BP2X
DELL	LCD Monitor	E178WFPC	CN-OWY564-64180-7C4-2SQH
DELL	Keyboard	L100	CNORH656658907BL05DC
DELL	Mouse	MOC5UO	G1900NKD
SAST	Modem	AEM-2100	0293
Kingston	Micro SD card	1 GB	N/A

Report No.: RSZ170713001-00A

FCC Part 15B, Class B Page 5 of 15


External I/O Cable

Cable Description	Length (m)	From/Port	То
Un-Shielding Detachable USB Cable	1.5	Host PC	Mouse
Un-Shielding Detachable Serial Cable	1.5	Host PC	Modem
Un-Shielding Detachable K/B Cable	1.5	Host PC	Keyboard
Un-Shielding Detachable VGA Cable	1.5	Host PC	LCD Monitor
Shielding Detachable USB Cable With Magnet Ring	1.0	EUT	Host PC
Un-shielding Un-detachable DC Cable	1.0	Modem	Modem Adapter

Report No.: RSZ170713001-00A

Block Diagram of Test Setup

For conducted emission:



FCC Part 15B, Class B Page 6 of 15

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Results	
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Spurious Emissions	Compliance

Report No.: RSZ170713001-00A

FCC Part 15B, Class B Page 7 of 15

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
	AC Lii	ne Conducted En	nission Test		
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2016-10-19	2017-10-19
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2016-12-07	2017-12-07
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-02-14	2017-08-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1- 0720-504504	2017-05-12	2017-11-12
	R	Radiated Emission	n Test		
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28
Rohde & Schwarz	Signal Generator	FSIQ26	8386001028	2017-04-24	2018-04-24
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-17	2017-12-16
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-02-14	2018-02-14
НР	Amplifier	HP8447E	1937A01046	2017-05-21	2017-11-19
Anritsu	Signal Generator	68369B	004114	2016-12-05	2017-12-05
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07
A.H. System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Ducommun technologies	RF Cable	UFA210A-1- 4724-30050U	MFR64369 223410-001	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	1	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	2	2017-05-22	2017-11-22

Report No.: RSZ170713001-00A

FCC Part 15B, Class B Page 8 of 15


^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.107 – AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC §15.107

EUT Setup



Report No.: RSZ170713001-00A

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the host PC was connected to the first LISN and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

FCC Part 15B, Class B Page 9 of 15

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Report No.: RSZ170713001-00A

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	26 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-07-28.


FCC Part 15B, Class B Page 10 of 15

EUT Operation Mode: Downloading

AC 120V/60 Hz, Line

EMI Auto Test L

Report No.: RSZ170713001-00A




Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
8.849190	46.2	20.0	60.0	13.8	QP
8.851690	46.3	20.0	60.0	13.7	QP
9.251190	46.0	20.0	60.0	14.0	QP
9.353690	46.1	20.0	60.0	13.9	QP
22.026550	47.9	20.1	60.0	12.1	QP
22.323050	47.6	20.1	60.0	12.4	QP
8.849190	45.3	20.0	50.0	4.7	Ave.
8.851690	45.5	20.0	50.0	4.5	Ave.
9.251190	44.7	20.0	50.0	5.3	Ave.
9.353690	45.2	20.0	50.0	4.8	Ave.
22.026550	44.5	20.1	50.0	5.5	Ave.
22.323050	44.0	20.1	50.0	6.0	Ave.

FCC Part 15B, Class B Page 11 of 15

AC 120V/60 Hz, Neutral

EMI Auto Test N

Report No.: RSZ170713001-00A



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
1.105410	37.9	20.1	56.0	18.1	QP
8.849250	44.0	20.0	60.0	16.0	QP
9.249690	43.8	20.0	60.0	16.2	QP
22.022670	49.9	20.1	60.0	10.1	QP
22.523670	47.6	20.1	60.0	12.4	QP
24.127430	44.7	20.0	60.0	15.3	QP
1.105410	37.2	20.1	46.0	8.8	Ave.
8.849250	42.3	20.0	50.0	7.7	Ave.
9.249690	42.2	20.0	50.0	7.8	Ave.
22.022670	45.0	20.1	50.0	5.0	Ave.
22.523670	46.4	20.1	50.0	3.6	Ave.
24.127430	39.6	20.0	50.0	10.4	Ave.

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
 3) Margin = Limit Corrected Amplitude

FCC Part 15B, Class B Page 12 of 15


FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §15.109


EUT Setup

Below 1GHz:



Report No.: RSZ170713001-00A

Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

FCC Part 15B, Class B Page 13 of 15

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Report No.: RSZ170713001-00A

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 13.45 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above I GHZ	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{\rm (Lm)} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

FCC Part 15B, Class B Page 14 of 15

Test Data

Environmental Conditions

Temperature:	26 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-07-28.

EUT Operation Mode: Downloading

30MHz - 13.45 GHz:

Frequency (MHz)	Receiver		Turntable	Rx Antenna			Corrected	FCC Part 15B	
	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height	Polar (H / V)	Factor (dB/m)	Amplitude (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.24	30.37	QP	332.0	1.1	V	0.1	30.47	40.00	9.53
36.77	35.22	QP	245.0	1.1	V	-4.1	31.12	40.00	8.88
48.01	45.08	QP	239.0	1.2	V	-10.5	34.58	40.00	5.42
55.51	47.03	QP	258.0	1.1	V	-11.5	35.53	40.00	4.47
63.16	43.61	QP	69.0	1.1	V	-11.9	31.71	40.00	8.29
114.55	40.34	QP	341.0	1.1	V	-6.9	33.44	43.50	10.06
1156.11	50.76	PK	223	1.4	Н	-8.48	42.28	74	31.72
1156.11	30.12	Ave.	223	1.4	Н	-8.48	21.64	54	32.36
1158.43	47.36	PK	153	1.3	V	-8.48	38.88	74	35.12
1158.43	29.84	Ave.	153	1.3	V	-8.48	21.36	54	32.64
1717.87	46.23	PK	205	2.4	Н	-5.23	41.00	74	33.00
1717.87	29.48	Ave.	205	2.4	Н	-5.23	24.25	54	29.75
1719.49	48.07	PK	61	2.4	V	-5.23	42.84	74	31.16
1719.49	29.90	Ave.	61	2.4	V	-5.23	24.67	54	29.33

Report No.: RSZ170713001-00A

Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss amplifier factor
- 2) Corrected Amplitude = Correction Factor + Reading
- 3) Margin = Limit Corrected Amplitude

***** END OF REPORT *****

FCC Part 15B, Class B Page 15 of 15