FCC Part 15D - APPLICATION FORM & SELF-DECLARATION

Applicant Name:	Agetra Doutschland CmbH		
Applicant Name: Address:	Aastra Deutschland GmbH Zeughofstr 1		
Contact person:	Gerhard Hofmann		
Phone No.:	"+49 30 6104 5329"	Fax No.:	"+49 30 6104 5157"
Manufacturer Name:	Aastra Deutschland GmbH		
Address:	Zeughofstr 1, 10997 Berlin		
	Ph Fh		
	PP		FP
Model Name:	622d		
FCC ID:	UOU80E00009622		
IC for Canada:	1884E-80E00009622		
Hardware:	63-001543-82		
Software:	1.01		
		•	
			Remarks
Does a system build with the EUT that implement the		✓ Yes	
provisions of 47CFR 15.323(c)(5) enabling the use of the upper			
threshold for deferral?		☐ No	
According to 47CFR 15.323(c)(5).4, does your model not use		√ Yes	
bandwidth in further cooperation with other devices at any		□ No	
range?			
Does a system build using the EUT that operate under the		Yes	
provision of 47CFR 15.323(c)(6) incorporating provisions for		✓ No	
waiting for a channel to go clear?			1
According to 47CFR 15.323(c)(8), does the EUT use the same antennas for transmission and reception as for monitoring?		✓ Yes	
		□ No	
Does the system built with the EUT that operate under the		Yes	
provision of 47CFR 15.323(c)(10) to test for deferral only in		☑ No	
conjunction with a companion device?			
Does a system built using the EUT that operate under the		Yes	
provision of 47CFR 15.323(c)(11) enabling the access criteria		✓ No	
check on the receive channel while in the presence of		□ NO	
collocated interference?			
According to 47CFR 15.323(c)(12), does EUT not work in a		✓ Yes	
mode with denies fair access to spectrum for other devices.		□ No	
Please provide also the following declaration and descriptions			
The channel plan			
Maximum EUT antenna gain G _A (dBi), and orientation and polarization for maximum gain			
Maximum peak power level			
Emission bandwidth			
Nominal receive bandwidth			
Frame period and time slot plan, if time-division multiple-access (TDMA) techniques are used			
Minimum and maximum burst length, if TDMA techniques are used Minimum and maximum energing temperature ranges dealered to the end uses			
Minimum and maximum operating temperature ranges declared to the end user The nominal value of the deferral threshold			
The provision within the EUT for self-check, by which compliance with 47CFR15.319(f) is obtained			
Whether the EUT does or does not transmit control and signalling channel(s)			
Nominal mains and battery voltage			
The manufacturer shall describe the channel monitoring and selection process used by the EUT, including details			
regarding the time between monitoring and transmission on the confirmed channel. Appropriate timing diagrams shall			
be included as necessary.			
,	⊃ / ,	1ai	/, > /
Signed by:	De(V.O. Signature:	(COV)	Le Belle.
Date:	July 104 2012		