

**FCC 47 CFR PART 15 SUBPART C AND ANSI C63.10:2013
TEST REPORT****For****Airoha Bluetooth 4.2 Data Module****Model: AB1122****Trade Name: Airoha****Issued for****Airoha Technology Corp.****5F.,No.6-5,Dusing Road , Hsinchu Science Park , Hsinchu 300,Taiwan****Issued by****Compliance Certification Services Inc.****Hsinchu Lab.****No.989-1, Wenshan Rd., Shangshan Village,
Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)****TEL: +886-3-5921698****FAX: +886-3-5921108****<http://www.ccsrf.com>****E-Mail: service@ccsrf.com****Issued Date: February 23, 2016**

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	02/23/2016	Initial Issue	All Page 47	Tiffany Liu

TABLE OF CONTENTS

TITLE	PAGE NO.
1. TEST REPORT CERTIFICATION.....	4
2. EUT DESCRIPTION.....	5
3. DESCRIPTION OF TEST MODES.....	6
4. TEST METHODOLOGY	7
5. FACILITIES AND ACCREDITATION.....	7
5.1 FACILITIES.....	7
5.2 ACCREDITATIONS	7
5.3 MEASUREMENT UNCERTAINTY.....	8
6. SETUP OF EQUIPMENT UNDER TEST	9
7. FCC PART 15.247 REQUIREMENTS.....	10
7.1 6dB BANDWIDTH.....	10
7.2 MAXIMUM PEAK OUTPUT POWER.....	14
7.3 AVERAGE POWER	16
7.4 POWER SPECTRAL DENSITY	18
7.5 CONDUCTED SPURIOUS EMISSION.....	22
7.6 RADIATED EMISSION	26
7.7 CONDUCTED EMISSION.....	39
8. APPENDIX SETUP PHOTOS	44

1. TEST REPORT CERTIFICATION

Applicant : Airoha Technology Corp.
Address : 5F.,No.6-5,Dusing Road , Hsinchu Science Park , Hsinchu 300,Taiwan
Equipment Under Test : Airoha Bluetooth 4.2 Data Module
Model : AB1122
Trade Name : Airoha
Tested Date : January 20 ~ February 19, 2016

APPLICABLE STANDARD	
Standard	Test Result
FCC Part 15 Subpart C AND ANSI C63.10:2013	PASS

WE HEREBY CERTIFY THAT: The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Sb. Lu
Sr. Engineer

Reviewed by:



Gundam Lin
Sr. Engineer

2. EUT DESCRIPTION

Product Name	Airoha Bluetooth 4.2 Data Module
Model Number	AB1122
Identify Number	T160120S02
Received Date	January 20, 2016
Frequency Range	2402MHz ~ 2480MHz
Transmit Power	5.21 dBm (0.0033W)
Channel Spacing	2MHz
Channel Number	40 Channels
Transmit Data Rate	1Mbps
Type of Modulation	GFSK
Antenna Type	PCB Antenna, Antenna Gain: 0 dBi
Power Rating	3.3Vdc
Test Voltage	120Vac, 60Hz

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. For more details, please refer to the User's manual of the EUT.
3. This submittal(s) (test report) is intended for FCC ID: UOW-AB1122 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.

3. DESCRIPTION OF TEST MODES

Conducted Emission / Radiated Emission Test (Below 1 GHz)

1. The following test modes were scanned during the preliminary test:

No.	Pre-Test mode
1	TX Mode

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Final Test mode		
Emission	Radiated Emission	Mode 1
	Conducted Emission	Mode 1

Remark: Then, the above highest emission mode of the configuration of the EUT and cable was chosen for all final test items.

Conducted / Radiated Emission Test (Above 1 GHz)

The EUT had been tested under operating condition.

Following channel(s) was (were) selected for the final test as listed below.

Channel	Frequency (MHz)
Low	2402
Middle	2440
High	2480

Remark: The field strength of spurious emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X, Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.

4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10:2013 and FCC CFR 47, 15.207, 15.209 and 15.247.

5. FACILITIES AND ACCREDITATION

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at No.989-1, Wenshan Rd., Shangshan Village, Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.10:2013 and CISPR 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4 and CISPR 16-1-5.

5.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

Taiwan TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	INDUSTRY CANADA
Japan	VCCI
Taiwan	BSMI
USA	FCC MRA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

Remark: FCC Designation Number TW1027.

5.3 MEASUREMENT UNCERTAINTY

The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4-2.

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_C) / Radiated Emission, 30 to 1000 MHz	+/- 3.97
Semi Anechoic Chamber (966 Chamber_C) / Radiated Emission, 1 to 18GHz	+/- 3.58
Semi Anechoic Chamber (966 Chamber_C) / Radiated Emission, 18 to 26 GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_C) / Radiated Emission, 26 to 40 GHz	+/- 3.81
Conducted Emission (Mains Terminals), 9kHz to 30MHz	+/- 2.48

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than U_{CISPR} which is 3.6dB and 5.2dB respectively. CCS values (called U_{Lab} in CISPR 16-4-2) is less than U_{CISPR} as shown in the table above. Therefore, MU need not be considered for compliance.

6. SETUP OF EQUIPMENT UNDER TEST

SUPPORT EQUIPMENT

No.	Product	Manufacturer	Model No.	Serial No.
1	Notebook PC	Acer	ZR1	LXAXP0J006652088082500
2	Mouse	Lenovo	MO28UOL	44G8596
3	Headset	i-Acon	CW-010M.V	---
4	Test Fixture	---	B861 & B864	---

No.	Signal Cable Description
1	Shielded USB cable, 1m × 2

No.	Product	Manufacturer	Model No.	Power Input	Power Output
1	Power Adapter	Hua shun da electric	GM-1018-S05	100-240Vac, 50/60Hz, 0.5A	+5Vdc, 3.0A

SETUP DIAGRAM FOR TESTS

EUT & peripherals setup diagram is shown in appendix setup photos.

EUT OPERATING CONDITION

1. EUT & peripherals setup diagram is shown in appendix setup photos.
2. TX mode:
 - ⇒ **Power control:**
 - Channel Low (2402MHz) Power set 46.
 - Channel Mid (2440MHz) Power set 46.
 - Channel High (2480MHz) Power set 46.
3. All of the functions are under run.
4. Start test

7. FCC PART 15.247 REQUIREMENTS

7.1 6dB BANDWIDTH

LIMITS

§ 15.247(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP





TEST PROCEDURE

1. The transmitter output was connected to a spectrum analyzer.
2. Set RBW = 100 kHz.
3. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


TEST RESULTS

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Davis Tseng
Test Model	AB1122	Test Date	2016/01/29
Test mode	TX Mode	Temp. & Humidity	22°C, 67%

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Result
Low	2402	0.65	500	PASS
Middle	2440	0.66	500	PASS
High	2480	0.66	500	PASS

6dB BANDWIDTH**CH Low****CH Middle**

CH High



7.2 MAXIMUM PEAK OUTPUT POWER

LIMITS

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following:

§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 watt.

§ 15.247(b) (4) Except as shown in paragraphs (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§ KDB 662911: For power measurements on IEEE 802.11 devices

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/08/2016
Power Sensor	Anritsu	MA2411B	1126148	12/08/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the power meter. The power meter is set to the peak power detection.

TEST RESULTS

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Davis Tseng
Test Model	AB1122	Test Date	2016/01/29
Test mode	TX Mode	Temp. & Humidity	22°C, 67%

Channel	Channel Frequency (MHz)	Maximum Peak Output Power				Result	
		Measured Value		Limit			
		(dBm)	(W)	(dBm)	(W)		
Low	2402	4.61	0.0029	30	1	PASS	
Middle	2440	5.07	0.0032	30	1	PASS	
High	2480	5.21	0.0033	30	1	PASS	

Remark: The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

7.3 AVERAGE POWER

LIMITS


None: For reporting purposes only.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/08/2016
Power Sensor	Anritsu	MA2411B	1126148	12/08/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the power meter. The power meter is set to the average power detection.

TEST RESULTS

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Davis Tseng
Test Model	AB1122	Test Date	2016/01/29
Test mode	TX Mode	Temp. & Humidity	22°C, 67%

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	4.32
Middle	2440	4.84
High	2480	4.99

Remark: The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

7.4 POWER SPECTRAL DENSITY

LIMITS

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set analyzer center frequency to DTS channel center frequency.
3. Set the span to 1.5 times the DTS channel bandwidth.
4. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
5. Set the VBW $\geq 3 \times \text{RBW}$.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum amplitude level within the RBW.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST RESULTS

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Davis Tseng
Test Model	AB1122	Test Date	2016/01/29
Test mode	TX Mode	Temp. & Humidity	22°C, 67%

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)		Result
		Measured Value	Limit	
Low	2402	-3.12	8	PASS
Middle	2440	-2.56	8	PASS
High	2480	-2.59	8	PASS

Remark: The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the spectrum analyzer to allow for direct reading of power.

POWER SPECTRAL DENSITY**CH Low****CH Middle**

CH High



7.5 CONDUCTED SPURIOUS EMISSION

LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the and that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

TEST RESULTS


Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Davis Tseng
Test Model	AB1122	Test Date	2016/01/29
Test mode	TX Mode	Temp. & Humidity	22°C, 67%

OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT


CH Low (2.38GHz ~ 2.5GHz)




CH Low (30MHz ~ 26.5GHz)




CH Middle (2.38GHz ~ 2.5GHz)




CH Middle (30MHz ~ 26.5GHz)



CH High (2.38GHz ~ 2.5GHz)



CH High (30MHz ~ 26.5GHz)



7.6 RADIATED EMISSION

LIMITS

(1) According to § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

Remark:

1. ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
2. ² Above 38.6

(2) According to § 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

(3) According to § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

Remark: **Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(4) According to § 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST EQUIPMENT

Radiated Emission / 966Chamber_C


Name of Equipment	Manufacture	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY45280064	03/26/2016
EMI Test Receiver	Rohde & Schwarz	ESCI	101387	10/06/2016
Bi-log Antenna	TESEQ	CBL 6112D	35404	08/04/2016
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-778	08/09/2016
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00078732	07/14/2016
Horn Antenna	COM-POWER	AH-840	03077	12/09/2015
Pre-Amplifier	EMCI	EMC001625	980243	04/12/2016
Pre-Amplifier	COM-POWER	PAM-118A	551043	04/12/2016
LOOP Antenna	COM-POWER	AL-130	121060	05/25/2015

Remark: Each piece of equipment is scheduled for calibration once a year.


TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission below 1GHz.


9kHz ~ 30MHz



30MHz ~ 1GHz



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



TEST PROCEDURE

1. The EUT was placed on the top of a rotating table 0.8 and 1.5 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
2. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Remark:

1. *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.*
2. *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.*
3. *The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.*

TEST RESULTS**Below 1 GHz (9kHz ~ 30MHz)**

No emission found between lowest internal used/generated frequency to 30MHz.

Below 1 GHz (30MHz ~ 1GHz)

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Crystal Wu
Test Model	AB1122	Test Date	2016/02/17
Test mode	Mode 1	Temp. & Humidity	20°C, 53%

966Chamber_C at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
199.75	51.19	-20.44	30.75	43.50	-12.75	82	200	Peak
344.28	46.55	-14.98	31.57	46.00	-14.43	113	200	Peak
499.48	45.55	-11.92	33.63	46.00	-12.37	93	100	Peak
568.35	45.61	-10.81	34.80	46.00	-11.20	269	100	Peak
582.90	44.89	-10.67	34.22	46.00	-11.78	97	100	Peak
750.71	44.42	-8.96	35.46	46.00	-10.54	117	100	Peak
828.31	42.49	-8.28	34.21	46.00	-11.79	133	100	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
59.10	56.91	-24.47	32.44	40.00	-7.56	274	100	Peak
99.84	53.96	-20.12	33.84	43.50	-9.66	88	100	Peak
159.98	57.19	-20.18	37.01	43.50	-6.49	131	100	Peak
333.61	51.64	-15.30	36.34	46.00	-9.66	286	200	Peak
499.48	43.99	-11.92	32.07	46.00	-13.93	317	100	Peak
565.44	45.86	-10.84	35.02	46.00	-10.98	258	100	Peak
977.69	41.24	-6.94	34.30	54.00	-19.70	89	100	Peak

Remark:

1. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit.
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – PreAmp.Gain (dB)
3. Result (dBuV/m) = Reading (dBuV) + Correction Factor (dB/m)
4. Margin (dB) = Remark result (dBuV/m) - Quasi-peak limit (dBuV/m).

Above 1 GHz

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Crystal Wu
Test Model	AB1122	Test Date	2016/02/16
Test mode	TX / CH Low	Temp. & Humidity	20°C, 53%

966Chamber_C at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
1108.00	45.26	-1.05	44.21	74.00	-29.79	45	100	Peak
1662.00	44.41	0.31	44.72	74.00	-29.28	145	100	Peak
2004.00	45.43	3.46	48.89	74.00	-25.11	125	100	Peak
2483.50	36.44	4.48	40.92	74.00	-33.08	342	100	Peak
4800.00	45.22	-0.33	44.89	54.00	-9.11	151	100	Average
4800.00	55.53	-0.33	55.20	74.00	-18.80	151	100	Peak
7200.00	37.76	2.68	40.44	54.00	-13.56	193	200	Average
7200.00	49.90	2.68	52.58	74.00	-21.42	193	200	Peak
12015.00	35.07	8.13	43.20	54.00	-10.80	168	100	Average
12015.00	49.18	8.13	57.31	74.00	-16.69	168	100	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
1000.00	47.59	-1.01	46.58	74.00	-27.42	99	100	Peak
1590.00	42.75	-0.35	42.40	74.00	-31.60	128	100	Peak
1670.00	43.20	0.39	43.59	74.00	-30.41	139	100	Peak
2002.00	47.52	3.45	50.97	74.00	-23.03	105	100	Peak
2483.50	35.53	4.48	40.01	74.00	-33.99	277	100	Peak
3135.00	50.99	-3.49	47.50	74.00	-26.50	355	100	Peak
4800.00	48.99	-0.33	48.66	74.00	-25.34	149	200	Peak
7200.00	46.77	2.68	49.45	74.00	-24.55	170	100	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Crystal Wu
Test Model	AB1122	Test Date	2016/02/16
Test mode	TX / CH Middle	Temp. & Humidity	20°C, 53%

966Chamber_C at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
1664.00	41.48	0.33	41.81	74.00	-32.19	60	100	Peak
2004.00	44.42	3.46	47.88	74.00	-26.12	267	200	Peak
2390.00	36.71	4.28	40.99	74.00	-33.01	116	200	Peak
2483.50	35.26	4.48	39.74	74.00	-34.26	164	100	Peak
4875.00	51.35	-0.06	51.29	74.00	-22.71	191	200	Peak
7320.00	36.55	2.74	39.29	54.00	-14.71	204	200	Average
7320.00	50.81	2.74	53.55	74.00	-20.45	204	200	Peak
10155.00	43.36	5.22	48.58	74.00	-25.42	357	100	Peak

966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
1002.00	48.24	-1.01	47.23	74.00	-26.77	107	200	Peak
1642.00	46.36	0.13	46.49	74.00	-27.51	269	200	Peak
2000.00	46.66	3.45	50.11	74.00	-23.89	107	100	Peak
2390.00	38.04	4.28	42.32	74.00	-31.68	129	100	Peak
2483.50	35.64	4.48	40.12	74.00	-33.88	5	200	Peak
4875.00	50.11	-0.06	50.05	74.00	-23.95	163	200	Peak
7080.00	43.28	2.63	45.91	74.00	-28.09	246	200	Peak
8520.00	43.98	3.70	47.68	74.00	-26.32	346	200	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Crystal Wu
Test Model	AB1122	Test Date	2016/02/16
Test mode	TX / CH High	Temp. & Humidity	20°C, 53%

966Chamber_C at 3Meter / Horizontal



Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
1000.00	43.90	-1.01	42.89	74.00	-31.11	73	200	Peak
1598.00	41.56	-0.28	41.28	74.00	-32.72	50	100	Peak
1998.00	42.33	3.43	45.76	74.00	-28.24	124	100	Peak
2390.00	36.29	4.28	40.57	74.00	-33.43	302	200	Peak
4965.00	51.94	0.26	52.20	74.00	-21.80	111	200	Peak
7440.00	47.66	2.79	50.45	74.00	-23.55	212	200	Peak
9930.00	43.63	4.81	48.44	74.00	-25.56	180	100	Peak



966Chamber_C at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
1002.00	53.00	-1.01	51.99	74.00	-22.01	114	100	Peak
1668.00	42.87	0.37	43.24	74.00	-30.76	159	200	Peak
2004.00	44.14	3.46	47.60	74.00	-26.40	175	100	Peak
2390.00	36.61	4.28	40.89	74.00	-33.11	309	100	Peak
4965.00	50.44	0.26	50.70	74.00	-23.30	154	200	Peak
7095.00	44.55	2.63	47.18	74.00	-26.82	220	100	Peak
9090.00	43.79	4.19	47.98	74.00	-26.02	260	200	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)


Restricted Band Edges**Detector mode: Peak****Polarity: Horizontal****Detector mode: Average****Polarity: Horizontal**

Detector mode: Peak**Polarity: Vertical****Detector mode: Average****Polarity: Vertical**

Detector mode: Peak**Polarity: Horizontal**


CH High

Data: 24

**Detector mode: Average****Polarity: Horizontal**

CH High

Data: 23




Detector mode: Peak**Polarity: Vertical**

CH High

Data: 22

Level (dBuV/m)

Date: 2016-02-16 Time: 20:22:15



Trace:

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2483.50	58.02	4.48	62.50	74.00	-11.50			Peak
2483.65	58.38	4.49	62.87	74.00	-11.13			Peak


Detector mode: Average**Polarity: Vertical**

CH High

Data: 21

Level (dBuV/m)

Date: 2016-02-18 Time: 11:05:37



Trace:

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2483.50	42.99	4.48	47.47	54.00	-6.53			Average
2483.68	42.81	4.49	47.30	54.00	-6.70			Average

7.7 CONDUCTED EMISSION

LIMITS



§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5.00	56	46
5.00 - 30.0	60	50

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
L.I.S.N	Schwarzbeck	NSLK 8127	8127465	08/05/2016
L.I.S.N	Schwarzbeck	NSLK 8127	8127473	03/09/2016
EMI Test Receiver	Rohde & Schwarz	ESHS 30	838550/003	10/31/2016
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100111	06/28/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP

TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.10:2013.

The test procedure is performed in a 4m × 3m × 2.4m (L×W×H) shielded room.


The EUT along with its peripherals were placed on a 1.0m (W) × 1.5m (L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.

The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.

The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN is 0.8 m. Where a mains flexible cord was provided by the manufacturer shall be 1 m long, or if in excess of 1 m, the excess cable was folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.


TEST RESULTS

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Kenneth Huang
Test Model	AB1122	Test Date	2016/02/17
Test mode	Mode 1	Temp. & Humidity	20.1 °C, 42%

LINE**Remark:**

1. Correction Factor = Insertion loss + Cable loss
2. Result level = Reading Value + Correction factor
3. Margin value = Result level – Limit value

Product Name	Airoha Bluetooth 4.2 Data Module	Test By	Kenneth Huang
Test Model	AB1122	Test Date	2016/02/17
Test Mode	Mode 1	Temp. & Humidity	20.1 °C, 42%

NEUTRAL**Remark:**

1. Correction Factor = Insertion loss + Cable loss
2. Result level = Reading Value + Correction factor
3. Margin value = Result level – Limit value