



FCC RF Test Report

(FHSS)

Report No.: JYTSZ-R12-2400355

Applicant: PICA Product Development

Address of Applicant: 4 Ash Street Extension, Derry, NH 03038 USA

Equipment Under Test (EUT)

Product Name: Skyhawk Trapmate PIR Sensor

Model No.: SHBAEG

Trade Mark: N/A

FCC ID: UOXSKEYHAWKBAESEN1

Applicable Standards: FCC CFR Title 47 Part 15C (§15.247)

Date of Sample Receipt: 15 Mar., 2024

Date of Test: 16 Mar., to 09 May., 2024

Date of Report Issued: 09 May., 2024

Test Result: PASS

Tested by:

June Li
Project Engineer

Date:

09 May., 2024

Reviewed by:

Peter Zhang
Senior Engineer

Date:

09 May., 2024

Approved by:

James Wei
Manager

Date:

09 May., 2024

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	09 May., 2024	Original

2 Contents

Page

Cover Page	1
1 Version	2
2 Contents.....	3
3 General Information.....	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode and Test Environment.....	5
3.4 Description of Test Auxiliary Equipment	5
3.5 Measurement Uncertainty	5
3.6 Additions to, Deviations, or Exclusions From the Method.....	6
3.7 Laboratory Facility	6
3.8 Laboratory Location.....	6
3.9 Test Instruments List.....	7
4 Measurement Setup and Procedure	9
4.1 Test Channel	9
4.2 Test Setup	9
4.3 Test Procedure.....	11
5 Test Results.....	12
5.1 Summary	12
5.1.1 Clause and data summary	12
5.1.2 Test Limit.....	13
5.2 Antenna Requirement	14
5.3 Conducted Output Power	15
5.4 20dB Occupied Bandwidth	16
5.5 Carrier Frequencies Separation	17
5.6 Hopping Channel Number.....	18
5.7 Dwell Time.....	19
5.8 Spurious Emission.....	20
5.8.1 Band-edge Emission.....	20
5.8.2 Conducted Spurious Emission.....	21
5.8.3 Emissions in Restricted Frequency Bands	22

3 General Information

3.1 Client Information

Applicant:	PICA Product Development
Address:	4 Ash Street Extension, Derry, NH 03038 USA
Manufacturer:	PICA Product Development
Address:	4 Ash Street Extension, Derry, NH 03038 USA

3.2 General Description of E.U.T.

Product Name:	Skyhawk Trapmate PIR Sensor
Model No.:	SHBAEG
Operation Frequency:	ISM :906 MHz – 923.5 MHz
Number of Channel:	50
Modulation Technology:	Frequency Hopping Spread Spectrum
Antenna Type:	Internal Antenna
Antenna Gain:	3.42 dBi (declare by applicant)
Power Supply:	DC 3.0 V(AA Battery * 2)
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3.3 Test Mode and Test Environment

Test Modes:	
Non-hopping mode:	Keep the EUT in continuous transmitting mode.
Hopping mode:	Keep the EUT in hopping mode.
Remark: For spurious emission of below 1GHz, pre-scan lowest, middle and highest channel, found lowest channel was worse case mode. The report only reflects the test data of worst mode.	
Operating Environment:	
Temperature:	15°C ~ 35°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar
Voltage:	Nominal: 3.00 Vdc,
Test Engineer:	June (Conducted measurement) Kiran (Radiated measurement)

3.4 Description of Test Auxiliary Equipment

The EUT has been tested as an independent unit.

3.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Radiated Emission (30MHz ~ 200MHz) (10m SAC)	4.3 dB
Radiated Emission (200MHz ~ 1000MHz) (10m SAC)	4.3 dB
Radiated Emission (30MHz ~ 1GHz) (3m FAR)	3.43 dB
Radiated Emission (1GHz ~ 6GHz) (3m FAR)	4.95 dB
Radiated Emission (6GHz ~ 18GHz) (3m FAR)	5.23 dB
Radiated Emission (18GHz ~ 40GHz) (3m FAR)	5.32 dB
Note: All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.	

3.6 Additions to, Deviations, or Exclusions From the Method

No

3.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.9 Test Instruments List

Radiated Emission(3m FAR):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m FAR	YUNYI	9m*6m*6m	WXJ097	06-15-2023	06-14-2028
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ097-2	07-13-2023	07-12-2024
Biconical Antenna	Schwarzbeck	VUBA9117	WXJ002-1	07-02-2021	07-01-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ097-3	07-14-2023	07-13-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-3	12-28-2023	12-27-2024
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	12-28-2023	12-27-2024
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-6	12-28-2023	12-27-2024
Pre-amplifier (30MHz ~ 1GHz)	YUNYI	PAM-310N	WXJ097-5	05-14-2023	05-13-2024
Pre-amplifier (1GHz ~ 18GHz)	YUNYI	PAM-118N	WXJ097-6	05-14-2023	05-13-2024
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	12-27-2023	12-26-2024
EMI Test Receiver	Rohde & Schwarz	ESCI3	WXJ003	12-27-2023	12-26-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	12-27-2023	12-26-2024
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ081-1	06-13-2023	06-12-2024
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-13M	WXG097-1	08-01-2023	07-31-2024
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG097-2	08-01-2023	07-31-2024
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG097-3	08-01-2023	07-31-2024
High Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Low Band Reject Filter Group	Tonscend	JS0806-F	WXJ097-4	N/A	
Test Software	Tonscend	TS+	Version: 5.0.0		

Radiated Emission(10m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
10m SAC	ETS	RFSD-100-F/A	WXJ090	04-28-2021	04-27-2026
BiConiLog Antenna	SCHWARZBECK	VULB 9168	WXJ090-1	12-28-2023	12-27-2024
BiConiLog Antenna	SCHWARZBECK	VULB 9168	WXJ090-2	12-28-2023	12-27-2024
EMI Test Receiver	R&S	ESR 3	WXJ090-3	12-27-2023	12-26-2024
EMI Test Receiver	R&S	ESR 3	WXJ090-4	12-27-2023	12-26-2024
Low Pre-amplifier	Bost	LNA 0920N	WXJ090-6	12-27-2023	12-26-2024
Low Pre-amplifier	Bost	LNA 0920N	WXJ090-7	12-27-2023	12-26-2024
Cable	Bost	JYT10M-1G-NN-10M	WXG002-7	01-17-2024	01-16-2025
Cable	Bost	JYT10M-1G-NN-10M	WXG002-8	01-17-2024	01-16-2025
Test Software	R&S	EMC32	Version: 10.50.40		

Conducted Method:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	12-27-2023	12-26-2024
EMI Test Receiver	Rohde & Schwarz	ESCI3	WXJ003	12-27-2023	12-26-2024
Spectrum Analyzer	Keysight	N9010B	WXJ004-3	09-25-2023	09-24-2024
DC Power Supply	Keysight	E3642A	WXJ025-2	N/A	

4 Measurement Setup and Procedure

4.1 Test Channel


According to ANSI C63.10-2013 chapter 5.6.1 Table 4 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:

Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	906.00	26	912.75	49	923.50


4.2 Test Setup

1) Radiated emission measurement:


Below 1GHz (10m SAC)



Above 1GHz (3m FAR)



2) Conducted test method



4.3 Test Procedure

Test method	Test step
Radiated emission	For below 1GHz: - The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 10 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 10 m. - EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. - Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. For above 1GHz: - The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. - EUT works in each mode of operation that needs to be tested, and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. - Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
Conducted test method	- The antenna port of EUT was connected to the test port of the test system through an RF cable. - The EUT is keeping in continuous transmission mode and tested in all modulation modes. - Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.

5 Test Results

5.1 Summary

5.1.1 Clause and data summary

Test items	Standard clause	Test data	Result
Antenna Requirement	15.203 15.247 (b)(4)	See Section 5.2	Pass
AC Power Line Conducted Emission	15.207	N/A	N/A
Conducted Output Power	15.247 (b)(2)	See Section 5.3	Pass
20dB Occupied Bandwidth	15.247 (a)(1)(i)	See Section 5.4	Pass
Carrier Frequencies Separation	15.247 (a)(1)	See Section 5.5	Pass
Hopping Channel Number	5.247 (a)(1)(i)	See Section 5.6	Pass
Dwell Time	15.247 (a)(1)(i)	See Section 5.7	Pass
Spurious Emission	15.205 15.209 15.247 (d)	See Section 5.8	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).			
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02		

5.1.2 Test Limit

Test items	Limit																														
Conducted Output Power	For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.																														
20dB Occupied Bandwidth Hopping Channel Number Dwell Time	For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.																														
Carrier Frequencies Separation	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater																														
Spurious Emission	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)): <table><tr><th rowspan="2">Frequency (MHz)</th><th colspan="2">Limit (dBµV/m)</th><th rowspan="2">Detector</th></tr><tr><th>@ 3m</th><th>@ 10m</th></tr><tr><td>30 – 88</td><td>40.0</td><td>30.0</td><td>Quasi-peak</td></tr><tr><td>88 – 216</td><td>43.5</td><td>33.5</td><td>Quasi-peak</td></tr><tr><td>216 – 960</td><td>46.0</td><td>36.0</td><td>Quasi-peak</td></tr><tr><td>960 – 1000</td><td>54.0</td><td>44.0</td><td>Quasi-peak</td></tr></table> Note: The more stringent limit applies at transition frequencies. <table><tr><th rowspan="2">Frequency</th><th colspan="2">Limit (dBµV/m) @ 3m</th></tr><tr><th>Average</th><th>Peake</th></tr><tr><td>Above 1 GHz</td><td>54.0</td><td>74.0</td></tr></table> Note: The measurement bandwidth shall be 1 MHz or greater.	Frequency (MHz)	Limit (dBµV/m)		Detector	@ 3m	@ 10m	30 – 88	40.0	30.0	Quasi-peak	88 – 216	43.5	33.5	Quasi-peak	216 – 960	46.0	36.0	Quasi-peak	960 – 1000	54.0	44.0	Quasi-peak	Frequency	Limit (dBµV/m) @ 3m		Average	Peake	Above 1 GHz	54.0	74.0
Frequency (MHz)	Limit (dBµV/m)		Detector																												
	@ 3m	@ 10m																													
30 – 88	40.0	30.0	Quasi-peak																												
88 – 216	43.5	33.5	Quasi-peak																												
216 – 960	46.0	36.0	Quasi-peak																												
960 – 1000	54.0	44.0	Quasi-peak																												
Frequency	Limit (dBµV/m) @ 3m																														
	Average	Peake																													
Above 1 GHz	54.0	74.0																													

5.2 Antenna Requirement


Standard requirement:	FCC Part 15 C Section 15.203 & 247(b)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
E.U.T Antenna:	
The EUT antenna is a Internal Antenna which permanently attached, and the best case gain of the antenna is 3.42 dBi. See product internal photos for details.	

5.3 Conducted Output Power


Test channel	Maximum Output Power (dBm)	Limit (dBm)	Result
Lowest channel	12.65	30.00	Pass
Middle channel	12.70	30.00	Pass
Highest channel	12.56	30.00	Pass

Test plot as follows:


Lowest channel



Middle channel



Highest channel



5.4 20dB Occupied Bandwidth

Test channel	20dB Occupy Bandwidth (kHz)	Limit (kHz)	Result
Lowest channel	16.80	250 kHz	Pass
Middle channel	16.50	250 kHz	Pass
Highest channel	16.60	250 kHz	Pass

Test plot as follows:




5.5 Carrier Frequencies Separation


Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest channel	250	25kHz	Pass
Middle channel	250	25kHz	Pass
Highest channel	250	25kHz	Pass

Test plot as follows:


Lowest channel



Middle channel




Highest channel



5.6 Hopping Channel Number

Hopping channel numbers	Limit	Result
50	$N_{ch} \geq 50$	Pass

Test plot as follows:




5.7 Dwell Time

Channel	T_{on} (s)	Hopping numbers (20 s period)	Dwell time (s)	Limit (s)	Result
Lowest	0.163	2	0.326	0.4	Pass
Middle	0.163	2	0.326	0.4	Pass
Highest	0.163	2	0.326	0.4	Pass

Note:

- T_{on} is time per hop.
- Dwell time = T_{on} * Hopping numbers.


Test plot as follows:




5.8 Spurious Emission

5.8.1 Band-edge Emission

Lowest Channel



No-hopping mode




Hopping mode

Highest Channel




No-hopping mode



Hopping mode


5.8.2 Conducted Spurious Emission

Lowest channel



30MHz~10GHz

Middle channel



30MHz~10GHz

Highest channel




30MHz~10GHz

5.8.3 Emissions in Restricted Frequency Bands

906MHz:

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	0.96GHz-1.0GHz	Polarization:	Vertical
Test Voltage:	DC 3.0V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	967.9200	14.49	26.67	41.16	54.00	12.84	PK	Vertical
2	983.4400	14.12	26.81	40.93	54.00	13.07	PK	Vertical
3	999.0000	14.03	26.75	40.78	54.00	13.22	PK	Vertical

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	0.96GHz-1.0GHz	Polarization:	Horizontal
Test Voltage:	DC 3.0V		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	965.5600	13.23	26.61	39.84	54.00	14.16	PK	Horizontal
2	984.2000	14.89	26.81	41.70	54.00	12.30	PK	Horizontal
3	998.7600	14.54	26.75	41.29	54.00	12.71	PK	Horizontal

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	1GHz-1.24GHz	Polarization:	Vertical
Test Voltage:	DC 3.0V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	1036.48	23.15	30.66	53.81	74.00	20.19	290	PK	PASS	Vertical
2	1036.48	11.19	30.66	41.85	54.00	12.15	280	AV	PASS	Vertical
3	1126.72	23.19	30.83	54.02	74.00	19.98	140	PK	PASS	Vertical
4	1126.72	10.70	30.83	41.53	54.00	12.47	110	AV	PASS	Vertical
5	1215.04	23.27	31.28	54.55	74.00	19.45	350	PK	PASS	Vertical
6	1215.04	11.03	31.28	42.31	54.00	11.69	10	AV	PASS	Vertical

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	1GHz-1.24GHz	Polarization:	Horizontal
Test Voltage:	DC 3.0V		



Suspected Data List


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	1039.36	22.75	30.68	53.43	74.00	20.57	200	PK	PASS	Horizontal
2	1039.36	10.84	30.68	41.52	54.00	12.48	100	AV	PASS	Horizontal
3	1131.76	22.47	30.86	53.33	74.00	20.67	200	PK	PASS	Horizontal
4	1131.76	10.57	30.86	41.43	54.00	12.57	30	AV	PASS	Horizontal
5	1223.68	23.45	31.34	54.79	74.00	19.21	340	PK	PASS	Horizontal
6	1223.68	11.46	31.34	42.80	54.00	11.20	50	AV	PASS	Horizontal

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

912.75MHz:

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	0.96GHz-1.0GHz	Polarization:	Vertical
Test Voltage:	DC 3.0V		



Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	965.2800	13.61	26.61	40.22	54.00	13.78	PK	Vertical
2	982.8800	14.41	26.81	41.22	54.00	12.78	PK	Vertical
3	999.0000	13.90	26.75	40.65	54.00	13.35	PK	Vertical

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	0.96GHz-1.0GHz	Polarization:	Horizontal
Test Voltage:	DC 3.0V		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	966.1200	13.35	26.63	39.98	54.00	14.02	PK	Horizontal
2	986.3600	14.13	26.84	40.97	54.00	13.03	PK	Horizontal
3	997.6400	13.16	26.76	39.92	54.00	14.08	PK	Horizontal

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	1GHz-1.24GHz	Polarization:	Vertical
Test Voltage:	DC 3.0V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	1035.04	23.17	30.66	53.83	74.00	20.17	190	PK	PASS	Vertical
2	1035.04	11.03	30.66	41.69	54.00	12.31	320	AV	PASS	Vertical
3	1128.64	22.46	30.85	53.31	74.00	20.69	140	PK	PASS	Vertical
4	1128.64	10.89	30.85	41.74	54.00	12.26	240	AV	PASS	Vertical
5	1210.48	23.85	31.24	55.09	74.00	18.91	350	PK	PASS	Vertical
6	1210.48	11.06	31.24	42.30	54.00	11.70	110	AV	PASS	Vertical

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	1GHz-1.24GHz	Polarization:	Horizontal
Test Voltage:	DC 3.0V		



Suspected Data List


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	1036.48	22.44	30.66	53.10	74.00	20.90	360	PK	PASS	Horizontal
2	1036.48	11.05	30.66	41.71	54.00	12.29	210	AV	PASS	Horizontal
3	1136.56	10.70	30.88	41.58	54.00	12.42	30	AV	PASS	Horizontal
4	1136.56	23.10	30.88	53.98	74.00	20.02	20	PK	PASS	Horizontal
5	1224.64	24.15	31.35	55.50	74.00	18.50	290	PK	PASS	Horizontal
6	1224.64	11.32	31.35	42.67	54.00	11.33	260	AV	PASS	Horizontal

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

923.5MHz:

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	0.96GHz-1.0GHz	Polarization:	Vertical
Test Voltage:	DC 3.0V		




Suspected Data List								
NO.	Freq. [MHz]	Reading[dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	963.2000	13.21	26.59	39.80	54.00	14.20	PK	Vertical
2	980.7200	14.56	26.81	41.37	54.00	12.63	PK	Vertical
3	997.1200	13.41	26.76	40.17	54.00	13.83	PK	Vertical

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	0.96GHz-1.0GHz	Polarization:	Horizontal
Test Voltage:	DC 3.0V		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	964.1600	13.20	26.60	39.80	54.00	14.20	PK	Horizontal
2	983.0000	13.45	26.81	40.26	54.00	13.74	PK	Horizontal
3	998.4400	13.41	26.75	40.16	54.00	13.84	PK	Horizontal

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	1GHz-1.24GHz	Polarization:	Vertical
Test Voltage:	DC 3.0V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	1036.00	22.94	30.66	53.60	74.00	20.40	30	PK	PASS	Vertical
2	1036.00	10.92	30.66	41.58	54.00	12.42	230	AV	PASS	Vertical
3	1127.92	22.97	30.85	53.82	74.00	20.18	340	PK	PASS	Vertical
4	1127.92	10.59	30.85	41.44	54.00	12.56	70	AV	PASS	Vertical
5	1220.32	23.03	31.31	54.34	74.00	19.66	70	PK	PASS	Vertical
6	1220.32	11.10	31.31	42.41	54.00	11.59	90	AV	PASS	Vertical

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Kiran	Test mode:	Tx mode
Test Channel:	1GHz-1.24GHz	Polarization:	Horizontal
Test Voltage:	DC 3.0V		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	1042.00	23.61	30.69	54.30	74.00	19.70	10	PK	PASS	Horizontal
2	1042.00	11.05	30.69	41.74	54.00	12.26	350	AV	PASS	Horizontal
3	1131.04	22.49	30.85	53.34	74.00	20.66	190	PK	PASS	Horizontal
4	1131.04	10.54	30.85	41.39	54.00	12.61	210	AV	PASS	Horizontal
5	1220.08	23.59	31.31	54.90	74.00	19.10	180	PK	PASS	Horizontal
6	1220.08	11.36	31.31	42.67	54.00	11.33	170	AV	PASS	Horizontal


Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Emissions in Non-restricted Frequency Bands

Below 1GHz:

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Asher	Test mode:	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	DC 3.0V		




Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
31.067000	11.67	30.00	18.33	100.0	V	5.0	-17.3
53.959000	11.16	30.00	18.84	100.0	V	146.0	-16.5
165.945500	13.97	33.50	19.53	100.0	V	24.0	-15.7
303.152000	15.37	36.00	20.63	100.0	V	172.0	-15.0
461.213500	23.68	36.00	12.32	100.0	V	253.0	-10.0
816.864000	28.62	36.00	7.38	100.0	V	0.0	-2.3

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Skyhawk Trapmate PIR Sensor	Product Model:	SHBAEG
Test By:	Asher	Test mode:	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	DC 3.0V		



Critical Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
53.183000	12.12	30.00	17.88	100.0	H	276.0	-16.5
138.834000	14.00	33.50	19.50	100.0	H	322.0	-16.3
190.389500	12.21	33.50	21.29	100.0	H	219.0	-18.3
286.662000	14.67	36.00	21.33	100.0	H	358.0	-15.6
467.712500	21.12	36.00	14.88	100.0	H	299.0	-9.9
767.151500	28.70	36.00	7.30	100.0	H	342.0	-3.0

Remark:

1. Level = Reading + FactorAntenna Factor + Cable Loss – Preamplifier Factor).

Above 1GHz:

Lowest channel						
Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polarization
1812.00	71.14	-20.86	50.28	74.00	23.72	Vertical
1812.00	69.03	-20.86	48.17	74.00	25.83	Horizontal
Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polarization
1812.00	65.81	-20.86	44.95	54.00	9.05	Vertical
1812.00	61.99	-20.86	41.13	54.00	12.87	Horizontal
Middle channel						
Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polarization
1825.50	63.05	-20.86	42.19	74.00	31.81	Vertical
1825.50	55.23	-20.86	34.37	74.00	39.63	Horizontal
Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polarization
1825.50	55.21	-20.86	34.35	54.00	19.65	Vertical
1825.50	45.80	-20.86	24.94	54.00	29.06	Horizontal
Highest channel						
Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polarization
1847.00	58.18	-20.86	37.32	74.00	36.68	Vertical
1847.00	53.63	-20.86	32.77	74.00	41.23	Horizontal
Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polarization
1847.00	47.96	-20.86	27.10	54.00	26.90	Vertical
1847.00	44.21	-20.86	23.35	54.00	30.65	Horizontal
Remark:						
1. Level = Read level + Factor.						

-----End of report-----