# FCC Part 15B Measurement and Test Report

#### For

TECHCity Technology Co., Ltd.

4F., No.4, Aly. 1, Siwei Ln., Zhongzheng Rd., Xindian Dist.,

New Taipei City 231, Taiwan(R.O.C.)

FCC ID: UQOLM-312M

Test Standards: FCC Part 15 Subpart B

Product Description: <u>Light Switch</u>

Tested Model: <u>LM-312M</u>

**Report No.:** <u>STR121280291</u>

**Tested Date:** <u>2012-12-07 to 2012-12-12</u>

**Issued Date:** <u>2013-01-16</u>

Tested By: Susan Su / Engineer

Reviewed By: Lahm Peng / EMC Manager

Approved & Authorized By: <u>Jandy so / PSQ Manager</u>

Prepared By:

SEM.Test Compliance Service Co., Ltd

3/F, Jinbao Commerce Building, Xin'an Fanshen Road,

Susom Su Lahm peny Jumbyso

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd

# TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
1.2 TEST STANDARDS	
1.3 TEST METHODOLOGY	
1.4 Test Facility	
1.5 EUT SETUP AND OPERATION MODE	5
2. SUMMARY OF TEST RESULTS	6
3. CONDUCTED EMISSIONS	7
3.1 Measurement Uncertainty	
3.2 TEST EQUIPMENT LIST AND DETAILS	
3.3 TEST PROCEDURE	
3.4 BASIC TEST SETUP BLOCK DIAGRAM	
3.5 Environmental Conditions	
3.6 SUMMARY OF TEST RESULTS/PLOTS	
3.7 CONDUCTED EMISSIONS TEST DATA	8
4. RADIATED EMISSIONS	11
4.1 Measurement Uncertainty	11
4.2 TEST EQUIPMENT LIST AND DETAILS	
4.3 Test Procedure	11
4.4 TEST RECEIVER SETUP	
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	
4.6 Environmental Conditions	
4.7 Summary of Test Results/Plots	12

#### 1. GENERAL INFORMATION

# 1.1 Product Description for Equipment Under Test (EUT)

**Client Information** 

Applicant: TECHCity Technology Co., Ltd.

Address of applicant: 4F., No.4, Aly. 1, Siwei Ln., Zhongzheng Rd.,

Xindian Dist., New Taipei City 231, Taiwan(R.O.C.)

Manufacturer: TECHCity Technology Co., Ltd.

Address of manufacturer: 4F., No.4, Aly. 1, Siwei Ln., Zhongzheng Rd.,

Xindian Dist., New Taipei City 231, Taiwan(R.O.C.)

Light Switch
e-live
LM-312M
LM-311M

Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model LM-312M, but the circuit and the electronic construction do not change, declared by the manufacturer.

Technical Characteristics of EUT			
Frequency Range:	433.92 MHz (Rx)		
Antenna Type:	Integral Antenna		
Modulation:	ASK		
Rated Voltage:	AC 100~240V		
Rated Current:	10A		
Rated Power:	1000W		
Lowest Internal Frequency:	4MHz		

#### 1.2 Test Standards

The following report is prepared on behalf of the TECHCity Technology Co., Ltd. in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart B, and section 15.205, 15.207, and 15.209 rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

#### 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

#### 1.4 Test Facility

#### • FCC – Registration No.: 994117

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

#### • Industry Canada (IC) Registration No.: 7673A

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

#### • CNAS Registration No.: L4062

Shenzhen SEM. Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

# **1.5 EUT Setup and Operation Mode**

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

#### Test Mode List:

Test Mode	Description	Remark
TM1	Operating	/

#### **EUT Cable List and Details**

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

# Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
/	/	/	/

#### Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

# 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.207 (a)	Conducted Emissions	Compliant
§ 15.209 (a)	Radiated Emissions	Compliant

N/A: not applicable

# 3. Conducted Emissions

# 3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.


# 3.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2012-03-28	2013-03-27
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2012-03-28	2013-03-27
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2012-03-28	2013-03-27

# 3.3 Test Procedure

Test is conducting under the description of ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

#### 3.4 Basic Test Setup Block Diagram



# 3.5 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

# 3.6 Summary of Test Results/Plots

According to the data in section 3.7, the EUT <u>complied with the FCC Part 15.107(a)</u> Conducted margin for a Class B device, with the *worst* margin reading of:


-5.12 dB at 0.158 MHz in the Neutral, Peak detector, 0.15-30MHz

# 3.7 Conducted Emissions Test Data


#### **Plot of Conducted Emissions Test Data**


EUT: Light Switch
Tested Model: LM-312M
Operating Condition: Operating
Comment: AC 120/60Hz

Test Specification: Neutral



EDIT PEAK LIST (Prescan Results)			
Trace1:	-QP		
Trace2:	-AV		
Trace3:			
TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB
1 Max Peak	158 kHz	60.44	-5.12
2 Average	158 kHz	46.90	-8.66
2 Average	618 kHz	34.27	-11.72
1 Max Peak	650 kHz	43.84	-12.15
2 Average	1.674 MHz	29.51	-16.48
2 Average	17.986 MHz	32.69	-17.30





EDIT PEAK LIST (Prescan Results)			
Trace1:	-QP		
Trace2:	-AV		
Trace3:			
TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB
1 Max Peak	154 kHz	59.77	-6.00
2 Average	154 kHz	47.19	-8.58
1 Max Peak	646 kHz	43.31	-12.68
2 Average	650 kHz	34.32	-11.67
1 Max Peak	1.55 MHz	38.84	-17.15
2 Average	17.986 MHz	33.55	-16.45

# 4. Radiated Emissions

# **4.1 Measurement Uncertainty**

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is  $\pm$  5.10 dB.


# 4.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2012-03-28	2013-03-27
EMI Test Receiver	R&S	ESVB	825471/005	2012-03-28	2013-03-27
Pre-amplifier	Agilent	8447F	3113A06717	2012-03-28	2013-03-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2012-03-28	2013-03-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2012-02-25	2013-02-24
Horn Antenna	ETS	3117	00086197	2012-02-25	2013-02-24
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2012-02-25	2013-02-24

#### **4.3 Test Procedure**

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.



#### 4.4 Test Receiver Setup

During the radiated emission test for above 1GHz, the test receiver was set with the following configurations:

For peak detector:

RBW = 1000kHz, VBW = 3000kHz, Sweep Time = Auto

For average detector:

RBW = 1000kHz, VBW = 10Hz, Sweep Time = Auto

#### 4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading - Corr. Factor

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of  $-6dB\mu V$  means the emission is  $6dB\mu V$  below the maximum limit for a Class B device. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – FCC Part 15.109(a) Limit

#### 4.6 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

#### 4.7 Summary of Test Results/Plots


According to the data, the EUT complied with the FCC Part 15.209(a) rule, and had the worst margin of:

-7.73 dB at 44.1202 MHz in the Vertical polarization, 9 kHz to 5 GHz, 3Meters

#### **Plot of Radiated Emissions Test Data**


EUT: Light Switch
Tested Model: LM-312M
Operating Condition: Operating
Comment: AC 120V/60Hz

Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	31.5095	21.76	8.30	30.06	40.00	-9.94	189	100	peak
2	42.3022	16.28	8.98	25.26	40.00	-14.74	67	100	peak
3	104.5361	16.57	6.39	22.96	43.50	-20.54	245	100	peak
4	739.6605	15.95	18.07	34.02	46.00	-11.98	65	100	peak

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( °)	(cm)	
1	44.1202	23.84	8.43	32.27	40.00	-7.73	233	100	peak
2	52.9453	22.89	6.34	29.23	40.00	-10.77	24	100	peak
3	416.1791	21.42	10.86	32.28	46.00	-13.72	64	100	peak
4	642.8613	20.27	15.14	35.41	46.00	-10.59	125	100	peak

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above  $5^{th}$  Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. The measurements greater than 20dB below the limit from 9kHz to 30MHz..

\*\*\*\*\* END OF REPORT \*\*\*\*\*