



FCC PART 15 SUBPART E

MEASUREMENT AND TEST REPORT

For

AZALEA NETWORKS

673 S. Milpitas Blvd., Ste 105
Milpitas, CA 95035

FCC ID: URP-MSR1000

| | |
|---|--|
| This Report Concerns: | Product type: |
| <input checked="" type="checkbox"/> Original Report | 802.11a/b/g Wireless Mesh Networking Device |
| Test Engineer: | Dan Corona <i>D. Corona</i> |
| Report Number: | R0702061-407 |
| Report Date: | 2007-03-21 |
| Reviewed By: | Hans Mellberg: VP of Engineering <i>H. Mellberg</i> |
| Prepared By: (12) | Bay Area Compliance Laboratories Corp. (BACL) 1274 Anvilwood Ave. Sunnyvale, CA 94089 Tel: (408) 732-9162 Fax: (408) 732 9164 |

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

| | |
|--|-----------|
| GENERAL INFORMATION..... | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3 |
| EUT PHOTO | 3 |
| MECHANICAL DESCRIPTION..... | 3 |
| OBJECTIVE | 3 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 4 |
| TEST METHODOLOGY | 4 |
| MEASUREMENT UNCERTAINTY | 4 |
| TEST FACILITY | 4 |
| SYSTEM TEST CONFIGURATION..... | 5 |
| JUSTIFICATION | 5 |
| EUT EXERCISE SOFTWARE | 5 |
| SPECIAL ACCESSORIES | 5 |
| EQUIPMENT MODIFICATIONS | 5 |
| LOCAL SUPPORT EQUIPMENT LIST AND DETAILS | 5 |
| SUMMARY OF TEST RESULTS | 6 |
| § 15.407 (F) AND § 2.1091 - RF EXPOSURE | 7 |
| §15.203 - ANTENNA REQUIREMENT..... | 9 |
| APPLICABLE STANDARD | 9 |
| §15.107 - CONDUCTED EMISSIONS | 11 |
| SECTION 15.107 CONDUCTED LIMITS:..... | 11 |
| TEST SETUP..... | 11 |
| TEST EQUIPMENT LIST AND DETAILS..... | 11 |
| TEST PROCEDURE | 11 |
| TEST SETUP DIAGRAM | 12 |
| SUMMARY OF TEST RESULTS | 12 |
| §15.205 & §15.109 & §15.407(B) - RADIATED SPURIOUS EMISSIONS..... | 17 |
| APPLICABLE STANDARD | 17 |
| TEST SETUP..... | 18 |
| TEST EQUIPMENT LIST AND DETAILS..... | 18 |
| TEST PROCEDURE | 19 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 19 |
| TEST SETUP DIAGRAM | 19 |
| SUMMARY OF TEST RESULTS | 20 |
| RADIATED EMISSIONS TEST PLOT & DATA:..... | 21 |
| §15.407 (A) (1) & (A) (2) - MAXIMUM POWER..... | 31 |
| APPLICABLE STANDARD | 31 |
| EQUIPMENT LIST | 31 |
| TEST SETUP DIAGRAM | 31 |
| §15.407 (A) (1) & (A)(3)(5) – PEAK POWER SPECTRAL DENSITY | 36 |
| APPLICABLE STANDARD | 36 |
| MEASUREMENT PROCEDURE..... | 36 |
| EQUIPMENT LIST | 36 |
| TEST SETUP DIAGRAM | 36 |
| §15.407(A) (6) – PEAK EXCURSION | 41 |
| APPLICABLE STANDARD | 41 |
| MEASUREMENT PROCEDURE..... | 41 |
| EQUIPMENT LIST | 41 |
| TEST SETUP DIAGRAM | 41 |


GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

This BACL measurement and test report has been compiled on behalf of *Azalea Networks* and their product *FCC ID: URP-MSR1000*, or the EUT as referred to in the rest of this report. The EUT is an 802.11 a/b/g wireless mesh networking device or router that operates on 2412-2462 MHz, 5180-5240 MHz and 5745-5805 MHz bands. It is designed to work in conjunction with neighboring routers in order to increase the efficiency of data transmissions in a high traffic environment.

** The test data gathered are from a production sample which is provided by the manufacturer with the serial number: 94V-0 0624.*

EUT Photo



Additional EUT photos in Exhibit C

Mechanical Description

The *Azalea Networks* product, measures approximately 267 mm (L) x 135 mm (W) x 35 mm (H) and weighs approximately 1280 g; it is of metallic construction.

Objective

This type approval report is prepared on behalf of *Azalea Networks*. in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for Maximum Output Power, Antenna Requirements, 26 dB Bandwidth, peak power spectral density, Peak excursion , Band Edges Measurement, Conducted and Radiated Spurious Emissions

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the values range from ± 2.0 for Conducted Emissions tests and ± 4.0 dB for Radiated Emissions tests are the most accurate estimates pertaining to uncertainty of EMC measurements at BACL.

Detailed instrumentation measurement uncertainties can be found in BACL report QAP-018.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by BACL Corp. to collect radiated and conducted emissions measurement data is located at it's facility in Sunnyvale, California, USA.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission and Voluntary Control Council for Interference have the reports on file and is listed under FCC registration number: 90464 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, BACL is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200167-0). The current scope of accreditations can be found at <http://ts.nist.gov/ts/htdocs/210/214/scopes/2001670.htm>

SYSTEM TEST CONFIGURATION

Justification

The host system was configured for testing according to ANSI C63.4-2003.

The EUT was tested in the testing mode to represent *worst*-case results during the final qualification test.

EUT Exercise Software

The EUT is programmed with the following data rate settings that were used during testing:

| MODE | 5180MHZ | 5220MHZ | 5240MHZ |
|---------|---------|---------|---------|
| 802.11a | 9 Mbps | 9 Mbps | 9 Mbps |

| MODE | 5745MHZ | 5800MHZ | 5805MHZ |
|---------|---------|---------|---------|
| 802.11a | 9 Mbps | 9 Mbps | 9 Mbps |

Special Accessories

There were no special accessories were required, included, or intended for use with EUT during these tests.

Equipment Modifications

No modifications were made to the EUT.

Local Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| IBM | Laptop | T42 | 23736UU |

SUMMARY OF TEST RESULTS

Results reported relate only to the product tested.

| FCC RULES | DESCRIPTION OF TEST | RESULT |
|--------------------------------------|------------------------------------|---|
| §15.407 (f) §2.1091 | RF Exposure | Compliant |
| §15.203 | Antenna Requirement | Compliant |
| § 15.207 (a) | Conducted Emissions | Compliant |
| § 15.407 (b)(1) & (b)(2) | Spurious Emissions at Antenna Port | Compliant |
| §15.205 | Restricted Band | Compliant |
| §15.209 (a) & §15.407(a)(1) & (a)(2) | Spurious Radiated Emissions | Compliant |
| §15.247 (a)(2) | 99% & 26 dB Bandwidth | N/R |
| §15.407 (a)(1) & (a)(2) | Maximum Peak Output Power | Compliant, Please refer to FCC ID: NKRCM9 |
| § 15.407 (a)(6) | Peak Excursion | Compliant, Please refer to FCC ID: NKRCM9 |
| §15.407 (a)(1) & (a)(2) | Power Spectral Density | Compliant, Please refer to FCC ID: NKRCM9 |
| §15.407 (h) | DFS | N/R |

§ 15.407 (f) and § 2.1091 - RF EXPOSURE

According to §15.407(f) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | f/1500 | 30 |
| 1500-100,000 | / | / | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Prediction

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

802.11a (5150 – 5250 MHz) mode:

| | |
|--|---------------------------------|
| Maximum peak output power at antenna input terminal: | <u>16.825 (dBm)</u> |
| Maximum peak output power at antenna input terminal: | <u>48.139 (mW)</u> |
| Predication distance: | <u>20 (cm)</u> |
| Predication frequency: | <u>5180 (MHz)</u> |
| Antenna Gain (typical): | <u>5 (dBi)</u> |
| antenna gain: | <u>3.16 (numeric)</u> |
| Power density at predication frequency at 20 cm: | <u>0.030(mW/cm²)</u> |

MPE limit for uncontrolled exposure at predication frequency: 1.0 (mW/cm²)

802.11a (5725 – 5825 MHz) mode:

| | |
|--|----------------------------------|
| Maximum peak output power at antenna input terminal: | <u>20.043 (dBm)</u> |
| Maximum peak output power at antenna input terminal: | <u>101.0 (mW)</u> |
| Prediction distance: | <u>20 (cm)</u> |
| Predication frequency: | <u>5805(MHz)</u> |
| Antenna Gain (typical): | <u>5 (dBi)</u> |
| antenna gain: | <u>3.16 (numeric)</u> |
| Power density at predication frequency at 20 cm: | <u>0.063 (mW/cm²)</u> |

MPE limit for uncontrolled exposure at prediction frequency: 1.0 (mW/cm²)

Test Result

The Power Density Level at 20 cm for b/g/n mode is:

For 5150 – 5250 MHz: 802.11a mode = 0.030mW/cm²

For 5725 – 5825 MHz: 802.11a mode = 0.063mW/cm²

which is below the uncontrolled exposure limit of 1.0mW/cm².

§15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Result: The antennae for this device are four identical, dual band antennae with the gain of 5 dBi. Each antenna features a reverse polarity connection type to ensure that non-OEM antennae cannot be implemented by the end user:



2.4 GHz band
Antenna: 5 dBi



5.2GHz band
Antenna: 5 dBi



§15.107 - CONDUCTED EMISSIONS

Section 15.107 Conducted limits:

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency of Emission (MHz) | Conducted Limit (dBuV) | |
|--------------------------------|------------------------|------------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56 * | 56 to 46 * |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

Test Setup

The measurement was performed at shielded room, using the setup per ANSI C63.4 – 2003 measurement procedure. The specification used was FCC Class B limits.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The EUT was connected with LISN-1.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date |
|-----------------|--------------------------|---------|---------------|------------------|
| Rohde & Schwarz | Artificial-Mains Network | ESH2-Z5 | 871884/039 | 2006-11-14 |
| Rohde & Schwarz | EMI Test Receiver | ESCS30 | 100176 | 2006-03-13 |

Statement of Traceability: BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

Test Procedure


During the conducted emissions test, the power cord of the EUT was connected to the mains outlet of the LISN-1.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the peak detection mode, quasi-peak and average. Quasi-Peak readings are distinguished with a “QP”. Average readings are distinguished with an “Ave”.

Test Setup Diagram

Conducted Emissions



Environmental Conditions

| | |
|--------------------|-------------------|
| Temperature: | 20° C -23° C |
| Relative Humidity: | 30% - 63% |
| ATM Pressure: | 101.1 – 101.9 kPa |

*The testing was performed by Dan Corona from 2007-02-15, 22 to 03-14

Summary of Test Results


According to the recorded data in following table, the EUT complied with the FCC standard's conducted emissions limits for Class B devices, with the *worst* margin reading of:

AC Adaptor:

-9.0 dB at 0.171760 MHz in the Line conductor mode

POE:


-4.3 dB at 16.777460 MHz in the Neutral Line conductor mode

Adaptor:**120V/60 Hz Line:****Quasi-Peak**

| Frequency (MHz) | Quasi Peak (dB μ V) | Line | Correction Factor (dB) | Limit (dB μ V) | Margin (dB) |
|-----------------|-------------------------|------|------------------------|--------------------|-------------|
| 0.171760 | 55.1 | L1 | 0.1 | 64.9 | -9.8 |
| 0.228820 | 48.4 | L1 | 0.2 | 62.5 | -14.1 |
| 0.228820 | 48.4 | L1 | 0.2 | 62.5 | -14.1 |
| 0.286020 | 41.8 | L1 | 0.2 | 60.6 | -18.8 |
| 0.340820 | 35.2 | L1 | 0.3 | 59.2 | -24.0 |
| 3.381890 | 31.3 | L1 | 0.3 | 56.0 | -24.7 |

Average


| Frequency (MHz) | Average (dB μ V) | Line | Correction Factor (dB) | Limit (dB μ V) | Margin (dB) |
|-----------------|----------------------|------|------------------------|--------------------|-------------|
| 0.171760 | 45.9 | L1 | 0.1 | 54.9 | -9.0 |
| 0.228820 | 40.9 | L1 | 0.2 | 52.5 | -11.6 |
| 0.228820 | 40.9 | L1 | 0.2 | 52.5 | -11.6 |
| 0.286020 | 33.7 | L1 | 0.2 | 50.6 | -17.0 |
| 4.295120 | 25.5 | L1 | 0.3 | 46.0 | -20.5 |
| 4.879150 | 20.5 | L1 | 0.3 | 46.0 | -25.5 |

120V/60 Hz Neutral:**Quasi-Peak**

| Frequency (MHz) | Quasi Peak (dB μ V) | Line | Correction Factor (dB) | Limit (dB μ V) | Margin (dB) |
|-----------------|-------------------------|---------|------------------------|--------------------|-------------|
| 0.205000 | 51.4 | Neutral | 0.2 | 63.4 | -12.0 |
| 0.309000 | 40.0 | Neutral | 0.2 | 60.0 | -20.0 |
| 0.809000 | 27.9 | Neutral | 0.3 | 56.0 | -28.1 |
| 0.409000 | 29.3 | Neutral | 0.4 | 57.7 | -28.4 |
| 1.169000 | 26.7 | Neutral | 0.3 | 56.0 | -29.3 |
| 1.369000 | 21.9 | Neutral | 0.2 | 56.0 | -34.1 |

Average


| Frequency (MHz) | Average (dB μ V) | Line | Correction Factor (dB) | Limit (dB μ V) | Margin (dB) |
|-----------------|----------------------|---------|------------------------|--------------------|-------------|
| 0.205000 | 39.3 | Neutral | 0.2 | 53.4 | -14.1 |
| 0.809000 | 24.8 | Neutral | 0.3 | 46.0 | -21.2 |
| 1.169000 | 24.3 | Neutral | 0.3 | 46.0 | -21.7 |
| 0.309000 | 28.1 | Neutral | 0.2 | 50.0 | -21.9 |
| 0.413000 | 21.2 | Neutral | 0.4 | 47.6 | -26.4 |
| 0.681000 | 18.7 | Neutral | 0.3 | 46.0 | -27.3 |

POE (Power over Ethernet):**120V/60 Hz Line:****Quasi-Peak**

| Frequency (MHz) | Quasi Peak (dB μ V) | Line | Correction Factor (dB) | Limit (dB μ V) | Margin (dB) |
|-----------------|-------------------------|------|------------------------|--------------------|-------------|
| 14.769230 | 43.4 | L1 | 0.5 | 60.0 | -16.6 |
| 15.616420 | 40.9 | L1 | 0.3 | 60.0 | -19.1 |
| 3.000900 | 36.5 | L1 | 0.3 | 56.0 | -19.5 |
| 3.249800 | 34.8 | L1 | 0.3 | 56.0 | -21.3 |
| 16.512210 | 37.8 | L1 | 0.4 | 60.0 | -22.2 |
| 3.750990 | 33.6 | L1 | 0.3 | 56.0 | -22.4 |

Average

| Frequency (MHz) | Average (dB μ V) | Line | Correction Factor (dB) | Limit (dB μ V) | Margin (dB) |
|-----------------|----------------------|------|------------------------|--------------------|-------------|
| 14.769230 | 42.0 | L1 | 0.5 | 50.0 | -8.0 |
| 3.000900 | 34.5 | L1 | 0.3 | 46.0 | -11.5 |
| 15.616420 | 38.1 | L1 | 0.3 | 50.0 | -11.9 |
| 3.249800 | 32.7 | L1 | 0.3 | 46.0 | -13.3 |
| 0.581280 | 32.2 | L1 | 0.3 | 46.0 | -13.9 |
| 2.749070 | 31.6 | L1 | 0.2 | 46.0 | -14.4 |

120V/60 Hz Neutral:**Quasi-Peak**

| Frequency (MHz) | Quasi Peak (dB μ V) | Line | Correction Factor (dB) | Limit (dB μ V) | Margin (dB) |
|-----------------|-------------------------|---------|------------------------|--------------------|-------------|
| 16.777460 | 48.0 | Neutral | 0.6 | 60.0 | -12.0 |
| 15.616420 | 41.2 | Neutral | 0.3 | 60.0 | -18.9 |
| 29.306470 | 38.3 | Neutral | 0.5 | 60.0 | -21.7 |
| 0.585930 | 33.5 | Neutral | 0.3 | 56.0 | -22.5 |
| 13.422440 | 36.6 | Neutral | 0.5 | 56.0 | -23.4 |
| 3.000900 | 31.4 | Neutral | 0.3 | 56.0 | -24.6 |

Average

| Frequency (MHz) | Average (dB μ V) | Line | Correction Factor (dB) | Limit (dB μ V) | Margin (dB) |
|-----------------|----------------------|---------|------------------------|--------------------|-------------|
| 16.777460 | 45.7 | Neutral | 0.6 | 50.0 | -4.3 |
| 15.616420 | 38.2 | Neutral | 0.3 | 50.0 | -11.8 |
| 0.585930 | 34.1 | Neutral | 0.3 | 46.0 | -11.9 |
| 29.306470 | 36.6 | Neutral | 0.5 | 50.0 | -13.4 |
| 3.000900 | 31.8 | Neutral | 0.3 | 46.0 | -14.2 |
| 3.098090 | 30.4 | Neutral | 0.3 | 46.0 | -15.6 |

§15.205 & §15.109 & §15.407(b) - RADIATED SPURIOUS EMISSIONS

Applicable Standard

As per 15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As per 15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009 - 0.490 | 2400/F(kHz) | 300 |
| 0.490 - 1.705 | 24000/F(kHz) | 30 |
| 1.705 - 30.0 | 30 | 30 |
| 30 - 88 | 100** | 3 |
| 88 - 216 | 150** | 3 |
| 216 - 960 | 200** | 3 |
| Above 960 | 500 | 3 |

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As Per 15.205(a) except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|---------------------|-----------------------|-----------------|---------------|
| 0.090 – 0.110 | 16.42 – 16.423 | 960 – 1240 | 4.5 – 5.15 |
| 0.495 – 0.505 | 16.69475 – 16.69525 | 1300 – 1427 | 5.35 – 5.46 |
| 2.1735 – 2.1905 | 25.5 – 25.67 | 1435 – 1626.5 | 7.25 – 7.75 |
| 4.125 – 4.128 | 37.5 – 38.25 | 1645.5 – 1646.5 | 8.025 – 8.5 |
| 4.17725 – 4.17775 | 73 – 74.6 | 1660 – 1710 | 9.0 – 9.2 |
| 4.20725 – 4.20775 | 74.8 – 75.2 | 1718.8 – 1722.2 | 9.3 – 9.5 |
| 6.215 – 6.218 | 108 – 121.94 | 2200 – 2300 | 10.6 – 12.7 |
| 6.26775 – 6.26825 | 123 – 138 | 2310 – 2390 | 13.25 – 13.4 |
| 6.31175 – 6.31225 | 149.9 – 150.05 | 2483.5 – 2500 | 14.47 – 14.5 |
| 8.291 – 8.294 | 156.52475 – 156.52525 | 2690 – 2900 | 15.35 – 16.2 |
| 8.362 – 8.366 | 156.7 – 156.9 | 3260 – 3267 | 17.7 – 21.4 |
| 8.37625 – 8.38675 | 162.0125 – 167.17 | 3.332 – 3.339 | 22.01 – 23.12 |
| 8.41425 – 8.41475 | 167.72 – 173.2 | 3.3458 – 3.358 | 23.6 – 24.0 |
| 12.29 – 12.293 | 240 – 285 | 3.600 – 4.400 | 31.2 – 31.8 |
| 12.51975 – 12.52025 | 322 – 335.4 | | 36.43 – 36.5 |
| 12.57675 – 12.57725 | 399.9 – 410 | | Above 38.6 |
| 13.36 – 13.41 | 608 – 614 | | |

As per 15.407(b): Undesirable emission limits: Except as shown in paragraph (b)(6) of this section, the peak emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz.
- (4) For transmitters operating in the 5.725–5.825 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of –17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of –27 dBm/MHz.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.
- (7) The provisions of §15.205 apply to intentional radiators operating under this section.
- (8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency block edges as the design of the equipment permits.

Test Setup

The radiated emissions tests were performed in the 3-meter open area test site, using the setup in accordance with ANSI C63.4-2003. The specification used was the FCC 15 Subpart E limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Cal. Date |
|--------------------|---------------------|--------------------|---------------|------------|
| Sonoma Instruments | Pre amplifier | 317 | 260408 | 2006-03-02 |
| Agilent | Pre amplifier | 8449B | 3008A01978 | 2006-08-10 |
| Sunol Science Corp | Combination Antenna | JB3 Antenna | A020106-3 | 2007-03-05 |
| Rohde & Schwarz | EMI Test Receiver | ESCI 1166.595 0K03 | 100337 | 2007-03-08 |
| Sunol Science Corp | System Controller | S9V | 113005-1 | NR |
| Agilent | Spectrum Analyzer | E4440A | MY44303352 | 2007-02-23 |
| A.R.A | Antenna Horn | DRG-118/A | 1132 | 2006-08-17 |
| Agilent | Spectrum Analyzer | 8565EC | 3946A00131 | 2007-01-24 |

* **Statement of Traceability:** BACL attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Procedure

For the radiated emissions test, the EUT, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 mete, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

The spectrum analyzer or receiver is set as:

Below 1000MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000MHz:

- (1) Peak: $\text{RBW} = 1\text{MHz} / \text{VBW} = 1\text{MHz} / \text{Sweep} = \text{Auto}$
- (2) Average: $\text{RBW} = 1\text{MHz} / \text{VBW} = 10\text{Hz} / \text{Sweep} = \text{Auto}$

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:


$$\text{Corrected Amplitude} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit.

The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{FCC Limit}$$

Test Setup Diagram



Environmental Conditions

| | |
|--------------------|----------------------|
| Temperature: | 20° C -23° C |
| Relative Humidity: | 30% - 63% |
| ATM Pressure: | 101.1kPa – 101.9 kPa |

**The testing was performed by Dan Corona from 2007-02-15, 22 to 03-14*

Summary of Test Results

According to the data hereinafter, the EUT complied with the FCC Title 47, Part 15, Subpart E, section 15.205, 15.209 and 15.407, and had the worst margin of:

Unintentional Emissions:

-19 dB at 669.392500 MHz in the **Vertical** polarization for 30 MHz to 1000 MHz

For 5150 – 5250 MHz: 802.11a

-7.8 dB at 155540.0000 MHz in the **Vertical** polarization for Low Channel, 1GHz – 25GHz

-7.9 dB at 15660.0000 MHz in the **Vertical** polarization for Middle Channel, 1GHz – 25GHz

-9.4 dB at 10480.0000 MHz in the **Vertical** polarization for High Channel, 1GHz – 25GHz

For 5745 – 5805 MHz: 802.11a

-17.8 dB at 11490.0000 MHz in the **Vertical** polarization for Low Channel, 1GHz – 25GHz


-3.9 dB at 11570.0000 MHz in the **Horizontal** polarization for Middle Channel, 1GHz – 25GHz

-2.1 dB at 17415.0000 MHz in the **Vertical** polarization for High Channel, 1GHz – 25GHz

Radiated Emissions Test plot & data:

Primary scan 30MHz -1GHz

| Frequency (MHz) | Quasi Peak (dB μ V/m) | Antenna Height (cm) | Polarity | Turntable Position (deg) | Correction Factor (dB) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|---------------------------|---------------------|----------|--------------------------|------------------------|----------------------|-------------|
| 669.392500 | 27.0 | 100.0 | V | 115.0 | -15.7 | 46.0 | -19.0 |
| 803.252500 | 26.5 | 102.0 | V | 248.0 | -14.0 | 46.0 | -19.5 |
| 640.008750 | 25.2 | 101.0 | H | 347.0 | -16.1 | 46.0 | -20.8 |
| 439.987500 | 23.9 | 156.0 | V | 137.0 | -19.1 | 46.0 | -22.1 |
| 480.000000 | 23.9 | 116.0 | V | 122.0 | -18.3 | 46.0 | -22.1 |
| 767.297500 | 15.2 | 101.0 | H | 10.0 | -13.9 | 46.0 | -30.8 |



For 5150 – 5250 MHz: 802.11a

Low channel

| Frequency (MHz) | Reading (dB μ V) | Azimuth Degree | Height (m) | Polar. H / V | Antenna Factor (dB/m) | Cable loss (dB) | Pre-Amp. dB | Correction Factor (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Comments |
|-----------------|----------------------|----------------|------------|--------------|-----------------------|-----------------|-------------|----------------------------------|----------------------|-------------|-----------|
| 5180.0000 | 101.3 | 289 | 2.0 | V | 34.0 | 3.9 | 34.9 | 104.3 | | | Fund/Peak |
| 5180.0000 | 93.2 | 48 | 1.0 | H | 34.0 | 3.9 | 34.9 | 96.3 | | | Fund/Peak |
| 5180.0000 | 91.5 | 289 | 2.0 | V | 34.0 | 3.9 | 34.9 | 94.6 | | | Ave |
| 5180.0000 | 83.5 | 48 | 1.0 | H | 34.0 | 3.9 | 34.9 | 86.6 | | | Ave |
| 15540.0000 | 31.8 | 156 | 1.5 | V | 40.4 | 7.3 | 33.2 | 46.2 | 54 | -7.8 | Ave |
| 15540.0000 | 31.8 | 217 | 1.0 | H | 40.4 | 7.3 | 33.2 | 46.2 | 54 | -7.8 | Ave |
| 10360.0000 | 38.0 | 252 | 1.5 | H | 38.0 | 5.7 | 36.8 | 44.9 | 54 | -9.1 | Ave |
| 10360.0000 | 37.0 | 301 | 1.7 | V | 38.0 | 5.7 | 36.8 | 43.9 | 54 | -10.1 | Ave |
| 10360.0000 | 51.4 | 252 | 1.5 | H | 38.0 | 5.7 | 36.8 | 58.3 | 74 | -15.7 | Peak |
| 15540.0000 | 43.6 | 156 | 1.7 | V | 40.4 | 7.3 | 33.2 | 58.0 | 74 | -16.0 | Peak |
| 10360.0000 | 50.3 | 301 | 1.7 | V | 38.0 | 5.7 | 36.8 | 57.2 | 74 | -16.8 | Peak |
| 15540.0000 | 42.5 | 217 | 1.0 | H | 40.4 | 7.3 | 33.2 | 56.9 | 74 | -17.1 | Peak |

Middle channel

| Frequency (MHz) | Reading (dB μ V) | Azimuth Degree | Height (m) | Polar. H / V | Antenna Factor (dB/m) | Cable loss (dB) | Pre-Amp. dB | Correction Factor (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Comments |
|-----------------|----------------------|----------------|------------|--------------|-----------------------|-----------------|-------------|----------------------------------|----------------------|-------------|-----------|
| 5220.0000 | 104.1 | 205 | 1.2 | V | 34.0 | 4.0 | 34.4 | 107.7 | | | Fund/Peak |
| 5220.0000 | 96.0 | 327 | 1.1 | H | 34.0 | 4.0 | 34.4 | 99.5 | | | Fund/Peak |
| 5220.0000 | 94.3 | 205 | 1.2 | V | 34.0 | 4.0 | 34.4 | 97.9 | | | Ave |
| 5220.0000 | 86.2 | 327 | 1.1 | H | 34.0 | 4.0 | 34.4 | 89.7 | | | Ave |
| 15660.0000 | 31.7 | 213 | 1.3 | V | 40.4 | 7.2 | 33.2 | 46.1 | 54 | -7.9 | Ave |
| 15660.0000 | 31.7 | 315 | 1.4 | H | 40.4 | 7.2 | 33.2 | 46.1 | 54 | -7.9 | Ave |
| 10440.0000 | 38.0 | 290 | 1.5 | H | 38.0 | 5.8 | 36.8 | 45.0 | 54 | -9.0 | Ave |
| 10440.0000 | 38.0 | 227 | 1.8 | V | 38.0 | 5.8 | 36.8 | 44.9 | 54 | -9.1 | Ave |
| 15660.0000 | 43.8 | 315 | 1.4 | H | 40.4 | 7.2 | 33.2 | 58.2 | 74 | -15.8 | Peak |
| 15660.0000 | 43.4 | 213 | 1.3 | V | 40.4 | 7.2 | 33.2 | 57.8 | 74 | -16.2 | Peak |
| 10440.0000 | 50.7 | 227 | 1.8 | V | 38.0 | 5.8 | 36.8 | 57.6 | 74 | -16.4 | Peak |
| 10440.0000 | 50.4 | 290 | 1.5 | H | 38.0 | 5.8 | 36.8 | 57.4 | 74 | -16.6 | Peak |

High channel

| Frequency (MHz) | Reading (dB μ V) | Azimuth Degree | Height (m) | Polar. H / V | Antenna Factor (dB/m) | Cable loss (dB) | Pre-Amp. dB | Correction Factor (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Comments |
|-----------------|----------------------|----------------|------------|--------------|-----------------------|-----------------|-------------|----------------------------------|----------------------|-------------|-----------|
| 5240.0000 | 104.3 | 177 | 1.6 | V | 34.0 | 4.0 | 34.4 | 107.8 | | | Fund/Peak |
| 5240.0000 | 92.6 | 232 | 1.6 | H | 34.0 | 4.0 | 34.4 | 96.2 | | | Fund/Peak |
| 5240.0000 | 94.8 | 177 | 1.6 | V | 34.0 | 4.0 | 34.4 | 98.4 | | | Ave |
| 5240.0000 | 84.0 | 232 | 1.6 | H | 34.0 | 4.0 | 34.4 | 87.6 | | | Ave |
| 10480.0000 | 37.6 | 239 | 1.5 | V | 38.0 | 5.8 | 36.8 | 44.6 | 54 | -9.4 | Ave |
| 10480.0000 | 37.6 | 277 | 1.3 | H | 38.0 | 5.8 | 36.8 | 44.6 | 54 | -9.4 | Ave |
| 15720.0000 | 30.1 | 325 | 1.3 | V | 40.4 | 7.3 | 33.2 | 44.5 | 54 | -9.5 | Ave |
| 15720.0000 | 30.1 | 273 | 1.1 | H | 40.4 | 7.3 | 33.2 | 44.5 | 54 | -9.5 | Ave |
| 10480.0000 | 50.5 | 239 | 1.5 | V | 38.0 | 5.8 | 36.8 | 57.4 | 74 | -16.6 | Peak |
| 10480.0000 | 49.5 | 277 | 1.3 | H | 38.0 | 5.8 | 36.8 | 56.4 | 74 | -17.6 | Peak |
| 15720.0000 | 41.8 | 325 | 1.3 | V | 40.4 | 7.3 | 33.2 | 56.2 | 74 | -17.8 | Peak |
| 15720.0000 | 41.6 | 273 | 1.1 | H | 40.4 | 7.3 | 33.2 | 56.1 | 74 | -17.9 | Peak |


Note: All frequencies from 1GHz to 40 GHz have been investigated.

The restricted band limit is 54 dB μ V/m, the out of band limit is 68.3 dB μ V/m.


Restricted band edge

Low channel


Peak, Horizontal




Average, Horizontal



Peak, Vertical



Average, Vertical



For 5745 – 5850 MHz: 802.11a

Low channel

| Frequency (MHz) | Reading (dB μ V) | Azimuth Degree | Height (m) | Polar. H / V | Antenna Factor (dB/m) | Cable loss (dB) | Pre-Amp. dB | Correction Factor (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Comments |
|-----------------|----------------------|----------------|------------|--------------|-----------------------|-----------------|-------------|----------------------------------|----------------------|-------------|-----------|
| 5745.0000 | 108.7 | 290 | 1.0 | V | 34.1 | 4.2 | 34.4 | 112.5 | | | Fund/Peak |
| 5745.0000 | 93.0 | 100 | 1.0 | H | 34.1 | 4.2 | 34.4 | 96.8 | | | Fund/Peak |
| 5745.0000 | 98.4 | 290 | 1.0 | V | 34.1 | 4.2 | 34.4 | 102.2 | | | Ave |
| 5745.0000 | 83.5 | 100 | 1.0 | H | 34.1 | 4.2 | 34.4 | 87.3 | | | Ave |
| 11490.0000 | 30.3 | 210 | 1.6 | V | 39.3 | 6.1 | 39.5 | 36.2 | 54 | -17.8 | Ave |
| 11490.0000 | 30.3 | 252 | 1.5 | H | 39.3 | 6.1 | 39.5 | 36.2 | 54 | -17.8 | Ave |
| 11490.0000 | 44.1 | 210 | 1.6 | V | 39.3 | 6.1 | 39.5 | 50.0 | 74 | -24.0 | Peak |
| 11490.0000 | 43.9 | 236 | 1.7 | H | 39.3 | 6.1 | 39.5 | 49.8 | 74 | -24.2 | Peak |

Middle channel

| Frequency (MHz) | Reading (dB μ V) | Azimuth Degree | Height (m) | Polar. H / V | Antenna Factor (dB/m) | Cable loss (dB) | Pre-Amp. dB | Correction Factor (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Comments |
|-----------------|----------------------|----------------|------------|--------------|-----------------------|-----------------|-------------|----------------------------------|----------------------|-------------|-----------|
| 5785.0000 | 111.8 | 306 | 1.0 | V | 34.1 | 4.3 | 34.4 | 115.7 | | | Fund/Peak |
| 5785.0000 | 98.3 | 119 | 1.5 | H | 34.1 | 4.3 | 34.4 | 102.2 | | | Fund/Peak |
| 5785.0000 | 101.7 | 306 | 1.0 | V | 34.1 | 4.3 | 34.4 | 105.6 | | | Ave |
| 5785.0000 | 88.3 | 119 | 1.5 | H | 34.1 | 4.3 | 34.4 | 92.2 | | | Ave |
| 11570.0000 | 36.4 | 165 | 1.2 | H | 39.5 | 6.1 | 32.0 | 50.1 | 54 | -3.9 | Ave |
| 11570.0000 | 32.4 | 155 | 1.1 | V | 39.5 | 6.1 | 32.0 | 46.1 | 54 | -7.9 | Ave |
| 11570.0000 | 47.9 | 165 | 1.2 | H | 39.5 | 6.1 | 32.0 | 61.6 | 74 | -12.4 | Peak |
| 11570.0000 | 44.6 | 155 | 1.1 | V | 39.5 | 6.1 | 32.0 | 58.3 | 74 | -15.7 | Peak |

High channel

| Frequency (MHz) | Reading (dB μ V) | Azimuth Degree | Height (m) | Polar. H / V | Antenna Factor (dB/m) | Cable loss (dB) | Pre-Amp. dB | Correction Factor (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Comments |
|-----------------|----------------------|----------------|------------|--------------|-----------------------|-----------------|-------------|----------------------------------|----------------------|-------------|-----------|
| 5805.0000 | 109.1 | 217 | 1.2 | V | 34.1 | 4.2 | 34.3 | 113.1 | | | Fund/Peak |
| 5805.0000 | 96.7 | 124 | 1.3 | H | 34.1 | 4.2 | 34.3 | 100.8 | | | Fund/Peak |
| 5805.0000 | 98.5 | 217 | 1.2 | V | 34.1 | 4.2 | 34.3 | 102.6 | | | Ave |
| 5805.0000 | 86.4 | 124 | 1.3 | H | 34.1 | 4.2 | 34.3 | 90.4 | | | Ave |
| 17415.0000 | 32.3 | 222 | 1.3 | V | 43.6 | 7.6 | 31.6 | 51.9 | 54 | -2.1 | Ave |
| 17415.0000 | 32.3 | 311 | 1.6 | H | 43.6 | 7.6 | 31.6 | 51.9 | 54 | -2.1 | Ave |
| 11610.0000 | 37.5 | 183 | 1.3 | V | 39.5 | 6.2 | 32.0 | 51.2 | 54 | -2.8 | Ave |
| 11610.0000 | 31.5 | 222 | 1.3 | H | 39.5 | 6.2 | 32.0 | 45.2 | 54 | -8.8 | Ave |
| 17415.0000 | 44.4 | 311 | 1.6 | H | 43.6 | 7.6 | 31.6 | 64.1 | 74 | -9.9 | Peak |
| 17415.0000 | 44.3 | 238 | 1.3 | V | 43.6 | 7.6 | 31.6 | 64.0 | 74 | -10.0 | Peak |
| 11610.0000 | 46.0 | 183 | 1.3 | V | 39.5 | 6.2 | 32.0 | 59.7 | 74 | -14.3 | Peak |
| 11610.0000 | 41.6 | 222 | 1.3 | H | 39.5 | 6.2 | 32.0 | 55.3 | 74 | -18.7 | Peak |


Note: All frequencies from 1GHz to 40 GHz have been investigated.

The restricted band limit is 54 dB μ V/m, the out of band limit is 68.3 dB μ V/m.


Restricted band edge

Low channel


Peak, Horizontal




Average, Horizontal



Peak, Vertical




Average, Vertical




High channel


Peak, Horizontal




Average, Horizontal



Peak, Vertical



Average, Vertical



§15.407 (a) (1) & (a) (2) - MAXIMUM POWER

Applicable Standard

§15.407 (a)(1) For the band 5.15 – 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or $4 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725–5.825 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 1 W or $17 \text{ dBm} + 10 \log B$, where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 17 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


Measurement Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to a spectrum analyzer.
3. Add a correction factor to the display.

Equipment List

Please refer to International Standard Laboratory report number **04LR018FC (FCC ID: NKRCM9)**.

Test Setup Diagram



Environmental Conditions

Please refer to International Standard Laboratory report number **04LR018FC (FCC ID: NKRCM9)**.

**The testing was performed by International Standard Laboratory*

Test Result



For 5150 – 5250 MHz: 802.11a


| Frequency (MHz) | Peak Power Output (dBm) | 26 dBc BW/Limit MHz/dBm | The lesser Limit (dBm) | Pass/Fail |
|-----------------|-------------------------|-------------------------|------------------------|-----------|
| 5180 | 14.481 | 25.83 / 18.12 | 17.00 | Pass |
| 5210 | 16.825 | 50.16 / 21.00 | 17.00 | Pass |
| 5240 | 13.918 | 26.28 / 18.20 | 17.00 | Pass |

For 5725 – 5825 MHz: 802.11a


| Frequency (MHz) | Peak Power Output (dBm) | 26 dBc BW/Limit MHz/dBm | The lesser Limit (dBm) | Pass/Fail |
|-----------------|-------------------------|-------------------------|------------------------|-----------|
| 5745 | 20.012 | 26.28 / 31.20 | 30.00 | Pass |
| 5760 | 19.293 | 53.04 / 34.25 | 30.00 | Pass |
| 5805 | 20.043 | 29.34 / 31.67 | 30.00 | Pass |



For 5150 – 5250 MHz: 802.11a





For 5725 – 5825 MHz: 802.11a





§15.407 (a) (1) & (a)(3)(5) – PEAK POWER SPECTRAL DENSITY

Applicable Standard

§15.407 (a)(1) For the band 5.15 – 5.25 GHz, the peak power spectral density shall not exceed 4 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§15.407 (a)(2) For the band 5.25 – 5.35 GHz, the peak power spectral density shall not exceed 11 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§15.407 (a)(3) For the band 5.725–5.825 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 1 W or $17 \text{ dBm} + 10 \log B$, where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 17 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

§15.407 (a)(5) The peak power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A resolution bandwidth less than the measurement bandwidth can be used, provided that the measured power is integrated to show total power over the measurement bandwidth. If the resolution bandwidth is approximately equal to the measurement bandwidth, and much less than the emission bandwidth of the equipment under test, the measured results shall be corrected to account for any difference between the resolution bandwidth of the test instrument and its actual noise bandwidth.


Measurement Procedure

1. Using sample detector and power averaging mode, set RBW=1 MHz and VBW > 1 MHz.
2. PSD is the highest level found across the emission in any 1-MHz band after 100 sweeps of averaging.
3. When the emission bandwidth is less than 1 MHz, a measurement bandwidth equal to the emission bandwidth is used in accordance with section 15.407(a) (5).

Equipment List

Please refer to International Standard Laboratory report number **04LR018FC (FCC ID: NKRCM9)**.

Test Setup Diagram



Environmental Conditions

Please refer to International Standard Laboratory report number **04LR018FC (FCC ID: NKRCM9)**.

**The testing was performed by International Standard Laboratory*

Test Result

For 5150 – 5250 MHz: 802.11a

| Frequency (MHz) | Spectrum Reading (dBm) | Cable Loss (dB) | Peak Power Output MHz/dBm | Limit (dBm/MHz) | Pass/Fail |
|-----------------|------------------------|-----------------|---------------------------|-----------------|-----------|
| 5180 | 2.68 | 1.20 | 3.88 | 4.00 | Pass |
| 5210 | 2.60 | 1.20 | 3.80 | 4.00 | Pass |
| 5240 | 2.13 | 1.20 | 3.33 | 4.00 | Pass |

For 5725 – 5825 MHz: 802.11a

| Frequency (MHz) | Spectrum Reading (dBm) | Cable Loss (dB) | Peak Power Output MHz/dBm | Limit (dBm/MHz) | Pass/Fail |
|-----------------|------------------------|-----------------|---------------------------|-----------------|-----------|
| 5745 | 8.07 | 1.20 | 9.27 | 17 | Pass |
| 5760 | 3.76 | 1.20 | 4.99 | 17 | Pass |
| 5805 | 8.34 | 1.20 | 9.54 | 17 | Pass |

For 5150 – 5250 MHz: 802.11a





For 5725 – 5825 MHz: 802.11a





§15.407(a) (6) – Peak Excursion

Applicable Standard

According to §15.407 (a)(6), the ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.


Measurement Procedure

1. Set the SA span to view the entire emission bandwidth. The largest difference between the following two traces must be less than or equal to 13 dB for all frequencies across the emission bandwidth.
2. For the first trace, set RBW = 1MHz and VBW greater or equal to 3MHz utilizing the peak detector and max-hold function. Second trace is created using the setting as described in method # 3 as used in measuring conducted peak output power under FCC Public Notice for U-NII devices August 30, 2002.

Equipment List

Please refer to International Standard Laboratory report number **04LR018FC (FCC ID: NKRCM9)**.

Test Setup Diagram



Environmental Conditions

Please refer to International Standard Laboratory report number **04LR018FC (FCC ID: NKRCM9)**.

**The testing was performed by International Standard Laboratory*

Test Result



For 5150 – 5250 MHz: 802.11a


| Frequency (MHz) | Peak Power Excursion (dBm) | Limit (dBm) | Pass/Fail |
|-----------------|----------------------------|-------------|-----------|
| 5180 | 11.98 | 13 | Pass |
| 5210 | 11.98 | 13 | Pass |
| 5240 | 11.73 | 13 | Pass |

For 5725 – 5825 MHz: 802.11a

| Frequency (MHz) | Peak Power Excursion (dBm) | Limit (dBm) | Pass/Fail |
|-----------------|----------------------------|-------------|-----------|
| 5745 | 11.98 | 13 | Pass |
| 5760 | 10.63 | 13 | Pass |
| 5805 | 11.04 | 13 | Pass |

For 5150 – 5250 MHz: 802.11a





For 5725 – 5825 MHz: 802.11a

