



March 13, 2007

Mr. Lee Masoian
Airrorlite Communications, Inc.
17-01 Politt Drive
Fair Lawn, NJ 07410

RE: FCC Part 90.219

APPLICATION: FCC ID: UT650289BA8800DL

Dear Mr. Masoian:

The device referenced by FCC ID above has been determined to meet Class B requirements under the FCC Rules.

Therefore, under guidance from FCC document 2-11-04/EAB/RF, Airrorlite Communications, Inc. is informed that the following FCC Part 90.219 requirements must be met.

§ 90.219 Use of signal boosters.

Licenses authorized to operate radio systems in the frequency bands above 150 MHz may employ signal boosters at fixed locations in accordance with the following criteria:

- (a) The amplified signal is retransmitted only on the exact frequency(ies) of the originating base, fixed, mobile, or portable station(s). The booster will fill in only weak signal areas and cannot extend the system's normal signal coverage area.
- (b) Class B broadband signal boosters are permitted to be used only in confined or indoor areas such as buildings, tunnels, underground areas, etc., or in remote areas, i.e., areas where there is little or no risk of interference to other users.

Please do not hesitate to contact us, should you have any questions.

Sincerely,

Steven D. Koster
EMC Operations Manager

Brian J. Dettling
Documentation Specialist

WLL Project #: 9520