

Straubing, 07 December 2006

T E S T - R E P O R T

No. 51971-060823-1 (Edition 1)

for

**WaveNET Router Node
Transceiver for Electronic Lock**

Applicant: SimonsVoss Technologies AG

Test Specifications: FCC Code of Federal Regulations,
CFR 47, Part 15,
Sections 15.107, 15.109, 15.205, 15.207,
15.215 and 15.249

Industry Canada Radio Standards
Specifications
RSS-Gen Issue 1, Sections 7.2.2, 7.2.3 and
RSS-210 Issue 6, Sections 2.2, A2.9
(Category I Equipment)

Note:

The test data of this report is related only to the individual item which has been tested. This report shall not be reproduced except in full extent without the written approval of the testing laboratory.

Table of Contents

1	Description of the Equipment Under Test (EUT)	3
2	Administrative Data.....	4
3	Identification of the Test Laboratory	5
4	Summary	6
5	Operation Mode and Configuration of EUT.....	7
6	Measurement Procedures.....	8
6.1	Conducted Output Power	8
6.2	Bandwidth Measurements	10
6.3	Conducted AC Powerline Emission	12
6.4	Radiated Emission in Fully or Semi Anechoic Room.....	14
6.5	Radiated Emission at Open Field Test Site.....	16
7	Photographs Taken During Testing	17
8	Test Results for Transmitter	22
8.1	Conducted Output Power	24
8.2	Occupied Bandwidth.....	25
8.3	Bandwidth of the Emission	29
8.4	Designation of Emissions	31
8.5	Restricted Bands of Operation	32
8.6	Conducted Powerline Emission Measurement 150 kHz to 30 MHz.....	33
8.7	Radiated Emission Measurement 30 MHz to 10 GHz	34
8.8	Exposure of Humans to RF Fields.....	36
9	Test Results for Receiver.....	38
9.1	Radiated Emission Measurement 30 MHz to 5 GHz	39
10	Referenced Regulations	40
11	Charts taken during testing	41

1 Description of the Equipment Under Test (EUT)

General data of EUT	
Type designation ¹ :	WaveNET Router Node
Parts ² :	
Serial number(s):	US-Band
Manufacturer:	SimonsVoss Technologies AG
Type of equipment:	Transceiver for Electronic Lock
Version:	As delivered
FCC ID:	
Additional parts/accessories:	

Technical data of EUT	
Application frequency range:	902 - 928 MHz
Frequency range:	915 MHz
Operating frequency:	915 MHz
Type of modulation:	GFSK
Pulse train:	---
Pulse width:	---
Number of RF-channels:	1
Channel spacing:	Not applicable
Designation of emissions ³ :	158kF1D
Type of antenna:	Monopole
Size/length of antenna:	105 mm
Connection of antenna:	<input checked="" type="checkbox"/> detachable <input type="checkbox"/> not detachable
Type of power supply:	DC supply
Specifications for power supply:	nominal voltage: 6.0 V minimum voltage: 5.4 V maximum voltage: 6.6 V

¹ Type designation of the system if EUT consists of more than one part.

² Type designations of the parts of the system, if applicable.

³ Also known as "Class of Emission".

2 Administrative Data

Application details	
Applicant (full address):	SimonsVoss Technologies AG Feringastrasse 4 85774 Unterföhring Germany
Contact person:	Mr. Ludger Voss
Contract identification:	---
Receipt of EUT:	19 September 2006
Date(s) of test:	September - November 2006
Note(s):	---

Report details	
Report number:	51971-060823-1
Edition:	1
Issue date:	07 December 2006

3 Identification of the Test Laboratory

Details of the Test Laboratory	
Company name:	Senton GmbH EMI/EMC Test Center
Address:	Aeussere Fruehlingstrasse 45 D-94315 Straubing Germany
Laboratory accreditation:	DAR-Registration No. DAT-P-171/94-02
FCC test site registration number	90926
Industry Canada test site registration:	IC 3050
Contact person:	Mr. Johann Roidt
	Phone: (+49) (0)9421 5522-0 Fax: (+49) (0)9421 5522-99

4 Summary

Summary of test results

The tested sample complies with the requirements set forth in the
Code of Federal Regulations CFR 47, Part 15, Sections 15.109, 15.205, 15.207, 15.215 and 15.249
of the Federal Communication Commission (FCC) and the
Radio Standards Specifications
RSS-Gen Issue 1, Sections 7.2.2, 7.2.3 and
RSS-210 Issue 6, Sections 2.2, 2.6, A2.9 (Category I Equipment)
of Industry Canada (IC).

Personnel involved in this report

Laboratory Manager:



Mr. Johann Roidt

Responsible for testing:



Mr. Martin Steindl

Responsible for test report:

Mr. Martin Steindl

5 Operation Mode and Configuration of EUT

Operation Modes

Tests were performed for receive mode and transmitting with normal modulation.

Configuration(s) of EUT

The EUT was configured as stand alone device.

List of ports and cables

Port	Description	Classification ⁴	Cable type	Cable length
1	DC power supply	dc power	Unshielded	

List of devices connected to EUT

Item	Description	Type Designation	Serial no. or ID	Manufacturer
	Not applicable			

List of support devices


Item	Description	Type Designation	Serial no. or ID	Manufacturer
	Not applicable			

⁴ Ports shall be classified as ac power, dc power or signal/control port

6 Measurement Procedures

6.1 Conducted Output Power

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 2, section 2.1046(a) IC RSS-Gen Issue 1, section 4.6
Guide:	CFR 47 Part 2, section 2.1046 / IC RSS-Gen Issue 1
Conducted output power is measured at the RF output terminals (e.g. antenna connector if antenna is detachable) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The RF output terminals are connected to a spectrum analyzer and/or a power meter with appropriate sensor. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable.	
If a spectrum analyzer is used and no other settings are specified resolution bandwidth shall be selected according to the carrier frequency f_c and set to 10 kHz ($150 \text{ kHz} \leq f_c < 30 \text{ MHz}$), 100 kHz ($30 \text{ MHz} \leq f_c < 1 \text{ GHz}$) or 1 MHz ($f_c \geq 1 \text{ GHz}$). The video bandwidth shall be at least three times greater than the resolution bandwidth. The settings used have to be indicated within the appropriate test record(s).	




Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
<input type="checkbox"/>	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	ESPI7	836914/0002	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/>	Power meter	NRVS	836856/015	Rohde & Schwarz
<input checked="" type="checkbox"/>	Peak power sensor	NRV-Z31	8579604.03	Rohde & Schwarz
<input type="checkbox"/>	Power sensor	NRV-Z52	837901/030	Rohde & Schwarz
<input checked="" type="checkbox"/>	Power sensor	NRV-Z4	863828/015	Rohde & Schwarz
<input type="checkbox"/>	DC-block	7006	A2798	Weinschel
<input type="checkbox"/>	Attenuator	4776-10	9412	Narda
<input type="checkbox"/>	Attenuator	4776-20	9503	Narda

6.2 Bandwidth Measurements

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 2, section 2.202(a) CFR 47 Part 15, section 15.215(c) IC RSS-Gen Issue 1, sections 4.4.1 and 4.4.2 IC RSS-210 Issue 6, section A1.1.3 ANSI C63.4, annex H.6
Guide:	ANSI C63.4 / IC RSS-Gen Issue 1, sections 4.4.1 and 4.4.2
Measurement setup:	<input checked="" type="checkbox"/> Conducted: See below <input type="checkbox"/> Radiated: Radiated Emission in Fully or Semi Anechoic Room (6.4)
<p>If antenna is detachable bandwidth measurements shall be performed at the antenna connector (conducted measurement) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The RF output terminals are connected to a spectrum analyzer. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable.</p> <p>If radiated measurements are performed the same test setups and instruments are used as with radiated emission measurements for the appropriate frequency range.</p> <p>The analyzer settings are specified by the test description of the appropriate test record(s).</p>	




Test instruments used for conducted measurements:

Used	Type	Model	Serial No. or ID	Manufacturer
<input type="checkbox"/>	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
<input checked="" type="checkbox"/>	EMI test receiver	ESPI7	836914/0002	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
<input type="checkbox"/>	Power meter	NRVS	836856/015	Rohde & Schwarz
<input type="checkbox"/>	Peak power sensor	NRV-Z31	8579604.03	Rohde & Schwarz
<input type="checkbox"/>	Power sensor	NRV-Z52	837901/030	Rohde & Schwarz
<input type="checkbox"/>	Power sensor	NRV-Z4	863828/015	Rohde & Schwarz
<input type="checkbox"/>	DC-block	7006	A2798	Weinschel
<input type="checkbox"/>	Attenuator	4776-10	9412	Narda
<input type="checkbox"/>	Attenuator	4776-20	9503	Narda

6.3 Conducted AC Powerline Emission

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, sections 15.107 and 15.207 IC RSS-Gen Issue 1, section 7.2.2
Guide:	ANSI C63.4 (CISPR 22)
Conducted emission tests in the frequency range 150 kHz to 30 MHz are performed using Line Impedance Stabilization Networks (LISNs). To simplify testing with quasi-peak and average detector the following procedure is used:	
First the whole spectrum of emission caused by the equipment under test (EUT) is recorded with detector set to peak using CISPR bandwidth of 10 kHz. After that all emission levels having less margin than 10 dB to or exceeding the average limit are retested with detector set to quasi-peak. If average limit is kept with quasi-peak levels no additional scan with average detector is necessary. In cases of emission levels between quasi-peak and average limit an additional scan with detector set to average is performed.	
According to ANSI C63.4, section 13.1.3.1, testing of intentional radiators with detachable antenna shall be performed using a suitable dummy load connected to the antenna output terminals. Otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. Testing with dummy load may be necessary to distinguish (unintentional) conducted emissions on the supply lines from (intentional) emissions radiated by the antenna and coupling directly to supply lines and/or LISN. Usage of dummy load has to be stated in the appropriate test record(s) and notes should be added to clarify the test setup.	




Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	EMI receiver	ESHS 10	860043/016	Rohde & Schwarz
<input checked="" type="checkbox"/>	LISN	ESH3-Z5	862770/021	Rohde & Schwarz
<input type="checkbox"/>	LISN	ESH3-Z5	830952/025	Rohde & Schwarz
<input type="checkbox"/>	Artificial mains network	ESH 2-Z5	842966/004	Rohde & Schwarz
<input type="checkbox"/>	Shielded room	No. 1	1451	Albatross Projects
<input checked="" type="checkbox"/>	Shielded room	No. 4	3FD-100 544	Euroshield

Note: Performed as conducted DC line emissions

6.4 Radiated Emission in Fully or Semi Anechoic Room

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, sections 15.109, 15.215(b) and 15.249 IC RSS-Gen Issue 1, sections 6(a), 7.2.3.2 IC RSS-210 Issue 6, section A2.9
Guide:	ANSI C63.4
<p>Radiated emission in fully or semi anechoic room is measured in the frequency range from 30 MHz to the maximum frequency as specified in CFR 47 Part 15 section 15.33.</p> <p>Measurements are made in both the horizontal and vertical planes of polarization in a fully anechoic room using a spectrum analyzer with the detector function set to peak and resolution as well as video bandwidth set to 100 kHz (below 1 GHz) or 1 MHz (above 1 GHz).</p> <p>Testing up to 1 GHz is performed with a linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna"). For testing above 1 GHz horn antennas are used.</p> <p>All tests below 18 GHz are performed at a test distance D of 3 meters. For higher frequencies the test distance is reduced (e.g. to 1 meter) due to the sensitivity of the measuring instrument(s) and the test results are calculated according to CFR 47 Part 15 section 15.31(f)(1) using an extrapolation factor of 20 dB/decade. If required, preamplifiers are used for the whole frequency range. Special care is taken to avoid overload, using appropriate attenuators and filters, if necessary.</p> <p>If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.</p> <p>Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.</p> <p>During testing the EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.</p> <p>For final testing below 1 GHz an open field test-site is used and the plots recorded in the fully or semi anechoic room are indicated as prescans.</p>	




Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
<input type="checkbox"/>	Spectrum analyzer	R 3271	05050023	Advantest
<input type="checkbox"/>	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/>	Preamplifier	CPA9231A	3393	Schaffner
<input type="checkbox"/>	Preamplifier	R14601		Advantest
<input checked="" type="checkbox"/>	Preamplifier 1-8 GHz	AFS3-00100800-32-LN	847743	Miteq
<input type="checkbox"/>	Preamplifier 0.5-8 GHz	AMF-4D-005080-25-13P	860149	Miteq
<input checked="" type="checkbox"/>	Preamplifier 8-18 GHz	ACO/180-3530	32641	CTT
<input type="checkbox"/>	External Mixer	WM782A	845881/005	Tektronix
<input type="checkbox"/>	Harmonic Mixer	FS-Z30	843389/007	Rohde & Schwarz
	Accessories			
<input checked="" type="checkbox"/>	Trilog broadband antenna	VULB 9163	9163-188	Schwarzbeck
<input checked="" type="checkbox"/>	Horn antenna	3115	9508-4553	EMCO
<input type="checkbox"/>	Horn antenna	3160-03	9112-1003	EMCO
<input type="checkbox"/>	Horn antenna	3160-04	9112-1001	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-05	9112-1001	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-06	9112-1001	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-07	9112-1008	EMCO
<input type="checkbox"/>	Horn antenna	3160-08	9112-1002	EMCO
<input type="checkbox"/>	Horn antenna	3160-09	9403-1025	EMCO
<input type="checkbox"/>	Horn antenna	3160-10	399185	EMCO
<input checked="" type="checkbox"/>	Fully anechoic room	No. 2	1452	Albatross Projects
<input type="checkbox"/>	Semi-anechoic room	No. 3	1453	Siemens

6.5 Radiated Emission at Open Field Test Site

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, sections 15.109, 15.215(b) and 15.249 IC RSS-Gen Issue 1, sections 6(a), 7.2.3.2 IC RSS-210 Issue 6, section A2.9
Guide:	ANSI C63.4
<p>Radiated emission at open field test site is measured in the frequency range 30 MHz to 1 GHz using a biconical antenna up to 300 MHz and a logarithmic periodic antenna above. The measurement bandwidth of the test receiver is set to 120 kHz with quasi-peak detector selected.</p> <p>If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.</p> <p>Hand-held or body-worn devices are tested in the position producing the highest emission relative to the limit as verified by prescans in the fully anechoic room. EUT is rotated all around and receiving antenna is raised and lowered within 1 meter to 4 meters to find the maximum levels of emission. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.</p> <p>For measuring emissions of intentional radiators and receivers a test distance D of 3 meters is selected. Testing of unintentional radiators is performed at a distance of 10 meters. If limits specified for 3 meters shall be used for measurements performed at 10 meters distance the limits are calculated according to CFR 47 Part 15 section 15.31(d) and (f)(1) using an inverse linear-distance extrapolation factor of 20 dB/decade.</p>	



Test instruments used:


Used	Type	Model	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	EMI receiver	ESVP	881120/024	Rohde & Schwarz
<input checked="" type="checkbox"/>	Biconical antenna	EG 1	HK 116	Rohde & Schwarz
<input checked="" type="checkbox"/>	Log. per. antenna	EG 1	HL 223	Rohde & Schwarz
<input checked="" type="checkbox"/>	Open field test site	EG 1	1450	Senton

7 Photographs Taken During Testing

Test setup for conducted DC powerline emission measurement



**Test setup for radiated emission measurement
(fully anechoic room)**



**Test setup for radiated emission measurement
(open field test site)**



**Test setup for radiated emission measurement
(open field test site) - continued -**



8 Test Results for Transmitter

FCC CFR 47 Parts 2 and 15			
Section(s)	Test	Page	Result
2.1046(a)	Conducted output power	24	Recorded
2.202(a)	Occupied bandwidth	25	Recorded
15.215(c)	Bandwidth of the emission	29	Test passed
2.201, 2.202	Class of emission	31	Calculated
15.35(c)	Pulse train measurement for pulsed operation	---	Not applicable
15.205(a)	Restricted bands of operation	32	Test passed
15.207	Conducted DC powerline emission 150 kHz to 30 MHz	33	Test passed
15.205(b) 15.249	Radiated emission 9 kHz to 30 MHz	---	Not applicable according to CFR 47 Part 15, section 15.33(a)
15.205(b) 15.215(b) 15.249	Radiated emission 30 MHz to 10 GHz	34	Test passed

IC RSS-Gen Issue 1			
Section(s)	Test	Page	Result
4.6	Transmitter output power (conducted)	24	Recorded
4.4.1	Occupied Bandwidth	25	Recorded
3.2(h), 8	Designation of emissions	31	Calculated
4.3	Pulsed operation	---	Not applicable
7.2.2	Transmitter DC power lines conducted emissions 150 kHz to 30 MHz	33	Test passed
5.5	Exposure of Humans to RF Fields	36	Exempted from SAR and RF evaluation

IC RSS-210 Issue 6			
Section(s)	Test	Page	Result
2.2(a)	Restricted bands and unwanted emission frequencies	32	Test passed
2.2(b)(c), 2.6 A2.9	Unwanted emissions 9 kHz to 30 MHz	---	Not applicable according to IC RSS-Gen Issue 1, section 4.7
2.2(b)(c), 2.6 A2.9	Unwanted emissions 30 MHz to 10 GHz	34	Test passed

8.1 Conducted Output Power

Rules and specifications:	CFR 47 Part 2, section 2.1046(a) IC RSS-Gen Issue 1, section 4.6
Guide:	CFR 47 Part 2, section 2.1046 / IC RSS-Gen Issue 1
Description:	Conducted output power shall be measured at the RF output terminals (e.g. antenna connector if antenna is detachable) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.
Measurement procedure:	Conducted Output Power (6.1)

Comment:	
Date of test:	07 December 2006
Test site:	Unshielded room

Antenna gain: dBi							
Mode	Frequency (MHz)	Power Type	Reading (dBm)	Correction (dB)	Output Power (dBm)	Limit (dBm)	Margin (dB)
	916.0	Peak	5.6	0.0	5.6		

Note 1: If applicable, PEP (peak envelope power) and RMS values are measured using a power meter with appropriate sensor.

Note 2: If applicable, peak or average values are measured using a spectrum analyzer with resolution and video bandwidth set to: RBW = , VBW =


Note 3: If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power limit is reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Occupied Bandwidth

Rules and specifications:	CFR 47 Part 2, section 2.202(a) ANSI C63.4, annex H.6								
Guide:	ANSI C63.4								
Description:	<p>The occupied bandwidth according to CFR 47 Part 2, section 2.202(a), is measured as the 99% emission bandwidth, i.e. below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5% of the total mean power radiated by a given emission.</p> <p>The occupied bandwidth according to ANSI C63.4, annex H.6; is measured as the frequency range defined by the points that are 26 dB down relative to the maximum level of the modulated carrier.</p> <p>The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:</p> <table border="1"><thead><tr><th>Fundamental frequency</th><th>Minimum resolution bandwidth</th></tr></thead><tbody><tr><td>9 kHz to 30 MHz</td><td>1 kHz</td></tr><tr><td>30 MHz to 1000 MHz</td><td>10 kHz</td></tr><tr><td>1000 MHz to 40 GHz</td><td>100 kHz</td></tr></tbody></table> <p>The video bandwidth shall be at least three times greater than the resolution bandwidth.</p>	Fundamental frequency	Minimum resolution bandwidth	9 kHz to 30 MHz	1 kHz	30 MHz to 1000 MHz	10 kHz	1000 MHz to 40 GHz	100 kHz
Fundamental frequency	Minimum resolution bandwidth								
9 kHz to 30 MHz	1 kHz								
30 MHz to 1000 MHz	10 kHz								
1000 MHz to 40 GHz	100 kHz								
Measurement procedure:	Bandwidth Measurements (6.2)								

Comment:	
Date of test:	7 December 2006
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):



Comment: 060822: Occupied Bandwidth
Date: 7.DEC.2006 17:24:52


Occupied Bandwidth (99 %): **86 kHz**

Occupied Bandwidth (continued)

Rules and specifications:	IC RSS-Gen Issue 1, section 4.4.1
Guide:	IC RSS-Gen Issue 1, section 4.4.1
Description:	<p>If not specified in the applicable RSS the occupied bandwidth is measured as the 99% emission bandwidth.</p> <p>The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth.</p> <p>The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is also recorded. The span between the two recorded frequencies is the occupied bandwidth.</p>
Measurement procedure:	Bandwidth Measurements (6.2)

Comment:	
Date of test:	7 December 2006
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):




Comment: 060822: Occupied Bandwidth
Date: 7.DEC.2006 17:24:52

Occupied Bandwidth (99 %): **86 kHz**

8.3 Bandwidth of the Emission

Rules and specifications:	CFR 47 Part 15, section 15.215(c)								
Guide:	ANSI C63.4								
Description:	<p>The 20 dB bandwidth of the emission is measured as the frequency range defined by the points that are 20 dB down relative to the maximum level of the modulated carrier.</p> <p>For intentional radiators operating under the alternative provisions to the general emission limits the requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.</p> <p>The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:</p> <table border="1"><thead><tr><th>Fundamental frequency</th><th>Minimum resolution bandwidth</th></tr></thead><tbody><tr><td>9 kHz to 30 MHz</td><td>1 kHz</td></tr><tr><td>30 MHz to 1000 MHz</td><td>10 kHz</td></tr><tr><td>1000 MHz to 40 GHz</td><td>100 kHz</td></tr></tbody></table> <p>The video bandwidth shall be at least three times greater than the resolution bandwidth.</p>	Fundamental frequency	Minimum resolution bandwidth	9 kHz to 30 MHz	1 kHz	30 MHz to 1000 MHz	10 kHz	1000 MHz to 40 GHz	100 kHz
Fundamental frequency	Minimum resolution bandwidth								
9 kHz to 30 MHz	1 kHz								
30 MHz to 1000 MHz	10 kHz								
1000 MHz to 40 GHz	100 kHz								
Measurement procedure:	Bandwidth Measurements (6.2)								

Comment:	
Date of test:	7 December 2007
Test site:	Fully anechoic room, cabin no. 2



Comment: 060822: Bandwidth of Emission
Date: 7.DEC.2006 17:25:44

Permitted frequency band:	902 - 928 MHz	
20 dB bandwidth:	102 kHz	
Carrier frequency stability:	<input type="checkbox"/> specified	<input checked="" type="checkbox"/> not specified
Maximum frequency tolerances:	+ kHz - kHz	
Bandwidth of the emission: kHz	within permitted frequency band ⁵ : <input checked="" type="checkbox"/> yes <input type="checkbox"/> no

Test Result:	Test passed
--------------	-------------

⁵ If a frequency stability is not specified, it is recommended that the fundamental emission is kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.4 Designation of Emissions

Rules and specifications:	CFR 47 Part 2, sections 2.201 and 2.202 IC RSS-Gen Issue 1, sections 3.2(h) and 8
Guide:	ANSI C63.4 / TRC-43

Type of modulation:	Frequency Modulation
---------------------	----------------------


$B_n = \text{Necessary Bandwidth}$	$B_n = 2M + 2DK$
$M = \text{Modulation frequency}$	$M = 19.2 \text{ kHz}$
$D = \text{Peak deviation}$	$D = 60 \text{ kHz}$
$K = \text{Overall numerical factor}$	$K = 1$
Calculation:	$B_n = 2 \cdot (19.2 \text{ kHz}) + 2 \cdot (30 \text{ kHz}) \cdot 1 = 158 \text{ kHz}$

Designation of Emissions:	158kF1D
---------------------------	----------------

8.5 Restricted Bands of Operation

Rules and specifications:	CFR 47 Part 15, section 15.205(a) IC RSS-210 Issue 6, section 2.2(a)
Guide:	ANSI C63.4
Limit:	Only spurious emissions are permitted in any of the frequency bands listed in CFR 47 Part 15, section 15.205(a) or IC RSS-210 Issue 6, section 2.2(a).
Measurement procedure:	Radiated Emission in Fully or Semi Anechoic Room (6.4)

Comment:	
Date of test:	7 December 2007
Test site:	Fully anechoic room, cabin no. 2
Test distance:	3 meters



Comment: 060822: Restricted Bands of Operation
Date: 7.DEC.2006 17:00:02

Test Result:	Test passed
--------------	-------------

8.6 Conducted Powerline Emission Measurement 150 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, section 15.207 IC RSS-Gen Issue 1, section 7.2.2		
Guide:	ANSI C63.4 / CISPR 22		
Limit:	Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
		Quasi-peak	Average
	0.15 - 0.5	66 to 56	56 to 46
	0.5 - 5	56	46
	5 - 30	60	50
Measurement procedure:	Conducted AC Powerline Emission (6.3)		

Comment:	
Date of test:	13 October 2007
Test site:	Shielded room, cabin no. 1

Test Result:	Test passed
--------------	-------------

Tested on:	plus
------------	------

All emissions show more than 20 dB margin to the limit

Tested on:	minus
------------	-------

All emissions show more than 20 dB margin to the limit

Sample calculation of final values:

$$\text{Final Value (dB}\mu\text{V)} = \text{Reading Value (dB}\mu\text{V)} + \text{Correction Factor (dB)}$$

8.7 Radiated Emission Measurement 30 MHz to 10 GHz

Rules and specifications:	CFR 47 Part 15, sections 15.215(b) and 15.249 IC RSS-210 Issue 6, section A2.9		
Guide:	ANSI C63.4		
Limit:	Frequency of Emission (MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)
	30 - 88	100	40.0
	88 - 216	150	43.5
	216 - 960	200	46.0
	Above 960	500	54.0
Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.			
Measurement procedures:	Radiated Emission in Fully or Semi Anechoic Room (6.4) Radiated Emission at Open Field Test Site (6.5)		

Comment:		
Date of test:	26 September 2006 / 9 October 2006	
Test site:	Frequencies \leq 1 GHz: Open field test site Frequencies $>$ 1 GHz: Fully anechoic room, cabin no. 2	
Test distance:	Frequencies \leq 8.2 GHz: 3 m Frequencies $>$ 8.2 GHz: 1 m	

Test Result:	Test passed
--------------	-------------

Frequency (MHz)	Antenna Polarization	Detector	Receiver Reading (dB μ V)	Correction Factor (dB/m)	Pulse Train Correction (dB)	Final Value (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
603.030	vertical	Quasi-Peak	20.4	22.1		42.5	46.0	3.5
655.030	vertical	Quasi-Peak	21.5	23.3		44.8	46.0	1.2
694.030	vertical	Quasi-Peak	20.5	24.0		44.5	46.0	1.5
785.030	vertical	Quasi-Peak	21.4	24.4		45.8	46.0	0.2
798.030	vertical	Quasi-Peak	18.7	24.7		43.4	46.0	2.6
863.030	vertical	Quasi-Peak	18.4	26.2		44.6	46.0	1.4
915.030	vertical	Quasi-Peak	67.2	26.3		93.5	94.0	0.5
967.030	horizontal	Quasi-Peak	17.7	27.7		45.4	54.0	8.6
1829.972	vertical	Average	21.8	31.4		53.2	54.0	0.8
2744.940	vertical	Average	17.9	34.8		52.7	54.0	1.4
5492.800	horizontal	Peak	12.1	34.9		47.0	54.0	7.0
6404.600	vertical	Peak	13.8	38.3		52.1	54.0	1.9
9150.400	horizontal	Peak	14.3	43.8		58.1	63.5	5.4

Sample calculation of final values:

Final Value (dB μ V/m) = Reading Value (dB μ V) + Correction Factor (dB/m)
+ Pulse Train Correction (dB)

8.8 Exposure of Humans to RF Fields

Rules and specifications:	IC RSS-Gen Issue 1, section 5.5
Guide:	IC RSS-102 Issue 2, section 2.5

Exposure of Humans to RF Fields		Applicable	Declared by applicant	Measured	Exemption
The antenna is					
<input checked="" type="checkbox"/> detachable					<input checked="" type="checkbox"/>
The conducted output power (CP in watts) is measured at the antenna connector:					
$CP = 3.6 \text{ mW}$					<input checked="" type="checkbox"/>
The effective isotropic radiated power (EIRP in watts) is calculated using					
<input checked="" type="checkbox"/> the numerical antenna gain: $G = 1$			<input checked="" type="checkbox"/>		
$EIRP = G \cdot CP \Rightarrow EIRP = 3.6 \text{ mW}$					
<input checked="" type="checkbox"/> the field strength ⁶ in V/m: $FS = 48.9 \text{ mV/m}$				<input checked="" type="checkbox"/>	
$EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = 719.6 \text{ mW}$					
with:					
Distance between the antennas in m: $D = 3 \text{ m}$					<input checked="" type="checkbox"/>
<input type="checkbox"/> not detachable					
A field strength measurement is used to determine the effective isotropic radiated power (EIRP in watts) given by ⁶ :					
$EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \dots \text{ W}$					
with:					
Field strength in V/m: $FS = \dots \text{ V/m}$				<input type="checkbox"/>	
Distance between the two antennas in m: $D = \dots \text{ m}$				<input type="checkbox"/>	
Selection of output power					
The output power TP is the higher of the conducted or effective isotropic radiated power (e.i.r.p.):					
$TP = 3.6 \text{ mW}$					

⁶ The conversion formula is valid only for properly matched antennas. In other cases the transmitter output power may have to be measured by a terminated measurement when applying the exemption clauses. If an open area test site is used for field strength measurement, the effect due to the metal ground reflecting plane should be subtracted from the maximum field strength value in order to reference it to free space, before calculating TP.

Exposure of Humans to RF Fields (continued)		Applicable	Declared by applicant	Measured	Exemption
Separation distance between the user and the transmitting device is					
<input type="checkbox"/> less than or equal to 20 cm <input checked="" type="checkbox"/> greater than 20 cm			<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Transmitting device is					
<input type="checkbox"/> in the vicinity of the human head <input type="checkbox"/> body-worn			<input checked="" type="checkbox"/>	<input type="checkbox"/>	
SAR evaluation					
SAR evaluation is required if the separation distance between the user and the device is less than or equal to 20 cm.					
<input type="checkbox"/> The device operates from 3 kHz up to 1 GHz inclusively and its source-based time-averaged output power is less than, or equal to 200 mW for General Public Use and 1000 mW for Controlled Use.					<input type="checkbox"/>
<input type="checkbox"/> The device operates above 1 GHz up to 2.2 GHz inclusively and its source-based time-averaged output power is less than, or equal to 100 mW for General Public Use and 500 mW for Controlled Use.					<input type="checkbox"/>
<input type="checkbox"/> The device operates above 2.2 GHz up to 3 GHz inclusively and its source-based time-averaged output power is less than, or equal to 20 mW for General Public Use and 100 mW for Controlled Use.					<input type="checkbox"/>
<input type="checkbox"/> The device operates above 3 GHz up to 6 GHz inclusively and its source-based time-averaged output power) is less than, or equal to 10 mW for General Public Use and 50 mW for Controlled Use.					<input type="checkbox"/>
<input type="checkbox"/> SAR evaluation is documented in test report no.					
RF exposure evaluation					
RF exposure evaluation is required if the separation distance between the user and the device is greater than 20 cm.					
<input checked="" type="checkbox"/> The device operates below 1.5 GHz and its e.i.r.p. is equal to or less than 2.5 W.				<input checked="" type="checkbox"/>	
<input type="checkbox"/> The device operates at or above 1.5 GHz and the e.i.r.p. of the device is equal to or less than 5 W.				<input type="checkbox"/>	
<input type="checkbox"/> RF exposure evaluation is documented in test report no.					

9 Test Results for Receiver

FCC CFR 47 Part 15			
<i>Section(s)</i>	<i>Test</i>	<i>Page</i>	<i>Result</i>
15.107	Conducted DC powerline emission 150 kHz to 30 MHz	---	Not applicable
15.109	Radiated emission 30 MHz to 5 GHz	39	Test passed
15.111(a)	Antenna power conduction emission of receivers 9 kHz to 5 GHz	---	Not applicable

IC RSS-Gen Issue 1			
<i>Section(s)</i>	<i>Test</i>	<i>Page</i>	<i>Result</i>
7.2.2	Transmitter DC power lines conducted emissions 150 kHz to 30 MHz	---	Not applicable
6(a), 7.2.3.2	Receiver spurious emissions (radiated) 30 MHz to 5 GHz	39	Test passed
6(b), 7.2.3.1	Receiver spurious emissions (antenna conducted) 9 kHz to 5 GHz	---	Not applicable

9.1 Radiated Emission Measurement 30 MHz to 5 GHz

Rules and specifications:	CFR 47 Part 15, section 15.109 (Class B) IC RSS-Gen Issue 1, sections 6(a) and 7.2.3.2		
Guide:	ANSI C63.4		
Limit:	Frequency of Emission (MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)
	30 - 88	100	40.0
	88 - 216	150	43.5
	216 - 960	200	46.0
Measurement procedures:	Above 960	500	54.0
	Radiated Emission in Fully or Semi Anechoic Room (6.4) Radiated Emission at Open Field Test Site (6.5)		

Comment:	
Date of test:	9 October 2006
Test site:	Frequencies \leq 1 GHz: Open field test site Frequencies $>$ 1 GHz: Fully anechoic room, cabin no. 2
Test distance:	3 meters

Test Result:	Test passed
--------------	-------------

Frequency (MHz)	Antenna Polarization	Detector	Receiver Reading (dB μ V)	Correction Factor (dB/m)	Final Value (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
688.990	vertical	Quasi-Peak	6.8	24.0	30.8	46.0	15.2

Sample calculation of field final values:

$$\text{Final Value (dB μ V/m)} = \text{Reading Value (dB μ V)} + \text{Correction Factor (dB/m)}$$

10 Referenced Regulations

All tests were performed with reference to the following regulations and standards:

<input checked="" type="checkbox"/>	CFR 47 Part 2	Code of Federal Regulations Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)	October 10, 2004
<input checked="" type="checkbox"/>	CFR 47 Part 15	Code of Federal Regulations Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)	September 19, 2005
<input checked="" type="checkbox"/>	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	December 11, 2003 (published on January 30, 2004)
<input checked="" type="checkbox"/>	RSS-Gen	Radio Standards Specification RSS-Gen Issue 1 containing General Requirements and Information for the Certification of Radiocommunication Equipment, published by Industry Canada	September 2005
<input checked="" type="checkbox"/>	RSS-210	Radio Standards Specification RSS-210 Issue 6 for Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, published by Industry Canada	September 2005
<input type="checkbox"/>	RSS-310	Radio Standards Specification RSS-310 Issue 1 for Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category II Equipment, published by Industry Canada	September 2005
<input checked="" type="checkbox"/>	RSS-102	Radio Standards Specification RSS-102 Issue 2: Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)	November 2005
<input type="checkbox"/>	ICES-003	Interference-Causing Equipment Standard ICES-003 Issue 4 for Digital Apparatus, published by Industry Canada	February 7, 2004
<input checked="" type="checkbox"/>	CISPR 22	Third Edition of the International Special Committee on Radio Interference (CISPR), Pub. 22, "Information Technology Equipment – Radio Disturbance Characteristics – Limits and Methods of Measurement"	1997
<input type="checkbox"/>	CAN/CSA-CEI/IEC CISPR 22	Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment	2002
<input checked="" type="checkbox"/>	TRC-43	Notes Regarding Designation of Emission (Including Necessary Bandwidth and Classification), Class of Station and Nature of Service, published by Industry Canada	October 9, 1982

11 Charts taken during testing


Conducted Emission Test 150 kHz - 30 MHz according to FCC Part 15 Subpart C

Model: WaveNET Router Node	
Serial no.: FCC sample	
Applicant: SimonsVoss Technologies AG	
Test site: Shielded room, cabin no. 4	
Tested on: Linecord DC supply plus	
Date of test: 10/13/2006	Operator: M. Steindl
Test performed: semi automatically	File name:

Mode: - DC 6 V power supply
- TX continuously with modulation

Detector: Peak / Final Results: QP

Final results: 20 dB Margin	25 Subranges
--------------------------------	--------------



Result: Limit kept

Project file: 51971-060823


Conducted Emission Test 150 kHz - 30 MHz according to FCC Part 15 Subpart C

Model: WaveNET Router Node	
Serial no.: FCC sample	
Applicant: SimonsVoss Technologies AG	
Test site: Shielded room, cabin no. 4	
Tested on: Linecord DC supply minus	
Date of test: 10/13/2006	Operator: M. Steindl
Test performed: semi automatically	File name:

Mode: - DC 6 V power supply
- TX continuously with modulation

Detector: Peak / Final Results: QP

Final results: 20 dB Margin	25 Subranges
--------------------------------	--------------



Result: Limit kept

Project file: 51971-060823


Radiated Emission Test 30 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model: WaveNET Router Node	
Serial no.: ---	
Applicant: SimonsVoss Technologies AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 09/26/2006	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - DC 6 V power supply - TX with modulation

Detector: Peak

List of values: Selected by hand



Result: Prescan

Project file: 51971-60823-2


Radiated Emission Test 30 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model: WaveNET Router Node	
Serial no.: ---	
Applicant: SimonsVoss Technologies AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 09/26/2006	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - DC 6 V power supply - TX with modulation

Detector: Peak

List of values: Selected by hand



Result: Prescan

Project file: 51971-60823-2


Radiated Emission Test 1 GHz - 3.95 GHz acc. to FCC Part 15 (EMCO 3115)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Horizontal Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
automatically	default.emi

Comment:
- DC 6 V power supply
- TX with modulation

Detector:
Peak

List of values:
Selected by hand



Result:
Prescan

Project file:
51971-60823-2


Radiated Emission Test 1 GHz - 3.95 GHz acc. to FCC Part 15 (EMCO 3115)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Vertical Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
automatically	default.emi

Comment:
- DC 6 V power supply
- TX with modulation

Detector:
Peak

List of values:
Selected by hand



Result:
Prescan

Project file:
51971-60823-2

Radiated Emission Test 1 GHz - 3.95 GHz


acc. to FCC Part 15 (EMCO 3115)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Vertical Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
by hand	default.emi

Comment:
- DC 6 V power supply
- TX with modulation
- RBW = 1 MHz VBW = 1 kHz

Detector:	Average
-----------	---------

List of values:
Selected by hand



Result:
Limit kept

Project file:
51971-60823-2


Radiated Emission Test 3.95 GHz - 5.85 GHz acc. to FCC Part 15 (EMCO 3160)

Model: WaveNET Router Node	
Serial no.: ---	
Applicant: SimonsVoss Technologies AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 09/26/2006	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - DC 6 V power supply - TX with modulation

Detector: Peak

List of values: 10 dB Margin	50 Subranges
---------------------------------	--------------



Result: Prescan

Project file: 51971-60823-2


Radiated Emission Test 3.95 GHz - 5.85 GHz acc. to FCC Part 15 (EMCO 3160)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Vertical Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
automatically	default.emi

Comment:
- DC 6 V power supply
- TX with modulation

Detector:	Peak
-----------	------

List of values:
Selected by hand



Result:
Prescan

Project file:
51971-60823-2


Radiated Emission Test 5.85 GHz - 8.2 GHz acc. to FCC Part 15 (EMCO 3160)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Horizontal Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
automatically	default.emi

Comment:
- DC 6 V power supply
- TX with modulation

Detector:
Peak

List of values:
Selected by hand



Result:
Limit kept

Project file:
51971-60823-2


Radiated Emission Test 5.85 GHz - 8.2 GHz acc. to FCC Part 15 (EMCO 3160)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Vertical Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
automatically	default.emi

Comment:
- DC 6 V power supply
- TX with modulation

Detector:
Peak

List of values:
Selected by hand



Result:
Limit kept

Project file:
51971-60823-2


Radiated Emission Test 8.2 GHz - 10 GHz acc. to FCC Part 15 (EMCO 3160)

Model: WaveNET Router Node	
Serial no.: ---	
Applicant: SimonsVoss Technologies AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Horizontal Polarization	
Date of test: 09/26/2006	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - DC 6 V power supply - TX with modulation

Detector: Peak

List of values: 10 dB Margin	50 Subranges
---------------------------------	--------------




Result: Limit kept

Project file: 51971-60823-2

Radiated Emission Test 8.2 GHz - 10 GHz acc. to FCC Part 15 (EMCO 3160)

Model: WaveNET Router Node	Comment: - DC 6 V power supply
Serial no.: ---	- TX with modulation
Applicant: SimonsVoss Technologies AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Vertical Polarization	
Date of test: 09/26/2006	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak	List of values: 10 dB Margin	50 Subranges
-------------------	---------------------------------	--------------




Result: Prescan

Project file: 51971-60823-2

Radiated Emission Test 30 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model: WaveNET Router Node	Comment: - DC 6 V power supply
Serial no.: ---	- RX
Applicant: SimonsVoss Technologies AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 09/26/2006	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak	List of values: 10 dB Margin	50 Subranges
-------------------	---------------------------------	--------------



Result: Prescan

Project file: 51971-60823-2


Radiated Emission Test 30 MHz - 1 GHz acc. to FCC Part 15 (Fully Anechoic Chamber)

Model: WaveNET Router Node	
Serial no.: ---	
Applicant: SimonsVoss Technologies AG	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 09/26/2006	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - DC 6 V power supply - RX

Detector: Peak

List of values: Selected by hand



Result: Prescan

Project file: 51971-60823-2


Radiated Emission Test 1 GHz - 3.95 GHz acc. to FCC Part 15 (EMCO 3115)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Horizontal Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
automatically	default.emi

Comment:	
- DC 6 V power supply	
- RX	

Detector:	
Peak	

List of values:	
Selected by hand	



Result:	
Prescan	

Project file:	
51971-60823-2	


Radiated Emission Test 1 GHz - 3.95 GHz acc. to FCC Part 15 (EMCO 3115)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Vertical Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
automatically	default.emi

Comment:
- DC 6 V power supply
- RX

Detector:	Peak
-----------	------

List of values:
Selected by hand



Result:
Limit kept

Project file:
51971-60823-2


Radiated Emission Test 3.95 GHz - 5 GHz acc. to FCC Part 15 (EMCO 3160)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Horizontal Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
automatically	default.emi

Comment:	
- DC 6 V power supply	
- RX	

Detector:	
Peak	

List of values:	
10 dB Margin	50 Subranges



Result:	
Prescan	

Project file:	
51971-60823-2	


Radiated Emission Test 3.95 GHz - 5 GHz acc. to FCC Part 15 (EMCO 3160)

Model:	WaveNET Router Node
Serial no.:	---
Applicant:	SimonsVoss Technologies AG
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Vertical Polarization
Date of test:	Operator:
09/26/2006	M. Steindl
Test performed:	File name:
automatically	default.emi

Comment:	
- DC 6 V power supply	
- RX	

Detector:	Peak
-----------	------

List of values:	
10 dB Margin	50 Subranges



Result:	
Limit kept	

Project file:	
51971-60823-2	