

Prüfbericht - Nr.: 14014822 001
Test Report No.:

Seite 1 von 9
Page 1 of 9

Auftraggeber: Inova Products Inc.
Client:
1851 Vista Del Sur
Gilroy
California
U.S.A.

Gegenstand der Prüfung: 315MHz Receiver
Test Item:

Bezeichnung: Series A
Identification:

Serien-Nr.: Engineering sample
Serial No.:

Wareneingangs-Nr.: 061213020-1
Receipt No.:

Eingangsdatum: 13.12.2006
Date of Receipt:

Prüfort: TÜV Rheinland Hong Kong Ltd.
Testing Location:
9th Floor, Oriental News Building, 7 Wang Tai Road, Kowloon Bay, Kowloon,
Hong Kong
Hong Kong Productivity Council
HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

Prüfgrundlage: FCC Part 15, Subpart B
Test Specification:
ANSI C63.4-2003
CISPR 22:1997

Prüfergebnis: Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n).
Test Result:
The test item passed the test specification(s).

Prüflaboratorium: TÜV Rheinland Hong Kong Ltd.
Testing Laboratory:
9th Floor, Oriental News Building, 7 Wang Tai Road, Kowloon Bay, Kowloon,
Hong Kong

geprüft / tested by:

05.01.2007 Hugo Wan
Datum Name/Stellung
Date Name/Position


Unterschrift
Signature

08.01.2007 Thomas Berns
Datum Name/Stellung
Date Name/Position


Unterschrift
Signature

Sonstiges / Other Aspects:

FCCID: UV2ACTIVENT-VU

Abkürzungen: P(ass) = entspricht Prüfgrundlage
F(all) = entspricht nicht Prüfgrundlage
N/A = nicht anwendbar
N/T = nicht getestet

Abbreviations: P(ass) = passed
F(all) = failed
N/A = not applicable
N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Test Summary

Spurious Radiated Emissions

Result: Pass

Contents

List of Test and Measurement Instruments.....	4
General Product Information	5
Product Function and Intended Use.....	5
Ratings and System Details	5
Independent Operation Modes.....	6
Submitted Documents	6
Related Submittal(s) Grants	6
Test Set-up and Operation Mode.....	7
Principle of Configuration Selection	7
Test Operation and Test Software.....	7
Special Accessories and Auxiliary Equipment	7
Countermeasures to achieve EMC Compliance.....	7
Test Methodology	8
Radiated Emission	8
Field Strength Calculation	8
Test Results	9
Spurious Radiated Emissions Section 15.109	9
Appendix 1: Test Setup	
Appendix 2: EUT External Photo	
Appendix 3: EUT Internal Photo	
Appendix 4: FCCID Label, Block Diagram, Schematics and User manual.	

List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

Kind of Equipment	Manufacturer	Type	S/N
Test Receiver	Rohde & Schwarz	ESVS30	842807/009
Active Loop Antenna	EMCO	6502	9107-2651
Biconical Antenna	Rohde & Schwarz	HK116	841489/015
Log.-Periodic Antenna	Rohde & Schwarz	HL223	841516/017
Double Ridge Horn Antenna	EMCO	3115	9002-3347
Signal Generator	Rohde & Schwarz	SMY 01	844146/024

General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a receiver of a remote control louver system operating at 315MHz. The EUT turns the louver close and open according to the command of the associate transmitter.

FCCID: UV2ACTIVENT-VU

Model	Product description
Series A	Activent

Ratings and System Details

	Receiver
Frequency range	315MHz
Number of channels	5 dip switches (using same frequency with different identification scheme depends on dip switch pattern)
Type of antenna	Integral antenna
Power supply	DC 6.0V, 4 x AA size batteries
Ports	none
Protection Class	III

Independent Operation Modes

The basic operation modes are:

- Power on when batteries are inserted.
- Louver movement: turn clockwise or anti-clockwise to open and close the louver.

For further information refer to User Manual

Submitted Documents

The submitted documents are listed as follow:

- User manual
- Label artwork

Related Submittal(s) Grants

This is a single application for certification of the Receiver.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the Circuit Diagram or the Technical Construction File. No additional measures were employed to achieve compliance.

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in section 7.1.1 and 7.1.2 of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Test Results

Spurious Radiated Emissions

Section 15.109

RESULT: Pass

Test Specification : FCC Part 15 Section 15.109
 Test Method : ANSI 63.4-2003
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Quasi Peak
 Measurement BW : 120 kHz
 Supply Voltage : DC 6.0V
 Measuring Frequency Range : 30-2000MHz
 Mode of operation : Standby

Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Delta to Limit (dB)
31.400	9.60	43.52	-33.92

Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Delta to Limit (dB)
315.26	14.1	46.02	-31.92

Remark: There is no spurious emission found between lowest oscillating frequency to 30 MHz.

Limit

Section 15.109

The field strength of radiated emissions from unintentional radiators at a distance of 3 meters:

Frequency (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
30-88	100	$20 \log(100) = 40.00$	3
88-216	150	$20 \log(150) = 43.52$	3
216-960	200	$20 \log(200) = 46.02$	3
Above 960	500	$20 \log(500) = 53.98$	3