



CE MARKING

ELECTROMAGNETIC COMPATIBILITY
ELECTRICAL SAFETY
LASER SPECTROSCOPY
ENVIRONMENTAL PHYSICS

G.S.D. S.r.l.
Certified in accordance with
UNI EN ISO 9001:2008
by
TÜV Rheinland Italia S.r.l.
Certificate N. 39 00 1850509

G.S.D. Srl PISA - Italy	Test Report n. FCC-17238	Rev. 01
Manufacturer	CAEN RFID S.r.l.	
Address	Via Vetraia, 11 55049 Viareggio (LU) Italy	
Test Family Name	R1170IU	
Testing Laboratory Name	G.S.D. S.r.l.	
Address	Via Marmiceto, 8 56121 Pisa (PI) Italy	
Tel/Fax	+39 050 984254 / +39 050 984262	
P.IVA/VAT	01343950505	
http – e-mail	www.gsd.it - info@gsd.it	
	FCC Listed: Registration Number: 424037	
Location and Date of Issue	Pisa, 2017 May 17	

G.S.D. s.r.l.
Via Marmiceto, 8
56121 OSPEALETTO - PISA
Tel. 050.984254 - Fax 050.984262
P. IVA 01343950505

SENIOR EMC TEST MANAGER
Dr. Gian Luca Genovesi

QUALITY MANAGER
Dr. David Reliccia

INDEX	
1. MANUFACTURER AND EUT IDENTIFICATION	3
2. REFERENCE STANDARDS.....	5
3. RESULT, CONDITION, MEASUREMENT UNCERTAINTY.....	6
4. RADIATED EMISSIONS.....	8
5. POWER LINES CONDUCTED EMISSIONS.....	21
6. OPERATION WITHIN THE BAND 902 - 928 MHZ.....	26
6.1. NUMBER OF HOPPING FREQUENCIES	26
6.2. CARRIER FREQUENCY SEPARATION.....	27
6.3. PEAK OUTPUT POWER (RADIATED).....	31
6.4. SPURIOUS EMISSIONS.....	33
6.5. BAND EDGE.....	34
7. BANDWIDTH AND AVERAGE TIME OF OCCUPANCY.....	38
8. PHOTO.....	50

1. MANUFACTURER AND EUT IDENTIFICATION¹

Manufacturer	CAEN RFID S.r.l..
Address	Via Vetraia, 11 55049 Viareggio (LU) Italy
Test Family Name	R1170IU
Date of reception	2017 April 11
Sampling	Laboratory sample for certification
Test Item Description	RFID Device
Nominal Input Voltage	5 Vdc (USB)
FCC ID	UVECAENRFID026

¹A detailed documentation is preserved in the internal fascicle.

This document may be only fully reproduced.

*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 3 / 54*



*Fig. 1.1
Equipment Photo*

2. REFERENCE STANDARDS	
Tests and measurements are performed accordingly to the reference standards given in the table below:	
<i>TEST</i>	<i>STANDARD</i>
Emissions: Conducted and Radiated – Section 15.207 and 15.209	FCC Rules ad Regulations, Title 47 Part 15 – Sub part B ANSI C63.4 2014 – American National Standard for Methods of Measuring of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
Operation within the band 902-928 MHz: Alternative Test Procedures 15.247 (b) and (c) , and (a) Bandwidth and average time of occupancy, Band Edge 15.247 (d)	FCC Rules ad Regulations, Title 47 Part 15 – Sub part C DA 00-705 (30 March 2000) – Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems ANSI C63.4 2014 – American National Standard for Methods of Measuring of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
Maximum Permissible Exposure	OET Bulletin 65 Evaluating Compliance with FCC Guidelines for Human Exposure to Radio-Frequency Electromagnetic Fields FCC Rules ad Regulations, Title 47 Part 15 – Sub part B DA 00-705 (30 March 2010) – Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems

3. RESULT, CONDITION, MEASUREMENT UNCERTAINTY

Summary of Test Results

TEST	RESULT
<i>Emissions: conducted</i> <i>Section 15.207</i>	<i>Pass</i>
<i>Emissions: radiated</i> <i>Section 15.209</i>	<i>Pass</i>
<i>Bandwidth and Average Time of Occupancy</i> <i>Section 15.247 (a)</i>	<i>Pass</i>
<i>Operation within the band 902-928 MHz:</i> <i>Section 15.247 (b) and (c)</i>	<i>Pass</i>
<i>Band Edge</i> <i>Section 15.247 (d)</i>	<i>Pass</i>

Measurement uncertainty

TEST	EXPANDED UNCERTAINTY
Conducted Emission – $50\Omega/50\mu\text{H}$ (150 kHz - 30 MHz)	± 3.5 dB
Radiated Emission – (Semianechoic Room) (30 MHz - 18 GHz)	± 4.7 dB

Climatic Conditions


PARAMETER	VALUE
Temperature	(293 ± 3) K
Relative humidity	(50 ± 5) %

Extensions

The results refer only to the sampled EUT and under the specified conditions.

Modulations:

PR ASK 40 kHz



Conducted and Radiated EUT Test Set-up example (ANSI C63.4 2014)

*This document may be only fully reproduced.
Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 7 / 54*

4. RADIATED EMISSIONS

In the following table you can find the limits established by the reference standard:

FREQUENCY RANGE (MHz)	Field Strength QUASI-PEAK LIMITS [dB (μ V/m)]
30 – 88	40
88 – 216	43.5
216 – 960	46
Above 960	54

Test Equipment

EQUIPMENT	MANUFACTURER	MODEL	CAL. DUE
MXE EMI Receiver	Agilent	N9038A	01/2018
Anechoic Chamber	Comtest	CSA01	01/2018
Bilog Antenna	Schaffner	CBL6112B	01/2018
Horn Antenna	EMCO	3115	01/2018
Horn Antenna	Alpha Industries	61932500	01/2018
Loop Antenna	ETS Lindgren	6215	01/2018
Controller	Deisel	HD100	01/2018
Turn Table	Deisel	MA240	01/2018
LISN	GSD	NTW06	01/2018

Test procedure: RE22R02

Notes

Azimuth position EUT-Antenna corresponding to 0° identifies the rotating table orientation (TT) in which the instrument to be tested shows the front part turned towards the antenna. Positive grades individuate clockwise rotations of TT when this one is observed from the top. For negative degrees, TT rotation is anticlockwise.

Antenna height respect to the mass plane is conventionally individuated with: MA=XXX where XXX indicates the height (always positive for d > 100) expressed in cm.

Antenna horizontal polarisation is indicated by POL=H.

Antenna vertical polarisation is indicated by POL=V.

EUT was tested in the three orthogonal planes.

Results and conclusions

In all the operative conditions, equipment complied with the standard limits. Graphics in following figures show the most significant registrations of the performed measurements.

This document may be only fully reproduced.


Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.


Report n. FCC-17238 Rev. 01, page 8 / 54



This document may be only fully reproduced.


*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 9 / 54*








This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 11 / 54












This document may be only fully reproduced.

*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
 Report n. FCC-17238 Rev. 01, page 15 / 54*









This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 18 / 54



This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 19 / 54



5. POWER LINES CONDUCTED EMISSIONS

Equipment shall meet the limits below when using a CISPR16 quasi-peak and average detector receivers.

FCC 15.207

FREQUENCY RANGE (MHz)	QUASI-PEAK LIMIT [dB (μV)]	AVERAGE LIMIT [dB (μV)]
0.15 – 0.50	66 – 56 ^(*)	56 – 46 ^(*)
0.50 – 5	56	46
5 – 30	60	50

^(*) Limit decreasing linearly with logarithm of frequency

Test Equipment

EQUIPMENT	MANUFACTURER	MODEL	CAL. DUE
MXE EMI Receiver	Agilent	N9038A	01/2018
Screened Room	GSD	CSC01	01/2018
LISN	GSD	GSDA01	01/2018
LISN	COMTEST	---	01/2018

Test procedure: CE22R01

The EUT power cable was connected to a LISN and the monitored output of the LISN was connected to a spectrum analyzer by a transient limiter. The conducted emissions from 150 kHz to 30 MHz were monitored and compared to the specification limits

Test method

Test method was in accordance with the reference standard.

EUT modes of operations were tested in order to achieve the maximum level of emission.


Results

Equipment complied with the test specification limits.

Graphics in following figures show some registrations of the frequency spectrum of the conducted emissions.

This document may be only fully reproduced.

*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 21 / 54*










6. OPERATION WITHIN THE BAND 902 - 928 MHz

6.1. NUMBER OF HOPPING FREQUENCIES

The frequency hopping systems operating in the 902-928 MHz band.



The number of hopping frequencies is 50.

6.2. CARRIER FREQUENCY SEPARATION


The frequency hopping systems operating in the 902-928 MHz band.


The measured values are:

Channel	Carrier Separation (kHz)
0	500.79
25	500.18
49	496.64

This document may be only fully reproduced.


*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 27 / 54*





This document may be only fully reproduced.

Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 29 / 54



6.3. PEAK OUTPUT POWER (RADIATED)

Equipment shall meet the limits below.

FREQUENCY RANGE (MHz)	RF POWER OUTPUT LIMIT (dBm)
902 - 928	36.0

The measured values are:

Channel	Output Power	
	(dB μ V/m)	(dBm erp)
0	111.36	16.1
25	113.15	17.9
49	112.07	16.8

The power was calculated according to the formula:

$$P_{erp} = \frac{(E \cdot d)^2}{30}$$

which comes from the document “DA 00-705 (30 March 2010) – Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems”

This document may be only fully reproduced.

*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 31 / 54*




Fig. 6.5
Pol H, Max Hold

6.4. SPURIOUS EMISSIONS

In the following table, are shown the absolute maximum values (measured without making reference to the polarization of acquisition).

Nr Harmonics	AV Level (dB μ V/m)						AV Limits (dB μ V/m)	Remark		
	Ch 0		Ch 25		Ch 49					
	F (MHz)	(dB μ V/m)	F (MHz)	(dB μ V/m)	F (MHz)	(dB μ V/m)				
2	1805.5	43.58	1830.5	40.35	1854.5	37.87	54.0			
3	2708.25	47.87	2745.75	43.78	2781.75	35.66	54.0			
4	3611	--	3661	--	3709	--	54.0			
5	4513.75	--	4576.25	43.09	1636.25	--	54.0			
6	5416.55	48.91	5491.5	47.38	5563.5	39.69	54.0			
7	--	--	--	--	--	--	54.0			
8		--		--		--	54.0			
9		--		--		--	54.0			
10		--		--		--	54.0			

Note: Levels below 20 dB of limits are indicated with (--).

Nr Harmonics	Peak Level (dB μ V/m)						Peak Limits (dB μ V/m)	Remark		
	Ch 0		Ch 25		Ch 49					
	F (MHz)	(dB μ V/m)	F (MHz)	(dB μ V/m)	F (MHz)	(dB μ V/m)				
2	1805.5	47.91	1830.5	45.69	1854.5	43.32	74.0			
3	2708.25	51.65	2745.75	48.95	2781.75	45.28	74.0			
4	3611	--	3661	--	3709	--	74.0			
5	4513.75	--	4576.25	49.65	1636.25	--	74.0			
6	5416.55		5491.5	53.09	5563.5	49.59	74.0			
7		--		--		--	74.0			
8		--		--		--	74.0			
9		--		--		--	74.0			
10		--		--		--	74.0			

Note: Levels below 20 dB of limits are indicated with (--).

This document may be only fully reproduced.

*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 33 / 54*

6.5. BAND EDGE
Emissions must be within the band 902-928 MHz.
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

This document may be only fully reproduced.

*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 34 / 54*




Fig. 6.6
Pol. H




Fig. 6.7

Pol. V

<u>Test Equipment</u>			
EQUIPMENT	MANUFACTURER	MODEL	CAL. DUE
MXE EMI Receiver	Agilent	N9038A	01/2018
Anechoic Chamber	Comtest	CSA01	01/2018
Bilog Antenna	Schaffner	CBL6112B	01/2018
Horn Antenna	EMCO	3115	01/2018
Controller	Deisel	HD100	01/2018
Turn Table	Deisel	MA240	01/2018
Attenuator	Narda	768-10	01/2018

<u>Test procedure:</u> CE22R01

This document may be only fully reproduced.

*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 37 / 54*

7. BANDWIDTH AND AVERAGE TIME OF OCCUPANCY


Equipment shall meet the limits below.

Systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period.

Bandwidth

Channel	Frequency [MHz]	Bandwidth [kHz]
0	902.74975	55.6
25	915.24950	58.4
49	927.25000	62.7










This document may be only fully reproduced.


Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 41 / 54

<i>Average Time of Occupancy:</i>			
Channel	Dwell Time (ms)	Nr. of Transmission for channel [average]	Time of Occupancy (ms) [average]
0	33.06	4 [4.26]	132.2 [141.0]
25	33.99	4 [4.27]	136.0 [145.2]
49	33.06	4 [4.27]	132.2 [141.3]











*This document may be only fully reproduced.
Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 46 / 54*





<u>Test Equipment</u>			
EQUIPMENT	MANUFACTURER	MODEL	CAL. DUE
PSA Spectrum Analyzer	Agilent	E4440	01/2018
RF Preselector	Agilent	N9039A	01/2018
Anechoic Chamber	Comtest	CSA01	01/2018
Bilog Antenna	Schaffner	CBL6112B	01/2018
Horn Antenna	EMCO	3115	01/2018
Controller	Deisel	HD100	01/2018
Turn Table	Deisel	MA240	01/2018

<u>Test procedure:</u> RE22R01


This document may be only fully reproduced.

*Every partial reproduction is only allowed after written approval released by G.S.D. S.r.l.
Report n. FCC-17238 Rev. 01, page 49 / 54*

8. PHOTO



*Fig. 8.1
Conducted Emissions Test Set-up*






*Fig. 8.3
Radiated Emissions Test Set-up*



*Fig. 8.4
Radiated Emissions Test Set-up*



*Fig. 8.5 - Particular
Radiated Emissions Test Set-up*