

Choose certainty.
Add value.

Report On

RF Exposure Assessment of the Bridge Systems BV BMS2-1 Wireless Base Station and BM2-1 Wireless Hand Held for Bridgemate Scoring System

FCC IDs: UVIBM21A and UVIBMS21A

Document 75921258 Report 04 Issue 2

July 2013



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North, Fareham, Hampshire, United Kingdom, PO15 5RL Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

REPORT ON RF Exposure Assessment of the

Bridge Systems BV

BMS2-1 Wireless Base Station and BM2-1 Wireless Hand Held for

Bridgemate Scoring System

Document 75921258 Report 04 Issue 2

July 2013

PREPARED FOR Bridge Systems BV

Van Vollenhovenstraat 56B

3016 BK Rotterdam The Netherlands

PREPARED BY

M Whiting
Project Manager

APPROVED BY

R H**ěnley**

Authorised Signatory

DATED 03 July 2013

This test report has been up issued to Issue 2 to include the FCC ID's of the units and also correct the FCC Specification Reference Dates.



CONTENTS

Section		Page No
1	REPORT SUMMARY	3
1.1 1.2 1.3 1.4	Introduction	5
2	TEST DETAILS	8
2.1 2.2 2.3 2.4	Rationale for Assessment of the RF Exposure Defined Limits Establishing Wavelength and 1/4 Wavelength Far Field Calculations	10 10
3	DISCLAIMERS AND COPYRIGHT	12
3.1	Disclaimers and Copyright	13



SECTION 1

REPORT SUMMARY

RF Exposure Assessment of the
Bridge Systems BV
BMS2-1 Wireless Base Station and BM2-1 Wireless Hand Held
for Bridgemate Scoring System



1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the Bridge Systems BV BMS2-1 Wireless Base Station and BM2-1 Wireless Hand Held for Bridgemate Scoring System to the requirements of the applied test specifications.

Objective To perform RF Exposure Assessment to determine the

Equipment Under Test's (EUT's) compliance of the applied

rules.

Applicant Bridge Systems BV

Manufacturer Bridge Systems BV

Manufacturing Description Wireless Base Station and Hand Held for Bridgemate

Scoring System

Model Number(s) BMS2-1 and BM2-1

Test Specification/Issue/Date EN 62311:2008

OET Bulletin 65 Edition 97-01 August 1997

RSS-102 Issue 4 March 2010

Radiocommunications (Electromagnetic Radiation –

Human Exposure) Standard: 2003

Related Document(s) Council Recommendation 1999/519/EC:1999

FCC CFR 47 Part 1: 2012 FCC CFR 47 Part 2: 2012 Health Canada's Safety Code 6

ARPANSA ICNIRP 1998

National Council on Radiation Protection and Measurements (NRPC) - Report No. 86(1986)

EN 50383:2002 IEEE Std C95.1-2005

Australian Standard 2772.2 - 1988



1.2 BRIEF SUMMARY OF RESULTS

1.2.1 General Public Exposure Levels

Antenna Gain (Numeric)	Peak Output Power (mW)	Field	Calculated RF Exposure at 0.2 m (20cm)	General Public Exposure Limit	Application
		S	0.00 W/m ²	4.512 W/m ²	ICNIRP
		S	0.000 mW/cm ²	0.602 mW/cm ²	FCC 47 CFR § 1.1310
		S	0.00 W/m ²	6.015 W/m ²	Canada's RF Safety Code 6
		S	0.00 W/m ²	4.512 W/m ²	ARPANSA
		E	0.02 V/m	41.303 V/m	ICNIRP
1.585	5	Е	0.02 V/m	N/A V/m	FCC 47 CFR § 1.1310
1.505	3	Е	0.02 V/m	47.611 V/m	Canada's RF Safety Code 6
		E	0.02 V/m	41.152 V/m	ARPANSA
		Н	0.00 A/m	0.111 A/m	ICNIRP
		Н	0.00 A/m	N/A A/m	FCC 47 CFR § 1.1310
		Н	0.00 A/m	0.126 A/m	Canada's RF Safety Code 6
		Н	0.00 A/m	0.109 A/m	ARPANSA

The calculations have shown that they **meet** the General Public Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines, Health Canada's RF exposure guideline Safety Code 6 and the Australian ARPANSA limits at **20**cm, the point of investigation.



1.2.2 Occupational Exposure Levels

Antenna Gain (Numeric)	Peak Output Power (mW)	Field	Calculated RF Exposure at 0.2 m (20cm)	Occupational Exposure Limit	Application
	5	S	0.00 W/m ²	22.558 W/m ²	ICNIRP
		S	0.000 mW/cm ²	3.008 mW/cm ²	FCC 47 CFR § 1.1310
		S	0.00 W/m ²	30.077 W/m ²	Canada's RF Safety Code 6
		S	0.00 W/m ²	22.558 W/m ²	ARPANSA
		E	0.02 V/m	90.115 V/m	ICNIRP
1.585		E	0.02 V/m	N/A V/m	FCC 47 CFR § 1.1310
1.565		E	0.02 V/m	106.336 V/m	Canada's RF Safety Code 6
		E	0.02 V/m	92.218 V/m	ARPANSA
		Н	0.00 A/m	0.240 A/m	ICNIRP
		Н	0.00 A/m	N/A A/m	FCC 47 CFR § 1.1310
		Н	0.00 A/m	0.282 A/m	Canada's RF Safety Code 6
		Н	0.00 A/m	0.245 A/m	ARPANSA

The calculations have shown that they **meet** the Occupational Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines, Health Canada's RF exposure guideline Safety Code 6 and the Australian ARPANSA limits at **20 cm**, the point of investigation.



1.3 PRODUCT INFORMATION

1.3.1 Attestation

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields (10 MHz - 300 MHz) - General public. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s).

1.3.2 Technical Description

The Equipment under test was a Bridge Systems BV BMS2-1 Wireless Base Station and BM2-1 Wireless Hand Held for Bridgemate Scoring System. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the BMS2-1 Wireless Base Station and BM2-1 Wireless Hand Held for Bridgemate Scoring System to demonstrate compliance with the applied test specification(s) the sample assessed was found to comply with the requirements of the applied rules.

1.4 SUMMARY

The RF exposure assessment is based upon the following criteria:

The BMS2-1 Wireless Base Station and BM2-1 Wireless Hand Held for Bridgemate Scoring System both operate in the frequency range of 902.3 – 927.7 MHz, having the same antenna length, gain, power and duty cycle.

Gain	2 dBi
Power	0.005 W
Distance	0.2 m (20 cm)
Duty Cycle	1%



SECTION 2

TEST DETAILS



2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields. The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in EN50383:2002 Clause 5.2; E-field or H-field calculation. The method of calculation used is defined in EN50383:2002; Clause 8.2.2, 8.2.3 and 8.2.4. The calculated values have been compared with limits provided in the ICNIRP guidelines. Calculations can be made in three separate regions, based on distance from the antenna. These are called:

- far-field region,
- radiating near-field region,
- reactive near-field region.

The theory that defines these regions is given in EN50383:2002 Annex A.

Far-field region

As shown in EN50383 Annex A, the far-field calculations are accurate when the distance, r, from an antenna of length D to a point of investigation is greater than

$$r = \frac{2D^2}{\lambda}$$

Where, r is the distance from the antenna to the point of investigation.

Radiating near-field region

The radiating near-field region of an antenna of length D as shown in EN50383 Annex A, this region is defined by

$$\frac{\lambda}{4} < r > \frac{2D^2}{\lambda}$$

Reactive near-field region

The reactive near-field region of an antenna as shown in EN50383 Annex A, this region is defined by

$$r \leq \frac{\lambda}{4}$$

Where, r is the distance from the antenna to the point of investigation.

Recommend $\lambda/4$ as the boundary between the radiated near-field and reactive near-field for RF exposure compliance assessment.



2.2 DEFINED LIMITS

Normative Reference: ICNIRP Advice on Limiting Exposure to Electromagnetic Fields (0-300GHz). Table A4, Reference Levels for General Public Exposure to Time Varying Electric & Magnetic Fields. Vol 15 No.2. 2004. The defined limits are in accordance with 47 CFR § 1.1310 Radiofrequency radiation exposure limits.

Reference levels for general public exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 902.3 MHz Power density (W/m²) = 4.512 **ICNIRP** Power density (mW/cm^2) = 0.602 FCC 47 CFR § 1.1310 = 6.015 Canada's RF Safety Code 6 Power density (W/m²) Power density (W/m²) = 4.512 Australian Radiation Protection Series Publication No. 3 E-Field (Vm-1) = 41.303 ICNIRP E-Field (Vm-1) = N/A FCC 47 CFR § 1.1310 E-Field (Vm-1) = 47.611 Canada's RF Safety Code 6 E-Field (Vm-1) = 41.152 Australian Radiation Protection Series Publication No. 3 H-Field (Am-1) = 0.111 ICNIRP FCC 47 CFR § 1.1310 H-Field (Am-1) = N/A = 0.126 Canada's RF Safety Code 6 H-Field (Am-1) = 0.109 Australian Radiation Protection Series Publication No. 3 H-Field (Am-1)

Reference levels for occupational exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 902.3 MHz Power density (W/m²) = 22.558 ICNIRP Power density $(mW/cm^2) = 3.008$ FCC 47 CFR § 1.1310 Power density (W/m²) = 30.077 Canada's RF Safety Code 6 Power density (W/m²) = 22.558 Australian Radiation Protection Series Publication No. 3 = 90.115 ICNIRP E-Field (Vm-1) FCC 47 CFR § 1.1310 E-Field (Vm-1) = N/A E-Field (Vm-1) = 106.336 Canada's RF Safety Code 6 = 92.218 Australian Radiation Protection Series Publication No. 3 E-Field (Vm-1) H-Field (Am-1) = 0.240 ICNIRP H-Field (Am-1) = N/A FCC 47 CFR § 1.1310 H-Field (Am-1) = 0.282 Canada's RF Safety Code 6 = 0.245 Australian Radiation Protection Series Publication No. 3 H-Field (Am-1)

2.3 ESTABLISHING WAVELENGTH AND 1/4 WAVELENGTH

Frequency (MHz)	$\lambda = \frac{3 \times 10^8}{f}$		$\frac{\lambda}{4}$		
	m	cm	m	cm	
902.3	0.332483652887066	33.2483652887066	0.0831209132217666	8.31209132217666	
914.9	0.327904689037053	32.7904689037053	0.0819761722592633	8.19761722592633	
927.7	0.323380403147569	32.3380403147569	0.0808451007868923	8.08451007868923	



2.4 FAR FIELD CALCULATIONS

The following calculations are based on: 2 dBi gain antenna

P = 0.005 (Power (Watts)) or 5 (Power milliwatts)

G = 1.585 (Numeric Gain)

r = 20 (Distance (centimetres)) or 0.2(Distance (meters))

The power flux:

$$S = \frac{PG_{(\theta,\phi)}}{4\pi r^2}$$
 S = 0.00 W/m2

S= 0.000 mW/cm²

The electric field strength:

$$E = \frac{\sqrt{30PG}_{(\theta,\phi)}}{r}$$
 E = 0.02 V/m

The magnetic field strength:

$$H = \frac{E}{\eta_{\circ}}$$
 H = 0.00 A/m

The calculations meet the General Public Exposure Levels described in the ICNIRP Guidelines. The calculations meet the General Public Exposure Levels described in the FCC 47CFR§1.1310. The calculations meet the General Public Exposure Levels described in the Canada's RF Safety Code 6. The calculations meet the General Public Exposure Levels described in the Australian Radiation Protection Series Publication No. 3

The calculations meet the Occupational Exposure Levels described in the ICNIRP Guidelines. The calculations meet the Occupational Exposure Levels described in the FCC 47CFR§1.1310 The calculations meet the Occupational Exposure Levels described in the Canada's RF Safety Code 6 The calculations meet the Occupational Exposure Levels described in the Australian Radiation Protection Series Publication No. 3



SECTION 3

DISCLAIMERS AND COPYRIGHT



3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of TÜV SÜD Product Service

© 2013 TÜV SÜD Product Service