Application No.: <u>HM157842</u>

Date: <u>2006-12-27</u>

FCC ID: <u>UVY06102</u>

## **Circuit Description**

The <u>2410.4MHz -2451.6 (16.0MHz crystal)</u> oscillator drives the base of <u>IC</u> the final/buffer amplifier. The modulation provided by <u>IC</u>. The output of <u>IC</u> has the matching network consisting of <u>L1, L2, L3</u> and <u>C3, C4, C5 C6</u> that limit the harmonic content and effect the proper coupling of the antenna to the output stage.

Antenna, Ground and Power Source

No external antenna. There is no external ground connection. The ground is only that of the printed circuit board. Electric current is supplied by a  $\frac{3 \text{ Volt ("AAA" size battery x 2)}}{4 \text{ primary battery.}}$ 

## **Operation Descriptions**

The transmitter is a <u>Student remote</u> operating at <u>2410.4MHz-2451.6</u>MHz band. The transmitter is powered by a <u>3V</u> battery (<u>AAA x 2</u>) and the transmitting frequency is crystal controlled. The operation is achieved by different combinations of form pulse modulating signal on the 2410.4MHz-2451.6MHz (16MHz crystal) carrier frequency.

## Remarks:

The transmitter is a 19 **Button** transmitter.

The EUT continues to transmit while **Button** is being pressed.

It is **Pulse** transmitter, Modulation by **IC**; and type is **Pulse** modulation.