



STC Test Report

Date : 2007-02-06

Page 1 of 39

No. : HM157981

Applicant:

GP Electronics (HK) Ltd.
Gold Peak Building, 6/F., 30 Kwai Wing Road,
Kwai Chung, N.T., Hong Kong.

Description of Samples:

Model name: KEF Wireless 5000 series
Brand name: KEF
Model no.: KEF Wireless 5000 series
FCC ID: UXD07001

Date Samples Received: 2006-12-30

Date Tested: 2007-01-05 to 2007-02-06

Investigation Requested: FCC Part 15 Regulations-Subpart C

Conclusions:

The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Remarks:

LEE Kam Chuen, EMD

For and on behalf of

The Hong Kong Standards and Testing Centre Ltd.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Tai Po Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from the Hong Kong Standards and Testing Centre Ltd.

For full text of "Conditions of Issuance of Test Report", please refer to overleaf or refer to the website of Homepage.



STC Test Report

Date : 2007-02-06

Page 2 of 39

No. : HM157981

CONTENT:

	Cover Content	Page 1 of 39 Page 2-3 of 39
<u>1.0</u>	<u>General Details</u>	
1.1	Test Laboratory	Page 4 of 39
1.2	Applicant Details Applicant HKSTC Code Number for Applicant Manufacturer	Page 4 of 39
1.3	Equipment Under Test [EUT] Description of EUT operation	Page 5 of 39
1.4	Date of Order	Page 5 of 39
1.5	Submitted Sample	Page 5 of 39
1.6	Test Duration	Page 5 of 39
1.7	Country of Origin	Page 5 of 39
<u>2.0</u>	<u>Technical Details</u>	
2.1	Investigations Requested	Page 6 of 39
2.2	Test Standards and Results Summary	Page 6 of 39
<u>3.0</u>	<u>Test Results</u>	
3.1 – 3.8	Radiated Emission	Page 7-32 of 39
3.9	Conducted Emission	Page 33-35 of 39

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 3 of 39

No. : HM157981

Appendix A

List of Measurement Equipment

Page 36 of 39

Appendix B

Photographs

Page 37-39 of 39

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 4 of 39

No. : HM157981

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd.
EMC Laboratory
10 Dai Wang Street, Taipo Industrial Estate
New Territories, Hong Kong

1.2 Applicant Details

Applicant

GP Electronics (HK) Ltd.
Gold Peak Building, 6/F., 30 Kwai Wing Road,
Kwai Chung, N.T., Hong Kong.

Manufacturer

GP Electronics (Huizhou) Co. Ltd.
No.9, Le Jin West Road,
Zhong Kai Hi-Tech Industrial Development Zone,
Huizhou, Guangdong, PRC

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 5 of 39

No. : HM157981

1.3 Equipment Under Test [EUT]

Description of Sample

Model Name: KEF Wireless 5000 series
Manufacturer: GP Electronics (Huizhou) Co. Ltd.
Brand Name: KEF
Model Number: KEF Wireless 5000 series
Rating: The AC/DC Adaptor used for the tests was provided by the applicant with the following details: Model Number: SA1460-220270, Input: 110-240Vd.c. 1.5A 50/60Hz, Output: 22Vd.c. 2.7A

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is a GP Electronics (HK) Ltd., KEF Wireless 5000 series, the transmission signal is frequency hopping with channel frequency 2.403-2.479GHz.

The system is based on one-way wireless digital audio transfer from an audio source to an audio recipient. The application consists of an Atx(audio source) and an Arx(audio receiver). Atx unit connects to an audio source like e.g. a CD player or MP3 player. Arx unit is used for connection to speakers.

1.4 Date of Order

2006-12-30

1.5 Submitted Sample(s):

1 Sample

1.6 Test Duration

2007-01-05 to 2007-01-22

1.7 Country of Origin

China

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 6 of 39

No. : HM157981

2.0 Technical Details

2.1 Investigations Requested

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2006 Regulations and ANSI C63.4:2003 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION Results Summary						
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result		
				Pass	Fail	N/A
Maximum Peak Conducted Output Power	FCC 47CFR 15.247	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Spurious RF Conducted Emissions	FCC 47CFR 15.247 (d)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated Emissions	FCC 47CFR 15.209	ANSI C63.4:2003	Class B	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Frequency Range	FCC 47CFR 15.3(m)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Hopping Channel Separation	FCC 47CFR 15.247(a)(1)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Number of Hopping Channel	FCC 47 CFR 15.247(a)(iii)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Pseudorandom Hopping Algorithm	FCC 47CFR 15.247(a)(1)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Time of Occupancy	FCC 47CFR 15.247(a)(1)(iii)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
RF Exposure	FCC 47CFR 15.247 (b)(5)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Antenna requirement	FCC 47 CFR 15.203	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Receiver Input Bandwidth	FCC 47CFR 15.247 (a)(1)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Receiver Hopping Capability	FCC 47CFR 15.247 (a)(1)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2003	Class B	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Note: N/A - Not Applicable

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 7 of 39

No. : HM157981

3.0 Test Results

3.1 Emission

3.1.1 Maximum Peak Conducted Output Power

Test Requirement: FCC 47CFR 15.247(b)(1)

Test Date: 2007-01-08


Mode of Operation: Tx mode

Test Method:

The transmitter output was connected to the spectrum / receiver through an attenuator. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 1MHz RBW and 1MHz VBW. Use Peak Search to read the peak power after Maximum Hold function is activated.

*:

Test Setup:



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 8 of 39

No. : HM157981

Limits for Peak Output Power of Fundamental Emissions [FCC 47CFR 15.247]:

The maximum peak output power shall not exceed the following limits:

For frequency hopping systems operating in the 2400-2483.5 MHz Band: 125mW (20.97dBm)

Results of transmission Mode (2.403.4GHz to 2.479.2GHz) : Pass (TX Unit)

Maximum Peak Conducted Output Power

Channel	Frequency (MHz)	Conducted Power (dBm)
0	2403.4	9.03
19	2442.2	10.00
37	2479.2	9.54

Results of transmission Mode (2.403.4GHz to 2.479.2GHz) : Pass (TX Unit)

Maximum EIRP

Channel	Frequency (MHz)	Transmitter Power (dBm)
0	2403.4	10.79
19	2442.2	12.30
37	2479.2	10.00

Calculated measurement uncertainty : 30MHz to 1GHz $\pm 5.2\text{dB}$
1GHz to 18GHz $\pm 4.4\text{dB}$

Antenna Gain dBi = Maximum EIRP (dBm) – Maximum Peak Conducted Output Power (dBm)

Transmission Frequency (MHz)	2403.4	2442.2	2479.2
Antenna Gain (dBi)	1.76	2.30	0.46

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 9 of 39

No. : HM157981

3.1.2 Spurious RF Conducted Emissions


Test Requirement: FCC 47CFR 15.247(d)
Test Date: 2007-01-08
Mode of Operation: Tx mode

Test Method:

The transmitter output was connected to the spectrum / receiver through an attenuator. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 1MHz RBW and 1MHz VBW. Use Peak Search to read the peak power after Maximum Hold function is activated.

*:

Test Setup:



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 10 of 39

No. : HM157981

Limits for Spurious RF Conducted Emissions [FCC 47CFR 15.247 (d)]:

The spurious RF conducted emissions shall meet the following limits:

At least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

Results of transmission Mode (2.403.4GHz to 2.479.2GHz) : Pass (TX Unit)

Tx frequency : Channel 0, 2403.4MHz

Spurious Frequency (MHz)	Power level (dBm)	Reference value (dBm)	Delta to reference level (dB)
No Emission Detected			

Tx frequency : Channel 19, 2442.2MHz

Spurious Frequency (MHz)	Power level (dBm)	Reference value (dBm)	Delta to reference level (dB)
No Emission Detected			

Tx frequency : Channel 37, 2479.2MHz

Spurious Frequency (MHz)	Power level (dBm)	Reference value (dBm)	Delta to reference level (dB)
No Emission Detected			

Calculated measurement uncertainty : 30MHz to 1GHz $\pm 5.2\text{dB}$
1GHz to 18GHz $\pm 4.4\text{dB}$

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 11 of 39

No. : HM157981

3.1.3 Radiated Emissions


Test Requirement: FCC 47CFR 15.247
Test Method: ANSI C63.4:2003
Test Date: 2007-01-08
Mode of Operation: Tx mode

Test Method:

The sample was placed 0.8m above the ground plane of semi-anechoic Chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. In the frequency range of 9kHz to 30MHz, The center of the loop antenna shall be 1 meter above the ground and rotated loop axis for maximum reading. The emissions worst-case are shown in Test Results of the following pages.

*: Semi-anechoic chamber located on the G/F of HKSTC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 607756.

Test Setup:



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 12 of 39

No. : HM157981

Limits for Field Strength of Harmonics Emissions [FCC 47CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [μ V/m]
30-88	100
88-216	150
216-960	200
Above960	500

Results of Transmit Mode (Channel 0, 2403.4MHz) : Pass

Field Strength of Harmonics Emissions Average Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
* 4806.8					500	Vertical
* 7210.2					500	Vertical
9613.6					500	Vertical
* 12017.0					500	Vertical
14420.4					500	Vertical
16823.8					500	Vertical
* 19227.2					500	Vertical
* 21630.6					500	Vertical
24034.0					500	Vertical

Remarks:

*: Denotes restricted band of operation.
Measurements were made using a peak detector. Any emission less than 1000 MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 and the limits of FCC Rules Part 15 Section 15.209 were applied.

Calculated measurement uncertainty : 30MHz to 1GHz $\pm 5.2\text{dB}$
1GHz to 18GHz $\pm 4.4\text{dB}$

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 13 of 39

No. : HM157981

Limits for Field Strength of Harmonics Emissions [FCC 47CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [μ V/m]
30-88	100
88-216	150
216-960	200
Above960	500

Results of Transmit Mode (Channel 19, 2442.2.4MHz) : Pass

Field Strength of Harmonics Emissions Average Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
* 4884.4					500	Vertical
* 7326.6					500	Vertical
9768.8					500	Vertical
* 12211.0					500	Vertical
14653.2					500	Vertical
17095.4					500	Vertical
* 19537.6					500	Vertical
* 21979.8					500	Vertical
24422.0					500	Vertical

Remarks:

*: Denotes restricted band of operation.
Measurements were made using a peak detector. Any emission less than 1000 MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 and the limits of FCC Rules Part 15 Section 15.209 were applied.

Calculated measurement uncertainty : 30MHz to 1GHz $\pm 5.2\text{dB}$
1GHz to 18GHz $\pm 4.4\text{dB}$

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 14 of 39

No. : HM157981

Limits for Field Strength of Harmonics Emissions [FCC 47CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [μ V/m]
30-88	100
88-216	150
216-960	200
Above960	500

Results of Transmit Mode (Channel 37, 2479.2MHz) : Pass

Field Strength of Harmonics Emissions Average Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
* 4958.4					500	Vertical
* 7437.6					500	Vertical
9916.8					500	Vertical
* 12396.0					500	Vertical
14875.2					500	Vertical
17354.4					500	Vertical
* 19833.6					500	Vertical
* 22312.8					500	Vertical
24792.0					500	Vertical

Remarks:

*: Denotes restricted band of operation.
Measurements were made using a peak detector. Any emission less than 1000 MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 and the limits of FCC Rules Part 15 Section 15.209 were applied.

Calculated measurement uncertainty : 30MHz to 1GHz $\pm 5.2\text{dB}$
1GHz to 18GHz $\pm 4.4\text{dB}$

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 15 of 39

No. : HM157981

Limits for Radiated Emissions other than Fundamental and Harmonics emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μ V/m]
0.009-0.490	240000/F(kHz)
0.490 - 1.705	240000/F(kHz)
1.705 - 30.0	300
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

Results of Transmit Mode: Pass

Radiated Emissions (below 30MHz) Quasi-Peak					
Emission Frequency MHz	E-Field Polarity	Level @3m dB μ V/m	Limit @3m dB μ V/m	Level @3m μ V/m	Limit @3m μ V/m
EMISSIONS DETECTED ARE MORE THAN 20dB BELOW THE FCC LIMITS					

Radiated Emissions (above 30MHz) Quasi-Peak					
Emission Frequency MHz	E-Field Polarity	Level @3m dB μ V/m	Limit @3m dB μ V/m	Level @3m @3m μ V/m	Limit @3m μ V/m
49.2	Vertical	38.9	40	64.6	100.0
393.2	Vertical	38.4	46	45.7	200.0
819.8	Vertical	30.7	46	96.6	200.0

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty	:	9kHz to 30 MHz	± 1.8 dB
		30MHz to 1GHz	± 5.2 dB
		1GHz to 18GHz	± 4.4 dB

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 16 of 39

No. : HM157981

3.2 Frequency Range Measurement

Test Requirement: FCC 47 CFR 15.247
Test Date: 2007-01-22
Mode of Operation: On mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06


Page 17 of 39

No. : HM157981


Limits for Frequency Range Measurement:

Frequency Range [MHz]	FCC Limits [MHz]
2403-2478	within 2400-2483.5

Lowest Operating Frequency



Highest Operating Frequency



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 18 of 39

No. : HM157981

3.3 Hopping Channel Separation Measurement

Test Requirement: FCC 47 CFR 15.247(a)(1)
Test Date: 2007-01-22
Mode of Operation: Tx mode

Test Method:

The transmitter output was connected to the spectrum / receiver through an attenuator. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 30kHz RBW and 100kHz VBW. Use Peak Search to read the peak power after Maximum Hold function is activated.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.

Limits:

Channel Separation Limits: >20dB bandwidth or 2/3 of 20dB bandwidth

Channel	Frequency (GHz)	Channel Separation (MHz)	20dB Bandwidth (MHz)
0	2.403328	2.048	1.803
19	2.442240	2.048	1.803
37	2.479104	2.048	1.792

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage




STC Test Report

Date : 2007-02-06

Page 19 of 39

No. : HM157981

20 dB Bandwidth Measurement – Channel 01 (2.403328 GHz)



Date: 13.MAR.2007 16:20:57

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage




STC Test Report

Date : 2007-02-06

Page 20 of 39

No. : HM157981

20 dB Bandwidth Measurement – Channel 19 (2.442240 GHz)



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage




STC Test Report

Date : 2007-02-06

Page 21 of 39

No. : HM157981

20 dB Bandwidth Measurement – Channel 37 (2.479104 GHz)



COPY

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage




STC Test Report

Date : 2007-02-06

Page 22 of 39

No. : HM157981

Channel Separation



Date: 1.MAR.2007 08:55:23

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 23 of 39

No. : HM157981

3.4 Number of Hopping Channel Measurement

Test Requirement: FCC 47 CFR 15.247(a)(iii)
Test Date: 2007-01-22
Mode of Operation: Tx mode

Test Method:

The transmitter output was connected to the spectrum / receiver through an attenuator. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 500kHz RBW and 500kHz VBW. Use Peak Search to read the peak power after Maximum Hold function is activated.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.

Channel Frequency Table

Channel	Centre Frequency (GHz)	Channel	Centre Frequency (GHz)
0	2.403328	19	2.442240
1	2.405376	20	2.444288
2	2.407424	21	2.446336
3	2.409472	22	2.448384
4	2.411520	23	2.450432
5	2.413568	24	2.452480
6	2.415616	25	2.454528
7	2.417664	26	2.456576
8	2.419712	27	2.458624
9	2.421760	28	2.460672
10	2.423808	29	2.462720
11	2.425856	30	2.464768
12	2.427904	31	2.466816
13	2.429952	32	2.468864
14	2.432000	33	2.470912
15	2.434048	34	2.472960
16	2.436096	35	2.475008
17	2.438144	36	2.477056
18	2.440192	37	2.479104

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06


Page 24 of 39

No. : HM157981

Limits:

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels.

Number of Hopping Channel



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 25 of 39

No. : HM157981

3.5 Pseudorandom Hopping Algorithm

Requirements:

The channel frequencies shall be selected from a pseudorandom ordered list of hopping frequencies. Each frequency must be used equally by the transmitter.

Pseudo random properties of the embedded FHSS engine

The embedded FHSS engine uses 38 hopping locations, out of which 18 are non-overlapping channels. The hopping sequence is contained in a table with the 38 frequency location entries staggered in a pseudorandom order. A single data frame is transmitted on each frequency location before skipping to the next hopping frequency in the list. Upon completion of the list, the hopping sequence is repeated on a cyclic basis.

Upon reception of faulty/no data, the frequency(ies) resulting in loss of data is temporarily removed from the hopping list. The hopping sequence cycle is thus correspondingly shortened. The frequency locations resulting in loss of data are added to a list of banned frequencies containing the frequency locations unsuitable for use. The list is limited to a maximum number.

In normal operation, the initial pseudorandom list of frequency hopping locations is volatile in terms of the number of hopping frequencies in use and the sequence of which they occur. These elements combined result in an unpredictable hopping sequence with pseudorandom properties.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 26 of 39

No. : HM157981

3.6 Time of Occupancy

Requirements:

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channel employed.
No requirements for Digital Transmission System.

Measurement Data: Number of RF channel: 38
 RF burst pr channel: 1.413 ms
 Time between each RF burst on same RF channel: 80.16 ms

Time of occupancy: $((1.413\text{ms} / 80.16\text{ms}) * 0.4\text{s} * 38\text{s}) = 0.268\text{ sec}$

See fig. A and B.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage




STC Test Report

Date : 2007-02-06

Page 27 of 39

No. : HM157981

Fig. A Time between RF Burst



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage




STC Test Report

Date : 2007-02-06

Page 28 of 39

No. : HM157981

Fig B . RF Burst



Date: 2.APR.2007 20:58:52

The Hong Kong Standards and Testing Centre Ltd.

Hong Kong Standards and Testing Centre
10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 29 of 39

No. : HM157981

3.7 RF Exposure

Test Requirements: §15.247(b)(5); §1.1307(b)(1)

Test Specification: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

Test Results: The EUT complied with the requirement(s) of this section.

EUT meets the requirements of these sections as proven through MPE calculation

The MPE calculation for EUT @ 20cm

Based on the highest P = 10 mW

$$\begin{aligned} Pd &= PG / 4\pi R^2 = (10 \times 1.7) / 12.566^* (20)^2 \\ &= (17.0) / 12.56637 \times 400 = 17.0 / 5026.55 \\ &= 0.004 \text{ mW/cm}^2 \end{aligned}$$

where:

*Pd = power density in mW/cm²

* G = Antenna numeric gain (1.7); Log G = g/10 (g = 2.31).

* P = Conducted RF power to antenna (10 mW).

* R = Minimum allowable distance. (20 cm)

*The power density Pd = 0.004 mW/cm² is less than 1 mW/cm² (listed MPE limit)

*The SAR evaluation is not needed (this is a desk top device, R > 20 cm)

* The EUT(antenna) must be 0.2 meters away from the General Population.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 30 of 39

No. : HM157981

3.8 Antenna Requirement

Test Requirements: S15.203

Test Specification:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Test Results:

The EUT antenna is permanently attached to the main unit and attached on PCB board. User unable to remove or change the antenna.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 31 of 39

No. : HM157981

3.9 Receiver Input Bandwidth

Test Requirements: S15.247 (a) (1)

Test Specification:

The associated receiver(s) complies with the requirement that its input bandwidth matches the bandwidth of the transmitted signal.

Test Results:

The receiver bandwidth is equal to the transmitter bandwidth in the 38 hopping channel modes. The frequency range is from 2403.328 MHz to 2479.104 MHz.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 32 of 39

No. : HM157981

3.10 Receiver Hopping Capability

Test Requirements: S15.247 (a) (1)

Test Specification:

The associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.

Test Results:

The EUT software operates by selecting a palette of 15 random channels out of the total 38 to hop on. For the 15-channel palette, any channels with poor transmission rates are replaced with better channels from the remaining 23 unused channels. The hopping pattern from channel to channel is a random pattern.

The master TX dwells on a single hopping channel and transmits a data packet to the slave RX. When the slave RX receives a good data packet from a TX, the RX sends an Acknowledgement back to the TX. Once the slave RX has responded to the master TX then both the TX and RX units each hop to the next frequency channel and the 2-way data communication is repeated, and so.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 33 of 39

No. : HM157981


3.11 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement: FCC 47CFR 15.207
Test Method: ANSI C63.4:2003
Test Date: 2007-01-08
Mode of Operation: Tx Mode

Test Method:

The test was performed in accordance with ANSI C63.4: 2003, with the following: an initial measurement was performed in peak and average detection mode on the live line, any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Test Setup:



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 34 of 39

No. : HM157981


Limit for Conducted Emissions (FCC 47 CFR 15.207):

Frequency Range [MHz]	Quasi-Peak Limits [dB μ V]	Average [dB μ V]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

Results of Tx Mode: PASS



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 35 of 39

No. : HM157981

Results of Tx Mode: PASS

Conductor Live or Neutral	Frequency MHz	Quasi-peak		Average	
		Level dB μ V	Limit dB μ V	Level dB μ V	Limit dB μ V
Live	0.250	-*-	-*-	23.9	52
Live	0.255	-*-	-*-	23.6	52
Live	0.570	33	56	30.3	46
Neutral	0.505	-*-	-*-	29.8	46
Neutral	29.920	35.6	60	-*-	-*-

Remarks:

Calculated measurement uncertainty : ± 3.97 dB

-*- Emission(s) that is far below the corresponding limit line.

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 36 of 39

No. : HM157981

Appendix A

List of Measurement Equipment

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410
EM011	ATTENUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262
EM020	HORN ANTENNA	ETS-Linggren	3115	4032
EM022	LOOP ANTENNA	ETS-Linggren	6502	1189-2424
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892
EM083	OPEN AREA TEST SITE	HKSTC	N/A	N/A
EM131	EMC ANALYZER	HEWLETT PACKARD	8595EM	3710A00155
EM145	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESCS 30	830245/021
EM195	ANTENNA POSITIONING MAST	ETS-Linggren	2075	2368
EM196	MULTI-DEVICE CONTROLLER	ETS-Linggren	2090	1662
EM215	MULTIDEVICE CONTROLER	ETS-Linggren	2090	00024676
EM216	MINI MAST SYSTEM	ETS-Linggren	2075	00026842
EM217	ELECTRIC POWERED TURNTABLE	ETS-Linggren	2088	00029144
EM218	ANECHOIC CHAMBER	ETS-Linggren	FACT-3	--
EM219	BICONILOG ANTENNA	ETS-Linggren	3142C	00029071
EM229	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESIB40	100248

Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A
EM119	LISN	ROHDE & SCHWARZ	ESH3-Z5	0831.5518.52
EM127	ISOLATION TRANSFORMER 220 TO 300V	WING SUN	N/A	N/A
EM233	PULSE LIMITER	ROHDE & SCHWARZ	ESH3-Z2	100314
EM181	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESIB7	100072
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057-99A
M197	LISN	ETS-Linggren	4825/2	1193

Remarks:-

CM Corrective Maintenance

N/A Not Applicable or Not Available

TBD To Be Determined

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



STC Test Report

Date : 2007-02-06

Page 37 of 39

No. : HM157981

Appendix B

Photographs of EUT

Front View of the product



Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 38 of 39

No. : HM157981

Photographs of EUT

Measurement of Radiated Emission Test Set Up



The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage



STC Test Report

Date : 2007-02-06

Page 39 of 39

No. : HM157981

Photographs of EUT

Measurement of Radiated Emission Test Set Up



Measurement of Conducted Emission Test Set Up



******* End of Test Report *******

The Hong Kong Standards and Testing Centre Ltd.

10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong

Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd.
For Conditions of Issuance of this test report, please refer to the overleaf or Homepage