

RF Exposure Report

Report No.: SA200703E03

FCC ID: UXX-S5A036A

Test Model: S5A037A

Series Model: S5A036A

Received Date: July 03, 2020

Test Date: July 24, 2020

Issued Date: Aug. 11, 2020

Applicant: Cradlepoint, Inc

Address: 1111 W. Jefferson Street Suite 400 Boise, ID 83702 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result	7
Appendix	8

Release Control Record

Issue No.	Description	Date Issued
SA200703E03	Original release.	Aug. 11, 2020

1 Certificate of Conformity

Product: Enterprise Branch Router

Brand: cradlepoint

Test Model: S5A037A

Series Model: S5A036A

Sample Status: ENGINEERING SAMPLE

Applicant: Cradlepoint, Inc

Test Date: July 24, 2020

Standards: FCC Part 2 (Section 2.1091)
IEEE C95.3-2002

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Vivian Huang , **Date:** Aug. 11, 2020
Vivian Huang / Specialist

Approved by : Clark Lin , **Date:** Aug. 11, 2020
Clark Lin / Technical Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WLAN Antenna								
Ant. No.	RF Chain No.	Brand	Ant. Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type	Cable Length (mm)	Cable Loss (dB)
1	WiFi Chain0	cradlepoint	2.9	2.4~2.4835	PCB	i-pex(MHF)	130	Including
			2.8	5.15~5.25				
			3.1	5.725~5.85				
2	WiFi Chain1	cradlepoint	2.9	2.4~2.4835	PCB	i-pex(MHF)	230	Including
			2.8	5.15~5.25				
			3.1	5.725~5.85				
WWAN Antenna								
Antenna No.		Band		Freq. Range (MHz)		Gain (dBi)		Antenna Type
1		WCDMA Band 2		1850~1910		1.4		Dipole
		WCDMA Band 4		1710~1755		1.4		
		WCDMA Band 5		824~849		0.72		
		LTE Band 2		1850~1910		1.54		
		LTE Band 4		1710~1755		1.54		
		LTE Band 5		824~849		0.7		
		LTE Band 12		688~716		0.7		
		LTE Band 13		777~787		0.7		
		LTE Band 14		788~798		0.7		
		LTE Band 66		1710~1780		1.54		
		LTE Band 71		663~698		0.7		
2		WCDMA Band 2		1850~1910		1.26		Dipole
		WCDMA Band 4		1710~1755		1.26		
		WCDMA Band 5		824~849		0.65		
		LTE Band 2		1850~1910		1.53		
		LTE Band 4		1710~1755		1.53		
		LTE Band 5		824~849		0.7		
		LTE Band 12		688~716		0.7		
		LTE Band 13		777~787		0.7		
		LTE Band 14		788~798		0.7		
		LTE Band 66		1710~1780		1.53		
		LTE Band 71		663~698		0.7		

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.5 Calculation Result

For WLAN

Operation Mode	Evaluation Frequency (MHz)	Max Power Average (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2412~2462	223.387	5.91	20	0.1733	1
WLAN 5GHz U-NII-1	5180~5240	245.002	5.81	20	0.18574	1
WLAN 5GHz U-NII-3	5745~5825	248.321	6.11	20	0.20172	1

NOTE:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. 2.4GHz: Directional gain = 2.9dBi + 10log(2) = 5.91dBi
3. 5GHz U-NII-1: Directional gain = 2.8dBi + 10log(2) = 5.81dBi
5GHz U-NII-3: Directional gain = 3.1dBi + 10log(2) = 6.11dBi

For WWAN module <Worst case> (FCC ID: XMR201808EC25AF)

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
LTE B71	663~698	222	0.71	20	0.05201	0.442

Note: *Limit of Power Density = F/1500

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$WLAN\ 2.4GHz + WLAN\ 5GHz + LTE\ B71 = 0.1733 / 1 + 0.20172 / 1 + 0.05201 / 0.442 = 0.49269$

Therefore the maximum calculations of above situations are less than the “1” limit.

Appendix

WWLAN module

MPE Evaluation for FCC ID: XMR201808EC25AF Module

Mode	Equipment Category	Transmitter Range (MHz)		Maximum Power		Antenna Gain (dBi)	Power Density (mW/cm ²)		Ratio
		Start	Stop	(dBm)	(mW)		Vaule	Limit	
WCDMA	WCDMA II	1850	1910	23.80	240	1.40	0.06591	1	0.06591
	WCDMA IV	1710	1755	23.46	222	1.40	0.06097	1	0.06097
	WCDMA V	824	849	23.20	209	0.72	0.04908	0.54933	0.08935
LTE	LTE B2	1850	1910	23.18	208	1.54	0.05899	1	0.05899
	LTE B4	1710	1755	23.73	236	1.54	0.06693	1	0.06693
	LTE B5	824	849	24.05	254	0.70	0.05937	0.54933	0.10808
	LTE B12	699	716	23.69	234	0.70	0.05469	0.466	0.11736
	LTE B13	777	787	23.86	243	0.70	0.05680	0.518	0.10965
	LTE B14	788	798	23.86	243	0.70	0.05680	0.52533	0.10812
	LTE B66	1710	1780	22.88	194	1.54	0.05502	1	0.05502
	LTE B71	663	698	23.46	222	0.70	0.05189	0.442	0.11740

--- END ---