

|               |               |                |              |
|---------------|---------------|----------------|--------------|
| Temperature   | 25°C          | Humidity       | 57%          |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n |
| Test Date     | Feb. 08, 2012 | Test Mode      | Mode 15      |

#### Configuration IEEE 802.11n MCS0 20MHz / Chain 1 (1TX, 2RX)

| Channel | Frequency | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Min. Limit (kHz) | Test Result |
|---------|-----------|---------------------|------------------------------|------------------|-------------|
| 149     | 5745 MHz  | 17.80               | 17.72                        | 500              | Complies    |
| 157     | 5785 MHz  | 17.80               | 17.72                        | 500              | Complies    |
| 165     | 5825 MHz  | 17.84               | 17.72                        | 500              | Complies    |

#### Configuration IEEE 802.11n MCS0 40MHz / Chain 1 (1TX, 2RX)


| Channel | Frequency | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Min. Limit (kHz) | Test Result |
|---------|-----------|---------------------|------------------------------|------------------|-------------|
| 151     | 5755 MHz  | 36.56               | 36.32                        | 500              | Complies    |
| 159     | 5795 MHz  | 36.64               | 36.40                        | 500              | Complies    |

|               |               |                |              |
|---------------|---------------|----------------|--------------|
| Temperature   | 25°C          | Humidity       | 56%          |
| Test Engineer | Satoshi Yang  | Configurations | IEEE 802.11a |
| Test Date     | Feb. 07, 2012 | Test Mode      | Mode 15      |

#### Configuration IEEE 802.11a / Chain 1 (1TX, 2RX)


| Channel | Frequency | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Min. Limit (kHz) | Test Result |
|---------|-----------|---------------------|------------------------------|------------------|-------------|
| 149     | 5745 MHz  | 16.60               | 16.56                        | 500              | Complies    |
| 157     | 5785 MHz  | 16.56               | 16.56                        | 500              | Complies    |
| 165     | 5825 MHz  | 16.60               | 16.56                        | 500              | Complies    |

# 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Chain 1 / 5785 MHz /Mode 15 (1TX, 2RX)




Date: 8.FEB.2012 21:53:03

# 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Chain 1 / 5755 MHz /Mode 15 (1TX, 2RX)



Date: 8.FEB.2012 21:48:04

# 6 dB Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 / 5785 MHz / Mode 15 (1TX, 2RX)



Date: 8.FEB.2012 21:59:23

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies<br>(MHz) | Field Strength<br>(micровolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                          | 300                              |
| 0.490~1.705          | 24000/F(KHz)                         | 30                               |
| 1.705~30.0           | 30                                   | 30                               |
| 30~88                | 100                                  | 3                                |
| 88~216               | 150                                  | 3                                |
| 216~960              | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter                        | Setting                                         |
|-------------------------------------------|-------------------------------------------------|
| Attenuation                               | Auto                                            |
| Start Frequency                           | 1000 MHz                                        |
| Stop Frequency                            | 10th carrier harmonic                           |
| RB / VB (Emission in restricted band)     | 1 MHz / 3MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 1 MHz / 3MHz for peak                           |


| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

|               |               |                |             |
|---------------|---------------|----------------|-------------|
| Temperature   | 24.7°C        | Humidity       | 57%         |
| Test Engineer | Benson Peng   | Configurations | Normal Link |
| Test Date     | Nov. 23, 2011 |                |             |

| Freq.<br>(MHz) | Level<br>(dBuV) | Over Limit<br>(dB) | Limit Line<br>(dBuV) | Remark   |
|----------------|-----------------|--------------------|----------------------|----------|
| -              | -               | -                  | -                    | See Note |

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.5.8. Results of Radiated Emissions (30MHz~1GHz)

|               |             |                |             |
|---------------|-------------|----------------|-------------|
| Temperature   | 21°C        | Humidity       | 59%         |
| Test Engineer | Benson Peng | Configurations | Normal Link |
| Test Mode     | Mode 3      |                |             |


##### Horizontal



|   | Freq   | Level  | Limit  | Over   | Read  | CableAntenna | Preamp |        | A/Pos  | T/Pos |              |
|---|--------|--------|--------|--------|-------|--------------|--------|--------|--------|-------|--------------|
|   | MHz    | dBuV/m | dBuV/m | Limit  | Level | Loss         | Factor | Factor | Remark | cm    | deg          |
| 1 | 34.85  | 33.18  | 40.00  | -6.82  | 44.40 | 0.50         | 16.08  | 27.80  | Peak   | 100   | 0 HORIZONTAL |
| 2 | 53.28  | 33.19  | 40.00  | -6.81  | 52.22 | 0.76         | 8.00   | 27.79  | Peak   | 100   | 0 HORIZONTAL |
| 3 | 98.87  | 35.56  | 43.50  | -7.94  | 51.20 | 1.18         | 10.79  | 27.61  | QP     | 210   | 5 HORIZONTAL |
| 4 | 165.80 | 28.09  | 43.50  | -15.41 | 41.36 | 1.53         | 12.47  | 27.27  | Peak   | 100   | 0 HORIZONTAL |
| 5 | 375.32 | 27.77  | 46.00  | -18.23 | 37.55 | 2.25         | 15.40  | 27.43  | Peak   | 100   | 0 HORIZONTAL |
| 6 | 500.45 | 36.43  | 46.00  | -9.57  | 44.20 | 2.70         | 17.63  | 28.10  | Peak   | 100   | 0 HORIZONTAL |



# Vertical



|   | Freq   | Level  | Limit<br>Line | Over<br>Limit | Read<br>Level | CableAntenna<br>Loss Factor | Preamp<br>Factor | Remark     | A/Pos | T/Pos | Pol/Phase |
|---|--------|--------|---------------|---------------|---------------|-----------------------------|------------------|------------|-------|-------|-----------|
|   | MHz    | dBuV/m | dBuV/m        | dB            | dBuV          | dB                          | dB/m             | dB         | cm    | deg   |           |
| 1 | 30.97  | 33.22  | 40.00         | -6.78         | 42.30         | 0.50                        | 18.22            | 27.80 Peak | 400   | 0     | VERTICAL  |
| 2 | 99.84  | 33.75  | 43.50         | -9.75         | 49.16         | 1.20                        | 10.99            | 27.60 Peak | 400   | 0     | VERTICAL  |
| 3 | 173.56 | 32.22  | 43.50         | -11.28        | 44.83         | 1.57                        | 13.05            | 27.23 Peak | 400   | 0     | VERTICAL  |
| 4 | 260.86 | 28.75  | 46.00         | -17.25        | 40.89         | 1.94                        | 12.90            | 26.98 Peak | 400   | 0     | VERTICAL  |
| 5 | 375.32 | 27.39  | 46.00         | -18.61        | 37.17         | 2.25                        | 15.40            | 27.43 Peak | 400   | 0     | VERTICAL  |
| 6 | 500.45 | 36.48  | 46.00         | -9.52         | 44.25         | 2.70                        | 17.63            | 28.10 Peak | 400   | 0     | VERTICAL  |


## Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


|               |             |                |             |
|---------------|-------------|----------------|-------------|
| Temperature   | 21°C        | Humidity       | 59%         |
| Test Engineer | Benson Peng | Configurations | Normal Link |
| Test Mode     | Mode 6      |                |             |

### Horizontal



|   | Freq   | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark | A/Pos | T/Pos | Pol/Phase  |
|---|--------|--------|------------|------------|------------|------------|----------------|---------------|--------|-------|-------|------------|
|   | MHz    | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |        | cm    | deg   |            |
| 1 | 99.84  | 30.69  | 43.50      | -12.81     | 46.10      | 1.20       | 10.99          | 27.60         | Peak   | 100   | 0     | HORIZONTAL |
| 2 | 165.80 | 28.79  | 43.50      | -14.71     | 42.06      | 1.53       | 12.47          | 27.27         | Peak   | 100   | 0     | HORIZONTAL |
| 3 | 250.19 | 29.41  | 46.00      | -16.59     | 41.74      | 1.90       | 12.77          | 27.00         | Peak   | 100   | 0     | HORIZONTAL |
| 4 | 375.32 | 39.93  | 46.00      | -6.07      | 49.71      | 2.25       | 15.40          | 27.43         | QP     | 100   | 50    | HORIZONTAL |
| 5 | 625.58 | 37.51  | 46.00      | -8.49      | 43.68      | 3.05       | 18.85          | 28.07         | Peak   | 100   | 0     | HORIZONTAL |
| 6 | 800.18 | 34.63  | 46.00      | -11.37     | 39.16      | 3.30       | 19.77          | 27.60         | Peak   | 100   | 0     | HORIZONTAL |
| 7 | 875.84 | 35.96  | 46.00      | -10.04     | 39.56      | 3.50       | 20.35          | 27.45         | Peak   | 100   | 0     | HORIZONTAL |

### Vertical



|   | Freq   | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark | A/Pos | T/Pos | Pol/Phase |
|---|--------|--------|------------|------------|------------|------------|----------------|---------------|--------|-------|-------|-----------|
|   | MHz    | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |        | cm    | deg   |           |
| 1 | 49.40  | 33.70  | 40.00      | -6.30      | 51.97      | 0.70       | 8.83           | 27.80         | Peak   | 400   | 0     | VERTICAL  |
| 2 | 98.87  | 35.58  | 43.50      | -7.92      | 51.22      | 1.18       | 10.79          | 27.61         | Peak   | 400   | 0     | VERTICAL  |
| 3 | 169.68 | 33.06  | 43.50      | -10.44     | 46.00      | 1.55       | 12.76          | 27.25         | Peak   | 400   | 0     | VERTICAL  |
| 4 | 375.32 | 33.09  | 46.00      | -12.91     | 42.87      | 2.25       | 15.40          | 27.43         | Peak   | 400   | 0     | VERTICAL  |
| 5 | 625.58 | 37.02  | 46.00      | -8.98      | 43.19      | 3.05       | 18.85          | 28.07         | Peak   | 400   | 0     | VERTICAL  |
| 6 | 800.18 | 32.84  | 46.00      | -13.16     | 37.37      | 3.30       | 19.77          | 27.60         | Peak   | 400   | 0     | VERTICAL  |
| 7 | 875.84 | 35.31  | 46.00      | -10.69     | 38.91      | 3.50       | 20.35          | 27.45         | Peak   | 400   | 0     | VERTICAL  |

### Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 20MHz Ch 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                                      |

##### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4824.51 | 43.78  | 74.00      | -30.22     | 42.44      | 3.31       | 33.06          | 35.03         | Peak    | 135   | 300   | HORIZONTAL |
| 2 | 4825.12 | 31.00  | 54.00      | -23.00     | 29.66      | 3.31       | 33.06          | 35.03         | Average | 135   | 300   | HORIZONTAL |

##### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4823.23 | 44.78  | 74.00      | -29.22     | 43.44      | 3.31       | 33.06          | 35.03         | Peak    | 129   | 336   | VERTICAL  |
| 2 | 4828.04 | 32.20  | 54.00      | -21.80     | 30.86      | 3.31       | 33.06          | 35.03         | Average | 129   | 336   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 20MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4874.03 | 42.26  | 54.00      | -11.74     | 40.80      | 3.33       | 33.16          | 35.03         | Average | 113   | 92    | HORIZONTAL |
| 2 | 4875.83 | 56.14  | 74.00      | -17.86     | 54.68      | 3.33       | 33.16          | 35.03         | Peak    | 113   | 92    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4869.71 | 42.49  | 54.00      | -11.51     | 41.07      | 3.33       | 33.12          | 35.03         | Average | 100   | 77    | VERTICAL  |
| 2 | 4869.85 | 56.36  | 74.00      | -17.64     | 54.94      | 3.33       | 33.12          | 35.03         | Peak    | 100   | 77    | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 20MHz Ch11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4918.20 | 44.48  | 74.00      | -29.52     | 42.92      | 3.35       | 33.23          | 35.02         | Peak    | 125   | 124   | HORIZONTAL |
| 2 | 4919.96 | 32.23  | 54.00      | -21.77     | 30.66      | 3.35       | 33.23          | 35.01         | Average | 125   | 124   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4929.71 | 33.59  | 54.00      | -20.41     | 31.99      | 3.35       | 33.26          | 35.01         | Average | 110   | 101   | VERTICAL  |
| 2 | 4932.85 | 47.10  | 74.00      | -26.90     | 45.50      | 3.35       | 33.26          | 35.01         | Peak    | 110   | 101   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 40MHz Ch 3 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4835.47 | 43.85  | 74.00      | -30.15     | 42.51      | 3.31       | 33.06          | 35.03         | Peak    | 104   | 127   | HORIZONTAL |
| 2 | 4848.39 | 30.30  | 54.00      | -23.70     | 28.92      | 3.32       | 33.09          | 35.03         | Average | 104   | 127   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4842.11 | 43.33  | 74.00      | -30.67     | 41.95      | 3.32       | 33.09          | 35.03         | Peak    | 104   | 6     | VERTICAL  |
| 2 | 4847.33 | 30.31  | 54.00      | -23.69     | 28.93      | 3.32       | 33.09          | 35.03         | Average | 104   | 6     | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 40MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4872.21 | 43.82  | 74.00      | -30.18     | 42.36      | 3.33       | 33.16          | 35.03         | Peak    | 124   | 314   | HORIZONTAL |
| 2 | 4874.96 | 31.04  | 54.00      | -22.96     | 29.58      | 3.33       | 33.16          | 35.03         | Average | 124   | 314   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4871.66 | 43.96  | 74.00      | -30.04     | 42.50      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 267   | VERTICAL  |
| 2 | 4872.88 | 31.41  | 54.00      | -22.59     | 29.95      | 3.33       | 33.16          | 35.03         | Average | 100   | 267   | VERTICAL  |



|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 40MHz Ch 9 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4911.24 | 30.03  | 54.00      | -23.97     | 28.48      | 3.34       | 33.23          | 35.02         | Average | 112   | 137   | HORIZONTAL |
| 2 | 4912.08 | 43.96  | 74.00      | -30.04     | 42.41      | 3.34       | 33.23          | 35.02         | Peak    | 112   | 137   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4906.60 | 30.93  | 54.00      | -23.07     | 29.38      | 3.34       | 33.23          | 35.02         | Average | 100   | 320   | VERTICAL  |
| 2 | 4913.36 | 42.45  | 74.00      | -31.55     | 40.90      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 320   | VERTICAL  |

|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11b CH 1 / Chain 2 (1TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                 |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4823.97 | 49.52  | 74.00      | -24.48     | 48.18      | 3.31       | 33.06          | 35.03         | Peak    | 119   | 339   | HORIZONTAL |
| 2 | 4823.97 | 45.09  | 54.00      | -8.91      | 43.75      | 3.31       | 33.06          | 35.03         | Average | 119   | 339   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4823.99 | 52.42  | 54.00      | -1.58      | 51.08      | 3.31       | 33.06          | 35.03         | Average | 100   | 92    | VERTICAL  |
| 2 | 4824.00 | 54.42  | 74.00      | -19.58     | 53.08      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 92    | VERTICAL  |

|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11b CH 6 / Chain 2 (1TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                 |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4873.97 | 47.46  | 54.00      | -6.54      | 46.00      | 3.33       | 33.16          | 35.03         | Average | 101   | 99    | HORIZONTAL |
| 2 | 4874.08 | 51.03  | 74.00      | -22.97     | 49.57      | 3.33       | 33.16          | 35.03         | Peak    | 101   | 99    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4873.93 | 55.70  | 74.00      | -18.30     | 54.24      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 91    | VERTICAL  |
| 2 | 4873.99 | 53.72  | 54.00      | -0.28      | 52.26      | 3.33       | 33.16          | 35.03         | Average | 100   | 91    | VERTICAL  |

|               |               |                |                                         |
|---------------|---------------|----------------|-----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                     |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11b CH 11 / Chain 2 (1TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                  |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4923.99 | 53.50  | 54.00      | -0.50      | 51.90      | 3.35       | 33.26          | 35.01         | Average | 101   | 68    | HORIZONTAL |
| 2 | 4924.04 | 55.18  | 74.00      | -18.82     | 53.58      | 3.35       | 33.26          | 35.01         | Peak    | 101   | 68    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4923.99 | 52.73  | 54.00      | -1.27      | 51.13      | 3.35       | 33.26          | 35.01         | Average | 109   | 115   | VERTICAL  |
| 2 | 4923.99 | 55.42  | 74.00      | -18.58     | 53.82      | 3.35       | 33.26          | 35.01         | Peak    | 109   | 115   | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11g CH 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                           |

### Horizontal

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     |         | cm    | deg   |            |
| 1 | 4823.56 | 44.18  | 74.00  | -29.82 | 42.84 | 3.31  | 33.06   | 35.03  | Peak    | 100   | 96    | HORIZONTAL |
| 2 | 4827.36 | 30.65  | 54.00  | -23.35 | 29.31 | 3.31  | 33.06   | 35.03  | Average | 100   | 96    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     |         | cm    | deg   |           |
| 1 | 4825.56 | 32.45  | 54.00  | -21.55 | 31.11 | 3.31  | 33.06   | 35.03  | Average | 100   | 81    | VERTICAL  |
| 2 | 4825.72 | 47.11  | 74.00  | -26.89 | 45.77 | 3.31  | 33.06   | 35.03  | Peak    | 100   | 81    | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11g CH 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4874.40 | 40.53  | 54.00      | -13.47     | 39.07      | 3.33       | 33.16          | 35.03         | Average | 100   | 113   | HORIZONTAL |
| 2 | 4874.56 | 55.24  | 74.00      | -18.76     | 53.78      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 113   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4872.96 | 42.74  | 54.00      | -11.26     | 41.28      | 3.33       | 33.16          | 35.03         | Average | 100   | 79    | VERTICAL  |
| 2 | 4877.64 | 57.05  | 74.00      | -16.95     | 55.59      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 79    | VERTICAL  |

|               |               |                |                                                   |
|---------------|---------------|----------------|---------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                               |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11g CH 11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 1                                            |

#### Horizontal

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp |         | A/Pos | T/Pos |            |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | Line   | Limit  | Level | Loss  | Factor  | Factor | Remark  | cm    | deg   | Pol/Phase  |
|   |         |        | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     |         |       |       |            |
| 1 | 4922.68 | 33.65  | 54.00  | -20.35 | 32.05 | 3.35  | 33.26   | 35.01  | Average | 100   | 74    | HORIZONTAL |
| 2 | 4922.88 | 48.58  | 74.00  | -25.42 | 46.98 | 3.35  | 33.26   | 35.01  | Peak    | 100   | 74    | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp |         | A/Pos | T/Pos |           |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | Line   | Limit  | Level | Loss  | Factor  | Factor | Remark  | cm    | deg   | Pol/Phase |
|   |         |        | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     |         |       |       |           |
| 1 | 4920.60 | 35.08  | 54.00  | -18.92 | 33.51 | 3.35  | 33.23   | 35.01  | Average | 100   | 73    | VERTICAL  |
| 2 | 4920.72 | 50.22  | 74.00  | -23.78 | 48.65 | 3.35  | 33.23   | 35.01  | Peak    | 100   | 73    | VERTICAL  |

#### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 20MHz Ch 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4825.06 | 54.47  | 74.00      | -19.53     | 53.13      | 3.31       | 33.06          | 35.03         | Peak    | 155   | 330   | HORIZONTAL |
| 2 | 4825.15 | 39.70  | 54.00      | -14.30     | 38.36      | 3.31       | 33.06          | 35.03         | Average | 155   | 330   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4822.88 | 49.51  | 74.00      | -24.49     | 48.17      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 33    | VERTICAL  |
| 2 | 4823.46 | 34.64  | 54.00      | -19.36     | 33.30      | 3.31       | 33.06          | 35.03         | Average | 100   | 33    | VERTICAL  |



|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 20MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4876.08 | 43.16  | 54.00      | -10.84     | 41.70      | 3.33       | 33.16          | 35.03         | Average | 147   | 205   | HORIZONTAL |
| 2 | 4876.28 | 57.92  | 74.00      | -16.08     | 56.46      | 3.33       | 33.16          | 35.03         | Peak    | 147   | 205   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4868.49 | 40.20  | 54.00      | -13.80     | 38.78      | 3.33       | 33.12          | 35.03         | Average | 113   | 155   | VERTICAL  |
| 2 | 4869.39 | 55.27  | 74.00      | -18.73     | 53.85      | 3.33       | 33.12          | 35.03         | Peak    | 113   | 155   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 20MHz Ch11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4923.26 | 38.88  | 54.00      | -15.12     | 37.28      | 3.35       | 33.26          | 35.01         | Average | 149   | 152   | HORIZONTAL |
| 2 | 4924.10 | 53.12  | 74.00      | -20.88     | 51.52      | 3.35       | 33.26          | 35.01         | Peak    | 149   | 152   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4921.98 | 49.13  | 74.00      | -24.87     | 47.53      | 3.35       | 33.26          | 35.01         | Peak    | 101   | 257   | VERTICAL  |
| 2 | 4923.65 | 36.26  | 54.00      | -17.74     | 34.66      | 3.35       | 33.26          | 35.01         | Average | 101   | 257   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 40MHz Ch 3 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4840.25 | 44.71  | 74.00      | -29.29     | 43.33      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 151   | HORIZONTAL |
| 2 | 4841.79 | 33.11  | 54.00      | -20.89     | 31.73      | 3.32       | 33.09          | 35.03         | Average | 100   | 151   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4835.76 | 44.17  | 74.00      | -29.83     | 42.83      | 3.31       | 33.06          | 35.03         | Peak    | 104   | 66    | VERTICAL  |
| 2 | 4842.24 | 31.04  | 54.00      | -22.96     | 29.66      | 3.32       | 33.09          | 35.03         | Average | 104   | 66    | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 40MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4875.57 | 50.22  | 74.00      | -23.78     | 48.76      | 3.33       | 33.16          | 35.03         | Peak    | 148   | 206   | HORIZONTAL |
| 2 | 4877.21 | 37.27  | 54.00      | -16.73     | 35.81      | 3.33       | 33.16          | 35.03         | Average | 148   | 206   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4874.13 | 50.64  | 74.00      | -23.36     | 49.18      | 3.33       | 33.16          | 35.03         | Peak    | 146   | 201   | VERTICAL  |
| 2 | 4875.38 | 36.83  | 54.00      | -17.17     | 35.37      | 3.33       | 33.16          | 35.03         | Average | 146   | 201   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 40MHz Ch 9 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4912.17 | 30.06  | 54.00      | -23.94     | 28.51      | 3.34       | 33.23          | 35.02         | Average | 100   | 52    | HORIZONTAL |
| 2 | 4913.94 | 42.90  | 74.00      | -31.10     | 41.35      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 52    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4912.01 | 42.87  | 74.00      | -31.13     | 41.32      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 18    | VERTICAL  |
| 2 | 4913.17 | 30.14  | 54.00      | -23.86     | 28.59      | 3.34       | 33.23          | 35.02         | Average | 100   | 18    | VERTICAL  |

|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11b CH 1 / Chain 1 (1TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                 |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4823.98 | 55.14  | 74.00      | -18.86     | 53.80      | 3.31       | 33.06          | 35.03         | Peak    | 131   | 300   | HORIZONTAL |
| 2 | 4823.99 | 53.46  | 54.00      | -0.54      | 52.12      | 3.31       | 33.06          | 35.03         | Average | 131   | 300   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4823.99 | 44.74  | 54.00      | -9.26      | 43.40      | 3.31       | 33.06          | 35.03         | Average | 112   | 255   | VERTICAL  |
| 2 | 4824.01 | 49.04  | 74.00      | -24.96     | 47.70      | 3.31       | 33.06          | 35.03         | Peak    | 112   | 255   | VERTICAL  |

|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11b CH 6 / Chain 1 (1TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                 |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4873.98 | 55.26  | 74.00      | -18.74     | 53.80      | 3.33       | 33.16          | 35.03         | Peak    | 145   | 315   | HORIZONTAL |
| 2 | 4873.99 | 53.19  | 54.00      | -0.81      | 51.73      | 3.33       | 33.16          | 35.03         | Average | 145   | 315   | HORIZONTAL |
| 3 | 7309.98 | 50.89  | 74.00      | -23.11     | 46.27      | 4.06       | 35.96          | 35.40         | Peak    | 115   | 133   | HORIZONTAL |
| 4 | 7310.28 | 44.27  | 54.00      | -9.73      | 39.65      | 4.06       | 35.96          | 35.40         | Average | 115   | 133   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4873.99 | 45.10  | 54.00      | -8.90      | 43.64      | 3.33       | 33.16          | 35.03         | Average | 101   | 251   | VERTICAL  |
| 2 | 4874.07 | 49.41  | 74.00      | -24.59     | 47.95      | 3.33       | 33.16          | 35.03         | Peak    | 101   | 251   | VERTICAL  |
| 3 | 7310.24 | 36.32  | 54.00      | -17.68     | 31.70      | 4.06       | 35.96          | 35.40         | Average | 100   | 140   | VERTICAL  |
| 4 | 7313.02 | 46.46  | 74.00      | -27.54     | 41.84      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 140   | VERTICAL  |

|               |               |                |                                         |
|---------------|---------------|----------------|-----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                     |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11b CH 11 / Chain 1 (1TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                  |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4924.00 | 53.97  | 54.00      | -0.03      | 52.37      | 3.35       | 33.26          | 35.01         | Average | 127   | 287   | HORIZONTAL |
| 2 | 4924.05 | 55.67  | 74.00      | -18.33     | 54.07      | 3.35       | 33.26          | 35.01         | Peak    | 127   | 287   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4924.00 | 51.08  | 74.00      | -22.92     | 49.48      | 3.35       | 33.26          | 35.01         | Peak    | 100   | 56    | VERTICAL  |
| 2 | 4924.00 | 48.38  | 54.00      | -5.62      | 46.78      | 3.35       | 33.26          | 35.01         | Average | 100   | 56    | VERTICAL  |



|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11g CH 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4825.56 | 35.32  | 54.00      | -18.68     | 33.98      | 3.31       | 33.06          | 35.03         | Average | 117   | 60    | HORIZONTAL |
| 2 | 4826.12 | 48.61  | 74.00      | -25.39     | 47.27      | 3.31       | 33.06          | 35.03         | Peak    | 117   | 60    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4823.76 | 45.46  | 74.00      | -28.54     | 44.12      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 61    | VERTICAL  |
| 2 | 4824.40 | 31.60  | 54.00      | -22.40     | 30.26      | 3.31       | 33.06          | 35.03         | Average | 100   | 61    | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 20°C          | Humidity       | 70%                                              |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11g CH 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                           |

### Horizontal

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp |         | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     | Remark  | cm    | deg   |            |
| 1 | 4869.52 | 58.54  | 74.00  | -15.46 | 57.12 | 3.33  | 33.12   | 35.03  | Peak    | 113   | 201   | HORIZONTAL |
| 2 | 4874.36 | 43.43  | 54.00  | -10.57 | 41.97 | 3.33  | 33.16   | 35.03  | Average | 113   | 201   | HORIZONTAL |
| 3 | 7309.44 | 48.33  | 54.00  | -5.67  | 43.71 | 4.06  | 35.96   | 35.40  | Average | 122   | 232   | HORIZONTAL |
| 4 | 7314.44 | 64.09  | 74.00  | -9.91  | 59.47 | 4.06  | 35.96   | 35.40  | Peak    | 122   | 232   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp |         | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     | Remark  | cm    | deg   |           |
| 1 | 4871.36 | 53.11  | 74.00  | -20.89 | 51.65 | 3.33  | 33.16   | 35.03  | Peak    | 100   | 249   | VERTICAL  |
| 2 | 4871.68 | 39.65  | 54.00  | -14.35 | 38.19 | 3.33  | 33.16   | 35.03  | Average | 100   | 249   | VERTICAL  |
| 3 | 7315.68 | 53.60  | 74.00  | -20.40 | 48.98 | 4.06  | 35.96   | 35.40  | Peak    | 100   | 182   | VERTICAL  |
| 4 | 7315.80 | 38.93  | 54.00  | -15.07 | 34.31 | 4.06  | 35.96   | 35.40  | Average | 100   | 182   | VERTICAL  |

|               |               |                |                                                   |
|---------------|---------------|----------------|---------------------------------------------------|
| Temperature   | 20°C          | Humidity       | 70%                                               |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11g CH 11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 2                                            |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4924.16 | 38.71  | 54.00      | -15.29     | 37.11      | 3.35       | 33.26          | 35.01         | Average | 127   | 283   | HORIZONTAL |
| 2 | 4924.16 | 53.43  | 74.00      | -20.57     | 51.83      | 3.35       | 33.26          | 35.01         | Peak    | 127   | 283   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4919.36 | 49.12  | 74.00      | -24.88     | 47.56      | 3.35       | 33.23          | 35.02         | Peak    | 100   | 248   | VERTICAL  |
| 2 | 4923.56 | 34.56  | 54.00      | -19.44     | 32.96      | 3.35       | 33.26          | 35.01         | Average | 100   | 248   | VERTICAL  |

|               |               |                |                                                               |
|---------------|---------------|----------------|---------------------------------------------------------------|
| Temperature   | 24°C          | Humidity       | 56%                                                           |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 20MHz CH 149 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 3                                                        |

### Horizontal

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 11480.56 | 51.92  | 74.00      | -22.08     | 43.32      | 5.11       | 38.77          | 35.28         | Peak    | 100   | 285   | HORIZONTAL |
| 2 | 11485.24 | 40.06  | 54.00      | -13.94     | 31.45      | 5.11       | 38.78          | 35.28         | Average | 100   | 285   | HORIZONTAL |

### Vertical

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 11486.24 | 38.55  | 54.00      | -15.45     | 29.94      | 5.11       | 38.78          | 35.28         | Average | 100   | 311   | VERTICAL  |
| 2 | 11498.36 | 51.00  | 74.00      | -23.00     | 42.38      | 5.12       | 38.78          | 35.28         | Peak    | 100   | 311   | VERTICAL  |

|               |               |                |                                                                  |
|---------------|---------------|----------------|------------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                              |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 20MHz CH 157 /<br>Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 3                                                           |

### Horizontal

|   | Freq     | Level  | Limit<br>Line | Over<br>Limit | Read<br>Level | CableAntenna<br>Loss Factor | Preamp<br>Factor | Remark        | A/Pos | T/Pos | Pol/Phase  |
|---|----------|--------|---------------|---------------|---------------|-----------------------------|------------------|---------------|-------|-------|------------|
|   | MHz      | dBuV/m | dBuV/m        | dB            | dBuV          | dB                          | dB/m             | dB            | cm    | deg   |            |
| 1 | 11567.88 | 41.13  | 54.00         | -12.87        | 32.47         | 5.13                        | 38.83            | 35.30 Average | 100   | 368   | HORIZONTAL |
| 2 | 11568.44 | 53.44  | 74.00         | -20.56        | 44.78         | 5.13                        | 38.83            | 35.30 Peak    | 100   | 368   | HORIZONTAL |

### Vertical

|   | Freq     | Level  | Limit<br>Line | Over<br>Limit | Read<br>Level | CableAntenna<br>Loss Factor | Preamp<br>Factor | Remark        | A/Pos | T/Pos | Pol/Phase |
|---|----------|--------|---------------|---------------|---------------|-----------------------------|------------------|---------------|-------|-------|-----------|
|   | MHz      | dBuV/m | dBuV/m        | dB            | dBuV          | dB                          | dB/m             | dB            | cm    | deg   |           |
| 1 | 11567.76 | 41.72  | 54.00         | -12.28        | 33.06         | 5.13                        | 38.83            | 35.30 Average | 100   | 333   | VERTICAL  |
| 2 | 11568.00 | 54.90  | 74.00         | -19.10        | 46.24         | 5.13                        | 38.83            | 35.30 Peak    | 100   | 333   | VERTICAL  |

|               |               |                |                                                               |
|---------------|---------------|----------------|---------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                           |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 20MHz CH 165 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 3                                                        |

### Horizontal

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 11648.24 | 40.35  | 54.00      | -13.65     | 31.63      | 5.16       | 38.86          | 35.30         | Average | 101   | 10    | HORIZONTAL |
| 2 | 11649.08 | 53.04  | 74.00      | -20.96     | 44.32      | 5.16       | 38.86          | 35.30         | Peak    | 101   | 10    | HORIZONTAL |

### Vertical

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 11647.96 | 41.85  | 54.00      | -12.15     | 33.13      | 5.16       | 38.86          | 35.30         | Average | 101   | 4     | VERTICAL  |
| 2 | 11650.56 | 54.48  | 74.00      | -19.52     | 45.76      | 5.16       | 38.86          | 35.30         | Peak    | 101   | 4     | VERTICAL  |

|               |               |                |                                                               |
|---------------|---------------|----------------|---------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                           |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 40MHz CH 151 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 3                                                        |

### Horizontal

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 11500.16 | 35.71  | 54.00      | -18.29     | 27.08      | 5.12       | 38.79          | 35.28         | Average | 130   | 349   | HORIZONTAL |
| 2 | 11503.24 | 49.03  | 74.00      | -24.97     | 40.40      | 5.12       | 38.79          | 35.28         | Peak    | 130   | 349   | HORIZONTAL |

### Vertical

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 11508.64 | 50.49  | 74.00      | -23.51     | 41.86      | 5.12       | 38.79          | 35.28         | Peak    | 129   | 177   | VERTICAL  |
| 2 | 11509.60 | 36.94  | 54.00      | -17.06     | 28.31      | 5.12       | 38.79          | 35.28         | Average | 129   | 177   | VERTICAL  |

|               |               |                |                                                               |
|---------------|---------------|----------------|---------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                           |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11n MCS0 40MHz CH 159 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 3                                                        |

### Horizontal

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 11587.16 | 48.02  | 74.00      | -25.98     | 39.35      | 5.14       | 38.83          | 35.30         | Peak    | 106   | 57    | HORIZONTAL |
| 2 | 11590.12 | 36.19  | 54.00      | -17.81     | 27.52      | 5.14       | 38.83          | 35.30         | Average | 106   | 57    | HORIZONTAL |

### Vertical

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 11585.64 | 52.65  | 74.00      | -21.35     | 43.98      | 5.14       | 38.83          | 35.30         | Peak    | 129   | 343   | VERTICAL  |
| 2 | 11587.20 | 39.06  | 54.00      | -14.94     | 30.39      | 5.14       | 38.83          | 35.30         | Average | 129   | 343   | VERTICAL  |



|               |               |                |                                                    |
|---------------|---------------|----------------|----------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11a CH 149 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 3                                             |

#### Horizontal

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 11489.18 | 37.14  | 54.00      | -16.86     | 28.53      | 5.11       | 38.78          | 35.28         | Average | 105   | 360   | HORIZONTAL |
| 2 | 11489.42 | 52.47  | 74.00      | -21.53     | 43.86      | 5.11       | 38.78          | 35.28         | Peak    | 105   | 360   | HORIZONTAL |

#### Vertical

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 11489.14 | 53.85  | 74.00      | -20.15     | 45.24      | 5.11       | 38.78          | 35.28         | Peak    | 113   | 350   | VERTICAL  |
| 2 | 11489.16 | 39.27  | 54.00      | -14.73     | 30.66      | 5.11       | 38.78          | 35.28         | Average | 113   | 350   | VERTICAL  |

|               |               |                |                                                    |
|---------------|---------------|----------------|----------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11a CH 157 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 3                                             |

#### Horizontal

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 11568.40 | 52.62  | 74.00      | -21.38     | 43.96      | 5.13       | 38.83          | 35.30         | Peak    | 109   | 5     | HORIZONTAL |
| 2 | 11569.70 | 38.38  | 54.00      | -15.62     | 29.72      | 5.13       | 38.83          | 35.30         | Average | 109   | 5     | HORIZONTAL |

#### Vertical

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 11569.10 | 41.14  | 54.00      | -12.86     | 32.48      | 5.13       | 38.83          | 35.30         | Average | 139   | 359   | VERTICAL  |
| 2 | 11569.10 | 56.41  | 74.00      | -17.59     | 47.75      | 5.13       | 38.83          | 35.30         | Peak    | 139   | 359   | VERTICAL  |

|               |               |                |                                                    |
|---------------|---------------|----------------|----------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                |
| Test Engineer | Benson Peng   | Configurations | IEEE 802.11a CH 165 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Nov. 23, 2011 | Test Mode      | Mode 3                                             |

#### Horizontal

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 11648.46 | 52.78  | 74.00      | -21.22     | 44.06      | 5.16       | 38.86          | 35.30         | Peak    | 102   | 8     | HORIZONTAL |
| 2 | 11649.20 | 38.44  | 54.00      | -15.56     | 29.72      | 5.16       | 38.86          | 35.30         | Average | 102   | 8     | HORIZONTAL |

#### Vertical

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|----------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 11648.84 | 41.15  | 54.00      | -12.85     | 32.43      | 5.16       | 38.86          | 35.30         | Average | 100   | 202   | VERTICAL  |
| 2 | 11653.06 | 55.37  | 74.00      | -18.63     | 46.65      | 5.16       | 38.86          | 35.30         | Peak    | 100   | 202   | VERTICAL  |

#### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS0 20MHz Ch 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4814.12 | 29.65  | 54.00      | -24.35     | 28.36      | 3.31       | 33.02          | 35.04         | Average | 100   | 62    | HORIZONTAL |
| 2 | 4824.76 | 42.51  | 74.00      | -31.49     | 41.17      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 62    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4814.00 | 29.59  | 54.00      | -24.41     | 28.30      | 3.31       | 33.02          | 35.04         | Average | 100   | 236   | VERTICAL  |
| 2 | 4821.76 | 42.46  | 74.00      | -31.54     | 41.12      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 236   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS0 20MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4872.28 | 45.72  | 74.00      | -28.28     | 44.26      | 3.33       | 33.16          | 35.03         | Peak    | 125   | 177   | HORIZONTAL |
| 2 | 4872.68 | 31.42  | 54.00      | -22.58     | 29.96      | 3.33       | 33.16          | 35.03         | Average | 125   | 177   | HORIZONTAL |
| 3 | 7301.36 | 32.03  | 54.00      | -21.97     | 27.45      | 4.06       | 35.92          | 35.40         | Average | 100   | 131   | HORIZONTAL |
| 4 | 7301.56 | 45.43  | 74.00      | -28.57     | 40.85      | 4.06       | 35.92          | 35.40         | Peak    | 100   | 131   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4874.16 | 32.78  | 54.00      | -21.22     | 31.32      | 3.33       | 33.16          | 35.03         | Average | 100   | 70    | VERTICAL  |
| 2 | 4874.80 | 46.67  | 74.00      | -27.33     | 45.21      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 70    | VERTICAL  |
| 3 | 7301.84 | 32.03  | 54.00      | -21.97     | 27.45      | 4.06       | 35.92          | 35.40         | Average | 100   | 220   | VERTICAL  |
| 4 | 7308.04 | 46.31  | 74.00      | -27.69     | 41.69      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 220   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS0 20MHz Ch11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4914.12 | 29.37  | 54.00      | -24.63     | 27.82      | 3.34       | 33.23          | 35.02         | Average | 100   | 296   | HORIZONTAL |
| 2 | 4916.08 | 43.08  | 74.00      | -30.92     | 41.52      | 3.35       | 33.23          | 35.02         | Peak    | 100   | 296   | HORIZONTAL |
| 3 | 7390.76 | 46.05  | 74.00      | -27.95     | 41.30      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 114   | HORIZONTAL |
| 4 | 7395.00 | 32.69  | 54.00      | -21.31     | 27.90      | 4.06       | 36.13          | 35.40         | Average | 100   | 114   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4914.00 | 29.33  | 54.00      | -24.67     | 27.78      | 3.34       | 33.23          | 35.02         | Average | 100   | 83    | VERTICAL  |
| 2 | 4919.48 | 43.40  | 74.00      | -30.60     | 41.84      | 3.35       | 33.23          | 35.02         | Peak    | 100   | 83    | VERTICAL  |
| 3 | 7394.92 | 47.22  | 74.00      | -26.78     | 42.43      | 4.06       | 36.13          | 35.40         | Peak    | 100   | 260   | VERTICAL  |
| 4 | 7395.32 | 32.67  | 54.00      | -21.33     | 27.88      | 4.06       | 36.13          | 35.40         | Average | 100   | 260   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS0 40MHz Ch 3 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4845.36 | 43.39  | 74.00      | -30.61     | 42.01      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 273   | HORIZONTAL |
| 2 | 4849.68 | 29.36  | 54.00      | -24.64     | 27.98      | 3.32       | 33.09          | 35.03         | Average | 100   | 273   | HORIZONTAL |
| 3 | 7266.20 | 46.23  | 74.00      | -27.77     | 41.72      | 4.06       | 35.85          | 35.40         | Peak    | 100   | 141   | HORIZONTAL |
| 4 | 7275.64 | 32.34  | 54.00      | -21.66     | 27.79      | 4.06       | 35.89          | 35.40         | Average | 100   | 141   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4848.60 | 29.38  | 54.00      | -24.62     | 28.00      | 3.32       | 33.09          | 35.03         | Average | 100   | 111   | VERTICAL  |
| 2 | 4852.80 | 43.19  | 74.00      | -30.81     | 41.81      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 111   | VERTICAL  |
| 3 | 7266.64 | 45.65  | 74.00      | -28.35     | 41.14      | 4.06       | 35.85          | 35.40         | Peak    | 100   | 239   | VERTICAL  |
| 4 | 7274.96 | 32.21  | 54.00      | -21.79     | 27.66      | 4.06       | 35.89          | 35.40         | Average | 100   | 239   | VERTICAL  |



|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS0 40MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4865.96 | 42.66  | 74.00      | -31.34     | 41.24      | 3.33       | 33.12          | 35.03         | Peak    | 100   | 322   | HORIZONTAL |
| 2 | 4873.96 | 29.39  | 54.00      | -24.61     | 27.93      | 3.33       | 33.16          | 35.03         | Average | 100   | 322   | HORIZONTAL |
| 3 | 7302.12 | 32.07  | 54.00      | -21.93     | 27.49      | 4.06       | 35.92          | 35.40         | Average | 100   | 124   | HORIZONTAL |
| 4 | 7305.20 | 45.56  | 74.00      | -28.44     | 40.98      | 4.06       | 35.92          | 35.40         | Peak    | 100   | 124   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4874.16 | 29.69  | 54.00      | -24.31     | 28.23      | 3.33       | 33.16          | 35.03         | Average | 100   | 127   | VERTICAL  |
| 2 | 4878.24 | 43.04  | 74.00      | -30.96     | 41.58      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 127   | VERTICAL  |
| 3 | 7301.76 | 32.07  | 54.00      | -21.93     | 27.49      | 4.06       | 35.92          | 35.40         | Average | 100   | 263   | VERTICAL  |
| 4 | 7311.08 | 45.17  | 74.00      | -28.83     | 40.55      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 263   | VERTICAL  |



|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS0 40MHz Ch 9 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4900.60 | 29.75  | 54.00      | -24.25     | 28.24      | 3.34       | 33.19          | 35.02         | Average | 100   | 83    | HORIZONTAL |
| 2 | 4908.12 | 43.36  | 74.00      | -30.64     | 41.81      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 83    | HORIZONTAL |
| 3 | 7354.48 | 32.43  | 54.00      | -21.57     | 27.75      | 4.06       | 36.02          | 35.40         | Average | 100   | 49    | HORIZONTAL |
| 4 | 7360.16 | 46.07  | 74.00      | -27.93     | 41.35      | 4.06       | 36.06          | 35.40         | Peak    | 100   | 49    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4907.86 | 30.83  | 54.00      | -23.17     | 29.28      | 3.34       | 33.23          | 35.02         | Average | 100   | 241   | VERTICAL  |
| 2 | 4908.92 | 43.55  | 74.00      | -30.45     | 42.00      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 241   | VERTICAL  |
| 3 | 7351.40 | 46.37  | 74.00      | -27.63     | 41.69      | 4.06       | 36.02          | 35.40         | Peak    | 100   | 219   | VERTICAL  |
| 4 | 7357.24 | 32.44  | 54.00      | -21.56     | 27.76      | 4.06       | 36.02          | 35.40         | Average | 100   | 219   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS8 20MHz Ch 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4823.76 | 28.73  | 54.00      | -25.27     | 27.39      | 3.31       | 33.06          | 35.03         | Average | 100   | 230   | HORIZONTAL |
| 2 | 4826.37 | 41.48  | 74.00      | -32.52     | 40.14      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 230   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4823.12 | 41.72  | 74.00      | -32.28     | 40.38      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 114   | VERTICAL  |
| 2 | 4825.75 | 28.88  | 54.00      | -25.12     | 27.54      | 3.31       | 33.06          | 35.03         | Average | 100   | 114   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS8 20MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4874.28 | 45.31  | 74.00      | -28.69     | 43.85      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 160   | HORIZONTAL |
| 2 | 4874.66 | 32.44  | 54.00      | -21.56     | 30.98      | 3.33       | 33.16          | 35.03         | Average | 100   | 160   | HORIZONTAL |
| 3 | 7307.96 | 45.07  | 74.00      | -28.93     | 40.45      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 68    | HORIZONTAL |
| 4 | 7313.53 | 32.36  | 54.00      | -21.64     | 27.74      | 4.06       | 35.96          | 35.40         | Average | 100   | 68    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4873.20 | 33.44  | 54.00      | -20.56     | 31.98      | 3.33       | 33.16          | 35.03         | Average | 100   | 164   | VERTICAL  |
| 2 | 4874.72 | 47.01  | 74.00      | -26.99     | 45.55      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 164   | VERTICAL  |
| 3 | 7306.83 | 32.34  | 54.00      | -21.66     | 27.76      | 4.06       | 35.92          | 35.40         | Average | 100   | 188   | VERTICAL  |
| 4 | 7313.76 | 46.08  | 74.00      | -27.92     | 41.46      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 188   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS8 20MHz Ch11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4915.38 | 41.92  | 74.00      | -32.08     | 40.36      | 3.35       | 33.23          | 35.02         | Peak    | 100   | 283   | HORIZONTAL |
| 2 | 4924.03 | 28.39  | 54.00      | -25.61     | 26.79      | 3.35       | 33.26          | 35.01         | Average | 100   | 283   | HORIZONTAL |
| 3 | 7378.79 | 32.68  | 54.00      | -21.32     | 27.93      | 4.06       | 36.09          | 35.40         | Average | 100   | 127   | HORIZONTAL |
| 4 | 7392.12 | 45.43  | 74.00      | -28.57     | 40.68      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 127   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4923.25 | 29.01  | 54.00      | -24.99     | 27.41      | 3.35       | 33.26          | 35.01         | Average | 100   | 240   | VERTICAL  |
| 2 | 4924.58 | 40.98  | 74.00      | -33.02     | 39.38      | 3.35       | 33.26          | 35.01         | Peak    | 100   | 240   | VERTICAL  |
| 3 | 7382.60 | 45.09  | 74.00      | -28.91     | 40.34      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 105   | VERTICAL  |
| 4 | 7395.26 | 32.70  | 54.00      | -21.30     | 27.91      | 4.06       | 36.13          | 35.40         | Average | 100   | 105   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS8 40MHz Ch 3 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4846.81 | 41.61  | 74.00      | -32.39     | 40.23      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 183   | HORIZONTAL |
| 2 | 4848.78 | 29.07  | 54.00      | -24.93     | 27.69      | 3.32       | 33.09          | 35.03         | Average | 100   | 183   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4848.44 | 41.92  | 74.00      | -32.08     | 40.54      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 124   | VERTICAL  |
| 2 | 4848.90 | 29.16  | 54.00      | -24.84     | 27.78      | 3.32       | 33.09          | 35.03         | Average | 100   | 124   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS8 40MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4875.70 | 29.26  | 54.00      | -24.74     | 27.80      | 3.33       | 33.16          | 35.03         | Average | 100   | 261   | HORIZONTAL |
| 2 | 4876.69 | 42.02  | 74.00      | -31.98     | 40.56      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 261   | HORIZONTAL |
| 3 | 7301.43 | 46.01  | 74.00      | -27.99     | 41.43      | 4.06       | 35.92          | 35.40         | Peak    | 100   | 144   | HORIZONTAL |
| 4 | 7306.48 | 32.71  | 54.00      | -21.29     | 28.13      | 4.06       | 35.92          | 35.40         | Average | 100   | 144   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4875.14 | 29.63  | 54.00      | -24.37     | 28.17      | 3.33       | 33.16          | 35.03         | Average | 100   | 113   | VERTICAL  |
| 2 | 4875.57 | 42.07  | 74.00      | -31.93     | 40.61      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 113   | VERTICAL  |
| 3 | 7304.46 | 45.65  | 74.00      | -28.35     | 41.07      | 4.06       | 35.92          | 35.40         | Peak    | 100   | 272   | VERTICAL  |
| 4 | 7308.98 | 32.66  | 54.00      | -21.34     | 28.04      | 4.06       | 35.96          | 35.40         | Average | 100   | 272   | VERTICAL  |

|               |               |                |                                                                |
|---------------|---------------|----------------|----------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                            |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11n MCS8 40MHz Ch 9 /<br>Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                                         |

### Horizontal

|   | Freq    | Level  | Limit<br>Line | Over<br>Limit | Read<br>Level | Cable<br>Loss | Antenna<br>Factor | Preamp<br>Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|---------------|---------------|---------------|---------------|-------------------|------------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m        | dB            | dBuV          | dB            | dB/m              | dB               |         | cm    | deg   |            |
| 1 | 4902.13 | 29.29  | 54.00         | -24.71        | 27.78         | 3.34          | 33.19             | 35.02            | Average | 100   | 287   | HORIZONTAL |
| 2 | 4903.41 | 42.50  | 74.00         | -31.50        | 40.99         | 3.34          | 33.19             | 35.02            | Peak    | 100   | 287   | HORIZONTAL |
| 3 | 7357.57 | 32.54  | 54.00         | -21.46        | 27.86         | 4.06          | 36.02             | 35.40            | Average | 100   | 199   | HORIZONTAL |
| 4 | 7360.28 | 45.00  | 74.00         | -29.00        | 40.28         | 4.06          | 36.06             | 35.40            | Peak    | 100   | 199   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit<br>Line | Over<br>Limit | Read<br>Level | Cable<br>Loss | Antenna<br>Factor | Preamp<br>Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|---------------|---------------|---------------|---------------|-------------------|------------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m        | dB            | dBuV          | dB            | dB/m              | dB               |         | cm    | deg   |           |
| 1 | 4901.05 | 28.94  | 54.00         | -25.06        | 27.43         | 3.34          | 33.19             | 35.02            | Average | 100   | 189   | VERTICAL  |
| 2 | 4904.77 | 41.46  | 74.00         | -32.54        | 39.91         | 3.34          | 33.23             | 35.02            | Peak    | 100   | 189   | VERTICAL  |
| 3 | 7353.34 | 45.47  | 74.00         | -28.53        | 40.79         | 4.06          | 36.02             | 35.40            | Peak    | 100   | 92    | VERTICAL  |
| 4 | 7358.76 | 32.71  | 54.00         | -21.29        | 27.99         | 4.06          | 36.06             | 35.40            | Average | 100   | 92    | VERTICAL  |



|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11b CH 1 / Chain 2 (1TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                 |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4823.79 | 28.98  | 54.00      | -25.02     | 27.64      | 3.31       | 33.06          | 35.03         | Average | 102   | 96    | HORIZONTAL |
| 2 | 4823.97 | 41.62  | 74.00      | -32.38     | 40.28      | 3.31       | 33.06          | 35.03         | Peak    | 102   | 96    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4823.79 | 43.53  | 74.00      | -30.47     | 42.19      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 209   | VERTICAL  |
| 2 | 4823.96 | 32.83  | 54.00      | -21.17     | 31.49      | 3.31       | 33.06          | 35.03         | Average | 100   | 209   | VERTICAL  |



|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11b CH 6 / Chain 2 (1TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                 |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4873.96 | 30.46  | 54.00      | -23.54     | 29.00      | 3.33       | 33.16          | 35.03         | Average | 101   | 142   | HORIZONTAL |
| 2 | 4874.08 | 43.33  | 74.00      | -30.67     | 41.87      | 3.33       | 33.16          | 35.03         | Peak    | 101   | 142   | HORIZONTAL |
| 3 | 7310.84 | 45.22  | 74.00      | -28.78     | 40.60      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 167   | HORIZONTAL |
| 4 | 7311.06 | 32.56  | 54.00      | -21.44     | 27.94      | 4.06       | 35.96          | 35.40         | Average | 100   | 167   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4873.85 | 43.24  | 74.00      | -30.76     | 41.78      | 3.33       | 33.16          | 35.03         | Peak    | 103   | 145   | VERTICAL  |
| 2 | 4873.96 | 31.97  | 54.00      | -22.03     | 30.51      | 3.33       | 33.16          | 35.03         | Average | 103   | 145   | VERTICAL  |
| 3 | 7311.06 | 45.76  | 74.00      | -28.24     | 41.14      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 197   | VERTICAL  |
| 4 | 7311.96 | 32.42  | 54.00      | -21.58     | 27.80      | 4.06       | 35.96          | 35.40         | Average | 100   | 197   | VERTICAL  |

|               |               |                |                                         |
|---------------|---------------|----------------|-----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                     |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11b CH 11 / Chain 2 (1TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                  |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4923.96 | 34.03  | 54.00      | -19.97     | 32.43      | 3.35       | 33.26          | 35.01         | Average | 123   | 145   | HORIZONTAL |
| 2 | 4924.08 | 43.96  | 74.00      | -30.04     | 42.36      | 3.35       | 33.26          | 35.01         | Peak    | 123   | 145   | HORIZONTAL |
| 3 | 7386.71 | 45.04  | 74.00      | -28.96     | 40.29      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 165   | HORIZONTAL |
| 4 | 7387.00 | 32.71  | 54.00      | -21.29     | 27.96      | 4.06       | 36.09          | 35.40         | Average | 100   | 165   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4923.79 | 44.94  | 74.00      | -29.06     | 43.34      | 3.35       | 33.26          | 35.01         | Peak    | 100   | 218   | VERTICAL  |
| 2 | 4923.96 | 37.34  | 54.00      | -16.66     | 35.74      | 3.35       | 33.26          | 35.01         | Average | 100   | 218   | VERTICAL  |
| 3 | 7385.57 | 45.71  | 74.00      | -28.29     | 40.96      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 123   | VERTICAL  |
| 4 | 7385.66 | 32.76  | 54.00      | -21.24     | 28.01      | 4.06       | 36.09          | 35.40         | Average | 100   | 123   | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11g CH 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4821.44 | 40.25  | 74.00      | -33.75     | 38.91      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 196   | HORIZONTAL |
| 2 | 4827.44 | 28.04  | 54.00      | -25.96     | 26.70      | 3.31       | 33.06          | 35.03         | Average | 100   | 196   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4824.50 | 40.96  | 74.00      | -33.04     | 39.62      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 304   | VERTICAL  |
| 2 | 4826.64 | 28.84  | 54.00      | -25.16     | 27.50      | 3.31       | 33.06          | 35.03         | Average | 100   | 304   | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11g CH 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4871.58 | 30.20  | 54.00      | -23.80     | 28.74      | 3.33       | 33.16          | 35.03         | Average | 100   | 5     | HORIZONTAL |
| 2 | 4876.50 | 42.08  | 74.00      | -31.92     | 40.62      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 5     | HORIZONTAL |
| 3 | 7315.16 | 43.46  | 74.00      | -30.54     | 38.84      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 236   | HORIZONTAL |
| 4 | 7318.12 | 30.78  | 54.00      | -23.22     | 26.16      | 4.06       | 35.96          | 35.40         | Average | 100   | 236   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4872.82 | 46.11  | 74.00      | -27.89     | 44.65      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 200   | VERTICAL  |
| 2 | 4873.30 | 32.20  | 54.00      | -21.80     | 30.74      | 3.33       | 33.16          | 35.03         | Average | 100   | 200   | VERTICAL  |
| 3 | 7311.52 | 30.75  | 54.00      | -23.25     | 26.13      | 4.06       | 35.96          | 35.40         | Average | 100   | 113   | VERTICAL  |
| 4 | 7311.52 | 44.00  | 74.00      | -30.00     | 39.38      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 113   | VERTICAL  |

|               |               |                |                                                   |
|---------------|---------------|----------------|---------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                               |
| Test Engineer | Wen Chao      | Configurations | IEEE 802.11g CH 11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Jan. 30, 2012 | Test Mode      | Mode 4                                            |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4923.92 | 28.04  | 54.00      | -25.96     | 26.44      | 3.35       | 33.26          | 35.01         | Average | 100   | 115   | HORIZONTAL |
| 2 | 4924.18 | 40.36  | 74.00      | -33.64     | 38.76      | 3.35       | 33.26          | 35.01         | Peak    | 100   | 115   | HORIZONTAL |
| 3 | 7386.28 | 31.19  | 54.00      | -22.81     | 26.44      | 4.06       | 36.09          | 35.40         | Average | 100   | 222   | HORIZONTAL |
| 4 | 7386.52 | 43.76  | 74.00      | -30.24     | 39.01      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 222   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4924.44 | 29.24  | 54.00      | -24.76     | 27.64      | 3.35       | 33.26          | 35.01         | Average | 114   | 223   | VERTICAL  |
| 2 | 4924.80 | 42.15  | 74.00      | -31.85     | 40.55      | 3.35       | 33.26          | 35.01         | Peak    | 114   | 223   | VERTICAL  |
| 3 | 7385.26 | 31.52  | 54.00      | -22.48     | 26.77      | 4.06       | 36.09          | 35.40         | Average | 100   | 178   | VERTICAL  |
| 4 | 7387.04 | 44.24  | 74.00      | -29.76     | 39.49      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 178   | VERTICAL  |

### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5          | Humidity       | 56%                                              |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 20MHz Ch 1 / Chain 1 (1X, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4913.30 | 30.72  | 54.00      | -23.28     | 29.17      | 3.34       | 33.23          | 35.02         | Average | 100   | 213   | HORIZONTAL |
| 2 | 4924.90 | 43.52  | 74.00      | -30.48     | 41.92      | 3.35       | 33.26          | 35.01         | Peak    | 100   | 213   | HORIZONTAL |
| 3 | 7389.80 | 34.61  | 54.00      | -19.39     | 29.86      | 4.06       | 36.09          | 35.40         | Average | 100   | 206   | HORIZONTAL |
| 4 | 7389.96 | 47.09  | 74.00      | -26.91     | 42.34      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 206   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4912.40 | 30.75  | 54.00      | -23.25     | 29.20      | 3.34       | 33.23          | 35.02         | Average | 100   | 113   | VERTICAL  |
| 2 | 4914.60 | 43.79  | 74.00      | -30.21     | 42.23      | 3.35       | 33.23          | 35.02         | Peak    | 100   | 113   | VERTICAL  |
| 3 | 7382.94 | 34.72  | 54.00      | -19.28     | 29.97      | 4.06       | 36.09          | 35.40         | Average | 100   | 182   | VERTICAL  |
| 4 | 7385.26 | 47.93  | 74.00      | -26.07     | 43.18      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 182   | VERTICAL  |



|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 20MHz Ch 6 / Chain 1 (1X, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4873.34 | 30.73  | 54.00      | -23.27     | 29.27      | 3.33       | 33.16          | 35.03         | Average | 100   | 222   | HORIZONTAL |
| 2 | 4876.36 | 43.27  | 74.00      | -30.73     | 41.81      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 222   | HORIZONTAL |
| 3 | 7306.96 | 33.56  | 54.00      | -20.44     | 28.98      | 4.06       | 35.92          | 35.40         | Average | 100   | 175   | HORIZONTAL |
| 4 | 7308.64 | 47.44  | 74.00      | -26.56     | 42.82      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 175   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4873.84 | 43.71  | 74.00      | -30.29     | 42.25      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 87    | VERTICAL  |
| 2 | 4875.72 | 31.00  | 54.00      | -23.00     | 29.54      | 3.33       | 33.16          | 35.03         | Average | 100   | 87    | VERTICAL  |
| 3 | 7301.70 | 34.36  | 54.00      | -19.64     | 29.78      | 4.06       | 35.92          | 35.40         | Average | 100   | 234   | VERTICAL  |
| 4 | 7302.90 | 47.23  | 74.00      | -26.77     | 42.65      | 4.06       | 35.92          | 35.40         | Peak    | 100   | 234   | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 20MHz Ch11 / Chain 1 (1X, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4823.28 | 43.74  | 74.00      | -30.26     | 42.40      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 162   | HORIZONTAL |
| 2 | 4827.00 | 30.88  | 54.00      | -23.12     | 29.54      | 3.31       | 33.06          | 35.03         | Average | 100   | 162   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4825.74 | 30.82  | 54.00      | -23.18     | 29.48      | 3.31       | 33.06          | 35.03         | Average | 100   | 215   | VERTICAL  |
| 2 | 4825.86 | 44.27  | 74.00      | -29.73     | 42.93      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 215   | VERTICAL  |



|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 40MHz Ch 3 / Chain 1 (1X, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                           |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4844.58 | 43.72  | 74.00      | -30.28     | 42.34      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 210   | HORIZONTAL |
| 2 | 4848.20 | 30.54  | 54.00      | -23.46     | 29.16      | 3.32       | 33.09          | 35.03         | Average | 100   | 210   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4844.72 | 43.17  | 74.00      | -30.83     | 41.79      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 90    | VERTICAL  |
| 2 | 4847.46 | 30.72  | 54.00      | -23.28     | 29.34      | 3.32       | 33.09          | 35.03         | Average | 100   | 90    | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 40MHz Ch 6 / Chain 1 (1X, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4873.48 | 30.81  | 54.00      | -23.19     | 29.35      | 3.33       | 33.16          | 35.03         | Average | 100   | 260   | HORIZONTAL |
| 2 | 4873.54 | 43.15  | 74.00      | -30.85     | 41.69      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 260   | HORIZONTAL |
| 3 | 7311.68 | 46.37  | 74.00      | -27.63     | 41.75      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 170   | HORIZONTAL |
| 4 | 7312.54 | 33.55  | 54.00      | -20.45     | 28.93      | 4.06       | 35.96          | 35.40         | Average | 100   | 170   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4873.86 | 43.30  | 74.00      | -30.70     | 41.84      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 72    | VERTICAL  |
| 2 | 4876.02 | 30.90  | 54.00      | -23.10     | 29.44      | 3.33       | 33.16          | 35.03         | Average | 100   | 72    | VERTICAL  |
| 3 | 7307.26 | 33.57  | 54.00      | -20.43     | 28.99      | 4.06       | 35.92          | 35.40         | Average | 100   | 216   | VERTICAL  |
| 4 | 7308.96 | 46.61  | 74.00      | -27.39     | 41.99      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 216   | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 40MHz Ch 9 / Chain 1 (1X, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4901.82 | 43.42  | 74.00      | -30.58     | 41.91      | 3.34       | 33.19          | 35.02         | Peak    | 100   | 143   | HORIZONTAL |
| 2 | 4903.16 | 31.00  | 54.00      | -23.00     | 29.49      | 3.34       | 33.19          | 35.02         | Average | 100   | 143   | HORIZONTAL |
| 3 | 7352.76 | 46.72  | 74.00      | -27.28     | 42.04      | 4.06       | 36.02          | 35.40         | Peak    | 100   | 183   | HORIZONTAL |
| 4 | 7356.28 | 33.85  | 54.00      | -20.15     | 29.17      | 4.06       | 36.02          | 35.40         | Average | 100   | 183   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4900.56 | 31.17  | 54.00      | -22.83     | 29.66      | 3.34       | 33.19          | 35.02         | Average | 100   | 247   | VERTICAL  |
| 2 | 4907.22 | 43.90  | 74.00      | -30.10     | 42.35      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 247   | VERTICAL  |
| 3 | 7353.54 | 33.87  | 54.00      | -20.13     | 29.19      | 4.06       | 36.02          | 35.40         | Average | 100   | 245   | VERTICAL  |
| 4 | 7356.64 | 46.89  | 74.00      | -27.11     | 42.21      | 4.06       | 36.02          | 35.40         | Peak    | 100   | 245   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5          | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 20MHz Ch 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4923.24 | 42.82  | 74.00      | -31.18     | 41.22      | 3.35       | 33.26          | 35.01         | Peak    | 100   | 155   | HORIZONTAL |
| 2 | 4924.32 | 30.12  | 54.00      | -23.88     | 28.52      | 3.35       | 33.26          | 35.01         | Average | 100   | 155   | HORIZONTAL |
| 3 | 7386.68 | 34.11  | 54.00      | -19.89     | 29.36      | 4.06       | 36.09          | 35.40         | Average | 100   | 259   | HORIZONTAL |
| 4 | 7387.56 | 46.29  | 74.00      | -27.71     | 41.54      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 259   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4923.52 | 30.59  | 54.00      | -23.41     | 28.99      | 3.35       | 33.26          | 35.01         | Average | 100   | 247   | VERTICAL  |
| 2 | 4924.60 | 43.49  | 74.00      | -30.51     | 41.89      | 3.35       | 33.26          | 35.01         | Peak    | 100   | 247   | VERTICAL  |
| 3 | 7386.00 | 34.20  | 54.00      | -19.80     | 29.45      | 4.06       | 36.09          | 35.40         | Average | 100   | 182   | VERTICAL  |
| 4 | 7386.80 | 46.21  | 74.00      | -27.79     | 41.46      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 182   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 20MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4874.12 | 30.63  | 54.00      | -23.37     | 29.17      | 3.33       | 33.16          | 35.03         | Average | 100   | 134   | HORIZONTAL |
| 2 | 4875.16 | 43.63  | 74.00      | -30.37     | 42.17      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 134   | HORIZONTAL |
| 3 | 7310.64 | 46.27  | 74.00      | -27.73     | 41.65      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 227   | HORIZONTAL |
| 4 | 7310.96 | 33.25  | 54.00      | -20.75     | 28.63      | 4.06       | 35.96          | 35.40         | Average | 100   | 227   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4873.08 | 43.27  | 74.00      | -30.73     | 41.81      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 218   | VERTICAL  |
| 2 | 4874.32 | 30.87  | 54.00      | -23.13     | 29.41      | 3.33       | 33.16          | 35.03         | Average | 100   | 218   | VERTICAL  |
| 3 | 7311.40 | 33.39  | 54.00      | -20.61     | 28.77      | 4.06       | 35.96          | 35.40         | Average | 100   | 120   | VERTICAL  |
| 4 | 7311.68 | 46.82  | 74.00      | -27.18     | 42.20      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 120   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 20MHz Ch11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4817.40 | 43.22  | 74.00      | -30.78     | 41.93      | 3.31       | 33.02          | 35.04         | Peak    | 100   | 145   | HORIZONTAL |
| 2 | 4824.56 | 30.80  | 54.00      | -23.20     | 29.46      | 3.31       | 33.06          | 35.03         | Average | 100   | 145   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4823.96 | 43.82  | 74.00      | -30.18     | 42.48      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 192   | VERTICAL  |
| 2 | 4824.44 | 30.67  | 54.00      | -23.33     | 29.33      | 3.31       | 33.06          | 35.03         | Average | 100   | 192   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 40MHz Ch 3 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4844.04 | 43.71  | 74.00      | -30.29     | 42.33      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 238   | HORIZONTAL |
| 2 | 4844.28 | 30.56  | 54.00      | -23.44     | 29.18      | 3.32       | 33.09          | 35.03         | Average | 100   | 238   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4842.12 | 43.05  | 74.00      | -30.95     | 41.67      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 140   | VERTICAL  |
| 2 | 4843.28 | 30.43  | 54.00      | -23.57     | 29.05      | 3.32       | 33.09          | 35.03         | Average | 100   | 140   | VERTICAL  |



|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 40MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4873.00 | 30.95  | 54.00      | -23.05     | 29.49      | 3.33       | 33.16          | 35.03         | Average | 100   | 204   | HORIZONTAL |
| 2 | 4873.40 | 43.41  | 74.00      | -30.59     | 41.95      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 204   | HORIZONTAL |
| 3 | 7310.84 | 45.51  | 74.00      | -28.49     | 40.89      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 148   | HORIZONTAL |
| 4 | 7311.00 | 33.62  | 54.00      | -20.38     | 29.00      | 4.06       | 35.96          | 35.40         | Average | 100   | 148   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4874.10 | 43.15  | 74.00      | -30.85     | 41.69      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 165   | VERTICAL  |
| 2 | 4874.40 | 31.07  | 54.00      | -22.93     | 29.61      | 3.33       | 33.16          | 35.03         | Average | 100   | 165   | VERTICAL  |
| 3 | 7311.24 | 33.46  | 54.00      | -20.54     | 28.84      | 4.06       | 35.96          | 35.40         | Average | 100   | 216   | VERTICAL  |
| 4 | 7313.76 | 45.58  | 74.00      | -28.42     | 40.96      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 216   | VERTICAL  |



|               |               |                |                                                           |
|---------------|---------------|----------------|-----------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                       |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 40MHz Ch 9 / Chain 1+Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                    |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4901.79 | 30.79  | 54.00      | -23.21     | 29.28      | 3.34       | 33.19          | 35.02         | Average | 100   | 241   | HORIZONTAL |
| 2 | 4906.25 | 43.71  | 74.00      | -30.29     | 42.16      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 241   | HORIZONTAL |
| 3 | 7336.80 | 46.58  | 74.00      | -27.42     | 41.93      | 4.06       | 35.99          | 35.40         | Peak    | 100   | 165   | HORIZONTAL |
| 4 | 7339.90 | 33.64  | 54.00      | -20.36     | 28.99      | 4.06       | 35.99          | 35.40         | Average | 100   | 165   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4901.70 | 30.81  | 54.00      | -23.19     | 29.30      | 3.34       | 33.19          | 35.02         | Average | 100   | 162   | VERTICAL  |
| 2 | 4905.97 | 43.96  | 74.00      | -30.04     | 42.41      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 162   | VERTICAL  |
| 3 | 7335.30 | 33.68  | 54.00      | -20.32     | 29.03      | 4.06       | 35.99          | 35.40         | Average | 100   | 264   | VERTICAL  |
| 4 | 7339.30 | 46.18  | 74.00      | -27.82     | 41.53      | 4.06       | 35.99          | 35.40         | Peak    | 100   | 264   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5          | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS8 20MHz Ch 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4822.38 | 40.93  | 74.00      | -33.07     | 39.59      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 244   | HORIZONTAL |
| 2 | 4825.08 | 28.53  | 54.00      | -25.47     | 27.19      | 3.31       | 33.06          | 35.03         | Average | 100   | 244   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4822.43 | 41.05  | 74.00      | -32.95     | 39.71      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 118   | VERTICAL  |
| 2 | 4826.34 | 28.52  | 54.00      | -25.48     | 27.18      | 3.31       | 33.06          | 35.03         | Average | 100   | 118   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS8 20MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4875.60 | 41.87  | 74.00      | -32.13     | 40.41      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 132   | HORIZONTAL |
| 2 | 4875.96 | 28.60  | 54.00      | -25.40     | 27.14      | 3.33       | 33.16          | 35.03         | Average | 100   | 132   | HORIZONTAL |
| 3 | 7307.12 | 32.02  | 54.00      | -21.98     | 27.44      | 4.06       | 35.92          | 35.40         | Average | 100   | 166   | HORIZONTAL |
| 4 | 7315.54 | 44.43  | 74.00      | -29.57     | 39.81      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 166   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4873.69 | 41.81  | 74.00      | -32.19     | 40.35      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 224   | VERTICAL  |
| 2 | 4875.27 | 28.76  | 54.00      | -25.24     | 27.30      | 3.33       | 33.16          | 35.03         | Average | 100   | 224   | VERTICAL  |
| 3 | 7313.70 | 31.52  | 54.00      | -22.48     | 26.90      | 4.06       | 35.96          | 35.40         | Average | 100   | 119   | VERTICAL  |
| 4 | 7314.58 | 44.12  | 74.00      | -29.88     | 39.50      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 119   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS8 20MHz Ch11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4920.00 | 41.29  | 74.00      | -32.71     | 39.72      | 3.35       | 33.23          | 35.01         | Peak    | 100   | 159   | HORIZONTAL |
| 2 | 4922.32 | 28.71  | 54.00      | -25.29     | 27.11      | 3.35       | 33.26          | 35.01         | Average | 100   | 159   | HORIZONTAL |
| 3 | 7387.62 | 32.06  | 54.00      | -21.94     | 27.31      | 4.06       | 36.09          | 35.40         | Average | 100   | 263   | HORIZONTAL |
| 4 | 7389.78 | 44.68  | 74.00      | -29.32     | 39.93      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 263   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4920.76 | 41.53  | 74.00      | -32.47     | 39.96      | 3.35       | 33.23          | 35.01         | Peak    | 100   | 288   | VERTICAL  |
| 2 | 4925.22 | 29.05  | 54.00      | -24.95     | 27.45      | 3.35       | 33.26          | 35.01         | Average | 100   | 288   | VERTICAL  |
| 3 | 7383.44 | 44.67  | 74.00      | -29.33     | 39.92      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 163   | VERTICAL  |
| 4 | 7386.70 | 32.01  | 54.00      | -21.99     | 27.26      | 4.06       | 36.09          | 35.40         | Average | 100   | 163   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS8 40MHz Ch 3 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4842.40 | 41.20  | 74.00      | -32.80     | 39.82      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 208   | HORIZONTAL |
| 2 | 4849.00 | 28.59  | 54.00      | -25.41     | 27.21      | 3.32       | 33.09          | 35.03         | Average | 100   | 208   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4841.86 | 41.39  | 74.00      | -32.61     | 40.01      | 3.32       | 33.09          | 35.03         | Peak    | 100   | 258   | VERTICAL  |
| 2 | 4846.39 | 28.46  | 54.00      | -25.54     | 27.08      | 3.32       | 33.09          | 35.03         | Average | 100   | 258   | VERTICAL  |

|               |               |                |                                                             |
|---------------|---------------|----------------|-------------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                         |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS8 40MHz Ch 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                      |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4875.80 | 28.87  | 54.00      | -25.13     | 27.41      | 3.33       | 33.16          | 35.03         | Average | 100   | 253   | HORIZONTAL |
| 2 | 4877.48 | 41.39  | 74.00      | -32.61     | 39.93      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 253   | HORIZONTAL |
| 3 | 7308.32 | 44.56  | 74.00      | -29.44     | 39.94      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 159   | HORIZONTAL |
| 4 | 7315.84 | 31.65  | 54.00      | -22.35     | 27.03      | 4.06       | 35.96          | 35.40         | Average | 100   | 159   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4874.26 | 28.83  | 54.00      | -25.17     | 27.37      | 3.33       | 33.16          | 35.03         | Average | 100   | 158   | VERTICAL  |
| 2 | 4877.52 | 41.31  | 74.00      | -32.69     | 39.85      | 3.33       | 33.16          | 35.03         | Peak    | 100   | 158   | VERTICAL  |
| 3 | 7310.16 | 31.74  | 54.00      | -22.26     | 27.12      | 4.06       | 35.96          | 35.40         | Average | 100   | 272   | VERTICAL  |
| 4 | 7315.38 | 44.78  | 74.00      | -29.22     | 40.16      | 4.06       | 35.96          | 35.40         | Peak    | 100   | 272   | VERTICAL  |

|               |               |                |                                                           |
|---------------|---------------|----------------|-----------------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                                       |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS8 40MHz Ch 9 / Chain 1+Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                                    |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4911.16 | 28.86  | 54.00      | -25.14     | 27.31      | 3.34       | 33.23          | 35.02         | Average | 100   | 122   | HORIZONTAL |
| 2 | 4913.60 | 41.16  | 74.00      | -32.84     | 39.61      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 122   | HORIZONTAL |
| 3 | 7350.28 | 32.22  | 54.00      | -21.78     | 27.54      | 4.06       | 36.02          | 35.40         | Average | 100   | 246   | HORIZONTAL |
| 4 | 7360.00 | 44.31  | 74.00      | -29.69     | 39.59      | 4.06       | 36.06          | 35.40         | Peak    | 100   | 246   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4906.48 | 42.20  | 74.00      | -31.80     | 40.65      | 3.34       | 33.23          | 35.02         | Peak    | 100   | 277   | VERTICAL  |
| 2 | 4910.76 | 30.15  | 54.00      | -23.85     | 28.60      | 3.34       | 33.23          | 35.02         | Average | 100   | 277   | VERTICAL  |
| 3 | 7347.40 | 32.26  | 54.00      | -21.74     | 27.58      | 4.06       | 36.02          | 35.40         | Average | 100   | 155   | VERTICAL  |
| 4 | 7350.92 | 44.21  | 74.00      | -29.79     | 39.53      | 4.06       | 36.02          | 35.40         | Peak    | 100   | 155   | VERTICAL  |



|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11b CH 1 / Chain 1 (1TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                 |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4823.94 | 30.76  | 54.00      | -23.24     | 29.42      | 3.31       | 33.06          | 35.03         | Average | 100   | 29    | HORIZONTAL |
| 2 | 4824.19 | 42.38  | 74.00      | -31.62     | 41.04      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 29    | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4823.98 | 46.81  | 74.00      | -27.19     | 45.47      | 3.31       | 33.06          | 35.03         | Peak    | 116   | 305   | VERTICAL  |
| 2 | 4824.00 | 41.68  | 54.00      | -12.32     | 40.34      | 3.31       | 33.06          | 35.03         | Average | 116   | 305   | VERTICAL  |



|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11b CH 6 / Chain 1 (1TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                 |

### Horizontal

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     |         | cm    | deg   |            |
| 1 | 4873.99 | 32.17  | 54.00  | -21.83 | 30.71 | 3.33  | 33.16   | 35.03  | Average | 100   | 231   | HORIZONTAL |
| 2 | 4874.12 | 42.69  | 74.00  | -31.31 | 41.23 | 3.33  | 33.16   | 35.03  | Peak    | 100   | 231   | HORIZONTAL |
| 3 | 7310.18 | 34.84  | 54.00  | -19.16 | 30.22 | 4.06  | 35.96   | 35.40  | Average | 100   | 296   | HORIZONTAL |
| 4 | 7313.56 | 46.07  | 74.00  | -27.93 | 41.45 | 4.06  | 35.96   | 35.40  | Peak    | 100   | 296   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     |         | cm    | deg   |           |
| 1 | 4873.95 | 45.24  | 74.00  | -28.76 | 43.78 | 3.33  | 33.16   | 35.03  | Peak    | 115   | 157   | VERTICAL  |
| 2 | 4874.00 | 38.64  | 54.00  | -15.36 | 37.18 | 3.33  | 33.16   | 35.03  | Average | 115   | 157   | VERTICAL  |
| 3 | 7309.18 | 47.82  | 74.00  | -26.18 | 43.20 | 4.06  | 35.96   | 35.40  | Peak    | 121   | 71    | VERTICAL  |
| 4 | 7309.22 | 38.58  | 54.00  | -15.42 | 33.96 | 4.06  | 35.96   | 35.40  | Average | 121   | 71    | VERTICAL  |

|               |               |                |                                         |
|---------------|---------------|----------------|-----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                     |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11b CH 11 / Chain 1 (1TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                  |

### Horizontal

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp |         | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     | Remark  | cm    | deg   |            |
| 1 | 4923.89 | 34.83  | 54.00  | -19.17 | 33.23 | 3.35  | 33.26   | 35.01  | Average | 102   | 248   | HORIZONTAL |
| 2 | 4923.92 | 42.13  | 74.00  | -31.87 | 40.53 | 3.35  | 33.26   | 35.01  | Peak    | 102   | 248   | HORIZONTAL |
| 3 | 7384.78 | 35.78  | 54.00  | -18.22 | 31.03 | 4.06  | 36.09   | 35.40  | Average | 100   | 304   | HORIZONTAL |
| 4 | 7384.98 | 46.50  | 74.00  | -27.50 | 41.75 | 4.06  | 36.09   | 35.40  | Peak    | 100   | 304   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp |         | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m | dB     | dBuV  | dB    | dB/m    | dB     | Remark  | cm    | deg   |           |
| 1 | 4923.86 | 46.21  | 74.00  | -27.79 | 44.61 | 3.35  | 33.26   | 35.01  | Peak    | 119   | 348   | VERTICAL  |
| 2 | 4924.00 | 42.20  | 54.00  | -11.80 | 40.60 | 3.35  | 33.26   | 35.01  | Average | 119   | 348   | VERTICAL  |
| 3 | 7385.02 | 52.01  | 74.00  | -21.99 | 47.26 | 4.06  | 36.09   | 35.40  | Peak    | 140   | 37    | VERTICAL  |
| 4 | 7385.24 | 45.06  | 54.00  | -8.94  | 40.31 | 4.06  | 36.09   | 35.40  | Average | 140   | 37    | VERTICAL  |

|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11g CH 1 / Chain 1 (1TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                 |

### Horizontal

|   | Freq    | Level  | Limit | Over   | Read  | CableAntenna | Preamp |        | A/Pos   | T/Pos | Pol/Phase      |
|---|---------|--------|-------|--------|-------|--------------|--------|--------|---------|-------|----------------|
|   | MHz     | dBuV/m | Line  | Limit  | Level | Loss         | Factor | Factor | Remark  | cm    | deg            |
| 1 | 4819.04 | 41.15  | 74.00 | -32.85 | 39.85 | 3.31         | 33.02  | 35.03  | Peak    | 100   | 122 HORIZONTAL |
| 2 | 4827.22 | 28.42  | 54.00 | -25.58 | 27.08 | 3.31         | 33.06  | 35.03  | Average | 100   | 122 HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit | Over   | Read  | CableAntenna | Preamp |        | A/Pos   | T/Pos | Pol/Phase    |
|---|---------|--------|-------|--------|-------|--------------|--------|--------|---------|-------|--------------|
|   | MHz     | dBuV/m | Line  | Limit  | Level | Loss         | Factor | Factor | Remark  | cm    | deg          |
| 1 | 4825.28 | 28.58  | 54.00 | -25.42 | 27.24 | 3.31         | 33.06  | 35.03  | Average | 100   | 209 VERTICAL |
| 2 | 4825.70 | 40.95  | 74.00 | -33.05 | 39.61 | 3.31         | 33.06  | 35.03  | Peak    | 100   | 209 VERTICAL |

|               |               |                |                                        |
|---------------|---------------|----------------|----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                    |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11g CH 6 / Chain 1 (1TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                 |

### Horizontal

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp |         | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m | Limit  | Level | Loss  | Factor  | Factor | Remark  | cm    | deg   |            |
| 1 | 4873.38 | 40.59  | 74.00  | -33.41 | 39.13 | 3.33  | 33.16   | 35.03  | Peak    | 100   | 250   | HORIZONTAL |
| 2 | 4875.86 | 28.85  | 54.00  | -25.15 | 27.39 | 3.33  | 33.16   | 35.03  | Average | 100   | 250   | HORIZONTAL |
| 3 | 7307.16 | 32.11  | 54.00  | -21.89 | 27.53 | 4.06  | 35.92   | 35.40  | Average | 100   | 185   | HORIZONTAL |
| 4 | 7311.52 | 43.72  | 74.00  | -30.28 | 39.10 | 4.06  | 35.96   | 35.40  | Peak    | 100   | 185   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit  | Over   | Read  | Cable | Antenna | Preamp |         | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|--------|-------|-------|---------|--------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m | Limit  | Level | Loss  | Factor  | Factor | Remark  | cm    | deg   |           |
| 1 | 4875.28 | 29.18  | 54.00  | -24.82 | 27.72 | 3.33  | 33.16   | 35.03  | Average | 100   | 120   | VERTICAL  |
| 2 | 4876.36 | 40.79  | 74.00  | -33.21 | 39.33 | 3.33  | 33.16   | 35.03  | Peak    | 100   | 120   | VERTICAL  |
| 3 | 7308.00 | 33.92  | 54.00  | -20.08 | 29.30 | 4.06  | 35.96   | 35.40  | Average | 100   | 240   | VERTICAL  |
| 4 | 7312.84 | 45.02  | 74.00  | -28.98 | 40.40 | 4.06  | 35.96   | 35.40  | Peak    | 100   | 240   | VERTICAL  |

|               |               |                |                                         |
|---------------|---------------|----------------|-----------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                     |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11g CH 11 / Chain 1 (1TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                  |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4921.30 | 40.86  | 74.00      | -33.14     | 39.29      | 3.35       | 33.23          | 35.01         | Peak    | 100   | 208   | HORIZONTAL |
| 2 | 4922.80 | 28.75  | 54.00      | -25.25     | 27.15      | 3.35       | 33.26          | 35.01         | Average | 100   | 208   | HORIZONTAL |
| 3 | 7382.36 | 44.47  | 74.00      | -29.53     | 39.72      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 277   | HORIZONTAL |
| 4 | 7390.08 | 32.18  | 54.00      | -21.82     | 27.43      | 4.06       | 36.09          | 35.40         | Average | 100   | 277   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4922.62 | 28.85  | 54.00      | -25.15     | 27.25      | 3.35       | 33.26          | 35.01         | Average | 100   | 135   | VERTICAL  |
| 2 | 4923.50 | 40.91  | 74.00      | -33.09     | 39.31      | 3.35       | 33.26          | 35.01         | Peak    | 100   | 135   | VERTICAL  |
| 3 | 7381.74 | 44.23  | 74.00      | -29.77     | 39.48      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 118   | VERTICAL  |
| 4 | 7389.06 | 32.36  | 54.00      | -21.64     | 27.61      | 4.06       | 36.09          | 35.40         | Average | 100   | 118   | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11g CH 1 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                           |

### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4823.96 | 40.61  | 74.00      | -33.39     | 39.27      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 320   | HORIZONTAL |
| 2 | 4825.60 | 27.81  | 54.00      | -26.19     | 26.47      | 3.31       | 33.06          | 35.03         | Average | 100   | 320   | HORIZONTAL |

### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4816.56 | 27.82  | 54.00      | -26.18     | 26.53      | 3.31       | 33.02          | 35.04         | Average | 100   | 126   | VERTICAL  |
| 2 | 4828.92 | 40.60  | 74.00      | -33.40     | 39.26      | 3.31       | 33.06          | 35.03         | Peak    | 100   | 126   | VERTICAL  |

|               |               |                |                                                  |
|---------------|---------------|----------------|--------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                              |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11g CH 6 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                           |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4865.24 | 39.73  | 54.00      | -14.27     | 38.31      | 3.33       | 33.12          | 35.03         | Average | 100   | 122   | HORIZONTAL |
| 2 | 4874.44 | 27.28  | 54.00      | -26.72     | 25.82      | 3.33       | 33.16          | 35.03         | Average | 100   | 122   | HORIZONTAL |
| 3 | 7304.68 | 43.52  | 74.00      | -30.48     | 38.94      | 4.06       | 35.92          | 35.40         | Peak    | 100   | 115   | HORIZONTAL |
| 4 | 7315.44 | 30.84  | 54.00      | -23.16     | 26.22      | 4.06       | 35.96          | 35.40         | Average | 100   | 115   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4869.16 | 39.99  | 74.00      | -34.01     | 38.57      | 3.33       | 33.12          | 35.03         | Peak    | 100   | 290   | VERTICAL  |
| 2 | 4872.92 | 27.12  | 54.00      | -26.88     | 25.66      | 3.33       | 33.16          | 35.03         | Average | 100   | 290   | VERTICAL  |
| 3 | 7306.08 | 43.52  | 74.00      | -30.48     | 38.94      | 4.06       | 35.92          | 35.40         | Peak    | 100   | 300   | VERTICAL  |
| 4 | 7311.64 | 30.79  | 54.00      | -23.21     | 26.17      | 4.06       | 35.96          | 35.40         | Average | 100   | 300   | VERTICAL  |



|               |               |                |                                                   |
|---------------|---------------|----------------|---------------------------------------------------|
| Temperature   | 24.5°C        | Humidity       | 56%                                               |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11g CH 11 / Chain 1 + Chain 2 (2TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 5                                            |

#### Horizontal

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|------------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |            |
| 1 | 4921.60 | 27.72  | 54.00      | -26.28     | 26.15      | 3.35       | 33.23          | 35.01         | Average | 100   | 90    | HORIZONTAL |
| 2 | 4923.14 | 40.30  | 74.00      | -33.70     | 38.70      | 3.35       | 33.26          | 35.01         | Peak    | 100   | 90    | HORIZONTAL |
| 3 | 7385.70 | 43.29  | 74.00      | -30.71     | 38.54      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 229   | HORIZONTAL |
| 4 | 7386.20 | 31.48  | 54.00      | -22.52     | 26.73      | 4.06       | 36.09          | 35.40         | Average | 100   | 229   | HORIZONTAL |

#### Vertical

|   | Freq    | Level  | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|------------|------------|------------|------------|----------------|---------------|---------|-------|-------|-----------|
|   | MHz     | dBuV/m | dBuV/m     | dB         | dBuV       | dB         | dB/m           | dB            |         | cm    | deg   |           |
| 1 | 4919.70 | 40.56  | 74.00      | -33.44     | 38.99      | 3.35       | 33.23          | 35.01         | Peak    | 100   | 237   | VERTICAL  |
| 2 | 4927.28 | 27.95  | 54.00      | -26.05     | 26.35      | 3.35       | 33.26          | 35.01         | Average | 100   | 237   | VERTICAL  |
| 3 | 7386.12 | 31.17  | 54.00      | -22.83     | 26.42      | 4.06       | 36.09          | 35.40         | Average | 100   | 139   | VERTICAL  |
| 4 | 7386.36 | 43.30  | 74.00      | -30.70     | 38.55      | 4.06       | 36.09          | 35.40         | Peak    | 100   | 139   | VERTICAL  |



|               |               |                |                                                     |
|---------------|---------------|----------------|-----------------------------------------------------|
| Temperature   | 24°C          | Humidity       | 56%                                                 |
| Test Engineer | Dennis Su     | Configurations | IEEE 802.11n MCS0 20MHz CH 149 / Chain 1 (1TX, 2RX) |
| Test Date     | Feb. 03, 2012 | Test Mode      | Mode 6                                              |

#### Horizontal

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamplifier Factor | Remark  | A/Pos | T/Pos | Pol/Phase  |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------------|---------|-------|-------|------------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB                | dB/m           | dB                  |         | cm    | deg   |            |
| 1 | 11490.00 | 48.81  | 74.00      | -25.19     | 40.20      | 5.11              | 38.78          | 35.28               | Peak    | 100   | 214   | HORIZONTAL |
| 2 | 11492.26 | 36.06  | 54.00      | -17.94     | 27.45      | 5.11              | 38.78          | 35.28               | Average | 100   | 214   | HORIZONTAL |

#### Vertical

|   | Freq     | Level  | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamplifier Factor | Remark  | A/Pos | T/Pos | Pol/Phase |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------------|---------|-------|-------|-----------|
|   | MHz      | dBuV/m | dBuV/m     | dB         | dBuV       | dB                | dB/m           | dB                  |         | cm    | deg   |           |
| 1 | 11485.08 | 47.91  | 74.00      | -26.09     | 39.30      | 5.11              | 38.78          | 35.28               | Peak    | 100   | 326   | VERTICAL  |
| 2 | 11489.04 | 36.15  | 54.00      | -17.85     | 27.54      | 5.11              | 38.78          | 35.28               | Average | 100   | 326   | VERTICAL  |