

RF Exposure Report

Report No.: SA160715E05

FCC ID: UZ7AP7622

Test Model: AP-7622

Received Date: July 15, 2016

Test Date: Sep. 21, 2016

Issued Date: Oct. 28, 2016

Applicant: Zebra Technologies Corporation

Address: One Zebra Plaza, Holtsville, NY,11742, USA

Manufacturer: Zebra Technologies Corporation

Address: One Zebra Plaza, Holtsville, NY,11742, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Report No.: SA160715E05 Page No. 1 / 7 Report Format Version: 6.1.1



Table of Contents

Relea	se Control Record	. 3
1	Certificate of Conformity	. 4
	RF Exposure	
	Limits For Maximum Permissible Exposure (MPE)	
2.2	MPE Calculation Formula	. 5
2.3	Classification	. 5
	Antenna Gain	
2.5	Calculation Result of Maximum Conducted Power	. 6



Release Control Record

Issue No.	Description	Date Issued
SA160715E05	Original release.	Oct. 28, 2016

Report No.: SA160715E05 Page No. 3 / 7 Report Format Version: 6.1.1



Certificate of Conformity 1

Product: Access Point

Brand: ZEBRA

Test Model: AP-7622

Sample Status: ENGINEERING SAMPLE

Applicant: Zebra Technologies Corporation

Test Date: Sep. 21, 2016

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Wendy Wu / Specialist Oct. 28, 2016

Approved by: Oct. 28, 2016 Date:

May Chen / Manager



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range Electric Field (MHz) Strength (V/m		Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

No.	PCB Chain No	Brand	Model	Antenna Gain(dBi) Including cable loss	Frequency range	Antenna Type	Connector type
				3.64	2.4~2.4835GHz	Monopole	i-pex(MHF)
				4.14	5.15~5.25GHz	Monopole	i-pex(MHF)
1	Chain 0	NA	NA	4.33	5.25~5.35GHz	Monopole	i-pex(MHF)
				4.66	5.47~5.725GHz	Monopole	i-pex(MHF)
				4.85	5.725~5.85GHz	Monopole	i-pex(MHF)
				2.65	2.4~2.4835GHz	Monopole	i-pex(MHF)
				4.5	5.15~5.25GHz	Monopole	i-pex(MHF)
2	Chain 1	NA	NA	5.77	5.25~5.35GHz	Monopole	i-pex(MHF)
				5.54	5.47~5.725GHz	Monopole	i-pex(MHF)
				4.78	5.725~5.85GHz	Monopole	i-pex(MHF)
3	BT	NA	NA	2.42	2.4~2.483GHz	Monopole	i-pex(MHF)

Report No.: SA160715E05 Page No. 5 / 7 Report Format Version: 6.1.1



2.5 Calculation Result of Maximum Conducted Power

For WLAN / BT coexistence mode:

Condition	Technology					
1	WLAN (2.4GHz-Chain0)	WLAN (5GHz-Chain1)	ВТ			
2	WLAN (2.4GHz-Chain1)	WLAN (5GHz-Chain0)	BT			
3	WLAN (2.4GHz-Chain0)	WLAN (2.4GHz-Chain1)	BT			
4	WLAN (5GHz-Chain0)	WLAN (5GHz-Chain1)	BT			

Condition 1							
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)		
2412-2462 (Chain 0)	153.462	3.64	20	0.07059	1		
5180-5240 5745-5825 (Chain 1)	154.882	4.78	20	0.09263	1		
2402-2480	6.339	2.42	20	0.00220	1		
Condition 2							
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)		
2412-2462 (Chain 1)	173.78	2.65	20	0.06364	1		
5180-5240 5745-5825 (Chain 0)	138.995	4.85	20	0.08448	1		
2402-2480	6.339	2.42	20	0.00220	1		
Condition 3							
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)		
2412-2462 (2TX)	327.242	6.17	20	0.26952	1		
2402-2480	6.339	2.42	20	0.00220	1		
Condition 4							
Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)		
5180-5240 5745-5825 (2TX)	293.877	7.83	20	0.35473	1		
2402-2480	6.339	2.42	20	0.00220	1		

NOTE:

2.4GHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.17dBi$

5GHz:

UNII-1: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 7.33$ dBi UNII-3: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 7.83$ dBi

Report No.: SA160715E05 Page No. 6 / 7 Report Format Version: 6.1.1



Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

Condition 1:

Therefore, the worst-case situation is 0.07059 / 1 + 0.09263 / 1 + 0.00220 / 1 = 0.16542, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

Condition 2:

Therefore, the worst-case situation is 0.06364 / 1 + 0.08448 / 1 + 0.00220 / 1 = 0.15032, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

Condition 3:

Therefore, the worst-case situation is 0.26952 / 1 + 0.00220 / 1 = 0.27172, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

Condition 4:

Therefore, the worst-case situation is 0.35473 / 1 + 0.00220 / 1 = 0.35693, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---