



FCC RADIO TEST REPORT

FCC ID : UZ7CR8288PC
Equipment : Presentation Cradle
Brand Name : Zebra
Model Name : CR8288-PC
Applicant : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
Manufacturer : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Apr. 21, 2025 and testing was performed from May 15, 2025 to Jun. 04, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	6
1.4 Testing Location	6
1.5 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 Test Result.....	12
3.1 6dB and 99% Bandwidth Measurement	12
3.2 Output Power Measurement.....	13
3.3 Power Spectral Density Measurement	14
3.4 Conducted Band Edges and Spurious Emission Measurement	15
3.5 Radiated Band Edges and Spurious Emission Measurement	16
3.6 AC Conducted Emission Measurement.....	20
3.7 Antenna Requirements.....	22
4 List of Measuring Equipment	23
5 Measurement Uncertainty	25
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Result	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR541705B	01	Initial issue of report	Jul. 04, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	5.15 dB under the limit at 2483.52 MHz
3.6	15.207	AC Conducted Emission	Pass	8.64 dB under the limit at 17.73 MHz
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Wei Chen

Report Producer: Hannah Yang



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Presentation Cradle
Brand Name	Zebra
Model Name	CR8288-PC
FCC ID	UZ7CR8288PC
EUT supports Radios application	Bluetooth LE WPT
HW Version	PC-002214-03
FW Version	CAAGNS00-001-N16D0
MFD	28MAR25
EUT Stage	Identical Prototype

Remark: The EUT's information above is declared by manufacturer.

Specification of Accessories				
5V Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V4W0US
12V Adaptor	Brand Name	Zebra	Part Number	PWR-BGA12V50W0WW
USB cable with 12V supply, 7ft	Brand Name	Zebra	Model Name	CBA-U42-S07PAR
USB cable with 5V supply, 7ft	Brand Name	Zebra	Model Name	CBA-U21-S07ZBR
USB cable with 12V supply, 15ft	Brand Name	Zebra	Model Name	CBA-U44-S15PAR
USB cable with 5V supply, 15ft	Brand Name	Zebra	Model Name	CBA-U30-S15ZBR
RS232 with 5V supply, 7ft	Brand Name	Zebra	Model Name	CBA-R01-S07PBR
RS232 with 5V supply, 20ft	Brand Name	Zebra	Model Name	CBA-R06-C20PBR
RS232 with 12v supply, 7FT	Brand Name	Zebra	Model Name	CBA-R12-S07PAR
RS232 with 12v supply, 15FT	Brand Name	Zebra	Model Name	CBA-R21-S15PAR
USB-C cable, 7ft	Brand Name	Zebra	Model Name	CBA-U65-S07ZAR
USB-C cable, 7ft	Brand Name	Zebra	Model Name	CBL-U67-S07ZAR
USB-C cable, 7ft	Brand Name	Zebra	Model Name	CBL-U68-S07ZAR

Supported Unit Used in Test Configuration and System				
Scanner	Brand Name	Zebra	Model Name	DS8288

1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	Bluetooth – LE: 2.75 dBm / 0.0019 W
99% Occupied Bandwidth	1.051 MHz
Antenna Type / Gain	PCB Trace with gain 3.87 dBi
Type of Modulation	Bluetooth LE: GFSK

Remark: The above EUT's information was declared by manufacturer. Please refer to Disclaimer in report summary.

1.3 Modification of EUT

No modifications made to the EUT during the testing.

1.4 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. CO05-HY (TAF Code: 1190)
Remark	The AC Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, 03CH22-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786



1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: not applicable), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: Bluetooth Link between Scanner (DS8288) and Cradle (CR8288-PC) + Scanner (DS8288) Scan bar code + Cradle (CR8288-PC) RS232 cable (CBA-R01-S07PBR) (Data Link with PC) + Scanner (DS8288) charging with Cradle (CR8288-PC) + Adapter (PWR-WUA5V4W0US)
Remark: - For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. - For Radiated Test Cases, the tests were performed with USB-C cable, 7ft (CBL-U67-S07ZAR). - The detailed Radiated test modes are shown in Appendix C.	

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth - LE Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC52U	MSQ-RTAC52U	N/A	Unshielded,1.8m
2.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0m	N/A
3.	LCD Monitor	View Sonic	VS17425	FCC DoC	Shielded, 1.6m	Unshielded,1.8m
4.	PC	MSI	PRO DP1 B0A7	FCC DoC	N/A	Unshielded,1.8m
5.	Keyboard	DELL	SK-8115	FCC DoC	Unshielded,1.2m	N/A
6.	Mouse	Acer	MOANUOA	FCC DoC	Unshielded,1.2m	N/A
7.	Notebook	DELL	Latitude5310	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “BT Regulatory Tset App v2.1.0.7” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9kHz~30MHz	Aug. 29, 2024	May 15, 2025 ~ May 20, 2025	Aug. 28, 2025	Radiation (03CH22-HY)
Bilog Antenna with 6dB	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63304 & 002	30MHz~1GHz	Dec. 17, 2024	May 15, 2025 ~ May 20, 2025	Dec. 16, 2025	Radiation (03CH22-HY)
Amplifier	SONOMA	310N	421581	N/A	Jul. 14, 2024	May 15, 2025 ~ May 20, 2025	Jul. 13, 2025	Radiation (03CH22-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-02038	1GHz~18GHz	Jul. 29, 2024	May 15, 2025 ~ May 20, 2025	Jul. 28, 2025	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1225	18GHz~40GHz	Jun. 24, 2024	May 15, 2025 ~ May 20, 2025	Jun. 23, 2025	Radiation (03CH22-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 27, 2024	May 15, 2025 ~ May 20, 2025	Sep. 26, 2025	Radiation (03CH22-HY)
Preamplifier	EMEC	EM18G40G	060872	18-40GHz	Nov. 29, 2024	May 15, 2025 ~ May 20, 2025	Nov. 28, 2025	Radiation (03CH22-HY)
Signal Analyzer	Keysight	N9010B	MY62170278	10Hz~44GHz	Sep. 24, 2024	May 15, 2025 ~ May 20, 2025	Sep. 23, 2025	Radiation (03CH22-HY)
Hygrometer	TECPEL	DTM-303A	TP211469	N/A	Dec. 24, 2024	May 15, 2025 ~ May 20, 2025	Dec. 23, 2025	Radiation (03CH22-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	May 15, 2025 ~ May 20, 2025	N/A	Radiation (03CH22-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 15, 2025 ~ May 20, 2025	N/A	Radiation (03CH22-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 15, 2025 ~ May 20, 2025	N/A	Radiation (03CH22-HY)
Software	Audix	E3	RK-002347	N/A	N/A	May 15, 2025 ~ May 20, 2025	N/A	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 05, 2025	May 15, 2025 ~ May 20, 2025	Mar. 04, 2026	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804390/2,804611/2,804615/2	N/A	Oct. 23, 2024	May 15, 2025 ~ May 20, 2025	Oct. 22, 2025	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER/EMCI	SUCOFLEX 102/EMCI01Y-KM-KM-500/EMCI01Y-KM-KM-9000	804611/2,240914,25043351,25043350	N/A	May 19, 2025	May 19, 2025 ~ May 20, 2025	May 18, 2026	Radiation (03CH22-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	May 21, 2025 ~ May 23, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	May 21, 2025 ~ May 23, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	May 21, 2025 ~ May 23, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	May 21, 2025 ~ May 23, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	May 21, 2025 ~ May 23, 2025	N/A	Conducted (TH05-HY)

**FCC RADIO TEST REPORT****Report No. : FR541705B**

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 04, 2025	N/A	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Oct. 14, 2024	Jun. 04, 2025	Oct. 13, 2025	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 12, 2024	Jun. 04, 2025	Dec. 11, 2025	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 14, 2024	Jun. 04, 2025	Nov. 13, 2025	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Jun. 04, 2025	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 30, 2024	Jun. 04, 2025	Jul. 29, 2025	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	N/A	Oct. 15, 2024	Jun. 04, 2025	Oct. 14, 2025	Conduction (CO05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.6 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Benny Ku	Temperature:	21~25	°C
Test Date:	2025/5/21~2025/5/23	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.050	0.505	0.50	Pass
BLE	1Mbps	1	19	2440	1.051	0.506	0.50	Pass
BLE	1Mbps	1	39	2480	1.051	0.503	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	2.65	30.00	3.87	6.52	36.00	Pass
BLE	1Mbps	1	19	2440	2.75	30.00	3.87	6.62	36.00	Pass
BLE	1Mbps	1	39	2480	2.65	30.00	3.87	6.52	36.00	Pass




TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	2.28	-14.49	3.87	8.00	Pass
BLE	1Mbps	1	19	2440	2.49	-14.29	3.87	8.00	Pass
BLE	1Mbps	1	39	2480	2.43	-14.30	3.87	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




**6dB Bandwidth**

<1M>

6 dB Bandwidth Plot on Channel 0**6 dB Bandwidth Plot on Channel 19****6 dB Bandwidth Plot on Channel 39**




**99% Occupied Bandwidth**

<1M>

99% Occupied Bandwidth Plot on Channel 0**99% Occupied Bandwidth Plot on Channel 19****99% Occupied Bandwidth Plot on Channel 39**





**Power Spectral Density (dBm/3kHz)**

<1M>

Power Density (dBm/3kHz) Plot Channel 0**Power Density (dBm/3kHz) Plot Channel 19****Power Density (dBm/3kHz) Plot Channel 39**

**Band Edge and Conducted Spurious Emission**


<1M>

Channel 0**100kHz PSD reference Level Plot****Plot on Channel 0****Spurious Emission 30MHz~1GHz Plot****Spurious Emission 1GHz~26.5GHz Plot**




Channel 19

100kHz PSD reference Level Plot




Plot on Channel 19

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 39


100kHz PSD reference Level Plot



Plot on Channel 39



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Appendix B. AC Conducted Emission Test Results


Test Engineer :	Liu Ying Qi	Temperature :	23 ~ 24°C
		Relative Humidity :	53.4 ~ 54.4%

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

541705
Mode 1
120Vac/60Hz
Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	33.21	55.88	22.67	L1	OFF	19.8
0.152250	44.33	---	65.88	21.55	L1	OFF	19.8
0.467250	---	35.11	46.56	11.45	L1	OFF	19.8
0.467250	40.84	---	56.56	15.72	L1	OFF	19.8
0.591000	---	34.10	46.00	11.90	L1	OFF	19.8
0.591000	41.38	---	56.00	14.62	L1	OFF	19.8
1.070250	---	28.74	46.00	17.26	L1	OFF	19.9
1.070250	36.21	---	56.00	19.79	L1	OFF	19.9
1.727250	---	27.02	46.00	18.98	L1	OFF	19.9
1.727250	35.34	---	56.00	20.66	L1	OFF	19.9
5.091000	---	28.16	50.00	21.84	L1	OFF	20.2
5.091000	34.63	---	60.00	25.37	L1	OFF	20.2
17.137500	---	38.35	50.00	11.65	L1	OFF	20.8
17.137500	46.89	---	60.00	13.11	L1	OFF	20.8
17.733750	---	41.36	50.00	8.64	L1	OFF	20.8
17.733750	48.70	---	60.00	11.30	L1	OFF	20.8
18.849750	---	35.29	50.00	14.71	L1	OFF	20.8
18.849750	44.79	---	60.00	15.21	L1	OFF	20.8
19.396500	---	35.26	50.00	14.74	L1	OFF	20.8
19.396500	44.40	---	60.00	15.60	L1	OFF	20.8

EUT Information

Report NO : 541705
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	32.83	55.88	23.05	N	OFF	19.8
0.152250	43.61	---	65.88	22.27	N	OFF	19.8
0.179250	---	30.95	54.52	23.57	N	OFF	19.8
0.179250	41.82	---	64.52	22.70	N	OFF	19.8
0.478500	---	33.12	46.37	13.25	N	OFF	19.8
0.478500	39.66	---	56.37	16.71	N	OFF	19.8
0.588750	---	33.73	46.00	12.27	N	OFF	19.8
0.588750	41.18	---	56.00	14.82	N	OFF	19.8
0.703500	---	25.94	46.00	20.06	N	OFF	19.9
0.703500	40.40	---	56.00	15.60	N	OFF	19.9
1.077000	---	27.70	46.00	18.30	N	OFF	19.9
1.077000	37.72	---	56.00	18.28	N	OFF	19.9
1.727250	---	26.75	46.00	19.25	N	OFF	19.9
1.727250	34.95	---	56.00	21.05	N	OFF	19.9
3.441750	---	27.54	46.00	18.46	N	OFF	20.0
3.441750	34.63	---	56.00	21.37	N	OFF	20.0
17.135250	---	38.35	50.00	11.65	N	OFF	20.8
17.135250	46.94	---	60.00	13.06	N	OFF	20.8
17.675250	---	34.29	50.00	15.71	N	OFF	20.8
17.675250	42.89	---	60.00	17.11	N	OFF	20.8
17.729250	---	40.91	50.00	9.09	N	OFF	20.8

17.729250	48.48	---	60.00	11.52	N	OFF	20.8
18.505500	---	34.30	50.00	15.70	N	OFF	20.8
18.505500	43.36	---	60.00	16.64	N	OFF	20.8
19.457250	---	35.11	50.00	14.89	N	OFF	20.8
19.457250	44.13	---	60.00	15.87	N	OFF	20.8



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Ken Kuo and York Huang	Relative Humidity :	54.5 ~ 58.9%
		Temperature :	20.8 ~ 22.6°C

Note symbol

-L	Low channel location
-R	High channel location

C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 5	2400-2483.5	SISO	Bluetooth-LE GSKF	00	2402	1Mbps	-	-
Mode 6	2400-2483.5	SISO	Bluetooth-LE GSKF	19	2440	1Mbps	-	-
Mode 7	2400-2483.5	SISO	Bluetooth-LE GSKF	39	2480	1Mbps	-	-
Mode 8	2400-2483.5	SISO	Bluetooth-LE GSKF	39	2480	1Mbps	-	LF



C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
5	Bluetooth-LE GSKF	00	2351.03	43.58	54.00	-10.42	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE GSKF	00	4804.00	47.38	74.00	-26.62	H	Peak	Pass	-	Harmonic
6	Bluetooth-LE GSKF	19	2486.56	43.99	54.00	-10.01	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE GSKF	19	7320.00	41.82	54.00	-12.18	H	Avg.	Pass	-	Harmonic
7	Bluetooth-LE GSKF	39	2483.52	48.85	54.00	-5.15	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE GSKF	39	7440.00	41.36	54.00	-12.64	V	Avg.	Pass	-	Harmonic
8	LF	39	72.68	30.57	40.00	-9.43	V	Peak	Pass	-	LF



Mode	5																																																																																																
	Band Edge																																																																																																
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz																																																																																																
ANT	SISO																																																																																																
Pol.	Horizontal						Fundamental																																																																																										
Peak	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_BE_74 3m 91200_02038_240729 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2350.48</td><td>51.49</td><td>74.00</td><td>-22.51</td><td>38.19</td><td>27.30</td><td>8.56</td><td>32.56</td><td>9.43</td><td>271</td><td>61 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2350.48	51.49	74.00	-22.51	38.19	27.30	8.56	32.56	9.43	271	61 PEAK	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_74 3m 91200_02038_240729 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>102.00</td><td>-----</td><td>-----</td><td>88.59</td><td>27.42</td><td>8.65</td><td>32.60</td><td>9.44</td><td>271</td><td>61 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	102.00	-----	-----	88.59	27.42	8.65	32.60	9.44	271	61 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2350.48	51.49	74.00	-22.51	38.19	27.30	8.56	32.56	9.43	271	61 PEAK																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2402.00	102.00	-----	-----	88.59	27.42	8.65	32.60	9.44	271	61 PEAK																																																																																						
Avg	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: AVG_BE_54 3m 91200_02038_240729 HORIZONTAL : RBW:1000.000kHz VBW:11.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2351.03</td><td>43.58</td><td>54.00</td><td>-10.42</td><td>30.28</td><td>27.30</td><td>8.56</td><td>32.56</td><td>9.43</td><td>271</td><td>61 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2351.03	43.58	54.00	-10.42	30.28	27.30	8.56	32.56	9.43	271	61 AVERAGE	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: AVG_54 3m 91200_02038_240729 HORIZONTAL : RBW:1000.000kHz VBW:11.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>101.55</td><td>-----</td><td>-----</td><td>88.06</td><td>27.42</td><td>8.65</td><td>32.60</td><td>9.44</td><td>271</td><td>61 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	101.55	-----	-----	88.06	27.42	8.65	32.60	9.44	271	61 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2351.03	43.58	54.00	-10.42	30.28	27.30	8.56	32.56	9.43	271	61 AVERAGE																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2402.00	101.55	-----	-----	88.06	27.42	8.65	32.60	9.44	271	61 AVERAGE																																																																																						



Mode	5																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz																																																																																																			
ANT	SISO																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_BE_74 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2333.18</td><td>51.19</td><td>74.00</td><td>-22.81</td><td>37.94</td><td>27.27</td><td>8.53</td><td>32.55</td><td>9.43</td><td>353</td><td>133</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2333.18	51.19	74.00	-22.81	37.94	27.27	8.53	32.55	9.43	353	133	PEAK	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_74 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>98.82</td><td>-----</td><td>-----</td><td>85.33</td><td>27.42</td><td>8.65</td><td>32.60</td><td>9.44</td><td>353</td><td>133</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	98.82	-----	-----	85.33	27.42	8.65	32.60	9.44	353	133	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2333.18	51.19	74.00	-22.81	37.94	27.27	8.53	32.55	9.43	353	133	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	98.82	-----	-----	85.33	27.42	8.65	32.60	9.44	353	133	PEAK																																																																																								
Avg	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: AVG_BE_54 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:11.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2376.52</td><td>43.43</td><td>54.00</td><td>-10.57</td><td>30.08</td><td>27.30</td><td>8.61</td><td>32.58</td><td>9.44</td><td>353</td><td>133</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2376.52	43.43	54.00	-10.57	30.08	27.30	8.61	32.58	9.44	353	133	AVERAGE	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: AVG_54 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:11.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>98.12</td><td>-----</td><td>-----</td><td>84.63</td><td>27.42</td><td>8.65</td><td>32.60</td><td>9.44</td><td>353</td><td>133</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	98.12	-----	-----	84.63	27.42	8.65	32.60	9.44	353	133	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2376.52	43.43	54.00	-10.57	30.08	27.30	8.61	32.58	9.44	353	133	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	98.12	-----	-----	84.63	27.42	8.65	32.60	9.44	353	133	AVERAGE																																																																																								



	6																																																																																									
Mode	Band Edge - L																																																																																									
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																									
ANT	SISO																																																																																									
Pol.	Horizontal					Fundamental																																																																																				
Peak	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_BE_74 3m 91200_02038_240729 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2388.26</td><td>51.37</td><td>74.00 -22.63</td><td>37.93</td><td>27.38</td><td>8.63</td><td>32.59</td><td>9.44</td><td>268</td><td>62 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg	1 2388.26	51.37	74.00 -22.63	37.93	27.38	8.63	32.59	9.44	268	62 PEAK	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_74 3m 91200_02038_240729 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2440.00</td><td>102.14</td><td>-----</td><td>88.41</td><td>27.60</td><td>8.72</td><td>32.62</td><td>9.45</td><td>268</td><td>62 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg	1 2440.00	102.14	-----	88.41	27.60	8.72	32.62	9.45	268	62 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																				
MHz	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg																																																																																	
1 2388.26	51.37	74.00 -22.63	37.93	27.38	8.63	32.59	9.44	268	62 PEAK																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																				
MHz	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg																																																																																	
1 2440.00	102.14	-----	88.41	27.60	8.72	32.62	9.45	268	62 PEAK																																																																																	
Avg	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: AVG_BE_54 3m 91200_02038_240729 HORIZONTAL : RBW:1000.000kHz VBW:11.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2389.43</td><td>43.32</td><td>54.00 -10.68</td><td>29.87</td><td>27.39</td><td>8.63</td><td>32.59</td><td>9.44</td><td>268</td><td>62 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg	1 2389.43	43.32	54.00 -10.68	29.87	27.39	8.63	32.59	9.44	268	62 AVERAGE	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: AVG_54 3m 91200_02038_240729 HORIZONTAL : RBW:1000.000kHz VBW:11.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2440.00</td><td>101.62</td><td>-----</td><td>87.89</td><td>27.60</td><td>8.72</td><td>32.62</td><td>9.45</td><td>268</td><td>62 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg	1 2440.00	101.62	-----	87.89	27.60	8.72	32.62	9.45	268	62 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																				
MHz	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg																																																																																	
1 2389.43	43.32	54.00 -10.68	29.87	27.39	8.63	32.59	9.44	268	62 AVERAGE																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																				
MHz	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg																																																																																	
1 2440.00	101.62	-----	87.89	27.60	8.72	32.62	9.45	268	62 AVERAGE																																																																																	



Mode	6										
	Band Edge - R										
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz										
ANT	SISO										
Pol.	Horizontal						Fundamental				
Peak	</										





	6																																																																																																			
Mode	Band Edge - L																																																																																																			
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																																			
ANT	SISO																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_BE_74 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2366.60</td><td>51.47</td><td>74.00</td><td>-22.53</td><td>38.14</td><td>27.30</td><td>8.59</td><td>32.57</td><td>9.44</td><td>383</td><td>138</td><td>PEAK</td></tr></table> Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_74 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>98.98</td><td>-----</td><td>-----</td><td>85.25</td><td>27.60</td><td>8.72</td><td>32.62</td><td>9.45</td><td>383</td><td>138</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2366.60	51.47	74.00	-22.53	38.14	27.30	8.59	32.57	9.44	383	138	PEAK		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	98.98	-----	-----	85.25	27.60	8.72	32.62	9.45	383	138	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2366.60	51.47	74.00	-22.53	38.14	27.30	8.59	32.57	9.44	383	138	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	98.98	-----	-----	85.25	27.60	8.72	32.62	9.45	383	138	PEAK																																																																																								
Avg	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: AVG_BE_54 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:11.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2351.34</td><td>43.15</td><td>54.00</td><td>-10.85</td><td>29.85</td><td>27.30</td><td>8.56</td><td>32.56</td><td>9.43</td><td>383</td><td>138</td><td>AVERAGE</td></tr></table> Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: AVG_54 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:11.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>98.61</td><td>-----</td><td>-----</td><td>84.88</td><td>27.60</td><td>8.72</td><td>32.62</td><td>9.45</td><td>383</td><td>138</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2351.34	43.15	54.00	-10.85	29.85	27.30	8.56	32.56	9.43	383	138	AVERAGE		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	98.61	-----	-----	84.88	27.60	8.72	32.62	9.45	383	138	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2351.34	43.15	54.00	-10.85	29.85	27.30	8.56	32.56	9.43	383	138	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	98.61	-----	-----	84.88	27.60	8.72	32.62	9.45	383	138	AVERAGE																																																																																								



Mode	6																																								
	Band Edge - R																																								
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																								
ANT	SISO																																								
Pol.	Vertical	Fundamental																																							
Peak	Level (dBuV/m) Date: 2025-05-15 PEAK_BE_74 Site : 03CH22-HY Condition: PEAK_BE_74 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2498.00</td><td>51.00</td><td>74.00</td><td>-22.20</td><td>37.79</td><td>27.00</td><td>8.83</td><td>32.66</td><td>9.46</td><td>383</td><td>138</td><td>PEAK</td></tr></table>	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2498.00	51.00	74.00	-22.20	37.79	27.00	8.83	32.66	9.46	383	138	PEAK	Blank
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																													
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																														
1	2498.00	51.00	74.00	-22.20	37.79	27.00	8.83	32.66	9.46	383	138	PEAK																													
Avg	Level (dBuV/m) Date: 2025-05-15 AVG_BE_54 Site : 03CH22-HY Condition: AVG_BE_54 3m 91200_02038_240729 VERTICAL : RBW:1000.000kHz VBW:11.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2486.56</td><td>43.99</td><td>54.00</td><td>-10.01</td><td>30.02</td><td>27.77</td><td>8.81</td><td>32.65</td><td>9.46</td><td>383</td><td>138</td><td>AVERAGE</td></tr></table>	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2486.56	43.99	54.00	-10.01	30.02	27.77	8.81	32.65	9.46	383	138	AVERAGE	Blank
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																													
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																														
1	2486.56	43.99	54.00	-10.01	30.02	27.77	8.81	32.65	9.46	383	138	AVERAGE																													



Mode	6																																																																																																																																																								
	Harmonic																																																																																																																																																								
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																																																																																								
ANT	SISO																																																																																																																																																								
Pol.	Horizontal							Vertical																																																																																																																																																	
Peak Avg	 Level (dBuV/m) Date: 2025-05-15 PEAK_74 AVG_54							 Level (dBuV/m) Date: 2025-05-15 PEAK_74 AVG_54																																																																																																																																																	
	Site : 03CH22-HY Condition: PEAK_74 3m 91200_02038_240729 HORIZONTAL							Site : 03CH22-HY Condition: PEAK_74 3m 91200_02038_240729 VERTICAL																																																																																																																																																	
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4880.00</td><td>47.41</td><td>74.00</td><td>-26.59</td><td>33.97</td><td>32.56</td><td>12.49</td><td>33.67</td><td>1.25</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>51.14</td><td>74.00</td><td>-22.86</td><td>33.56</td><td>36.72</td><td>15.41</td><td>36.61</td><td>1.01</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>3</td><td>7320.00</td><td>41.82</td><td>54.00</td><td>-12.18</td><td>24.24</td><td>36.72</td><td>15.41</td><td>36.61</td><td>1.01</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4880.00	47.41	74.00	-26.59	33.97	32.56	12.49	33.67	1.25	--	--	--	PEAK	2	7320.00	51.14	74.00	-22.86	33.56	36.72	15.41	36.61	1.01	--	--	--	PEAK	3	7320.00	41.82	54.00	-12.18	24.24	36.72	15.41	36.61	1.01	--	--	--	Average	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4880.00</td><td>46.43</td><td>74.00</td><td>-27.57</td><td>32.99</td><td>32.56</td><td>12.49</td><td>33.67</td><td>1.25</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>50.31</td><td>74.00</td><td>-23.69</td><td>32.73</td><td>36.72</td><td>15.41</td><td>36.61</td><td>1.01</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>3</td><td>7320.00</td><td>41.65</td><td>54.00</td><td>-12.35</td><td>24.07</td><td>36.72</td><td>15.41</td><td>36.61</td><td>1.01</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4880.00	46.43	74.00	-27.57	32.99	32.56	12.49	33.67	1.25	--	--	--	PEAK	2	7320.00	50.31	74.00	-23.69	32.73	36.72	15.41	36.61	1.01	--	--	--	PEAK	3	7320.00	41.65	54.00	-12.35	24.07	36.72	15.41	36.61	1.01	--	--	--
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																													
1	4880.00	47.41	74.00	-26.59	33.97	32.56	12.49	33.67	1.25	--	--	--	PEAK																																																																																																																																												
2	7320.00	51.14	74.00	-22.86	33.56	36.72	15.41	36.61	1.01	--	--	--	PEAK																																																																																																																																												
3	7320.00	41.82	54.00	-12.18	24.24	36.72	15.41	36.61	1.01	--	--	--	Average																																																																																																																																												
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																													
1	4880.00	46.43	74.00	-27.57	32.99	32.56	12.49	33.67	1.25	--	--	--	PEAK																																																																																																																																												
2	7320.00	50.31	74.00	-23.69	32.73	36.72	15.41	36.61	1.01	--	--	--	PEAK																																																																																																																																												
3	7320.00	41.65	54.00	-12.35	24.07	36.72	15.41	36.61	1.01	--	--	--	Average																																																																																																																																												



		7									
Mode		Band Edge									
		2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz									
ANT		SISO									
Pol.		Horizontal					Fundamental				
Peak	<										



		7									
Mode		Band Edge									
		2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz									
ANT		SISO									
Pol.		Vertical					Fundamental				
Peak											



		7																																																																																																																																																																			
Mode		Harmonic																																																																																																																																																																			
		2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz																																																																																																																																																																			
ANT		SISO																																																																																																																																																																			
Pol.		Horizontal																																																																																																																																																																			
Peak Avg		Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_74 3m 91200_02038_240729 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4960.00</td><td>47.35</td><td>74.00</td><td>-26.65</td><td>33.62</td><td>32.98</td><td>12.56</td><td>33.67</td><td>1.08</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>48.45</td><td>74.00</td><td>-25.55</td><td>31.30</td><td>36.30</td><td>15.55</td><td>36.79</td><td>1.03</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>3</td><td>7440.00</td><td>40.74</td><td>54.00</td><td>-13.26</td><td>23.59</td><td>36.30</td><td>15.55</td><td>36.79</td><td>1.03</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4960.00	47.35	74.00	-26.65	33.62	32.98	12.56	33.67	1.08	--	--	--	PEAK	2	7440.00	48.45	74.00	-25.55	31.30	36.30	15.55	36.79	1.03	--	--	--	PEAK	3	7440.00	40.74	54.00	-13.26	23.59	36.30	15.55	36.79	1.03	--	--	--	Average	Level (dBuV/m) Date: 2025-05-15 Site : 03CH22-HY Condition: PEAK_74 3m 91200_02038_240729 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4960.00</td><td>46.56</td><td>74.00</td><td>-27.44</td><td>32.83</td><td>32.98</td><td>12.56</td><td>33.67</td><td>1.08</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>48.72</td><td>74.00</td><td>-25.28</td><td>31.57</td><td>36.30</td><td>15.55</td><td>36.79</td><td>1.03</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>3</td><td>7440.00</td><td>41.36</td><td>54.00</td><td>-12.64</td><td>24.21</td><td>36.30</td><td>15.55</td><td>36.79</td><td>1.03</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4960.00	46.56	74.00	-27.44	32.83	32.98	12.56	33.67	1.08	--	--	--	PEAK	2	7440.00	48.72	74.00	-25.28	31.57	36.30	15.55	36.79	1.03	--	--	--	PEAK	3	7440.00	41.36	54.00	-12.64	24.21	36.30	15.55	36.79	1.03	--	--	--	Average
			Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																						
			MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																							
		1	4960.00	47.35	74.00	-26.65	33.62	32.98	12.56	33.67	1.08	--	--	--	PEAK																																																																																																																																																						
		2	7440.00	48.45	74.00	-25.55	31.30	36.30	15.55	36.79	1.03	--	--	--	PEAK																																																																																																																																																						
3	7440.00	40.74	54.00	-13.26	23.59	36.30	15.55	36.79	1.03	--	--	--	Average																																																																																																																																																								
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																									
1	4960.00	46.56	74.00	-27.44	32.83	32.98	12.56	33.67	1.08	--	--	--	PEAK																																																																																																																																																								
2	7440.00	48.72	74.00	-25.28	31.57	36.30	15.55	36.79	1.03	--	--	--	PEAK																																																																																																																																																								
3	7440.00	41.36	54.00	-12.64	24.21	36.30	15.55	36.79	1.03	--	--	--	Average																																																																																																																																																								



Mode	8																																																																																																																																																																																																																																					
	LF																																																																																																																																																																																																																																					
	2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz																																																																																																																																																																																																																																					
ANT	SISO																																																																																																																																																																																																																																					
Pol.	Horizontal						Vertical																																																																																																																																																																																																																															
QPI Peak	Level (dBuV/m) Date: 2025-05-20 Site : 03CH22-HY Condition: QP 3m Bilog_63304_241217 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>72.68</td><td>27.77</td><td>40.00</td><td>-12.23</td><td>46.51</td><td>12.53</td><td>1.40</td><td>32.70</td><td>0.03</td><td>253</td><td>360</td><td>QP</td></tr><tr><td>2</td><td>159.98</td><td>27.45</td><td>43.50</td><td>-16.05</td><td>41.49</td><td>16.40</td><td>2.12</td><td>32.64</td><td>0.08</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>271.53</td><td>27.54</td><td>46.00</td><td>-18.46</td><td>38.41</td><td>19.01</td><td>2.70</td><td>32.62</td><td>0.04</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>400.00</td><td>37.01</td><td>46.00</td><td>-8.99</td><td>42.40</td><td>23.60</td><td>3.64</td><td>32.79</td><td>0.16</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>640.13</td><td>30.64</td><td>46.00</td><td>-15.36</td><td>32.54</td><td>26.60</td><td>4.21</td><td>32.79</td><td>0.08</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>950.53</td><td>33.93</td><td>46.00</td><td>-12.07</td><td>28.77</td><td>31.23</td><td>5.06</td><td>31.33</td><td>0.20</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	72.68	27.77	40.00	-12.23	46.51	12.53	1.40	32.70	0.03	253	360	QP	2	159.98	27.45	43.50	-16.05	41.49	16.40	2.12	32.64	0.08	--	--	Peak	3	271.53	27.54	46.00	-18.46	38.41	19.01	2.70	32.62	0.04	--	--	Peak	4	400.00	37.01	46.00	-8.99	42.40	23.60	3.64	32.79	0.16	--	--	Peak	5	640.13	30.64	46.00	-15.36	32.54	26.60	4.21	32.79	0.08	--	--	Peak	6	950.53	33.93	46.00	-12.07	28.77	31.23	5.06	31.33	0.20	--	--	Peak	Level (dBuV/m) Date: 2025-05-20 Site : 03CH22-HY Condition: QP 3m Bilog_63304_241217 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>72.68</td><td>30.57</td><td>40.00</td><td>-9.43</td><td>49.31</td><td>12.53</td><td>1.40</td><td>32.70</td><td>0.03</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>134.76</td><td>30.30</td><td>43.50</td><td>-13.20</td><td>43.61</td><td>17.42</td><td>1.88</td><td>32.66</td><td>0.05</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>256.98</td><td>28.16</td><td>46.00</td><td>-17.84</td><td>38.45</td><td>19.66</td><td>2.62</td><td>32.62</td><td>0.05</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>299.66</td><td>35.01</td><td>46.00</td><td>-10.99</td><td>45.35</td><td>19.39</td><td>2.86</td><td>32.62</td><td>0.03</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>740.04</td><td>31.38</td><td>46.00</td><td>-14.62</td><td>31.29</td><td>28.10</td><td>4.54</td><td>32.67</td><td>0.12</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>939.86</td><td>34.69</td><td>46.00</td><td>-11.31</td><td>30.43</td><td>30.49</td><td>5.04</td><td>31.44</td><td>0.17</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	72.68	30.57	40.00	-9.43	49.31	12.53	1.40	32.70	0.03	--	--	Peak	2	134.76	30.30	43.50	-13.20	43.61	17.42	1.88	32.66	0.05	--	--	Peak	3	256.98	28.16	46.00	-17.84	38.45	19.66	2.62	32.62	0.05	--	--	Peak	4	299.66	35.01	46.00	-10.99	45.35	19.39	2.86	32.62	0.03	--	--	Peak	5	740.04	31.38	46.00	-14.62	31.29	28.10	4.54	32.67	0.12	--	--	Peak	6	939.86	34.69	46.00	-11.31	30.43	30.49	5.04	31.44	0.17	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																												
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																												
1	72.68	27.77	40.00	-12.23	46.51	12.53	1.40	32.70	0.03	253	360	QP																																																																																																																																																																																																																										
2	159.98	27.45	43.50	-16.05	41.49	16.40	2.12	32.64	0.08	--	--	Peak																																																																																																																																																																																																																										
3	271.53	27.54	46.00	-18.46	38.41	19.01	2.70	32.62	0.04	--	--	Peak																																																																																																																																																																																																																										
4	400.00	37.01	46.00	-8.99	42.40	23.60	3.64	32.79	0.16	--	--	Peak																																																																																																																																																																																																																										
5	640.13	30.64	46.00	-15.36	32.54	26.60	4.21	32.79	0.08	--	--	Peak																																																																																																																																																																																																																										
6	950.53	33.93	46.00	-12.07	28.77	31.23	5.06	31.33	0.20	--	--	Peak																																																																																																																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																												
1	72.68	30.57	40.00	-9.43	49.31	12.53	1.40	32.70	0.03	--	--	Peak																																																																																																																																																																																																																										
2	134.76	30.30	43.50	-13.20	43.61	17.42	1.88	32.66	0.05	--	--	Peak																																																																																																																																																																																																																										
3	256.98	28.16	46.00	-17.84	38.45	19.66	2.62	32.62	0.05	--	--	Peak																																																																																																																																																																																																																										
4	299.66	35.01	46.00	-10.99	45.35	19.39	2.86	32.62	0.03	--	--	Peak																																																																																																																																																																																																																										
5	740.04	31.38	46.00	-14.62	31.29	28.10	4.54	32.67	0.12	--	--	Peak																																																																																																																																																																																																																										
6	939.86	34.69	46.00	-11.31	30.43	30.49	5.04	31.44	0.17	--	--	Peak																																																																																																																																																																																																																										



Appendix D. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth - LE for 1Mbps	17.95	112	8.93	11kHz

