## **FCC RF Test Report**

APPLICANT : Zebra Technologies Corporation

**EQUIPMENT**: Presentation Cradle

BRAND NAME : Zebra

MODEL NAME : CR8178-PC

FCC ID : UZ7CRD8178PC

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Aug. 02, 2016 and testing was completed on Aug. 30, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 1 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

1190

Report No.: FR680209B

## **TABLE OF CONTENTS**

SU	MMAF	RY OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Product Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	5
	1.5	Modification of EUT	6
	1.6	Testing Location	6
	1.7	Applicable Standards	7
2	TES1	CONFIGURATION OF EQUIPMENT UNDER TEST	8
	2.1	Descriptions of Test Mode	8
	2.2	Test Mode	10
	2.3	Connection Diagram of Test System	11
	2.4	Support Unit used in test configuration and system	12
	2.5	EUT Operation Test Setup	12
	2.6	Measurement Results Explanation Example	12
3	TES1	「RESULT	13
	3.1	6dB and 99% Bandwidth Measurement	13
	3.2	Peak Output Power Measurement	18
	3.3	Power Spectral Density Measurement	19
	3.4	Conducted Band Edges and Spurious Emission Measurement	24
	3.5	Radiated Band Edges and Spurious Emission Measurement	
	3.6	AC Conducted Emission Measurement	37
	3.7	Antenna Requirements	41
4	LIST	OF MEASURING EQUIPMENT	42
5	UNC	ERTAINTY OF EVALUATION	43
ΑP	PEND	IX A. CONDUCTED TEST RESULTS	
ΑP	PEND	IX B. RADIATED SPURIOUS EMISSION	
ΑP	PEND	IX C. RADIATED SPURIOUS EMISSION PLOTS	
ΑP	PEND	IX D. DUTY CYCLE PLOTS	

**APPENDIX E. SETUP PHOTOGRAPHS** 

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 2 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## **REVISION HISTORY**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR680209B	Rev. 01	Initial issue of report	Sep. 14, 2016

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 3 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## **SUMMARY OF TEST RESULT**

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.54 dB at 4804.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.00 dB at 0.518 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 4 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 1 General Description

## 1.1 Applicant

**Zebra Technologies Corporation** 

1 Zebra Plaza, Holtsville, NY 11742

## 1.2 Manufacturer

**Zebra Technologies Corporation** 

1 Zebra Plaza, Holtsville, NY 11742

## 1.3 Product Feature of Equipment Under Test

Product Feature			
Equipment	Presentation Cradle		
Brand Name	Zebra		
Model Name	CR8178-PC		
FCC ID	UZ7CRD8178PC		
EUT supports Radios application	Bluetooth EDR/LE		
HW Version	Rev A		
SW Version	Rev A		
MFD	05MAY16		
EUT Stage	Identical Prototype		

Report No.: FR680209B

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification			
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz		
Maximum Output Power to Antenna	4.81 dBm (0.0030 W)		
99% Occupied Bandwidth	1.016MHz		
Antenna Type / Gain	SMD Antenna with gain 2.70 dBi		
Type of Modulation	Bluetooth LE : GFSK		

 SPORTON INTERNATIONAL INC.
 Page Number
 : 5 of 43

 TEL: 886-3-327-3456
 Report Issued Date
 : Sep. 14, 2016

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: UZ7CRD8178PC Report Template No.: BU5-FR15CBT4.0 Version 1.3

Specification of Accessories						
DS8178	DS8178 Battery			Part Number	82-17890-01	
	12V Adapter (Sanhua)	Brand Name	Zebra	Part Number	PWR-BGA12V50W0WW	
	12V Adapter (Phihong)	Brand Name	Zebra	Part Number	PWRBGAV50W0WW	
	5V Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V4W0US	
CR8178-SC	USB 5V Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V6W0WW	
CR8178-PC	RJ-50-RS232 Cable 1	Brand Name	Zebra	Part Number	CBA-R21-S15PAR	
	RJ-50-RS232 Cable 2	Brand Name	Zebra	Part Number	CBA-R01-S07PAR	
	RJ-50 to USB Cable 1	Brand Name	Zebra	Part Number	CBA-U21-S07ZBR	
	RJ-50 to USB Cable 2	Brand Name	Zebra	Part Number	CBA-U47-S15ZAR	

Report No.: FR680209B

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.			
	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park,			
Test Site Location	Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.			
rest Site Location	TEL: +886-3-327-3456			
	FAX: +886-3-328-4978			
Test Site No.		Sporton Site No.		
rest site No.	TH02-HY	CO05-HY	03CH07-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 6 of 43

 TEL: 886-3-327-3456
 Report Issued Date
 : Sep. 14, 2016

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: UZ7CRD8178PC Report Template No.: BU5-FR15CBT4.0 Version 1.3

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ANSI C63.10-2013

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 7 of 43

Report Issued Date : Sep. 14, 2016

Report Version : Rev. 01

Report No.: FR680209B

## 2 Test Configuration of Equipment Under Test

## 2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

## < 5V Adapter>

	Frequency	Bluetooth – LE Average Output Power
Channel		Data Rate / Modulation
Chaine		GFSK
		1Mbps
Ch00	2402MHz	3.85 dBm
Ch19	2440MHz	4.17 dBm
Ch39	2480MHz	<mark>4.25</mark> dBm

	F	Bluetooth – LE Peak Output Power
Channal		Data Rate / Modulation
Channel	Frequency	GFSK
		1Mbps
Ch00	2402MHz	4.22 dBm
Ch19	2440MHz	4.47 dBm
Ch39	2480MHz	<mark>4.77</mark> dBm

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 8 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

### <12V Adapter (Sanhua)>

		Bluetooth – LE Average Output Power	
Channel		Data Rate / Modulation	
Chamile	Frequency	GFSK	
		1Mbps	
Ch00	2402MHz	4.00 dBm	
Ch19	2440MHz	4.28 dBm	
Ch39	2480MHz	<mark>4.61</mark> dBm	

	Frequency	Bluetooth – LE Peak Output Power
Channal		Data Rate / Modulation
Channel		GFSK
		1Mbps
Ch00	2402MHz	4.26 dBm
Ch19	2440MHz	4.50 dBm
Ch39	2480MHz	4.81 dBm

- a. Since the worst case is 12V for RF output power, we use 12V Adapter (Sanhua) to perform other testing items.
- b. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (X plane as worst plane) from all possible combinations.
- c. AC power line Conducted Emission was tested under maximum output power.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 9 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.

	Summary table of Test Cases			
Test Item	Data Rate / Modulation			
rest item	Bluetooth – LE / GFSK			
Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps			
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps			
TCs	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps			
Radiated	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps			
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps			
TCs	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps			
AC	Made 4. Digital Seemer charging with ELIT (Presentation Cradic) LELIT (Presentation			
Conducted	Mode 1: Digital Scanner charging with EUT (Presentation Cradle) + EUT (Presentation			
Emission	Cradle) RJ-50 to USB Cable 2 + USB 5V Adapter			
Remark: For	Remark: For Radiated Test Cases, The tests were performance with 12V Adapter (Sanhua)			


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 10 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 1.3


Report No.: FR680209B

## 2.3 Connection Diagram of Test System

<Bluetooth - LE Tx Mode>



<AC Conducted Emission Mode>



SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 11 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1	Digital	Zebra	DS8178	UZ7DS8178	N/A	N/A
	Scanner	Zobia	D00170	027000170	14/74	14/74

## 2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, "Tool" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

## 2.6 Measurement Results Explanation Example

#### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

#### Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).  
= 
$$4.2 + 10 = 14.2$$
 (dB)

Report No.: FR680209B

## 3 Test Result

### 3.1 6dB and 99% Bandwidth Measurement

### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


## 3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.1.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- 5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
- 6. Measure and record the results in the test report.

### 3.1.4 Test Setup



SPORTON INTERNATIONAL INC. TEL: 886-3-327-3456


FAX : 886-3-328-4978 FCC ID : UZ7CRD8178PC Page Number : 13 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.1.5 Test Result of 6dB Bandwidth

Test data refer to Appendix A.

#### 6 dB Bandwidth Plot on Channel 00




Date: 16.AUG.2016 19:55:12

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 14 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01


Report No.: FR680209B

### 6 dB Bandwidth Plot on Channel 19



Date: 16.AUG.2016 20:03:14

### 6 dB Bandwidth Plot on Channel 39



Date: 16.AUG.2016 20:07:05

SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 15 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.1.6 Test Result of 99% Occupied Bandwidth

Test data refer to Appendix A.

#### 99% Bandwidth Plot on Channel 00




Date: 16.AUG.2016 19:58:29

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 16 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01


Report No.: FR680209B

### 99% Occupied Bandwidth Plot on Channel 19



Date: 16.AUG.2016 20:05:30

## 99% Occupied Bandwidth Plot on Channel 39



Date: 16.AUG.2016 20:09:04

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 17 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.2 Peak Output Power Measurement

## 3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


## 3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.2.3 Test Procedures

- The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas.
   Guidance v03r05 section 9.1.2 PKPM1 Peak power meter method.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



## 3.2.5 Test Result of Peak Output Power

Test data refer to Appendix A.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 18 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.3 Power Spectral Density Measurement

## 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


## 3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.3.3 Test Procedures

- The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.
- 7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup



SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 19 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01


Report No.: FR680209B

## 3.3.5 Test Result of Power Spectral Density

Test data refers to Appendix A.

## 3.3.6 Test Result of Power Spectral Density Plots (100kHz)

#### PSD 100kHz Plot on Channel 00




Date: 16.AUG.2016 19:56:46

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 20 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01


Report No.: FR680209B

### **PSD 100kHz Plot on Channel 19**



Date: 16.AUG.2016 20:04:24

### PSD 100kHz Plot on Channel 39



Date: 16.AUG.2016 20:07:41


SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 21 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.3.7 Test Result of Power Spectral Density Plots (3kHz)

### **PSD 3kHz Plot on Channel 00**




Date: 16.AUG.2016 19:56:28

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 22 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01


Report No.: FR680209B

### **PSD 3kHz Plot on Channel 19**



Date: 16.AUG.2016 20:03:46

#### PSD 3kHz Plot on Channel 39



Date: 16.AUG.2016 20:07:27

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 23 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.4 Conducted Band Edges and Spurious Emission Measurement

## 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


## 3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.4.3 Test Procedure

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### 3.4.4 Test Setup




TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 24 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.4.5 Test Result of Conducted Band Edges Plots

## Low Band Edge Plot on Channel 00




Date: 16.AUG.2016 19:57:08

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 25 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## **High Band Edge Plot on Channel 39**




Date: 16.AUG.2016 20:08:19

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 26 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.4.6 Test Result of Conducted Spurious Emission Plots

# Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 16.AUG.2016 19:57:25

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 27 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 1.3


Report No.: FR680209B



Date: 16.AUG.2016 19:57:33

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 28 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01


Report No.: FR680209B



Date: 16.AUG.2016 20:15:07

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 29 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01


Report No.: FR680209B



Date: 16.AUG.2016 20:15:15

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 30 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01


Report No.: FR680209B



Date: 16.AUG.2016 20:08:34

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 31 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B



Date: 16.AUG.2016 20:08:43

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 32 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.5 Radiated Band Edges and Spurious Emission Measurement

## 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency	Field Strength	Measurement Distance		
(MHz)	(microvolts/meter)	(meters)		
0.009 - 0.490	2400/F(kHz)	300		
0.490 – 1.705	24000/F(kHz)	30		
1.705 – 30.0	30	30		
30 – 88	100	3		
88 – 216	150	3		
216 - 960	200	3		
Above 960	500	3		

## 3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 33 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 1.3

Report No.: FR680209B

#### 3.5.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.

Report No.: FR680209B

- 3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- 7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \ge 1$  GHz for peak measurement. For average measurement:
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(μs)	1/T(kHz)	VBW Setting
Bluetooth - LE	64.54	404	2.48	3kHz

 SPORTON INTERNATIONAL INC.
 Page Number
 : 34 of 43


 TEL: 886-3-327-3456
 Report Issued Date
 : Sep. 14, 2016

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01


FCC ID : UZ7CRD8178PC Report Template No.: BU5-FR15CBT4.0 Version 1.3

## 3.5.4 Test Setup

### For radiated emissions below 30MHz




### For radiated emissions from 30MHz to 1GHz



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 35 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

#### For radiated emissions above 1GHz



## 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

## 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

## 3.5.7 Duty Cycle

Please refer to Appendix D.

## 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 36 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.6 AC Conducted Emission Measurement

## 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)				
Frequency of emission (MHZ)	Quasi-peak	Average			
0.15-0.5	66 to 56*	56 to 46*			
0.5-5	56	46			
5-30	60	50			

<sup>\*</sup>Decreases with the logarithm of the frequency.

## 3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.6.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


FCC ID: UZ7CRD8178PC

FAX: 886-3-328-4978

Page Number : 37 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.6.4 Test Setup



AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 38 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

#### 3.6.5 **Test Result of AC Conducted Emission**

Test Mode :	Mode 1	Temperature :	22~24℃			
Test Engineer :	Eric Jeng and Kai-Chun Chu	Relative Humidity :	51~53%			
Test Voltage :	est Voltage: 120Vac / 60Hz		Line			
Function Type:	Digital Scanner charging with EUT (Presentation Cradle) + EUT (Presentation					

Cradle) RJ-50 to USB Cable 2 + USB 5V Adapter



### Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	46.6	Off	L1	19.6	19.4	66.0
0.166000	44.5	Off	L1	19.6	20.7	65.2
0.222000	42.0	Off	L1	19.6	20.7	62.7
0.470000	40.0	Off	L1	19.6	16.5	56.5
0.502000	40.8	Off	L1	19.6	15.2	56.0
0.518000	44.9	Off	L1	19.6	11.1	56.0
4.014000	31.4	Off	L1	19.8	24.6	56.0
10.094000	35.3	Off	L1	20.1	24.7	60.0

### Final Result : Average


٠.	mar Nesult : Average							
	Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	
	0.150000	35.0	Off	L1	19.6	21.0	56.0	
	0.166000	34.5	Off	L1	19.6	20.7	55.2	
	0.222000	32.3	Off	L1	19.6	20.4	52.7	
	0.470000	32.4	Off	L1	19.6	14.1	46.5	
	0.502000	34.7	Off	L1	19.6	11.3	46.0	
	0.518000	40.0	Off	L1	19.6	6.0	46.0	
	4.014000	24.3	Off	L1	19.8	21.7	46.0	
	10.094000	23.1	Off	L1	20.1	26.9	50.0	

Report No.: FR680209B

: Rev. 01 Report Version



Test Mode :	Mode 1	Temperature :	<b>22~24</b> ℃				
Test Engineer :	est Engineer : Eric Jeng and Kai-Chun Chu Relative		51~53%				
Test Voltage :	120Vac / 60Hz	Phase :	Neutral				
Function Type :	Digital Scanner charging with EUT (Presentation Cradle) + EUT (Presentation Cradle) R.I-50 to USB Cable 2 + USB 5V Adapter						



## Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	49.1	Off	N	19.6	16.9	66.0
0.166000	46.6	Off	N	19.6	18.6	65.2
0.238000	42.9	Off	N	19.6	19.3	62.2
0.462000	41.0	Off	N	19.6	15.7	56.7
0.510000	44.7	Off	N	19.6	11.3	56.0
0.966000	35.5	Off	N	19.6	20.5	56.0
1.942000	32.7	Off	N	19.7	23.3	56.0
9.662000	33.4	Off	N	20.1	26.6	60.0

### Final Result : Average

mai itcsuit	.,					
Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	35.3	Off	N	19.6	20.7	56.0
0.166000	34.3	Off	N	19.6	20.9	55.2
0.238000	31.8	Off	N	19.6	20.4	52.2
0.462000	34.4	Off	N	19.6	12.3	46.7
0.510000	35.8	Off	N	19.6	10.2	46.0
0.966000	28.3	Off	N	19.6	17.7	46.0
1.942000	25.4	Off	N	19.7	20.6	46.0
9.662000	22.0	Off	N	20.1	28.0	50.0

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 40 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 3.7 Antenna Requirements

## 3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

## 3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

### 3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

Page Number : 41 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Jan. 08, 2016	Aug. 04, 2016 ~ Aug. 16, 2016	Jan. 07, 2017	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Jan. 07, 2016	Aug. 04, 2016 ~ Aug. 16, 2016	Jan. 06, 2017	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 17, 2016	Aug. 04, 2016 ~ Aug. 16, 2016	Jun. 16, 2017	Conducted (TH02-HY)
AC Power Source	ChainTek	APC-1000 W	N/A	N/A	N/A	Aug. 28, 2016 ~ Aug. 30, 2016	N/A	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Aug. 28, 2016 ~ Aug. 30, 2016	Dec. 01, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 14, 2015	Aug. 28, 2016 ~ Aug. 30, 2016	Dec. 13, 2016	Conduction (CO05-HY)
EMI Test Receiver	Keysight	N9038A(M XE)	MY54130085	20Hz ~ 8.4GHz	Nov. 04, 2015	Aug. 28, 2016 ~ Aug. 30, 2016	Nov. 03, 2016	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D	35419	30MHz to 1GHz	Jan. 13, 2016	Aug. 16, 2016 ~ Aug. 17, 2016	Jan. 12, 2017	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 21, 2015	Aug. 16, 2016 ~ Aug. 17, 2016	Aug. 20, 2016	Radiation (03CH07-HY)
EMI Test Receiver	Keysight	N9038A(M XE)	MY54130085	20Hz ~ 8.4GHz	Nov. 04, 2015	Aug. 16, 2016 ~ Aug. 17, 2016	Nov. 03, 2016	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Aug. 16, 2016 ~ Aug. 17, 2016	Sep. 01, 2016	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0 0101800-3 0-10P	1590075	1GHz ~ 18GHz	Apr. 15, 2016	Aug. 16, 2016 ~ Aug. 17, 2016	Apr. 14, 2017	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 18, 2016	Aug. 16, 2016 ~ Aug. 17, 2016	Mar. 17, 2017	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Oct. 19, 2015	Aug. 16, 2016 ~ Aug. 17, 2016	Oct. 18, 2016	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Feb. 27, 2016	Aug. 16, 2016 ~ Aug. 17, 2016	Feb. 26, 2017	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520B S	N/A	1m~4m	N/A	Aug. 16, 2016 ~ Aug. 17, 2016	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Aug. 16, 2016 ~ Aug. 17, 2016	N/A	Radiation (03CH07-HY)
Preamplifier	MITEQ	JS44-1800 4000-33-8 P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Aug. 16, 2016 ~ Aug. 17, 2016	Jun. 13, 2017	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 02, 2015	Aug. 16, 2016 ~ Aug. 17, 2016	Nov. 01, 2016	Radiation (03CH07-HY)

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 42 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B

## 5 Uncertainty of Evaluation

## Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.26
of 95% (U = 2Uc(y))	2.20

## Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence	5.70
of 95% (U = 2Uc(y))	5.70

## <u>Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	5.50
of 95% (U = 2Uc(y))	3.30

### <u>Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	5.00
of 95% (U = 2Uc(y))	5.20

SPORTON INTERNATIONAL INC. TEL: 886-3-327-3456

FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : 43 of 43
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 1.3

Report No.: FR680209B

## **Appendix A. Conducted Test Results**

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7CRD8178PC Page Number : A1 of A1
Report Issued Date : Sep. 14, 2016
Report Version : Rev. 01

Report No.: FR680209B