

FCC SAR Test Report

APPLICANT : Motorola, Inc.

EQUIPMENT: Enterprise Smartphone

BRAND NAME : Motorola MODEL NAME : ES405B

FCC ID : UZ7ES405B

STANDARD : FCC 47 CFR Part 2 (2.1093)

IEEE C95.1-1999 IEEE 1528-2003

FCC OET Bulletin 65 Supplement C (Edition 01-01)

The product was received on Jan. 01, 2010 and completely tested on Feb. 14, 2010. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Roy Wu / Manager

lac-MRA



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 1 of 40
Report Issued Date : Mar. 18, 2010

Table of Contents

Rev		History	
1.		ment of Compliance	
2.		nistration Data	
	2.1	Testing Laboratory	5
	2.2	Applicant	
	2.3	Manufacturer	
	2.4	Application Details	
3.	Gener	al Information	6
	3.1	Description of Device Under Test (DUT)	6
	3.2	Product Photos	7
	3.3	Applied Standards	
	3.4	Device Category and SAR Limits	ع
	3.5	Test Conditions	
	0.0	3.5.1 Ambient Condition	
		3.5.2 Test Configuration	
4.	Speci	fic Absorption Rate (SAR)	
•	4.1	Introduction	
	4.2	SAR Definition	
5		Neasurement System	
٥.	5.1	E-Field Probe	
	0.1	5.1.1 E-Field Probe Specification	13
		5.1.2 E-Field Probe Calibration	
	5.2	Data Acquisition Electronics (DAE)	
	5.3	Robot	
	5.4	Measurement Server	
	5.5	Phantom	
	5.6	Device Holder	
	5.7	Data Storage and Evaluation	
	5.7	5.7.1 Data Storage	
		5.7.2 Data Evaluation	
	5.8	Test Equipment List	
6.		e Simulating Liquids	22
		tainty Assessment	
7. 8.		Neasurement Evaluation	
0.	8.1	Purpose of System Performance check	
	8.2	System Setup	27
	8.3	Validation Results	.21
^		resting Position	
		rement Procedures	
10.			
	10.1	Spatial Peak SAR Evaluation	
	10.2	Scan Procedures	
44	10.3		
11.		Test Results	
	11.1	Conducted Power (Unit: dBm)	
	11.2	Test Records for Head SAR Test	.36
40	11.3	Test Records for Body SAR Test	
12.	Refere	ences	.40

Appendix A. Plots of System Performance Check

Appendix B. Plots of SAR Measurement Appendix C. DASY Calibration Certificate

Appendix D. Product Photos

Appendix E. Test Setup Photos

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B

Report Issued Date: Mar. 18, 2010 Report Version : Rev. 01



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA010103B	Rev. 01	Initial issue of report	Mar. 18, 2010

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 3 of 40
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) were found during testing for Motorola, Inc. Enterprise Smartphone Motorola ES405B, which are as follows (with expanded uncertainty 21.8 % for 300 MHz to 3 GHz, and 25.6% for 3 GHz to 6 GHz).

Band	Position	SAR _{1g} (W/kg)
	Head	0.128
802.11b/g	Body (with 1.5 cm Gap)	0.061
	Body (with Holster)	0.083
	Head	0.445
802.11a	Body (with 1.5 cm Gap)	0.317
	Body (with Holster)	0.281
	Head	N/A
Bluetooth	Body (with 1.5 cm Gap)	N/A
	Body (with Holster)	N/A

They are in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1999, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003 and FCC OET Bulletin 65 Supplement C (Edition 01-01).

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B

Page Number : 4 of 40 Report Issued Date: Mar. 18, 2010

2. Administration Data

2.1 Testing Laboratory

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. : SAR01-HY ; SAR02-HY

2.2 Applicant

Company Name	Motorola, Inc.
Address	One Motorola Plaza, Holtsville, NY 11742-1300 USA

2.3 Manufacturer

Company Name	Inventec Appliances Corp.
Address	No. 37, Wugong 5th Road, Wugu industrial Park, Taipei County 248, Taiwan

2.4 Application Details

Date of Receipt of Application	Jan. 01, 2010
Date of Start during the Test	Jan. 21, 2010
Date of End during the Test	Feb. 14, 2010

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 5 of 40
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B



3. General Information

3.1 <u>Description of Device Under Test (DUT)</u>

Prod	Product Feature & Specification				
DUT Type	Enterprise Smartphone				
Brand Name	Motorola				
Model Name	ES405B				
FCC ID	UZ7ES405B				
	802.11b/g : 2400 MHz ~ 2483.5 MHz				
ut Type rand Name odel Name CC ID x Frequency x Frequency aximum Output Power to Antenna ntenna Type W Version W Version	802.11a : 5150 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz; 5725 MHz ~ 5850 MHz				
Rx Frequency	802.11a : 5150 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz; 5725 MHz ~ 5850 MHz				
	Bluetooth : 2400 MHz ~ 2483.5 MHz				
Maximum Output Power to Antenna	802.11b : Peak 17.22 dBm, Avg 13.98 dBm 802.11g : Peak 21.71 dBm, Avg 15.39 dBm 802.11a : Peak 21.40 dBm, Avg 15.29 dBm Bluetooth : 2.54 dBm				
Antenna Type	Motorola				
HW Version	EVT2				
SW Version	BSP2410				
Type of Modulation	802.11a/g: OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth (1Mbps): GFSK Bluetooth EDR (2Mbps): π/4-DQPSK				
DUT Stage	802.11a : 5150 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz; 5725 MHz ~ 5850 MHz				

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 6 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No.: FA010103B

List of Accessory:

	Specification of Accessory					
	Brand Name	MOTOROLA				
AC Adomtor	Model Name	IU08-2050120-WP				
AC Adapter		I/P:100-240Vac, 50-60Hz, 0.2A;				
	Power Rating	O/P: 5Vdc, 1.2A				
	Brand Name	MOTOROLA				
Dottom: 1	Model Name	82-118523-01				
Battery 1	Power Rating	3.7Vdc, 1540mAh, 5.70Wh				
	Туре	Li-ion				
	Brand Name	MOTOROLA				
Dottony 2	Model Name	82-118524-01				
Battery 2	Power Rating	3.7Vdc, 3080mAh, 11.40Wh				
	Туре	Li-ion				
	Brand Name	VXI				
Earphone	Model Name	VR 10				
	Signal Line Type	1.8 meter non-shielded cable with ferrite core				
	Brand Name	MOTOROLA				
USB Cable	Model Name	25-128458-01R				
	Signal Line Type	1.5 meter shielded cable without ferrite core				
Holster	Brand Name	MOTOROLA				
noistei	Model Name	SG-ES4021210-01R				
LCD Panel	Brand Name	SAMSUNG				
LCD Fallel	Model Name	3.0"VGA PenTile				
Cradle	Brand Name	MOTOROLA				
Craule	Model Name	CRD400-1000				
Camera	Brand Name	MOTOROLA JABIL				
Caillela	Model Name	3Mpixels				

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

3.2 Product Photos

Please refer to Appendix D.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 7 of 40
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B



3.3 Applied Standards

The Specific Absorption Rate (SAR) testing specification, method and procedure for this Enterprise Smartphone is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- IEEE C95.1-1999
- IEEE 1528-2003
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- FCC KDB 248227 D01 v01r02
- FCC KDB 648474 D01 v01r05

3.4 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

3.5 Test Conditions

3.5.1 Ambient Condition

Ambient Temperature	20 to 24 ℃
Humidity	< 60 %

3.5.2 Test Configuration

For WLAN SAR testing, WLAN engineering testing software installed on the DUT can provide continuous transmitting RF signal. This RF signal utilized in SAR measurement has almost 100% duty cycle and its crest factor is 1.

The data rates for WLAN SAR testing were set in 1 Mbps for 802.11b and 6 Mbps for 802.11a/g due to the highest RF output power which was measured by power meter. The RF power table of 802.11b/g/a is as below:

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 8 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No.: FA010103B



<Peak Power>

	Data	•	1	-	2	5		1	-
	Rate	Mb	ps	Mb	ps	Mb	ps	Mb	ps
802.11b	CH 01	16	.89	16	.82	16	.87	16.	88
	CH 06	17	.05	17	.02	16	.95	16.	98
	CH 11	17.22		17.16		17.19		17.20	
	Data	6	9	12	18	24	36	48	54
	Rate	Mbps							
802.11g	CH 01	19.94	19.52	20.05	19.41	19.78	19.75	19.67	19.92
	CH 06	21.71	21.66	21.69	21.58	21.70	21.41	21.18	20.78
	CH 11	20.25	20.01	20.36	20.03	20.49	20.05	20.02	20.44

	Data Rate	6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
	CH 36	20.33	20.16	20.45	20.21	20.27	20.19	20.25	20.21
	CH 44	21.28	21.17	21.30	21.17	21.21	20.72	20.50	20.35
	CH 48	21.34	21.27	21.33	21.31	21.31	20.85	20.60	20.39
	CH 52	21.40	21.23	21.39	21.27	21.39	20.75	20.26	20.14
000 44 0	CH 60	21.26	21.21	21.37	21.24	21.34	20.72	20.34	20.10
802.11a	CH 64	20.96	20.76	21.04	20.79	20.91	20.81	20.51	20.21
	CH 100	19.76	19.57	19.89	19.43	19.72	19.61	19.50	19.42
	CH 120	19.99	19.88	20.00	19.84	19.97	19.56	19.28	18.86
	CH 140	18.57	18.32	18.64	18.29	18.49	18.30	18.37	18.25
	CH 149	19.79	19.70	19.74	19.71	19.77	19.21	18.83	18.76
	CH 157	19.61	19.54	19.61	19.52	19.52	18.96	18.70	18.43
	CH 165	19.53	19.42	19.50	19.44	19.46	18.98	18.69	18.55

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 9 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No. : FA010103B



<Average Power>

Average	1 011012								
	Data	1	1	-	2	5.		11	-
	Rate	Mb	Mbps		Mbps		ps	Mbps	
802.11b	CH 01	13.68		13.64		13.66		13.49	
	CH 06	13.98		13.87		13.84		13.78	
	CH 11	13.92		13.81		13.88		13.85	
	Data	6	9	12	18	24	36	48	54
	Rate	Mbps							
802.11g	CH 01	10.50	10.35	10.36	10.13	9.92	9.71	9.53	9.60
	CH 06	15.39	15.30	15.21	15.26	15.00	13.95	12.70	10.53
	CH 11	11.50	11.43	11.25	11.13	11.22	10.84	10.55	10.54

	Data Rate	6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
	CH 36	12.33	12.33	12.23	12.19	11.96	11.86	11.78	10.97
	CH 44	15.25	15.15	14.99	14.94	14.71	12.47	11.58	10.76
	CH 48	15.29	15.22	15.08	15.09	14.91	12.68	11.74	10.90
	CH 52	15.11	15.11	15.07	14.97	14.64	12.35	11.51	10.49
002 440	CH 60	14.91	14.84	14.83	14.73	14.48	12.47	11.33	10.39
802.11a	CH 64	13.43	13.34	13.30	13.24	13.01	12.82	11.41	10.52
	CH 100	12.20	12.19	12.04	11.93	11.82	11.68	11.62	10.63
	CH 120	14.69	14.63	14.63	14.55	14.36	12.60	11.41	10.52
	CH 140	10.85	10.71	10.72	10.58	10.32	10.33	10.09	10.11
	CH 149	14.35	14.21	14.24	14.16	14.01	12.15	10.92	10.09
	CH 157	14.76	14.59	14.47	14.59	14.30	12.00	10.86	9.90
	CH 165	15.08	14.73	14.75	14.77	14.50	12.13	11.12	10.21

The simultaneous transmission SAR for WLAN and BT was not required because the closest separation distance of these antennas (3.8 cm) is larger than 2.5 cm and the output power of Bluetooth (2.54 dBm) is less than P_{Ref} (10.8 dBm).

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 10 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No.: FA010103B



4. Specific Absorption Rate (SAR)

4.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

4.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C\left(\frac{\delta T}{\delta t}\right)$$

Where: C is the specific head capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 11 of 40
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B



5. SAR Measurement System



Fig 5.1 SPEAG DASY4 or DASY5 System Configurations

The DASY4 or DASY5 system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- > A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (ECO) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- > A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY4 or DASY5 software
- Remove control with teach pendant and additional circuitry for robot safety such as warming lamps, etc.
- > The SAM twin phantom
- A device holder
- > Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Some of the components are described in details in the following sub-sections.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 12 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01



5.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

5.1.1 E-Field Probe Specification

<ET3DV6>

<e13dv0></e13dv0>		
Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 3 GHz; Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis)± 0.4 dB in HSL (rotation normal to probe axis)	
Dynamic Range	5 μW/g to 100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 330 mm (Tip: 16 mm) Tip diameter: 6.8 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.7 mm	Fig 5.2 Photo of ET3DV6

<EX3DV3 Probe>

		1	
Construction	Symmetrical design with triangular core		
	Built-in shielding against static charges		
	PEEK enclosure material (resistant to		
	organic solvents, e.g., DGBE)		-
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB		
Directivity	± 0.3 dB in HSL (rotation around probe		1
	axis)		
	± 0.5 dB in tissue material (rotation		3011
	normal to probe axis)		
Dynamic Range	10 μW/g to 100 mW/g; Linearity: ± 0.2 dB		
	(noise: typically < 1 μW/g)		
Dimensions	Overall length: 330 mm (Tip: 20 mm)		
	Tip diameter: 2.5 mm (Body: 12 mm)		
	Typical distance from probe tip to dipole		
	centers: 1 mm		
			T
			· I -
		Fig 5.3	Photo of EX3DV3

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 13 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No.: FA010103B



5.1.2 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than \pm 10%. The spherical isotropy shall be evaluated and within \pm 0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

5.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.4 Photo of DAE

5.3 Robot

The SPEAG DASY system uses the high precision robots (DASY4: RX90BL; DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB; DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- ➤ High precision (repeatability ±0.035 mm)
- > High reliability (industrial design)
- > Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)







Fig 5.6 Photo of DASY5

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 14 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

5.4 Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY4: 166 MHz, Intel Pentium; DASY5: 400 MHz, Intel Celeron), chipdisk (DASY4: 32 MB; DASY5: 128 MB), RAM (DASY4: 64 MB, DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.





Report No.: FA010103B

Fig 5.7 Photo of Server for DASY4

Fig 5.8 Photo of Server for DASY5

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 15 of 40
Report Issued Date : Mar. 18, 2010

5.5 Phantom

<SAM Twin Phantom>

2 ± 0.2 mm;	
Center ear point: 6 ± 0.2 mm	
Approx. 25 liters	The state of the s
Length: 1000 mm; Width: 500 mm;	
Height: adjustable feet	<u> </u>
Left Hand, Right Hand, Flat Phantom	Fig 5.9 Photo of SAM Phantom
	Center ear point: 6 ± 0.2 mm Approx. 25 liters Length: 1000 mm; Width: 500 mm; Height: adjustable feet

Report No.: FA010103B

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI4 Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	Fig 5.10 Photo of ELI4 Phantom

The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

Page Number

Report Version

: 16 of 40

: Rev. 01

Report Issued Date: Mar. 18, 2010

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B



5.6 Device Holder

<Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of \pm 0.5 mm would produce a SAR uncertainty of \pm 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Fig 5.11 Device Holder

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 17 of 40
Report Issued Date : Mar. 18, 2010

<Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.




Fig 5.12 Laptop Extension Kit

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 18 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No.: FA010103B



5.7 Data Storage and Evaluation

5.7.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

5.7.2 Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters: - Sensitivity Norm_i, a_{i0} , a_{i1} , a_{i2}

Conversion factor
 Diode compression point
 Frequency
 ConvF_i
 dcp_i
 f

Device parameters: - Frequency f

 $\begin{array}{c} \text{- Crest factor} & \text{cf} \\ \textbf{Media parameters} & \text{- Conductivity} & \sigma \end{array}$

- Density ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 19 of 40
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B

The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Report No.: FA010103B

with V_i = compensated signal of channel i, (i = x, y, z)

 U_i = input signal of channel i, (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp_i = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated:

$$\text{E-field Probes}: E_i = \sqrt{\frac{v_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

H-field Probes :
$$H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with V_i = compensated signal of channel i, (i = x, y, z)

Norm_i = sensor sensitivity of channel i, (i = x, y, z), $\mu V/(V/m)^2$ for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g

 E_{tot} = total field strength in V/m

 σ = conductivity in [mho/m] or [Siemens/m]

 ρ = equivalent tissue density in g/cm³

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

Page Number

Report Version

: 20 of 40

: Rev. 01

Report Issued Date: Mar. 18, 2010

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B

5.8 Test Equipment List

		- 0- 1		Calib	Calibration		
Manufacturer	Name of Equipment	Type/Model	Serial Number	Last Cal.	Due Date		
SPEAG	Dosimetric E-Field Probe	ET3DV6	1787	May 26, 2009	May 25, 2010		
SPEAG	Dosimetric E-Field Probe	ET3DV6	1788	Sep. 23, 2009	Sep. 22, 2010		
SPEAG	Dosimetric E-Field Probe	EX3DV3	3514	Jan. 26, 2010	Jan. 25, 2011		
SPEAG	Dosimetric E-Field Probe	EX3DV4	3578	Jun. 26, 2009	Jun. 25, 2010		
SPEAG	Dosimetric E-Field Probe	EX3DV4	3661	Dec. 30, 2009	Dec. 29, 2010		
SPEAG	Dosimetric E-Field Probe	EX3DV4	3697	Nov. 23, 2009	Nov. 22, 2010		
SPEAG	835MHz System Validation Kit	D835V2	499	Mar. 17, 2008	Mar. 16, 2010		
SPEAG	900MHz System Validation Kit	D900V2	190	Jul. 21, 2009	Jul. 20, 2011		
SPEAG	1800MHz System Validation Kit	D1800V2	2d076	Jul. 20, 2009	Jul. 19, 2011		
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Mar. 28, 2008	Mar. 27, 2010		
SPEAG	2000MHz System Validation Kit	D2000V2	1010	Sep. 17, 2008	Sep. 16, 2010		
SPEAG	2300MHz System Validation Kit	D2300V2	1006	Sep. 24, 2009	Sep. 23, 2011		
SPEAG	2450MHz System Validation Kit	D2450V2	736	Jul. 20, 2009	Jul. 19, 2011		
SPEAG	2600MHz System Validation Kit	D2600V2	1008	Sep. 24, 2009	Sep. 23, 2011		
SPEAG	3500MHz System Validation Kit	D3500V2	1014	Sep. 17, 2009	Sep. 16, 2011		
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Jan. 21, 2010	Jan. 20, 2012		
SPEAG	Data Acquisition Electronics	DAE3	577	Aug. 24, 2009	Aug. 23, 2010		
SPEAG	Data Acquisition Electronics	DAE4	778	Sep. 18, 2009	Sep. 17, 2010		
SPEAG	Data Acquisition Electronics	DAE4	1210	Nov. 16, 2009	Nov. 15, 2010		
SPEAG	Device Holder	N/A	N/A	NCR	NCR		
SPEAG	SAM Phantom	QD 000 P40 C	TP-1303	NCR	NCR		
SPEAG	SAM Phantom	QD 000 P40 C	TP-1383	NCR	NCR		
SPEAG	SAM Phantom	QD 000 P40 C	TP-1446	NCR	NCR		
SPEAG	SAM Phantom	QD 000 P40 C	TP-1478	NCR	NCR		
SPEAG	ELI4 Phantom	QD 0VA 001 BB	1026	NCR	NCR		
SPEAG	ELI4 Phantom	QD 0VA 001 BA	1029	NCR	NCR		
Agilent	PNA Series Network Analyzer	E8358A	US40260131	Apr. 17, 2009	Apr. 16, 2010		
Agilent	Wireless Communication Test Set	E5515C	MY48360820	Dec. 15, 2008	Dec. 14, 2010		
Agilent	Wireless Communication Test Set	E5515C	GB46311322	Feb. 16, 2009	Feb. 15, 2011		
R&S	Universal Radio Communication Tester	CMU200	108082	Jun. 08, 2009	Jun. 07, 2010		
Agilent	Dielectric Probe Kit	85070D	US01440205	NCR	NCR		
Agilent	Dual Directional Coupler	778D	50422	NCR	NCR		
AR	Power Amplifier	5S1G4M2	0328767	NCR	NCR		
R&S	Spectrum Analyzer	FSP7	101131	Mar. 17, 2009	Mar. 16, 2010		

Table 5.1 Test Equipment List

Note: The calibration certificate of DASY can be referred to appendix C of this report.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 21 of 40
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B



6. <u>Tissue Simulating Liquids</u>

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.





Fig 6.1 Photo of Liquid Height for Head SAR

Fig 6.2 Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency	Water	Sugar	Cellulose	Salt	Preventol	DGBE	Conductivity	Permittivity		
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	(σ)	(ε _r)		
	For Head									
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5		
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5		
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0		
2450	55.0	0	0	0	0	45.0	1.80	39.2		
				For Body						
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2		
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0		
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3		
2450	68.6	0	0	0	0	31.4	1.95	52.7		

Table 6.1 Recipes of Tissue Simulating Liquid

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 22 of 40
Report Issued Date : Mar. 18, 2010



The following table gives the targets for tissue simulating liquid.

Frequency (MHz)	Liquid Type	Conductivity (σ)	±5% Range	Permittivity (ϵ_r)	±5% Range
2450	Head	1.80	1.71 ~ 1.89	39.2	37.2 ~ 41.2
5200	Head	4.66	4.43 ~ 4.89	36.0	34.2 ~ 37.8
5500	Head	4.96	4.71 ~ 5.21	35.6	33.8 ~ 37.4
5800	Head	5.27	5.01 ~ 5.53	35.3	33.5 ~ 37.1
2450	Body	1.95	1.85 ~ 2.05	52.7	50.1 ~ 55.3
5200	Body	5.30	5.04 ~ 5.57	49.0	46.6 ~ 51.5
5500	Body	5.65	5.37 ~ 5.93	48.6	46.2 ~ 51.0
5800	Body	6.00	5.70 ~ 6.30	48.2	45.8 ~ 50.6

Table 6.2 Targets of Tissue Simulating Liquid

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

The following table shows the measuring results for simulating liquid.

Frequency (MHz)	Liquid Type	Temperature (°C)	Conductivity (σ)	Permittivity (ε _r)	Measurement Date
2450	Head	21.4	1.86	37.5	Jan. 21, 2010
2450	Head	21.5	1.84	38.7	Feb. 02, 2010
2450	Body	21.3	1.91	53.4	Jan. 21, 2010
2450	Body	21.3	1.93	53.3	Feb. 08, 2010
5200	Head	21.4	4.56	35.9	Jan. 30, 2010
5200	Body	21.3	5.11	47.4	Feb. 09, 2010
5200	Body	21.3	5.14	47.5	Feb. 13, 2010
5200	Body	21.3	5.34	47.5	Feb. 14, 2010
5500	Head	21.4	4.86	35.1	Feb. 01, 2010
5500	Body	21.3	5.49	47.0	Feb. 09, 2010
5500	Body	21.3	5.73	46.9	Feb. 14, 2010
5800	Head	21.4	5.17	34.9	Jan. 30, 2010
5800	Body	21.3	5.96	46.5	Feb. 13, 2010

Table 6.3 Measuring Results for Simulating Liquid

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 23 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No.: FA010103B

7. Uncertainty Assessment

The component of uncertainly may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainly by the statistical analysis of a series of observations is termed a Type An evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 7.1

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	1/k ^(b)	1/√3	1/√6	1/√2

⁽a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

Table 7.1 Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is showed in Table 7.2 and Table 7.3.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 24 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No.: FA010103B

⁽b) κ is the coverage factor

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Standard Uncertainty (1g)		
Measurement System				_			
Probe Calibration	5.9	Normal	1	1	± 5.9 %		
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %		
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %		
Boundary Effects	1.0	Rectangular	√3	1	± 0.6 %		
Linearity	4.7	Rectangular	√3	1	± 2.7 %		
System Detection Limits	1.0	Rectangular	√3	1	± 0.6 %		
Readout Electronics	0.3	Normal	1	1	± 0.3 %		
Response Time	0.8	Rectangular	√3	1	± 0.5 %		
Integration Time	2.6	Rectangular	√3	1	± 1.5 %		
RF Ambient Noise	3.0	Rectangular	√3	1	± 1.7 %		
RF Ambient Reflections	3.0	Rectangular	√3	1	± 1.7 %		
Probe Positioner	0.4	Rectangular	√3	1	± 0.2 %		
Probe Positioning	2.9	Rectangular	√3	1	± 1.7 %		
Max. SAR Eval.	1.0	Rectangular	√3	1	± 0.6 %		
Test Sample Related							
Device Positioning	2.9	Normal	1	1	± 2.9 %		
Device Holder	3.6	Normal	1	1	± 3.6 %		
Power Drift	5.0	Rectangular	√3	1	± 2.9 %		
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	± 2.3 %		
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	± 1.8 %		
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	± 1.6 %		
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	± 1.7 %		
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	± 1.5 %		
Combined Standard Uncertainty							
Coverage Factor for 95 %							
Expanded Uncertainty					± 21.8 %		

Table 7.2 Uncertainty Budget of DASY for frequency range 300 MHz to 3 GHz

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 25 of 40
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B

CC SAR Test Report	Report No. : FA010103B
--------------------	------------------------

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Standard Uncertainty (1g)	
Measurement System		•		•		
Probe Calibration	6.5	Normal	1	1	± 6.5 %	
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %	
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %	
Boundary Effects	2.0	Rectangular	√3	1	± 1.2 %	
Linearity	4.7	Rectangular	√3	1	± 2.7 %	
System Detection Limits	1.0	Rectangular	√3	1	± 0.6 %	
Readout Electronics	0.3	Normal	1	1	± 0.3 %	
Response Time	0.8	Rectangular	√3	1	± 0.5 %	
Integration Time	2.6	Rectangular	√3	1	± 1.5 %	
RF Ambient Noise	3.0	Rectangular	√3	1	± 1.7 %	
RF Ambient Reflections	3.0	Rectangular	√3	1	± 1.7 %	
Probe Positioner	0.8	Rectangular	√3	1	± 0.5 %	
Probe Positioning	9.9	Rectangular	√3	1	± 5.7 %	
Max. SAR Eval.	4.0	Rectangular	√3	1	± 2.3 %	
Test Sample Related						
Device Positioning	2.9	Normal	1	1	± 2.9 %	
Device Holder	3.6	Normal	1	1	± 3.6 %	
Power Drift	5.0	Rectangular	√3	1	± 2.9 %	
Phantom and Setup						
Phantom Uncertainty	4.0	Rectangular	√3	1	± 2.3 %	
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.43	± 1.8 %	
Liquid Conductivity (Meas.)	2.5	Normal	1	0.43	± 1.6 %	
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.49	± 1.7 %	
Liquid Permittivity (Meas.)	2.5	Normal	1	0.49	± 1.5 %	
Combined Standard Uncertainty						
Coverage Factor for 95 %					K = 2	
Expanded Uncertainty					± 25.6 %	

Table 7.3 Uncertainty Budget of DASY for frequency range 3 GHz to 6 GHz

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 26 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01



8. SAR Measurement Evaluation

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

8.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

8.2 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig 8.1 System Setup for System Evaluation

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 27 of 40
Report Issued Date : Mar. 18, 2010



- 1. Signal Generator
- 2. Amplifier
- 3. Directional Coupler
- 4. Power Meter
- 5. Calibrated Dipole

The output power on dipole port must be calibrated to 20 dBm (100 mW) before dipole is connected.



Fig 8.2 Photo of Dipole Setup

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B

Page Number : 28 of 40 Report Issued Date: Mar. 18, 2010

Report No.: FA010103B

8.3 Validation Results

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %. Table 8.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Measurement Date	Frequency (MHz)	Targeted SAR _{1g} (W/kg)	Measured SAR _{1g} (W/kg)	Deviation (%)
Jan. 21, 2010	2450	54.20	53.70	-0.92
Feb. 02, 2010	2450	54.20	53.10	-2.03
Feb. 08, 2010	2450	53.00	49.10	-7.36
Jan. 30, 2010	5200	82.20	86.40	5.11
Feb. 09, 2010	5200	79.00	71.90	-8.99
Feb. 13, 2010	5200	79.00	82.30	4.18
Feb. 14, 2010	5200	79.00	75.00	-5.06
Feb. 01, 2010	5500	88.80	93.80	5.63
Feb. 09, 2010	5500	85.40	78.80	-7.73
Feb. 14, 2010	5500	85.40	82.30	-3.63
Jan. 30, 2010	5800	78.20	80.30	2.69
Feb. 13, 2010	5800	73.70	78.40	6.38

Table 8.1 Target and Measurement SAR after Normalized

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B

Page Number : 29 of 40 Report Issued Date: Mar. 18, 2010

Report No.: FA010103B



9. <u>DUT Testing Position</u>

This DUT was tested in seven different positions. They are right cheek, right tilted, left cheek, left tilted, face of the DUT with phantom 1.5 cm gap, bottom of the DUT with phantom 1.5 cm gap, and bottom of holster with the phantom 0 cm gap as illustrated below:

1. Define two imaginary lines on the handset

- (a) The vertical centerline passes through two points on the front side of the handset the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig 9.1 Illustration for Handset Vertical and Horizontal Reference Lines

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 30 of 40
Report Issued Date : Mar. 18, 2010



2. Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 9.2).



Fig 9.2 Illustration for Cheek Position

3. Tilted Position

- (a) To position the device in the "cheek" position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 9.3).



Fig 9.3 Illustration for Tilted Position

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 31 of 40 Report Issued Date : Mar. 18, 2010



4. Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.5 cm or bottom of holster and the flat phantom to 0 cm.




Fig 9.4 Illustration for Body Worn Position

5. DUT Setup Photos

Please refer to Appendix E for the test setup photos.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 32 of 40 Report Issued Date : Mar. 18, 2010

Report No.: FA010103B

10. Measurement Procedures

The measurement procedures are as follows:

- (a) Use engineering software to transmit RF power continuously (continuous Tx) in the middle channel
- (b) Measure output power through RF cable and power meter
- (c) Place the DUT in the positions described in the last section
- (d) Set scan area, grid size and other setting on the DASY software
- (e) Taking data for the middle channel on each testing position
- (f) Find out the largest SAR result on these testing positions of each band
- (g) Measure SAR results for the lowest and highest channels in worst SAR testing position

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

10.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 33 of 40
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B



10.2 Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4.3, 4.3 and 3 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

10.3 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 34 of 40 Report Issued Date : Mar. 18, 2010

Report No.: FA010103B



11. SAR Test Results

11.1 Conducted Power (Unit: dBm)

Band	802.11b			802.11g		
Channel	1	6	11	1	6	11
Frequency (MHz)	2412	2437	2462	2412	2437	2462
Peak Power	16.89	17.05	17.22	19.94	21.71	20.25
Average Power	13.68	13.98	13.92	10.50	15.39	11.50

Band	802.11a					
Channel	36	36 44 48 52 60 64				
Frequency (MHz)	5180	5240	5260	5320	5500	5600
Peak Power	20.33	21.28	21.34	21.40	21.26	20.96
Average Power	12.33	15.25	15.29	15.11	14.91	13.43

Band		802.11a				
Channel	100	100 120 140 149 157 165				
Frequency (MHz)	5500	5600	5700	5745	5785	5825
Peak Power	19.76	19.99	18.57	19.79	19.61	19.53
Average Power	12.20	14.69	10.85	14.35	14.76	15.08

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B

Page Number : 35 of 40 Report Issued Date: Mar. 18, 2010

Report No. : FA010103B



11.2 Test Records for Head SAR Test

Plot No.	Band	Test Position	Channel	Battery	SAR _{1g} (W/kg)
#143	802.11b	Right Cheek	6	1	0.065
#144	802.11b	Right Cheek	6	2	0.063
#145	802.11g	Right Cheek	6	1	0.094
#146	802.11g	Right Tilted	6	1	0.079
#147	802.11g	Left Cheek	6	1	0.124
#148	802.11g	Left Tilted	6	1	0.089
#149	802.11g	Left Cheek	1	1	0.05
#150	802.11g	Left Cheek	11	1	0.038
#151	802.11g	Left Cheek	12	1	0.012
#152	802.11g	Left Cheek	13	1	0.000243
#153	802.11g with Bluetooth On	Left Cheek	6	1	0.128
#111	802.11a	Right Cheek	36	1	0.052
#112	802.11a	Right Cheek	36	2	0.046
#113	802.11a	Right Tilted	36	1	0.06
#114	802.11a	Left Cheek	36	1	0.074
#115	802.11a	Left Tilted	36	1	0.075
#116	802.11a	Left Tilted	48	1	0.213
#117	802.11a with Bluetooth On	Left Tilted	48	1	0.163
#118	802.11a	Right Cheek	52	1	0.159
#119	802.11a	Right Cheek	52	2	0.103
#120	802.11a	Right Tilted	52	1	0.117
#121	802.11a	Left Cheek	52	1	0.147
#122	802.11a	Left Tilted	52	1	0.135
#123	802.11a	Right Cheek	64	1	0.073
#124	802.11a with Bluetooth On	Right Cheek	52	1	0.126
#125	802.11a	Right Cheek	104	1	0.204
#126	802.11a	Right Cheek	104	2	0.212
#127	802.11a	Right Tilted	104	2	0.229
#128	802.11a	Left Cheek	104	2	0.225
#129	802.11a	Left Tilted	104	2	0.24
#130	802.11a	Left Tilted	116	2	0.445
#131	802.11a	Left Tilted	124	2	0.433
#132	802.11a	Left Tilted	136	2	0.175
#133	802.11a with Bluetooth On	Left Tilted	116	2	0.443

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 36 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No. : FA010103B



Plot No.	Band	Test Position	Channel	Battery	SAR _{1g} (W/kg)
#134	802.11a	Right Cheek	149	1	0.252
#135	802.11a	Right Cheek	149	2	0.22
#136	802.11a	Right Tilted	149	1	0.271
#137	802.11a	Left Cheek	149	1	0.329
#138	802.11a	Left Tilted	149	1	0.332
#139	802.11a	Left Tilted	157	1	0.257
#140	802.11a	Left Tilted	161	1	0.355
#141	802.11a	Left Tilted	165	1	0.351
#142	802.11a with Bluetooth On	Left Tilted	161	1	0.351

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 37 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No.: FA010103B



11.3 Test Records for Body SAR Test

<1> DUT with Flat Phantom 1.5 cm Gap

Plot No.	Band	Test Position	Separation Distance (cm)	Channel	Battery	SAR _{1g} (W/kg)
#154	802.11b	Bottom	1.5	6	1	0.044
#155	802.11b	Bottom	1.5	6	2	0.036
#156	802.11g	Bottom	1.5	6	1	0.061
#157	802.11g	Face	1.5	6	1	0.016
#158	802.11g	Bottom	1.5	1	1	0.018
#159	802.11g	Bottom	1.5	11	1	0.021
#160	802.11g	Bottom	1.5	12	1	0.00511
#161	802.11g	Bottom	1.5	13	1	0.000112
#162	802.11g with Bluetooth On	Bottom	1.5	6	1	0.06
#163	802.11a	Bottom	1.5	36	1	0.135
#164	802.11a	Bottom	1.5	36	2	0.105
#165	802.11a	Face	1.5	36	1	0.078
#166	802.11a	Bottom	1.5	48	1	0.211
#167	802.11a with Bluetooth On	Bottom	1.5	48	1	0.215
#168	802.11a	Bottom	1.5	52	1	0.299
#169	802.11a	Bottom	1.5	52	2	0.153
#170	802.11a	Face	1.5	52	1	0.119
#171	802.11a	Bottom	1.5	64	1	0.317
#172	802.11a with Bluetooth On	Bottom	1.5	64	1	0.156
#173	802.11a	Bottom	1.5	104	1	0.143
#174	802.11a	Bottom	1.5	104	2	0.104
#175	802.11a	Face	1.5	104	1	0.058
#176	802.11a	Bottom	1.5	116	1	0.221
#177	802.11a	Bottom	1.5	124	1	0.201
#178	802.11a	Bottom	1.5	136	1	0.097
#179	802.11a with Bluetooth On	Bottom	1.5	116	1	0.158
#180	802.11a	Bottom	1.5	149	1	0.243
#181	802.11a	Bottom	1.5	149	2	0.221
#182	802.11a	Face	1.5	149	1	0.05
#183	802.11a	Bottom	1.5	157	1	0.225
#184	802.11a	Bottom	1.5	161	1	0.216
#185	802.11a	Bottom	1.5	165	1	0.237
#186	802.11a with Bluetooth On	Bottom	1.5	149	1	0.219

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B

Page Number : 38 of 40 Report Issued Date: Mar. 18, 2010 Report Version : Rev. 01

<2> Holster Touching with Flat Phantom 0 cm Gap

Plot No.	Band	Test Position	Separation Distance (cm)	Channel	Battery	SAR _{1g} (W/kg)
#01	802.11b	Bottom	0	6	1	0.081
#02	802.11b	Bottom	0	6	2	0.056
#03	802.11g	Bottom	0	6	1	0.072
#04	802.11b	Face	0	6	1	0.015
#05	802.11b	Bottom	0	1	1	0.081
#06	802.11b	Bottom	0	11	1	0.061
#07	802.11b	Bottom	0	12	1	0.02
#08	802.11b	Bottom	0	13	1	0.00389
#09	802.11b with Bluetooth On	Bottom	0	1	1	0.083
#10	802.11a	Bottom	0	36	1	0.052
#11	802.11a	Bottom	0	36	2	0.031
#12	802.11a	Face	0	36	1	0.00126
#13	802.11a	Bottom	0	48	1	0.136
#14	802.11a with Bluetooth On	Bottom	0	48	1	0.153
#15	802.11a	Bottom	0	52	1	0.15
#16	802.11a	Bottom	0	52	2	0.084
#17	802.11a	Face	0	52	1	0.02
#18	802.11a	Bottom	0	64	1	0.099
#19	802.11a with Bluetooth On	Bottom	0	52	1	0.123
#20	802.11a	Bottom	0	104	1	0.124
#21	802.11a	Bottom	0	104	2	0.159
#22	802.11a	Face	0	104	1	0.028
#23	802.11a	Bottom	0	116	1	0.252
#24	802.11a	Bottom	0	124	1	0.258
#25	802.11a	Bottom	0	136	1	0.217
#26	802.11a with Bluetooth On	Bottom	0	124	1	0.247
#27	802.11a	Bottom	0	149	1	0.281
#28	802.11a	Bottom	0	149	2	0.189
#29	802.11a	Face	0	149	1	0.061
#30	802.11a	Bottom	0	157	1	0.239
#31	802.11a	Bottom	0	161	1	0.228
#32	802.11a	Bottom	0	165	1	0.224
#33	802.11a with Bluetooth On	Bottom	0	149	1	0.221

Test Engineer: A-Rod Chen, Eric Huang and Robert Liu

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : 39 of 40
Report Issued Date : Mar. 18, 2010
Report Version : Rev. 01

Report No. : FA010103B



12. References

[1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"

Report No.: FA010103B

- [2] IEEE Std. C95.1-1999, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", 1999
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", June 2001
- [5] SPEAG DASY System Handbook
- [6] FCC KDB 248227 D01 v01r02, "SAR Measurement Procedures for 802.11 a/b/g Transmitters", May 2007
- [7] FCC KDB 447498 D01 v04, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", November 2009
- [8] FCC KDB 447498 D02 v02, "SAR Measurement Procedures for USB Dongle Transmitters", November 2009
- [9] FCC KDB 616217 D01 v01r01, "SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens", November 2009
- [10] FCC KDB 616217 D03 v01, "SAR Evaluation Considerations for Laptop/Notebook/Netbook and Tablet Computers", November 2009
- [11] FCC KDB 648474 D01 v01r05, "SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas", September 2008
- [12] FCC KDB 941225 D01 v02, "SAR Measurement Procedures for 3G Devices CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA", October 2007
- [13] FCC KDB 941225 D03 v01, "Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE", December 2008

 SPORTON INTERNATIONAL INC.
 Page Number
 : 40 of 40

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 18, 2010

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID: UZ7ES405B



Appendix A. Plots of System Performance Check

The plots are shown as follows.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : A1 of A1
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B



Appendix B. Plots of SAR Measurement

The plots are shown as follows.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : B1 of B1
Report Issued Date : Mar. 18, 2010

Report No.: FA010103B



Appendix C. DASY Calibration Certificate

The DASY calibration certificates are shown as follows.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ES405B Page Number : C1 of C1
Report Issued Date : Mar. 18, 2010

Report No. : FA010103B