FCC RF Test Report

APPLICANT: Zebra Technologies Corporation

EQUIPMENT: Enterprise Tablet

BRAND NAME : Zebra

MODEL NAME : ET55BE

FCC ID : UZ7ET55BE

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION: (DTS) Digital Transmission System

The product was received on May 03, 2016 and testing was completed on Jun. 07. 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 1 of 35 Report Issued Date : Jun. 22, 2016

1190

: Rev. 01

Report No.: FR650305B

Report Template No.: BU5-FR15CBT4.0 Version 1.3

Report Version

TABLE OF CONTENTS

SU	MMAI	RY OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	
	1.3	Product Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	5
	1.5	Modification of EUT	6
	1.6	Testing Location	6
	1.7	Applicable Standards	6
2	TES	T CONFIGURATION OF EQUIPMENT UNDER TEST	7
	2.1	Descriptions of Test Mode	7
	2.2	Test Mode	7
	2.3	Connection Diagram of Test System	8
	2.4	Support Unit used in test configuration and system	
	2.5	EUT Operation Test Setup	9
	2.6	Measurement Results Explanation Example	9
3	TES	T RESULT	10
	3.1	6dB and 99% Bandwidth Measurement	10
	3.2	Peak Output Power Measurement	15
	3.3	Power Spectral Density Measurement	16
	3.4	Conducted Band Edges and Spurious Emission Measurement	
	3.5	Radiated Band Edges and Spurious Emission Measurement	26
	3.6	AC Conducted Emission Measurement	
	3.7	Antenna Requirements	33
4	LIST	OF MEASURING EQUIPMENT	34
5	UNC	ERTAINTY OF EVALUATION	35
ΑP	PEND	DIX A. CONDUCTED TEST RESULTS	
ΑP	PEND	DIX B. RADIATED SPURIOUS EMISSION	
ΑP	PEND	DIX C. RADIATED SPURIOUS EMISSION PLOTS	
ΑP	PEND	DIX D. DUTY CYCLE PLOTS	

SPORTON INTERNATIONAL INC.

APPENDIX E. SETUP PHOTOGRAPHS

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 2 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No. : FR650305B

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR650305B	Rev. 01	Initial issue of report	Jun. 22, 2016

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 3 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(1)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 7.47 dB at 2488.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 14.60 dB at 1.030 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 4 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

1 General Description

1.1 Applicant

Zebra Technologies Corporation

1 Zebra Plaza, Holtsville, NY 11742

1.2 Manufacturer

Zebra Technologies Corporation

1 Zebra Plaza, Holtsville, NY 11742

1.3 Product Feature of Equipment Under Test

Product Feature				
Equipment	Enterprise Tablet			
Brand Name	Zebra			
Model Name	ET55BE			
FCC ID	UZ7ET55BE			
	Brand Name: Sierra			
Integrated WWAN Module	Model Name: EM7355			
	FCC ID: N7NEM7355			
	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/NFC			
FUT assessed Badisa anniisation	WLAN 11a/b/g/n HT20/HT40			
EUT supports Radios application	WLAN 11ac VHT20/VHT40/VHT80			
	Bluetooth v4.0 EDR/LE			
HW Version	DV1			
SW Version	5.1.1			
FW Version	7.35.205.4			
MFD	23-Mar-16			
EUT Stage	Identical Prototype			

Report No.: FR650305B

: 5 of 35

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification			
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz		
Number of Channels	40		
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)		
Maximum Output Power to Antenna	6.43 dBm (0.0044 W)		
99% Occupied Bandwidth	1.05MHz		
Antenna Type	Ceramic Chip Antenna type with gain 1.90 dBi		
Type of Modulation	Bluetooth LE : GFSK		

SPORTON INTERNATIONAL INC.Page NumberTEL: 886-3-327-3456Report Issued

TEL: 886-3-327-3456 Report Issued Date : Jun. 22, 2016 FAX: 886-3-328-4978 Report Version : Rev. 01

FCC ID : UZ7ET55BE Report Template No.: BU5-FR15CBT4.0 Version 1.3

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Report No.: FR650305B

Test Site	SPORTON INTERNATIONAL INC.		
	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park,		
Toot Site Legation	Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.		
Test Site Location	TEL: +886-3-327-3456		
	FAX: +886-3-328-4978		
Took Site No		Sporton Site No.	
Test Site No.	TH05-HY	CO05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ANSI C63.10-2013

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 6 of 35

 TEL: 886-3-327-3456
 Report Issued Date
 : Jun. 22, 2016

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID : UZ7ET55BE Report Template No.: BU5-FR15CBT4.0 Version 1.3

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

		Bluetooth 4.0 – LE RF Output Power
Channal	Eroguenev	Data Rate / Modulation
Channel	el Frequency	GFSK
		1Mbps
Ch00	2402MHz	4.70 dBm
Ch19	2440MHz	<mark>6.43</mark> dBm
Ch39	2480MHz	6.04 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (X plane as worst plane) from all possible combinations.
- b. AC power line Conducted Emission was tested under maximum output power.

2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


	Summary table of Test Cases				
Test Item	Data Rate / Modulation				
rest item	Bluetooth 4.0 – LE / GFSK				
Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps				
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps				
TCs	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps				
Radiated	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps				
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps				
TCs	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps				
AC	Mode 1: Bluetooth Link + WLAN (2.4GHz) Link + Battery + Earphone + USB Cable				
Conducted					
Emission	(Charging from Adapter)				

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 7 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01


Report No.: FR650305B

2.3 Connection Diagram of Test System

<Bluetooth 4.0 - LE Tx Mode>



<AC Conducted Emission Mode>



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 8 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	D-Link	DIR-865L	KA2IR865LA1	N/A	Unshielded, 1.8 m
3.	Notebook	DELL		FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	USB2.0 HD	WD	WDBAAR3200 ABK-PESN	FCC DoC	Unshielded, 0.5 m	N/A
5.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
6.	Adapter	Delta Electronics	ADP-10BWC	FCC DoC	N/A	N/A
7.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, "ADB" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB). = 4.2 + 10 = 14.2 (dB) Report No.: FR650305B

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- 5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
- 6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth


Test data refer to Appendix A.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 10 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01


Report No.: FR650305B

6 dB Bandwidth Plot on Channel 00



Date: 7.JUN.2016 05:25:22

6 dB Bandwidth Plot on Channel 19




Date: 7.JUN.2016 05:11:41

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 11 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

6 dB Bandwidth Plot on Channel 39



Date: 7.JUN.2016 05:16:01


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 12 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

3.1.6 Test Result of 99% Occupied Bandwidth


Test data refer to Appendix A.

99% Bandwidth Plot on Channel 00



Date: 7.JUN.2016 05:07:39

99% Occupied Bandwidth Plot on Channel 19




Date: 7.JUN.2016 05:13:34

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 13 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

99% Occupied Bandwidth Plot on Channel 39



Date: 7.JUN.2016 05:18:20

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 14 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

- The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas.
 Guidance v03r05 section 9.1.2 PKPM1 Peak power meter method.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Test data refers to Appendix A.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 15 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

- The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.
- 7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Test data refers to Appendix A.


SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 16 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B


3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00



Date: 7.JUN.2016 05:06:30

PSD 100kHz Plot on Channel 19




Date: 7.JUN.2016 05:12:37

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 17 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

PSD 100kHz Plot on Channel 39




Date: 7.JUN.2016 05:17:03

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 18 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B


3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00



Date: 7.JUN.2016 05:06:11

PSD 3kHz Plot on Channel 19




Date: 7.JUN.2016 05:12:14

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 19 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

PSD 3kHz Plot on Channel 39



Date: 7.JUN.2016 05:16:23

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 20 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
- 5. Measure and record the results in the test report.
- The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup




SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 21 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B


3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 7.JUN.2016 05:06:48

High Band Edge Plot on Channel 39



Date: 7.JUN.2016 05:17:22


SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 22 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B


3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 7.JUN.2016 05:07:02

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 7.JUN.2016 05:07:11

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 23 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01


Report No.: FR650305B

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 7.JUN.2016 05:12:53

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 7.JUN.2016 05:13:02

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 24 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01


Report No.: FR650305B

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 7.JUN.2016 05:17:41

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 7.JUN.2016 05:17:50

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 25 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency	Field Strength	Measurement Distance	
(MHz)	(microvolts/meter)	(meters)	
0.009 - 0.490	2400/F(kHz)	300	
0.490 – 1.705	24000/F(kHz)	30	
1.705 – 30.0	30	30	
30 – 88	100	3	
88 – 216	150	3	
216 - 960	200	3	
Above 960	500	3	

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
- 3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- 7. Use the following spectrum analyzer settings:

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 26 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B


- - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;

Report No.: FR650305B


- (3) Set RBW = 1 MHz, VBW= 3MHz for $f \ge 1$ GHz for peak measurement. For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 27 of 35 Report Issued Date: Jun. 22, 2016 Report Version : Rev. 01

For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 28 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)		
Frequency of emission (MHZ)	Quasi-peak	Average	
0.15-0.5	66 to 56*	56 to 46*	
0.5-5	56	46	
5-30	60	50	

^{*}Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures


- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

SPORTON INTERNATIONAL INC.
TEL: 886-3-327-3456

FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 29 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

3.6.4 Test Setup



AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 30 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

3.6.5 **Test Result of AC Conducted Emission**

Test Mode :	Mode 1	Temperature :	25~26℃
Test Engineer :	Kai-Chun Chu	Relative Humidity :	54~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type:	Bluetooth Link + WLAN (2.4GHz) Link + Battery + Earphone + USB Cable		

(Charging from Adapter)



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.166000	40.3	Off	L1	19.6	24.9	65.2
0.238000	38.9	Off	L1	19.6	23.3	62.2
0.326000	38.3	Off	L1	19.6	21.3	59.6
0.990000	39.6	Off	L1	19.6	16.4	56.0
1.198000	38.7	Off	L1	19.6	17.3	56.0
2.206000	32.1	Off	L1	19.5	23.9	56.0
3.142000	31.6	Off	L1	19.6	24.4	56.0

Final Result : Average

٠.	mai itcsait						
	Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
	(1411-12)	(ивру)			(ub)	(ub)	(ασμν)
	0.166000	28.0	Off	L1	19.6	27.2	55.2
	0.238000	32.4	Off	L1	19.6	19.8	52.2
	0.326000	27.9	Off	L1	19.6	21.7	49.6
	0.990000	27.9	Off	L1	19.6	18.1	46.0
	1.198000	27.4	Off	L1	19.6	18.6	46.0
	2.206000	21.8	Off	L1	19.5	24.2	46.0
	3.142000	21.4	Off	L1	19.6	24.6	46.0

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE


Page Number : 31 of 35 Report Issued Date: Jun. 22, 2016 Report Version : Rev. 01

Report No.: FR650305B



Test Mode :	Mode 1	Temperature :	25~26 ℃
Test Engineer :	Kai-Chun Chu	Relative Humidity :	54~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral

Function Type: Bluetooth Link + WLAN (2.4GHz) Link + Battery + Earphone + USB Cable (Charging from Adapter)



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	42.6	Off	N	19.6	23.0	65.6
0.238000	41.3	Off	N	19.6	20.9	62.2
0.358000	38.5	Off	N	19.6	20.3	58.8
0.718000	36.9	Off	N	19.6	19.1	56.0
0.918000	38.6	Off	N	19.6	17.4	56.0
1.030000	41.4	Off	N	19.6	14.6	56.0
1.190000	41.0	Off	N	19.6	15.0	56.0
1.590000	37.3	Off	N	19.6	18.7	56.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	27.7	Off	N	19.6	27.9	55.6
0.238000	35.0	Off	N	19.6	17.2	52.2
0.358000	29.2	Off	N	19.6	19.6	48.8
0.718000	25.5	Off	N	19.6	20.5	46.0
0.918000	24.9	Off	N	19.6	21.1	46.0
1.030000	27.6	Off	N	19.6	18.4	46.0
1.190000	28.0	Off	N	19.6	18.0	46.0
1.590000	26.6	Off	N	19.6	19.4	46.0

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 32 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 33 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1132003	300MHz~40GH z	Aug. 12, 2015	Jun. 02, 2016 ~ Jun. 07, 2016	Aug. 11, 2016	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1126017	300MHz~40GH z	Aug. 12, 2015	Jun. 02, 2016 ~ Jun. 07, 2016	Aug. 11, 2016	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 23, 2015	Jun. 02, 2016 ~ Jun. 07, 2016	Nov. 22, 2016	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 14, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	May 14, 2016	Aug. 25, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	May 14, 2016	Dec. 01, 2016	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D	35419	30MHz to 1GHz	Jan. 13, 2016	May 18, 2016 ~ Jun. 06, 2016	Jan. 12, 2017	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 21, 2015	May 18, 2016 ~ Jun. 06, 2016	Aug. 20, 2016	Radiation (03CH07-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY541300 85	20Hz ~ 8.4GHz	Nov. 04, 2015	May 18, 2016 ~ Jun. 06, 2016	Nov. 03, 2016	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	May 18, 2016 ~ Jun. 06, 2016	Sep. 01, 2016	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz ~ 18GHz	Apr. 15, 2016	May 18, 2016 ~ Jun. 06, 2016	Apr. 14, 2017	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 18, 2016	May 18, 2016 ~ Jun. 06, 2016	Mar. 17, 2017	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A023 62	1GHz~ 26.5GHz	Oct. 19, 2015	May 18, 2016 ~ Jun. 06, 2016	Oct. 18, 2016	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Feb. 27, 2016	May 18, 2016 ~ Jun. 06, 2016	Feb. 26, 2017	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	May 18, 2016 ~ Jun. 06, 2016	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	May 18, 2016 ~ Jun. 06, 2016	N/A	Radiation (03CH07-HY)
Preamplifier	MITEQ	TTA0204	1872107	2GHz~40GHz	Feb. 15, 2015	May 18, 2016 ~ Jun. 06, 2016	Feb. 14, 2017	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 02, 2015	May 18, 2016 ~ Jun. 06, 2016	Nov. 01, 2016	Radiation (03CH07-HY)

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 34 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report No.: FR650305B

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.26
of 95% (U = 2Uc(y))	2.20

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence	5.0
of 95% (U = 2Uc(y))	5.6

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : 35 of 35
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 1.3

Report No.: FR650305B

Appendix A. Conducted Test Results

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: UZ7ET55BE Page Number : A1 of A1
Report Issued Date : Jun. 22, 2016
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 1.0

Report No.: FR650305B

Report Number : FR650305B

Bluetooth Low Energy

Test Engineer:	Luffy Lin	Temperature:	21~25	°C
Test Date:	2016/06/02 ~ 2016/06/07	Relative Humidity:	51~54	%

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

М	od.	Data Rate	NTX	СН.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
В	LE	1Mbps	1	0	2402	1.05	0.70	0.50	Pass
В	LE	1Mbps		19	2440	1.05	0.70	0.50	Pass
В	LE	1Mbps	1	39	2480	1.05	0.70	0.50	Pass

TEST RESULTS DATA

Peak Power Table

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	4.70	30.00	1.90	6.60	36.00	Pass
BLE	1Mbps	1	19	2440	6.43	30.00	1.90	8.33	36.00	Pass
BLE	1Mbps	1	39	2480	6.04	30.00	1.90	7.94	36.00	Pass

TEST RESULTS DATA Average Power Table (Reporting Only)

Mod	Data Rate	N⊤×	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	 1Mbps	1	0	2402	2.05	1.89
BLE	1Mbps	1	19	2440	2.05	4.18
BLE	1Mbps	1	39	2480	2.05	3.92

TEST RESULTS DATA Peak Power Density

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	0.95	-12.78	1.90	8.00	Pass
BLE	1Mbps	1	19	2440	3.51	-10.22	1.90	8.00	Pass
BLE	1Mbps	1	39	2480	3.15	-10.61	1.90	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Appendix B. Radiated Spurious Emission

Test Engineer :	Jesse Wang, James Chiu, Derek Hsu, and Luke Chang	Temperature :	25~26℃
		Relative Humidity :	54~55%

2.4GHz 2400~2483.5MHz BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2357.34	55.21	-18.79	74	50.52	31.84	7.24	34.39	300	81	Р	Н
		2384.61	45.86	-8.14	54	41	31.89	7.31	34.34	300	81	Α	Н
	*	2402	96.69	-	-	91.76	31.93	7.31	34.31	300	81	Р	Н
	*	2402	96.03	-	-	91.1	31.93	7.31	34.31	300	81	Α	Н
BLE													Н
CH 00													Н
2402MHz		2374.08	55.76	-18.24	74	50.99	31.89	7.24	34.36	376	182	Р	V
2402111112		2385.6	45.91	-8.09	54	41.01	31.93	7.31	34.34	376	182	Α	V
	*	2402	99.33	-	-	94.4	31.93	7.31	34.31	376	182	Р	V
	*	2402	98.72	-	-	93.79	31.93	7.31	34.31	376	182	Α	V
													V
													٧
		2364.81	55.01	-18.99	74	50.3	31.84	7.24	34.37	342	266	Р	Н
		2387.13	45.91	-8.09	54	41.01	31.93	7.31	34.34	342	266	Α	Н
	*	2440	96.53	-	-	91.35	32.07	7.36	34.25	342	266	Р	Н
	*	2440	95.94	-	-	90.76	32.07	7.36	34.25	342	266	Α	Н
D. F.		2498	55.53	-18.47	74	50.08	32.2	7.4	34.15	342	266	Р	Н
BLE CH 19		2496.08	46.47	-7.53	54	41.03	32.2	7.4	34.16	342	266	Α	Н
2440MHz		2339.7	54.96	-19.04	74	50.4	31.8	7.18	34.42	375	99	Р	٧
244UIVII112		2364.54	45.84	-8.16	54	41.13	31.84	7.24	34.37	375	99	Α	V
	*	2440	98.43	-	-	93.25	32.07	7.36	34.25	375	99	Р	V
	*	2440	97.85	-	-	92.67	32.07	7.36	34.25	375	99	Α	V
		2484.52	55.24	-18.76	74	49.86	32.16	7.4	34.18	375	99	Р	V
		2493.92	46.37	-7.63	54	40.93	32.2	7.4	34.16	375	99	Α	V

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number

: B1 of B6



	*	2480	100.35	-	-	94.97	32.16	7.4	34.18	138	285	Р	
	*	2480	99.57	-	-	94.19	32.16	7.4	34.18	138	285	Α	
		2485.04	55.58	-18.42	74	50.19	32.16	7.4	34.17	138	285	Р	
		2488	46.53	-7.47	54	41.1	32.2	7.4	34.17	138	285	Α	
LE													
1 39 0MHz	*	2480	100.59	-	-	95.21	32.16	7.4	34.18	358	159	Р	
OIVII IZ	*	2480	99.93	-	-	94.55	32.16	7.4	34.18	358	159	Α	
		2498.52	55.85	-18.15	74	50.4	32.2	7.4	34.15	358	159	Р	
		2483.92	46.41	-7.59	54	41.03	32.16	7.4	34.18	358	159	Α	

All results are PASS against Peak and Average limit line.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		4806	41.25	-32.75	74	54.31	34.19	11.83	59.08	100	0	Р	Н
													Н
													Н
BLE													Н
CH 00		4806	41.75	-32.25	74	54.81	34.19	11.83	59.08	100	0	Р	V
2402MHz													V
													V
													V
		4878	40.23	-33.77	74	53.41	34.23	11.53	58.94	100	0	Р	Н
		7320	40.32	-33.68	74	48.87	35.6	13.81	57.96	100	0	Р	Н
													Н
BLE													Н
CH 19		4878	40.16	-33.84	74	53.34	34.23	11.53	58.94	100	0	Р	V
2440MHz		7320	40.63	-33.37	74	49.18	35.6	13.81	57.96	100	0	Р	V
													٧
													٧
		4962	40.45	-33.55	74	53.72	34.28	11.22	58.77	100	0	Р	Н
		7440	40.82	-33.18	74	49.3	35.6	14.05	58.13	100	0	Р	Н
													Н
BLE													Н
CH 39		4962	40.24	-33.76	74	53.51	34.28	11.22	58.77	100	0	Р	V
2480MHz		7440	40.76	-33.24	74	49.24	35.6	14.05	58.13	100	0	Р	V
													V
													V
Damaria	1. No	o other spurious	s found.	L	ı	ı			1	1	1	1	
Remark	2. All	results are PA	SS against F	Peak and	l Average lim	it line.							

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number

: B3 of B6

Emission below 1GHz 2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antonno	Cabla	Draama	A 4			
							Antenna	Cable .	Preamp	Ant		ļ	Pol.
İ		(MHz)	(dBµV/m)	Limit (dB)	Line (dBµV/m)	Level (dBµV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg.	(H/V)
		41.34	24.11	-15.89	40	35.26	19.28	1.07	31.5	-	-	P	Н
		106.14	23.38	-20.12	43.5	36.41	16.94	1.55	31.52	-	-	Р	Н
		240.06	28.4	-17.6	46	39.64	18.09	2.07	31.4	-	-	Р	Н
-		780.2	33.13	-12.87	46	32.35	27.5	3.9	30.62	-	-	Р	Н
_		899.9	33.59	-12.41	46	30.96	29	4.17	30.54	100	0	Р	Н
		940.5	31.41	-14.59	46	27.88	29.99	4.07	30.53	-	-	Р	Н
													Н
													Н
													Н
													Н
													Н
2.4GHz													Н
BLE		30	28.94	-11.06	40	33.22	26	1.07	31.35	100	0	Р	V
LF -		139.89	24.37	-19.13	43.5	36.32	18	1.55	31.5	-	-	Р	V
		240.06	25.88	-20.12	46	37.12	18.09	2.07	31.4	-	-	Р	V
		816.6	31.5	-14.5	46	30.15	28.03	3.9	30.58	-	-	Р	V
		850.9	32.23	-13.77	46	29.98	28.71	4.1	30.56	-	-	Р	V
		951.7	32.78	-13.22	46	29.04	30.2	4.07	30.53	-	-	Р	V
													V
													V
													V
-													V
													V
													V

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number

: B4 of B6

Note symbol

Report No. : FR650305B

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions
	shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

SPORTON INTERNATIONAL INC. Page Number : B5 of B6

TEL: 886-3-327-3456 FAX: 886-3-328-4978

A calculation example for radiated spurious emission is shown as below:

Report No.: FR650305B

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

1. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level(dBµV/m) Limit Line(dBµV/m)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

SPORTON INTERNATIONAL INC. Page Number : B6 of B6

TEL: 886-3-327-3456 FAX: 886-3-328-4978

Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Jesse Wang, James Chiu, Derek Hsu, and Luke Chang	Temperature :	25~26 ℃
		Relative Humidity:	54~55%

Report No.: FR650305B


Note symbol

-L	Low channel location
-R	High channel location


SPORTON INTERNATIONAL INC. Page Number : C1 of C10


TEL: 886-3-327-3456 FAX: 886-3-328-4978


2.4GHz 2400~2483.5MHz BLE (Band Edge @ 3m)





TEL: 886-3-327-3456 FAX: 886-3-328-4978

















2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)






TEL: 886-3-327-3456 FAX: 886-3-328-4978



Emission below 1GHz 2.4GHz BLE (LF)




TEL: 886-3-327-3456 FAX: 886-3-328-4978



Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth 4.0 – LE	62.32	387	2.58	3kHz

Bluetooth 4.0 - LE



Date: 2.JUN.2016 04:27:43

TEL: 886-3-327-3456 FAX: 886-3-328-4978