Mode	54	
	Band Edge - R	
	U-NII-8_6.875-7.125_802.11ax HE40_CH227_Full RU_7085MHz	
ANT	1+2	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 1080.60 46.88 74.00 -27.12 54.45 25.47 3.82 36.86 0.00 243 345 Peak 2 7085.00 114.08 ------ ------ 104.33 36.20 9.78 36.23 0.00 243 345 PEAK	Blank
Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 1080.60 31.40 54.00 -22.60 38.97 25.47 3.82 36.86 0.00 243 345 Average 2 7085.00 105.40 ------ ------ 95.62 36.23 9.78 36.23 0.00 243 345 AVERAGE	Blank

Mode	54	
	Band Edge - L	
	U-NII-8_6.875-7.125_802.11ax HE40_CH227_Full RU_7085MHz	
ANT	1+2	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7125.64 73.62 88.20 -14.58 63.58 36.45 9.83 36.24 0.00 160 49 PEAK	Blank
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7125.32 63.63 68.20 -4.57 53.59 36.45 9.83 36.24 0.00 160 49 AVERAGE	Blank

Mode	54	
	Band Edge - R	
	U-NII-8_6.875-7.125_802.11ax HE40_CH227_Full RU_7085MHz	
ANT	1+2	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 1024.80 44.55 74.00 -29.45 52.55 25.15 3.72 36.87 0.00 160 49 Peak 2 7085.00 112.28 ------ ------ 102.53 36.20 9.78 36.23 0.00 160 49 PEAK	Blank
Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 1024.80 29.58 54.00 -24.42 37.58 25.15 3.72 36.87 0.00 160 49 Average 2 7085.00 102.73 ------ ------ 92.98 36.20 9.78 36.23 0.00 160 49 AVERAGE	Blank

Mode	54	
	Harmonic	
	U-NII-8_6.875-7.125_802.11ax HE40_CH227_Full RU_7085MHz	
ANT	1+2	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 1m BBHA9170576 HORIZONTAL Freq / Level / Limit Line / Margin / Read Level / Ant Factor / Cable Loss / Preamp Factor / Aux Factor / APos / TPos / Remark MHz / dBuV/m / dBuV/m / dB / dBuV / dB/m / dB / dB / dB / cm / deg 1 14170.00 46.92 88.20 -41.28 48.40 41.27 14.26 58.06 1.05 -- -- Peak 2 21255.00 37.28 74.00 -36.72 56.91 38.45 6.26 54.80 -9.54 -- -- Peak	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 1m BBHA9170576 VERTICAL Freq / Level / Limit Line / Margin / Read Level / Ant Factor / Cable Loss / Preamp Factor / Aux Factor / APos / TPos / Remark MHz / dBuV/m / dBuV/m / dB / dBuV / dB/m / dB / dB / dB / cm / deg 1 14170.00 47.51 88.20 -40.69 48.99 41.27 14.26 58.06 1.05 -- -- Peak 2 21255.00 38.09 74.00 -35.91 57.72 38.45 6.26 54.80 -9.54 -- -- Peak

Mode	54	
	Harmonic	
	U-NII-8_6.875-7.125_802.11ax HE40_CH227_Full RU_7085MHz	
ANT	1+2	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
17.7G ~18G Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL

Mode	55	
	Band Edge	
	U-NII-8_6.875-7.125_802.11ax HE40_CH227_Partial_242/62RU_7085MHz	
ANT	1+2	
Pol.	Horizontal	Fundamental

Peak



Site : 03CH15-HY
Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7126.76	80.30	88.20	-7.90	70.25	36.46	9.83	36.24	0.00	344	0	PEAK



Site : 03CH15-HY
Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7085.00	116.31	------	------	106.44	36.30	9.80	36.23	0.00	344	0	PEAK

Avg



Site : 03CH15-HY
Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7127.40	62.86	68.20	-5.34	52.81	36.46	9.83	36.24	0.00	344	0	AVERAGE



Site : 03CH15-HY
Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7085.00	109.49	------	------	99.65	36.28	9.79	36.23	0.00	344	0	AVERAGE

Mode	55	
	Band Edge	
	U-NII-8_6.875-7.125_802.11ax HE40_CH227_Partial_242/62RU_7085MHz	
ANT	1+2	
Pol.	Vertical	Fundamental

Peak



Site : 03CH15-HY
Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7136.36	76.56	88.20	-11.64	66.44	36.52	9.84	36.24	0.00	152	59	PEAK



Site : 03CH15-HY
Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7085.00	115.46	------	------	105.65	36.25	9.79	36.23	0.00	152	59	PEAK

Avg



Site : 03CH15-HY
Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7125.16	60.68	68.20	-7.52	50.64	36.45	9.83	36.24	0.00	152	59	AVERAGE



Site : 03CH15-HY
Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7085.00	107.73	------	------	97.86	36.30	9.80	36.23	0.00	152	59	AVERAGE

Mode	56	
	Harmonic	
	U-NII-8_6.875-7.125_802.11ax HE80_CH199_Full RU_6945MHz	
ANT	1+2	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 1m BBHA9170576 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos cm TPos deg Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 13890.00 47.52 88.20 -40.68 49.48 40.88 14.08 58.00 1.08 -- -- Peak 2 20835.00 37.28 74.00 -36.72 57.28 38.24 6.17 54.87 -9.54 -- -- Peak	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 1m BBHA9170576 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos cm TPos deg Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 13890.00 47.44 88.20 -40.76 49.40 40.88 14.08 58.00 1.08 -- -- Peak 2 20835.00 37.02 74.00 -36.98 57.02 38.24 6.17 54.87 -9.54 -- -- Peak

Mode	56	
	Harmonic	
	U-NII-8_6.875-7.125_802.11ax HE80_CH199_Full RU_6945MHz	
ANT	1+2	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
17.7G ~18G Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL

Mode	57	
	Band Edge - L	
	U-NII-8_6.875-7.125_802.11ax HE80_CH215_Full RU_7025MHz	
ANT	1+2	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7125.10 71.80 88.20 -16.40 61.76 36.45 9.83 36.24 0.00 253 345 PEAK	Blank
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7125.10 63.04 68.20 -5.16 53.00 36.45 9.83 36.24 0.00 253 345 AVERAGE	Blank

Mode	57	
	Band Edge - R	
	U-NII-8_6.875-7.125_802.11ax HE80_CH215_Full RU_7025MHz	
ANT	1+2	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq / Level / Limit Line / Margin / Read Level / Ant Factor / Cable Loss / Preamp Factor / Aux Factor / APos / TPos / Remark MHz / dBuV/m / dBuV/m / dB / dBuV / dB/m / dB / dB / dB / cm / deg 1 1006.20 46.01 74.00 -27.99 54.01 25.19 3.69 36.88 0.00 253 345 Peak 2 7025.00 112.00 ------ ------ 102.48 36.01 9.73 36.22 0.00 253 345 PEAK	Blank
Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq / Level / Limit Line / Margin / Read Level / Ant Factor / Cable Loss / Preamp Factor / Aux Factor / APos / TPos / Remark MHz / dBuV/m / dBuV/m / dB / dBuV / dB/m / dB / dB / dB / cm / deg 1 1006.20 32.00 54.00 -22.00 40.00 25.19 3.69 36.88 0.00 253 345 Average 2 7025.00 103.55 ------ ------ 94.01 36.03 9.73 36.22 0.00 253 345 AVERAGE	Blank

Mode	57	
	Band Edge - L	
	U-NII-8_6.875-7.125_802.11ax HE80_CH215_Full RU_7025MHz	
ANT	1+2	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7126.42 69.23 88.20 -18.97 59.18 36.46 9.83 36.24 0.00 150 58 PEAK	Blank
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 7125.10 60.65 68.20 -7.55 50.61 36.45 9.83 36.24 0.00 150 58 AVERAGE	Blank

Mode	57	
	Band Edge - R	
	U-NII-8_6.875-7.125_802.11ax HE80_CH215_Full RU_7025MHz	
ANT	1+2	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 1018.60 45.27 74.00 -28.73 53.28 25.16 3.71 36.88 0.00 150 58 Peak 2 7025.00 109.31 ------ ------ 99.82 35.98 9.72 36.21 0.00 150 58 PEAK	Blank
Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 1018.60 30.89 54.00 -23.11 38.90 25.16 3.71 36.88 0.00 150 58 Average 2 7025.00 100.03 ------ ------ 90.54 35.98 9.72 36.21 0.00 150 58 AVERAGE	Blank

Mode	57	
	Harmonic	
	U-NII-8_6.875-7.125_802.11ax HE80_CH215_Full RU_7025MHz	
ANT	1+2	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 1m BBHA9170576 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 14050.00 48.75 88.20 -39.45 50.34 41.15 14.19 58.02 1.09 -- -- Peak 2 21075.00 37.28 74.00 -36.72 57.04 38.42 6.16 54.80 -9.54 -- -- Peak	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 1m BBHA9170576 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 14050.00 47.25 88.20 -40.95 48.84 41.15 14.19 58.02 1.09 -- -- Peak 2 21075.00 37.57 74.00 -36.43 57.33 38.42 6.16 54.80 -9.54 -- -- Peak

Mode	57	
	Harmonic	
	U-NII-8_6.875-7.125_802.11ax HE80_CH215_Full RU_7025MHz	
ANT	1+2	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
17.7G ~18G Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL

Mode	58	
	Band Edge	
	U-NII-8_6.875-7.125_802.11ax HE80_CH215_Partial_484/66RU_7025MHz	
ANT	1+2	
Pol.	Horizontal	Fundamental

Peak



Site : 03CH15-HY
Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7125.54	70.09	88.20	-18.11	60.05	36.45	9.83	36.24	0.00	328	1	PEAK



Site : 03CH15-HY
Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7025.00	115.92	------	------	106.32	36.08	9.74	36.22	0.00	328	1	PEAK

Avg



Site : 03CH15-HY
Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7125.10	55.87	68.20	-12.33	45.83	36.45	9.83	36.24	0.00	328	1	AVERAGE



Site : 03CH15-HY
Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7025.00	107.32	------	------	97.78	36.03	9.73	36.22	0.00	328	1	AVERAGE

Mode	58	
	Band Edge	
	U-NII-8_6.875-7.125_802.11ax HE80_CH215_Partial_484/66RU_7025MHz	
ANT	1+2	
Pol.	Vertical	Fundamental

Peak



Site : 03CH15-HY
Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7125.10	72.78	88.20	-15.42	62.74	36.45	9.83	36.24	0.00	249	48	PEAK



Site : 03CH15-HY
Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7025.00	112.53	------	------	102.93	36.08	9.74	36.22	0.00	249	48	PEAK

Avg



Site : 03CH15-HY
Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7125.10	54.31	68.20	-13.89	44.27	36.45	9.83	36.24	0.00	249	48	AVERAGE



Site : 03CH15-HY
Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7025.00	104.31	------	------	94.71	36.08	9.74	36.22	0.00	249	48	AVERAGE

Mode	59	
	Band Edge	
	U-NII-8_6.875-7.125_802.11ax HE160_CH207_Full RU_6985MHz	
ANT	1+2	
Pol.	Horizontal	Fundamental

Peak



Site : 03CH15-HY
Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7126.12	76.57	88.20	-11.63	66.52	36.46	9.83	36.24	0.00	238	344	PEAK



Site : 03CH15-HY
Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6985.00	108.39	------	------	99.05	35.86	9.69	36.21	0.00	238	344	PEAK

Avg



Site : 03CH15-HY
Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7125.16	66.73	68.20	-1.47	56.69	36.45	9.83	36.24	0.00	238	344	AVERAGE



Site : 03CH15-HY
Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6985.00	99.44	------	------	90.14	35.81	9.69	36.20	0.00	238	344	AVERAGE

Mode	59	
	Band Edge	
	U-NII-8_6.875-7.125_802.11ax HE160_CH207_Full RU_6985MHz	
ANT	1+2	
Pol.	Vertical	Fundamental

Peak



Site : 03CH15-HY
Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7125.64	74.58	88.20	-13.62	64.54	36.45	9.83	36.24	0.00	154	49	PEAK



Site : 03CH15-HY
Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6985.00	106.58	------	------	97.28	35.81	9.69	36.20	0.00	154	49	PEAK

Avg



Site : 03CH15-HY
Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7125.40	64.67	68.20	-3.53	54.63	36.45	9.83	36.24	0.00	154	49	AVERAGE



Site : 03CH15-HY
Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:0.010kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6985.00	97.59	------	------	88.19	35.91	9.70	36.21	0.00	154	49	AVERAGE

Mode	59	
	Harmonic	
	U-NII-8_6.875-7.125_802.11ax HE160_CH207_Full RU_6985MHz	
ANT	1+2	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 1m BBHA9170576 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 13970.00 47.84 88.20 -40.36 49.54 41.05 14.15 58.00 1.10 -- -- Peak 2 20955.00 37.23 74.00 -36.77 57.10 38.35 6.14 54.82 -9.54 -- -- Peak	 Site : 03CH15-HY Condition: PEAK(UNII)_6E 1m BBHA9170576 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 13970.00 48.42 88.20 -39.78 50.12 41.05 14.15 58.00 1.10 -- -- Peak 2 20955.00 38.45 74.00 -35.55 58.32 38.35 6.14 54.82 -9.54 -- -- Peak

Mode	59	
	Harmonic	
	U-NII-8_6.875-7.125_802.11ax HE160_CH207_Full RU_6985MHz	
ANT	1+2	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
17.7G ~18G Avg	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL	 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL

Mode	60	
	Band Edge	
	U-NII-8_6.875-7.125_802.11ax HE160_CH207_Partial_996/68RU_6985MHz	
ANT	1+2	
Pol.	Horizontal	Fundamental

Peak



Site : 03CH15-HY
Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7133.56	79.19	88.20	-9.01	69.10	36.50	9.83	36.24	0.00	400	349	PEAK



Site : 03CH15-HY
Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6985.00	109.07	------	------	99.61	35.96	9.71	36.21	0.00	400	349	PEAK

Avg



Site : 03CH15-HY
Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:1.500kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7133.80	65.85	68.20	-2.35	55.76	36.50	9.83	36.24	0.00	400	349	AVERAGE



Site : 03CH15-HY
Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 HORIZONTAL
: RBW:1000.000kHz VBW:1.500kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6985.00	100.31	------	------	90.77	36.03	9.73	36.22	0.00	400	349	AVERAGE

Mode	60	
	Band Edge	
	U-NII-8_6.875-7.125_802.11ax HE160_CH207_Partial_996/68RU_6985MHz	
ANT	1+2	
Pol.	Vertical	Fundamental

Peak



Site : 03CH15-HY
Condition: PEAK_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7131.16	77.00	88.20	-11.20	66.92	36.49	9.83	36.24	0.00	213	68	PEAK



Site : 03CH15-HY
Condition: PEAK(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:3000.000kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6985.00	103.61	------	------	94.24	35.88	9.70	36.21	0.00	213	68	PEAK

Avg



Site : 03CH15-HY
Condition: AVG_BE(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:1.500kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	7131.16	62.00	68.20	-6.20	51.92	36.49	9.83	36.24	0.00	213	68	AVERAGE



Site : 03CH15-HY
Condition: AVG(UNII)_6E 3m BBHA 9120 D_9120D-02038 VERTICAL
: RBW:1000.000kHz VBW:1.500kHz SWT:Auto

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6985.00	96.38	------	------	86.71	36.13	9.76	36.22	0.00	213	68	AVERAGE

Mode	61
	LF
	U-NII-8_6.875-7.125_802.11ax HE20_CH233_Full RU_7115MHz
ANT	1+2

Pol.	Horizontal	Vertical

QP/ Peak



Site : 03CH15-HY
Condition: QP 3m CBL 6111D & 00800N1D01N-06_41912&05 HORIZONTAL

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	50.37	30.71	40.00	-9.29	47.82	14.43	0.87	32.46	0.05	--	--	Peak
2	148.34	31.50	43.50	-12.00	45.19	17.12	1.45	32.39	0.13	--	--	Peak
3	221.09	37.90	46.00	-8.10	53.02	15.27	1.76	32.39	0.24	--	--	Peak
4	450.98	37.73	46.00	-8.27	44.86	22.69	2.49	32.41	0.10	--	--	Peak
5	676.02	36.95	46.00	-9.05	40.25	25.91	3.01	32.36	0.14	--	--	Peak
6	900.09	36.04	46.00	-9.96	35.50	28.32	3.48	31.46	0.20	--	--	Peak



Site : 03CH15-HY
Condition: QP 3m CBL 6111D & 00800N1D01N-06_41912&05 VERTICAL

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	36.79	33.63	40.00	-6.37	43.87	21.34	0.76	32.41	0.07	--	--	Peak
2	147.37	37.00	43.50	-6.50	50.61	17.20	1.45	32.39	0.13	--	--	Peak
3	221.09	37.50	46.00	-8.50	52.62	15.27	1.76	32.39	0.24	--	--	Peak
4	441.28	39.39	46.00	-6.61	46.73	22.51	2.46	32.41	0.10	100	143	QP
5	750.71	39.84	46.00	-6.16	41.23	27.52	3.18	32.22	0.13	--	--	Peak
6	888.45	37.18	46.00	-8.82	36.93	28.15	3.45	31.54	0.19	--	--	Peak

Appendix D. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1+2	802.11a	99.29	-	-	10Hz
1+2	6GHz 802.11ax HE20 Full RU	99.71	-	-	10Hz
1+2	6GHz 802.11ax HE20 106 RU	85.45	4580	0.22	240Hz
1+2	6GHz 802.11ax HE40 Full RU	99.44	-	-	10Hz
1+2	6GHz 802.11ax HE40 242 RU	99.32	-	-	10Hz
1+2	6GHz 802.11ax HE80 Full RU	99.10	-	-	10Hz
1+2	6GHz 802.11ax HE80 484 RU	99.38	-	-	10Hz
1+2	6GHz 802.11ax HE160 Full RU	95.92	376	2.66	2.7kHz
1+2	6GHz 802.11ax HE160 996 RU	97.80	710	1.41	1.5kHz

MIMO <Ant. 1+2>

802.11a



6GHz 802.11ax HE20 Full RU



6GHz 802.11ax HE20 106 RU



6GHz 802.11ax HE40 Full RU



6GHz 802.11ax HE40 242 RU



6GHz 802.11ax HE80 Full RU



6GHz 802.11ax HE80 484 RU



6GHz 802.11ax HE160 Full RU



6GHz 802.11ax HE160 996 RU



Appendix F. Spot Check Evaluation on KC50E22

Conducted power test and radiated spurious emission test configurations were selected from the worst cases identified in the parent model and tested to demonstrate the test data from original model remains representative for the variant model.

The deviation between the spot check and the referenced values is within 3dB, therefore data referencing is justified according to the guidance in the ECR inquiry

Mode	Test Item	UZ7KC50A22 Reference Worst mode Test Result	UZ7KC50E22 Variant Check Test Result	Deviation	Limit (dB)
Bluetooth	Number of Channels	79	79	0	Within the authorized block
	Hopping Channel Separation	1.003	1.007	0.004	Within the authorized block
	Dwell Time of Each Channel	0.31	0.31	0	Within the authorized block
	20dB Bandwidth	0.893	0.891	0.002	Within the authorized frequency block
	99% Bandwidth	0.827	0.827	0	Within the authorized frequency block
	Conducted Band Edges	-41.22	-41.73	0.51	Deviation (ddB) < 3 dB
	Conducted Spurious Emission	-31.93	-32.30	0.37	Deviation (ddB) < 3 dB
	Peak Output Power	5.40	6.20	0.8	Deviation (ddB) < 3 dB
	Radiated Band Edges and Radiated Spurious Emission	42.16	39.94	2.22	Deviation (ddB) < 3 dB
	AC Conducted Emission	42.98	40.01	2.97	Deviation (ddB) < 3 dB
Bluetooth-LE	6dB Bandwidth	0.674	0.668	0.006	Within the authorized frequency block
	99% Bandwidth	1.019	1.019	0	Within the authorized frequency block
	Power Spectral Density	-9.55	-10.09	0.54	Deviation (ddB) < 3 dB
	Conducted Band Edges	-41.10	-42.38	1.28	Deviation (ddB) < 3 dB
	Conducted Spurious Emission	-31.69	-32.23	0.54	Deviation (ddB) < 3 dB
	Power Output Measurement	4.80	4.60	0.2	Deviation (ddB) < 3 dB
	Radiated Band Edges and Spurious Emission	42.35	39.81	2.54	Deviation (ddB) < 3 dB
	AC Conducted Emission	42.98	40.01	2.97	Deviation (ddB) < 3 dB
WIFI 2.4G	6dB Bandwidth	8.06	8.08	0.02	Within the authorized frequency block
	99% Bandwidth	13.04	13.09	0.05	Within the authorized frequency block
	Power Spectral Density	3.70	3.78	0.08	Deviation (ddB) < 3 dB
	Conducted Band Edges	-36.65	-36.24	0.41	Deviation (ddB) < 3 dB
	Conducted Spurious Emission	-42.84	-41.89	0.95	Deviation (ddB) < 3 dB
	Output Power	26.46	26.36	0.1	Deviation (ddB) < 3 dB
	Radiated Band Edges and Spurious Emission	52.24	51.35	0.89	Deviation (ddB) < 3 dB
	AC Conducted Emission	42.98	40.01	2.97	Deviation (ddB) < 3 dB

Mode	Test Item	UZ7KC50A22 Reference Worst mode Test Result	UZ7KC50E22 Variant Check Test Result	Deviation	Limit (dB)
WIFI 5G	26dB Bandwidth	165.98	165.94	0.04	Within the authorized frequency block
	99% Bandwidth	156.32	156.56	0.24	Within the authorized frequency block
	Power Spectral Density	10.52	10.38	0.14	Deviation (ddB) < 3 dB
	Maximum Conducted Output Power	23.58	23.48	0.1	Deviation (ddB) < 3 dB
	Unwanted Emissions	66.96	64.84	2.12	Deviation (ddB) < 3 dB
	AC Conducted Emission	41.81	40.50	1.31	Deviation (ddB) < 3 dB
WIFI 6G	26dB Emission Bandwidth	165.84	166.56	0.72	Within the authorized frequency block
	99% Occupied Bandwidth	156.80	157.76	0.96	Within the authorized frequency block
	Contention Based Protocol	-66.35	-68.65	2.3	Within the authorized block
	Fundamental Maximum EIRP	26.54	25.96	0.58	Deviation (ddB) < 3 dB
	Fundamental Power Spectral Density	16.81	16.71	0.1	Deviation (ddB) < 3 dB
	In-Band Emissions (Channel Mask)	-42.43	-41.04	1.39	Deviation (ddB) < 3 dB
	Unwanted Emissions	67.14	66.93	0.21	Deviation (ddB) < 3 dB
	AC Conducted Emission	41.15	40.16	0.99	Deviation (ddB) < 3 dB

CBP test results on UZ7KC50E22: presented in Page F3 – F23

Band	Channel Freq. (MHz)	Channel BW (MHz)	Incumbent freq. (MHz)	Injected AWGN Level (dBm)	Detection Rate (%)	Regulated Threshold level (dBm)	Adjusted Power (dBm)	Margin (dB)
UNII Band 5	6135	20	6135	-70.07	100	-62	-73.50	11.50
					Result: Stop Transmission			
				-77.07	< 90	-62	-80.50	18.50
					Result: Minimal Operation			
				-78.07	0	-62	-81.50	19.50
					Result: Normal Operation			
	6185	160	6110	-66.26	100	-62	-69.69	7.69
					Result: Stop Transmission			
				-69.26	< 90	-62	-72.69	10.69
					Result: Minimal Operation			
				-70.26	0	-62	-73.69	11.69
					Result: Normal Operation			
			6185	-61.26	100	-62	-64.69	2.69
					Result: Stop Transmission			
				-63.26	< 90	-62	-66.69	4.69
					Result: Minimal Operation			
				-64.26	0	-62	-67.69	5.69
					Result: Normal Operation			
			6260	-66.07	100	-62	-69.50	7.50
					Result: Stop Transmission			
				-68.07	< 90	-62	-71.50	9.50
					Result: Minimal Operation			
				-69.07	0	-62	-72.50	10.50
					Result: Normal Operation			

Note 1: Adjusted Power = Injected AWGN Level - minimum antenna gain (3.43 dBi).

Note 2: The antenna gain has included the path loss between RF connector and antenna.

Note 3: Margin = Regulated Threshold level - Adjusted Power.

Band	Channel Freq. (MHz)	Channel BW (MHz)	Incumbent freq. (MHz)	Injected AWGN Level (dBm)	Detection Rate (%)	Regulated Threshold level (dBm)	Adjusted Power (dBm)	Margin (dB)
UNII Band 6	6455	20	6455	-70.83	100	-62	-74.32	12.32
					Result: Stop Transmission			
				-74.83	< 90	-62	-78.32	16.32
					Result: Minimal Operation			
				-75.83	0	-62	-79.32	17.32
					Result: Normal Operation			
	6505	160	6430	-63.95	100	-62	-67.44	5.44
					Result: Stop Transmission			
				-68.95	< 90	-62	-72.44	10.44
					Result: Minimal Operation			
				-69.95	0	-62	-73.44	11.44
					Result: Normal Operation			
			6505	-60.86	100	-62	-64.35	2.35
					Result: Stop Transmission			
				-62.86	< 90	-62	-66.35	4.35
					Result: Minimal Operation			
				-63.86	0	-62	-67.35	5.35
					Result: Normal Operation			
			6580	-64.75	100	-62	-68.24	6.24
					Result: Stop Transmission			
				-68.75	< 90	-62	-72.24	10.24
					Result: Minimal Operation			
				-69.75	0	-62	-73.24	11.24
					Result: Normal Operation			

Note 1: Adjusted Power = Injected AWGN Level - minimum antenna gain (3.49 dBi).

Note 2: The antenna gain has included the path loss between RF connector and antenna.

Note 3: Margin = Regulated Threshold level - Adjusted Power.

Band	Channel Freq. (MHz)	Channel BW (MHz)	Incumbent freq. (MHz)	Injected AWGN Level (dBm)	Detection Rate (%)	Regulated Threshold level (dBm)	Adjusted Power (dBm)	Margin (dB)
UNII Band 7	6695	20	6695	-71.01	100	-62	-74.50	12.50
					Result: Stop Transmission			
				-75.01	< 90	-62	-78.50	16.50
					Result: Minimal Operation			
				-76.01	0	-62	-79.50	17.50
					Result: Normal Operation			
	6665	160	6590	-67.73	100	-62	-71.22	9.22
					Result: Stop Transmission			
				-70.73	< 90	-62	-74.22	12.22
					Result: Minimal Operation			
				-71.73	0	-62	-75.22	13.22
					Result: Normal Operation			
			6665	-63.84	100	-62	-67.33	5.33
					Result: Stop Transmission			
				-65.84	< 90	-62	-69.33	7.33
					Result: Minimal Operation			
				-66.84	0	-62	-70.33	8.33
					Result: Normal Operation			
			6740	-66.95	100	-62	-70.44	8.44
					Result: Stop Transmission			
				-70.95	< 90	-62	-74.44	12.44
					Result: Minimal Operation			
				-71.95	0	-62	-75.44	13.44
					Result: Normal Operation			

Note 1: Adjusted Power = Injected AWGN Level - minimum antenna gain (3.49 dBi).

Note 2: The antenna gain has included the path loss between RF connector and antenna.

Note 3: Margin = Regulated Threshold level - Adjusted Power.

Band	Channel Freq. (MHz)	Channel BW (MHz)	Incumbent freq. (MHz)	Injected AWGN Level (dBm)	Detection Rate (%)	Regulated Threshold level (dBm)	Adjusted Power (dBm)	Margin (dB)
UNII Band 8	7015	20	7015	-67.53	100	-62	-71.14	9.14
					Result: Stop Transmission			
				-72.53	< 90	-62	-76.14	14.14
					Result: Minimal Operation			
				-73.53	0	-62	-77.14	15.14
					Result: Normal Operation			
	6985	160	6910	-64.78	100	-62	-68.39	6.39
					Result: Stop Transmission			
				-67.78	< 90	-62	-71.39	9.39
					Result: Minimal Operation			
				-68.78	0	-62	-72.39	10.39
					Result: Normal Operation			
			6985	-59.65	100	-62	-63.26	1.26
					Result: Stop Transmission			
				-61.65	< 90	-62	-65.26	3.26
					Result: Minimal Operation			
				-62.65	0	-62	-66.26	4.26
					Result: Normal Operation			
			7060	-64.53	100	-62	-68.14	6.14
					Result: Stop Transmission			
				-67.53	< 90	-62	-71.14	9.14
					Result: Minimal Operation			
				-68.53	0	-62	-72.14	10.14
					Result: Normal Operation			

Note 1: Adjusted Power = Injected AWGN Level - minimum antenna gain (3.84 dBi).

Note 2: The antenna gain has included the path loss between RF connector and antenna.

Note 3: Margin = Regulated Threshold level - Adjusted Power.

Test Plots of Contention Based Protocol Test

Contention Based Protocol Result Plots on U-NII 5 (AWGN Interference)	
802.11ax (HE20) / 6135MHz Threshold Level (TL) = -70.07dBm	802.11ax (HE20) / CH37 Test result is pass due to no transmission occur.
	
802.11ax (HE20) / 6135MHz Threshold Level (TL) = -71.08dBm	802.11ax (HE20) / CH37 Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 5 (AWGN Interference)	
802.11ax (HE160) / 6110MHz (Lower edge) Threshold Level (TL) = -66.26dBm	802.11ax (HE160) / CH47 (Lower edge) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6110MHz (Lower edge) Threshold Level (TL) = -67.26dBm	802.11ax (HE160) / CH47 (Lower edge) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 5 (AWGN Interference)	
802.11ax (HE160) / 6185MHz (Middle) Threshold Level (TL) = -61.26dBm	802.11ax (HE160) / CH47 (Middle) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6185MHz (Middle) Threshold Level (TL) = -62.25dBm	802.11ax (HE160) / CH47 (Middle) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 5 (AWGN Interference)	
802.11ax (HE160) / 6260MHz (Upper edge) Threshold Level (TL) = -66.07dBm	802.11ax (HE160) / CH47 (Upper edge) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6260MHz (Upper edge) Threshold Level (TL) = -67.07dBm	802.11ax (HE160) / CH47 (Upper edge) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 6 (AWGN Interference)	
802.11ax (HE20) / 6455MHz Threshold Level (TL) = -70.83dBm	802.11ax (HE20) / CH101 Test result is pass due to no transmission occur.
	
802.11ax (HE20) / 6455MHz Threshold Level (TL) = -71.82dBm	802.11ax (HE20) / CH101 Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 6 (AWGN Interference)	
802.11ax (HE160) / 6430MHz (Lower edge) Threshold Level (TL) = -63.95dBm	802.11ax (HE160) / CH111 (Lower edge) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6430MHz (Lower edge) Threshold Level (TL) = -64.95dBm	802.11ax (HE160) / CH111 (Lower edge) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 6 (AWGN Interference)	
802.11ax (HE160) / 6505MHz (Middle) Threshold Level (TL) = -60.86dBm	802.11ax (HE160) / CH111 (Middle) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6505MHz (Middle) Threshold Level (TL) = -61.86dBm	802.11ax (HE160) / CH111 (Middle) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 6 (AWGN Interference)	
802.11ax (HE160) / 6580MHz (Upper edge) Threshold Level (TL) = -64.75dBm	802.11ax (HE160) / CH111 (Upper edge) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6580MHz (Upper edge) Threshold Level (TL) = -65.73dBm	802.11ax (HE160) / CH111 (Upper edge) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 7 (AWGN Interference)	
802.11ax (HE20) / 6695MHz Threshold Level (TL) = -71.01dBm	802.11ax (HE20) / CH149 Test result is pass due to no transmission occur.
	
802.11ax (HE20) / 6695MHz Threshold Level (TL) = -72.01dBm	802.11ax (HE20) / CH149 Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 7 (AWGN Interference)	
802.11ax (HE160) / 6590MHz (Lower edge) Threshold Level (TL) = -67.73dBm	802.11ax (HE160) / CH143 (Lower edge) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6590MHz (Lower edge) Threshold Level (TL) = -68.74dBm	802.11ax (HE160) / CH143 (Lower edge) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 7 (AWGN Interference)	
802.11ax (HE160) / 6665MHz (Middle) Threshold Level (TL) = -63.84dBm	802.11ax (HE160) / CH143 (Middle) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6665MHz (Middle) Threshold Level (TL) = -64.84dBm	802.11ax (HE160) / CH143 (Middle) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 7 (AWGN Interference)	
802.11ax (HE160) / 6740MHz (Upper edge) Threshold Level (TL) = -66.95dBm	802.11ax (HE160) / CH143 (Upper edge) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6740MHz (Upper edge) Threshold Level (TL) = -67.94dBm	802.11ax (HE160) / CH143 (Upper edge) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 8 (AWGN Interference)	
802.11ax (HE20) / 7015MHz Threshold Level (TL) = -67.53dBm	802.11ax (HE20) / CH213 Test result is pass due to no transmission occur.
	
802.11ax (HE20) / 7015MHz Threshold Level (TL) = -68.55dBm	802.11ax (HE20) / CH213 Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 8 (AWGN Interference)	
802.11ax (HE160) / 6910MHz (Lower edge) Threshold Level (TL) = -64.78dBm	802.11ax (HE160) / CH207 (Lower edge) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6910MHz (Lower edge) Threshold Level (TL) = -65.79dBm	802.11ax (HE160) / CH207 (Lower edge) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 8 (AWGN Interference)	
802.11ax (HE160) / 6985MHz (Middle) Threshold Level (TL) = -59.65dBm	802.11ax (HE160) / CH207 (Middle) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 6985MHz (Middle) Threshold Level (TL) = -60.67dBm	802.11ax (HE160) / CH207 (Middle) Transmit when the interferer is 1dB lower.
	

Contention Based Protocol Result Plots on U-NII 8 (AWGN Interference)	
802.11ax (HE160) / 7060MHz (Upper edge) Threshold Level (TL) = -64.53dBm	802.11ax (HE160) / CH207 (Upper edge) Test result is pass due to no transmission occur.
	
802.11ax (HE160) / 7060MHz (Upper edge) Threshold Level (TL) = -65.53dBm	802.11ax (HE160) / CH207 (Upper edge) Transmit when the interferer is 1dB lower.
	

CBP verify with frequency domain plots

The device does not support channel puncturing with regards to Contention Based Protocol.

The entire bandwidth 160MHz stops transmission after the incumbent signal appears.

Otherwise, the entire 160MHz bandwidth is reduced to 20MHz or 80MHz.

Before incumbent injected on 160MHz channel	After 10MHz incumbent injected on center of channel, the entire 160MHz bandwidth stops transmission.
	
After 10MHz incumbent injected on bottom of channel, the EUT bandwidth is reduced from 160MHz to 20MHz channel.	After 10MHz incumbent injected on top of channel, the EUT bandwidth is reduced from 160MHz to 80MHz channel.
	

List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Signal Generator (Interferer)	Rohde & Schwarz	SMW200A	109425	100kHz~7.5GHz	Dec. 20, 2023	Jul. 31, 2024	Dec. 19, 2024	CBP (DF02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV3013	101549	10Hz~13.6GHz	Jan. 30, 2024	Jul. 31, 2024	Jan. 29, 2025	CBP (DF02-HY)
Power Divider	Woken	2Way Divider	DCMB1KW7A2	0.5GHz-18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
Power Divider	Woken	3Way SMA Power Divder Rated to 20W	STI08-0010(#2)	2GHz-8GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
Power Divider	Woken	0120A04051801O	DCMB1CW3A7	0.5-18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
Coupler	Woken	10dB 30W SMA	DOM5CIW3A1	0.5-18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
RF Cable	MTJ Cooperstion	SBF405-105FLEX	MTJ-30cm-01	30 kHz~18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
RF Cable	MTJ Cooperstion	SBF405-105FLEX	MTJ-30cm-03	30 kHz~18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
RF Cable	MTJ Cooperstion	SBF405-105FLEX	MTJ-30cm-05	30 kHz~18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
RF Cable	EM	SFL402	SFL402-30cm-#8	30 kHz~18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
RF Cable	EC	SS405	SS405-100cm-05	30 kHz~18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
RF Cable	EC	SS405	SS405-100cm-06	30 kHz~18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
RF Cable	EC	SLF405	EC-SFL405-100cm-#8	30 kHz~18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
RF Cable	EC	SLF405	EC-SFL405-100cm-#9	30 kHz~18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
RF Cable	MVE	SPF141	SPF141-100cm-#12	30 kHz~18GHz	Calibration from System	Jul. 31, 2024	Calibration from System	CBP (DF02-HY)
Software 1	Sporton	Adaptivity Test Tools	N/A	Ver 1.7.7	NCR	Jul. 31, 2024	NCR	CBP (DF02-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	Jul. 26, 2024~Aug. 02, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Sensor	DARE	RPR3008W	RPR8W-23010011 (NO:109)	10MHz~8GHz	Jul. 04, 2024	Jul. 26, 2024~Aug. 02, 2024	Jul. 03, 2025	Conducted (TH05-HY)
Switch Control Mainframe	Burgeon	ETF-058	EC1300485 (BOX4)	N/A	Apr. 08, 2024	Jul. 26, 2024~Aug. 02, 2024	Apr. 07, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101564	10Hz ~ 40GHz	Sep. 12, 2023	Jul. 26, 2024~Aug. 02, 2024	Sep. 11, 2024	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240411	N/A	Conducted Other Test Item	N/A	Jul. 26, 2024~Aug. 02, 2024	N/A	Conducted (TH05-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Jul. 16, 2024	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 16, 2024	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2023	Jul. 16, 2024	Oct. 19, 2024	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 14, 2024	Jul. 16, 2024	Mar. 13, 2025	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 10, 2024	Jul. 16, 2024	Mar. 09, 2025	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 07, 2024	Jul. 16, 2024	Mar. 06, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 20, 2023	Jul. 16, 2024	Sep. 19, 2024	Conduction (CO07-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 12, 2023	Jul. 26, 2024~ Jul. 30, 2024	Sep. 11, 2024	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	41912 & 05	30MHz~1GHz	Feb. 04, 2024	Jul. 26, 2024~ Jul. 30, 2024	Feb. 03, 2025	Radiation (03CH15-HY)
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	9120D-0229 4	1GHz~18GHz	Jun. 20, 2024	Jul. 26, 2024~ Jul. 30, 2024	Jun. 19, 2025	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZB ECK	BBHA 9170	00993	18GHz~40GHz	Nov. 24, 2023	Jul. 26, 2024~ Jul. 30, 2024	Nov. 23, 2024	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 25, 2023	Jul. 26, 2024~ Jul. 30, 2024	Dec. 24, 2024	Radiation (03CH15-HY)
Preamplifier	EMEC	EM01G18G	060837	1GHz~18GHz	Feb. 15, 2024	Jul. 26, 2024~ Jul. 30, 2024	Feb. 14, 2025	Radiation (03CH15-HY)
Preamplifier	EM Electronics	EM01G18G	060802	1GHz~18GHz	Feb. 29, 2024	Jul. 26, 2024~ Jul. 30, 2024	Feb. 28, 2025	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 27, 2024	Jul. 26, 2024~ Jul. 30, 2024	May 26, 2025	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY5413008 5	20MHz~8.4GHz	Oct. 06, 2023	Jul. 26, 2024~ Jul. 30, 2024	Oct. 05, 2024	Radiation (03CH15-HY
Spectrum Analyzer	Keysight	N9010B	MY6024105 8	10Hz~44GHz	Jul. 11, 2024	Jul. 26, 2024~ Jul. 30, 2024	Jul. 10, 2025	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jul. 26, 2024~ Jul. 30, 2024	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jul. 26, 2024~ Jul. 30, 2024	N/A	Radiation (03CH15-HY)
Software	Audix	E3_V9_23062 1	RK-002394	N/A	N/A	Jul. 26, 2024~ Jul. 30, 2024	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104, 102E	MY582185/4 ,519228/2,80 3950/2	N/A	Jun. 11, 2024	Jul. 26, 2024~ Jul. 30, 2024	Jun. 10, 2025	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,80 4012/2	18-40G	Jan. 02, 2024	Jul. 26, 2024~ Jul. 30, 2024	Jan. 01, 2025	Radiation (03CH15-HY)
Filter	Wainwright	WRCQV14-5 425-5825-652 5-6925-60SS	SN1	N/A	Jan. 05, 2024	Jul. 26, 2024~ Jul. 30, 2024	Jan. 04, 2025	Radiation (03CH15-HY)
Filter	Wainwright	WRCQV14-6 025-6425-712 5-7525-60SS	SN2	N/A	Jan. 05, 2024	Jul. 26, 2024~ Jul. 30, 2024	Jan. 04, 2025	Radiation (03CH15-HY)
Filter	Wainwright	WLJ4-1000-1 530-6000-40S T	SN4	1.53GHz Low Pass Filter	Jun. 05, 2024	Jul. 26, 2024~ Jul. 30, 2024	Jun. 04, 2025	Radiation (03CH15-HY)
Filter	Wainwright	WHKX6-7268 -9200-26500- 40CD	SN4	9GHz High Pass Filter	May 22, 2024	Jul. 26, 2024~ Jul. 30, 2024	May 21, 2025	Radiation (03CH15-HY)
Hygrometer	TECPEL	DTM-302	SN4	N/A	Sep. 08, 2023	Jul. 26, 2024~ Jul. 30, 2024	Sep. 07, 2024	Radiation (03CH15-HY)

THE END