



FCC RADIO TEST REPORT

FCC ID : UZ7KC50E22
Equipment : KC50E22 Kiosk Computer
Brand Name : Zebra
Model Name : KC50E22
Applicant : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
Manufacturer : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on May 14, 2024 and testing was performed from May 14, 2024 to Aug. 06, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sportun International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 EUT Information (Referenced Model).....	5
1.3 Product Specification of Equipment Under Test.....	6
1.4 Modification of EUT	6
1.5 Testing Location	7
1.6 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	12
3 Test Result.....	13
3.1 6dB and 99% Bandwidth Measurement	13
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	16
3.5 Radiated Band Edges and Spurious Emission Measurement	17
3.6 AC Conducted Emission Measurement.....	21
3.7 Antenna Requirements	23
4 List of Measuring Equipment	24
5 Measurement Uncertainty	26
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	
Appendix G. Spot Check Evaluation on KC50E22	



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	3.65 dB under the limit at 449.80 MHz
3.6	15.207	AC Conducted Emission	Pass	7.02 dB under the limit at 13.15 MHz
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. ECR inquiry for data referencing from UZ7KC50A22 has been approved by FCC. The ECR inquiry and the associated document are submitted in the confidential exhibit.
2. UZ7KC50E22 is different from FCC ID: UZ7KC50A22 (Reference model), in the following:
 - The only difference between UZ7KC50E22 and UZ7KC50A22 are the main board schematics, key components of BOM and NFC software and hardware.
3. All the test results are referenced from UZ7KC50A22 (Sporton Test Report FR450112B), and spot check results to justify data referencing is presented in the Appendix G.
4. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
5. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Yun Huang**Report Producer: Clio Lo**



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	KC50E22 Kiosk Computer
Brand Name	Zebra
Model Name	KC50E22
FCC ID	UZ7KC50E22
Supports Radios application	WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE

1.2 EUT Information (Referenced Model)

Product Feature	
FCC ID	UZ7KC50A22
EUT supports Radios application	NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
HW Version	REV:PT
SW Version	13-30-02.00-TG-U00-STD-ATH-04
OS Version	Android 13
MFD	10MAY24
EUT Stage	Identical Prototype

Remark: The EUT's information above is declared by manufacturer.

Specification of Accessories				
AC Adapter	Brand Name	ZEBRA	Model Name	PS000088A01
USB C-C Cable	Brand Name	ZEBRA	Part Number	CBL-EC5X-USBC3A-01
Stand	Brand Name	ZEBRA	Part Number	3PTY-SC-2000-CF2-01
Printer	Brand Name	ZEBRA	Model Name	ZD230t
2nd display	Brand Name	ZEBRA	Model Name	TD50-15F00
Edge scanner	Brand Name	ZEBRA	Part Number	ZFLX-SCNR-E00
Edge LED Light Bar	Brand Name	ZEBRA	Part Number	ZFLX-LTBAR-200
USB Cable	Brand Name	ZEBRA	Part Number	300283-002



1.3 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	<Ant. 1> Bluetooth – LE (1Mbps): 4.80 dBm / 0.0030 W Bluetooth – LE (2Mbps): 5.00 dBm / 0.0032 W <Ant. 2> Bluetooth – LE (1Mbps): 4.30 dBm / 0.0027 W Bluetooth – LE (2Mbps): 4.40 dBm / 0.0028 W
99% Occupied Bandwidth	<Ant. 1> 1.019 MHz for 1Mbps 1.998 MHz for 2Mbps <Ant. 2> 1.019 MHz for 1Mbps 1.998 MHz for 2Mbps
Antenna Type / Gain	<Ant. 1>: PIFA with gain 2.81 dBi <Ant. 2>: Coupling with gain 2.80 dBi
Type of Modulation	Bluetooth LE: GFSK

Remark: The above EUT's information was declared by manufacturer. Please refer to Disclaimer in report summary.

1.4 Modification of EUT

No modifications made to the EUT during the testing.



1.5 Testing Location

Test Site	Sportun International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sportun Site No. TH05-HY, CO07-HY, 03CH22-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.6 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-



2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	<Ant. 1> Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps <Ant. 2> Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps




Summary table of Test Cases	
Test Item	Data Rate / Modulation
Radiated Test Cases	<p><Ant. 1></p> <p>Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps</p> <p>Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps</p> <p>Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps</p> <p>Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps</p> <p>Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps</p> <p>Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps</p> <p><Ant. 2></p> <p>Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps</p> <p>Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps</p> <p>Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps</p> <p>Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps</p> <p>Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps</p> <p>Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps</p>
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + Scan Bar Code + USB C-C Cable Display with 2nd display + USB Cable with Printer + AC Adapter + LAN Link with Notebook + Edge USB-C with (Edge scanner + (Data Link with USB Flash Drive (USB to SD Card) + Edge LED Light Bar + Mouse) + Stand
Remark:	
1. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. Data Link with USB Flash Drive means data application transferred mode between EUT and USB Flash Drive.	

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth -LE Tx Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	Barcode	N/A	N/A	N/A	N/A	N/A
3.	WLAN AP	ASUS	RT-AC52	MSQ-RTAC4A00	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Mouse	ACER	MOANUOA	FCC DoC	Shielded, 1.7 m	N/A
6.	USB dongle	SanDisk	E4BDC	FCC DoC	N/A	N/A
7.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT4.0.211.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\text{Offset(dB)} = \text{RF cable loss(dB)} + \text{attenuator factor(dB)}$$

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.



3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9kHz~30MHz	Sep. 12, 2023	May 14, 2024~Jul. 10, 2024	Sep. 11, 2024	Radiation (03CH22-HY)
Bilog Antenna with 6dB	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63304 & 002	30MHz~1GHz	Oct. 15, 2023	May 14, 2024~Jul. 10, 2024	Oct. 14, 2024	Radiation (03CH22-HY)
Amplifier	SONOMA	310N	421581	N/A	Jul. 15, 2023	May 14, 2024~Jul. 10, 2024	Jul. 14, 2024	Radiation (03CH22-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C04A18EN	1GHz~18GHz	Jul. 12, 2023	May 14, 2024~Jul. 10, 2024	Jul. 11, 2024	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1224	18GHz-40GHz	Jul. 10, 2023	May 14, 2024~Jun. 17, 2024	Jul. 09, 2024	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1224	18GHz-40GHz	Jun. 24, 2024	Jun. 25, 2024~Jul. 10, 2024	Jun. 23, 2025	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz-40GHz	May 18, 2024	Jun. 17, 2024~Jun. 25, 2024	May 17, 2025	Radiation (03CH22-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 28, 2023	May 14, 2024~Jul. 10, 2024	Sep. 27, 2024	Radiation (03CH22-HY)
Preamplifier	EMEC	EM18G40G	060872	18-40GHz	Sep. 06, 2023	May 14, 2024~Jul. 10, 2024	Sep. 05, 2024	Radiation (03CH22-HY)
Signal Analyzer	Keysight	N9010B	MY62170278	10Hz~44GHz	Aug. 31, 2023	May 14, 2024~Jul. 10, 2024	Aug. 30, 2024	Radiation (03CH22-HY)
EMI Test Receiver	Keysight	N9038B	MY62210111	20Hz~8.4GHz	Aug. 23, 2023	May 14, 2024~Jul. 10, 2024	Aug. 22, 2024	Radiation (03CH22-HY)
Hygrometer	TECPTEL	DTM-303A	TP211469	N/A	Jan. 03, 2024	May 14, 2024~Jul. 10, 2024	Jan. 02, 2025	Radiation (03CH22-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	May 14, 2024~Jul. 10, 2024	N/A	Radiation (03CH22-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 14, 2024~Jul. 10, 2024	N/A	Radiation (03CH22-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 14, 2024~Jul. 10, 2024	N/A	Radiation (03CH22-HY)
Software	Audix	E3 6.09824_2019 122	RK-002347	N/A	N/A	May 14, 2024~Jul. 10, 2024	N/A	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 06, 2024	May 14, 2024~Jul. 10, 2024	Mar. 05, 2025	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804390/2,8046 11/2,804615/2	N/A	Oct. 24, 2023	May 14, 2024~Jul. 10, 2024	Oct. 23, 2024	Radiation (03CH22-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Jun. 26, 2024	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 26, 2024	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2023	Jun. 26, 2024	Oct. 19, 2024	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 14, 2024	Jun. 26, 2024	Mar. 13, 2025	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 10, 2024	Jun. 26, 2024	Mar. 09, 2025	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 07, 2024	Jun. 26, 2024	Mar. 06, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 20, 2023	Jun. 26, 2024	Sep. 19, 2024	Conduction (CO07-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	May 14, 2024~May 20, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO 35 (NO:109)	10MHz~6GHz	Jan. 15, 2024	May 14, 2024~May 20, 2024	Jan. 14, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2023	May 14, 2024~May 20, 2024	Aug. 22, 2024	Conducted (TH05-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	3.44 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	6.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	4.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	4.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	5.40 dB
---	---------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Sylvia Li				Temperature:	21~25		°C
Test Date:	2024/05/13~2024/05/20				Relative Humidity:	51~54		%

<Ant. 1>

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.017	0.677	0.50	Pass
BLE	1Mbps	1	19	2440	1.019	0.674	0.50	Pass
BLE	1Mbps	1	39	2480	1.019	0.675	0.50	Pass

TEST RESULTS DATA Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	4.80	30.00	2.81	7.61	36.00	Pass
BLE	1Mbps	1	19	2440	4.50	30.00	2.81	7.31	36.00	Pass
BLE	1Mbps	1	39	2480	4.60	30.00	2.81	7.41	36.00	Pass

TEST RESULTS DATA Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	4.72	-9.55	2.81	8.00	Pass
BLE	1Mbps	1	19	2440	4.16	-10.12	2.81	8.00	Pass
BLE	1Mbps	1	39	2480	4.47	-9.81	2.81	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	1.998	1.151	0.50	Pass
BLE	2Mbps	1	19	2440	1.998	1.149	0.50	Pass
BLE	2Mbps	1	39	2480	1.998	1.148	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	5.00	30.00	2.81	7.81	36.00	Pass
BLE	2Mbps	1	19	2440	4.50	30.00	2.81	7.31	36.00	Pass
BLE	2Mbps	1	39	2480	4.60	30.00	2.81	7.41	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	4.75	-12.47	2.81	8.00	Pass
BLE	2Mbps	1	19	2440	4.17	-13.06	2.81	8.00	Pass
BLE	2Mbps	1	39	2480	4.46	-12.76	2.81	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<Ant. 2>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.019	0.675	0.50	Pass
BLE	1Mbps	1	19	2440	1.019	0.673	0.50	Pass
BLE	1Mbps	1	39	2480	1.017	0.667	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	4.00	30.00	2.80	6.80	36.00	Pass
BLE	1Mbps	1	19	2440	4.30	30.00	2.80	7.10	36.00	Pass
BLE	1Mbps	1	39	2480	4.20	30.00	2.80	7.00	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	3.17	-11.16	2.80	8.00	Pass
BLE	1Mbps	1	19	2440	3.47	-10.87	2.80	8.00	Pass
BLE	1Mbps	1	39	2480	3.07	-11.23	2.80	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	1.998	1.146	0.50	Pass
BLE	2Mbps	1	19	2440	1.998	1.148	0.50	Pass
BLE	2Mbps	1	39	2480	1.998	1.147	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	4.00	30.00	2.80	6.80	36.00	Pass
BLE	2Mbps	1	19	2440	4.40	30.00	2.80	7.20	36.00	Pass
BLE	2Mbps	1	39	2480	4.20	30.00	2.80	7.00	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	3.15	-14.16	2.80	8.00	Pass
BLE	2Mbps	1	19	2440	3.47	-13.81	2.80	8.00	Pass
BLE	2Mbps	1	39	2480	3.07	-14.18	2.80	8.00	Pass


Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.



<Ant. 1>


6dB Bandwidth

<1Mbps>






<2Mbps>






99% Occupied Bandwidth

<1Mbps>






<2Mbps>






Power Spectral Density (dBm/3kHz)

<1Mbps>






<2Mbps>







Band Edge and Conducted Spurious Emission

<1Mbps>












<2Mbps>










<Ant. 2>


6dB Bandwidth

<1Mbps>






<2Mbps>






99% Occupied Bandwidth

<1Mbps>






<2Mbps>






Power Spectral Density (dBm/3kHz)

<1Mbps>






<2Mbps>







Band Edge and Conducted Spurious Emission

<1Mbps>












<2M>










Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	Temperature :	22.3~24.7°C
		Relative Humidity :	40.4~48.9%

EUT Information

Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	22.86	55.63	32.77	L1	OFF	19.9
0.156750	45.74	---	65.63	19.89	L1	OFF	19.9
0.280770	---	15.55	50.79	35.24	L1	OFF	19.9
0.280770	34.26	---	60.79	26.53	L1	OFF	19.9
0.462840	---	19.18	46.64	27.46	L1	OFF	19.9
0.462840	27.05	---	56.64	29.59	L1	OFF	19.9
2.835150	---	21.54	46.00	24.46	L1	OFF	20.0
2.835150	26.52	---	56.00	29.48	L1	OFF	20.0
11.564070	---	32.34	50.00	17.66	L1	OFF	20.1
11.564070	37.63	---	60.00	22.37	L1	OFF	20.1
11.936670	---	32.07	50.00	17.93	L1	OFF	20.1
11.936670	38.96	---	60.00	21.04	L1	OFF	20.1
12.659730	---	34.51	50.00	15.49	L1	OFF	20.1
12.659730	39.76	---	60.00	20.24	L1	OFF	20.1
13.059870	---	41.41	50.00	8.59	L1	OFF	20.1
13.059870	47.53	---	60.00	12.47	L1	OFF	20.1
13.558920	---	41.46	50.00	8.54	L1	OFF	20.1
13.558920	46.47	---	60.00	13.53	L1	OFF	20.1
14.155440	---	34.12	50.00	15.88	L1	OFF	20.1

14.155440	40.20	---	60.00	19.80	L1	OFF	20.1
14.550000	---	35.43	50.00	14.57	L1	OFF	20.1
14.550000	41.81	---	60.00	18.19	L1	OFF	20.1
15.148500	---	32.88	50.00	17.12	L1	OFF	20.1
15.148500	39.68	---	60.00	20.32	L1	OFF	20.1

EUT Information

Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	23.01	55.63	32.62	N	OFF	19.9
0.156750	46.26	---	65.63	19.37	N	OFF	19.9
0.264750	---	19.36	51.28	31.92	N	OFF	19.9
0.264750	35.40	---	61.28	25.88	N	OFF	19.9
11.571000	---	27.77	50.00	22.23	N	OFF	20.1
11.571000	34.50	---	60.00	25.50	N	OFF	20.1
12.032610	---	33.48	50.00	16.52	N	OFF	20.1
12.032610	38.62	---	60.00	21.38	N	OFF	20.1
12.766830	---	33.82	50.00	16.18	N	OFF	20.1
12.766830	41.44	---	60.00	18.56	N	OFF	20.1
13.152570	---	42.98	50.00	7.02	N	OFF	20.1
13.152570	48.27	---	60.00	11.73	N	OFF	20.1
13.561710	---	41.23	50.00	8.77	N	OFF	20.1
13.561710	46.12	---	60.00	13.88	N	OFF	20.1
14.550000	---	34.93	50.00	15.07	N	OFF	20.1
14.550000	41.02	---	60.00	18.98	N	OFF	20.1
15.744750	---	29.80	50.00	20.20	N	OFF	20.2
15.744750	36.90	---	60.00	23.10	N	OFF	20.2
29.617350	---	25.04	50.00	24.96	N	OFF	20.2

29.617350	30.97	---	60.00	29.03	N	OFF	20.2
-----------	-------	-----	-------	-------	---	-----	------



Appendix C. Radiated Spurious Emission

Test Engineer :	Ken Kuo, BANK Lin, Fred Tseng and Karl Hou	Temperature :		20.8~24.8°C	
		Relative Humidity :	52.4~63.8%		

<Ant. 1_1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE Ant	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2375.1	51.28	-22.72	74	38.3	27	18.33	32.35	300	45	P	H
		2376.045	41.87	-12.13	54	28.88	27	18.34	32.35	300	45	A	H
	*	2402	101.21	-	-	88.19	27	18.38	32.36	300	45	P	H
	*	2402	100.61	-	-	87.59	27	18.38	32.36	300	45	A	H
													H
		2316.09	50.6	-23.4	74	37.63	27.06	18.22	32.31	200	39	P	V
		2332.155	41.1	-12.9	54	28.09	27.08	18.25	32.32	200	39	A	V
	*	2402	99.19	-	-	86.17	27	18.38	32.36	200	39	P	V
	*	2402	98.59	-	-	85.57	27	18.38	32.36	200	39	A	V
													V
BLE CH 19 2440MHz		2376.4	52.19	-21.81	74	39.2	27	18.34	32.35	292	44	P	H
		2375.92	42.5	-11.5	54	29.51	27	18.34	32.35	292	44	A	H
	*	2440	102.31	-	-	89.44	26.8	18.45	32.38	292	44	P	H
	*	2440	101.71	-	-	88.84	26.8	18.45	32.38	292	44	A	H
		2499.12	51.21	-22.79	74	38.08	26.99	18.56	32.42	292	44	P	H
		2498.16	41.32	-12.68	54	28.2	26.98	18.56	32.42	292	44	A	H
		2378.48	50.91	-23.09	74	37.92	27	18.34	32.35	216	34	P	V
		2377.04	40.86	-13.14	54	27.87	27	18.34	32.35	216	34	A	V
	*	2440	99.33	-	-	86.46	26.8	18.45	32.38	216	34	P	V
	*	2440	98.78	-	-	85.91	26.8	18.45	32.38	216	34	A	V
		2496.08	50.59	-23.41	74	37.5	26.96	18.55	32.42	216	34	P	V
		2491.76	41.29	-12.71	54	28.24	26.92	18.55	32.42	216	34	A	V



BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz	*	2480	101.93	-	-	88.92	26.9	18.52	32.41	277	43	P	H
	*	2480	101.32	-	-	88.31	26.9	18.52	32.41	277	43	A	H
		2498.6	50.83	-23.17	74	37.7	26.99	18.56	32.42	277	43	P	H
		2483.64	41.26	-12.74	54	28.24	26.9	18.53	32.41	277	43	A	H
													H
													H
	*	2480	98.55	-	-	85.54	26.9	18.52	32.41	258	3	P	V
	*	2480	97.97	-	-	84.96	26.9	18.52	32.41	258	3	A	V
		2484.12	50.87	-23.13	74	37.85	26.9	18.53	32.41	258	3	P	V
		2495.16	41.23	-12.77	54	28.15	26.95	18.55	32.42	258	3	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		1262	54.17	-19.83	74	45.67	24.3	15.99	31.79	300	45	P	H
		1336	53.68	-20.32	74	44.88	24.44	16.16	31.8	300	45	P	H
		4804	43.76	-30.24	74	31.91	32.32	13.03	33.5	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		1262	48.44	-25.56	74	39.94	24.3	15.99	31.79	200	39	P	V
		1412	50.03	-23.97	74	40.71	24.8	16.33	31.81	200	39	P	V
		4804	44.41	-29.59	74	32.56	32.32	13.03	33.5	-	-	P	V
													V
													V
													V
													V
													V
													V



BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 19 2440MHz		1262	54.07	-19.93	74	45.57	24.3	15.99	31.79	292	44	P	H
		1336	52.39	-21.61	74	43.59	24.44	16.16	31.8	292	44	P	H
		4880	44.62	-29.38	74	32.48	32.56	13.07	33.49	-	-	P	H
		7320	49.27	-24.73	74	31.61	37.5	16.01	35.85	-	-	P	H
		7320	40.15	-13.85	54	22.49	37.5	16.01	35.85	-	-	A	H
													H
													H
													H
													H
													H
													H
													H
		1262	48.72	-25.28	74	40.22	24.3	15.99	31.79	216	34	P	V
		1410	50.69	-23.31	74	41.38	24.8	16.32	31.81	216	34	P	V
		4880	44.8	-29.2	74	32.66	32.56	13.07	33.49	-	-	P	V
		7320	49.18	-24.82	74	31.52	37.5	16.01	35.85	-	-	P	V
		7320	40.02	-13.98	54	22.36	37.5	16.01	35.85	-	-	A	V
													V
													V
													V
													V
													V



BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz		1262	55.83	-18.17	74	47.33	24.3	15.99	31.79	277	43	P	H
		1338	52.24	-21.76	74	43.45	24.42	16.17	31.8	277	43	P	H
		4960	44.87	-29.13	74	32.53	32.7	13.11	33.47	-	-	P	H
		7440	49.06	-24.94	74	31.52	37.32	16.15	35.93	-	-	P	H
		7440	39.39	-14.61	54	21.85	37.32	16.15	35.93	-	-	A	H
													H
													H
													H
													H
													H
													H
													H
													H
													V
		1336	50.2	-23.8	74	41.4	24.44	16.16	31.8	258	3	P	V
		1782	49.65	-24.35	74	39.78	24.72	17.14	31.99	258	3	P	V
		4960	44.97	-29.03	74	32.63	32.7	13.11	33.47	-	-	P	V
		7440	49.06	-24.94	74	31.52	37.32	16.15	35.93	-	-	P	V
		7440	39.37	-14.63	54	21.83	37.32	16.15	35.93	-	-	A	V
													V
													V
													V
													V
													V
													V
	<p>1. No other spurious found. 2. All results are PASS against Peak and Average limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.</p>												



Emission above 18GHz

2.4GHz BLE (SHF)

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE SHF		24958	38.05	-35.95	74	38.55	39.33	19.75	59.58	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
Remark	1.	No other spurious found.											
	2.	All results are PASS against limit line.											
	3.	The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.											



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		45.39	26.96	-13.04	40	41.4	17.12	1.16	32.72	-	-	P	H
		150.15	31.94	-11.56	43.5	45.45	17.01	2.19	32.71	-	-	P	H
		225.21	37.77	-8.23	46	52.17	15.61	2.66	32.67	-	-	P	H
		449.8	36.55	-9.45	46	42.56	22.95	3.79	32.75	-	-	P	H
		661.2	39.85	-6.15	46	41.76	26.35	4.55	32.81	-	-	P	H
		749.4	37.46	-8.54	46	37	28.23	4.9	32.67	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
Remark	1.	No other spurious found.											
	2.	All results are PASS against limit line.											
	3.	The emission position marked as “-” means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.											



<Ant. 1_2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE Ant	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2383.29	50.19	-23.81	74	37.22	26.97	18.35	32.35	279	304	P	H
		2349.165	41.55	-12.45	54	28.59	27	18.29	32.33	279	304	A	H
	*	2402	99.95	-	-	86.93	27	18.38	32.36	279	304	P	H
	*	2402	98.51	-	-	85.49	27	18.38	32.36	279	304	A	H
													H
													H
		2388.96	50.51	-23.49	74	37.59	26.91	18.36	32.35	328	314	P	V
		2354.625	41.66	-12.34	54	28.69	27	18.3	32.33	328	314	A	V
	*	2402	98.98	-	-	85.96	27	18.38	32.36	328	314	P	V
	*	2402	97.47	-	-	84.45	27	18.38	32.36	328	314	A	V
													V
BLE CH 19 2440MHz		2364.72	50.95	-23.05	74	37.98	27	18.31	32.34	202	312	P	H
		2363.12	41.54	-12.46	54	28.57	27	18.31	32.34	202	312	A	H
	*	2440	99.66	-	-	86.79	26.8	18.45	32.38	202	312	P	H
	*	2440	98.26	-	-	85.39	26.8	18.45	32.38	202	312	A	H
		2488.48	50.07	-23.93	74	37.04	26.9	18.54	32.41	202	312	P	H
		2496.4	41.6	-12.4	54	28.51	26.96	18.55	32.42	202	312	A	H
		2353.52	50.76	-23.24	74	37.8	27	18.29	32.33	213	315	P	V
		2373.04	41.86	-12.14	54	28.87	27	18.33	32.34	213	315	A	V
	*	2440	99.61	-	-	86.74	26.8	18.45	32.38	213	315	P	V
	*	2440	98.23	-	-	85.36	26.8	18.45	32.38	213	315	A	V
		2487.28	50.19	-23.81	74	37.16	26.9	18.54	32.41	213	315	P	V
		2495.12	41.59	-12.41	54	28.51	26.95	18.55	32.42	213	315	A	V



BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz	*	2480	99.65	-	-	86.64	26.9	18.52	32.41	202	305	P	H
	*	2480	98.35	-	-	85.34	26.9	18.52	32.41	202	305	A	H
		2483.72	50.62	-23.38	74	37.6	26.9	18.53	32.41	202	305	P	H
		2498.08	42.16	-11.84	54	29.04	26.98	18.56	32.42	202	305	A	H
													H
													H
	*	2480	99.91	-	-	86.9	26.9	18.52	32.41	293	318	P	V
	*	2480	98.61	-	-	85.6	26.9	18.52	32.41	293	318	A	V
		2487.84	51.23	-22.77	74	38.2	26.9	18.54	32.41	293	318	P	V
		2496.08	42.01	-11.99	54	28.92	26.96	18.55	32.42	293	318	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)





BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz		4960	45.02	-28.98	74	32.68	32.7	13.11	33.47	-	-	P	H
		7440	49.62	-24.38	74	32.08	37.32	16.15	35.93	-	-	P	H
		7440	40.43	-13.57	54	22.89	37.32	16.15	35.93	-	-	A	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
Remark	1.	No other spurious found.											
	2.	All results are PASS against Peak and Average limit line.											
	3.	The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.											



<Ant. 2_1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE Ant	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2374.995	50.91	-23.09	74	37.92	27	18.33	32.34	389	33	P	H
		2376.15	41.54	-12.46	54	28.55	27	18.34	32.35	389	33	A	H
	*	2402	100.59	-	-	87.57	27	18.38	32.36	389	33	P	H
	*	2402	100.02	-	-	87	27	18.38	32.36	389	33	A	H
													H
													H
		2334.57	50.7	-23.3	74	37.71	27.05	18.26	32.32	347	346	P	V
		2388.645	41.02	-12.98	54	28.1	26.91	18.36	32.35	347	346	A	V
	*	2402	98.72	-	-	85.7	27	18.38	32.36	347	346	P	V
	*	2402	98.17	-	-	85.15	27	18.38	32.36	347	346	A	V
BLE CH 19 2440MHz													V
		2327.28	50.75	-23.25	74	37.72	27.1	18.25	32.32	383	29	P	H
		2376.72	41.43	-12.57	54	28.44	27	18.34	32.35	383	29	A	H
	*	2440	101.76	-	-	88.89	26.8	18.45	32.38	383	29	P	H
	*	2440	101.24	-	-	88.37	26.8	18.45	32.38	383	29	A	H
		2490.4	50.3	-23.7	74	37.27	26.9	18.54	32.41	383	29	P	H
		2499.28	41.2	-12.8	54	28.07	26.99	18.56	32.42	383	29	A	H
		2351.44	50.72	-23.28	74	37.76	27	18.29	32.33	361	360	P	V
		2376.88	41.17	-12.83	54	28.18	27	18.34	32.35	361	360	A	V
	*	2440	99.81	-	-	86.94	26.8	18.45	32.38	361	360	P	V
	*	2440	99.29	-	-	86.42	26.8	18.45	32.38	361	360	A	V
		2491.36	50.22	-23.78	74	37.18	26.91	18.54	32.41	361	360	P	V
		2484.56	40.97	-13.03	54	27.95	26.9	18.53	32.41	361	360	A	V



BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz	*	2480	101.99	-	-	88.98	26.9	18.52	32.41	369	29	P	H
	*	2480	101.44	-	-	88.43	26.9	18.52	32.41	369	29	A	H
		2497.92	50.46	-23.54	74	37.34	26.98	18.56	32.42	369	29	P	H
		2493.92	41.08	-12.92	54	28.01	26.94	18.55	32.42	369	29	A	H
													H
													H
	*	2480	99.46	-	-	86.45	26.9	18.52	32.41	354	360	P	V
	*	2480	98.92	-	-	85.91	26.9	18.52	32.41	354	360	A	V
		2498	50.5	-23.5	74	37.38	26.98	18.56	32.42	354	360	P	V
		2486.6	41.26	-12.74	54	28.23	26.9	18.54	32.41	354	360	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		1262	53.36	-20.64	74	44.86	24.3	15.99	31.79	389	33	P	H
		1336	49.37	-24.63	74	40.57	24.44	16.16	31.8	389	33	P	H
		4804	43.66	-30.34	74	31.81	32.32	13.03	33.5	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		1114	50.96	-23.04	74	43.12	23.98	15.62	31.76	347	346	P	V
		1262	50.44	-23.56	74	41.94	24.3	15.99	31.79	347	346	P	V
		4804	44.54	-29.46	74	32.69	32.32	13.03	33.5	-	-	P	V
													V
													V
													V
													V
													V
													V



BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 19 2440MHz		1262	53.89	-20.11	74	45.39	24.3	15.99	31.79	383	29	P	H
		1336	50.12	-23.88	74	41.32	24.44	16.16	31.8	383	29	P	H
		4880	44.67	-29.33	74	32.53	32.56	13.07	33.49	-	-	P	H
		7320	49.48	-24.52	74	31.82	37.5	16.01	35.85	-	-	P	H
		7320	39.99	-14.01	54	22.33	37.5	16.01	35.85	-	-	A	H
													H
													H
													H
													H
													H
													H
													H
		1262	50.86	-23.14	74	42.36	24.3	15.99	31.79	361	360	P	V
		1410	51.91	-22.09	74	42.6	24.8	16.32	31.81	361	360	P	V
		4880	45.22	-28.78	74	33.08	32.56	13.07	33.49	-	-	P	V
		7320	49.06	-24.94	74	31.4	37.5	16.01	35.85	-	-	P	V
		7320	40.09	-13.91	54	22.43	37.5	16.01	35.85	-	-	A	V
													V
													V
													V
													V
													V



BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz		1262	53.48	-20.52	74	44.98	24.3	15.99	31.79	369	29	P	H
		1336	50.12	-23.88	74	41.32	24.44	16.16	31.8	369	29	P	H
		4960	45.98	-28.02	74	33.64	32.7	13.11	33.47	-	-	P	H
		7440	49.08	-24.92	74	31.54	37.32	16.15	35.93	-	-	P	H
		7440	39.27	-14.73	54	21.73	37.32	16.15	35.93	-	-	A	H
													H
													H
													H
													H
													H
Remark	1.	No other spurious found.											
	2.	All results are PASS against Peak and Average limit line.											
	3.	The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.											



Emission above 18GHz

2.4GHz BLE (SHF)

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE SHF		23705	38.4	-35.6	74	40.56	38.78	19.08	60.02	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
Remark	1.	No other spurious found.											
	2.	All results are PASS against limit line.											
	3.	The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.											



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		45.39	26.96	-13.04	40	41.4	17.12	1.16	32.72	-	-	P	H
		150.15	31.94	-11.56	43.5	45.45	17.01	2.19	32.71	-	-	P	H
		225.21	37.77	-8.23	46	52.17	15.61	2.66	32.67	-	-	P	H
		449.8	36.55	-9.45	46	42.56	22.95	3.79	32.75	-	-	P	H
		661.2	39.85	-6.15	46	41.76	26.35	4.55	32.81	-	-	P	H
		749.4	37.46	-8.54	46	37	28.23	4.9	32.67	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
2.4GHz BLE LF		45.39	33.7	-6.3	40	48.14	17.12	1.16	32.72	-	-	P	V
		146.91	33.81	-9.69	43.5	47.11	17.25	2.16	32.71	-	-	P	V
		224.94	38	-8	46	52.45	15.58	2.64	32.67	-	-	P	V
		449.8	42.35	-3.65	46	48.36	22.95	3.79	32.75	100	170	Q	V
		675.2	38.93	-7.07	46	40.73	26.39	4.61	32.8	-	-	P	V
		717.9	38.85	-7.15	46	39.74	27.09	4.77	32.75	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1.	No other spurious found.											
	2.	All results are PASS against limit line.											
	3.	The emission position marked as “-” means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.											



<Ant. 2_2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE Ant	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2368.695	51.21	-22.79	74	38.23	27	18.32	32.34	387	29	P	H
		2375.835	42.13	-11.87	54	29.14	27	18.34	32.35	387	29	A	H
	*	2402	101.01	-	-	87.99	27	18.38	32.36	387	29	P	H
	*	2402	99.59	-	-	86.57	27	18.38	32.36	387	29	A	H
													H
													H
		2389.38	50.29	-23.71	74	37.37	26.91	18.36	32.35	374	360	P	V
		2374.785	42.01	-11.99	54	29.02	27	18.33	32.34	374	360	A	V
	*	2402	100.41	-	-	87.39	27	18.38	32.36	374	360	P	V
	*	2402	98.84	-	-	85.82	27	18.38	32.36	374	360	A	V
BLE CH 19 2440MHz													V
		2377.68	51.17	-22.83	74	38.18	27	18.34	32.35	383	31	P	H
		2375.92	42.15	-11.85	54	29.16	27	18.34	32.35	383	31	A	H
	*	2440	101.52	-	-	88.65	26.8	18.45	32.38	383	31	P	H
	*	2440	100.08	-	-	87.21	26.8	18.45	32.38	383	31	A	H
		2497.12	50.32	-23.68	74	37.22	26.97	18.55	32.42	383	31	P	H
		2499.04	41.78	-12.22	54	28.65	26.99	18.56	32.42	383	31	A	H
		2332.4	50.44	-23.56	74	37.43	27.08	18.25	32.32	368	360	P	V
		2379.44	41.72	-12.28	54	28.73	27	18.34	32.35	368	360	A	V
	*	2440	99.81	-	-	86.94	26.8	18.45	32.38	368	360	P	V
	*	2440	98.38	-	-	85.51	26.8	18.45	32.38	368	360	A	V
		2500	50.28	-23.72	74	37.13	27	18.57	32.42	368	360	P	V
		2498.96	42.01	-11.99	54	28.88	26.99	18.56	32.42	368	360	A	V



BLE Ant	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak	Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE CH 39 2480MHz	*	2480	101.82	-	-	88.81	26.9	18.52	32.41	365	28	P	H	
	*	2480	100.35	-	-	87.34	26.9	18.52	32.41	365	28	A	H	
		2495.8	50.46	-23.54	74	37.37	26.96	18.55	32.42	365	28	P	H	
		2491.72	41.57	-12.43	54	28.52	26.92	18.55	32.42	365	28	A	H	
													H	
													H	
	*	2480	99.44	-	-	86.43	26.9	18.52	32.41	355	360	P	V	
	*	2480	98.04	-	-	85.03	26.9	18.52	32.41	355	360	A	V	
		2495.68	50.89	-23.11	74	37.8	26.96	18.55	32.42	355	360	P	V	
		2497.32	41.84	-12.16	54	28.73	26.97	18.56	32.42	355	360	A	V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		1262	54.59	-19.41	74	46.09	24.3	15.99	31.79	387	29	P	H
		1336	49.31	-24.69	74	40.51	24.44	16.16	31.8	387	29	P	H
		4804	43.45	-30.55	74	31.6	32.32	13.03	33.5	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
		1262	51.35	-22.65	74	42.85	24.3	15.99	31.79	374	360	P	V
		1410	51.26	-22.74	74	41.95	24.8	16.32	31.81	374	360	P	V
		4804	43.87	-30.13	74	32.02	32.32	13.03	33.5	-	-	P	V
													V
													V
													V
													V
													V
													V



BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 19 2440MHz		1262	53.78	-20.22	74	45.28	24.3	15.99	31.79	383	31	P	H
		1336	51.18	-22.82	74	42.38	24.44	16.16	31.8	383	31	P	H
		4880	44.85	-29.15	74	32.71	32.56	13.07	33.49	-	-	P	H
		7320	50.05	-23.95	74	32.39	37.5	16.01	35.85	-	-	P	H
		7320	40.3	-13.7	54	22.64	37.5	16.01	35.85	-	-	A	H
													H
													H
													H
													H
													H
													H
													H
		1262	50.98	-23.02	74	42.48	24.3	15.99	31.79	368	360	P	V
		1410	50.61	-23.39	74	41.3	24.8	16.32	31.81	368	360	P	V
		4880	44.62	-29.38	74	32.48	32.56	13.07	33.49	-	-	P	V
		7320	48.81	-25.19	74	31.15	37.5	16.01	35.85	-	-	P	V
		7320	40.16	-13.84	54	22.5	37.5	16.01	35.85	-	-	A	V
													V
													V
													V
													V
													V



BLE Ant	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz		1262	52.35	-21.65	74	43.85	24.3	15.99	31.79	365	28	P	H
		1336	49.02	-24.98	74	40.22	24.44	16.16	31.8	365	28	P	H
		4960	45.01	-28.99	74	32.67	32.7	13.11	33.47	-	-	P	H
		7440	49.36	-24.64	74	31.82	37.32	16.15	35.93	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													V
Remark	1.	No other spurious found.											
	2.	All results are PASS against Peak and Average limit line.											
	3.	The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.											



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is Margin line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A) (H/V)	
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dB μ V/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Margin (dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dB μ V) – 35.86 (dB)

= 55.45 (dB μ V/m)

2. Margin (dB)

= Level(dB μ V/m) – Limit Line(dB μ V/m)

= 55.45(dB μ V/m) – 74(dB μ V/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dB μ V) – 35.86 (dB)

= 43.54 (dB μ V/m)

2. Margin (dB)

= Level(dB μ V/m) – Limit Line(dB μ V/m)

= 43.54(dB μ V/m) – 54(dB μ V/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots


Test Engineer :	Ken Kuo, BANK Lin, Fred Tseng and Karl Hou	Temperature :	20.8~24.8°C
		Relative Humidity :	52.4~63.8%


Note symbol


-L	Low channel location
-R	High channel location





<Ant. 1_1Mbps>


2.4GHz 2400~2483.5MHz**BLE (Band Edge @ 3m)**











BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LE204A18EN_230712_HORIZONTAL : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH22-HY Condition : AVG_BE_54 3m LE204A18EN_230712_HORIZONTAL : R8W:1000.000KHz VBW:2.7000-ls SWT:Auto</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LE204A18EN_230712 VERTICAL : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH22-HY Condition : AVG_BE_54 3m LE204A18EN_230712 VERTICAL : R8W:1000.000KHz VBW:2.7000KHz SWT:Auto</p>	Left blank











2.4GHz 2400~2483.5MHz


BLE (Harmonic @ 3m)

















Emission above 18GHz


2.4GHz BLE (SHF @ 1m)





Emission below 1GHz

2.4GHz BLE (LF)








<Ant. 1_2Mbps>

2.4GHz 2400~2483.5MHz



BLE (Band Edge @ 3m)












BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LE204A18EN_230712 HORIZONTAL : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH22-HY Condition : AVG_BE_54 3m LE204A18EN_230712 HORIZONTAL : R8W:1000.000KHz VBW:5.100KHz SWT:Auto</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LE204A18EN_230712 VERTICAL : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH22-HY Condition : AVG_BE_54 3m LE204A18EN_230712 VERTICAL : R8W:1000.000KHz VBW:5.100KHz SWT:Auto</p>	Left blank

