

## RF Exposure Report

**Report No.:** SA131028E08N

**FCC ID:** UZ7MC32N0

**Test Model:** MC32N0

**Received Date:** Mar. 15, 2017

**Test Date:** Mar. 21, 2017

**Issued Date:** Apr. 21, 2017

**Applicant:** Zebra Technologies Corporation

**Address:** 1 Zebra Plaza, Holtsville, NY 11742

**Manufacturer:** Symbol Technologies, Inc.

**Address:** 1 Zebra Plaza, Holtsville, NY 11742

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

## Table of Contents

<b>Report Issue History Record of EUT (MC32N0).....</b>	<b>3</b>
<b>Release Control Record.....</b>	<b>3</b>
<b>1      Certificate of Conformity.....</b>	<b>4</b>
<b>2      Evaluation Rule.....</b>	<b>5</b>
<b>3      SAR Test Exclusion Thresholds (BT-LE).....</b>	<b>6</b>
<b>4      Simultaneous Multi-band Transmission Evaluation .....</b>	<b>7</b>

### Report Issue History Record of EUT (MC32N0)

Attachment No.	Issue Date	Description
131028E08	Feb. 07, 2014	Original release.
131028E08J	Mar. 02, 2017	<ol style="list-style-type: none"> <li>1. Upgraded standard version.</li> <li>2. Change Mg alloy to Al alloy for LCD frame</li> <li>3. Remove 2 LCD contact springs in the middle</li> <li>4. Reduce 3 screws from PCB to Option Frame mount from LCD side</li> <li>5. Change Audio amplifier from SSM2317 to TPA2038</li> <li>6. Change uSD socket without card detection pin</li> <li>7. Remove IST (sensor hub) microcontroller and connect the Accelerometer directly to SoC (OMAP)</li> <li>8. Change Antenna connector from Hirose to IPEX</li> <li>9. Solder bumps instead of gold tracing in PCB board</li> </ol>
131028E08K	Mar. 29, 2017	<ol style="list-style-type: none"> <li>1. Add BT-LE function</li> <li>2. Add new OS Android Lollipop</li> </ol>
131028E08N	Apr. 21, 2017	<ol style="list-style-type: none"> <li>1. Add RF Exposure Report</li> </ol>

### Release Control Record

Issue No.	Description	Date Issued
SA131028E08N	Original release.	Apr. 21, 2017

## 1 Certificate of Conformity

**Product:** Mobile Computer

**Brand:** Symbol

**Test Model:** MC32N0

**Sample Status:** MASS-PRODUCTION

**Applicant:** Zebra Technologies Corporation

**Test Date:** Mar. 21, 2017

**Standards:** FCC Part 2 (Section 2.1093)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Wendy Wu, **Date:** Apr. 21, 2017

Wendy Wu / Specialist

**Approved by :** May Chen, **Date:** Apr. 21, 2017

May Chen / Manager

## 2 Evaluation Rule

Following FCC KDB 447498 D01 "General SAR test exclusion guidance"

The corresponding SAR Exclusion Threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
  - $f(\text{GHz})$  is the RF channel transmit frequency in GHz.
  - Power and distance are rounded to the nearest mW and mm before calculation.
  - The result is rounded to one decimal place for comparison. The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.
- 2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:
  - a)  $[\text{Threshold at } 50 \text{ mm in step 1}) + (\text{test separation distance} - 50\text{mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$ , at 100MHz to 1500 MHz
  - b)  $[\text{Threshold at } 50 \text{ mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$  at  $> 1500$  MHz and  $\leq 6$  GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
  - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$  for test separation distances  $> 50$  mm and  $< 200$  mm.
  - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$  for test separation distances  $\leq 50$  mm.
  - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

### 3 SAR Test Exclusion Thresholds (BT-LE)

#### For BT-LE SAR Test Exclusion Thresholds

Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	SAR test exclusion calculation value <sup>(NOTE 1)</sup>	10-g extremity SAR test exclusion thresholds	Result
2.402 ~ 2.480	2	2	0.6	7.5	Pass

**NOTE:** 1. Calculate SAR test exclusion thresholds from condition "1" formulas.

## 4 Simultaneous Multi-band Transmission Evaluation

### 4.7.4 Simultaneous Multi-band Transmission Evaluation

#### <Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of <= 0.4 W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \frac{\sqrt{f_{(\text{GHz})}}}{7.5}$$

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 0.4 W/kg is used for SAR-1g.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
BT (DTS)	2.48	2.0	Body-worn	0	0.08

#### Note:

1. The separation distance is determined from the outer housing of the EUT to the user.
2. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

#### <SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR<sub>1g</sub> of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR<sub>1g</sub> 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR<sub>1g</sub> is greater than the SAR limit (SAR<sub>1g</sub> 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
1	WLAN (DTS) + BT (DTS)	Body-Worn	0.19	0.08	0.27	$\Sigma$ SAR < 1.6, Not required
2	WLAN (NII) + BT (DTS)	Body-Worn	0.85	0.08	0.93	$\Sigma$ SAR < 1.6, Not required

--- END ---