



FCC RADIO TEST REPORT

FCC ID : UZ7MC330L
Equipment : Mobile Computer
Brand Name : Zebra
Model Name : MC330L
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC Part 15 Subpart C §15.247

The product was received on Aug. 12, 2019 and testing was started from Aug. 24, 2019 and completed on Oct. 24, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	8
1.3 Modification of EUT	9
1.4 Testing Location	9
1.5 Applicable Standards.....	9
2 Test Configuration of Equipment Under Test.....	10
2.1 Carrier Frequency Channel	10
2.2 Test Mode	11
2.3 Connection Diagram of Test System	13
2.4 Support Unit used in test configuration and system	14
2.5 EUT Operation Test Setup	14
2.6 Measurement Results Explanation Example.....	14
3 Test Result.....	15
3.1 6dB and 99% Bandwidth Measurement	15
3.2 Output Power Measurement.....	24
3.3 Power Spectral Density Measurement	26
3.4 Conducted Band Edges and Spurious Emission Measurement	34
3.5 Radiated Band Edges and Spurious Emission Measurement	43
3.6 AC Conducted Emission Measurement.....	47
3.7 Antenna Requirements.....	49
4 List of Measuring Equipment	50
5 Uncertainty of Evaluation.....	52
Appendix A. AC Conducted Emission Test Result	
Appendix B. Radiated Spurious Emission	
Appendix C. Radiated Spurious Emission Plots	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Peak Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 4.77 dB at 42.610 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 12.94 dB at 0.152 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Yimin Ho



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Computer
Brand Name	Zebra
Model Name	MC330L
FCC ID	UZ7MC330L
EUT supports Radios application	NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DV
SW Version_Gun	Android Version 9
SW Version_Brick	Android Version 9
SW Version_Rotate	Android Version 9
FW Version_Gun	Terminal Version: 02-11-08.00-PG-U00-PLT
FW Version_Brick	Terminal Version: 02-11-08.00-PG-U00-PLT
FW Version_Rotate	Terminal Version: 02-11-08.00-PG-U00-PLT
MFD_Gun	01AUG19
MFD_Brick	02AUG19
MFD_Rotate	27JUL19
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.



Specification of Accessories				
Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V12W0US
U cable	Brand Name	Symbol	Model Name	CBL-MC33-USBCHG-01
MC32 1X battery (Inventus)	Brand Name	Symbol	Model Number	82-000011-01
MC32 2X battery (Inventus)	Brand Name	Symbol	Model Number	82-000012-02
MC32 2X battery (TWS)	Brand Name	Symbol	Model Number	82-000012-02
MC33 1X battery (Inventus)	Brand Name	ZEBRA	Model Number	BT-000338
MC33 2X battery (Inventus)	Brand Name	ZEBRA	Model Number	BT-000337
MC33 2X battery (TWS)	Brand Name	ZEBRA	Model Number	BT-000337A
MC33 7000mA 2X (Inventus)	Brand Name	ZEBRA	Model Number	BT-000375
Holster for MC3XXX Gun configuration	Brand Name	Zebra	Model Number	SG-MC3021212-01R
Rigid holster for MC3XXX Gun configuration	Brand Name	Zebra	Model Number	SG-MC33-RDHLST-01
Holster for MC3XXXX Brick configuration	Brand Name	Zebra	Model Number	11-69293-01R
Rigid holster for MC3XXX Brick configuration	Brand Name	Zebra	Model Number	SG-MC33-RDHLST-01
Lanyard for MC3XXX Brick Configuration	Brand Name	Zebra	Model Number	SG-MC33-LNYDB-01
Protective boot for MC3XXX straight shooter	Brand Name	Zebra	Model Number	SG-MC33-RBTG-01
Protective boot for MC3XXX Turret Cup of Rotate configuration	Brand Name	Zebra	Model Number	SG-MC33-RBTRT-01
Protective boot for MC3XXX Rotate configuration	Brand Name	Zebra	Model Number	SG-MC33-RBTRD-01



<Sample Information>

Organization / Function / Group	SKU1	SKU2	SKU3	SKU4	SKU5
Phase	DV	DV	DV	DV	DV
Configuration					
Form Factor	Gun	Gun	Gun - Amazon	Gun China	Rotate
Scanner	SE965	SE4850 new 20-4850-IM001R	SE4770	SE4720	SE965
Keypad	Numeric (29Key)	Function Numeric (47Key)	AlphaNum (47Key)	Function Numeric (38Key)	Numeric (47Key)
Tier	Base	Base	Base	Base	Base
NFC	Yes	Yes	Yes	Yes	Yes
Camera	NA	NA	NA	NA	No
Audio Jack (NA)	NA	NA	NA	NA	No
Back Hsg	Gun 18D	Gun 18D	Gun 18D	Gun 18D	Rotate Head
Screen Protector	No	Yes	Yes	No	No
RFID Tag	Yes	Yes	Yes	Yes	No
Hand strap	No	Yes	Yes	No	No
USB Charge cable in box	No	No	No	Yes	No
Wal wart adaptor	No	No	No	Yes	No
PCB	Tripod	Tripod	Tripod	Tripod	Tripod
DRAM/eMMCIC	4/32 GB MLC	4/32 GB MLC	4/32 GB MLC	4/16 GB MLC	4/32 GB MLC
DRAM/eMMC Mfr main source	Hynix/Hynix	Hynix/Hynix	Hynix/Hynix	Hynix/Hynix	Hynix/Hynix



Organization / Function / Group	SKU6	SKU7	SKU8	SKU9	SKU10
Phase	DV	DV	DV	DV	DV
Configuration					
Form Factor	Straight (S)	Straight (S)	Straight (S) China	Straight (L)	Straight(45)
Scanner	SE965	SE4770	SE4720	SE4850 new 20-4850-IM001R	SE4770
Keypad	AlphaNum (47Key)	Function Numeric (38Key)	Function Numeric (38Key)	Numeric (29Key)	Function Numeric (38Key)
Tier	Base + Camera	Base + Camera	Base	Base + Camera	Base + Camera
NFC	Yes	Yes	Yes	Yes	Yes
Camera	Yes	Yes	No	Yes	Yes
Audio Jack (NA)	No	No	No	No	No
Back Hsg	22 Deg ST	22 Deg ST	22 Deg ST	18 deg ST	45 deg ST
Screen Protector	No	No	No	Yes	Yes
RFID Tag	No	No	No	No	No
Hand strap	Yes	No	No	No	Yes
USB Charge cable in box	No	No	Yes	No	No
Wal wart adaptor	No	No	Yes	No	No
PCB	Tripod	Tripod	Tripod	Tripod	Tripod
DRAM/eMMC	4/32 GB MLC	4/32 GB MLC	4/16 GB MLC	4/32 GB MLC	4/32 GB MLC
DRAM/eMMC Mfr main source	Hynix/Hynix	Hynix/Hynix	Hynix/Hynix	Hynix/Hynix	Hynix/Hynix

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	0.30 dBm (0.0011 W) for 1Mbps 0.20 dBm (0.0010 W) for 2Mbps
99% Occupied Bandwidth	1.029 MHz for 1Mbps 2.038 MHz for 2Mbps
Antenna Type / Gain	PIFA Antenna type with gain 3.40 dBi
Type of Modulation	Bluetooth LE : GFSK



1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sportun Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sportun Site No.	
	03CH12-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-



2.2 Test Mode

Channel	Frequency	Bluetooth – LE 1Mbps RF Average Output Power
		Data Rate / Modulation
		GFSK
		1Mbps
Ch00	2402MHz	-1.10 dBm
Ch19	2440MHz	0.30 dBm
Ch39	2480MHz	0.20 dBm
Channel	Frequency	Bluetooth – LE 2Mbps RF Average Output Power
		Data Rate / Modulation
		GFSK
		2Mbps
Ch00	2402MHz	-1.20 dBm
Ch19	2440MHz	0.20 dBm
Ch39	2480MHz	0.10 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.




The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + Color bar + MC33 7000mA 2X (Inventus) + USB Data Link with Notebook (eMMC to Notebook) for SKU 5
Remark: 1. Data Linking with Notebook means data application transferred mode between EUT and Notebook. 2. For Radiated Test Cases, the tests were performed with MC33 2X battery (Inventus) and SKU 5.	

2.3 Connection Diagram of Test System

<Bluetooth – LE Tx Mode>



<AC Conducted Emission Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
4.	Notebook	DELL	Latitude E5570	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT v3.0.298.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
6. Measure and record the results in the test report.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth

Test Engineer :	Kai Liao			Temperature :	21~25°C
				Relative Humidity :	51~54%

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	0.669	0.50	Pass
BLE	1Mbps	1	19	2440	0.661	0.50	Pass
BLE	1Mbps	1	39	2480	0.665	0.50	Pass
BLE	2Mbps	1	0	2402	1.549	0.50	Pass
BLE	2Mbps	1	19	2440	1.134	0.50	Pass
BLE	2Mbps	1	39	2480	1.139	0.50	Pass


<1 Mbps>

6 dB Bandwidth Plot on Channel 00






6 dB Bandwidth Plot on Channel 19



Date: 24.OCT.2019 23:18:16

6 dB Bandwidth Plot on Channel 39




Date: 24.OCT.2019 23:23:47




<2 Mbps>

6 dB Bandwidth Plot on Channel 00



Date: 24.OCT.2019 23:38:36


6 dB Bandwidth Plot on Channel 19



Date: 24.OCT.2019 23:31:33



6 dB Bandwidth Plot on Channel 39




3.1.6 Test Result of 99% Occupied Bandwidth

Test Engineer :	Kai Liao			Temperature :	21~25°C
				Relative Humidity :	51~54%

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.029	Pass
BLE	1Mbps	1	19	2440	1.023	Pass
BLE	1Mbps	1	39	2480	1.027	Pass
BLE	2Mbps	1	0	2402	2.038	Pass
BLE	2Mbps	1	19	2440	2.034	Pass
BLE	2Mbps	1	39	2480	2.030	Pass


<1 Mbps>

99% Bandwidth Plot on Channel 00






99% Occupied Bandwidth Plot on Channel 19



99% Occupied Bandwidth Plot on Channel 39




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<2 Mbps>

99% Bandwidth Plot on Channel 00




99% Occupied Bandwidth Plot on Channel 19





99% Occupied Bandwidth Plot on Channel 39



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for average output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the average output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Average Output Power

Test Engineer :		Kai Liao				Temperature :		21~25°C	
						Relative Humidity :		51~54%	

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	-1.10	30.00	3.40	2.30	36.00	Pass
BLE	1Mbps	1	19	2440	0.30	30.00	3.40	3.70	36.00	Pass
BLE	1Mbps	1	39	2480	0.20	30.00	3.40	3.60	36.00	Pass
BLE	2Mbps	1	0	2402	-1.20	30.00	3.40	2.20	36.00	Pass
BLE	2Mbps	1	19	2440	0.20	30.00	3.40	3.60	36.00	Pass
BLE	2Mbps	1	39	2480	0.10	30.00	3.40	3.50	36.00	Pass

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 30dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Test Engineer :	Kai Liao	Temperature :		21~25°C	
		Relative Humidity :		51~54%	


Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-1.07	-15.49	3.40	8.00	Pass
BLE	1Mbps	1	19	2440	0.52	-13.99	3.40	8.00	Pass
BLE	1Mbps	1	39	2480	0.38	-14.08	3.40	8.00	Pass
BLE	2Mbps	1	0	2402	-1.05	-18.98	3.40	8.00	Pass
BLE	2Mbps	1	19	2440	0.56	-17.33	3.40	8.00	Pass
BLE	2Mbps	1	39	2480	0.37	-17.47	3.40	8.00	Pass

3.3.6 Test Result of Power Spectral Density Plots (100kHz)

Test Engineer :	Kai Liao	Temperature :		21~25°C	
		Relative Humidity :		51~54%	

<1 Mbps>


PSD 100kHz Plot on Channel 00




Date: 24.OCT.2019 23:21:09



PSD 100kHz Plot on Channel 19




PSD 100kHz Plot on Channel 39






<2 Mbps>

PSD 100kHz Plot on Channel 00




PSD 100kHz Plot on Channel 19





PSD 100kHz Plot on Channel 39




3.3.7 Test Result of Power Spectral Density Plots (3kHz)

Test Engineer :	Kai Liao	Temperature :	21~25°C
		Relative Humidity :	51~54%


<1 Mbps>

PSD 3kHz Plot on Channel 00






PSD 3kHz Plot on Channel 19



Date: 24.OCT.2019 23:18:28

PSD 3kHz Plot on Channel 39




Date: 24.OCT.2019 23:24:04




<2 Mbps>

PSD 3kHz Plot on Channel 00




PSD 3kHz Plot on Channel 19





PSD 3kHz Plot on Channel 39





3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup




3.4.5 Test Result of Conducted Band Edges Plots


Test Engineer :	Kai Liao	Temperature :	21~25°C
		Relative Humidity :	51~54%

<1 Mbps>

Low Band Edge Plot on Channel 00




High Band Edge Plot on Channel 39






<2 Mbps>

Low Band Edge Plot on Channel 00



High Band Edge Plot on Channel 39




3.4.6 Test Result of Conducted Spurious Emission Plots

Test Engineer :	Kai Liao	Temperature :	21~25°C
		Relative Humidity :	51~54%


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00






Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 19



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 19






Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 39






Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 00



Conducted Spurious Emission Plot on Bluetooth LE 2Mbps


GFSK Channel 00






Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 19



Conducted Spurious Emission Plot on Bluetooth LE 2Mbps


GFSK Channel 19






Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 39



Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 39





3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.



3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Sep. 07, 2019~Oct. 14, 2019	Jan. 06, 2020	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	37059&01	30MHz~1GHz	Oct. 13, 2018	Sep. 07, 2019~Oct. 11, 2019	Oct. 12, 2019	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	37059&01	30MHz~1GHz	Oct. 12, 2019	Oct. 12, 2019~Oct. 14, 2019	Oct. 11, 2020	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-132 8	1GHz ~ 18GHz	Nov. 09, 2018	Sep. 07, 2019~Oct. 14, 2019	Nov. 08, 2019	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 584	18GHz ~ 40GHz	Dec. 05, 2018	Sep. 07, 2019~Oct. 14, 2019	Dec. 04, 2019	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 25, 2019	Sep. 07, 2019~Oct. 14, 2019	Mar. 24, 2020	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A023 75	1GHz~26.5GHz	May 27, 2019	Sep. 07, 2019~Oct. 14, 2019	May 26, 2020	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03K	171000180 0054002	1GHz~18GHz	Aug. 06, 2019	Sep. 07, 2019~Oct. 14, 2019	Aug. 05, 2020	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA00101800 -30-10P	160111800 02	1GHz~18GHz	Aug. 01, 2019	Oct. 14, 2019~Oct. 14, 2019	Jul. 31, 2020	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 06, 2018	Sep. 07, 2019~Oct. 14, 2019	Dec. 05, 2019	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY553705 26	10Hz~44GHz	Mar. 19, 2019	Sep. 07, 2019~Oct. 14, 2019	Mar. 18, 2020	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-1 2SS	SN1	1.2 GHz Lowpass	Mar. 22, 2019	Sep. 07, 2019~Oct. 14, 2019	Mar. 21, 2020	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60ST	SN2	3GHz High Pass	Jul. 15, 2019	Sep. 07, 2019~Oct. 14, 2019	Jul. 14, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M~40GHz	Feb. 26, 2019	Sep. 07, 2019~Oct. 14, 2019	Feb. 25, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40GHz	Feb. 26, 2019	Sep. 07, 2019~Oct. 14, 2019	Feb. 25, 2020	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Sep. 07, 2019~Oct. 14, 2019	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Sep. 07, 2019~Oct. 14, 2019	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-00098 9	N/A	N/A	Sep. 07, 2019~Oct. 14, 2019	N/A	Radiation (03CH12-HY)
Power Sensor	DARE	RPR3006W	13I00030S NO32	9kHz~6GHz	Dec. 03, 2018	Oct. 23, 2019~Oct. 24, 2019	Dec. 02, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	Oct. 23, 2019~Oct. 24, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Oct. 23, 2019~Oct. 24, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC120838 2	N/A	Mar. 27, 2019	Oct. 23, 2019~Oct. 24, 2019	Mar. 26, 2020	Conducted (TH05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 24, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Aug. 24, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Aug. 24, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Aug. 24, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Aug. 24, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Aug. 24, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Aug. 24, 2019	Dec. 30, 2019	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	5.1
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)


Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	5.2
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	4.7
---	-----




Appendix A. AC Conducted Emission Test Results





Test Engineer :	Louis Chung	Temperature :	25.2~26.2°C
Test Voltage :	120Vac / 60Hz	Relative Humidity :	47.4~58.2%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	52.86	---	65.88	13.02	N	OFF	19.4
0.152250	---	36.01	55.88	19.87	N	OFF	19.4
0.161250	50.23	---	65.40	15.17	N	OFF	19.4
0.161250	---	33.45	55.40	21.95	N	OFF	19.4
0.170250	47.25	---	64.95	17.70	N	OFF	19.4
0.170250	---	30.06	54.95	24.89	N	OFF	19.4
0.487500	33.97	---	56.21	22.24	N	OFF	19.5
0.487500	---	28.17	46.21	18.04	N	OFF	19.5
3.475500	35.20	---	56.00	20.80	N	OFF	19.5
3.475500	---	27.65	46.00	18.35	N	OFF	19.5
3.669000	35.08	---	56.00	20.92	N	OFF	19.5
3.669000	---	27.74	46.00	18.26	N	OFF	19.5



Appendix B. Radiated Spurious Emission

Test Engineer :	Jack Cheng, Lance Chiang and CR Liao	Temperature :		23.1~26.4°C	
		Relative Humidity :		51.8~60.9%	

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak (P/A)	Avg. (H/V)
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)		
BLE CH 00 2402MHz		2315.145	55.54	-18.46	74	44.26	27.81	16.54	33.07	250	344	P	H
		2337.51	46.16	-7.84	54	35.02	27.67	16.57	33.1	250	344	A	H
	*	2402	88.62	-	-	77.65	27.5	16.64	33.17	250	344	P	H
	*	2402	87.89	-	-	76.92	27.5	16.64	33.17	250	344	A	H
													H
		2375.625	55.39	-18.61	74	44.37	27.55	16.61	33.14	208	336	P	V
		2329.845	46.28	-7.72	54	35.09	27.72	16.56	33.09	208	336	A	V
	*	2402	98.51	-	-	87.54	27.5	16.64	33.17	208	336	P	V
	*	2402	97.86	-	-	86.89	27.5	16.64	33.17	208	336	A	V
													V
BLE CH 19 2440MHz		2323.58	55.75	-18.25	74	44.52	27.76	16.55	33.08	216	337	P	H
		2341.36	46.07	-7.93	54	34.95	27.65	16.57	33.1	216	337	A	H
	*	2440	89.47	-	-	78.6	27.42	16.67	33.22	216	337	P	H
	*	2440	88.73	-	-	77.86	27.42	16.67	33.22	216	337	A	H
		2498.11	54.67	-19.33	74	43.94	27.3	16.72	33.29	216	337	P	H
		2491.95	45.8	-8.2	54	35.04	27.32	16.72	33.28	216	337	A	H
		2354.24	56.11	-17.89	74	45.05	27.59	16.59	33.12	195	324	P	V
		2310.98	46.47	-7.53	54	35.17	27.83	16.53	33.06	195	324	A	V
	*	2440	99.98	-	-	89.11	27.42	16.67	33.22	195	324	P	V
	*	2440	99.43	-	-	88.56	27.42	16.67	33.22	195	324	A	V
		2498.6	54.73	-19.27	74	44	27.3	16.72	33.29	195	324	P	V
		2496.92	45.9	-8.1	54	35.16	27.31	16.72	33.29	195	324	A	V



BLE CH 39 2480MHz	*	2480	88.95	-	-	78.17	27.34	16.71	33.27	400	46	P	H
	*	2480	88.34	-	-	77.56	27.34	16.71	33.27	400	46	A	H
		2499.64	54.81	-19.19	74	44.08	27.3	16.72	33.29	400	46	P	H
		2494.32	45.88	-8.12	54	35.13	27.31	16.72	33.28	400	46	A	H
													H
													H
	*	2480	100.76	-	-	89.98	27.34	16.71	33.27	194	326	P	V
	*	2480	100.09	-	-	89.31	27.34	16.71	33.27	194	326	A	V
		2485.52	54.92	-19.08	74	44.15	27.33	16.71	33.27	194	326	P	V
		2484.36	45.97	-8.03	54	35.2	27.33	16.71	33.27	194	326	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	38.24	-35.76	74	60.35	31.1	10.07	63.28	100	0	P	H
													H
													H
													H
		4804	37.58	-36.42	74	59.69	31.1	10.07	63.28	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	38.12	-35.88	74	60.19	31.1	10.08	63.25	100	0	P	H
		7320	43.88	-30.12	74	55.54	36.56	12.5	60.72	100	0	P	H
													H
													H
		4880	38.23	-35.77	74	60.3	31.1	10.08	63.25	100	0	P	V
		7320	44.27	-29.73	74	55.93	36.56	12.5	60.72	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	39.09	-34.91	74	60.91	31.32	10.08	63.22	100	0	P	H
		7440	43.46	-30.54	74	55.04	36.38	12.61	60.57	100	0	P	H
													H
													H
		4960	38.34	-35.66	74	60.16	31.32	10.08	63.22	100	0	P	V
		7440	43.15	-30.85	74	54.73	36.38	12.61	60.57	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2321.13	55.67	-18.33	74	44.43	27.77	6.52	33.08	250	342	P	H
		2310.105	47.79	-6.21	54	36.48	27.84	6.5	33.06	250	342	A	H
	*	2402	88.25	-	-	77.28	27.5	6.61	33.17	250	342	P	H
	*	2402	86.99	-	-	76.02	27.5	6.61	33.17	250	342	A	H
													H
													H
		2310.945	55.04	-18.96	74	43.74	27.83	6.5	33.06	200	340	P	V
		2325.75	47.91	-6.09	54	36.69	27.75	6.52	33.08	200	340	A	V
	*	2402	98.78	-	-	87.81	27.5	6.61	33.17	200	340	P	V
	*	2402	97.41	-	-	86.44	27.5	6.61	33.17	200	340	A	V
BLE CH 19 2440MHz													V
		2332.4	55.67	-18.33	74	44.49	27.71	6.53	33.09	211	343	P	H
		2337.02	48.29	-5.71	54	37.14	27.68	6.53	33.09	211	343	A	H
	*	2440	89.47	-	-	78.6	27.42	6.64	33.22	211	343	P	H
	*	2440	88.2	-	-	77.33	27.42	6.64	33.22	211	343	A	H
		2489.71	55.26	-18.74	74	44.5	27.32	6.69	33.28	211	343	P	H
		2490.06	47.55	-6.45	54	36.79	27.32	6.69	33.28	211	343	A	H
		2363.06	55.43	-18.57	74	44.39	27.57	6.57	33.13	214	326	P	V
		2320.08	47.73	-6.27	54	36.48	27.78	6.51	33.07	214	326	A	V
	*	2440	100.04	-	-	89.17	27.42	6.64	33.22	214	326	P	V
	*	2440	98.63	-	-	87.76	27.42	6.64	33.22	214	326	A	V
		2488.1	54.78	-19.22	74	44.03	27.32	6.68	33.28	214	326	P	V
		2487.47	47.61	-6.39	54	36.84	27.33	6.68	33.27	214	326	A	V



BLE CH 39 2480MHz	*	2480	89.02	-	-	78.24	27.34	6.68	33.27	400	49	P	H
	*	2480	87.66	-	-	76.88	27.34	6.68	33.27	400	49	A	H
		2497.88	55.05	-18.95	74	44.32	27.3	6.69	33.29	400	49	P	H
		2485.4	47.47	-6.53	54	36.7	27.33	6.68	33.27	400	49	A	H
													H
													H
	*	2480	100.74	-	-	89.96	27.34	6.68	33.27	201	324	P	V
	*	2480	99.37	-	-	88.59	27.34	6.68	33.27	201	324	A	V
		2496.56	55.36	-18.64	74	44.62	27.31	6.69	33.29	201	324	P	V
		2493.08	47.38	-6.62	54	36.63	27.31	6.69	33.28	201	324	A	V
													V
													V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	37.93	-36.07	74	60.04	31.1	9.59	63.28	100	0	P	H
													H
													H
													H
		4804	38.01	-35.99	74	60.12	31.1	9.59	63.28	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	38.06	-35.94	74	60.13	31.1	9.6	63.25	100	0	P	H
		7320	44.23	-29.77	74	55.89	36.56	12.03	60.72	100	0	P	H
													H
													H
		4880	37.62	-36.38	74	59.69	31.1	9.6	63.25	100	0	P	V
		7320	44.1	-29.9	74	55.76	36.56	12.03	60.72	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	38.97	-35.03	74	60.79	31.32	9.61	63.22	100	0	P	H
		7440	43.04	-30.96	74	54.62	36.38	12.13	60.57	100	0	P	H
													H
													H
		4960	38.34	-35.66	74	60.16	31.32	9.61	63.22	100	0	P	V
		7440	42.98	-31.02	74	54.56	36.38	12.13	60.57	100	0	P	V
													V
													V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
			Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A) (H/V)	
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dB μ V/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) - Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dB μ V) - 35.86 (dB)

= 55.45 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) - Limit Line(dB μ V/m)

= 55.45(dB μ V/m) - 74(dB μ V/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dB μ V) - 35.86 (dB)

= 43.54 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) - Limit Line(dB μ V/m)

= 43.54(dB μ V/m) - 54(dB μ V/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".



Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Jack Cheng, Lance Chiang and CR Liao	Temperature :	23.1~26.4°C
		Relative Humidity :	51.8~60.9%

Note symbol





-L	Low channel location
-R	High channel location





<1Mbps>

2.4GHz 2400~2483.5MHz



BLE (Band Edge @ 3m)


BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH12-HV Condition : PEAK_BE_74 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 981244</p>	 <p>Site : 03CH12-HV Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 981244</p>
Avg.	 <p>Site : 03CH12-HV Condition : AVG_BE_54 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.0000Hz VBW:3.0000Hz SWT:Auto Detector : Peak Project : 981244</p>	 <p>Site : 03CH12-HV Condition : AVG_54 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.0000Hz VBW:3.0000Hz SWT:Auto Detector : Peak Project : 981244</p>











BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Horizontal	Fundamental
Peak	 <p>Level (dBuV/m)</p> <p>Date: 2019-09-10</p> <p>Site : 03CH12-HV Condition : PEAK_BE_74 3m HORN_9120D_132B HORIZONTAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak 981244</p>	Left blank
Avg.	 <p>Level (dBuV/m)</p> <p>Date: 2019-09-10</p> <p>Site : 03CH12-HV Condition : AVG_BE_54 3m HORN_9120D_132B HORIZONTAL Detector : R8W:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak 981244</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Vertical	Fundamental
Peak	 <p>Site : 03CH12-HV Condition : PEAK_BE_74 3m HORN_9120D_1328 VERTICAL Detector : Peak Project : 981244</p>	Left blank
Avg.	 <p>Site : 03CH12-HV Condition : AVG_BE_54 3m HORN_9120D_1328 VERTICAL Detector : Peak Project : 981244</p>	Left blank











2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 <p>Site : 03QH12-HV Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Project : 981244</p>	 <p>Site : 03QH12-HV Condition : PEAK_74 3m HORN_9120D_1328 VERTICAL Detector : Peak Project : 981244</p>













<2Mbps>

2.4GHz 2400~2483.5MHz


BLE (Band Edge @ 3m)


BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH12-I-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 981244</p>	 <p>Site : 03CH12-I-HY Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 981244</p>
Avg.	 <p>Site : 03CH12-I-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL : RBW:1000.0000Hz VBW:10.0000Hz SWT:Auto Detector : Peak Project : 981244</p>	 <p>Site : 03CH12-I-HY Condition : AVG_54 3m HORN_91200_1328 HORIZONTAL : RBW:1000.0000Hz VBW:10.0000Hz SWT:Auto Detector : Peak Project : 981244</p>











BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Horizontal	Fundamental
Peak	 <p>Level (dBuV/m)</p> <p>Date: 2019-09-10</p> <p>Site : 03CH12-HV Condition : PEAK_BE_74 3m HORN_9120D_132B HORIZONTAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak 981244</p>	Left blank
Avg.	 <p>Level (dBuV/m)</p> <p>Date: 2019-09-10</p> <p>Site : 03CH12-HV Condition : AVG_BE_54 3m HORN_9120D_132B HORIZONTAL Detector : R8W:1000.000KHz VBW:10.000KHz SWT:Auto Project : Peak 981244</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 <p>Level (dBuV/m)</p> <p>Date: 2019-09-10</p> <p>PEAK_BE_74</p> <p>Site : 03CH12-HV Condition : PEAK_BE_74 3m HORN_9120D_132B VERTICAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak 981244</p>	Left blank
Avg.	 <p>Level (dBuV/m)</p> <p>Date: 2019-09-10</p> <p>AVG_BE_54</p> <p>Site : 03CH12-HV Condition : AVG_BE_54 3m HORN_9120D_132B VERTICAL Detector : R8W:1000.000KHz VBW:10.000KHz SWT:Auto Project : Peak 981244</p>	Left blank











2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 <p>Site : 03QH12-HV Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Project : 981244</p>	 <p>Site : 03QH12-HV Condition : PEAK_74 3m HORN_9120D_1328 VERTICAL Detector : Peak Project : 981244</p>








Emission below 1GHz


2.4GHz BLE (LF)






Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth -LE for 1Mbps	62.4	390	2.56	3kHz	2.05
Bluetooth -LE for 2Mbps	32.8	205	4.88	10kHz	4.84

**1Mbps**

Date: 23.OCT.2019 00:53:34

2Mbps

Date: 23.OCT.2019 00:54:37