



FCC RADIO TEST REPORT

FCC ID : UZ7MC345B
Equipment : Mobile Computer
Brand Name : ZEBRA
Model Name : MC345B
Applicant : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
Manufacturer : Zebra Technologies Corporation
3 Overlook Point, Lincolnshire, IL 60069 USA
Standard : FCC Part 15 Subpart E §15.407

The product was received on Oct. 25, 2024 and testing was performed from Nov. 01, 2024 to Jan. 21, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 EUT Information (Referenced Model).....	5
1.3 Product Specification of Equipment Under Test.....	7
1.4 Modification of EUT	9
1.5 Testing Location	10
1.6 Applicable Standards.....	10
2 Test Configuration of Equipment Under Test	11
2.1 Carrier Frequency and Channel	11
2.2 Test Mode.....	12
2.3 Connection Diagram of Test System.....	13
2.4 Support Unit used in test configuration and system	14
2.5 EUT Operation Test Setup	15
2.6 Measurement Results Explanation Example.....	15
3 Test Result	16
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	16
3.2 Maximum Conducted Output Power Measurement	17
3.3 Power Spectral Density Measurement	18
3.4 Unwanted Emissions Measurement.....	20
3.5 AC Conducted Emission Measurement.....	25
3.6 Antenna Requirements.....	27
4 List of Measuring Equipment.....	28
5 Measurement Uncertainty	29
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Data	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	
Appendix F. Spot Check Evaluation on MC345B	



History of this test report

Report No.	Version	Description	Issue Date
FR4O2225F	01	Initial issue of report	Feb. 19, 2025



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	1.17 dB under the limit at 5931.80 MHz
3.5	15.207	AC Conducted Emission	Pass	14.45 dB under the limit at 0.16 MHz
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. ECR inquiry for data referencing from UZ7MC345A has been approved by FCC. The ECR inquiry and the associated document are submitted in the confidential exhibit.
2. UZ7MC345B is different from FCC ID: UZ7MC345A (Reference model), in the following:
 - The only difference between UZ7MC345A and UZ7MC345B are the WWAN support bands, which is controlled by software.
3. All the test results are referenced from UZ7MC345A (Sporton Test Report FR4O2228F), and spot check results to justify data referencing is presented in the Appendix F.
4. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
5. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Mila Chen



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Computer
Brand Name	ZEBRA
Model Name	MC345B
FCC ID	UZ7MC345B
Supported Radios application	WCDMA/HSPA/LTE/5G NR/NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE

1.2 EUT Information (Referenced Model)

Product Feature	
FCC ID	UZ7MC345A
Sample 1	SKU 9 (Brick+SE5800+38 Keypad)
Sample 2	SKU 10 (Gun+SE4770+29 Keypad)
Sample 3	SKU 11 (Gun+SE5500+47 Keypad)
EUT supports Radios application	WCDMA/HSPA/LTE/5G NR/NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
HW Version	EV
SW Version	14-10-10.00-UG-U00-PRD-NEM-04
FW Version	FUSION_QA_6_1.0.0.001_U
MFD	14SEP24
EUT Stage	Identical Prototype

Remark: The EUT's information above is declared by manufacturer.



Stage	MC34 WWAN SKU list				
Configuration	SKU3	SKU6	SKU9	SKU10	SKU11
WW/WL	WWAN	WWAN	WWAN	WWAN	WWAN
Form Factor	FA	FA	FA	FA	FA
SKU	Prem	Prem+	Prem+	Prem	Prem+
Brick / Gun	Gun	Gun	Brick	Gun	Gun
DDR size	6GB	6GB	6GB	6GB	6GB
UFS size	64GB	128GB	128GB	64GB	128GB
Scan engine	SE5500	SE5800	SE5800	SE4770	SE5500
FF Camera	None	5MP (PN)	5MP (PN)	None	5MP (PN)
RF Camera		13MP (PN)	13MP (PN)		13MP (PN)
Keypad	47	47	38	29	47
Battery	7000mAh	7000mAh	7000mAh	7000mAh	7000mAh
Region (ROW or NA)	NA	NA	NA	NA	NA

Specification of Accessories				
Adapter USB Wall Charger	Brand Name	Zebra	Model Number	PWR-WUA5V12W0US
Battery 1 Standard Battery (7000mAh)	Brand Name	Zebra	Model Number	BT-000375
			Manufacturer	TWS
Battery 2 Standard Battery (7000mAh)	Brand Name	Zebra	Model Number	BT-000375
			Manufacturer	Inventus
Battery 3 BLE Battery (7000mAh)	Brand Name	Zebra	Model Number	BT-000444
Battery 4 BLE Battery (7000mAh)	Brand Name	Zebra	Model Number	BT-000375
Type C USB Cable	Brand Name	Zebra	Model Number	CBL-TC5X-USBC2A-01
USB Cable Cup	Brand Name	Zebra	Model Number	CBL-MC33-USBCCHG-01
Soft Holster for Gun Type	Brand Name	Zebra	Model Number	SG-MC3021212-01R
Soft Holster for Brick Type	Brand Name	Zebra	Model Number	SG-MC3X-SHLSTB-01
USB-C PTT Headset	Brand Name	Zebra	Model Number	HDST-USBC-PTT1-01
USB-C to 3.5mm adapter	Brand Name	Zebra	Model Number	ADP-USBC-35MM1-01
3.5mm To Quick Disconnect (QD) Adapter Cable	Brand Name	Zebra	Model Number	ADP-35M-QDCBL1-01
3.5mm PTT Headset	Brand Name	Zebra	Model Number	HDST-35MM-PTT1-01
3.5mm PTT HS2100 Headset	Brand Name	Zebra	Model Number	HS2100
Quick Disconnect (QD) Cable	Brand Name	Zebra	Model Number	CBL-HS2100-QDC1-01

1.3 Product Specification of Equipment Under Test

Product Specification is subject to this standard			
Tx/Rx Frequency Range	5725 MHz ~ 5850 MHz		
Maximum Output Power to Antenna	MIMO <Ant. 6+7> 802.11a: 24.32 dBm / 0.2704 W 802.11n HT20: 23.44 dBm / 0.2208 W 802.11n HT40: 22.90 dBm / 0.1950 W 802.11ac VHT20: 23.54 dBm / 0.2259 W 802.11ac VHT40: 23.00 dBm / 0.1995 W 802.11ac VHT80: 20.87 dBm / 0.1222 W 802.11ax HE20: 23.64 dBm / 0.2312 W 802.11ax HE40: 23.10 dBm / 0.2042 W 802.11ax HE80: 20.97 dBm / 0.1250 W		
99% Occupied Bandwidth	<Ant. 6> 802.11a: 16.66 MHz 802.11ac VHT20: 17.65 MHz 802.11ac VHT40: 36.29 MHz 802.11ac VHT80: 75.36 MHz 802.11ax HE20: 19.08 MHz 802.11ax HE40: 38.08 MHz 802.11ax HE80: 77.21 MHz <Ant. 7> 802.11a: 16.48 MHz 802.11ac VHT20: 17.64 MHz 802.11ac VHT40: 36.26 MHz 802.11ac VHT80: 75.44 MHz 802.11ax HE20: 18.96 MHz 802.11ax HE40: 38.00 MHz 802.11ax HE80: 77.16 MHz		
Antenna Type / Gain	<Ant. 6> : PIFA Antenna with gain 1.31 dBi <Ant. 7> : Monopole Antenna with gain 0.98 dBi		
Type of Modulation	802.11a/n: OFDM (BPSK/QPSK/16QAM/64QAM) 802.11ac: OFDM (BPSK/QPSK/16QAM/64QAM/256QAM) 802.11ax: OFDMA (BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM)		
Antenna Function Description		Ant. 6	Ant. 7
	802.11a/n/ac/ax MIMO	V	V
	802.11ax TXBF	V	V

Remark:

1. MIMO Ant. 6+7 Directional Gain is a calculated result from MIMO Ant. 6 and MIMO Ant. 7. The formula used in calculation is documented in section 1.2.1.
2. Power of MIMO Ant. 6 + Ant. 7 is a calculated result from sum of the power MIMO Ant. 6 and MIMO Ant. 7.
3. 802.11ax Support Tx Beamforming mode, and the manufacturer declares that Tx Beamforming power/EIRP is less than CDD mode 3dbm, so CDD mode cover Tx Beamforming mode.
4. The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.3.1 Antenna Directional Gain

<For CDD Mode>

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

			DG for Power	DG for PSD	Power Limit Reduction	PSD Limit Reduction
	Ant 6 (dBi)	Ant 7 (dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	1.31	0.98	1.31	4.16	0.00	0.00

Calculation example:

If a device has two antenna, $G_{ANT6}=1.31$ dBi; $G_{ANT7}=0.98$ dBi

Directional gain of power measurement = $\max(1.31, 0.98) + 0 = 1.31$ dBi

Directional gain of PSD derived from formula which is

$10 \times \log \{ \{ [10^{(1.31 \text{ dBi} / 20)} + 10^{(0.98 \text{ dBi} / 20)}]^2 \} / 2 \}$

= 4.16 dBi

Power and PSD limit reduction = Composite gain – 6dBi, (min = 0)

<TXBF Modes>

The EUT supports beamforming modes , then

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)e)ii)

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

The directional gain “DG” is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 6	Ant 7	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	1.31	0.98	4.16	4.16	0.00	0.00

Calculation example:

Directional gain is derived from formula which is

$$10 \times \log \{ \{ [10^{\wedge} (1.31 \text{ dBi} / 20) + 10^{\wedge} (0.98 \text{ dBi} / 20)]^{\wedge} 2 \} / 2 \}$$

$$= 4.16 \text{ dBi}$$

$$\text{Power and PSD limit reduction} = \text{Composite gain} - 6\text{dBi}, (\text{min} = 0)$$

1.4 Modification of EUT

No modifications made to the EUT during the testing.

1.5 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. CO05-HY (TAF Code: 1190)
Remark	The Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, 03CH20-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.6 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel with "[#]" are 802.11ac VHT80 and 802.11ax HE80.

2.2 Test Mode

This device support 26/52/106/242/484/996-tone RU.

The PSD of partial RU is reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2022.

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The 242-tone RU is covered by 20MHz channel, 484-tone RU is covered by 40MHz channel and 996-tone RU is covered by 80MHz channel.

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is tested.

The power for 802.11n mode is smaller than 802.11ac mode, so all other conducted and radiated test is covered by 802.11ac mode.

The final test modes include the worst data rates for each modulation shown in the table below.

MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11n HT40 (Covered by VHT40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Remark: The conducted power level of each chain in MIMO mode is equal or higher than SISO mode.


Test Cases	
AC Conducted Emission	Mode 1 : LTE Band 7 Link + WLAN (5GHz) Link + Bluetooth Link + MPEG4 + Battery 1 Standard Battery (7000mAh) + USB Cable Cup (Charge from Adapter USB Wall Charger) for Sample 1
Remark: For Radiated Test Cases, the tests were performed with Battery 1 Standard Battery (7000mAh) and Sample 1.	


Ch. #		Band IV : 5725-5850 MHz				
		802.11a	802.11ac VHT20	802.11ax HE20	802.11ax HE40	802.11ax HE80
L	Low	149	149	149	151	-
M	Middle	157	-	157	-	155
H	High	165	-	165	159	-

Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<WLAN Tx Mode>

2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY700A2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
4.	Notebook	Lenovo	TP00116A	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m



2.5 EUT Operation Test Setup

The RF test items, utility "QRCT V4.1 Version 4.0.118.0" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85 GHz
2. Set RBW = 100 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

Method SA-2


(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300kHz.
 - Set VBW $\geq$ 1 MHz.
 - Add $10 \log(500 \text{ kHz/RBW})$ to the measured result, whereas RBW ($<500 \text{ kHz}$) is the reduced resolution bandwidth of the spectrum analyzer set during measurement
 - Number of points in sweep $\geq 2 \text{ Span / RBW}$.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6 \text{ dB}$ if the duty cycle is 25 percent.
1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
 3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

- (3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.



3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
(3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.


6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.4.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz





3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	N/A	Oct. 16, 2024	Nov. 01, 2024~ Dec. 17, 2024	Oct. 15, 2025	Radiation (03CH20-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Aug. 29, 2024	Nov. 01, 2024~ Dec. 17, 2024	Aug. 28, 2025	Radiation (03CH20-HY)
Preamplifier	EMEC	EM18G40G	060871	18GHz~40GHz	Aug. 23, 2024	Nov. 01, 2024~ Dec. 17, 2024	Aug. 22, 2025	Radiation (03CH20-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Nov. 01, 2024~ Dec. 17, 2024	N/A	Radiation (03CH20-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Nov. 01, 2024~ Dec. 17, 2024	N/A	Radiation (03CH20-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Nov. 01, 2024~ Dec. 17, 2024	N/A	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	N/A	Dec. 12, 2023	Nov. 01, 2024~ Nov. 25, 2024	Dec. 11, 2024	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY64320114	N/A	Oct. 05, 2024	Nov. 26, 2024~ Dec. 08, 2024	Oct. 04, 2025	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	N/A	Dec. 09, 2024	Dec. 09, 2024~ Dec. 17, 2024	Dec. 08, 2025	Radiation (03CH20-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800N 1D01N-06	47020 & 06	30MHz~1GHz	Oct. 05, 2024	Nov. 01, 2024~ Dec. 17, 2024	Oct. 04, 2025	Radiation (03CH20-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	02360	1GHz-18GHz	Nov. 01, 2024	Nov. 01, 2024~ Dec. 17, 2024	Oct. 30, 2025	Radiation (03CH20-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1224	18GHz-40GHz	Jun. 24, 2024	Nov. 01, 2024~ Dec. 17, 2024	Jun. 23, 2025	Radiation (03CH20-HY)
Preamplifier	COM-POWER	PAM-103	18020201	1MHz-1000MHz	Jan. 01, 2024	Nov. 01, 2024~ Dec. 17, 2024	Dec. 31, 2024	Radiation (03CH20-HY)
Amplifier	EMCI	EMC118A45SE	980792	N/A	Nov. 13, 2023	Nov. 01, 2024~ Nov. 11, 2024	Nov. 12, 2024	Radiation (03CH20-HY)
Amplifier	EMCI	EMC118A45SE	980792	N/A	Nov. 12, 2024	Nov. 12, 2024~ Dec. 17, 2024	Nov. 11, 2025	Radiation (03CH20-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	519229/2,8040 15/2,804027/2	N/A	Jan. 17, 2024	Nov. 01, 2024~ Dec. 17, 2024	Jan. 16, 2025	Radiation (03CH20-HY)
Hygrometer	TECPEL	DTM-303A	TP211382	N/A	Mar. 27, 2024	Nov. 01, 2024~ Dec. 17, 2024	Mar. 26, 2025	Radiation (03CH20-HY)
Software	Audix	N/A	RK-002156	N/A	N/A	Nov. 01, 2024~ Dec. 17, 2024	N/A	Radiation (03CH20-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Nov. 05, 2024~ Dec. 18, 2024	Oct. 30, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	15I00041SNO 10 (NO:248)	10MHz~6GHz	Jan. 10, 2024	Nov. 05, 2024~ Dec. 18, 2024	Jan. 09, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	Nov. 05, 2024~ Dec. 18, 2024	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	Burgeon	ETF-058	EC1300484 (BOX3)	N/A	May 20, 2024	Nov. 05, 2024~ Dec. 18, 2024	May 19, 2025	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_v ersion_240513	N/A	Conducted Other Test Item	N/A	Nov. 05, 2024~ Dec. 18, 2024	N/A	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Nov. 11, 2024	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 06, 2023	Nov. 11, 2024	Dec. 05, 2024	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Oct. 14, 2024	Nov. 11, 2024	Oct. 13, 2025	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 08, 2023	Nov. 11, 2024	Dec. 07, 2024	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Nov. 11, 2024	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	00691	N/A	Jul. 30, 2024	Nov. 11, 2024	Jul. 29, 2025	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	N/A	Oct. 15, 2024	Nov. 11, 2024	Oct. 14, 2025	Conduction (CO05-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.6 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Junyu Jhou	Temperature:	21~25	°C
Test Date:	2024/11/05~2024/12/18	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 6	Ant 7	Ant 6	Ant 7	Ant 6	Ant 7		
11a	6Mbps	2	149	5745	16.66	16.48	25.84	20.84	16.31	16.31	0.5	Pass
11a	6Mbps	2	157	5785	16.59	16.47	23.08	20.57	16.02	16.28	0.5	Pass
11a	6Mbps	2	165	5825	16.55	16.47	20.71	20.51	16.29	16.30	0.5	Pass
VHT20	MCS0	2	149	5745	17.62	17.61	20.90	21.26	16.92	16.66	0.5	Pass
VHT20	MCS0	2	157	5785	17.65	17.64	21.18	22.14	16.04	16.65	0.5	Pass
VHT20	MCS0	2	165	5825	17.61	17.61	21.21	21.14	16.67	17.28	0.5	Pass
VHT40	MCS0	2	151	5755	36.29	36.24	41.41	40.74	36.29	35.93	0.5	Pass
VHT40	MCS0	2	159	5795	36.24	36.26	41.26	41.06	36.06	36.01	0.5	Pass
VHT80	MCS0	2	155	5775	75.36	75.44	84.00	82.56	72.93	75.07	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
11a	6Mbps	2	149	5745	21.29	21.21	24.26	30.00		1.31		Pass
11a	6Mbps	2	157	5785	21.00	20.90	23.96	30.00		1.31		Pass
11a	6Mbps	2	165	5825	21.29	21.32	24.32	30.00		1.31		Pass
HT20	MCS0	2	149	5745	20.38	20.10	23.25	30.00		1.31		Pass
HT20	MCS0	2	157	5785	20.65	20.20	23.44	30.00		1.31		Pass
HT20	MCS0	2	165	5825	20.50	20.06	23.30	30.00		1.31		Pass
HT40	MCS0	2	151	5755	20.24	19.50	22.90	30.00		1.31		Pass
HT40	MCS0	2	159	5795	19.90	19.20	22.57	30.00		1.31		Pass
VHT20	MCS0	2	149	5745	20.48	20.20	23.35	30.00		1.31		Pass
VHT20	MCS0	2	157	5785	20.75	20.30	23.54	30.00		1.31		Pass
VHT20	MCS0	2	165	5825	20.60	20.16	23.40	30.00		1.31		Pass
VHT40	MCS0	2	151	5755	20.34	19.60	23.00	30.00		1.31		Pass
VHT40	MCS0	2	159	5795	20.00	19.30	22.67	30.00		1.31		Pass
VHT80	MCS0	2	155	5775	17.99	17.72	20.87	30.00		1.31		Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-3 MIMO														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
11a	6Mbps	2	149	5745	0.03	0.03	6.41	6.17	9.42	30.00		4.16		Pass
11a	6Mbps	2	157	5785	0.03	0.03	6.23	6.14	9.24	30.00		4.16		Pass
11a	6Mbps	2	165	5825	0.03	0.03	6.35	6.46	9.47	30.00		4.16		Pass
VHT20	MCS0	2	149	5745	0.02	0.01	5.29	5.02	8.30	30.00		4.16		Pass
VHT20	MCS0	2	157	5785	0.02	0.01	6.03	5.80	9.04	30.00		4.16		Pass
VHT20	MCS0	2	165	5825	0.02	0.01	5.32	5.21	8.33	30.00		4.16		Pass
VHT40	MCS0	2	151	5755	0.00	0.00	2.42	1.78	5.43	30.00		4.16		Pass
VHT40	MCS0	2	159	5795	0.00	0.00	2.29	1.86	5.30	30.00		4.16		Pass
VHT80	MCS0	2	155	5775	0.02	0.00	-2.84	-3.03	0.17	30.00		4.16		Pass

Note: PSD Sum = Max PSD(Ant. 6, Ant. 7) + 10 log (n)

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 MIMO													
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 6	Ant 7	Ant 6	Ant 7	Ant 6	Ant 7		
HE20	MCS0	2	149	5745	Full	19.02	18.95	23.26	21.39	18.74	18.51	0.5	Pass
HE20	MCS0	2	157	5785	Full	19.08	18.96	30.95	21.91	18.55	18.62	0.5	Pass
HE20	MCS0	2	165	5825	Full	19.00	18.95	23.26	21.16	18.62	18.58	0.5	Pass
HE40	MCS0	2	151	5755	Full	38.08	37.98	44.54	41.30	37.73	37.11	0.5	Pass
HE40	MCS0	2	159	5795	Full	38.00	38.00	41.87	41.62	37.79	37.19	0.5	Pass
HE80	MCS0	2	155	5775	Full	77.21	77.16	82.56	83.23	76.93	75.10	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
HE20	MCS0	2	149	5745	Full	20.58	20.30	23.45	30.00		1.31		Pass
HE20	MCS0	2	149	5745	26/0	10.49	10.23	13.37	30.00		1.31		Pass
HE20	MCS0	2	149	5745	52/37	14.03	13.62	16.84	30.00		1.31		Pass
HE20	MCS0	2	149	5745	106/53	17.15	16.71	19.95	30.00		1.31		Pass
HE20	MCS0	2	157	5785	Full	20.85	20.40	23.64	30.00		1.31		Pass
HE20	MCS0	2	157	5785	26/4	11.35	10.75	14.07	30.00		1.31		Pass
HE20	MCS0	2	157	5785	52/38	14.27	13.85	17.08	30.00		1.31		Pass
HE20	MCS0	2	157	5785	106/53	17.38	17.41	20.41	30.00		1.31		Pass
HE20	MCS0	2	165	5825	Full	20.70	20.26	23.50	30.00		1.31		Pass
HE20	MCS0	2	165	5825	26/8	10.58	10.67	13.64	30.00		1.31		Pass
HE20	MCS0	2	165	5825	52/40	13.66	13.60	16.64	30.00		1.31		Pass
HE20	MCS0	2	165	5825	106/54	16.67	16.77	19.73	30.00		1.31		Pass
HE40	MCS0	2	151	5755	Full	20.44	19.70	23.10	30.00		1.31		Pass
HE40	MCS0	2	151	5755	242/61	17.43	17.25	20.35	30.00		1.31		Pass
HE40	MCS0	2	159	5795	Full	20.10	19.40	22.77	30.00		1.31		Pass
HE40	MCS0	2	159	5795	242/62	16.82	16.54	19.69	30.00		1.31		Pass
HE80	MCS0	2	155	5775	Full	18.09	17.82	20.97	30.00		1.31		Pass
HE80	MCS0	2	155	5775	484/65	15.00	14.52	17.78	30.00		1.31		Pass
HE80	MCS0	2	155	5775	484/66	14.74	14.34	17.55	30.00		1.31		Pass

TEST RESULTS DATA
Power Spectral Density


U-NII-3 MIMO															
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
						Ant 6	Ant 7	Ant 6	Ant 7	SUM	Ant 6	Ant 7	Ant 6	Ant 7	
HE20	MCS0	2	149	5745	Full	0.02	0.00	4.99	4.84	8.00	30.00		4.16		Pass
HE20	MCS0	2	149	5745	26/0	0.02	0.02	4.51	4.44	7.52	30.00		4.16		Pass
HE20	MCS0	2	149	5745	52/37	0.02	0.02	4.89	4.59	7.90	30.00		4.16		Pass
HE20	MCS0	2	149	5745	106/53	0.00	0.01	4.80	4.42	7.81	30.00		4.16		Pass
HE20	MCS0	2	157	5785	Full	0.02	0.00	5.64	5.26	8.65	30.00		4.16		Pass
HE20	MCS0	2	157	5785	26/4	0.02	0.02	5.45	5.08	8.46	30.00		4.16		Pass
HE20	MCS0	2	157	5785	52/38	0.02	0.02	5.55	5.15	8.56	30.00		4.16		Pass
HE20	MCS0	2	157	5785	106/53	0.00	0.01	5.23	5.53	8.54	30.00		4.16		Pass
HE20	MCS0	2	165	5825	Full	0.02	0.00	5.23	5.02	8.24	30.00		4.16		Pass
HE20	MCS0	2	165	5825	26/8	0.02	0.02	4.94	5.11	8.12	30.00		4.16		Pass
HE20	MCS0	2	165	5825	52/40	0.02	0.02	4.86	4.83	7.87	30.00		4.16		Pass
HE20	MCS0	2	165	5825	106/54	0.00	0.01	4.56	4.82	7.83	30.00		4.16		Pass
HE40	MCS0	2	151	5755	Full	0.01	0.01	2.11	1.46	5.12	30.00		4.16		Pass
HE40	MCS0	2	151	5755	242/61	0.03	0.03	1.72	1.58	4.73	30.00		4.16		Pass
HE40	MCS0	2	159	5795	Full	0.01	0.01	2.18	1.48	5.19	30.00		4.16		Pass
HE40	MCS0	2	159	5795	242/62	0.03	0.03	1.34	1.18	4.35	30.00		4.16		Pass
HE80	MCS0	2	155	5775	Full	0.01	0.01	-2.99	-3.17	0.02	30.00		4.16		Pass
HE80	MCS0	2	155	5775	484/65	0.05	0.05	-3.31	-3.73	-0.30	30.00		4.16		Pass
HE80	MCS0	2	155	5775	484/66	0.05	0.05	-3.56	-3.77	-0.55	30.00		4.16		Pass

Note: PSD Sum = Max PSD(Ant. 6, Ant. 7) + 10 log (n)

**Test Result of 6dB and 26dB and 99% Occupied Bandwidth**


MIMO <Ant. 6+7>

<802.11a>






<802.11ac VHT20>






<802.11ac VHT40>






<802.11ac VHT80>






<802.11ax HE20>






<802.11ax HE40>






<802.11ax HE80>




**Test Result of Power Spectral Density**

<802.11a>




<802.11ac VHT20>






<802.11ac VHT40>




<802.11ac VHT80>






<802.11ax HE20>




<802.11ax HE40>





<802.11ax HE80>





Appendix B. AC Conducted Emission Test Results


Test Engineer :	Calvin Wang	Temperature :	23~26°C
		Relative Humidity :	45~55%

EUT Information

Test Mode :
Test Voltage :
Phase :

Mode 1
120Vac/60Hz
Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.159000	---	40.96	55.52	14.56	L1	OFF	19.8
0.159000	51.07	---	65.52	14.45	L1	OFF	19.8
0.181500	---	28.13	54.42	26.29	L1	OFF	19.8
0.181500	36.52	---	64.42	27.90	L1	OFF	19.8
0.285000	---	25.23	50.67	25.44	L1	OFF	19.8
0.285000	33.21	---	60.67	27.46	L1	OFF	19.8
0.327750	---	33.84	49.51	15.67	L1	OFF	19.8
0.327750	38.90	---	59.51	20.61	L1	OFF	19.8
0.629250	---	23.79	46.00	22.21	L1	OFF	19.8
0.629250	25.76	---	56.00	30.24	L1	OFF	19.8
7.786500	---	25.90	50.00	24.10	L1	OFF	20.2
7.786500	27.28	---	60.00	32.72	L1	OFF	20.2

EUT Information

Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.159000	---	38.59	55.52	16.93	N	OFF	19.8
0.159000	50.66	---	65.52	14.86	N	OFF	19.8
0.213000	---	29.23	53.09	23.86	N	OFF	19.8
0.213000	38.33	---	63.09	24.76	N	OFF	19.8
0.325500	---	29.06	49.57	20.51	N	OFF	19.8
0.325500	33.75	---	59.57	25.82	N	OFF	19.8
0.426750	---	27.26	47.32	20.06	N	OFF	19.8
0.426750	30.69	---	57.32	26.63	N	OFF	19.8
0.816000	---	23.60	46.00	22.40	N	OFF	19.8
0.816000	25.54	---	56.00	30.46	N	OFF	19.8
7.860750	---	26.35	50.00	23.65	N	OFF	20.2
7.860750	28.06	---	60.00	31.94	N	OFF	20.2



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	John Chuang, David Dai and Sam Chou	Temperature :	19.6~23.4°C
		Relative Humidity :	64.8~70.5%

Note symbol

-L	Low channel location
-R	High channel location

<Sample 1>

C1. Radiated Spurious Emission Test Modes




Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 51	U-NII-3	5.725-5.85	6+7	802.11a	149	5745	6Mbps	-	-
Mode 52	U-NII-3	5.725-5.85	6+7	802.11a	157	5785	6Mbps	-	-
Mode 53	U-NII-3	5.725-5.85	6+7	802.11a	165	5825	6Mbps	-	-
Mode 54	U-NII-3	5.725-5.85	6+7	802.11ax HE20	149	5745	MCS0	Full RU	-
Mode 55	U-NII-3	5.725-5.85	6+7	802.11ax HE20	149	5745	MCS0	Partial_106/53RU	-
Mode 56	U-NII-3	5.725-5.85	6+7	802.11ax HE20	157	5825	MCS0	Full RU	-
Mode 57	U-NII-3	5.725-5.85	6+7	802.11ax HE20	165	5825	MCS0	Full RU	-
Mode 58	U-NII-3	5.725-5.85	6+7	802.11ax HE20	165	5825	MCS0	Partial_106/54RU	-
Mode 59	U-NII-3	5.725-5.85	6+7	802.11ax HE40	151	5755	MCS0	Full RU	-
Mode 60	U-NII-3	5.725-5.85	6+7	802.11ax HE40	151	5755	MCS0	Partial_242/61RU	-
Mode 61	U-NII-3	5.725-5.85	6+7	802.11ax HE40	159	5795	MCS0	Full RU	-
Mode 62	U-NII-3	5.725-5.85	6+7	802.11ax HE40	159	5795	MCS0	Partial_242/62RU	-
Mode 63	U-NII-3	5.725-5.85	6+7	802.11ax HE80	155	5775	MCS0	Full RU	-
Mode 64	U-NII-3	5.725-5.85	6+7	802.11ax HE80	155	5775	MCS0	Partial_484/65RU	-
Mode 65	U-NII-3	5.725-5.85	6+7	802.11ax HE80	155	5775	MCS0	Partial_484/66RU	-
Mode 69	U-NII-3	5.725-5.85	6+7	802.11ax HE80	155	5775	MCS0	Partial_484/65RU	LF
Mode 71	U-NII-3	5.725-5.85	6+7	802.11ac VHT20	149	5745	MCS0	-	-






C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
51	802.11a	149	5647.56	62.99	68.20	-5.21	V	Peak	Pass	-	Band Edge
	802.11a	149	11490.00	46.00	54.00	-8.00	V	Avg.	Pass	-	Harmonic
52	802.11a	157	5925.25	56.52	68.20	-11.68	V	Peak	Pass	-	Band Edge
	802.11a	157	11570.00	45.04	54.00	-8.96	H	Avg.	Pass	-	Harmonic
53	802.11a	165	5924.63	58.88	68.48	-9.60	V	Peak	Pass	-	Band Edge
	802.11a	165	11650.00	44.75	54.00	-9.25	H	Avg.	Pass	-	Harmonic
54	802.11ax HE20	149	5648.00	64.78	68.20	-3.42	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	149	11490.00	45.41	54.00	-8.59	H	Avg.	Pass	Full RU	Harmonic
55	802.11ax HE20	149	5651.04	67.78	68.97	-1.19	V	Peak	Pass	Partial_106/53RU	Band Edge
	802.11ax HE20	149	-	-	-	-	-	-	-	Partial_106/53RU	Harmonic
56	802.11ax HE20	157	5652.17	60.74	69.81	-9.07	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	157	11570.00	44.55	54.00	-9.45	H	Avg.	Pass	Full RU	Harmonic
57	802.11ax HE20	165	5925.63	62.04	68.20	-6.16	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	165	11650.00	43.83	54.00	-10.17	H	Avg.	Pass	Full RU	Harmonic
58	802.11ax HE20	165	5935.00	66.05	68.20	-2.15	H	Peak	Pass	Partial_106/54RU	Band Edge
	802.11ax HE20	165	-	-	-	-	-	-	-	Partial_106/54RU	Harmonic
59	802.11ax HE40	151	5653.17	62.86	70.55	-7.69	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE40	151	11510.00	41.35	54.00	-12.65	H	Avg.	Pass	Full RU	Harmonic
60	802.11ax HE40	151	5642.32	64.72	68.20	-3.48	H	Peak	Pass	Partial_242/61RU	Band Edge
	802.11ax HE40	151	-	-	-	-	-	-	-	Partial_242/61RU	Harmonic
61	802.11ax HE40	159	5922.41	66.07	70.11	-4.04	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE40	159	11590.00	41.78	54.00	-12.22	V	Avg.	Pass	Full RU	Harmonic
62	802.11ax HE40	159	5931.56	66.27	68.20	-1.93	H	Peak	Pass	Partial_242/62RU	Band Edge
	802.11ax HE40	159	-	-	-	-	-	-	-	Partial_242/62RU	Harmonic
63	802.11ax HE80	155	5949.83	64.69	68.20	-3.51	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE80	155	11550.00	41.96	54.00	-12.04	V	Avg.	Pass	Full RU	Harmonic
64	802.11ax HE80	155	5931.80	67.03	68.20	-1.17	H	Peak	Pass	Partial_484/65RU	Band Edge
	802.11ax HE80	155	-	-	-	-	-	-	-	Partial_484/65RU	Harmonic
65	802.11ax HE80	155	5929.35	63.92	68.20	-4.28	V	Peak	Pass	Partial_484/66RU	Band Edge
	802.11ax HE80	155	-	-	-	-	-	-	-	Partial_484/66RU	Harmonic
69	LF	155	55.22	31.96	40.00	-8.04	V	QP	Pass	-	LF
71	802.11ac VHT20	149	5646.26	58.21	68.20	-9.99	V	Peak	Pass	-	Band Edge
	802.11ac VHT20	149	11490.00	44.61	54.00	-9.39	H	Avg.	Pass	-	Harmonic





	51																																																																																																																																																						
Mode	Band Edge																																																																																																																																																						
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																																						
ANT	6+7																																																																																																																																																						
Pol.	Horizontal						Fundamental																																																																																																																																																
Peak	 Site : 03CH20-HY Condition: PEAK_BE(84)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5647.56</td><td>60.06</td><td>68.20</td><td>-8.14</td><td>51.24</td><td>33.19</td><td>13.55</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr><tr><td>2</td><td>5650.17</td><td>59.30</td><td>68.33</td><td>-9.03</td><td>50.46</td><td>33.20</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr><tr><td>3</td><td>5716.29</td><td>80.81</td><td>109.76</td><td>-28.95</td><td>71.45</td><td>33.63</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr><tr><td>4</td><td>5720.35</td><td>81.99</td><td>111.60</td><td>-29.61</td><td>72.62</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5647.56	60.06	68.20	-8.14	51.24	33.19	13.55	37.92	0.00	100	335	PEAK	2	5650.17	59.30	68.33	-9.03	50.46	33.20	13.56	37.92	0.00	100	335	PEAK	3	5716.29	80.81	109.76	-28.95	71.45	33.63	13.65	37.92	0.00	100	335	PEAK	4	5720.35	81.99	111.60	-29.61	72.62	33.64	13.65	37.92	0.00	100	335	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>110.66</td><td>-----</td><td>-----</td><td>101.22</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5745.00	110.66	-----	-----	101.22	33.68	13.68	37.92	0.00	100	335	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																													
	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																													
1	5647.56	60.06	68.20	-8.14	51.24	33.19	13.55	37.92	0.00	100	335	PEAK																																																																																																																																											
2	5650.17	59.30	68.33	-9.03	50.46	33.20	13.56	37.92	0.00	100	335	PEAK																																																																																																																																											
3	5716.29	80.81	109.76	-28.95	71.45	33.63	13.65	37.92	0.00	100	335	PEAK																																																																																																																																											
4	5720.35	81.99	111.60	-29.61	72.62	33.64	13.65	37.92	0.00	100	335	PEAK																																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																														
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																													
1	5745.00	110.66	-----	-----	101.22	33.68	13.68	37.92	0.00	100	335	PEAK																																																																																																																																											
Avg.	Blank												 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>102.88</td><td>-----</td><td>-----</td><td>93.42</td><td>33.69</td><td>13.69</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5745.00	102.88	-----	-----	93.42	33.69	13.69	37.92	0.00	100	335	AVERAGE																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																													
	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																													
1	5745.00	102.88	-----	-----	93.42	33.69	13.69	37.92	0.00	100	335	AVERAGE																																																																																																																																											






	51																																																																																																																																				
Mode	Band Edge																																																																																																																																				
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																				
ANT	6+7																																																																																																																																				
Pol.	Vertical						Fundamental																																																																																																																														
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5647.56</td><td>62.99</td><td>68.20</td><td>-5.21</td><td>54.17</td><td>33.19</td><td>13.55</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr><tr><td>2</td><td>5651.33</td><td>62.53</td><td>69.19</td><td>-6.66</td><td>53.68</td><td>33.21</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr><tr><td>3</td><td>5716.58</td><td>86.61</td><td>109.84</td><td>-23.23</td><td>77.25</td><td>33.63</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr><tr><td>4</td><td>5720.06</td><td>86.21</td><td>110.94</td><td>-24.73</td><td>76.84</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5647.56	62.99	68.20	-5.21	54.17	33.19	13.55	37.92	0.00	100	256	PEAK	2	5651.33	62.53	69.19	-6.66	53.68	33.21	13.56	37.92	0.00	100	256	PEAK	3	5716.58	86.61	109.84	-23.23	77.25	33.63	13.65	37.92	0.00	100	256	PEAK	4	5720.06	86.21	110.94	-24.73	76.84	33.64	13.65	37.92	0.00	100	256	PEAK	 Site : 03CH20-HY Condition: PEAK(UNI) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>112.24</td><td>-----</td><td>-----</td><td>102.80</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5745.00	112.24	-----	-----	102.80	33.68	13.68	37.92	0.00	100	256	PEAK
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																								
1	5647.56	62.99	68.20	-5.21	54.17	33.19	13.55	37.92	0.00	100	256	PEAK																																																																																																																									
2	5651.33	62.53	69.19	-6.66	53.68	33.21	13.56	37.92	0.00	100	256	PEAK																																																																																																																									
3	5716.58	86.61	109.84	-23.23	77.25	33.63	13.65	37.92	0.00	100	256	PEAK																																																																																																																									
4	5720.06	86.21	110.94	-24.73	76.84	33.64	13.65	37.92	0.00	100	256	PEAK																																																																																																																									
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																								
1	5745.00	112.24	-----	-----	102.80	33.68	13.68	37.92	0.00	100	256	PEAK																																																																																																																									
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>105.90</td><td>-----</td><td>-----</td><td>96.46</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5745.00	105.90	-----	-----	96.46	33.68	13.68	37.92	0.00	100	256	AVERAGE																																																																																
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																								
1	5745.00	105.90	-----	-----	96.46	33.68	13.68	37.92	0.00	100	256	AVERAGE																																																																																																																									




Mode	51												
	Harmonic												
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz												
ANT	6+7												
Pol.	Horizontal						Vertical						
Peak Avg.													
	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 HORIZONTAL						Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 VERTICAL						
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	11490.00	52.93	74.00	-21.07	35.82	39.20	19.46	42.47	0.92	321	177	PEAK	
2	11490.00	45.76	54.00	-8.24	28.65	39.20	19.46	42.47	0.92	321	177	Average	
3	17235.00	53.90	68.20	-14.30	33.94	39.57	24.06	44.61	0.94	--	--	PEAK	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	11490.00	52.24	74.00	-21.76	35.13	39.20	19.46	42.47	0.92	315	335	PEAK	
2	11490.00	46.00	54.00	-8.00	28.89	39.20	19.46	42.47	0.92	315	335	Average	
3	17235.00	53.64	68.20	-14.56	33.68	39.57	24.06	44.61	0.94	--	--	PEAK	






Mode	52																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5643.29</td><td>51.97</td><td>68.20</td><td>-16.23</td><td>43.17</td><td>33.17</td><td>13.55</td><td>37.92</td><td>0.00</td><td>200</td><td>325</td><td>PEAK</td></tr><tr><td>2</td><td>5651.06</td><td>51.36</td><td>68.99</td><td>-17.63</td><td>42.51</td><td>33.21</td><td>13.56</td><td>37.92</td><td>0.00</td><td>200</td><td>325</td><td>PEAK</td></tr><tr><td>3</td><td>5700.09</td><td>61.46</td><td>105.22</td><td>-43.76</td><td>52.15</td><td>33.60</td><td>13.63</td><td>37.92</td><td>0.00</td><td>200</td><td>325</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>65.47</td><td>110.95</td><td>-45.48</td><td>56.10</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>200</td><td>325</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5643.29	51.97	68.20	-16.23	43.17	33.17	13.55	37.92	0.00	200	325	PEAK	2	5651.06	51.36	68.99	-17.63	42.51	33.21	13.56	37.92	0.00	200	325	PEAK	3	5700.09	61.46	105.22	-43.76	52.15	33.60	13.63	37.92	0.00	200	325	PEAK	4	5720.07	65.47	110.95	-45.48	56.10	33.64	13.65	37.92	0.00	200	325	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5785.00</td><td>107.37</td><td>-----</td><td>-----</td><td>97.55</td><td>34.00</td><td>13.74</td><td>37.92</td><td>0.00</td><td>200</td><td>325</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	107.37	-----	-----	97.55	34.00	13.74	37.92	0.00	200	325	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5643.29	51.97	68.20	-16.23	43.17	33.17	13.55	37.92	0.00	200	325	PEAK																																																																																																																															
2	5651.06	51.36	68.99	-17.63	42.51	33.21	13.56	37.92	0.00	200	325	PEAK																																																																																																																															
3	5700.09	61.46	105.22	-43.76	52.15	33.60	13.63	37.92	0.00	200	325	PEAK																																																																																																																															
4	5720.07	65.47	110.95	-45.48	56.10	33.64	13.65	37.92	0.00	200	325	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5785.00	107.37	-----	-----	97.55	34.00	13.74	37.92	0.00	200	325	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5785.00</td><td>101.96</td><td>-----</td><td>-----</td><td>92.18</td><td>33.96</td><td>13.74</td><td>37.92</td><td>0.00</td><td>200</td><td>325</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	101.96	-----	-----	92.18	33.96	13.74	37.92	0.00	200	325	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5785.00	101.96	-----	-----	92.18	33.96	13.74	37.92	0.00	200	325	AVERAGE																																																																																																																															




Mode	52																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																							
ANT	6+7																																																																							
Pol.	Horizontal	Fundamental																																																																						
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5854.96</td><td>66.09</td><td>110.89</td><td>-44.80</td><td>55.86</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00 200 325 PEAK</td></tr><tr><td>2</td><td>5872.29</td><td>61.59</td><td>105.96</td><td>-44.37</td><td>51.33</td><td>34.30</td><td>13.88</td><td>37.92</td><td>0.00 200 325 PEAK</td></tr><tr><td>3</td><td>5923.68</td><td>52.15</td><td>69.23</td><td>-17.08</td><td>41.82</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00 200 325 PEAK</td></tr><tr><td>4</td><td>5925.09</td><td>51.86</td><td>68.20</td><td>-16.34</td><td>41.53</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00 200 325 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5854.96	66.09	110.89	-44.80	55.86	34.30	13.85	37.92	0.00 200 325 PEAK	2	5872.29	61.59	105.96	-44.37	51.33	34.30	13.88	37.92	0.00 200 325 PEAK	3	5923.68	52.15	69.23	-17.08	41.82	34.30	13.96	37.93	0.00 200 325 PEAK	4	5925.09	51.86	68.20	-16.34	41.53	34.30	13.96	37.93	0.00 200 325 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1	5854.96	66.09	110.89	-44.80	55.86	34.30	13.85	37.92	0.00 200 325 PEAK																																																															
2	5872.29	61.59	105.96	-44.37	51.33	34.30	13.88	37.92	0.00 200 325 PEAK																																																															
3	5923.68	52.15	69.23	-17.08	41.82	34.30	13.96	37.93	0.00 200 325 PEAK																																																															
4	5925.09	51.86	68.20	-16.34	41.53	34.30	13.96	37.93	0.00 200 325 PEAK																																																															





Mode	52																																																																																																																							
	Band Edge - L																																																																																																																							
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																																																							
ANT	6+7																																																																																																																							
Pol.	Vertical					Fundamental																																																																																																																		
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5643.66</td><td>53.17</td><td>68.20</td><td>-15.03</td><td>44.37</td><td>33.17</td><td>13.55</td><td>37.92</td><td>0.00 111 300 PEAK</td></tr><tr><td>2</td><td>5650.32</td><td>51.86</td><td>68.44</td><td>-16.58</td><td>43.02</td><td>33.20</td><td>13.56</td><td>37.92</td><td>0.00 111 300 PEAK</td></tr><tr><td>3</td><td>5707.67</td><td>67.97</td><td>107.35</td><td>-39.38</td><td>58.63</td><td>33.62</td><td>13.64</td><td>37.92</td><td>0.00 111 300 PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>69.75</td><td>110.95</td><td>-41.20</td><td>60.38</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00 111 300 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5643.66	53.17	68.20	-15.03	44.37	33.17	13.55	37.92	0.00 111 300 PEAK	2	5650.32	51.86	68.44	-16.58	43.02	33.20	13.56	37.92	0.00 111 300 PEAK	3	5707.67	67.97	107.35	-39.38	58.63	33.62	13.64	37.92	0.00 111 300 PEAK	4	5720.07	69.75	110.95	-41.20	60.38	33.64	13.65	37.92	0.00 111 300 PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>113.90</td><td>-----</td><td>-----</td><td>104.00</td><td>34.00</td><td>13.74</td><td>37.92</td><td>0.00 111 300 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5785.00	113.90	-----	-----	104.00	34.00	13.74	37.92	0.00 111 300 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																															
1	5643.66	53.17	68.20	-15.03	44.37	33.17	13.55	37.92	0.00 111 300 PEAK																																																																																																															
2	5650.32	51.86	68.44	-16.58	43.02	33.20	13.56	37.92	0.00 111 300 PEAK																																																																																																															
3	5707.67	67.97	107.35	-39.38	58.63	33.62	13.64	37.92	0.00 111 300 PEAK																																																																																																															
4	5720.07	69.75	110.95	-41.20	60.38	33.64	13.65	37.92	0.00 111 300 PEAK																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																															
1	5785.00	113.90	-----	-----	104.00	34.00	13.74	37.92	0.00 111 300 PEAK																																																																																																															
Avg.	Blank					 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>107.58</td><td>-----</td><td>-----</td><td>97.76</td><td>34.00</td><td>13.74</td><td>37.92</td><td>0.00 111 300 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5785.00	107.58	-----	-----	97.76	34.00	13.74	37.92	0.00 111 300 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																															
1	5785.00	107.58	-----	-----	97.76	34.00	13.74	37.92	0.00 111 300 AVERAGE																																																																																																															






Mode	52																																																																																			
	Band Edge - R																																																																																			
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																			
ANT	6+7																																																																																			
Pol.	Vertical	Fundamental																																																																																		
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.30</td><td>70.98</td><td>112.40</td><td>-41.42</td><td>60.75</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>111</td><td>300</td><td>PEAK</td></tr><tr><td>2</td><td>5872.29</td><td>67.83</td><td>105.96</td><td>-38.13</td><td>57.57</td><td>34.30</td><td>13.88</td><td>37.92</td><td>0.00</td><td>111</td><td>300</td><td>PEAK</td></tr><tr><td>3</td><td>5924.59</td><td>56.44</td><td>68.50</td><td>-12.06</td><td>46.11</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>111</td><td>300</td><td>PEAK</td></tr><tr><td>4</td><td>5925.25</td><td>56.52</td><td>68.20</td><td>-11.68</td><td>46.19</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>111</td><td>300</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5854.30	70.98	112.40	-41.42	60.75	34.30	13.85	37.92	0.00	111	300	PEAK	2	5872.29	67.83	105.96	-38.13	57.57	34.30	13.88	37.92	0.00	111	300	PEAK	3	5924.59	56.44	68.50	-12.06	46.11	34.30	13.96	37.93	0.00	111	300	PEAK	4	5925.25	56.52	68.20	-11.68	46.19	34.30	13.96	37.93	0.00	111	300	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																											
Freq	Level	Line	Level	Factor	Loss	Factor	Factor																																																																													
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																											
1	5854.30	70.98	112.40	-41.42	60.75	34.30	13.85	37.92	0.00	111	300	PEAK																																																																								
2	5872.29	67.83	105.96	-38.13	57.57	34.30	13.88	37.92	0.00	111	300	PEAK																																																																								
3	5924.59	56.44	68.50	-12.06	46.11	34.30	13.96	37.93	0.00	111	300	PEAK																																																																								
4	5925.25	56.52	68.20	-11.68	46.19	34.30	13.96	37.93	0.00	111	300	PEAK																																																																								






Mode	52																																																																																																																																						
	Harmonic																																																																																																																																						
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																																																																						
ANT	6+7																																																																																																																																						
Pol.	Horizontal								Vertical																																																																																																																														
Peak Avg.																																																																																																																																							
	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 11570.00</td><td>52.66</td><td>74.00</td><td>-21.34</td><td>35.92</td><td>38.82</td><td>19.53</td><td>42.53</td><td>0.92</td><td>332 320 PEAK</td></tr><tr><td>2 11570.00</td><td>45.04</td><td>54.00</td><td>-8.96</td><td>28.30</td><td>38.82</td><td>19.53</td><td>42.53</td><td>0.92</td><td>332 320 Average</td></tr><tr><td>3 17355.00</td><td>55.00</td><td>68.20</td><td>-13.20</td><td>34.81</td><td>39.82</td><td>24.14</td><td>44.71</td><td>0.94</td><td>-- -- PEAK</td></tr></tbody></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11570.00	52.66	74.00	-21.34	35.92	38.82	19.53	42.53	0.92	332 320 PEAK	2 11570.00	45.04	54.00	-8.96	28.30	38.82	19.53	42.53	0.92	332 320 Average	3 17355.00	55.00	68.20	-13.20	34.81	39.82	24.14	44.71	0.94	-- -- PEAK	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 11570.00</td><td>53.11</td><td>74.00</td><td>-20.89</td><td>36.37</td><td>38.82</td><td>19.53</td><td>42.53</td><td>0.92</td><td>225 35 PEAK</td></tr><tr><td>2 11570.00</td><td>45.00</td><td>54.00</td><td>-9.00</td><td>28.26</td><td>38.82</td><td>19.53</td><td>42.53</td><td>0.92</td><td>225 35 Average</td></tr><tr><td>3 17355.00</td><td>55.34</td><td>68.20</td><td>-12.86</td><td>35.15</td><td>39.82</td><td>24.14</td><td>44.71</td><td>0.94</td><td>-- -- PEAK</td></tr></tbody></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11570.00	53.11	74.00	-20.89	36.37	38.82	19.53	42.53	0.92	225 35 PEAK	2 11570.00	45.00	54.00	-9.00	28.26	38.82	19.53	42.53	0.92	225 35 Average	3 17355.00	55.34	68.20	-12.86	35.15	39.82	24.14	44.71	0.94
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																														
1 11570.00	52.66	74.00	-21.34	35.92	38.82	19.53	42.53	0.92	332 320 PEAK																																																																																																																														
2 11570.00	45.04	54.00	-8.96	28.30	38.82	19.53	42.53	0.92	332 320 Average																																																																																																																														
3 17355.00	55.00	68.20	-13.20	34.81	39.82	24.14	44.71	0.94	-- -- PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																														
1 11570.00	53.11	74.00	-20.89	36.37	38.82	19.53	42.53	0.92	225 35 PEAK																																																																																																																														
2 11570.00	45.00	54.00	-9.00	28.26	38.82	19.53	42.53	0.92	225 35 Average																																																																																																																														
3 17355.00	55.34	68.20	-12.86	35.15	39.82	24.14	44.71	0.94	-- -- PEAK																																																																																																																														





	53																																																																																																																							
Mode	Band Edge																																																																																																																							
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHZ																																																																																																																							
ANT	6+7																																																																																																																							
Pol.	Horizontal					Fundamental																																																																																																																		
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5855.00</td><td>80.39</td><td>110.00</td><td>-30.41</td><td>70.16</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100 198 PEAK</td></tr><tr><td>2 5855.00</td><td>80.39</td><td>110.00</td><td>-30.41</td><td>70.16</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100 198 PEAK</td></tr><tr><td>3 5924.75</td><td>54.52</td><td>68.38</td><td>-13.86</td><td>44.19</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100 198 PEAK</td></tr><tr><td>4 5925.88</td><td>54.50</td><td>68.20</td><td>-13.70</td><td>44.17</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100 198 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5855.00	80.39	110.00	-30.41	70.16	34.30	13.85	37.92	0.00	100 198 PEAK	2 5855.00	80.39	110.00	-30.41	70.16	34.30	13.85	37.92	0.00	100 198 PEAK	3 5924.75	54.52	68.38	-13.86	44.19	34.30	13.96	37.93	0.00	100 198 PEAK	4 5925.88	54.50	68.20	-13.70	44.17	34.30	13.96	37.93	0.00	100 198 PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5825.00</td><td>116.77</td><td>-----</td><td>-----</td><td>106.66</td><td>34.22</td><td>13.81</td><td>37.92</td><td>0.00</td><td>100 198 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5825.00	116.77	-----	-----	106.66	34.22	13.81	37.92	0.00	100 198 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																														
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5855.00	80.39	110.00	-30.41	70.16	34.30	13.85	37.92	0.00	100 198 PEAK																																																																																																															
2 5855.00	80.39	110.00	-30.41	70.16	34.30	13.85	37.92	0.00	100 198 PEAK																																																																																																															
3 5924.75	54.52	68.38	-13.86	44.19	34.30	13.96	37.93	0.00	100 198 PEAK																																																																																																															
4 5925.88	54.50	68.20	-13.70	44.17	34.30	13.96	37.93	0.00	100 198 PEAK																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5825.00	116.77	-----	-----	106.66	34.22	13.81	37.92	0.00	100 198 PEAK																																																																																																															
Avg.	Blank					 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5825.00</td><td>110.17</td><td>-----</td><td>-----</td><td>100.06</td><td>34.22</td><td>13.81</td><td>37.92</td><td>0.00</td><td>100 198 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5825.00	110.17	-----	-----	100.06	34.22	13.81	37.92	0.00	100 198 AVERAGE																																																																						
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																														
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5825.00	110.17	-----	-----	100.06	34.22	13.81	37.92	0.00	100 198 AVERAGE																																																																																																															






	53																																																																																																																																										
Mode	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHZ																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.08</td><td>80.42</td><td>111.08</td><td>-30.66</td><td>70.19</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr><tr><td>2</td><td>5863.13</td><td>80.90</td><td>108.52</td><td>-27.62</td><td>70.66</td><td>34.30</td><td>13.86</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr><tr><td>3</td><td>5924.63</td><td>58.88</td><td>68.48</td><td>-9.60</td><td>48.55</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr><tr><td>4</td><td>5925.38</td><td>57.72</td><td>68.20</td><td>-10.48</td><td>47.39</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.08	80.42	111.08	-30.66	70.19	34.30	13.85	37.92	0.00	100	256	PEAK	2	5863.13	80.90	108.52	-27.62	70.66	34.30	13.86	37.92	0.00	100	256	PEAK	3	5924.63	58.88	68.48	-9.60	48.55	34.30	13.96	37.93	0.00	100	256	PEAK	4	5925.38	57.72	68.20	-10.48	47.39	34.30	13.96	37.93	0.00	100	256	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>113.18</td><td>-----</td><td>-----</td><td>103.14</td><td>34.17</td><td>13.79</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	113.18	-----	-----	103.14	34.17	13.79	37.92	0.00	100	256	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5854.08	80.42	111.08	-30.66	70.19	34.30	13.85	37.92	0.00	100	256	PEAK																																																																																																																															
2	5863.13	80.90	108.52	-27.62	70.66	34.30	13.86	37.92	0.00	100	256	PEAK																																																																																																																															
3	5924.63	58.88	68.48	-9.60	48.55	34.30	13.96	37.93	0.00	100	256	PEAK																																																																																																																															
4	5925.38	57.72	68.20	-10.48	47.39	34.30	13.96	37.93	0.00	100	256	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	113.18	-----	-----	103.14	34.17	13.79	37.92	0.00	100	256	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>106.53</td><td>-----</td><td>-----</td><td>96.45</td><td>34.20</td><td>13.80</td><td>37.92</td><td>0.00</td><td>100</td><td>256</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	106.53	-----	-----	96.45	34.20	13.80	37.92	0.00	100	256	AVERAGE																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	106.53	-----	-----	96.45	34.20	13.80	37.92	0.00	100	256	AVERAGE																																																																																																																															






Mode	53																																																																																																																																																						
	Harmonic																																																																																																																																																						
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz																																																																																																																																																						
ANT	6+7																																																																																																																																																						
Pol.	Horizontal						Vertical																																																																																																																																																
Peak Avg.																																																																																																																																																							
	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 HORIZONTAL						Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 VERTICAL																																																																																																																																																
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11650.00</td><td>52.78</td><td>74.00</td><td>-21.22</td><td>36.15</td><td>38.70</td><td>19.60</td><td>42.60</td><td>0.93</td><td>200</td><td>313</td><td>PEAK</td></tr><tr><td>2</td><td>11650.00</td><td>44.75</td><td>54.00</td><td>-9.25</td><td>28.12</td><td>38.70</td><td>19.60</td><td>42.60</td><td>0.93</td><td>200</td><td>313</td><td>Average</td></tr><tr><td>3</td><td>17475.00</td><td>54.74</td><td>68.20</td><td>-13.46</td><td>34.29</td><td>40.10</td><td>24.22</td><td>44.81</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11650.00	52.78	74.00	-21.22	36.15	38.70	19.60	42.60	0.93	200	313	PEAK	2	11650.00	44.75	54.00	-9.25	28.12	38.70	19.60	42.60	0.93	200	313	Average	3	17475.00	54.74	68.20	-13.46	34.29	40.10	24.22	44.81	0.94	--	--	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11650.00</td><td>51.85</td><td>74.00</td><td>-22.15</td><td>35.22</td><td>38.70</td><td>19.60</td><td>42.60</td><td>0.93</td><td>177</td><td>56</td><td>PEAK</td></tr><tr><td>2</td><td>11650.00</td><td>44.02</td><td>54.00</td><td>-9.98</td><td>27.39</td><td>38.70</td><td>19.60</td><td>42.60</td><td>0.93</td><td>177</td><td>56</td><td>Average</td></tr><tr><td>3</td><td>17475.00</td><td>54.46</td><td>68.20</td><td>-13.74</td><td>34.01</td><td>40.10</td><td>24.22</td><td>44.81</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11650.00	51.85	74.00	-22.15	35.22	38.70	19.60	42.60	0.93	177	56	PEAK	2	11650.00	44.02	54.00	-9.98	27.39	38.70	19.60	42.60	0.93	177	56	Average	3	17475.00	54.46	68.20	-13.74	34.01	40.10	24.22	44.81	0.94	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																													
1	11650.00	52.78	74.00	-21.22	36.15	38.70	19.60	42.60	0.93	200	313	PEAK																																																																																																																																											
2	11650.00	44.75	54.00	-9.25	28.12	38.70	19.60	42.60	0.93	200	313	Average																																																																																																																																											
3	17475.00	54.74	68.20	-13.46	34.29	40.10	24.22	44.81	0.94	--	--	PEAK																																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																													
1	11650.00	51.85	74.00	-22.15	35.22	38.70	19.60	42.60	0.93	177	56	PEAK																																																																																																																																											
2	11650.00	44.02	54.00	-9.98	27.39	38.70	19.60	42.60	0.93	177	56	Average																																																																																																																																											
3	17475.00	54.46	68.20	-13.74	34.01	40.10	24.22	44.81	0.94	--	--	PEAK																																																																																																																																											





	54																																																																																																															
Mode	Band Edge																																																																																																															
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz																																																																																																															
ANT	6+7																																																																																																															
Pol.	Horizontal	Fundamental																																																																																																														
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5649.74</td><td>60.77</td><td>68.20</td><td>-7.43</td><td>51.93</td><td>33.20</td><td>13.56</td><td>37.92</td><td>0.00 100 336 PEAK</td></tr><tr><td>2</td><td>5650.03</td><td>60.36</td><td>68.22</td><td>-7.86</td><td>51.52</td><td>33.20</td><td>13.56</td><td>37.92</td><td>0.00 100 336 PEAK</td></tr><tr><td>3</td><td>5715.86</td><td>79.92</td><td>109.64</td><td>-29.72</td><td>70.56</td><td>33.63</td><td>13.65</td><td>37.92</td><td>0.00 100 336 PEAK</td></tr><tr><td>4</td><td>5720.21</td><td>81.51</td><td>111.27</td><td>-29.76</td><td>72.14</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00 100 336 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5649.74	60.77	68.20	-7.43	51.93	33.20	13.56	37.92	0.00 100 336 PEAK	2	5650.03	60.36	68.22	-7.86	51.52	33.20	13.56	37.92	0.00 100 336 PEAK	3	5715.86	79.92	109.64	-29.72	70.56	33.63	13.65	37.92	0.00 100 336 PEAK	4	5720.21	81.51	111.27	-29.76	72.14	33.64	13.65	37.92	0.00 100 336 PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5745.00</td><td>107.04</td><td>-----</td><td>-----</td><td>97.60</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00 100 336 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5745.00	107.04	-----	-----	97.60	33.68	13.68	37.92	0.00 100 336 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1	5649.74	60.77	68.20	-7.43	51.93	33.20	13.56	37.92	0.00 100 336 PEAK																																																																																																							
2	5650.03	60.36	68.22	-7.86	51.52	33.20	13.56	37.92	0.00 100 336 PEAK																																																																																																							
3	5715.86	79.92	109.64	-29.72	70.56	33.63	13.65	37.92	0.00 100 336 PEAK																																																																																																							
4	5720.21	81.51	111.27	-29.76	72.14	33.64	13.65	37.92	0.00 100 336 PEAK																																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1	5745.00	107.04	-----	-----	97.60	33.68	13.68	37.92	0.00 100 336 PEAK																																																																																																							
Avg.	Blank	 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5745.00</td><td>101.28</td><td>-----</td><td>-----</td><td>91.82</td><td>33.69</td><td>13.69</td><td>37.92</td><td>0.00 100 336 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5745.00	101.28	-----	-----	91.82	33.69	13.69	37.92	0.00 100 336 AVERAGE																																																																						
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1	5745.00	101.28	-----	-----	91.82	33.69	13.69	37.92	0.00 100 336 AVERAGE																																																																																																							






Mode	54																																																																																																																																										
	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5648.00</td><td>64.78</td><td>68.20</td><td>-3.42</td><td>55.96</td><td>33.19</td><td>13.55</td><td>37.92</td><td>0.00</td><td>100</td><td>258</td><td>PEAK</td></tr><tr><td>2</td><td>5651.19</td><td>64.25</td><td>69.08</td><td>-4.83</td><td>55.40</td><td>33.21</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>258</td><td>PEAK</td></tr><tr><td>3</td><td>5710.20</td><td>87.85</td><td>108.06</td><td>-20.21</td><td>78.51</td><td>33.62</td><td>13.64</td><td>37.92</td><td>0.00</td><td>100</td><td>258</td><td>PEAK</td></tr><tr><td>4</td><td>5720.06</td><td>88.40</td><td>110.94</td><td>-22.54</td><td>79.03</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>258</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5648.00	64.78	68.20	-3.42	55.96	33.19	13.55	37.92	0.00	100	258	PEAK	2	5651.19	64.25	69.08	-4.83	55.40	33.21	13.56	37.92	0.00	100	258	PEAK	3	5710.20	87.85	108.06	-20.21	78.51	33.62	13.64	37.92	0.00	100	258	PEAK	4	5720.06	88.40	110.94	-22.54	79.03	33.64	13.65	37.92	0.00	100	258	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>114.15</td><td>-----</td><td>-----</td><td>104.71</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>100</td><td>258</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	114.15	-----	-----	104.71	33.68	13.68	37.92	0.00	100	258	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5648.00	64.78	68.20	-3.42	55.96	33.19	13.55	37.92	0.00	100	258	PEAK																																																																																																																															
2	5651.19	64.25	69.08	-4.83	55.40	33.21	13.56	37.92	0.00	100	258	PEAK																																																																																																																															
3	5710.20	87.85	108.06	-20.21	78.51	33.62	13.64	37.92	0.00	100	258	PEAK																																																																																																																															
4	5720.06	88.40	110.94	-22.54	79.03	33.64	13.65	37.92	0.00	100	258	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	114.15	-----	-----	104.71	33.68	13.68	37.92	0.00	100	258	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>107.08</td><td>-----</td><td>-----</td><td>97.64</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>100</td><td>258</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	107.08	-----	-----	97.64	33.68	13.68	37.92	0.00	100	258	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	107.08	-----	-----	97.64	33.68	13.68	37.92	0.00	100	258	AVERAGE																																																																																																																															






		54															
Mode		Harmonic															
		U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz															
ANT		6+7															
Pol.		Horizontal												Vertical			
Peak Avg.																	
	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 HORIZONTAL																
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			
		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg				
		1	11490.00	52.36	74.00	-21.64	35.25	39.20	19.46	42.47	0.92	322	335	PEAK			
		2	11490.00	45.41	54.00	-8.59	28.30	39.20	19.46	42.47	0.92	322	335	Average			
		3	17235.00	53.52	68.20	-14.68	33.56	39.57	24.06	44.61	0.94	--	--	PEAK			
																	
		Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 VERTICAL															
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			
		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg				
		1	11490.00	51.39	74.00	-22.61	34.28	39.20	19.46	42.47	0.92	274	285	PEAK			
		2	11490.00	45.40	54.00	-8.60	28.29	39.20	19.46	42.47	0.92	274	285	Average			
		3	17235.00	54.74	68.20	-13.46	34.78	39.57	24.06	44.61	0.94	--	--	PEAK			






Mode	55																																																																																																																																										
	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Partial_106/53RU_5745MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5647.42</td><td>66.10</td><td>68.20</td><td>-2.10</td><td>57.28</td><td>33.19</td><td>13.55</td><td>37.92</td><td>0.00</td><td>200</td><td>331</td><td>PEAK</td></tr><tr><td>2</td><td>5655.39</td><td>69.78</td><td>72.20</td><td>-2.42</td><td>60.90</td><td>33.24</td><td>13.56</td><td>37.92</td><td>0.00</td><td>200</td><td>331</td><td>PEAK</td></tr><tr><td>3</td><td>5709.91</td><td>87.60</td><td>107.98</td><td>-20.38</td><td>78.26</td><td>33.62</td><td>13.64</td><td>37.92</td><td>0.00</td><td>200</td><td>331</td><td>PEAK</td></tr><tr><td>4</td><td>5720.64</td><td>85.65</td><td>112.26</td><td>-26.61</td><td>76.28</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>200</td><td>331</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5647.42	66.10	68.20	-2.10	57.28	33.19	13.55	37.92	0.00	200	331	PEAK	2	5655.39	69.78	72.20	-2.42	60.90	33.24	13.56	37.92	0.00	200	331	PEAK	3	5709.91	87.60	107.98	-20.38	78.26	33.62	13.64	37.92	0.00	200	331	PEAK	4	5720.64	85.65	112.26	-26.61	76.28	33.64	13.65	37.92	0.00	200	331	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5745.00</td><td>109.92</td><td>-----</td><td>-----</td><td>100.48</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>200</td><td>331</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	109.92	-----	-----	100.48	33.68	13.68	37.92	0.00	200	331	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5647.42	66.10	68.20	-2.10	57.28	33.19	13.55	37.92	0.00	200	331	PEAK																																																																																																																															
2	5655.39	69.78	72.20	-2.42	60.90	33.24	13.56	37.92	0.00	200	331	PEAK																																																																																																																															
3	5709.91	87.60	107.98	-20.38	78.26	33.62	13.64	37.92	0.00	200	331	PEAK																																																																																																																															
4	5720.64	85.65	112.26	-26.61	76.28	33.64	13.65	37.92	0.00	200	331	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	109.92	-----	-----	100.48	33.68	13.68	37.92	0.00	200	331	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.120kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5745.00</td><td>103.32</td><td>-----</td><td>-----</td><td>93.88</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>200</td><td>331</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	103.32	-----	-----	93.88	33.68	13.68	37.92	0.00	200	331	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	103.32	-----	-----	93.88	33.68	13.68	37.92	0.00	200	331	AVERAGE																																																																																																																															




Mode	55																																																																																																																																								
	Band Edge																																																																																																																																								
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Partial_106/53RU_5745MHz																																																																																																																																								
ANT	6+7																																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																																		
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5649.45</td><td>66.76</td><td>68.20</td><td>-1.44</td><td>57.92</td><td>33.20</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>306</td><td>PEAK</td></tr><tr><td>2</td><td>5651.04</td><td>67.78</td><td>68.97</td><td>-1.19</td><td>58.93</td><td>33.21</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>306</td><td>PEAK</td></tr><tr><td>3</td><td>5704.69</td><td>87.80</td><td>106.51</td><td>-18.71</td><td>78.48</td><td>33.61</td><td>13.63</td><td>37.92</td><td>0.00</td><td>100</td><td>306</td><td>PEAK</td></tr><tr><td>4</td><td>5720.79</td><td>89.04</td><td>112.59</td><td>-23.55</td><td>79.67</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>306</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5649.45	66.76	68.20	-1.44	57.92	33.20	13.56	37.92	0.00	100	306	PEAK	2	5651.04	67.78	68.97	-1.19	58.93	33.21	13.56	37.92	0.00	100	306	PEAK	3	5704.69	87.80	106.51	-18.71	78.48	33.61	13.63	37.92	0.00	100	306	PEAK	4	5720.79	89.04	112.59	-23.55	79.67	33.64	13.65	37.92	0.00	100	306	PEAK	 Site : 03CH20-HY Condition: PEAK(UNI) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>113.29</td><td>-----</td><td>-----</td><td>103.83</td><td>33.69</td><td>13.69</td><td>37.92</td><td>0.00</td><td>100</td><td>306</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	113.29	-----	-----	103.83	33.69	13.69	37.92	0.00	100	306	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5649.45	66.76	68.20	-1.44	57.92	33.20	13.56	37.92	0.00	100	306	PEAK																																																																																																																													
2	5651.04	67.78	68.97	-1.19	58.93	33.21	13.56	37.92	0.00	100	306	PEAK																																																																																																																													
3	5704.69	87.80	106.51	-18.71	78.48	33.61	13.63	37.92	0.00	100	306	PEAK																																																																																																																													
4	5720.79	89.04	112.59	-23.55	79.67	33.64	13.65	37.92	0.00	100	306	PEAK																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5745.00	113.29	-----	-----	103.83	33.69	13.69	37.92	0.00	100	306	PEAK																																																																																																																													
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.120kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>107.74</td><td>-----</td><td>-----</td><td>98.30</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>100</td><td>306</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	107.74	-----	-----	98.30	33.68	13.68	37.92	0.00	100	306	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5745.00	107.74	-----	-----	98.30	33.68	13.68	37.92	0.00	100	306	AVERAGE																																																																																																																													



	56																																																																																																																																										
Mode	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5825MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5645.88</td><td>54.83</td><td>68.20</td><td>-13.37</td><td>46.02</td><td>33.18</td><td>13.55</td><td>37.92</td><td>0.00</td><td>100</td><td>331</td><td>PEAK</td></tr><tr><td>2</td><td>5652.17</td><td>56.90</td><td>69.81</td><td>-12.91</td><td>48.04</td><td>33.22</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>331</td><td>PEAK</td></tr><tr><td>3</td><td>5709.34</td><td>68.49</td><td>107.82</td><td>-39.33</td><td>59.15</td><td>33.62</td><td>13.64</td><td>37.92</td><td>0.00</td><td>100</td><td>331</td><td>PEAK</td></tr><tr><td>4</td><td>5720.44</td><td>69.76</td><td>111.79</td><td>-42.03</td><td>60.39</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>331</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5645.88	54.83	68.20	-13.37	46.02	33.18	13.55	37.92	0.00	100	331	PEAK	2	5652.17	56.90	69.81	-12.91	48.04	33.22	13.56	37.92	0.00	100	331	PEAK	3	5709.34	68.49	107.82	-39.33	59.15	33.62	13.64	37.92	0.00	100	331	PEAK	4	5720.44	69.76	111.79	-42.03	60.39	33.64	13.65	37.92	0.00	100	331	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>111.31</td><td>-----</td><td>-----</td><td>101.53</td><td>33.96</td><td>13.74</td><td>37.92</td><td>0.00</td><td>100</td><td>331</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	111.31	-----	-----	101.53	33.96	13.74	37.92	0.00	100	331	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5645.88	54.83	68.20	-13.37	46.02	33.18	13.55	37.92	0.00	100	331	PEAK																																																																																																																															
2	5652.17	56.90	69.81	-12.91	48.04	33.22	13.56	37.92	0.00	100	331	PEAK																																																																																																																															
3	5709.34	68.49	107.82	-39.33	59.15	33.62	13.64	37.92	0.00	100	331	PEAK																																																																																																																															
4	5720.44	69.76	111.79	-42.03	60.39	33.64	13.65	37.92	0.00	100	331	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	111.31	-----	-----	101.53	33.96	13.74	37.92	0.00	100	331	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>104.28</td><td>-----</td><td>-----</td><td>94.50</td><td>33.96</td><td>13.74</td><td>37.92</td><td>0.00</td><td>100</td><td>331</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	104.28	-----	-----	94.50	33.96	13.74	37.92	0.00	100	331	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	104.28	-----	-----	94.50	33.96	13.74	37.92	0.00	100	331	AVERAGE																																																																																																																															




	56																																																																																													
Mode	Band Edge - R																																																																																													
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5825MHz																																																																																													
ANT	6+7																																																																																													
Pol.	Horizontal						Fundamental																																																																																							
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.96</td><td>67.00</td><td>110.89</td><td>-43.89</td><td>56.77</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100</td><td>331</td><td>PEAK</td></tr><tr><td>2</td><td>5874.76</td><td>65.36</td><td>105.27</td><td>-39.91</td><td>55.10</td><td>34.30</td><td>13.88</td><td>37.92</td><td>0.00</td><td>100</td><td>331</td><td>PEAK</td></tr><tr><td>3</td><td>5923.27</td><td>52.25</td><td>69.47</td><td>-17.22</td><td>41.92</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100</td><td>331</td><td>PEAK</td></tr><tr><td>4</td><td>5934.00</td><td>54.47</td><td>68.20</td><td>-13.73</td><td>44.13</td><td>34.30</td><td>13.97</td><td>37.93</td><td>0.00</td><td>100</td><td>331</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	5854.96	67.00	110.89	-43.89	56.77	34.30	13.85	37.92	0.00	100	331	PEAK	2	5874.76	65.36	105.27	-39.91	55.10	34.30	13.88	37.92	0.00	100	331	PEAK	3	5923.27	52.25	69.47	-17.22	41.92	34.30	13.96	37.93	0.00	100	331	PEAK	4	5934.00	54.47	68.20	-13.73	44.13	34.30	13.97	37.93	0.00	100	331	PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																						
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																					
1	5854.96	67.00	110.89	-43.89	56.77	34.30	13.85	37.92	0.00	100	331	PEAK																																																																																		
2	5874.76	65.36	105.27	-39.91	55.10	34.30	13.88	37.92	0.00	100	331	PEAK																																																																																		
3	5923.27	52.25	69.47	-17.22	41.92	34.30	13.96	37.93	0.00	100	331	PEAK																																																																																		
4	5934.00	54.47	68.20	-13.73	44.13	34.30	13.97	37.93	0.00	100	331	PEAK																																																																																		





Mode	56																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5825MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5649.95</td><td>58.23</td><td>68.20</td><td>-9.97</td><td>49.39</td><td>33.20</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>257</td><td>PEAK</td></tr><tr><td>2</td><td>5652.17</td><td>60.74</td><td>69.81</td><td>-9.07</td><td>51.88</td><td>33.22</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>257</td><td>PEAK</td></tr><tr><td>3</td><td>5703.23</td><td>71.33</td><td>106.11</td><td>-34.78</td><td>62.01</td><td>33.61</td><td>13.63</td><td>37.92</td><td>0.00</td><td>100</td><td>257</td><td>PEAK</td></tr><tr><td>4</td><td>5720.44</td><td>73.98</td><td>111.79</td><td>-37.81</td><td>64.61</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>257</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5649.95	58.23	68.20	-9.97	49.39	33.20	13.56	37.92	0.00	100	257	PEAK	2	5652.17	60.74	69.81	-9.07	51.88	33.22	13.56	37.92	0.00	100	257	PEAK	3	5703.23	71.33	106.11	-34.78	62.01	33.61	13.63	37.92	0.00	100	257	PEAK	4	5720.44	73.98	111.79	-37.81	64.61	33.64	13.65	37.92	0.00	100	257	PEAK	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>114.00</td><td>-----</td><td>-----</td><td>104.30</td><td>33.96</td><td>13.74</td><td>37.92</td><td>0.00</td><td>100</td><td>257</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	114.00	-----	-----	104.30	33.96	13.74	37.92	0.00	100	257	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5649.95	58.23	68.20	-9.97	49.39	33.20	13.56	37.92	0.00	100	257	PEAK																																																																																																																															
2	5652.17	60.74	69.81	-9.07	51.88	33.22	13.56	37.92	0.00	100	257	PEAK																																																																																																																															
3	5703.23	71.33	106.11	-34.78	62.01	33.61	13.63	37.92	0.00	100	257	PEAK																																																																																																																															
4	5720.44	73.98	111.79	-37.81	64.61	33.64	13.65	37.92	0.00	100	257	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	114.00	-----	-----	104.30	33.96	13.74	37.92	0.00	100	257	PEAK																																																																																																																															
Avg.	Blank						Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>106.27</td><td>-----</td><td>-----</td><td>96.49</td><td>33.96</td><td>13.74</td><td>37.92</td><td>0.00</td><td>100</td><td>257</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	106.27	-----	-----	96.49	33.96	13.74	37.92	0.00	100	257	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	106.27	-----	-----	96.49	33.96	13.74	37.92	0.00	100	257	AVERAGE																																																																																																																															






	56																																																																							
Mode	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5825MHz																																																																							
ANT	6+7																																																																							
Pol.	Vertical	Fundamental																																																																						
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5854.63</td><td>71.75</td><td>111.64</td><td>-39.89</td><td>61.52</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00 100 257 PEAK</td></tr><tr><td>2</td><td>5868.41</td><td>74.95</td><td>109.28</td><td>-34.33</td><td>64.71</td><td>34.30</td><td>13.86</td><td>37.92</td><td>0.00 100 257 PEAK</td></tr><tr><td>3</td><td>5923.11</td><td>60.16</td><td>69.60</td><td>-9.44</td><td>49.83</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00 100 257 PEAK</td></tr><tr><td>4</td><td>5928.72</td><td>58.17</td><td>68.20</td><td>-10.03</td><td>47.83</td><td>34.30</td><td>13.97</td><td>37.93</td><td>0.00 100 257 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5854.63	71.75	111.64	-39.89	61.52	34.30	13.85	37.92	0.00 100 257 PEAK	2	5868.41	74.95	109.28	-34.33	64.71	34.30	13.86	37.92	0.00 100 257 PEAK	3	5923.11	60.16	69.60	-9.44	49.83	34.30	13.96	37.93	0.00 100 257 PEAK	4	5928.72	58.17	68.20	-10.03	47.83	34.30	13.97	37.93	0.00 100 257 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1	5854.63	71.75	111.64	-39.89	61.52	34.30	13.85	37.92	0.00 100 257 PEAK																																																															
2	5868.41	74.95	109.28	-34.33	64.71	34.30	13.86	37.92	0.00 100 257 PEAK																																																															
3	5923.11	60.16	69.60	-9.44	49.83	34.30	13.96	37.93	0.00 100 257 PEAK																																																															
4	5928.72	58.17	68.20	-10.03	47.83	34.30	13.97	37.93	0.00 100 257 PEAK																																																															






Mode	56																																																																																		
	Harmonic																																																																																		
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5825MHz																																																																																		
ANT	6+7																																																																																		
Pol.	Horizontal							Vertical																																																																											
Peak Avg.																																																																																			
	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 HORIZONTAL																																																																																		
<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11570.00</td><td>53.08</td><td>74.00</td><td>-20.92</td><td>36.34</td><td>38.82</td><td>19.53</td><td>42.53</td><td>0.92</td><td>100</td><td>281</td><td>Peak</td><td></td></tr><tr><td>2</td><td>11570.00</td><td>44.55</td><td>54.00</td><td>-9.45</td><td>27.81</td><td>38.82</td><td>19.53</td><td>42.53</td><td>0.92</td><td>100</td><td>281</td><td>Average</td><td></td></tr><tr><td>3</td><td>17355.00</td><td>54.34</td><td>68.20</td><td>-13.86</td><td>34.15</td><td>39.82</td><td>24.14</td><td>44.71</td><td>0.94</td><td>--</td><td>--</td><td>Peak</td><td></td></tr></table>															Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11570.00	53.08	74.00	-20.92	36.34	38.82	19.53	42.53	0.92	100	281	Peak		2	11570.00	44.55	54.00	-9.45	27.81	38.82	19.53	42.53	0.92	100	281	Average		3	17355.00	54.34	68.20	-13.86	34.15	39.82	24.14	44.71	0.94	--	--	Peak	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1	11570.00	53.08	74.00	-20.92	36.34	38.82	19.53	42.53	0.92	100	281	Peak																																																																							
2	11570.00	44.55	54.00	-9.45	27.81	38.82	19.53	42.53	0.92	100	281	Average																																																																							
3	17355.00	54.34	68.20	-13.86	34.15	39.82	24.14	44.71	0.94	--	--	Peak																																																																							
Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 VERTICAL																																																																																			
<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11570.00</td><td>50.81</td><td>74.00</td><td>-23.19</td><td>34.07</td><td>38.82</td><td>19.53</td><td>42.53</td><td>0.92</td><td>300</td><td>248</td><td>Peak</td><td></td></tr><tr><td>2</td><td>11570.00</td><td>44.27</td><td>54.00</td><td>-9.73</td><td>27.53</td><td>38.82</td><td>19.53</td><td>42.53</td><td>0.92</td><td>300</td><td>248</td><td>Average</td><td></td></tr><tr><td>3</td><td>17355.00</td><td>53.31</td><td>68.20</td><td>-14.89</td><td>33.12</td><td>39.82</td><td>24.14</td><td>44.71</td><td>0.94</td><td>--</td><td>--</td><td>Peak</td><td></td></tr></table>															Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11570.00	50.81	74.00	-23.19	34.07	38.82	19.53	42.53	0.92	300	248	Peak		2	11570.00	44.27	54.00	-9.73	27.53	38.82	19.53	42.53	0.92	300	248	Average		3	17355.00	53.31	68.20	-14.89	33.12	39.82	24.14	44.71	0.94	--	--	Peak	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1	11570.00	50.81	74.00	-23.19	34.07	38.82	19.53	42.53	0.92	300	248	Peak																																																																							
2	11570.00	44.27	54.00	-9.73	27.53	38.82	19.53	42.53	0.92	300	248	Average																																																																							
3	17355.00	53.31	68.20	-14.89	33.12	39.82	24.14	44.71	0.94	--	--	Peak																																																																							





	57																																																																																																															
Mode	Band Edge																																																																																																															
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz																																																																																																															
ANT	6+7																																																																																																															
Pol.	Horizontal	Fundamental																																																																																																														
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5854.00</td><td>83.29</td><td>113.08</td><td>-29.79</td><td>73.06</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100 195 PEAK</td></tr><tr><td>2 5858.75</td><td>83.45</td><td>109.75</td><td>-26.30</td><td>73.22</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100 195 PEAK</td></tr><tr><td>3 5925.00</td><td>59.00</td><td>68.20</td><td>-9.20</td><td>48.67</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100 195 PEAK</td></tr><tr><td>4 5925.75</td><td>59.17</td><td>68.20</td><td>-9.03</td><td>48.84</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100 195 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5854.00	83.29	113.08	-29.79	73.06	34.30	13.85	37.92	0.00	100 195 PEAK	2 5858.75	83.45	109.75	-26.30	73.22	34.30	13.85	37.92	0.00	100 195 PEAK	3 5925.00	59.00	68.20	-9.20	48.67	34.30	13.96	37.93	0.00	100 195 PEAK	4 5925.75	59.17	68.20	-9.03	48.84	34.30	13.96	37.93	0.00	100 195 PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5825.00</td><td>117.73</td><td>-----</td><td>-----</td><td>107.65</td><td>34.20</td><td>13.80</td><td>37.92</td><td>0.00</td><td>100 195 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5825.00	117.73	-----	-----	107.65	34.20	13.80	37.92	0.00	100 195 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1 5854.00	83.29	113.08	-29.79	73.06	34.30	13.85	37.92	0.00	100 195 PEAK																																																																																																							
2 5858.75	83.45	109.75	-26.30	73.22	34.30	13.85	37.92	0.00	100 195 PEAK																																																																																																							
3 5925.00	59.00	68.20	-9.20	48.67	34.30	13.96	37.93	0.00	100 195 PEAK																																																																																																							
4 5925.75	59.17	68.20	-9.03	48.84	34.30	13.96	37.93	0.00	100 195 PEAK																																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1 5825.00	117.73	-----	-----	107.65	34.20	13.80	37.92	0.00	100 195 PEAK																																																																																																							
Avg.	Blank	 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5825.00</td><td>109.79</td><td>-----</td><td>-----</td><td>99.71</td><td>34.20</td><td>13.80</td><td>37.92</td><td>0.00</td><td>100 195 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5825.00	109.79	-----	-----	99.71	34.20	13.80	37.92	0.00	100 195 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1 5825.00	109.79	-----	-----	99.71	34.20	13.80	37.92	0.00	100 195 AVERAGE																																																																																																							






	57																																																																																																																																										
Mode	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5854.25</td><td>84.04</td><td>112.51</td><td>-28.47</td><td>73.81</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100</td><td>299</td><td>PEAK</td></tr><tr><td>2</td><td>5863.00</td><td>81.76</td><td>108.56</td><td>-26.80</td><td>71.52</td><td>34.30</td><td>13.86</td><td>37.92</td><td>0.00</td><td>100</td><td>299</td><td>PEAK</td></tr><tr><td>3</td><td>5923.63</td><td>62.79</td><td>69.21</td><td>-6.42</td><td>52.46</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100</td><td>299</td><td>PEAK</td></tr><tr><td>4</td><td>5925.63</td><td>62.04</td><td>68.20</td><td>-6.16</td><td>51.71</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100</td><td>299</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.25	84.04	112.51	-28.47	73.81	34.30	13.85	37.92	0.00	100	299	PEAK	2	5863.00	81.76	108.56	-26.80	71.52	34.30	13.86	37.92	0.00	100	299	PEAK	3	5923.63	62.79	69.21	-6.42	52.46	34.30	13.96	37.93	0.00	100	299	PEAK	4	5925.63	62.04	68.20	-6.16	51.71	34.30	13.96	37.93	0.00	100	299	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>114.27</td><td>-----</td><td>-----</td><td>104.19</td><td>34.20</td><td>13.80</td><td>37.92</td><td>0.00</td><td>100</td><td>299</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	114.27	-----	-----	104.19	34.20	13.80	37.92	0.00	100	299	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5854.25	84.04	112.51	-28.47	73.81	34.30	13.85	37.92	0.00	100	299	PEAK																																																																																																																															
2	5863.00	81.76	108.56	-26.80	71.52	34.30	13.86	37.92	0.00	100	299	PEAK																																																																																																																															
3	5923.63	62.79	69.21	-6.42	52.46	34.30	13.96	37.93	0.00	100	299	PEAK																																																																																																																															
4	5925.63	62.04	68.20	-6.16	51.71	34.30	13.96	37.93	0.00	100	299	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	114.27	-----	-----	104.19	34.20	13.80	37.92	0.00	100	299	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>107.13</td><td>-----</td><td>-----</td><td>97.05</td><td>34.20</td><td>13.80</td><td>37.92</td><td>0.00</td><td>100</td><td>299</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	107.13	-----	-----	97.05	34.20	13.80	37.92	0.00	100	299	AVERAGE																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	107.13	-----	-----	97.05	34.20	13.80	37.92	0.00	100	299	AVERAGE																																																																																																																															



Mode	57																																																																																																																																													
	Harmonic																																																																																																																																													
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz																																																																																																																																													
ANT	6+7																																																																																																																																													
Pol.	Horizontal	Vertical																																																																																																																																												
Peak Avg.	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11650.00</td><td>51.85</td><td>74.00</td><td>-22.15</td><td>35.22</td><td>38.70</td><td>19.60</td><td>42.60</td><td>0.93</td><td>100</td><td>277</td><td>PEAK</td><td></td></tr><tr><td>2</td><td>11650.00</td><td>43.83</td><td>54.00</td><td>-10.17</td><td>27.20</td><td>38.70</td><td>19.60</td><td>42.60</td><td>0.93</td><td>100</td><td>277</td><td>Average</td><td></td></tr><tr><td>3</td><td>17475.00</td><td>54.73</td><td>68.20</td><td>-13.47</td><td>34.28</td><td>40.10</td><td>24.22</td><td>44.81</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11650.00	51.85	74.00	-22.15	35.22	38.70	19.60	42.60	0.93	100	277	PEAK		2	11650.00	43.83	54.00	-10.17	27.20	38.70	19.60	42.60	0.93	100	277	Average		3	17475.00	54.73	68.20	-13.47	34.28	40.10	24.22	44.81	0.94	--	--	PEAK		 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11650.00</td><td>51.54</td><td>74.00</td><td>-22.46</td><td>34.91</td><td>38.70</td><td>19.60</td><td>42.60</td><td>0.93</td><td>211</td><td>32</td><td>PEAK</td><td></td></tr><tr><td>2</td><td>11650.00</td><td>43.80</td><td>54.00</td><td>-10.20</td><td>27.17</td><td>38.70</td><td>19.60</td><td>42.60</td><td>0.93</td><td>211</td><td>32</td><td>Average</td><td></td></tr><tr><td>3</td><td>17475.00</td><td>55.01</td><td>68.20</td><td>-13.19</td><td>34.56</td><td>40.10</td><td>24.22</td><td>44.81</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11650.00	51.54	74.00	-22.46	34.91	38.70	19.60	42.60	0.93	211	32	PEAK		2	11650.00	43.80	54.00	-10.20	27.17	38.70	19.60	42.60	0.93	211	32	Average		3	17475.00	55.01	68.20	-13.19	34.56	40.10	24.22	44.81	0.94	--	--	PEAK	
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																		
1	11650.00	51.85	74.00	-22.15	35.22	38.70	19.60	42.60	0.93	100	277	PEAK																																																																																																																																		
2	11650.00	43.83	54.00	-10.17	27.20	38.70	19.60	42.60	0.93	100	277	Average																																																																																																																																		
3	17475.00	54.73	68.20	-13.47	34.28	40.10	24.22	44.81	0.94	--	--	PEAK																																																																																																																																		
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																		
1	11650.00	51.54	74.00	-22.46	34.91	38.70	19.60	42.60	0.93	211	32	PEAK																																																																																																																																		
2	11650.00	43.80	54.00	-10.20	27.17	38.70	19.60	42.60	0.93	211	32	Average																																																																																																																																		
3	17475.00	55.01	68.20	-13.19	34.56	40.10	24.22	44.81	0.94	--	--	PEAK																																																																																																																																		






Mode	58																																																																																																																							
	Band Edge																																																																																																																							
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Partial_106/54RU_5825MHz																																																																																																																							
ANT	6+7																																																																																																																							
Pol.	Horizontal					Fundamental																																																																																																																		
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5854.88</td><td>85.24</td><td>111.08</td><td>-25.84</td><td>75.01</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>206 303 PEAK</td></tr><tr><td>2 5865.63</td><td>85.03</td><td>107.82</td><td>-22.79</td><td>74.79</td><td>34.30</td><td>13.86</td><td>37.92</td><td>0.00</td><td>206 303 PEAK</td></tr><tr><td>3 5922.38</td><td>67.03</td><td>70.13</td><td>-3.10</td><td>56.70</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>206 303 PEAK</td></tr><tr><td>4 5935.00</td><td>66.05</td><td>68.20</td><td>-2.15</td><td>55.70</td><td>34.30</td><td>13.98</td><td>37.93</td><td>0.00</td><td>206 303 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5854.88	85.24	111.08	-25.84	75.01	34.30	13.85	37.92	0.00	206 303 PEAK	2 5865.63	85.03	107.82	-22.79	74.79	34.30	13.86	37.92	0.00	206 303 PEAK	3 5922.38	67.03	70.13	-3.10	56.70	34.30	13.96	37.93	0.00	206 303 PEAK	4 5935.00	66.05	68.20	-2.15	55.70	34.30	13.98	37.93	0.00	206 303 PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5825.00</td><td>115.00</td><td>-----</td><td>-----</td><td>105.69</td><td>34.22</td><td>13.81</td><td>37.92</td><td>0.00</td><td>206 303 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5825.00	115.00	-----	-----	105.69	34.22	13.81	37.92	0.00	206 303 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																															
1 5854.88	85.24	111.08	-25.84	75.01	34.30	13.85	37.92	0.00	206 303 PEAK																																																																																																															
2 5865.63	85.03	107.82	-22.79	74.79	34.30	13.86	37.92	0.00	206 303 PEAK																																																																																																															
3 5922.38	67.03	70.13	-3.10	56.70	34.30	13.96	37.93	0.00	206 303 PEAK																																																																																																															
4 5935.00	66.05	68.20	-2.15	55.70	34.30	13.98	37.93	0.00	206 303 PEAK																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																															
1 5825.00	115.00	-----	-----	105.69	34.22	13.81	37.92	0.00	206 303 PEAK																																																																																																															
Avg.	Blank					 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.120kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5825.00</td><td>109.72</td><td>-----</td><td>-----</td><td>99.61</td><td>34.22</td><td>13.81</td><td>37.92</td><td>0.00</td><td>206 303 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5825.00	109.72	-----	-----	99.61	34.22	13.81	37.92	0.00	206 303 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																															
1 5825.00	109.72	-----	-----	99.61	34.22	13.81	37.92	0.00	206 303 AVERAGE																																																																																																															




	58																																																																																																																																	
Mode	Band Edge																																																																																																																																	
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Partial_106/54RU_5825MHz																																																																																																																																	
ANT	6+7																																																																																																																																	
Pol.	Vertical						Fundamental																																																																																																																											
Peak	Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.63</td><td>86.42</td><td>111.65</td><td>-25.23</td><td>76.19</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>160</td><td>360</td><td>PEAK</td></tr><tr><td>2</td><td>5869.00</td><td>81.87</td><td>106.88</td><td>-25.01</td><td>71.62</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>160</td><td>360</td><td>PEAK</td></tr><tr><td>3</td><td>5924.88</td><td>58.53</td><td>68.29</td><td>-9.76</td><td>48.20</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>160</td><td>360</td><td>PEAK</td></tr><tr><td>4</td><td>5926.75</td><td>60.23</td><td>68.20</td><td>-7.97</td><td>49.90</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>160</td><td>360</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5854.63	86.42	111.65	-25.23	76.19	34.30	13.85	37.92	0.00	160	360	PEAK	2	5869.00	81.87	106.88	-25.01	71.62	34.30	13.87	37.92	0.00	160	360	PEAK	3	5924.88	58.53	68.29	-9.76	48.20	34.30	13.96	37.93	0.00	160	360	PEAK	4	5926.75	60.23	68.20	-7.97	49.90	34.30	13.96	37.93	0.00	160	360	PEAK	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>113.90</td><td>-----</td><td>-----</td><td>103.79</td><td>34.22</td><td>13.81</td><td>37.92</td><td>0.00</td><td>160</td><td>360</td><td>PEAK</td></tr></table>								Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5825.00	113.90	-----	-----	103.79	34.22	13.81	37.92	0.00	160	360	PEAK
		Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																						
1	5854.63	86.42	111.65	-25.23	76.19	34.30	13.85	37.92	0.00	160	360	PEAK																																																																																																																						
2	5869.00	81.87	106.88	-25.01	71.62	34.30	13.87	37.92	0.00	160	360	PEAK																																																																																																																						
3	5924.88	58.53	68.29	-9.76	48.20	34.30	13.96	37.93	0.00	160	360	PEAK																																																																																																																						
4	5926.75	60.23	68.20	-7.97	49.90	34.30	13.96	37.93	0.00	160	360	PEAK																																																																																																																						
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																						
1	5825.00	113.90	-----	-----	103.79	34.22	13.81	37.92	0.00	160	360	PEAK																																																																																																																						
Avg.	Blank						Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.120kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>106.93</td><td>-----</td><td>-----</td><td>96.79</td><td>34.24</td><td>13.82</td><td>37.92</td><td>0.00</td><td>160</td><td>360</td><td>AVERAGE</td></tr></table>								Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5825.00	106.93	-----	-----	96.79	34.24	13.82	37.92	0.00	160	360	AVERAGE																																																																														
		Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																						
1	5825.00	106.93	-----	-----	96.79	34.24	13.82	37.92	0.00	160	360	AVERAGE																																																																																																																						






Mode	59																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5626.20</td><td>58.30</td><td>68.20</td><td>-9.90</td><td>49.59</td><td>33.10</td><td>13.53</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr><tr><td>2</td><td>5652.55</td><td>59.75</td><td>70.09</td><td>-10.34</td><td>50.89</td><td>33.22</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr><tr><td>3</td><td>5713.46</td><td>74.04</td><td>108.97</td><td>-34.93</td><td>64.69</td><td>33.63</td><td>13.64</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr><tr><td>4</td><td>5722.45</td><td>78.12</td><td>116.39</td><td>-38.27</td><td>68.74</td><td>33.64</td><td>13.66</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5626.20	58.30	68.20	-9.90	49.59	33.10	13.53	37.92	0.00	100	335	PEAK	2	5652.55	59.75	70.09	-10.34	50.89	33.22	13.56	37.92	0.00	100	335	PEAK	3	5713.46	74.04	108.97	-34.93	64.69	33.63	13.64	37.92	0.00	100	335	PEAK	4	5722.45	78.12	116.39	-38.27	68.74	33.64	13.66	37.92	0.00	100	335	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>105.92</td><td>-----</td><td>-----</td><td>96.42</td><td>33.72</td><td>13.70</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	105.92	-----	-----	96.42	33.72	13.70	37.92	0.00	100	335	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5626.20	58.30	68.20	-9.90	49.59	33.10	13.53	37.92	0.00	100	335	PEAK																																																																																																																															
2	5652.55	59.75	70.09	-10.34	50.89	33.22	13.56	37.92	0.00	100	335	PEAK																																																																																																																															
3	5713.46	74.04	108.97	-34.93	64.69	33.63	13.64	37.92	0.00	100	335	PEAK																																																																																																																															
4	5722.45	78.12	116.39	-38.27	68.74	33.64	13.66	37.92	0.00	100	335	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5755.00	105.92	-----	-----	96.42	33.72	13.70	37.92	0.00	100	335	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>98.62</td><td>-----</td><td>-----</td><td>89.12</td><td>33.72</td><td>13.70</td><td>37.92</td><td>0.00</td><td>100</td><td>335</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	98.62	-----	-----	89.12	33.72	13.70	37.92	0.00	100	335	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5755.00	98.62	-----	-----	89.12	33.72	13.70	37.92	0.00	100	335	AVERAGE																																																																																																																															




Mode	59																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																							
ANT	6+7																																																																							
Pol.	Horizontal	Fundamental																																																																						
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5854.84</td><td>53.41</td><td>111.17</td><td>-57.76</td><td>43.18</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00 100 335 PEAK</td></tr><tr><td>2</td><td>5872.59</td><td>56.91</td><td>105.88</td><td>-48.97</td><td>46.65</td><td>34.30</td><td>13.88</td><td>37.92</td><td>0.00 100 335 PEAK</td></tr><tr><td>3</td><td>5924.85</td><td>49.60</td><td>68.31</td><td>-18.71</td><td>39.27</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00 100 335 PEAK</td></tr><tr><td>4</td><td>5927.19</td><td>50.67</td><td>68.20</td><td>-17.53</td><td>40.34</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00 100 335 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5854.84	53.41	111.17	-57.76	43.18	34.30	13.85	37.92	0.00 100 335 PEAK	2	5872.59	56.91	105.88	-48.97	46.65	34.30	13.88	37.92	0.00 100 335 PEAK	3	5924.85	49.60	68.31	-18.71	39.27	34.30	13.96	37.93	0.00 100 335 PEAK	4	5927.19	50.67	68.20	-17.53	40.34	34.30	13.96	37.93	0.00 100 335 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1	5854.84	53.41	111.17	-57.76	43.18	34.30	13.85	37.92	0.00 100 335 PEAK																																																															
2	5872.59	56.91	105.88	-48.97	46.65	34.30	13.88	37.92	0.00 100 335 PEAK																																																															
3	5924.85	49.60	68.31	-18.71	39.27	34.30	13.96	37.93	0.00 100 335 PEAK																																																															
4	5927.19	50.67	68.20	-17.53	40.34	34.30	13.96	37.93	0.00 100 335 PEAK																																																															





	59																																																																																																																																								
Mode	Band Edge - L																																																																																																																																								
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																																																																								
ANT	6+7																																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																																		
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5641.23</td><td>59.16</td><td>68.20</td><td>-9.04</td><td>50.37</td><td>33.16</td><td>13.55</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>2</td><td>5653.17</td><td>62.86</td><td>70.55</td><td>-7.69</td><td>53.99</td><td>33.23</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>3</td><td>5719.35</td><td>80.78</td><td>110.62</td><td>-29.84</td><td>71.41</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>4</td><td>5720.75</td><td>79.76</td><td>112.50</td><td>-32.74</td><td>70.39</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5641.23	59.16	68.20	-9.04	50.37	33.16	13.55	37.92	0.00	100	301	PEAK	2	5653.17	62.86	70.55	-7.69	53.99	33.23	13.56	37.92	0.00	100	301	PEAK	3	5719.35	80.78	110.62	-29.84	71.41	33.64	13.65	37.92	0.00	100	301	PEAK	4	5720.75	79.76	112.50	-32.74	70.39	33.64	13.65	37.92	0.00	100	301	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>109.46</td><td>-----</td><td>-----</td><td>99.96</td><td>33.72</td><td>13.70</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	109.46	-----	-----	99.96	33.72	13.70	37.92	0.00	100	301	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5641.23	59.16	68.20	-9.04	50.37	33.16	13.55	37.92	0.00	100	301	PEAK																																																																																																																													
2	5653.17	62.86	70.55	-7.69	53.99	33.23	13.56	37.92	0.00	100	301	PEAK																																																																																																																													
3	5719.35	80.78	110.62	-29.84	71.41	33.64	13.65	37.92	0.00	100	301	PEAK																																																																																																																													
4	5720.75	79.76	112.50	-32.74	70.39	33.64	13.65	37.92	0.00	100	301	PEAK																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5755.00	109.46	-----	-----	99.96	33.72	13.70	37.92	0.00	100	301	PEAK																																																																																																																													
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>102.68</td><td>-----</td><td>-----</td><td>93.00</td><td>33.81</td><td>13.71</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	102.68	-----	-----	93.00	33.81	13.71	37.92	0.00	100	301	AVERAGE																																																																																		
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5755.00	102.68	-----	-----	93.00	33.81	13.71	37.92	0.00	100	301	AVERAGE																																																																																																																													






Mode	59																																																																																			
	Band Edge - R																																																																																			
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																			
ANT	6+7																																																																																			
Pol.	Vertical	Fundamental																																																																																		
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.06</td><td>61.41</td><td>112.94</td><td>-51.53</td><td>51.18</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>2</td><td>5878.64</td><td>61.61</td><td>106.42</td><td>-44.81</td><td>51.36</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>3</td><td>5924.85</td><td>58.22</td><td>68.31</td><td>-10.09</td><td>47.89</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>4</td><td>5929.72</td><td>57.40</td><td>68.20</td><td>-10.80</td><td>47.06</td><td>34.30</td><td>13.97</td><td>37.93</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.06	61.41	112.94	-51.53	51.18	34.30	13.85	37.92	0.00	100	301	PEAK	2	5878.64	61.61	106.42	-44.81	51.36	34.30	13.87	37.92	0.00	100	301	PEAK	3	5924.85	58.22	68.31	-10.09	47.89	34.30	13.96	37.93	0.00	100	301	PEAK	4	5929.72	57.40	68.20	-10.80	47.06	34.30	13.97	37.93	0.00	100	301	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.06	61.41	112.94	-51.53	51.18	34.30	13.85	37.92	0.00	100	301	PEAK																																																																								
2	5878.64	61.61	106.42	-44.81	51.36	34.30	13.87	37.92	0.00	100	301	PEAK																																																																								
3	5924.85	58.22	68.31	-10.09	47.89	34.30	13.96	37.93	0.00	100	301	PEAK																																																																								
4	5929.72	57.40	68.20	-10.80	47.06	34.30	13.97	37.93	0.00	100	301	PEAK																																																																								




	59																																																																																		
Mode	Harmonic																																																																																		
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																		
ANT	6+7																																																																																		
Pol.	Horizontal							Vertical																																																																											
Peak Avg.																																																																																			
	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 HORIZONTAL																																																																																		
<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11510.00</td><td>51.62</td><td>74.00</td><td>-22.38</td><td></td><td>34.57</td><td>39.14</td><td>19.48</td><td>42.49</td><td>0.92</td><td>300</td><td>290</td><td>PEAK</td></tr><tr><td>2</td><td>11510.00</td><td>41.35</td><td>54.00</td><td>-12.65</td><td></td><td>24.30</td><td>39.14</td><td>19.48</td><td>42.49</td><td>0.92</td><td>300</td><td>290</td><td>Average</td></tr><tr><td>3</td><td>17265.00</td><td>54.78</td><td>68.20</td><td>-13.42</td><td></td><td>34.79</td><td>39.60</td><td>24.08</td><td>44.63</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11510.00	51.62	74.00	-22.38		34.57	39.14	19.48	42.49	0.92	300	290	PEAK	2	11510.00	41.35	54.00	-12.65		24.30	39.14	19.48	42.49	0.92	300	290	Average	3	17265.00	54.78	68.20	-13.42		34.79	39.60	24.08	44.63	0.94	--	--	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1	11510.00	51.62	74.00	-22.38		34.57	39.14	19.48	42.49	0.92	300	290	PEAK																																																																						
2	11510.00	41.35	54.00	-12.65		24.30	39.14	19.48	42.49	0.92	300	290	Average																																																																						
3	17265.00	54.78	68.20	-13.42		34.79	39.60	24.08	44.63	0.94	--	--	PEAK																																																																						
Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 VERTICAL																																																																																			
<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11510.00</td><td>51.51</td><td>74.00</td><td>-22.49</td><td></td><td>34.46</td><td>39.14</td><td>19.48</td><td>42.49</td><td>0.92</td><td>300</td><td>263</td><td>PEAK</td></tr><tr><td>2</td><td>11510.00</td><td>41.28</td><td>54.00</td><td>-12.72</td><td></td><td>24.23</td><td>39.14</td><td>19.48</td><td>42.49</td><td>0.92</td><td>300</td><td>263</td><td>Average</td></tr><tr><td>3</td><td>17265.00</td><td>54.47</td><td>68.20</td><td>-13.73</td><td></td><td>34.48</td><td>39.60</td><td>24.08</td><td>44.63</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11510.00	51.51	74.00	-22.49		34.46	39.14	19.48	42.49	0.92	300	263	PEAK	2	11510.00	41.28	54.00	-12.72		24.23	39.14	19.48	42.49	0.92	300	263	Average	3	17265.00	54.47	68.20	-13.73		34.48	39.60	24.08	44.63	0.94	--	--	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1	11510.00	51.51	74.00	-22.49		34.46	39.14	19.48	42.49	0.92	300	263	PEAK																																																																						
2	11510.00	41.28	54.00	-12.72		24.23	39.14	19.48	42.49	0.92	300	263	Average																																																																						
3	17265.00	54.47	68.20	-13.73		34.48	39.60	24.08	44.63	0.94	--	--	PEAK																																																																						






Mode	60																																																																																																																								
	Band Edge - L																																																																																																																								
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Partial_242/61RU_5755MHz																																																																																																																								
ANT	6+7																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																		
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5642.32</td><td>64.72</td><td>68.20</td><td>-3.48</td><td>55.92</td><td>33.17</td><td>13.55</td><td>37.92</td><td>0.00 209 306 PEAK</td></tr><tr><td>2</td><td>5656.42</td><td>67.68</td><td>72.97</td><td>-5.29</td><td>58.78</td><td>33.25</td><td>13.57</td><td>37.92</td><td>0.00 209 306 PEAK</td></tr><tr><td>3</td><td>5717.96</td><td>85.33</td><td>110.23</td><td>-24.90</td><td>75.96</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00 209 306 PEAK</td></tr><tr><td>4</td><td>5722.30</td><td>81.89</td><td>116.03</td><td>-34.14</td><td>72.51</td><td>33.64</td><td>13.66</td><td>37.92</td><td>0.00 209 306 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5642.32	64.72	68.20	-3.48	55.92	33.17	13.55	37.92	0.00 209 306 PEAK	2	5656.42	67.68	72.97	-5.29	58.78	33.25	13.57	37.92	0.00 209 306 PEAK	3	5717.96	85.33	110.23	-24.90	75.96	33.64	13.65	37.92	0.00 209 306 PEAK	4	5722.30	81.89	116.03	-34.14	72.51	33.64	13.66	37.92	0.00 209 306 PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5755.00</td><td>110.76</td><td>-----</td><td>-----</td><td>101.32</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00 209 306 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5755.00	110.76	-----	-----	101.32	33.68	13.68	37.92	0.00 209 306 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																
1	5642.32	64.72	68.20	-3.48	55.92	33.17	13.55	37.92	0.00 209 306 PEAK																																																																																																																
2	5656.42	67.68	72.97	-5.29	58.78	33.25	13.57	37.92	0.00 209 306 PEAK																																																																																																																
3	5717.96	85.33	110.23	-24.90	75.96	33.64	13.65	37.92	0.00 209 306 PEAK																																																																																																																
4	5722.30	81.89	116.03	-34.14	72.51	33.64	13.66	37.92	0.00 209 306 PEAK																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																
1	5755.00	110.76	-----	-----	101.32	33.68	13.68	37.92	0.00 209 306 PEAK																																																																																																																
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5755.00</td><td>103.64</td><td>-----</td><td>-----</td><td>94.20</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00 209 306 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5755.00	103.64	-----	-----	94.20	33.68	13.68	37.92	0.00 209 306 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																
1	5755.00	103.64	-----	-----	94.20	33.68	13.68	37.92	0.00 209 306 AVERAGE																																																																																																																




Mode	60																																																																																														
	Band Edge - R																																																																																														
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Partial_242/61RU_5755MHz																																																																																														
ANT	6+7																																																																																														
Pol.	Horizontal						Fundamental																																																																																								
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.06</td><td>58.95</td><td>112.94</td><td>-53.99</td><td>48.72</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>209</td><td>306</td><td>PEAK</td></tr><tr><td>2</td><td>5866.93</td><td>68.61</td><td>107.46</td><td>-38.85</td><td>58.36</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>209</td><td>306</td><td>PEAK</td></tr><tr><td>3</td><td>5917.83</td><td>64.92</td><td>73.49</td><td>-8.57</td><td>54.60</td><td>34.30</td><td>13.95</td><td>37.93</td><td>0.00</td><td>209</td><td>306</td><td>PEAK</td></tr><tr><td>4</td><td>5937.52</td><td>61.26</td><td>68.20</td><td>-6.94</td><td>50.91</td><td>34.30</td><td>13.98</td><td>37.93</td><td>0.00</td><td>209</td><td>306</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5854.06	58.95	112.94	-53.99	48.72	34.30	13.85	37.92	0.00	209	306	PEAK	2	5866.93	68.61	107.46	-38.85	58.36	34.30	13.87	37.92	0.00	209	306	PEAK	3	5917.83	64.92	73.49	-8.57	54.60	34.30	13.95	37.93	0.00	209	306	PEAK	4	5937.52	61.26	68.20	-6.94	50.91	34.30	13.98	37.93	0.00	209	306	PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																					
1	5854.06	58.95	112.94	-53.99	48.72	34.30	13.85	37.92	0.00	209	306	PEAK																																																																																			
2	5866.93	68.61	107.46	-38.85	58.36	34.30	13.87	37.92	0.00	209	306	PEAK																																																																																			
3	5917.83	64.92	73.49	-8.57	54.60	34.30	13.95	37.93	0.00	209	306	PEAK																																																																																			
4	5937.52	61.26	68.20	-6.94	50.91	34.30	13.98	37.93	0.00	209	306	PEAK																																																																																			






Mode	60																																																																																																																																													
	Band Edge - L																																																																																																																																													
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Partial_242/61RU_5755MHz																																																																																																																																													
ANT	6+7																																																																																																																																													
Pol.	Vertical						Fundamental																																																																																																																																							
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5628.06</td><td>63.91</td><td>68.20</td><td>-4.29</td><td>55.19</td><td>33.11</td><td>13.53</td><td>37.92</td><td>0.00</td><td>178</td><td>22</td><td>PEAK</td></tr><tr><td>2</td><td>5658.22</td><td>63.38</td><td>68.36</td><td>-4.98</td><td>54.54</td><td>33.20</td><td>13.56</td><td>37.92</td><td>0.00</td><td>178</td><td>22</td><td>PEAK</td></tr><tr><td>3</td><td>5717.65</td><td>86.50</td><td>110.14</td><td>-23.64</td><td>77.13</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>178</td><td>22</td><td>PEAK</td></tr><tr><td>4</td><td>5728.75</td><td>80.63</td><td>112.50</td><td>-31.87</td><td>71.26</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>178</td><td>22</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5628.06	63.91	68.20	-4.29	55.19	33.11	13.53	37.92	0.00	178	22	PEAK	2	5658.22	63.38	68.36	-4.98	54.54	33.20	13.56	37.92	0.00	178	22	PEAK	3	5717.65	86.50	110.14	-23.64	77.13	33.64	13.65	37.92	0.00	178	22	PEAK	4	5728.75	80.63	112.50	-31.87	71.26	33.64	13.65	37.92	0.00	178	22	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>109.88</td><td>-----</td><td>-----</td><td>100.44</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>178</td><td>22</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5755.00	109.88	-----	-----	100.44	33.68	13.68	37.92	0.00	178	22	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																				
1	5628.06	63.91	68.20	-4.29	55.19	33.11	13.53	37.92	0.00	178	22	PEAK																																																																																																																																		
2	5658.22	63.38	68.36	-4.98	54.54	33.20	13.56	37.92	0.00	178	22	PEAK																																																																																																																																		
3	5717.65	86.50	110.14	-23.64	77.13	33.64	13.65	37.92	0.00	178	22	PEAK																																																																																																																																		
4	5728.75	80.63	112.50	-31.87	71.26	33.64	13.65	37.92	0.00	178	22	PEAK																																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																				
1	5755.00	109.88	-----	-----	100.44	33.68	13.68	37.92	0.00	178	22	PEAK																																																																																																																																		
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>103.69</td><td>-----</td><td>-----</td><td>94.25</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>178</td><td>22</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5755.00	103.69	-----	-----	94.25	33.68	13.68	37.92	0.00	178	22	AVERAGE																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																				
1	5755.00	103.69	-----	-----	94.25	33.68	13.68	37.92	0.00	178	22	AVERAGE																																																																																																																																		




Mode	60																																																																																												
	Band Edge - R																																																																																												
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Partial_242/61RU_5755MHz																																																																																												
ANT	6+7																																																																																												
Pol.	Vertical						Fundamental																																																																																						
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.65</td><td>59.26</td><td>111.61</td><td>-52.35</td><td>49.03</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>178</td><td>22</td><td>PEAK</td></tr><tr><td>2</td><td>5868.10</td><td>64.12</td><td>107.13</td><td>-43.01</td><td>53.87</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>178</td><td>22</td><td>PEAK</td></tr><tr><td>3</td><td>5922.51</td><td>53.90</td><td>70.04</td><td>-16.14</td><td>43.57</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>178</td><td>22</td><td>PEAK</td></tr><tr><td>4</td><td>5930.70</td><td>52.23</td><td>68.20</td><td>-15.97</td><td>41.89</td><td>34.30</td><td>13.97</td><td>37.93</td><td>0.00</td><td>178</td><td>22</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5854.65	59.26	111.61	-52.35	49.03	34.30	13.85	37.92	0.00	178	22	PEAK	2	5868.10	64.12	107.13	-43.01	53.87	34.30	13.87	37.92	0.00	178	22	PEAK	3	5922.51	53.90	70.04	-16.14	43.57	34.30	13.96	37.93	0.00	178	22	PEAK	4	5930.70	52.23	68.20	-15.97	41.89	34.30	13.97	37.93	0.00	178	22	PEAK	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																							
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																				
1	5854.65	59.26	111.61	-52.35	49.03	34.30	13.85	37.92	0.00	178	22	PEAK																																																																																	
2	5868.10	64.12	107.13	-43.01	53.87	34.30	13.87	37.92	0.00	178	22	PEAK																																																																																	
3	5922.51	53.90	70.04	-16.14	43.57	34.30	13.96	37.93	0.00	178	22	PEAK																																																																																	
4	5930.70	52.23	68.20	-15.97	41.89	34.30	13.97	37.93	0.00	178	22	PEAK																																																																																	






	61																																																																																																																																										
Mode	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5647.39</td><td>60.73</td><td>68.20</td><td>-7.47</td><td>51.91</td><td>33.19</td><td>13.55</td><td>37.92</td><td>0.00</td><td>100</td><td>198</td><td>PEAK</td></tr><tr><td>2</td><td>5653.82</td><td>64.16</td><td>71.04</td><td>-6.88</td><td>55.29</td><td>33.23</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>198</td><td>PEAK</td></tr><tr><td>3</td><td>5700.62</td><td>65.04</td><td>105.37</td><td>-40.33</td><td>55.73</td><td>33.60</td><td>13.63</td><td>37.92</td><td>0.00</td><td>100</td><td>198</td><td>PEAK</td></tr><tr><td>4</td><td>5720.32</td><td>65.63</td><td>111.52</td><td>-45.89</td><td>56.26</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>198</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5647.39	60.73	68.20	-7.47	51.91	33.19	13.55	37.92	0.00	100	198	PEAK	2	5653.82	64.16	71.04	-6.88	55.29	33.23	13.56	37.92	0.00	100	198	PEAK	3	5700.62	65.04	105.37	-40.33	55.73	33.60	13.63	37.92	0.00	100	198	PEAK	4	5720.32	65.63	111.52	-45.89	56.26	33.64	13.65	37.92	0.00	100	198	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5795.00</td><td>112.19</td><td>-----</td><td>-----</td><td>102.37</td><td>34.00</td><td>13.74</td><td>37.92</td><td>0.00</td><td>100</td><td>198</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	112.19	-----	-----	102.37	34.00	13.74	37.92	0.00	100	198	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5647.39	60.73	68.20	-7.47	51.91	33.19	13.55	37.92	0.00	100	198	PEAK																																																																																																																															
2	5653.82	64.16	71.04	-6.88	55.29	33.23	13.56	37.92	0.00	100	198	PEAK																																																																																																																															
3	5700.62	65.04	105.37	-40.33	55.73	33.60	13.63	37.92	0.00	100	198	PEAK																																																																																																																															
4	5720.32	65.63	111.52	-45.89	56.26	33.64	13.65	37.92	0.00	100	198	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	112.19	-----	-----	102.37	34.00	13.74	37.92	0.00	100	198	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5795.00</td><td>105.70</td><td>-----</td><td>-----</td><td>95.82</td><td>34.05</td><td>13.75</td><td>37.92</td><td>0.00</td><td>100</td><td>198</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	105.70	-----	-----	95.82	34.05	13.75	37.92	0.00	100	198	AVERAGE																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	105.70	-----	-----	95.82	34.05	13.75	37.92	0.00	100	198	AVERAGE																																																																																																																															




Mode	61																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																							
ANT	6+7																																																																							
Pol.	Horizontal	Fundamental																																																																						
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5854.83</td><td>72.51</td><td>111.19</td><td>-38.68</td><td>62.28</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00 100 198 PEAK</td></tr><tr><td>2</td><td>5873.74</td><td>70.83</td><td>105.55</td><td>-35.52</td><td>59.77</td><td>34.30</td><td>13.88</td><td>37.92</td><td>0.00 100 198 PEAK</td></tr><tr><td>3</td><td>5923.34</td><td>61.50</td><td>69.42</td><td>-7.92</td><td>51.17</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00 100 198 PEAK</td></tr><tr><td>4</td><td>5930.94</td><td>63.05</td><td>68.20</td><td>-5.15</td><td>52.71</td><td>34.30</td><td>13.97</td><td>37.93</td><td>0.00 100 198 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5854.83	72.51	111.19	-38.68	62.28	34.30	13.85	37.92	0.00 100 198 PEAK	2	5873.74	70.83	105.55	-35.52	59.77	34.30	13.88	37.92	0.00 100 198 PEAK	3	5923.34	61.50	69.42	-7.92	51.17	34.30	13.96	37.93	0.00 100 198 PEAK	4	5930.94	63.05	68.20	-5.15	52.71	34.30	13.97	37.93	0.00 100 198 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1	5854.83	72.51	111.19	-38.68	62.28	34.30	13.85	37.92	0.00 100 198 PEAK																																																															
2	5873.74	70.83	105.55	-35.52	59.77	34.30	13.88	37.92	0.00 100 198 PEAK																																																															
3	5923.34	61.50	69.42	-7.92	51.17	34.30	13.96	37.93	0.00 100 198 PEAK																																																															
4	5930.94	63.05	68.20	-5.15	52.71	34.30	13.97	37.93	0.00 100 198 PEAK																																																															




	61																																																																																																																																										
Mode	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5640.95</td><td>58.60</td><td>68.20</td><td>-9.60</td><td>49.61</td><td>33.16</td><td>13.55</td><td>37.92</td><td>0.00</td><td>107</td><td>300</td><td>PEAK</td></tr><tr><td>2</td><td>5650.31</td><td>58.59</td><td>68.43</td><td>-9.84</td><td>49.75</td><td>33.20</td><td>13.56</td><td>37.92</td><td>0.00</td><td>107</td><td>300</td><td>PEAK</td></tr><tr><td>3</td><td>5701.40</td><td>64.98</td><td>105.59</td><td>-40.61</td><td>55.67</td><td>33.60</td><td>13.63</td><td>37.92</td><td>0.00</td><td>107</td><td>300</td><td>PEAK</td></tr><tr><td>4</td><td>5720.12</td><td>64.77</td><td>111.07</td><td>-46.30</td><td>55.40</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>107</td><td>300</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5640.95	58.60	68.20	-9.60	49.61	33.16	13.55	37.92	0.00	107	300	PEAK	2	5650.31	58.59	68.43	-9.84	49.75	33.20	13.56	37.92	0.00	107	300	PEAK	3	5701.40	64.98	105.59	-40.61	55.67	33.60	13.63	37.92	0.00	107	300	PEAK	4	5720.12	64.77	111.07	-46.30	55.40	33.64	13.65	37.92	0.00	107	300	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>109.96</td><td>-----</td><td>-----</td><td>100.02</td><td>34.10</td><td>13.76</td><td>37.92</td><td>0.00</td><td>107</td><td>300</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	109.96	-----	-----	100.02	34.10	13.76	37.92	0.00	107	300	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5640.95	58.60	68.20	-9.60	49.61	33.16	13.55	37.92	0.00	107	300	PEAK																																																																																																																															
2	5650.31	58.59	68.43	-9.84	49.75	33.20	13.56	37.92	0.00	107	300	PEAK																																																																																																																															
3	5701.40	64.98	105.59	-40.61	55.67	33.60	13.63	37.92	0.00	107	300	PEAK																																																																																																																															
4	5720.12	64.77	111.07	-46.30	55.40	33.64	13.65	37.92	0.00	107	300	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	109.96	-----	-----	100.02	34.10	13.76	37.92	0.00	107	300	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>102.91</td><td>-----</td><td>-----</td><td>92.97</td><td>34.10</td><td>13.76</td><td>37.92</td><td>0.00</td><td>107</td><td>300</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	102.91	-----	-----	92.97	34.10	13.76	37.92	0.00	107	300	AVERAGE																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	102.91	-----	-----	92.97	34.10	13.76	37.92	0.00	107	300	AVERAGE																																																																																																																															







Mode	61																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																				
ANT	6+7																																																																																				
Pol.	Vertical	Fundamental																																																																																			
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.06</td><td>70.51</td><td>112.95</td><td>-42.44</td><td>60.28</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>107</td><td>300</td><td>PEAK</td></tr><tr><td>2</td><td>5872.35</td><td>70.17</td><td>105.94</td><td>-35.77</td><td>59.91</td><td>34.30</td><td>13.88</td><td>37.92</td><td>0.00</td><td>107</td><td>300</td><td>PEAK</td></tr><tr><td>3</td><td>5922.41</td><td>66.07</td><td>70.11</td><td>-4.04</td><td>55.74</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>107</td><td>300</td><td>PEAK</td></tr><tr><td>4</td><td>5944.73</td><td>62.94</td><td>68.20</td><td>-5.26</td><td>52.58</td><td>34.30</td><td>13.99</td><td>37.93</td><td>0.00</td><td>107</td><td>300</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5854.06	70.51	112.95	-42.44	60.28	34.30	13.85	37.92	0.00	107	300	PEAK	2	5872.35	70.17	105.94	-35.77	59.91	34.30	13.88	37.92	0.00	107	300	PEAK	3	5922.41	66.07	70.11	-4.04	55.74	34.30	13.96	37.93	0.00	107	300	PEAK	4	5944.73	62.94	68.20	-5.26	52.58	34.30	13.99	37.93	0.00	107	300	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																											
1	5854.06	70.51	112.95	-42.44	60.28	34.30	13.85	37.92	0.00	107	300	PEAK																																																																									
2	5872.35	70.17	105.94	-35.77	59.91	34.30	13.88	37.92	0.00	107	300	PEAK																																																																									
3	5922.41	66.07	70.11	-4.04	55.74	34.30	13.96	37.93	0.00	107	300	PEAK																																																																									
4	5944.73	62.94	68.20	-5.26	52.58	34.30	13.99	37.93	0.00	107	300	PEAK																																																																									




		61																																																																																	
Mode		Harmonic																																																																																	
		U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																	
ANT		6+7																																																																																	
Pol.		Horizontal												Vertical																																																																					
Peak Avg.																																																																																			
	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 HORIZONTAL																																																																																		
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11590.00</td><td>51.82</td><td>74.00</td><td>-22.18</td><td>35.15</td><td>38.74</td><td>19.55</td><td>42.55</td><td>0.93</td><td>155</td><td>42</td><td>PEAK</td></tr><tr><td>2</td><td>11590.00</td><td>41.77</td><td>54.00</td><td>-12.23</td><td>25.10</td><td>38.74</td><td>19.55</td><td>42.55</td><td>0.93</td><td>155</td><td>42</td><td>Average</td></tr><tr><td>3</td><td>17385.00</td><td>54.78</td><td>68.20</td><td>-13.42</td><td>34.47</td><td>39.94</td><td>24.16</td><td>44.73</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>																	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11590.00	51.82	74.00	-22.18	35.15	38.74	19.55	42.55	0.93	155	42	PEAK	2	11590.00	41.77	54.00	-12.23	25.10	38.74	19.55	42.55	0.93	155	42	Average	3	17385.00	54.78	68.20	-13.42	34.47	39.94	24.16	44.73	0.94	--	--	PEAK
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1	11590.00	51.82	74.00	-22.18	35.15	38.74	19.55	42.55	0.93	155	42	PEAK																																																																							
2	11590.00	41.77	54.00	-12.23	25.10	38.74	19.55	42.55	0.93	155	42	Average																																																																							
3	17385.00	54.78	68.20	-13.42	34.47	39.94	24.16	44.73	0.94	--	--	PEAK																																																																							
<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11590.00</td><td>51.58</td><td>74.00</td><td>-22.42</td><td>34.91</td><td>38.74</td><td>19.55</td><td>42.55</td><td>0.93</td><td>211</td><td>24</td><td>PEAK</td></tr><tr><td>2</td><td>11590.00</td><td>41.78</td><td>54.00</td><td>-12.22</td><td>25.11</td><td>38.74</td><td>19.55</td><td>42.55</td><td>0.93</td><td>211</td><td>24</td><td>Average</td></tr><tr><td>3</td><td>17385.00</td><td>54.61</td><td>68.20</td><td>-13.59</td><td>34.30</td><td>39.94</td><td>24.16</td><td>44.73</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>																	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11590.00	51.58	74.00	-22.42	34.91	38.74	19.55	42.55	0.93	211	24	PEAK	2	11590.00	41.78	54.00	-12.22	25.11	38.74	19.55	42.55	0.93	211	24	Average	3	17385.00	54.61	68.20	-13.59	34.30	39.94	24.16	44.73	0.94	--	--	PEAK	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1	11590.00	51.58	74.00	-22.42	34.91	38.74	19.55	42.55	0.93	211	24	PEAK																																																																							
2	11590.00	41.78	54.00	-12.22	25.11	38.74	19.55	42.55	0.93	211	24	Average																																																																							
3	17385.00	54.61	68.20	-13.59	34.30	39.94	24.16	44.73	0.94	--	--	PEAK																																																																							






Mode	62																																																																																																																																															
	Band Edge - L																																																																																																																																															
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial_242/62RU_5795MHz																																																																																																																																															
ANT	6+7																																																																																																																																															
Pol.	Horizontal						Fundamental																																																																																																																																									
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5645.63</td><td>56.64</td><td>68.20</td><td>-11.56</td><td>47.83</td><td>33.18</td><td>13.55</td><td>37.92</td><td>0.00</td><td>203</td><td>305 PEAK</td></tr><tr><td>2</td><td>5650.90</td><td>58.72</td><td>68.87</td><td>-10.15</td><td>49.87</td><td>33.21</td><td>13.56</td><td>37.92</td><td>0.00</td><td>203</td><td>305 PEAK</td></tr><tr><td>3</td><td>5713.10</td><td>70.50</td><td>108.87</td><td>-38.37</td><td>61.15</td><td>33.63</td><td>13.64</td><td>37.92</td><td>0.00</td><td>203</td><td>305 PEAK</td></tr><tr><td>4</td><td>5721.49</td><td>66.51</td><td>114.19</td><td>-47.68</td><td>57.14</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>203</td><td>305 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5645.63	56.64	68.20	-11.56	47.83	33.18	13.55	37.92	0.00	203	305 PEAK	2	5650.90	58.72	68.87	-10.15	49.87	33.21	13.56	37.92	0.00	203	305 PEAK	3	5713.10	70.50	108.87	-38.37	61.15	33.63	13.64	37.92	0.00	203	305 PEAK	4	5721.49	66.51	114.19	-47.68	57.14	33.64	13.65	37.92	0.00	203	305 PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5795.00</td><td>111.14</td><td>-----</td><td>-----</td><td>101.20</td><td>34.10</td><td>13.76</td><td>37.92</td><td>0.00</td><td>203</td><td>305 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5795.00	111.14	-----	-----	101.20	34.10	13.76	37.92	0.00	203	305 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																						
1	5645.63	56.64	68.20	-11.56	47.83	33.18	13.55	37.92	0.00	203	305 PEAK																																																																																																																																					
2	5650.90	58.72	68.87	-10.15	49.87	33.21	13.56	37.92	0.00	203	305 PEAK																																																																																																																																					
3	5713.10	70.50	108.87	-38.37	61.15	33.63	13.64	37.92	0.00	203	305 PEAK																																																																																																																																					
4	5721.49	66.51	114.19	-47.68	57.14	33.64	13.65	37.92	0.00	203	305 PEAK																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																						
1	5795.00	111.14	-----	-----	101.20	34.10	13.76	37.92	0.00	203	305 PEAK																																																																																																																																					
Avg.	 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5795.00</td><td>104.18</td><td>-----</td><td>-----</td><td>94.24</td><td>34.10</td><td>13.76</td><td>37.92</td><td>0.00</td><td>203</td><td>305 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5795.00	104.18	-----	-----	94.24	34.10	13.76	37.92	0.00	203	305 AVERAGE	 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5795.00</td><td>104.18</td><td>-----</td><td>-----</td><td>94.24</td><td>34.10</td><td>13.76</td><td>37.92</td><td>0.00</td><td>203</td><td>305 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5795.00	104.18	-----	-----	94.24	34.10	13.76	37.92	0.00	203	305 AVERAGE																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																						
1	5795.00	104.18	-----	-----	94.24	34.10	13.76	37.92	0.00	203	305 AVERAGE																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																						
1	5795.00	104.18	-----	-----	94.24	34.10	13.76	37.92	0.00	203	305 AVERAGE																																																																																																																																					




Mode	62																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial_242/62RU_5795MHz																																																																							
ANT	6+7																																																																							
Pol.	Horizontal	Fundamental																																																																						
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5854.83</td><td>67.23</td><td>111.19</td><td>-43.96</td><td>57.00</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00 203 305 PEAK</td></tr><tr><td>2</td><td>5872.66</td><td>74.17</td><td>105.86</td><td>-31.69</td><td>63.91</td><td>34.30</td><td>13.88</td><td>37.92</td><td>0.00 203 305 PEAK</td></tr><tr><td>3</td><td>5922.41</td><td>64.47</td><td>70.11</td><td>-5.64</td><td>54.14</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00 203 305 PEAK</td></tr><tr><td>4</td><td>5931.56</td><td>66.27</td><td>68.20</td><td>-1.93</td><td>55.93</td><td>34.30</td><td>13.97</td><td>37.93</td><td>0.00 203 305 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5854.83	67.23	111.19	-43.96	57.00	34.30	13.85	37.92	0.00 203 305 PEAK	2	5872.66	74.17	105.86	-31.69	63.91	34.30	13.88	37.92	0.00 203 305 PEAK	3	5922.41	64.47	70.11	-5.64	54.14	34.30	13.96	37.93	0.00 203 305 PEAK	4	5931.56	66.27	68.20	-1.93	55.93	34.30	13.97	37.93	0.00 203 305 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1	5854.83	67.23	111.19	-43.96	57.00	34.30	13.85	37.92	0.00 203 305 PEAK																																																															
2	5872.66	74.17	105.86	-31.69	63.91	34.30	13.88	37.92	0.00 203 305 PEAK																																																															
3	5922.41	64.47	70.11	-5.64	54.14	34.30	13.96	37.93	0.00 203 305 PEAK																																																															
4	5931.56	66.27	68.20	-1.93	55.93	34.30	13.97	37.93	0.00 203 305 PEAK																																																															






	62																																																																																																																																								
Mode	Band Edge - L																																																																																																																																								
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial_242/62RU_5795MHz																																																																																																																																								
ANT	6+7																																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																																		
Peak	 Level (dBuV/m) vs Frequency (MHz) for Vertical polarization. The plot shows a noisy blue signal with a red limit line. Peaks are labeled 1, 2, 3, and 4. A red label 'PEAK_BE(B4)_16-24' is at the top right. Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5643.49</td><td>60.92</td><td>68.20</td><td>-7.28</td><td>52.12</td><td>33.17</td><td>13.55</td><td>37.92</td><td>0.00</td><td>173</td><td>360</td><td>PEAK</td></tr><tr><td>2</td><td>5654.68</td><td>62.12</td><td>71.62</td><td>-9.50</td><td>53.24</td><td>33.24</td><td>13.56</td><td>37.92</td><td>0.00</td><td>173</td><td>360</td><td>PEAK</td></tr><tr><td>3</td><td>5710.57</td><td>73.94</td><td>108.16</td><td>-34.22</td><td>64.60</td><td>33.62</td><td>13.64</td><td>37.92</td><td>0.00</td><td>173</td><td>360</td><td>PEAK</td></tr><tr><td>4</td><td>5720.90</td><td>69.68</td><td>112.85</td><td>-43.17</td><td>60.31</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>173</td><td>360</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5643.49	60.92	68.20	-7.28	52.12	33.17	13.55	37.92	0.00	173	360	PEAK	2	5654.68	62.12	71.62	-9.50	53.24	33.24	13.56	37.92	0.00	173	360	PEAK	3	5710.57	73.94	108.16	-34.22	64.60	33.62	13.64	37.92	0.00	173	360	PEAK	4	5720.90	69.68	112.85	-43.17	60.31	33.64	13.65	37.92	0.00	173	360	PEAK	 Level (dBuV/m) vs Frequency (MHz) for Fundamental polarization. The plot shows a noisy blue signal with a red limit line. A sharp peak is labeled 1. A red label 'PEAK(UNI)' is at the top right. Site : 03CH20-HY Condition: PEAK(UNI) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>111.10</td><td>-----</td><td>-----</td><td>101.13</td><td>34.12</td><td>13.77</td><td>37.92</td><td>0.00</td><td>173</td><td>360</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	111.10	-----	-----	101.13	34.12	13.77	37.92	0.00	173	360	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5643.49	60.92	68.20	-7.28	52.12	33.17	13.55	37.92	0.00	173	360	PEAK																																																																																																																													
2	5654.68	62.12	71.62	-9.50	53.24	33.24	13.56	37.92	0.00	173	360	PEAK																																																																																																																													
3	5710.57	73.94	108.16	-34.22	64.60	33.62	13.64	37.92	0.00	173	360	PEAK																																																																																																																													
4	5720.90	69.68	112.85	-43.17	60.31	33.64	13.65	37.92	0.00	173	360	PEAK																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5795.00	111.10	-----	-----	101.13	34.12	13.77	37.92	0.00	173	360	PEAK																																																																																																																													
Avg.	Blank						 Level (dBuV/m) vs Frequency (MHz) for Fundamental polarization. The plot shows a noisy blue signal with a red limit line. A sharp peak is labeled 1. A red label 'AVG_54' is at the top right. Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>103.39</td><td>-----</td><td>-----</td><td>93.42</td><td>34.12</td><td>13.77</td><td>37.92</td><td>0.00</td><td>173</td><td>360</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	103.39	-----	-----	93.42	34.12	13.77	37.92	0.00	173	360	AVERAGE																																																																																		
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5795.00	103.39	-----	-----	93.42	34.12	13.77	37.92	0.00	173	360	AVERAGE																																																																																																																													




Mode	62																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial_242/62RU_5795MHz																																																																																				
ANT	6+7																																																																																				
Pol.	Vertical	Fundamental																																																																																			
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.68</td><td>70.26</td><td>111.54</td><td>-41.28</td><td>60.03</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>173</td><td>360</td><td>PEAK</td></tr><tr><td>2</td><td>5871.73</td><td>72.53</td><td>106.12</td><td>-33.59</td><td>62.28</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>173</td><td>360</td><td>PEAK</td></tr><tr><td>3</td><td>5924.89</td><td>61.93</td><td>68.28</td><td>-6.35</td><td>51.60</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>173</td><td>360</td><td>PEAK</td></tr><tr><td>4</td><td>5935.12</td><td>63.67</td><td>68.20</td><td>-4.53</td><td>53.32</td><td>34.30</td><td>13.98</td><td>37.93</td><td>0.00</td><td>173</td><td>360</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.68	70.26	111.54	-41.28	60.03	34.30	13.85	37.92	0.00	173	360	PEAK	2	5871.73	72.53	106.12	-33.59	62.28	34.30	13.87	37.92	0.00	173	360	PEAK	3	5924.89	61.93	68.28	-6.35	51.60	34.30	13.96	37.93	0.00	173	360	PEAK	4	5935.12	63.67	68.20	-4.53	53.32	34.30	13.98	37.93	0.00	173	360	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.68	70.26	111.54	-41.28	60.03	34.30	13.85	37.92	0.00	173	360	PEAK																																																																									
2	5871.73	72.53	106.12	-33.59	62.28	34.30	13.87	37.92	0.00	173	360	PEAK																																																																									
3	5924.89	61.93	68.28	-6.35	51.60	34.30	13.96	37.93	0.00	173	360	PEAK																																																																									
4	5935.12	63.67	68.20	-4.53	53.32	34.30	13.98	37.93	0.00	173	360	PEAK																																																																									






Mode	63																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5642.88</td><td>61.67</td><td>68.20</td><td>-6.53</td><td>52.87</td><td>33.17</td><td>13.55</td><td>37.92</td><td>0.00</td><td>100</td><td>195</td><td>PEAK</td></tr><tr><td>2</td><td>5650.93</td><td>62.47</td><td>68.89</td><td>-6.42</td><td>53.62</td><td>33.21</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>195</td><td>PEAK</td></tr><tr><td>3</td><td>5702.38</td><td>73.33</td><td>105.87</td><td>-32.54</td><td>64.02</td><td>33.60</td><td>13.63</td><td>37.92</td><td>0.00</td><td>100</td><td>195</td><td>PEAK</td></tr><tr><td>4</td><td>5720.23</td><td>71.84</td><td>111.31</td><td>-39.47</td><td>62.47</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>195</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5642.88	61.67	68.20	-6.53	52.87	33.17	13.55	37.92	0.00	100	195	PEAK	2	5650.93	62.47	68.89	-6.42	53.62	33.21	13.56	37.92	0.00	100	195	PEAK	3	5702.38	73.33	105.87	-32.54	64.02	33.60	13.63	37.92	0.00	100	195	PEAK	4	5720.23	71.84	111.31	-39.47	62.47	33.64	13.65	37.92	0.00	100	195	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>100.17</td><td>-----</td><td>-----</td><td>98.67</td><td>33.72</td><td>13.70</td><td>37.92</td><td>0.00</td><td>100</td><td>195</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	100.17	-----	-----	98.67	33.72	13.70	37.92	0.00	100	195	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5642.88	61.67	68.20	-6.53	52.87	33.17	13.55	37.92	0.00	100	195	PEAK																																																																																																																															
2	5650.93	62.47	68.89	-6.42	53.62	33.21	13.56	37.92	0.00	100	195	PEAK																																																																																																																															
3	5702.38	73.33	105.87	-32.54	64.02	33.60	13.63	37.92	0.00	100	195	PEAK																																																																																																																															
4	5720.23	71.84	111.31	-39.47	62.47	33.64	13.65	37.92	0.00	100	195	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	100.17	-----	-----	98.67	33.72	13.70	37.92	0.00	100	195	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>100.57</td><td>-----</td><td>-----</td><td>98.79</td><td>33.96</td><td>13.74</td><td>37.92</td><td>0.00</td><td>100</td><td>195</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	100.57	-----	-----	98.79	33.96	13.74	37.92	0.00	100	195	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	100.57	-----	-----	98.79	33.96	13.74	37.92	0.00	100	195	AVERAGE																																																																																																																															




Mode	63																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																				
ANT	6+7																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.45</td><td>68.17</td><td>112.05</td><td>-43.88</td><td>57.94</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100</td><td>195</td><td>PEAK</td></tr><tr><td>2</td><td>5867.75</td><td>70.38</td><td>107.23</td><td>-36.85</td><td>60.13</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>100</td><td>195</td><td>PEAK</td></tr><tr><td>3</td><td>5920.95</td><td>63.29</td><td>71.19</td><td>-7.90</td><td>52.97</td><td>34.30</td><td>13.95</td><td>37.93</td><td>0.00</td><td>100</td><td>195</td><td>PEAK</td></tr><tr><td>4</td><td>5930.58</td><td>61.44</td><td>68.20</td><td>-6.76</td><td>51.10</td><td>34.30</td><td>13.97</td><td>37.93</td><td>0.00</td><td>100</td><td>195</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.45	68.17	112.05	-43.88	57.94	34.30	13.85	37.92	0.00	100	195	PEAK	2	5867.75	70.38	107.23	-36.85	60.13	34.30	13.87	37.92	0.00	100	195	PEAK	3	5920.95	63.29	71.19	-7.90	52.97	34.30	13.95	37.93	0.00	100	195	PEAK	4	5930.58	61.44	68.20	-6.76	51.10	34.30	13.97	37.93	0.00	100	195	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.45	68.17	112.05	-43.88	57.94	34.30	13.85	37.92	0.00	100	195	PEAK																																																																									
2	5867.75	70.38	107.23	-36.85	60.13	34.30	13.87	37.92	0.00	100	195	PEAK																																																																									
3	5920.95	63.29	71.19	-7.90	52.97	34.30	13.95	37.93	0.00	100	195	PEAK																																																																									
4	5930.58	61.44	68.20	-6.76	51.10	34.30	13.97	37.93	0.00	100	195	PEAK																																																																									




Mode	63																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5642.88</td><td>62.78</td><td>68.20</td><td>-5.42</td><td>53.98</td><td>33.17</td><td>13.55</td><td>37.92</td><td>0.00</td><td>102</td><td>301</td><td>PEAK</td></tr><tr><td>2</td><td>5651.63</td><td>62.91</td><td>69.41</td><td>-6.50</td><td>54.06</td><td>33.21</td><td>13.56</td><td>37.92</td><td>0.00</td><td>102</td><td>301</td><td>PEAK</td></tr><tr><td>3</td><td>5702.90</td><td>73.19</td><td>106.01</td><td>-32.82</td><td>63.87</td><td>33.61</td><td>13.63</td><td>37.92</td><td>0.00</td><td>102</td><td>301</td><td>PEAK</td></tr><tr><td>4</td><td>5721.10</td><td>73.95</td><td>113.31</td><td>-39.36</td><td>64.58</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>102</td><td>301</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5642.88	62.78	68.20	-5.42	53.98	33.17	13.55	37.92	0.00	102	301	PEAK	2	5651.63	62.91	69.41	-6.50	54.06	33.21	13.56	37.92	0.00	102	301	PEAK	3	5702.90	73.19	106.01	-32.82	63.87	33.61	13.63	37.92	0.00	102	301	PEAK	4	5721.10	73.95	113.31	-39.36	64.58	33.64	13.65	37.92	0.00	102	301	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>105.44</td><td>-----</td><td>-----</td><td>95.78</td><td>33.86</td><td>13.72</td><td>37.92</td><td>0.00</td><td>102</td><td>301</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	105.44	-----	-----	95.78	33.86	13.72	37.92	0.00	102	301	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5642.88	62.78	68.20	-5.42	53.98	33.17	13.55	37.92	0.00	102	301	PEAK																																																																																																																															
2	5651.63	62.91	69.41	-6.50	54.06	33.21	13.56	37.92	0.00	102	301	PEAK																																																																																																																															
3	5702.90	73.19	106.01	-32.82	63.87	33.61	13.63	37.92	0.00	102	301	PEAK																																																																																																																															
4	5721.10	73.95	113.31	-39.36	64.58	33.64	13.65	37.92	0.00	102	301	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	105.44	-----	-----	95.78	33.86	13.72	37.92	0.00	102	301	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>98.02</td><td>-----</td><td>-----</td><td>88.36</td><td>33.86</td><td>13.72</td><td>37.92</td><td>0.00</td><td>102</td><td>301</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	98.02	-----	-----	88.36	33.86	13.72	37.92	0.00	102	301	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	98.02	-----	-----	88.36	33.86	13.72	37.92	0.00	102	301	AVERAGE																																																																																																																															






Mode	63																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																				
ANT	6+7																																																																																				
Pol.	Vertical	Fundamental																																																																																			
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5853.05</td><td>70.14</td><td>115.25</td><td>-45.11</td><td>59.92</td><td>34.30</td><td>13.84</td><td>37.92</td><td>0.00</td><td>102</td><td>301</td><td>PEAK</td></tr><tr><td>2</td><td>5867.40</td><td>70.26</td><td>107.33</td><td>-37.07</td><td>60.01</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>102</td><td>301</td><td>PEAK</td></tr><tr><td>3</td><td>5922.00</td><td>63.70</td><td>70.41</td><td>-6.71</td><td>53.37</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>102</td><td>301</td><td>PEAK</td></tr><tr><td>4</td><td>5949.83</td><td>64.69</td><td>68.20</td><td>-3.51</td><td>54.32</td><td>34.30</td><td>14.00</td><td>37.93</td><td>0.00</td><td>102</td><td>301</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5853.05	70.14	115.25	-45.11	59.92	34.30	13.84	37.92	0.00	102	301	PEAK	2	5867.40	70.26	107.33	-37.07	60.01	34.30	13.87	37.92	0.00	102	301	PEAK	3	5922.00	63.70	70.41	-6.71	53.37	34.30	13.96	37.93	0.00	102	301	PEAK	4	5949.83	64.69	68.20	-3.51	54.32	34.30	14.00	37.93	0.00	102	301	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																													
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																											
1	5853.05	70.14	115.25	-45.11	59.92	34.30	13.84	37.92	0.00	102	301	PEAK																																																																									
2	5867.40	70.26	107.33	-37.07	60.01	34.30	13.87	37.92	0.00	102	301	PEAK																																																																									
3	5922.00	63.70	70.41	-6.71	53.37	34.30	13.96	37.93	0.00	102	301	PEAK																																																																									
4	5949.83	64.69	68.20	-3.51	54.32	34.30	14.00	37.93	0.00	102	301	PEAK																																																																									




		63																																																																																	
Mode		Harmonic																																																																																	
		U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																	
ANT		6+7																																																																																	
Pol.		Horizontal												Vertical																																																																					
Peak Avg.																																																																																			
	Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91280_02360_241101 HORIZONTAL																																																																																		
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11550.00</td><td>52.28</td><td>74.00</td><td>-21.72</td><td>35.47</td><td>38.90</td><td>19.51</td><td>42.52</td><td>0.92</td><td>115</td><td>245</td><td>PEAK</td></tr><tr><td>2</td><td>11550.00</td><td>41.93</td><td>54.00</td><td>-12.07</td><td>25.12</td><td>38.90</td><td>19.51</td><td>42.52</td><td>0.92</td><td>115</td><td>245</td><td>Average</td></tr><tr><td>3</td><td>17325.00</td><td>54.60</td><td>68.20</td><td>-13.60</td><td>34.52</td><td>39.70</td><td>24.12</td><td>44.68</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>																	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11550.00	52.28	74.00	-21.72	35.47	38.90	19.51	42.52	0.92	115	245	PEAK	2	11550.00	41.93	54.00	-12.07	25.12	38.90	19.51	42.52	0.92	115	245	Average	3	17325.00	54.60	68.20	-13.60	34.52	39.70	24.12	44.68	0.94	--	--	PEAK
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1	11550.00	52.28	74.00	-21.72	35.47	38.90	19.51	42.52	0.92	115	245	PEAK																																																																							
2	11550.00	41.93	54.00	-12.07	25.12	38.90	19.51	42.52	0.92	115	245	Average																																																																							
3	17325.00	54.60	68.20	-13.60	34.52	39.70	24.12	44.68	0.94	--	--	PEAK																																																																							
<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11550.00</td><td>51.66</td><td>74.00</td><td>-22.34</td><td>34.85</td><td>38.90</td><td>19.51</td><td>42.52</td><td>0.92</td><td>225</td><td>24</td><td>PEAK</td></tr><tr><td>2</td><td>11550.00</td><td>41.96</td><td>54.00</td><td>-12.04</td><td>25.15</td><td>38.90</td><td>19.51</td><td>42.52</td><td>0.92</td><td>225</td><td>24</td><td>Average</td></tr><tr><td>3</td><td>17325.00</td><td>54.52</td><td>68.20</td><td>-13.68</td><td>34.44</td><td>39.70</td><td>24.12</td><td>44.68</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>																	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11550.00	51.66	74.00	-22.34	34.85	38.90	19.51	42.52	0.92	225	24	PEAK	2	11550.00	41.96	54.00	-12.04	25.15	38.90	19.51	42.52	0.92	225	24	Average	3	17325.00	54.52	68.20	-13.68	34.44	39.70	24.12	44.68	0.94	--	--	PEAK	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1	11550.00	51.66	74.00	-22.34	34.85	38.90	19.51	42.52	0.92	225	24	PEAK																																																																							
2	11550.00	41.96	54.00	-12.04	25.15	38.90	19.51	42.52	0.92	225	24	Average																																																																							
3	17325.00	54.52	68.20	-13.68	34.44	39.70	24.12	44.68	0.94	--	--	PEAK																																																																							






Mode	64																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial_484/65RU_5775MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5648.25</td><td>64.06</td><td>68.20</td><td>-4.14</td><td>55.28</td><td>33.16</td><td>13.54</td><td>37.92</td><td>0.00</td><td>100</td><td>196</td><td>PEAK</td></tr><tr><td>2</td><td>5651.63</td><td>63.97</td><td>69.41</td><td>-5.44</td><td>55.12</td><td>33.21</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>196</td><td>PEAK</td></tr><tr><td>3</td><td>5707.28</td><td>71.17</td><td>107.24</td><td>-36.07</td><td>61.85</td><td>33.61</td><td>13.63</td><td>37.92</td><td>0.00</td><td>100</td><td>196</td><td>PEAK</td></tr><tr><td>4</td><td>5720.05</td><td>70.10</td><td>110.91</td><td>-40.81</td><td>60.73</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>196</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5648.25	64.06	68.20	-4.14	55.28	33.16	13.54	37.92	0.00	100	196	PEAK	2	5651.63	63.97	69.41	-5.44	55.12	33.21	13.56	37.92	0.00	100	196	PEAK	3	5707.28	71.17	107.24	-36.07	61.85	33.61	13.63	37.92	0.00	100	196	PEAK	4	5720.05	70.10	110.91	-40.81	60.73	33.64	13.65	37.92	0.00	100	196	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5775.00</td><td>107.66</td><td>-----</td><td>-----</td><td>98.00</td><td>33.86</td><td>13.72</td><td>37.92</td><td>0.00</td><td>100</td><td>196</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	107.66	-----	-----	98.00	33.86	13.72	37.92	0.00	100	196	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5648.25	64.06	68.20	-4.14	55.28	33.16	13.54	37.92	0.00	100	196	PEAK																																																																																																																															
2	5651.63	63.97	69.41	-5.44	55.12	33.21	13.56	37.92	0.00	100	196	PEAK																																																																																																																															
3	5707.28	71.17	107.24	-36.07	61.85	33.61	13.63	37.92	0.00	100	196	PEAK																																																																																																																															
4	5720.05	70.10	110.91	-40.81	60.73	33.64	13.65	37.92	0.00	100	196	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	107.66	-----	-----	98.00	33.86	13.72	37.92	0.00	100	196	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5775.00</td><td>100.17</td><td>-----</td><td>-----</td><td>90.67</td><td>33.72</td><td>13.70</td><td>37.92</td><td>0.00</td><td>100</td><td>196</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	100.17	-----	-----	90.67	33.72	13.70	37.92	0.00	100	196	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	100.17	-----	-----	90.67	33.72	13.70	37.92	0.00	100	196	AVERAGE																																																																																																																															




Mode	64																																																																																			
	Band Edge - R																																																																																			
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial_484/65RU_5775MHz																																																																																			
ANT	6+7																																																																																			
Pol.	Horizontal	Fundamental																																																																																		
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5853.05</td><td>73.65</td><td>115.25</td><td>-41.60</td><td>63.43</td><td>34.30</td><td>13.84</td><td>37.92</td><td>0.00</td><td>100</td><td>196</td><td>PEAK</td></tr><tr><td>2</td><td>5872.13</td><td>74.41</td><td>106.00</td><td>-31.59</td><td>64.15</td><td>34.30</td><td>13.88</td><td>37.92</td><td>0.00</td><td>100</td><td>196</td><td>PEAK</td></tr><tr><td>3</td><td>5922.70</td><td>67.41</td><td>69.89</td><td>-2.48</td><td>57.08</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100</td><td>196</td><td>PEAK</td></tr><tr><td>4</td><td>5931.80</td><td>67.03</td><td>68.20</td><td>-1.17</td><td>56.69</td><td>34.30</td><td>13.97</td><td>37.93</td><td>0.00</td><td>100</td><td>196</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	5853.05	73.65	115.25	-41.60	63.43	34.30	13.84	37.92	0.00	100	196	PEAK	2	5872.13	74.41	106.00	-31.59	64.15	34.30	13.88	37.92	0.00	100	196	PEAK	3	5922.70	67.41	69.89	-2.48	57.08	34.30	13.96	37.93	0.00	100	196	PEAK	4	5931.80	67.03	68.20	-1.17	56.69	34.30	13.97	37.93	0.00	100	196	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																												
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																											
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																											
1	5853.05	73.65	115.25	-41.60	63.43	34.30	13.84	37.92	0.00	100	196	PEAK																																																																								
2	5872.13	74.41	106.00	-31.59	64.15	34.30	13.88	37.92	0.00	100	196	PEAK																																																																								
3	5922.70	67.41	69.89	-2.48	57.08	34.30	13.96	37.93	0.00	100	196	PEAK																																																																								
4	5931.80	67.03	68.20	-1.17	56.69	34.30	13.97	37.93	0.00	100	196	PEAK																																																																								






Mode	64																																																																																																															
	Band Edge - L																																																																																																															
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial_484/65RU_5775MHz																																																																																																															
ANT	6+7																																																																																																															
Pol.	Vertical	Fundamental																																																																																																														
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5629.75</td><td>60.75</td><td>68.20</td><td>-7.45</td><td>52.02</td><td>33.12</td><td>13.53</td><td>37.92</td><td>0.00</td><td>100 301 PEAK</td></tr><tr><td>2 5653.73</td><td>63.07</td><td>70.97</td><td>-7.90</td><td>54.20</td><td>33.23</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100 301 PEAK</td></tr><tr><td>3 5702.73</td><td>71.45</td><td>105.96</td><td>-34.51</td><td>62.13</td><td>33.61</td><td>13.63</td><td>37.92</td><td>0.00</td><td>100 301 PEAK</td></tr><tr><td>4 5720.75</td><td>73.47</td><td>112.51</td><td>-39.04</td><td>64.10</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100 301 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5629.75	60.75	68.20	-7.45	52.02	33.12	13.53	37.92	0.00	100 301 PEAK	2 5653.73	63.07	70.97	-7.90	54.20	33.23	13.56	37.92	0.00	100 301 PEAK	3 5702.73	71.45	105.96	-34.51	62.13	33.61	13.63	37.92	0.00	100 301 PEAK	4 5720.75	73.47	112.51	-39.04	64.10	33.64	13.65	37.92	0.00	100 301 PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5775.00</td><td>105.50</td><td>-----</td><td>-----</td><td>96.00</td><td>33.72</td><td>13.70</td><td>37.92</td><td>0.00</td><td>100 301 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5775.00	105.50	-----	-----	96.00	33.72	13.70	37.92	0.00	100 301 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																							
1 5629.75	60.75	68.20	-7.45	52.02	33.12	13.53	37.92	0.00	100 301 PEAK																																																																																																							
2 5653.73	63.07	70.97	-7.90	54.20	33.23	13.56	37.92	0.00	100 301 PEAK																																																																																																							
3 5702.73	71.45	105.96	-34.51	62.13	33.61	13.63	37.92	0.00	100 301 PEAK																																																																																																							
4 5720.75	73.47	112.51	-39.04	64.10	33.64	13.65	37.92	0.00	100 301 PEAK																																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																							
1 5775.00	105.50	-----	-----	96.00	33.72	13.70	37.92	0.00	100 301 PEAK																																																																																																							
Avg.	Blank	 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5775.00</td><td>98.03</td><td>-----</td><td>-----</td><td>88.59</td><td>33.68</td><td>13.68</td><td>37.92</td><td>0.00</td><td>100 301 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5775.00	98.03	-----	-----	88.59	33.68	13.68	37.92	0.00	100 301 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																							
1 5775.00	98.03	-----	-----	88.59	33.68	13.68	37.92	0.00	100 301 AVERAGE																																																																																																							




Mode	64																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial_484/65RU_5775MHz																																																																																				
ANT	6+7																																																																																				
Pol.	Vertical	Fundamental																																																																																			
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5853.05</td><td>73.10</td><td>115.25</td><td>-42.15</td><td>62.88</td><td>34.30</td><td>13.84</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>2</td><td>5867.93</td><td>73.84</td><td>107.18</td><td>-33.34</td><td>63.59</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>3</td><td>5923.93</td><td>64.63</td><td>68.99</td><td>-4.36</td><td>54.30</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>4</td><td>5927.78</td><td>66.46</td><td>68.20</td><td>-1.74</td><td>56.13</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5853.05	73.10	115.25	-42.15	62.88	34.30	13.84	37.92	0.00	100	301	PEAK	2	5867.93	73.84	107.18	-33.34	63.59	34.30	13.87	37.92	0.00	100	301	PEAK	3	5923.93	64.63	68.99	-4.36	54.30	34.30	13.96	37.93	0.00	100	301	PEAK	4	5927.78	66.46	68.20	-1.74	56.13	34.30	13.96	37.93	0.00	100	301	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5853.05	73.10	115.25	-42.15	62.88	34.30	13.84	37.92	0.00	100	301	PEAK																																																																									
2	5867.93	73.84	107.18	-33.34	63.59	34.30	13.87	37.92	0.00	100	301	PEAK																																																																									
3	5923.93	64.63	68.99	-4.36	54.30	34.30	13.96	37.93	0.00	100	301	PEAK																																																																									
4	5927.78	66.46	68.20	-1.74	56.13	34.30	13.96	37.93	0.00	100	301	PEAK																																																																									






	65																																																																																																																																																		
Mode	Band Edge - L																																																																																																																																																		
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial_484/66RU_5775MHz																																																																																																																																																		
ANT	6+7																																																																																																																																																		
Pol.	Horizontal							Fundamental																																																																																																																																											
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Limit</th><th>Level</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5639.03</td><td>62.83</td><td>68.20</td><td>-5.37</td><td></td><td>54.05</td><td>33.16</td><td>13.54</td><td>37.92</td><td>0.00</td><td>100</td><td>197</td><td>PEAK</td></tr><tr><td>2</td><td>5653.55</td><td>63.08</td><td>70.84</td><td>-7.76</td><td></td><td>54.21</td><td>33.23</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>197</td><td>PEAK</td></tr><tr><td>3</td><td>5709.38</td><td>67.99</td><td>107.83</td><td>-39.84</td><td></td><td>58.65</td><td>33.62</td><td>13.64</td><td>37.92</td><td>0.00</td><td>100</td><td>197</td><td>PEAK</td></tr><tr><td>4</td><td>5720.05</td><td>69.18</td><td>110.91</td><td>-41.73</td><td></td><td>59.81</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>197</td><td>PEAK</td></tr></tbody></table>															Freq	Limit	Level	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5639.03	62.83	68.20	-5.37		54.05	33.16	13.54	37.92	0.00	100	197	PEAK	2	5653.55	63.08	70.84	-7.76		54.21	33.23	13.56	37.92	0.00	100	197	PEAK	3	5709.38	67.99	107.83	-39.84		58.65	33.62	13.64	37.92	0.00	100	197	PEAK	4	5720.05	69.18	110.91	-41.73		59.81	33.64	13.65	37.92	0.00	100	197	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII) 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Limit</th><th>Level</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5775.00</td><td>100.00</td><td>-----</td><td>-----</td><td></td><td>90.18</td><td>34.00</td><td>13.74</td><td>37.92</td><td>0.00</td><td>100</td><td>197</td><td>PEAK</td></tr></tbody></table>								Freq	Limit	Level	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5775.00	100.00	-----	-----		90.18	34.00	13.74	37.92	0.00	100	197	PEAK
		Freq	Limit	Level	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																						
1	5639.03	62.83	68.20	-5.37		54.05	33.16	13.54	37.92	0.00	100	197	PEAK																																																																																																																																						
2	5653.55	63.08	70.84	-7.76		54.21	33.23	13.56	37.92	0.00	100	197	PEAK																																																																																																																																						
3	5709.38	67.99	107.83	-39.84		58.65	33.62	13.64	37.92	0.00	100	197	PEAK																																																																																																																																						
4	5720.05	69.18	110.91	-41.73		59.81	33.64	13.65	37.92	0.00	100	197	PEAK																																																																																																																																						
	Freq	Limit	Level	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																						
1	5775.00	100.00	-----	-----		90.18	34.00	13.74	37.92	0.00	100	197	PEAK																																																																																																																																						
Avg.	Blank														 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Limit</th><th>Level</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5775.00</td><td>100.37</td><td>-----</td><td>-----</td><td></td><td>90.36</td><td>34.15</td><td>13.78</td><td>37.92</td><td>0.00</td><td>100</td><td>197</td><td>AVERAGE</td></tr></tbody></table>								Freq	Limit	Level	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5775.00	100.37	-----	-----		90.36	34.15	13.78	37.92	0.00	100	197	AVERAGE																																																																																				
		Freq	Limit	Level	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																						
1	5775.00	100.37	-----	-----		90.36	34.15	13.78	37.92	0.00	100	197	AVERAGE																																																																																																																																						




Mode	65																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial_484/66RU_5775MHz																																																																							
ANT	6+7																																																																							
Pol.	Horizontal	Fundamental																																																																						
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.28</td><td>67.38</td><td>112.45</td><td>-45.07</td><td>57.15</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100 197 PEAK</td></tr><tr><td>2 5867.93</td><td>73.62</td><td>107.18</td><td>-33.56</td><td>63.37</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>100 197 PEAK</td></tr><tr><td>3 5917.45</td><td>62.04</td><td>73.77</td><td>-11.73</td><td>51.72</td><td>34.30</td><td>13.95</td><td>37.93</td><td>0.00</td><td>100 197 PEAK</td></tr><tr><td>4 5926.55</td><td>63.52</td><td>68.20</td><td>-4.68</td><td>53.19</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100 197 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1 5854.28	67.38	112.45	-45.07	57.15	34.30	13.85	37.92	0.00	100 197 PEAK	2 5867.93	73.62	107.18	-33.56	63.37	34.30	13.87	37.92	0.00	100 197 PEAK	3 5917.45	62.04	73.77	-11.73	51.72	34.30	13.95	37.93	0.00	100 197 PEAK	4 5926.55	63.52	68.20	-4.68	53.19	34.30	13.96	37.93	0.00	100 197 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																		
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																															
1 5854.28	67.38	112.45	-45.07	57.15	34.30	13.85	37.92	0.00	100 197 PEAK																																																															
2 5867.93	73.62	107.18	-33.56	63.37	34.30	13.87	37.92	0.00	100 197 PEAK																																																															
3 5917.45	62.04	73.77	-11.73	51.72	34.30	13.95	37.93	0.00	100 197 PEAK																																																															
4 5926.55	63.52	68.20	-4.68	53.19	34.30	13.96	37.93	0.00	100 197 PEAK																																																															





	65																																																																																																																																										
Mode	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial_484/66RU_5775MHz																																																																																																																																										
ANT	6+7																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5645.05</td><td>59.86</td><td>68.20</td><td>-8.34</td><td>51.05</td><td>33.18</td><td>13.55</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>2</td><td>5650.93</td><td>59.53</td><td>68.89</td><td>-9.36</td><td>50.68</td><td>33.21</td><td>13.56</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>3</td><td>5702.90</td><td>67.57</td><td>106.01</td><td>-38.44</td><td>58.25</td><td>33.61</td><td>13.63</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr><tr><td>4</td><td>5720.05</td><td>70.34</td><td>110.91</td><td>-40.57</td><td>60.97</td><td>33.64</td><td>13.65</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5645.05	59.86	68.20	-8.34	51.05	33.18	13.55	37.92	0.00	100	301	PEAK	2	5650.93	59.53	68.89	-9.36	50.68	33.21	13.56	37.92	0.00	100	301	PEAK	3	5702.90	67.57	106.01	-38.44	58.25	33.61	13.63	37.92	0.00	100	301	PEAK	4	5720.05	70.34	110.91	-40.57	60.97	33.64	13.65	37.92	0.00	100	301	PEAK	 Site : 03CH20-HY Condition: PEAK(UNII)_3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>105.35</td><td>-----</td><td>-----</td><td>95.34</td><td>34.15</td><td>13.78</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	105.35	-----	-----	95.34	34.15	13.78	37.92	0.00	100	301	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5645.05	59.86	68.20	-8.34	51.05	33.18	13.55	37.92	0.00	100	301	PEAK																																																																																																																															
2	5650.93	59.53	68.89	-9.36	50.68	33.21	13.56	37.92	0.00	100	301	PEAK																																																																																																																															
3	5702.90	67.57	106.01	-38.44	58.25	33.61	13.63	37.92	0.00	100	301	PEAK																																																																																																																															
4	5720.05	70.34	110.91	-40.57	60.97	33.64	13.65	37.92	0.00	100	301	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	105.35	-----	-----	95.34	34.15	13.78	37.92	0.00	100	301	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH20-HY Condition: AVG_54 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>98.01</td><td>-----</td><td>-----</td><td>88.00</td><td>34.15</td><td>13.78</td><td>37.92</td><td>0.00</td><td>100</td><td>301</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	98.01	-----	-----	88.00	34.15	13.78	37.92	0.00	100	301	AVERAGE																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	98.01	-----	-----	88.00	34.15	13.78	37.92	0.00	100	301	AVERAGE																																																																																																																															



Mode	65																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial_484/66RU_5775MHz																																																																							
ANT	6+7																																																																							
Pol.	Vertical	Fundamental																																																																						
Peak	 Site : 03CH20-HY Condition: PEAK_BE(B4)_16-24 3m HF_91200_02360_241101 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.63</td><td>62.78</td><td>111.65</td><td>-48.87</td><td>52.55</td><td>34.30</td><td>13.85</td><td>37.92</td><td>0.00</td><td>100 301 PEAK</td></tr><tr><td>2 5867.75</td><td>74.68</td><td>107.23</td><td>-32.55</td><td>64.43</td><td>34.30</td><td>13.87</td><td>37.92</td><td>0.00</td><td>100 301 PEAK</td></tr><tr><td>3 5922.70</td><td>65.52</td><td>69.89</td><td>-4.37</td><td>55.19</td><td>34.30</td><td>13.96</td><td>37.93</td><td>0.00</td><td>100 301 PEAK</td></tr><tr><td>4 5929.35</td><td>63.92</td><td>68.20</td><td>-4.28</td><td>53.58</td><td>34.30</td><td>13.97</td><td>37.93</td><td>0.00</td><td>100 301 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1 5854.63	62.78	111.65	-48.87	52.55	34.30	13.85	37.92	0.00	100 301 PEAK	2 5867.75	74.68	107.23	-32.55	64.43	34.30	13.87	37.92	0.00	100 301 PEAK	3 5922.70	65.52	69.89	-4.37	55.19	34.30	13.96	37.93	0.00	100 301 PEAK	4 5929.35	63.92	68.20	-4.28	53.58	34.30	13.97	37.93	0.00	100 301 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																		
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																															
1 5854.63	62.78	111.65	-48.87	52.55	34.30	13.85	37.92	0.00	100 301 PEAK																																																															
2 5867.75	74.68	107.23	-32.55	64.43	34.30	13.87	37.92	0.00	100 301 PEAK																																																															
3 5922.70	65.52	69.89	-4.37	55.19	34.30	13.96	37.93	0.00	100 301 PEAK																																																															
4 5929.35	63.92	68.20	-4.28	53.58	34.30	13.97	37.93	0.00	100 301 PEAK																																																															



Mode	69																																																																																																																							
	LF																																																																																																																							
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial_484/65RU_5775MHz																																																																																																																							
ANT	6+7																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																	
QPI Peak																																																																																																																								
	Site : 03CH20-HY Condition: QP 3m CBL6111D800802N1D01N-06_47020 & 06_241005 HORIZONTAL																																																																																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>30.97</td><td>24.08</td><td>40.00</td><td>-15.92</td><td>34.15</td><td>24.25</td><td>1.02</td><td>35.59</td><td>0.25</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>95.96</td><td>31.05</td><td>43.50</td><td>-12.45</td><td>48.92</td><td>15.62</td><td>1.85</td><td>35.51</td><td>0.17</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>262.00</td><td>22.25</td><td>46.00</td><td>-23.75</td><td>34.22</td><td>20.07</td><td>2.97</td><td>35.20</td><td>0.19</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>511.12</td><td>26.38</td><td>46.00</td><td>-19.62</td><td>32.84</td><td>23.88</td><td>4.10</td><td>34.57</td><td>0.13</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>746.83</td><td>31.75</td><td>46.00</td><td>-14.25</td><td>32.01</td><td>28.38</td><td>4.91</td><td>33.69</td><td>0.14</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>953.44</td><td>35.47</td><td>46.00</td><td>-10.53</td><td>31.75</td><td>31.08</td><td>5.51</td><td>32.96</td><td>0.09</td><td>--</td><td>--</td><td>Peak</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	30.97	24.08	40.00	-15.92	34.15	24.25	1.02	35.59	0.25	--	--	Peak	2	95.96	31.05	43.50	-12.45	48.92	15.62	1.85	35.51	0.17	--	--	Peak	3	262.00	22.25	46.00	-23.75	34.22	20.07	2.97	35.20	0.19	--	--	Peak	4	511.12	26.38	46.00	-19.62	32.84	23.88	4.10	34.57	0.13	--	--	Peak	5	746.83	31.75	46.00	-14.25	32.01	28.38	4.91	33.69	0.14	--	--	Peak	6	953.44	35.47	46.00	-10.53	31.75	31.08	5.51	32.96	0.09	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																																														
1	30.97	24.08	40.00	-15.92	34.15	24.25	1.02	35.59	0.25	--	--	Peak																																																																																																												
2	95.96	31.05	43.50	-12.45	48.92	15.62	1.85	35.51	0.17	--	--	Peak																																																																																																												
3	262.00	22.25	46.00	-23.75	34.22	20.07	2.97	35.20	0.19	--	--	Peak																																																																																																												
4	511.12	26.38	46.00	-19.62	32.84	23.88	4.10	34.57	0.13	--	--	Peak																																																																																																												
5	746.83	31.75	46.00	-14.25	32.01	28.38	4.91	33.69	0.14	--	--	Peak																																																																																																												
6	953.44	35.47	46.00	-10.53	31.75	31.08	5.51	32.96	0.09	--	--	Peak																																																																																																												
Site : 03CH20-HY Condition: QP 3m CBL6111D800802N1D01N-06_47020 & 06_241005 VERTICAL																																																																																																																								
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>55.22</td><td>31.96</td><td>40.00</td><td>-8.04</td><td>53.38</td><td>12.52</td><td>1.40</td><td>35.57</td><td>0.23</td><td>119</td><td>253</td><td>QP</td></tr><tr><td>2</td><td>93.05</td><td>31.49</td><td>43.50</td><td>-12.01</td><td>49.86</td><td>15.16</td><td>1.82</td><td>35.52</td><td>0.17</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>253.10</td><td>22.45</td><td>46.00</td><td>-23.55</td><td>35.47</td><td>19.08</td><td>2.92</td><td>35.21</td><td>0.19</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>497.54</td><td>27.64</td><td>46.00</td><td>-18.36</td><td>34.32</td><td>23.76</td><td>4.05</td><td>34.62</td><td>0.13</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>756.53</td><td>33.44</td><td>46.00</td><td>-12.56</td><td>33.62</td><td>28.38</td><td>4.94</td><td>33.64</td><td>0.14</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>837.04</td><td>37.68</td><td>46.00</td><td>-8.32</td><td>36.67</td><td>29.16</td><td>5.15</td><td>33.42</td><td>0.12</td><td>--</td><td>--</td><td>Peak</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	55.22	31.96	40.00	-8.04	53.38	12.52	1.40	35.57	0.23	119	253	QP	2	93.05	31.49	43.50	-12.01	49.86	15.16	1.82	35.52	0.17	--	--	Peak	3	253.10	22.45	46.00	-23.55	35.47	19.08	2.92	35.21	0.19	--	--	Peak	4	497.54	27.64	46.00	-18.36	34.32	23.76	4.05	34.62	0.13	--	--	Peak	5	756.53	33.44	46.00	-12.56	33.62	28.38	4.94	33.64	0.14	--	--	Peak	6	837.04	37.68	46.00	-8.32	36.67	29.16	5.15	33.42	0.12	--	--	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																																														
1	55.22	31.96	40.00	-8.04	53.38	12.52	1.40	35.57	0.23	119	253	QP																																																																																																												
2	93.05	31.49	43.50	-12.01	49.86	15.16	1.82	35.52	0.17	--	--	Peak																																																																																																												
3	253.10	22.45	46.00	-23.55	35.47	19.08	2.92	35.21	0.19	--	--	Peak																																																																																																												
4	497.54	27.64	46.00	-18.36	34.32	23.76	4.05	34.62	0.13	--	--	Peak																																																																																																												
5	756.53	33.44	46.00	-12.56	33.62	28.38	4.94	33.64	0.14	--	--	Peak																																																																																																												
6	837.04	37.68	46.00	-8.32	36.67	29.16	5.15	33.42	0.12	--	--	Peak																																																																																																												