

RF EXPOSURE EVALUATION REPORT


FCC ID : UZ7RE40
Equipment : RFID Module
Brand Name : Zebra
Model Name : RE40
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC. has been evaluated this product in accordance with 47 CFR Part 2.1091 and it complies with applicable limit.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.



Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	4
3. RF EXPOSURE LIMIT INTRODUCTION	5
4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	5
4.1. Standalone Power Density Calculation	5



History of this test report

Report No.	Version	Description	Issued Date
FA051819	Rev. 01	Initial issue of report	Jul. 15, 2020

**1. Description of Equipment Under Test (EUT)**

Product Feature & Specification	
EUT Type	RFID Module
Brand Name	Zebra
Model Name	RE40
FCC ID	UZ7RE40
Wireless Technology and Frequency Range	RFID : 902.75 MHz ~ 927.25 MHz
Mode	RFID:ASK
HW Version	DV
FW Version	CAAFBS00-001-N12D0 (3.0.10.0)
MFD	6-May-20
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Reviewed by: Jason Wang

Report Producer: Wan Liu

2. Maximum RF average output power among production units

Mode	Maximum Average Power (dBm)
RFID	27



3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 25 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

4. Radio Frequency Radiation Exposure Evaluation

4.1. Standalone Power Density Calculation

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 25cm (mW/cm ²)	Limit (mW/cm ²)
RFID	6.00	27.00	33.000	1.995	1995.262	0.254	0.602

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.